

Programming with Big Data in R

Drew Schmidt and George Ostrouchov

August 8, 2013



About This Presentation

Downloads

This presentation and supplemental materials are available at:

<http://r-pbd.org/tutorial>

Sample R scripts and pbs job scripts available on Chester:

`/lustre/scratch/sw/r/3.0.1.new/chester/gnu4.7.3/
EXAMPLES/scripts.tar.gz`

About This Presentation

Speaking Serial R with a Parallel Accent

The content of this presentation is based in part on the **pbdDEMO** vignette *Speaking Serial R with a Parallel Accent*

<http://goo.gl/HZkRt>

It contains more examples, and sometimes added detail.

About This Presentation

Installation Instructions

Installation instructions for setting up a pbdR environment are available:

<http://r-pbd.org/install.html>

This includes instructions for installing R, MPI, and pbdR.

Contents

- 1 Introduction to pbdDMAT and the DMAT Structure
- 2 Examples Using pbdDMAT

Contents

- 1 Introduction to pbdDMAT and the DMAT Structure
 - Introduction to Distributed Matrices
 - DMAT Distributions
 - pbdDMAT

Distributed Matrices

Most problems in data science are matrix algebra problems, so:

Distributed matrices \implies Handle Bigger data

Distributed Matrices

High level OOP allows *native* serial R syntax:

```
1 x <- x[-1, 2:5]
2 x <- log(abs(x) + 1)
3 xtx <- t(x) %*% x
4 ans <- svd(solve(xtx))
```

However...

Distributed Matrices

DMAT:

- Distributed **MAT**rix data structure.
- No single processor should hold all of the data.
- Block-cyclic matrix distributed across a 2-dimensional grid of processors.
- Very robust, but confusing data structure.

Distributed Matrices



(a) Block



(b) Cyclic




(c) Block-Cyclic

Figure: Matrix Distribution Schemes


Distributed Matrices



(a) 2d Block



(b) 2d Cyclic



(c) 2d Block-Cyclic

Figure: Matrix Distribution Schemes Onto a 2-Dimensional Grid

Processor Grid Shapes

$$\begin{bmatrix} 0 \\ 1 \\ 2 \\ 3 \\ 4 \\ 5 \end{bmatrix}^T$$

(a) 1×6

$$\begin{bmatrix} 0 & 1 & 2 \\ 3 & 4 & 5 \end{bmatrix}$$

(b) 2×3

$$\begin{bmatrix} 0 & 1 \\ 2 & 3 \\ 4 & 5 \end{bmatrix}$$

(c) 3×2

$$\begin{bmatrix} 0 \\ 1 \\ 2 \\ 3 \\ 4 \\ 5 \end{bmatrix}$$

(d) 6×1

Table: Processor Grid Shapes with 6 Processors

Distributed Matrices

The data structure is a special R class (in the OOP sense) called `ddmatrix`. It is the “under the rug” storage for a block-cyclic matrix distributed onto a 2-dimensional processor grid.

```

ddmatrix = {
  Data   S4 local submatrix, an R matrix
  dim    S4 dimension of the global matrix, a numeric pair
  ldim   S4 dimension of the local submatrix, a numeric pair
  bldim  S4 ScaLAPACK blocking factor, a numeric pair
  CTXT   S4 BLACS context, an numeric singleton

```

with prototype


```

new("ddmatrix") = {
  Data   = matrix(0.0)
  dim    = c(1,1)
  ldim   = c(1,1)
  bldim  = c(1,1)
  CTXT   = 0.0

```

Distributed Matrices: The Data Structure

Example: an 9×9 matrix is distributed with a “block-cycling” factor of 2×2 on a 2×2 processor grid:



$$= \left\{ \begin{array}{ll} \text{Data} & = \text{matrix}(\dots) \\ \text{dim} & = \text{c}(9, 9) \\ \text{ldim} & = \text{c}(\dots) \\ \text{bldim} & = \text{c}(2, 2) \\ \text{CTXT} & = 0 \end{array} \right.$$

See <http://acts.nersc.gov/scalapack/hands-on/datadist.html>

Understanding Dmat: Global Matrix

$$X = \begin{bmatrix} X_{11} & X_{12} & X_{13} & X_{14} & X_{15} & X_{16} & X_{17} & X_{18} & X_{19} \\ X_{21} & X_{22} & X_{23} & X_{24} & X_{25} & X_{26} & X_{27} & X_{28} & X_{29} \\ X_{31} & X_{32} & X_{33} & X_{34} & X_{35} & X_{36} & X_{37} & X_{38} & X_{39} \\ X_{41} & X_{42} & X_{43} & X_{44} & X_{45} & X_{46} & X_{47} & X_{48} & X_{49} \\ X_{51} & X_{52} & X_{53} & X_{54} & X_{55} & X_{56} & X_{57} & X_{58} & X_{59} \\ X_{61} & X_{62} & X_{63} & X_{64} & X_{65} & X_{66} & X_{67} & X_{68} & X_{69} \\ X_{71} & X_{72} & X_{73} & X_{74} & X_{75} & X_{76} & X_{77} & X_{78} & X_{79} \\ X_{81} & X_{82} & X_{83} & X_{84} & X_{85} & X_{86} & X_{87} & X_{88} & X_{89} \\ X_{91} & X_{92} & X_{93} & X_{94} & X_{95} & X_{96} & X_{97} & X_{98} & X_{99} \end{bmatrix}_{9 \times 9}$$

DMAT: 1-dimensional Row Block

$$X = \begin{bmatrix} X_{11} & X_{12} & X_{13} & X_{14} & X_{15} & X_{16} & X_{17} & X_{18} & X_{19} \\ X_{21} & X_{22} & X_{23} & X_{24} & X_{25} & X_{26} & X_{27} & X_{28} & X_{29} \\ X_{31} & X_{32} & X_{33} & X_{34} & X_{35} & X_{36} & X_{37} & X_{38} & X_{39} \\ \hline X_{41} & X_{42} & X_{43} & X_{44} & X_{45} & X_{46} & X_{47} & X_{48} & X_{49} \\ X_{51} & X_{52} & X_{53} & X_{54} & X_{55} & X_{56} & X_{57} & X_{58} & X_{59} \\ X_{61} & X_{62} & X_{63} & X_{64} & X_{65} & X_{66} & X_{67} & X_{68} & X_{69} \\ \hline X_{71} & X_{72} & X_{73} & X_{74} & X_{75} & X_{76} & X_{77} & X_{78} & X_{79} \\ X_{81} & X_{82} & X_{83} & X_{84} & X_{85} & X_{86} & X_{87} & X_{88} & X_{89} \\ X_{91} & X_{92} & X_{93} & X_{94} & X_{95} & X_{96} & X_{97} & X_{98} & X_{99} \end{bmatrix}_{9 \times 9}$$

$$\text{Processor grid} = \begin{vmatrix} 0 \\ 1 \\ 2 \\ 3 \end{vmatrix} = \begin{vmatrix} (0,0) \\ (0,1) \\ (1,0) \\ (1,1) \end{vmatrix}$$

DMAT: 2-dimensional Row Block

$$X = \left[\begin{array}{ccccc|cccc} X_{11} & X_{12} & X_{13} & X_{14} & X_{15} & X_{16} & X_{17} & X_{18} & X_{19} \\ X_{21} & X_{22} & X_{23} & X_{24} & X_{25} & X_{26} & X_{27} & X_{28} & X_{29} \\ X_{31} & X_{32} & X_{33} & X_{34} & X_{35} & X_{36} & X_{37} & X_{38} & X_{39} \\ X_{41} & X_{42} & X_{43} & X_{44} & X_{45} & X_{46} & X_{47} & X_{48} & X_{49} \\ X_{51} & X_{52} & X_{53} & X_{54} & X_{55} & X_{56} & X_{57} & X_{58} & X_{59} \\ \hline X_{61} & X_{62} & X_{63} & X_{64} & X_{65} & X_{66} & X_{67} & X_{68} & X_{69} \\ X_{71} & X_{72} & X_{73} & X_{74} & X_{75} & X_{76} & X_{77} & X_{78} & X_{79} \\ X_{81} & X_{82} & X_{83} & X_{84} & X_{85} & X_{86} & X_{87} & X_{88} & X_{89} \\ X_{91} & X_{92} & X_{93} & X_{94} & X_{95} & X_{96} & X_{97} & X_{98} & X_{99} \end{array} \right]_{9 \times 9}$$

$$\text{Processor grid} = \left| \begin{array}{cc} 0 & 1 \\ 2 & 3 \end{array} \right| = \left| \begin{array}{cc} (0,0) & (0,1) \\ (1,0) & (1,1) \end{array} \right|$$

DMAT: 1-dimensional Row Cyclic

$$X = \begin{bmatrix} X_{11} & X_{12} & X_{13} & X_{14} & X_{15} & X_{16} & X_{17} & X_{18} & X_{19} \\ X_{21} & X_{22} & X_{23} & X_{24} & X_{25} & X_{26} & X_{27} & X_{28} & X_{29} \\ X_{31} & X_{32} & X_{33} & X_{34} & X_{35} & X_{36} & X_{37} & X_{38} & X_{39} \\ X_{41} & X_{42} & X_{43} & X_{44} & X_{45} & X_{46} & X_{47} & X_{48} & X_{49} \\ X_{51} & X_{52} & X_{53} & X_{54} & X_{55} & X_{56} & X_{57} & X_{58} & X_{59} \\ X_{61} & X_{62} & X_{63} & X_{64} & X_{65} & X_{66} & X_{67} & X_{68} & X_{69} \\ X_{71} & X_{72} & X_{73} & X_{74} & X_{75} & X_{76} & X_{77} & X_{78} & X_{79} \\ X_{81} & X_{82} & X_{83} & X_{84} & X_{85} & X_{86} & X_{87} & X_{88} & X_{89} \\ X_{91} & X_{92} & X_{93} & X_{94} & X_{95} & X_{96} & X_{97} & X_{98} & X_{99} \end{bmatrix}_{9 \times 9}$$

$$\text{Processor grid} = \begin{bmatrix} 0 \\ 1 \\ 2 \\ 3 \end{bmatrix} = \begin{bmatrix} (0,0) \\ (0,1) \\ (1,0) \\ (1,1) \end{bmatrix}$$

DMAT: 2-dimensional Row Cyclic

$$X = \begin{bmatrix} X_{11} & X_{12} & X_{13} & X_{14} & X_{15} & X_{16} & X_{17} & X_{18} & X_{19} \\ X_{21} & X_{22} & X_{23} & X_{24} & X_{25} & X_{26} & X_{27} & X_{28} & X_{29} \\ X_{31} & X_{32} & X_{33} & X_{34} & X_{35} & X_{36} & X_{37} & X_{38} & X_{39} \\ X_{41} & X_{42} & X_{43} & X_{44} & X_{45} & X_{46} & X_{47} & X_{48} & X_{49} \\ X_{51} & X_{52} & X_{53} & X_{54} & X_{55} & X_{56} & X_{57} & X_{58} & X_{59} \\ X_{61} & X_{62} & X_{63} & X_{64} & X_{65} & X_{66} & X_{67} & X_{68} & X_{69} \\ X_{71} & X_{72} & X_{73} & X_{74} & X_{75} & X_{76} & X_{77} & X_{78} & X_{79} \\ X_{81} & X_{82} & X_{83} & X_{84} & X_{85} & X_{86} & X_{87} & X_{88} & X_{89} \\ X_{91} & X_{92} & X_{93} & X_{94} & X_{95} & X_{96} & X_{97} & X_{98} & X_{99} \end{bmatrix}_{9 \times 9}$$

$$\text{Processor grid} = \begin{vmatrix} 0 & 1 \\ 2 & 3 \end{vmatrix} = \begin{vmatrix} (0,0) & (0,1) \\ (1,0) & (1,1) \end{vmatrix}$$

DMAT: 2-dimensional Block-Cyclic

$$X = \begin{bmatrix} \begin{array}{cc|cc|cc|cc|c} X_{11} & X_{12} & X_{13} & X_{14} & X_{15} & X_{16} & X_{17} & X_{18} & X_{19} \\ X_{21} & X_{22} & X_{23} & X_{24} & X_{25} & X_{26} & X_{27} & X_{28} & X_{29} \end{array} \\ \hline \begin{array}{cc|cc|cc|cc|c} X_{31} & X_{32} & X_{33} & X_{34} & X_{35} & X_{36} & X_{37} & X_{38} & X_{39} \\ X_{41} & X_{42} & X_{43} & X_{44} & X_{45} & X_{46} & X_{47} & X_{48} & X_{49} \end{array} \\ \hline \begin{array}{cc|cc|cc|cc|c} X_{51} & X_{52} & X_{53} & X_{54} & X_{55} & X_{56} & X_{57} & X_{58} & X_{59} \\ X_{61} & X_{62} & X_{63} & X_{64} & X_{65} & X_{66} & X_{67} & X_{68} & X_{69} \end{array} \\ \hline \begin{array}{cc|cc|cc|cc|c} X_{71} & X_{72} & X_{73} & X_{74} & X_{75} & X_{76} & X_{77} & X_{78} & X_{79} \\ X_{81} & X_{82} & X_{83} & X_{84} & X_{85} & X_{86} & X_{87} & X_{88} & X_{89} \end{array} \\ \hline \begin{array}{cc|cc|cc|cc|c} X_{91} & X_{92} & X_{93} & X_{94} & X_{95} & X_{96} & X_{97} & X_{98} & X_{99} \end{array} \end{bmatrix}_{9 \times 9}$$

$$\text{Processor grid} = \begin{vmatrix} 0 & 1 \\ 2 & 3 \end{vmatrix} = \begin{vmatrix} (0,0) & (0,1) \\ (1,0) & (1,1) \end{vmatrix}$$

The DMAT Data Structure

The more complicated the processor grid, the more complicated the distribution.

DMAT: 2-dimensional Block-Cyclic with 6 Processors

$$X = \begin{bmatrix} \begin{array}{cc|cc|cc|cc|c} X_{11} & X_{12} & X_{13} & X_{14} & X_{15} & X_{16} & X_{17} & X_{18} & X_{19} \\ X_{21} & X_{22} & X_{23} & X_{24} & X_{25} & X_{26} & X_{27} & X_{28} & X_{29} \end{array} \\ \hline \begin{array}{cc|cc|cc|cc|c} X_{31} & X_{32} & X_{33} & X_{34} & X_{35} & X_{36} & X_{37} & X_{38} & X_{39} \\ X_{41} & X_{42} & X_{43} & X_{44} & X_{45} & X_{46} & X_{47} & X_{48} & X_{49} \end{array} \\ \hline \begin{array}{cc|cc|cc|cc|c} X_{51} & X_{52} & X_{53} & X_{54} & X_{55} & X_{56} & X_{57} & X_{58} & X_{59} \\ X_{61} & X_{62} & X_{63} & X_{64} & X_{65} & X_{66} & X_{67} & X_{68} & X_{69} \end{array} \\ \hline \begin{array}{cc|cc|cc|cc|c} X_{71} & X_{72} & X_{73} & X_{74} & X_{75} & X_{76} & X_{77} & X_{78} & X_{79} \\ X_{81} & X_{82} & X_{83} & X_{84} & X_{85} & X_{86} & X_{87} & X_{88} & X_{89} \end{array} \\ \hline \begin{array}{cc|cc|cc|cc|c} X_{91} & X_{92} & X_{93} & X_{94} & X_{95} & X_{96} & X_{97} & X_{98} & X_{99} \end{array} \end{bmatrix}_{9 \times 9}$$

$$\text{Processor grid} = \begin{vmatrix} 0 & 1 & 2 \\ 3 & 4 & 5 \end{vmatrix} = \begin{vmatrix} (0,0) & (0,1) & (0,2) \\ (1,0) & (1,1) & (1,2) \end{vmatrix}$$

Understanding DMAT: Local View

$\begin{bmatrix} X_{11} & X_{12} & X_{17} & X_{18} \\ X_{21} & X_{22} & X_{27} & X_{28} \\ X_{51} & X_{52} & X_{57} & X_{58} \\ X_{61} & X_{62} & X_{67} & X_{68} \\ X_{91} & X_{92} & X_{97} & X_{98} \end{bmatrix}$	5×4	$\begin{bmatrix} X_{13} & X_{14} & X_{19} \\ X_{23} & X_{24} & X_{29} \\ X_{53} & X_{54} & X_{59} \\ X_{63} & X_{64} & X_{69} \\ X_{93} & X_{94} & X_{99} \end{bmatrix}$	5×3	$\begin{bmatrix} X_{15} & X_{16} \\ X_{25} & X_{26} \\ X_{55} & X_{56} \\ X_{65} & X_{66} \\ X_{95} & X_{96} \end{bmatrix}$	5×2
$\begin{bmatrix} X_{31} & X_{32} & X_{37} & X_{38} \\ X_{41} & X_{42} & X_{47} & X_{48} \\ X_{71} & X_{72} & X_{77} & X_{78} \\ X_{81} & X_{82} & X_{87} & X_{88} \end{bmatrix}$	4×4	$\begin{bmatrix} X_{33} & X_{34} & X_{39} \\ X_{43} & X_{44} & X_{49} \\ X_{73} & X_{74} & X_{79} \\ X_{83} & X_{84} & X_{89} \end{bmatrix}$	4×3	$\begin{bmatrix} X_{35} & X_{36} \\ X_{45} & X_{46} \\ X_{75} & X_{76} \\ X_{85} & X_{86} \end{bmatrix}$	4×2

$$\text{Processor grid} = \begin{vmatrix} 0 & 1 & 2 \\ 3 & 4 & 5 \end{vmatrix} = \begin{vmatrix} (0,0) & (0,1) & (0,2) \\ (1,0) & (1,1) & (1,2) \end{vmatrix}$$

The DMAT Data Structure

- ① DMAT is *distributed*. No one processor owns all of the matrix.
 - ② DMAT is *non-overlapping*. Any piece owned by one processor is owned by no other processors.
-
- ③ DMAT can be row-contiguous or not, depending on the processor grid and blocking factor used.
 - ④ DMAT is locally column-major and globally, it depends. . .
 - ⑥ GBD is a generalization of the one-dimensional block DMAT distribution. Otherwise there is no relation.
 - ⑦ DMAT is confusing, but very robust.

X ₁₁	X ₁₂	X ₁₃	X ₁₄	X ₁₅
X ₂₁	X ₂₂	X ₂₃	X ₂₄	X ₂₅
X ₃₁	X ₃₂	X ₃₃	X ₃₄	X ₃₅
X ₄₁	X ₄₂	X ₄₃	X ₄₄	X ₄₅
X ₅₁	X ₅₂	X ₅₃	X ₅₄	X ₅₅
X ₆₁	X ₆₂	X ₆₃	X ₆₄	X ₆₅
X ₇₁	X ₇₂	X ₇₃	X ₇₄	X ₇₅
X ₈₁	X ₈₂	X ₈₃	X ₈₄	X ₈₅
X ₉₁	X ₉₂	X ₉₃	X ₉₄	X ₉₅

Pros and Cons of This Data Structure

Pros

- Fast for distributed matrix computations

Cons

- Literally everything else

This is why we hide most of the distributed details.

The details are there if you want them (you don't want them).

Distributed Matrix Methods

pbdDMAT has over 100 methods with *identical* syntax to R:

- ``[, rbind(), cbind(), ...`
- `lm.fit(), prcomp(), cov(), ...`
- ``%*%`, solve(), svd(), norm(), ...`
- `median(), mean(), rowSums(), ...`

Serial Code

```
1 cov(x)
```

Parallel Code

```
1 cov(x)
```

Comparing pbdMPI and pbdDMAT

pbdMPI:

- MPI + sugar.
- GBD not the only structure **pbdMPI** can handle (just a useful convention).

pbdDMAT:

- More of a software package.
- DMAT structure *must* be used for **pbdDMAT**.
- If the data is not 2d block-cyclic compatible, DMAT will *definitely* give the wrong answer.

Quick Comments for Using pbdDMAT

- 1 Start by loading the package:

```
1 library(pbdDMAT, quiet = TRUE)
```

- 2 Always initialize before starting and finalize when finished:

```
1 init.grid()  
2  
3 # ...  
4  
5 finalize()
```

- 3 Distributed DMAT objects will be given the suffix `.dmat` to visually help distinguish them from global objects. This suffix carries no semantic meaning.

Contents

- 2 Examples Using pbdDMAT
 - Statistics Examples with pbdDMAT
 - RandSVD

Sample Covariance

Serial Code

```
1 Cov.X <- cov(X)
2 print(Cov.X)
```

Parallel Code

```
1 Cov.X <- cov(X)
2 print(Cov.X)
```

Linear Regression

Serial Code

```
1 tX <- t(X)
2 A <- tX %*% X
3 B <- tX %*% y
4
5 ols <- solve(A) %*% B
6
7 # or
8 ols <- lm.fit(X, y)
```

Parallel Code

```
1 tX <- t(X)
2 A <- tX %*% X
3 B <- tX %*% y
4
5 ols <- solve(A) %*% B
6
7 # or
8 ols <- lm.fit(X, y)
```

Example 5: PCA

PCA: pca.r

```

1 library(pbdDMAT, quiet=T)
2 init.grid()
3
4 n <- 1e4
5 p <- 250
6
7 comm.set.seed(diff=T)
8 x.dmat <- ddmatrix("rnorm", nrow=n, ncol=p, mean=100, sd=25)
9
10 pca <- prcomp(x=x.dmat, retx=TRUE, scale=TRUE)
11 prop_var <- cumsum(pca$sdev)/sum(pca$sdev)
12 i <- max(min(which(prop_var > 0.9)) - 1, 1)
13
14 y.dmat <- pca$x[, 1:i]
15
16 comm.cat("\nCols: ", i, "\n", quiet=T)
17 comm.cat("%Cols: ", i/dim(x.dmat)[2], "\n\n", quiet=T)
18
19 finalize()

```

Execute this script via:

```
1 mpirun -np 2 Rscript 5_pca.r
```

Sample Output:

```

1 Cols: 221
2 %Cols: 0.884

```


Distributed Matrices

pbdDEMO contains many other examples of reading and managing GBD and DMAT data

Randomized SVD¹

PROTOTYPE FOR RANDOMIZED SVD

Given an $m \times n$ matrix A , a target number k of singular vectors, and an exponent q (say, $q = 1$ or $q = 2$), this procedure computes an approximate rank- $2k$ factorization $U\Sigma V^*$, where U and V are orthonormal, and Σ is nonnegative and diagonal.

Stage A:

- 1 Generate an $n \times 2k$ Gaussian test matrix Ω .
- 2 Form $Y = (AA^*)^q A\Omega$ by multiplying alternately with A and A^* .
- 3 Construct a matrix Q whose columns form an orthonormal basis for the range of Y .

Stage B:

- 4 Form $B = Q^*A$.
- 5 Compute an SVD of the small matrix: $B = \tilde{U}\Sigma V^*$.
- 6 Set $U = Q\tilde{U}$.

Note: The computation of Y in step 2 is vulnerable to round-off errors. When high accuracy is required, we must incorporate an orthonormalization step between each application of A and A^* ; see Algorithm 4.4.

ALGORITHM 4.4: RANDOMIZED SUBSPACE ITERATION

Given an $m \times n$ matrix A and integers ℓ and q , this algorithm computes an $m \times \ell$ orthonormal matrix Q whose range approximates the range of A .

- 1 Draw an $n \times \ell$ standard Gaussian matrix Ω .
- 2 Form $Y_0 = A\Omega$ and compute its QR factorization $Y_0 = Q_0R_0$.
- 3 for $j = 1, 2, \dots, q$
 - 4 Form $\tilde{Y}_j = A^*Q_{j-1}$ and compute its QR factorization $\tilde{Y}_j = \tilde{Q}_j\tilde{R}_j$.
 - 5 Form $Y_j = A\tilde{Q}_j$ and compute its QR factorization $Y_j = Q_jR_j$.
- 6 end
- 7 $Q = Q_q$.

Serial R

```

1 randSVD <- function(A, k, q=3)
2 {
3   ## Stage A
4   Omega <- matrix(rnorm(n*2*k),
5                     nrow=n, ncol=2*k)
6   Y <- A %*% Omega
7   Q <- qr.Q(qr(Y))
8   At <- t(A)
9   for(i in 1:q)
10    {
11      Y <- At %*% Q
12      Q <- qr.Q(qr(Y))
13      Y <- A %*% Q
14      Q <- qr.Q(qr(Y))
15    }
16
17   ## Stage B
18   B <- t(Q) %*% A
19   U <- La.svd(B)$u
20   U <- Q %*% U
21   U[, 1:k]
22 }
```

¹Halko N, Martinsson P-G and Tropp J A 2011 Finding structure with randomness: probabilistic algorithms for constructing approximate matrix decompositions *SIAM Rev.* **53** 217–88

Randomized SVD

Serial R

```

1 randSVD <- function(A, k, q=3)
2 {
3   ## Stage A
4   Omega <- matrix(rnorm(n*2*k),
5                   nrow=n, ncol=2*k)
6   Y <- A %*% Omega
7   Q <- qr.Q(qr(Y))
8   At <- t(A)
9   for(i in 1:q)
10    {
11      Y <- At %*% Q
12      Q <- qr.Q(qr(Y))
13      Y <- A %*% Q
14      Q <- qr.Q(qr(Y))
15    }
16
17   ## Stage B
18   B <- t(Q) %*% A
19   U <- La.svd(B)$u
20   U <- Q %*% U
21   U[, 1:k]
22 }
```

Parallel pbdR


```

1 randSVD <- function(A, k, q=3)
2 {
3   ## Stage A
4   Omega <- ddmatrix("rnorm",
5                   nrow=n, ncol=2*k)
6   Y <- A %*% Omega
7   Q <- qr.Q(qr(Y))
8   At <- t(A)
9   for(i in 1:q)
10    {
11      Y <- At %*% Q
12      Q <- qr.Q(qr(Y))
13      Y <- A %*% Q
14      Q <- qr.Q(qr(Y))
15    }
16
17   ## Stage B
18   B <- t(Q) %*% A
19   U <- La.svd(B)$u
20   U <- Q %*% U
21   U[, 1:k]
22 }
```

Randomized SVD

30 Singular Vectors from a 100,000 by 1,000 Matrix

Algorithm — full — randomized



30 Singular Vectors from a 100,000 by 1,000 Matrix
Speedup of Randomized vs. Full SVD

