

A Quick Guide for the pbdMPI Package

Wei-Chen Chen¹, George Ostrouchov^{1,2}, Drew Schmidt²,
Pragneshkumar Patel², Hao Yu³

¹Computer Science and Mathematics Division,
Oak Ridge National Laboratory,
Oak Ridge, TN, USA

²Remote Data Analysis and Visualization Center,
University of Tennessee,
Knoxville, TN, USA

³University of Western Ontario,
London, Ontario, Canada

Contents

Acknowledgement	iii
1. Introduction	1
1.1. System Requirements	2
1.2. Installation and Quick Start	2
1.3. Basic Steps	3
1.4. More Examples	4
2. Performance	4
3. FAQs	6
3.1. General	6
3.2. Programming	7
3.3. MPI Errors	8
4. Windows Systems	10
4.1. Install from Binary	10
4.2. Build from Source	11
5. SPMD in Examples from package parallel	11
References	15

© 2012 pbdR Core Team.

Permission is granted to make and distribute verbatim copies of this vignette and its source provided the copyright notice and this permission notice are preserved on all copies.

This publication was typeset using L^AT_EX.

Acknowledgement

Chen and Ostrouchov were supported in part by the project “Visual Data Exploration and Analysis of Ultra-large Climate Data” funded by U.S. DOE Office of Science under Contract No. DE-AC05-00OR22725. Ostrouchov, Schmidt, and Patel were supported in part by the project “NICS Remote Data Analysis and Visualization Center” funded by the Office of Cyberinfrastructure of the U.S. National Science Foundation under Award No. ARRA-NSF-OCI-0906324 for NICS-RDAV center.

This work used resources of the Oak Ridge Leadership Computing Facility at the Oak Ridge National Laboratory, which is supported by the Office of Science of the U.S. Department of Energy under Contract No. DE-AC05-00OR22725. This work also used resources of National Institute for Computational Sciences at the University of Tennessee, Knoxville, which is supported by the Office of Cyberinfrastructure of the U.S. National Science Foundation under Award No. ARRA-NSF-OCI-0906324 for NICS-RDAV center. This work used resources of the Newton HPC Program at the University of Tennessee, Knoxville.

We thank our colleagues from the Scientific Data Group, Computer Science and Mathematics Division, Oak Ridge National Laboratory (ORNL), Hasan Abbasi, Jong Youl Choi, Scott Klasky, and Nobert Podhorszki for discussing windows MPI systems, compiler issues, dynamic libraries, and generally improving our knowledge of MPI performance issues.

We also thank Brian D. Ripley, Kurt Hornik, Uwe Ligges, and Simon Urbanek from the R Core Team for discussing package release issues and helping us solve portability problems on different platforms.

Warning: This document is written to explain the main functions of **pbdMPI** (Chen *et al.* 2012), version 0.1-1. Every effort will be made to ensure future versions are consistent with these instructions, but features in later versions may not be explained in this document.

Information about the functionality of this package, and any changes in future versions can be found on website: “Programming with Big Data in R” at <http://r-pbd.org/>.

1. Introduction

Our intent is to bring the most common parallel programming model from supercomputing, Single Program Multiple Data (SPMD), to R and enable distributed handling of truly large data. Consequently, **pbdMPI** is intended for batch mode programming with big data (pbd). Unlike **Rmpi** (Yu 2010), **snow** (Tierney *et al.* 2012), or **parallel** (R Core Team 2012), interactive mode is not supported. We think that interaction with a large distributed parallel computing platform is better handled with a client/server relationship, and we are developing other packages in this direction. **pbdMPI** simplifies MPI interaction, but leaves low and mid level functions available for advanced programmers. For example, it is easy to hand communicators to **pbdMPI** from other applications through MPI array pointers. This is intended for integration with other, possibly non-R, parallel software.

Under the SPMD parallel programming model, the identical program runs on every processor but typically works on different parts of a large data set, while communicating with other copies of itself as needed. Differences in execution stem from `comm.rank`, which is typically different on every processor. While on the surface this sounds complicated, after some experience and a new mindset, programming is surprisingly simple. There is no master. There is only cooperation among the workers. Although we target very large distributed computing platforms, SPMD works well even on small multicore platforms.

In the following, we list the main features of **pbdMPI**.

1. Under the SPMD batch programming model, a single program is written, which is spawned by `mpirun`. No spawning and broadcasting from within R are required.
2. S4 methods are used for most collective functions so it is easy to extend them for general R objects.
3. Default methods (like `Robj` functions in **Rmpi**) have homogeneous checking for data type so they are safe for general users.
4. The API in all functions is simplified, with all default arguments in control objects.
5. Methods for array or matrix types are implemented without serialization and un-serialization, resulting in faster communication than **Rmpi**.
6. Basic data types of integer, double and raw in **pbdMPI** are communicated without further checking. This is risky but fast for advanced programmers.
7. Character data type is serialized and communicated by raw type.

System requirements and installation of **pbdMPI** are described next. Section 2 gives a short example for comparing performance of **pbdMPI** and **Rmpi** (Yu 2010). In Section 3, a few

quick answers for questions are given. Section 4 provides settings for Windows environments. Finally, in Section 5, two examples from **parallel** are shown as SPMD **pbdMPI** programs.

1.1. System Requirements

pbdMPI requires MPI (http://en.wikipedia.org/wiki/Message_Passing_Interface). The package is mainly developed and tested under **OpenMPI** (<http://www.open-mpi.org/>) in xubuntu 11.04 (<http://xubuntu.org/>) and should also work with LAM/MPI (<http://www.lam-mpi.org/>) and MPICH2 (<http://www.mcs.anl.gov/research/projects/mpich2/>). In addition to unix, **pbdMPI** should also run under other operating systems such as Mac OS X with OpenMPI or Windows 7 with MPICH2 if MPI is installed and launched properly, although we have not tested on multiple machines yet. Please let us know about your experience.

For normal installation, see Sec. 1.2. To build as a static library, which may be required on some large systems, use

Shell Command

```
./configure --enable-static --prefix=${MPI_ROOT}
make
make install
```

where **--enable-static** can build a static library (optional), and **\${MPI_ROOT}** is the path to MPI root. Note that the static library is not necessary for **pbdMPI** but may avoid dynamic loading problems.

To make sure your MPI system is working, test with

Shell Command

```
mpiexec -np 2 hostname
```

This should list two host names where MPI jobs are running. Note to use **hostname.exe** with the extension on a Windows system.

1.2. Installation and Quick Start

One can download **pbdMPI** from CRAN at <http://cran.r-project.org>, and the intallation can be done with the following commands (using OpenMPI library)

Shell Command

```
tar zxvf pbdMPI_0.1-0.tar.gz
R CMD INSTALL pbdMPI
```

Further configure arguments include

Argument	Default
--with-Rmpi-type	OPENMPI
--with-Rmpi-include	\${MPI_ROOT}/include
--with-Rmpi-libpath	\${MPI_ROOT}/lib
--with-mpi	\${MPI_ROOT}

where `${MPI_ROOT}` is the path to the MPI root. For non-default and unusual installations of MPI systems, the commands may be

Shell Command

```
### Under command mode
R CMD INSTALL pbdMPI \
  --configure-args="--with-Rmpi-type=OPENMPI \
  --with-mpi=/usr/local"
R CMD INSTALL pbdMPI \
  --configure-args="--with-Rmpi-type=OPENMPI \
  --with-Rmpi-include=/usr/local/ompi/include \
  --with-Rmpi-libpath=/usr/local/ompi/lib"
```

See the package source file `pbdMPI/configure` for details.

One can get started quickly with **pbdMPI** by learning from the following six examples.

Shell Command

```
### At the shell prompt, run the demo with 2 processors by
### (Use Rscript.exe for windows system)
mpiexec -np 2 Rscript -e "demo(allgather, 'pbdMPI', ask=F, echo=F)"
mpiexec -np 2 Rscript -e "demo(allreduce, 'pbdMPI', ask=F, echo=F)"
mpiexec -np 2 Rscript -e "demo(bcast, 'pbdMPI', ask=F, echo=F)"
mpiexec -np 2 Rscript -e "demo(gather, 'pbdMPI', ask=F, echo=F)"
mpiexec -np 2 Rscript -e "demo(reduce, 'pbdMPI', ask = F, echo=F)"
mpiexec -np 2 Rscript -e "demo(scatter, 'pbdMPI', ask=F, echo=F)"
```

1.3. Basic Steps

In the SPMD world, every processor is a worker, every worker knows about all the others, and each worker does its own job, possibly communicating with the others. Unlike the manager/workers style, SPMD is more likely to fully use the computer resources. The following shows typical basic steps of using **pbdMPI**.

1. Initialize. (`init`)
2. Read your portion of the data.
3. Compute. (`send`, `recv`, `barrier`, ...)
4. Communicate results among workers. (`gather`, `allgather`, `reduce`, `allreduce`, ...)
5. Finalize. (`finalize`)

In a given application, the Compute and Communicate steps may be repeated several times for intermediate results. The Compute and Communicate steps are more general than the “map” and “reduce” steps of the map-reduce paradigm but similar in spirit. One big difference is that the Communicate step may place the “reductions” on all processors rather than just one (the manager for map-reduce) for roughly the same time cost. With some experience, one can easily convert existing R scripts, and quickly parallelize serial code. **pbdMPI** tends to reduce programming effort, avoid complicated MPI techniques, and gain computing performance.

The major communication functions of **pbdMPI** and corresponding similar functions of **Rmpi** are listed in the following.

pbdMPI (S4)	Rmpi
allgather	mpi.allgather, mpi.allgatherv, mpi.allgather.Robj
allreduce	mpi.allreduce
bcast	mpi.bcast, mpi.bcast.Robj
gather	mpi.gather, mpi.gatherv, mpi.gather.Robj
recv	mpi.recv, mpi.recv.Robj
reduce	mpi.reduce
scatter	mpi.scatter, mpi.scatterv, mpi.scatter.Robj
send	mpi.send, mpi.send.Robj

1.4. More Examples

The package source files provide several examples based on **pbdMPI**, such as

Directory	Examples
pbdMPI/inst/examples/test_spmd/	main SPMD functions
pbdMPI/inst/examples/test_rmpi/	comparison to Rmpi
pbdMPI/inst/examples/test_parallel/	comparison to parallel
pbdMPI/inst/examples/test_performance/	performance testing
pbdMPI/inst/examples/test_s4/	S4 extension

2. Performance

There are more examples for testing performance in pbdMPI/inst/examples/test_rmpi. Here, we only show a simple comparison of **pbdMPI** to **Rmpi**. The two scripts are equivalent for **pbdMPI** and **Rmpi**. We run them with two processors and obtain computing times listed below.

Save the following script in `demo_spmd.r` and run it with two processors by

Shell Command

```
mpiexec -np 2 Rscript demo_spmd.r
```

to see the computing time on your platform.

pbdMPI R Script

```
### Save this script in "demo_spmd.r".
library(pbdMPI, quiet = TRUE)
init()

time.proc <- list()
```

```
time.proc$default <- system.time({
  for(i in 1:1000) y <- allgather(list(x = 1:10000))
  barrier()
})

time.proc$matrix <- system.time({
  for(i in 1:1000) y <- allgather(matrix(1:10000, nrow = 100))
  barrier()
})

comm.print(time.proc, quiet = TRUE)
finalize()
```

Save the following script in `demo_rmpi.r` and run with two processors by

Shell Command

```
mpiexec -np 2 Rscript demo_rmpi.r
```

to see the computing time on your platform.

Rmpi R Script

```
### Save this script in "demo_rmpi.r".
library(Rmpi)
invisible(mpi.comm.dup(0, 1))

time.proc <- list()
time.proc$Robj <- system.time({
  for(i in 1:1000) y <- mpi.allgather.Robj(list(x = 1:10000))
  mpi.barrier()
})

time.proc$matrix <- system.time({
  for(i in 1:1000) y <- mpi.allgather.Robj(matrix(1:10000, nrow =
    100))
  mpi.barrier()
})

if(mpi.comm.rank(1) == 0) print(time.proc)
mpi.quit()
```

The following shows the computing time of the above two scripts on a single machine with two processors Intel(R) Core(TM) i5-2410M CPU @ 2.30 GHz, xubuntu 11.04 system, and OpenMPI 1.6. The **pbdMPI** is more efficient than **Rmpi** with `list` and `matrix/array` data structures.

R Output

```
>> Output from demo_spmd.r
$default
   user  system elapsed
1.680   0.030   1.706
```



```

$matrix
  user  system elapsed
0.950   0.000   0.953

>> Output from demo_rmpi.r
$Robj
  user  system elapsed
2.960   0.090   3.041

$matrix
  user  system elapsed
3.120   0.030   3.147

```

3. FAQs

3.1. General

1. **Q:** Do I need MPI knowledge to run **pbdMPI**?

A: Yes, but only the big picture, not the details. We provide several examples in `pbdMPI/inst/examples/test_spmd/` to introduce essential methods for learning MPI communication.

2. **Q:** Can I run **pbdMPI** on my laptop locally?

A: Sure, as long as you have an MPI system. You even can run it on 1 CPU.

3. **Q:** Does **pbdMPI** support Windows clusters?

A: Yes, the released binary currently supports OpenMPI and MPICH2. For other MPI systems, users have to compile from source.

4. **Q:** Can I run **pbdMPI** in OpenMPI and MPICH2 together?

A: No, you can have both OpenMPI and MPICH2 installed in your OS, but you are only allowed to run **pbdMPI** with one MPI system. Just pick one.

5. **Q:** Does **pbdMPI** support any interactive mode?

A: No, but yes. **pbdMPI** only considers batch execution and aims for programming with big data that do not fit on desktop platforms. We think that interaction with big data on a big machine is better handled with a client/server interface, where the server runs SPMD codes on big data and the client operates with reduced data representations.

If you really need an interactive mode, such as for debugging, you can utilize **pbdMPI** scripts inside **Rmpi**. **Rmpi** mainly focuses on Manager/Workers computing environments, but can run SPMD codes on workers only with a few adjustments. See the “Programming with Big Data in R” website for details at <http://r-pbd.org/>.

Note that **pbdMPI** uses communicators different from **Rmpi**. Be sure to free the memory correctly for both packages before quitting. `finalize(mpi.finalize = FALSE)` can free the memory allocated by **pbdMPI**, but does not terminate MPI before calling `mpi.quit` of **Rmpi**.

6. **Q:** Can I write my own collective functions for my own data type?

A: Yes, S4 methods allow users to add their own data type, and functions. Quick examples can be found in `pbdsMPI/inst/examples/test_s4/`.

3.2. Programming

1. **Q:** Can I run task jobs by using `pbdsMPI`?

A: Yes, it is relatively straightforward for parallel tasks. Neither extra automatic functions nor further command/data communication is required. In other words, SPMD is easier for Monte Carlo, bootstrap, MCMC simulation and statistical analysis for ultra-large datasets.

Example 1:

SPMD R Script

```
library(pbdMPI, quiet = TRUE)
init()

id <- get.jid(total.tasks)

### Using a loop
for(i in id){
  # put independent task i script here
}

### or using apply-like functions.
lapply(id, function(i){
  # put independent task i script here.
})

finalize()
```

Note that `id` gets different values on different processors, accomplishing `total.tasks` across all processors. Also note that any data and partial results are not shared across the processors unless communicated.

Example 2:

SPMD R Script

```
library(pbdMPI, quiet = TRUE)
init()

### Directly using a loop
for(i in 1:total.tasks){
  if(i %% comm.size() == comm.rank()){
    # put independent task i script here
  }
}

### or using apply-like function.
```

```
lapply(1:total.tasks, function(i){
  if(i %% comm.size() == comm.rank()){
    # put independent task i script here.
  }
})

finalize()
```

2. **Q:** What if I want to run task push or pull by using **pbdMPI**?

A: No problem. As in the two preceding examples, task push or pull can be done in the same way by using rank 0 as the manager and the other ranks as workers. However, we do not recommend it except perhaps for inhomogeneous computing environments.

3. **Q:** Are S4 methods more efficient?

A: Yes and No. S4 methods are a little less efficient than using `switch ... case ...` in C, but most default methods use `raw` with `un-` and `serialize` which may cost 3-10 times more than using `integer` or `double`. Instead of writing C code, it is easier to take advantage of S4 methods to extend to general R objects (`matrix`, `array`, `list`, `data.frame`, and `class ...`) by communicating with basic data types (`integer` and `double`) and avoiding serialization.

4. **Q:** Can **pbdMPI** take or export communicators?

A: Yes, the physical memory address is set to the variable `.__MPI_APTS__` in the `.GlobalEnv` through a call to `init()`. The variable points to a structure containing MPI structure arrays preallocated while **pbdMPI** is loaded. `pbdMPI/src/pkg_*` provides a mechanism to take or export external/global variables at the C language level.

3.3. MPI Errors

1. **Q:** If installation fails with

Error Message

```
Error in dyn.load(file, DLLpath = DLLpath, ...) :
  unable to load shared object '/.../pbdMPI/libs/pbdMPI.so':
  libmpi.so: cannot open shared object file: No such file or
  directory
```

A: OpenMPI may not be installed in the usual location, so the environment variable `LD_LIBRARY_PATH` should be set to the `libmpi.so` path, such as

Shell Command

```
export LD_LIBRARY_PATH=/usr/local/openmpi/lib:$LD_LIBRARY_PATH
```

where `/usr/local/openmpi/lib` should be replaced by the path to `libmpi.so`. Or, use `LD_PRELOAD` to preload the MPI library if the library name is not conventional, such as

Shell Command

```
export LD_PRELOAD=/usr/local/openmpi/lib/libmpi.so:$LD_PRELOAD
```

Another solution may be to use the unix command `ldconfig` to setup the correct path.

2. **Q:** **pb(MPI)** installs successfully, but fails at initialization when calling the function `init()` with error message

Error Message

```
/usr/lib/R/bin/exec/R: symbol lookup error:
/usr/lib/openmpi/lib/openmpi/mca_paffinity_linux.so: undefined
symbol:
mca_base_param_reg_int
```

A: The linked library at installation may be different from the runtime library, especially when your system has more than one MPI systems. Since the library at installation is detected by `autoconf` (`configure`) and `automake` (`Makevars`), it can be linked with OpenMPI library, but MPICH2 or LAM/MPI is searched before OpenMPI according to `$PATH`.

Solutions:

- Check which MPI system is your favorite to call. If you use OpenMPI, then you have to link with OpenMPI. Similarly, for MPICH2.
 - Or, only keep the MPI system you do like and drop others.
 - Use `--with-Rmpi-type` to specify the MPI type.
 - Use `--with-Rmpi-include` and `--with-Rmpi-libpath` to specify the right version.
3. **Q:** (Linux) If OpenMPI `mpiexec` fails with

Error Message

```
mca: base: component_find: unable to open
/.../openmpi/lib/openmpi/mca_paffinity_hwloc:
/.../openmpi/lib/openmpi/mca_paffinity_hwloc.so:
undefined symbol: opal_hwloc_topology (ignored)
...
mca: base: component_find: unable to open
/.../openmpi/lib/openmpi/mca_carto_auto_detect:
/.../openmpi/lib/openmpi/mca_carto_auto_detect.so:
undefined symbol: opal_carto_base_graph_get_host_graph_fn
(ignored)
...
```

A: The linked MPI library `libmpi.so` may be missing or have a different name. OpenMPI builds shared/dynamic libraries by default and the target file `libmpi.so` is used by `pb(MPI)/src/spmd.c` through `#include <dlfcn.h>` and `dlopen(...)` in the file `pb(MPI)/src/pkg_dl.c`.

Solutions:

- Check if the path and version of `libmpi.so` are correct. In particular, one may have different MPI systems installed.
- When linking with `libmpi.so` in OpenMPI, one must run/load **pb(MPI)** with OpenMPI's `libmpi.so`. The same for LAM/MPI and MPICH2.

- Use `export LD_PRELOAD=$PATH_TO_libmpi.so.*` in command mode.
- Use the file `/etc/ld.so.conf` and the command `ldconfig` to manage personal MPI installation.
- Or, recompile OpenMPI with a static library, and use `libmpi.a` instead.

4. **Q:** (Windows) If OpenMPI `mpiexec` fails with

Error Message

```
ORTE_ERROR_LOG: Error in file ..\..\..\openmpi-1
.6\orte\mca\ess\hnp\ess_hnp_module.c at line 194
...
ORTE_ERROR_LOG: Error in file ..\..\..\openmpi-1
.6\orte\runtime\orte_init.c at line 128
...
```

A: Check if the network is unplugged, the network should be “ON” even on a single machine. At least, the status of network interface should be correct.

4. Windows Systems

Currently, **pbdMPI** supports Windows with MPICH2 (<http://www.mcs.anl.gov/research/projects/mpich2/>). The binary installations of both MPI systems are available from the website. `mpich2-1.4.1p1-win-ia32.msi` is for 32-bits and `mpich2-1.4.1p1-win-x86-64.msi` is for 64-bits. The installation is easily done with a few clicks. The default environment and path are recommended.

For running MPI and R, users need to set `PATH` to the `mpiexec.exe` and `Rscript.exe`. By default,

Shell Command

```
### Under command mode, or save in a batch file.
SET R_HOME=C:\Program Files\R\R-2.15.1
SET MPI_ROOT=C:\Program Files\MPICH2
SET PATH=%MPI_ROOT%\bin\;%R_HOME%\bin\;%PATH%
```

is for the 64-bit MPICH2, but replace

Shell Command

```
SET MPI_ROOT=C:\Program Files (x86)\MPICH2
```

for the 32-bit MPICH2.

4.1. Install from Binary

The binary packages of **pbdMPI** are available on the website: “Programming with Big Data in R” at <http://r-pbd.org/>. Note that different MPI systems require different binaries. The binary can be installed by

Shell Command

```
R CMD INSTALL pbdMPI_0.1-0.zip
```

As on Unix systems, one can start quickly with **pbdMPI** by learning from the following demos. There are six basic examples.

Shell Command

```
### Run the demo with 2 processors by
mpiexec -np 2 Rscript.exe -e "demo(allgather, 'pbdMPI', ask=F, echo=F)"
mpiexec -np 2 Rscript.exe -e "demo(allreduce, 'pbdMPI', ask=F, echo=F)"
mpiexec -np 2 Rscript.exe -e "demo(bcast, 'pbdMPI', ask=F, echo=F)"
mpiexec -np 2 Rscript.exe -e "demo(gather, 'pbdMPI', ask=F, echo=F)"
mpiexec -np 2 Rscript.exe -e "demo(reduce, 'pbdMPI', ask=F, echo=F)"
mpiexec -np 2 Rscript.exe -e "demo(scatter, 'pbdMPI', ask=F, echo=F)"
```

Warning: Note that spacing inside **demo** is not working for Windows systems and **Rscript.exe** should be evoked rather than **Rscript**.

4.2. Build from Source

Warning: This section is only for building binary in 32- and 64-bit Windows system. A more general way can be found in the file **pbdMPI/INSTALL.win**.

Make sure that **R**, **Rtools**, and **MINGW** are in the **PATH**. See details on the website "Building R for Windows" at <http://cran.r-project.org/bin/windows/Rtools/>. But, if both 32- and 64-bits **MPICH2** are installed, two different environment variables **MPI_ROOT_32** and **MPI_ROOT_64** need to be set for building binaries.

For example, the minimum requirement may be

Shell Command

```
### Under command mode, or save in a batch file.
SET R_HOME=C:\Program Files\R\R-2.15.1
SET RTOOLS=C:\Rtools\bin\
SET MINGW=C:\Rtools\gcc-4.6.3\bin
SET PATH=%R_HOME%;%R_HOME%\BIN\;%RTOOLS%;%MINGW%;%PATH%
SET MPI_ROOT_64=C:\Program Files\MPICH2
SET MPI_ROOT_32=C:\Program Files (x86)\MPICH2
```

With a correct **PATH**, one can use the **R** commands to install/build the **pbdMPI**:

Shell Command

```
### Under command mode, build and install the binary.
tar zxvf pbdMPI_0.1-0.tar.gz
R CMD INSTALL --build pbdMPI
R CMD INSTALL pbdMPI_0.1-0.zip
```

5. SPMD in Examples from package parallel

We demonstrate how a simple script from **parallel** can be written in batch by using **pbdMPI**. Each time, we first give the version using **parallel** followed by the version using **pbdMPI**. All codes are available in `pbdMPI/inst/examples/test_parallel/`.

Example 1: (`mclapply()` originates in **multicore** ([Urbanek 2011](#)))

Save the following script in a file and run with

Shell Command

```
Rscript 01_mclapply_par.r
```

to see the computing time on your platform.

multicore R Script

```
### File Name: 01_mclapply_par.r
library(parallel)

system.time(
  unlist(mclapply(1:32, function(x) sum(rnorm(1e7))))
)
```

Now save this script in a file and run with

Shell Command

```
mpirun -np 2 Rscript 01_mclapply_spmd.r
```

to see the computing time on your platform.

SPMD R Script

```
### File Name: 01_mclapply_spmd.r
library(pbdMPI, quiet = TRUE)
init()

time.proc <- system.time({
  id <- get.jid(32)
  ret <- unlist(lapply(id, function(i) sum(rnorm(1e7))))
  ret <- allgather(ret, unlist = TRUE)
})
comm.print(time.proc)

finalize()
```

The following shows the computing time of the above codes on a single local machine with two cores Intel(R) Core(TM) i5-2410M CPU @ 2.30 GHz, xubuntu 11.04 system, and OpenMPI 1.6. There is not much communication latency in this example since all computations are on one “node” which is also a limitation of **parallel**.

R Output

```
>> Test ./01_mclapply_par.r
      user  system elapsed
16.800    0.570   17.419
```

```
>> Test ./01_mclapply_spmd.r
COMM.RANK = 0
      user  system elapsed
17.130    0.460   17.583
```

Example 2: (`parMM()` originates in **snow** (Tierney *et al.* 2012))

Save the following code in a file and run with two processors

Shell Command

```
Rscript 02_parMM_par.r
```

to see the computing time on your platform.

snow R Script

```
### File Name: 02_parMM_par.r
library(parallel)
cl <- makeCluster(2)

splitRows <- function (x, ncl){
  lapply(splitIndices(nrow(x), ncl), function(i) x[i, , drop = FALSE])
}
parMM <- function (cl, A, B){
  do.call(rbind, clusterApply(cl, splitRows(A, length(cl)),
    get("%*%"), B))
}

set.seed(123)
A <- matrix(rnorm(1000000), 1000)
system.time(replicate(10, A %*% A))
system.time(replicate(10, parMM(cl, A, A)))

stopCluster(cl)
```

Now save this script in a file and run with

Shell Command

```
mpirun -np 2 Rscript 02_parMM_spmd.r
```

to see the computing time on your platform.

SPMD R Script

```
### File Name: 02_parMM_spmd.r
library(pbdMPI, quiet = TRUE)
init()

set.seed(123)
x <- matrix(rnorm(1000000), 1000)

parMM.spmd <- function(x, y){
  id <- get.jid(nrow(x))
```



```
do.call(rbind, allgather(x[id,] %*% y))
}
time.proc <- system.time(replicate(10, parMM.spmc(x, x)))
comm.print(time.proc)

finalize()
```

The following shows the computing time of the above code on a single machine with two processors Intel(R) Core(TM) i5-2410M CPU @ 2.30 GHz, xubuntu 11.04 system, and OpenMPI 1.6. **pbdMPI** performs better than **snow** in this example even without communication over network.

R Output

```
>> Test ./02_parMM_par.r
      user  system elapsed
12.460    0.170   12.625
      user  system elapsed
 1.780    0.820   10.095

>> Test ./02_parMM_spmc.r
COMM.RANK = 0
      user  system elapsed
  8.84    0.42    9.26
```

References

- Chen WC, Ostrouchov G, Schmidt D, Patel P, Yu H (2012). “pbdMPI: Programming with Big Data – Interface to MPI.” R Package, URL <http://cran.r-project.org/package=pbdMPI>.
- R Core Team (2012). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria. ISBN 3-900051-07-0, URL <http://www.r-project.org/>.
- Tierney L, Rossini AJ, Li N, Sevcikova H (2012). “snow: Simple Network of Workstations.” R package (v:0.3-9), URL <http://cran.r-project.org/package=snow>.
- Urbanek S (2011). “multicore: Parallel processing of R code on machines with multiple cores or CPUs.” R package (v:0.1-7), URL <http://cran.r-project.org/package=multicore>.
- Yu H (2010). “Rmpi: Interface (Wrapper) to MPI (Message-Passing Interface).” R Package (v:0.5-9), URL <http://cran.r-project.org/package=Rmpi>.