

Guide to the **pbdPROF** Package

Gaurav Sehrawat¹, Wei-Chen Chen², Drew Schmidt³, Pragneshkumar Patel³, and
George Ostrouchov^{2,3}

¹Jaypee Institute of Information Technology
Uttar Pradesh, India

²Computer Science and Mathematics Division,
Oak Ridge National Laboratory,
Oak Ridge, TN, USA

³Remote Data Analysis and Visualization Center
University of Tennessee,
Knoxville, TN, USA

July 10, 2013

Contents

Acknowledgement	ii
1 Introduction	1
1.1 System Requirements	1
2 Installation	1
2.1 fpmi	1
2.2 mpiP	2
2.3 Test Script	2
3 FAQ	2
References	3
4 References	3

© 2013 pbdR Core Team.

Permission is granted to make and distribute verbatim copies of this vignette and its source provided the copyright notice and this permission notice are preserved on all copies.

This publication was typeset using L^AT_EX.

Acknowledgement

Sehrawat was generously supported by Google for Google Summer of Code 2013.

Chen and Ostrouchov were supported in part by the project “Visual Data Exploration and Analysis of Ultra-large Climate Data” funded by U.S. DOE Office of Science under Contract No. DE-AC05-00OR22725. Ostrouchov, Schmidt, and Patel were supported in part by the project “NICS Remote Data Analysis and Visualization Center” funded by the Office of Cyberinfrastructure of the U.S. National Science Foundation under Award No. ARRA-NSF-OCI-0906324 for NICS-RDAV center.

Warning: The findings and conclusions in this article have not been formally disseminated by the U.S. Department of Energy and should not be construed to represent any determination or policy of University, Agency, and National Laboratory.

This document is written to explain the main functions of **pbDPROF** (Sehrawat *et al.*, 2013), version 0.1-0. Every effort will be made to ensure future versions are consistent with these instructions, but features in later versions may not be explained in this document.

Information about the functionality of this package, and any changes in future versions can be found on website: “Programming with Big Data in R” at <http://r-pbd.org/>.

1 Introduction

The main features of **pbDPROF** are:

1. ...

1.1 System Requirements

pbDPROF requires an MPI installation and an MPI-using package, such as **pbDMPI** (Chen *et al.*, 2012a) or **Rmpi** (Yu, 2010). For information regarding how to install MPI or **pbDMPI**, please see the **pbDMPI** vignette (Chen *et al.*, 2012b) or the pbdR website <http://r-pbd.org/>.

2 Installation

2.1 fpmPI

WCC: Need **fpmPI** reference.

Using internal **fpmPI** library, via

Shell Command

```
R CMD INSTALL pbdPROF_0.1-0.tar.gz
```

By default, this compiles `src/fpmPI/*`, generates a static library `libfpmPI.a`, and installs the library to `pbdPROF/lib/`. No shared library is generated or needed, so the directory `pbdPROF/libs/` is empty (no need to build `pbdPROF.so`.) The linking argument is saved in `Makeconf` and installed to `pbdPROF/etc/` for further linking such as **pbDMPI** is reinstalled with `--enable-pbdPROF`.

Linking with external **fpmPI** library, via

Shell Command

```
R CMD INSTALL pbdPROF_0.1-0.tar.gz \
  --configure-args="--with-fpmPI='-L/path_to_fpmPI/lib -lfpmPI'"
```

This only provides the linking arguments `-L/path_to_fpmPI/lib -lfpmPI` which is saved in `Makeconf` and installed to `pbdPROF/etc/` for further linking such as **pbDMPI** is reinstalled with `--enable-pbdPROF`.

Reinstall **pbDMPI**, **pbdSLAP**, and **pbdNCDF4**, via

Shell Command

```
R CMD INSTALL pbdMPI_1.0-0.tar.gz --configure-args="--enable-pbdPROF"
R CMD INSTALL pbdSLAP_0.1-6.tar.gz
R CMD INSTALL pbdNCDF4_0.1-1.tar.gz
```

Note that the `pbdMPI/R/get_conf.r` and `pbdMPI/R/get_lib.r` are used in `pbdMPI/configure.ac` or `pbdMPI/configure` to determine an appropriate linking flag `PROF_LDFLAGS` based on preset flags in `pbdPROF/etc/Makeconf`.

If the internal library is used in **pbdPROF**, then the path to the `pbdPROF/lib/libfpmpi.a` is set in the flag `PKG_LIBS` of `pbdMPI/src/Makevars.in`. If the external library is used in **pbdPROF**, then the linking arguments `-L/path_to_fpmpi/lib -lfpmi` is set in the flag `PKG_LIBS` of `pbdMPI/src/Makevars.in`. Therefore, the **pbdMPI** can be intercepted by the **fpmpi** library when MPI function calls are evoked.

WCC: I am not sure I need to reinstall **pbdSLAP** or **pbdNCDF4**. I suspect only **pbdMPI** is good enough, but how **fpmpi** instrument or intercept the MPI calls???

Reinstall for **pbdMPI** has no doubt to me. However, for 100% sure, we need to run a simple example twice based on **pbdBASE** demo to see if the outputs are the same for both of reinstall **pbdSLAP** (with `PROF_LDFLAGS`) and no reinstall **pbdSLAP** (without `PROF_LDFLAGS`).

2.2 mpiP

2.3 Test Script

Below we provide sample scripts to test that the installation of **pbdPROF** was successful. For **pbdMPI**, use:

Test script for pbdMPI

```
library(pbdMPI)
init()

set.seed(comm.rank())
x <- allreduce(rnorm(100))

finalize()
```

and for **Rmpi**, use:

Test script for pbdMPI

```
library(Rmpi)

# ...
```

3 FAQ

4 References

- Chen WC, Ostrouchov G, Schmidt D, Patel P, Yu H (2012a). “pbdMPI: Programming with Big Data – Interface to MPI.” R Package, URL <http://cran.r-project.org/package=pbdMPI>.
- Chen WC, Ostrouchov G, Schmidt D, Patel P, Yu H (2012b). *A Quick Guide for the pbdMPI package*. R Vignette, URL <http://cran.r-project.org/package=pbdMPI>.
- Sehrawat G, Chen W-C Schmidt D, Patel P, Ostrouchov G (2013). “pbdPROF: Programming with Big Data – MPI Profiling Tools.” R Package, URL <http://cran.r-project.org/package=pbdPROF>.
- Yu H (2010). “Rmpi: Interface (Wrapper) to MPI (Message-Passing Interface).” R Package (v:0.5-9), URL <http://cran.r-project.org/package=Rmpi>.