

A) Original Design

Model for μ_j and μ_i and μ :
{Phenotype ~ Gen. * Experimental Env.}

μ_i	Gen.	Native Env.	μ_j
---------	------	-------------	---------

0.68	G_1	E_1	-0.68
0.68	G_2	E_1	-0.68
0.68	G_3	E_1	-0.68
0.68	G_4	E_1	-0.68
-0.68	G_5	E_2	0.68
-0.68	G_6	E_2	0.68
-0.68	G_7	E_2	0.68
-0.68	G_8	E_2	0.68
$\mu = 0.00$			

B) Unbalanced Design

Model for μ_j and μ_i and μ :
{Phenotype ~ Gen. * Experimental Env.}

μ_i	Gen.	Native Env.	μ_j
---------	------	-------------	---------

0.68	G_1	E_1	-0.98
-0.68	G_5	E_2	0.27
-0.68	G_6	E_2	0.27
-0.68	G_7	E_2	0.27
-0.68	G_8	E_2	0.27
$\mu = -0.21$			

C) Unbalanced Design using correction


Model for μ_j and μ :
{Phenotype ~ Group * Experimental Env.}
Model for μ_i :
{Phenotype ~ Gen. * Experimental Env.}

μ_i	Gen.	Native Env.	μ_j	Group
---------	------	-------------	---------	-------

0.68	G_1	E_1	-0.68	A
-0.68	G_5	E_2	0.68	B
-0.68	G_6	E_2	0.68	B
-0.68	G_7	E_2	0.68	B
-0.68	G_8	E_2	0.68	B
$\mu = 0.00$				


Incompatible Designs

A)




Compatible Designs


B)




C)




D)





A) Data collection:



B) Compatible Experimental design:



Example reaction norms compatible with analysis:



Example reaction norms incompatible with analysis:

