




Menu ▾

Log in



HTML

CSS

**Build a personal website fast**

Try free


Aprendizado de Máquina - Regressão Polinomial

[< Anterior](#)[Próximo >](#)

Regressão Polinomial

Se seus pontos de dados claramente não se encaixam em uma regressão linear (uma linha reta passando por todos os pontos de dados), pode ser ideal para uma regressão polinomial.

A regressão polinomial, como a regressão linear, usa a relação entre as variáveis x e y para encontrar a melhor maneira de traçar uma linha através dos pontos de dados.



Como funciona?

Python has methods for finding a relationship between data-points and to draw a line of polynomial regression. We will show you how to use these methods instead of going through the mathematic formula.

In the example below, we have registered 18 cars as they were passing a certain tollbooth.

We have registered the car's speed, and the time of day (hour) the passing occurred.

The x-axis represents the hours of the day and the y-axis represents the speed:

Example


Start by drawing a scatter plot:

```
import matplotlib.pyplot as plt

x = [1,2,3,5,6,7,8,9,10,12,13,14,15,16,18,19,21,22]
y = [100,90,80,60,60,55,60,65,70,70,75,76,78,79,90,99,99,100]
```

```
plt.scatter(x, y)
plt.show()
```

Result:



Run example »

Example

Import `numpy` and `matplotlib` then draw the line of Polynomial Regression:

```
import numpy
import matplotlib.pyplot as plt


x = [1,2,3,5,6,7,8,9,10,12,13,14,15,16,18,19,21,22]
y = [100,90,80,60,60,55,60,65,70,70,75,76,78,79,90,99,99,100]

mymodel = numpy.poly1d(numpy.polyfit(x, y, 3))

myline = numpy.linspace(1, 22, 100)
```

```
plt.scatter(x, y)
plt.plot(myline, mymodel(myline))
plt.show()
```

Result:

[Run example »](#)

Example Explained

Import the modules you need.

You can learn about the NumPy module in our [NumPy Tutorial](#).

You can learn about the SciPy module in our [SciPy Tutorial](#).

```
import numpy
import matplotlib.pyplot as plt
```

Create the arrays that represent the values of the x and y axis:

```
x = [1,2,3,5,6,7,8,9,10,12,13,14,15,16,18,19,21,22]  
y = [100,90,80,60,60,55,60,65,70,70,75,76,78,79,90,99,99,100]
```

NumPy has a method that lets us make a polynomial model:

```
mymodel = numpy.poly1d(numpy.polyfit(x, y, 3))
```

Then specify how the line will display, we start at position 1, and end at position 22:

```
myline = numpy.linspace(1, 22, 100)
```

Draw the original scatter plot:

```
plt.scatter(x, y)
```

Draw the line of polynomial regression:

```
plt.plot(myline, mymodel(myline))
```

Display the diagram:

```
plt.show()
```

PROPAGANDA

Stand out from the crowd with a personal website

Try free for 14-days



R-Squared

It is important to know how well the relationship between the values of the x- and y-axis is, if there are no relationship the polynomial regression can not be used to predict anything.

The relationship is measured with a value called the r-squared.

The r-squared value ranges from 0 to 1, where 0 means no relationship, and 1 means 100% related.

Python and the Sklearn module will compute this value for you, all you have to do is feed it with the x and y arrays:

Example

How well does my data fit in a polynomial regression?

```
import numpy
from sklearn.metrics import r2_score

x = [1,2,3,5,6,7,8,9,10,12,13,14,15,16,18,19,21,22]
y = [100,90,80,60,60,55,60,65,70,70,75,76,78,79,90,99,99,100]

mymodel = numpy.poly1d(numpy.polyfit(x, y, 3))

print(r2_score(y, mymodel(x)))
```

Try if Yourself »

Note: The result 0.94 shows that there is a very good relationship, and we can use polynomial regression in future predictions.

Predict Future Values

Now we can use the information we have gathered to predict future values.

Example: Let us try to predict the speed of a car that passes the tollbooth at around 17 P.M:

To do so, we need the same `mymodel` array from the example above:

```
mymodel = numpy.poly1d(numpy.polyfit(x, y, 3))
```

Example

Predict the speed of a car passing at 17 P.M:

```
import numpy
from sklearn.metrics import r2_score


x = [1,2,3,5,6,7,8,9,10,12,13,14,15,16,18,19,21,22]
y = [100,90,80,60,60,55,60,65,70,70,75,76,78,79,90,99,99,100]

mymodel = numpy.poly1d(numpy.polyfit(x, y, 3))

speed = mymodel(17)
print(speed)
```

Run example »

The example predicted a speed to be 88.87, which we also could read from the diagram:



Bad Fit?

Let us create an example where polynomial regression would not be the best method to predict future values.

Example

These values for the x- and y-axis should result in a very bad fit for polynomial regression:

```
import numpy
import matplotlib.pyplot as plt

x = [89,43,36,36,95,10,66,34,38,20,26,29,48,64,6,5,36,66,72,40]
y = [21,46,3,35,67,95,53,72,58,10,26,34,90,33,38,20,56,2,47,15]

mymodel = numpy.poly1d(numpy.polyfit(x, y, 3))


myline = numpy.linspace(2, 95, 100)

plt.scatter(x, y)
```



```
plt.plot(myline, mymodel(myline))  
plt.show()
```

Result:



[Run example »](#)

And the r-squared value?

Example

Você deve obter um valor de r-quadrado muito baixo.

```
import numpy  
from sklearn.metrics import r2_score  
  
x = [89,43,36,36,95,10,66,34,38,20,26,29,48,64,6,5,36,66,72,40]  
y = [21,46,3,35,67,95,53,72,58,10,26,34,90,33,38,20,56,2,47,15]  
  
mymodel = numpy.poly1d(numpy.polyfit(x, y, 3))
```

```
print(r2_score(y, mymodel(x)))
```

[Experimente você mesmo »](#)

O resultado: 0,00995 indica um relacionamento muito ruim e nos diz que esse conjunto de dados não é adequado para regressão polinomial.

[< Anterior](#)[Próximo >](#)

PROPAGANDA




NOVO

Acabamos de lançar
vídeos do W3Schools



Explorar agora

SELETOR DE CORES



Obtenha a certificação
completando
um curso hoje!



iniciar

JOGO DE CÓDIGO





Jogar um jogo

PROPAGANDA


Personal Site Maker Made Easy

Try free for 14-days








PROPAGANDA

 Touchcast

Product Launches, Revolutionized.



PROPAGANDA



[Reportar erro](#)

[Fórum](#)

[Sobre](#)

[Comprar](#)

Principais tutoriais

[Tutorial HTML](#) [Tutorial CSS](#) [Tutorial JavaScript](#)
[How To Tutorial](#) [SQL Tutorial](#) [Python Tutorial](#)
[W3.CSS Tutorial](#) [Bootstrap Tutorial](#) [PHP Tutorial](#)
[Java Tutorial](#) [C++ Tutorial](#) [jQuery](#)

Principais referências

[HTML Reference](#) [CSS Reference](#) [JavaScript Reference](#)
[SQL Reference](#) [Python Reference](#) [W3.CSS Reference](#)
[Bootstrap Reference](#) [PHP Reference](#) [HTML Colors](#)
[Java Reference](#)

[Angular Reference](#)[jQuery Reference](#)

Top Examples

[HTML Examples](#)[CSS Examples](#)[JavaScript Examples](#)[How To Examples](#)[SQL Examples](#)[Python Examples](#)[W3.CSS Examples](#)[Bootstrap Examples](#)[PHP Examples](#)[Java Examples](#)[XML Examples](#)[jQuery Examples](#)

Web Courses

[HTML Course](#)[CSS Course](#)[JavaScript Course](#)[Front End Course](#)[SQL Course](#)[Python Course](#)[PHP Course](#)[jQuery Course](#)[Java Course](#)[C++ Course](#)[C# Course](#)[XML Course](#)[Get Certified »](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.

W3Schools is Powered by W3.CSS.

