

# AWaveFormer: Audio Wavelet Transformer Network for Generalized Audio Deepfake Detection

*Authors: Z. Wu, T. Li, H. Guan, and S. Gao*

Published in: IEEE Transactions on Audio, Speech and Language Processing (2025) | Vol: 33, Pages: 450-465  
DOI: 10.1109/TASLPRO.2025.3611229

## Abstract

Generative neural vocoders like HiFi-GAN and WaveNet generate synthetic speech with high perceptual realism. AWaveFormer presents a unified generalized deepfake detection network that decomposes raw audio into time-frequency subbands via Stationary Wavelet Transform (SWT) and models long-range temporal artifacts using a multi-head Wavelet Transformer encoder.

## Key Methodology & Architecture

Stationary Wavelet Transform (SWT), Multi-Head Self-Attention Transformer, Cross-Scale Feature Fusion, Binary Cross-Entropy classification.

## Datasets & Benchmark Environments

ASVspoof 2019 LA/DF, WaveFake, In-the-Wild Deepfake Audio Dataset.

## Performance Metrics & Graph Axis Parameters

**Reported Results:** Equal Error Rate (EER) = 0.82%, Tandem Detection Cost Function (t-DCF) = 0.024, Accuracy = 99.18%.

**Graph Parameter Mapping:** X-axis: False Alarm Rate (FAR in %, 0% to 10%); Y-axis: Miss Detection Rate (MDR in %, 0% to 10%) [ROC Curve].

## Comparative Analysis

| Advantages (Pros)                                                                    | Limitations (Cons)                                          |
|--------------------------------------------------------------------------------------|-------------------------------------------------------------|
| Exceptional cross-dataset generalization across unseen text-to-speech (TTS) engines. | Wavelet decomposition adds non-negligible memory footprint. |

## IEEE Citation Format

Z. Wu, T. Li, H. Guan, and S. Gao, "AWaveFormer: Audio Wavelet Transformer Network for Generalized Audio Deepfake Detection," *IEEE Transactions on Audio, Speech and Language Processing*, vol. 33, pp. 450-465, 2025,

doi: 10.1109/TASLPRO.2025.3611229.