

RNPM: Neural-Guided Embedding Region Selection and Error Correction for Robust Audio Multi-Watermarking

Authors: H. Chen, M. Zhang, Y. Zhao, and R. Wang

Published in: IEEE Transactions on Audio, Speech and Language Processing (2025) | Vol: 33, Pages: 1120-1134

DOI: 10.1109/TASLPRO.2025.3624964

Abstract

Audio multi-watermarking demands inserting multiple independent payload keys simultaneously without degrading audio fidelity. This study introduces RNPM, a neural-guided region selection network that identifies perceptually insensitive regions in audio Short-Time Fourier Transform (STFT) spectrograms, combined with BCH error-correcting codes.

Key Methodology & Architecture

STFT spectrogram analysis, Neural Saliency Masking network, BCH Error-Correcting Code, multi-key orthogonal embedding.

Datasets & Benchmark Environments

LJSpeech-1.1, LibriTTS, ESC-50 Environmental Audio.

Performance Metrics & Graph Axis Parameters

Reported Results: Payload Capacity = 128 bits/sec, PSNR = 44.8 dB, BER under 15 dB Gaussian noise = 0.02%.

Graph Parameter Mapping: X-axis: Watermark Capacity (bits per second, 16 to 256 bps); Y-axis: Perceptual Audio Quality (ODG Score, -4 to 0).

Comparative Analysis

Advantages (Pros)	Limitations (Cons)
Supports multiple concurrent watermark payloads with low bit error rate.	STFT framing artifact potential if frame size is misconfigured.

IEEE Citation Format

H. Chen, M. Zhang, Y. Zhao, and R. Wang, "RNPM: Neural-Guided Embedding Region Selection and Error Correction for Robust Audio Multi-Watermarking," *IEEE Transactions on Audio, Speech and Language Processing*, vol. 33, pp. 1120-1134, 2025, doi: 10.1109/TASLPRO.2025.3624964.