



## 1-3. 배포 시 특이사항

**/etc/nginx/sites-enabled/default**

```
server {  
  
    server_name {domain};  
  
    proxy_set_header Host $host;  
    proxy_set_header X-Real-IP $remote_addr;  
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;  
    proxy_set_header X-Forwarded-Proto $scheme;  
  
    include /etc/nginx/conf.d/service-url.inc;  
  
    location /api {  
        proxy_pass $service_url;  
    }  
  
    location ~ ^/(v2|v3|configuration|swagger-resources|swagger-ui|webjars|file|image|  
swagger) {  
        proxy_pass $service_url;  
    }  
  
    include /etc/nginx/conf.d/react-mobile-service-url.inc;  
  
    location /mobile {  
        proxy_pass $react_mobile_service_url;  
        proxy_http_version 1.1;  
        proxy_set_header Upgrade $http_upgrade;  
        proxy_set_header Connection "Upgrade";  
        proxy_set_header Host $host;  
        proxy_cache_bypass $http_upgrade;  
  
        client_max_body_size 100M;  
        proxy_read_timeout 3600s;  
        proxy_send_timeout 3600s;  
        proxy_connect_timeout 3600s;  
        keepalive_timeout 3600s;  
    }  
  
    location /ws {  
        proxy_pass $service_url;  
    }  
}
```

```

        proxy_http_version 1.1;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection "Upgrade";
        proxy_set_header Host $host;
        proxy_cache_bypass $http_upgrade;

        client_max_body_size 100M;
        proxy_read_timeout 3600s;
        proxy_send_timeout 3600s;
        proxy_connect_timeout 3600s;
        keepalive_timeout 3600s;
    }

    location ~ ^/mobile/(static|favicon.ico|logo192.png|manifest.json|assets|service-worker.js) {
        rewrite ^/mobile/(.*)$ /$1 break;
        proxy_pass $react_mobile_service_url;
    }

    include /etc/nginx/conf.d/react-website-service-url.inc;

    location /website {
        proxy_pass $react_website_service_url;
    }

    location ~ ^/website/(static|favicon.ico|logo192.png|manifest.json|assets) {
        rewrite ^/website/(.*)$ /$1 break;
        proxy_pass $react_website_service_url;
    }

    include /etc/nginx/conf.d/react-customersite-service-url.inc;

    location /customersite {
        proxy_pass $react_customersite_service_url;
    }

    location ~ ^/customersite/(static|favicon.ico|logo192.png|manifest.json|assets) {
        rewrite ^/customersite/(.*)$ /$1 break;
        proxy_pass $react_customersite_service_url;
    }

    listen [::]:443 ssl ipv6only=on; # managed by Certbot
    listen 443 ssl; # managed by Certbot
    ssl_certificate /etc/letsencrypt/live/j9e203.p.ssafy.io/fullchain.pem; # managed by Certbot
    ssl_certificate_key /etc/letsencrypt/live/j9e203.p.ssafy.io/privkey.pem; # managed by Certbot
    include /etc/letsencrypt/options-ssl-nginx.conf; # managed by Certbot
    ssl_dhparam /etc/letsencrypt/ssl-dhparams.pem; # managed by Certbot
}

```

```
server {
    if ($host = {domain}) {
        return 301 https://$host$request_uri;
    } # managed by Certbot

    listen 80 default_server;
    listen [::]:80 default_server;

    server_name j9e203.p.ssafy.io;
    return 404; # managed by Certbot

}
```

## react-customersite-service-url.inc

```
set $react_customersite_service_url http://127.0.0.1:3005;
```

## react-website-service-url.inc

```
set $react_website_service_url http://127.0.0.1:3003;
```

## react-mobile-service-url.inc

```
set $react_mobile_service_url http://127.0.0.1:3001;
```

## service-url.inc

```
set $service_url http://127.0.0.1:8081;
```