Newton's Law of Cooling

$$-\frac{dT}{dt} = K(T - T_s)$$

At $t=0$

$T_0 > T_s$

T_s

T_0

$\longrightarrow$

At $t=t$

T_s

T

$$-\int_{T_0}^{T} \frac{dT}{T - T_s} = K \int_0^t dt$$

$$-\ln[T - T_s]_{T_0}^{T} = Kt$$

$$\ln\left(\frac{T - T_s}{T_0 - T_s}\right) = -Kt$$

$$T - T_s = (T_0 - T_s)e^{-Kt}$$

$$\boxed{T = T_s + (T_0 - T_s)e^{-Kt}}$$

$\underline{T = T_s}$ when $t \to \infty$.

T

T_0

T_s

t

Avg form of Newton's Law of Colling

T_s

T_i T_f

$t = 0$ $t = t$

$$-\frac{dT}{dt} = K(T - T_s)$$

$$T = \left(\frac{T_i + T_f}{2}\right)$$

$$-\frac{\Delta T}{t} = K\left(\frac{T_i + T_f}{2} - T_s\right)$$

$dT \to \Delta T$
$dt \to t$

$$\frac{T_i - T_f}{t} = K\left(\frac{T_i + T_f}{2} - T_s\right)$$

$$\frac{T_i - T_f}{t} = K\left(\frac{T_i + T_f}{2} - T_s\right)$$

$\downarrow$

Avg. Method.

\# $T_s = 16C$

$\boxed{4\dot{0}C} \longrightarrow \boxed{36\,C} \longrightarrow \boxed{32\,C}$

$t = 5\,min$ $t = ??$

M-1

Integration Method.., At $t=t$, body tempbe T

$$-\frac{dT}{dt} = K(T - T_s)$$

$$-\int_{40}^{36} \frac{dT}{T - T_s} = K \int_{0}^{5} dt \longrightarrow$$

$??$

$$T_S = 16°C.$$

$$-\int_{40}^{36} \frac{dT}{T-T_s} = K \int_0^5 dt \quad \rightarrow$$

$$-\ln[T-T_s]_{40}^{36} = 5K$$

$$-\ln\left[\frac{20}{24}\right] = 5K$$

$$-\ln\left(\frac{5}{6}\right) = 5K$$

$$K = \frac{1}{5}\ln\left(\frac{6}{5}\right) \checkmark$$

$$36°C \xrightarrow{\ t=??\ } 32°C$$

$$-\int_{36}^{32} \frac{dT}{T-T_s} = \boxed{K}\int_0^t dt$$

$$\Downarrow$$

$$t = ?? \quad \checkmark$$

M-2

Avg. Method.

$$dT \longrightarrow \frac{T_i - T_f}{t} = K\left[\left(\frac{T_i + T_f}{2}\right) - T_s\right]$$

dt

$$\left(\frac{40 - 36}{5}\right) = K\left[\left(\frac{40 + 36}{2}\right) - 16\right]$$

$$K = \frac{0.8}{22} \text{ min}^{-1}$$

$$K = \frac{8}{220} = \frac{2}{55} \text{ min}^{-1}$$

$t = 5\text{min}$ $t = ?$

$40c \longrightarrow 36c \longrightarrow 32c$

$$\frac{36 - 32}{t} = \left(\frac{2}{55}\right)\left(\frac{36 + 32}{2} - 16\right)$$

$t = ??$ ✓

$t = 6.1 \text{ min}$ ✓

THERMODYNAMICS

• System & Surrounding

$\downarrow$

$\left(\begin{array}{c} \text{The part under} \\ \text{Observation} \end{array}\right)$

$\downarrow$

$\left(\begin{array}{c} \text{Other than System} \\ \text{is Surrounding} \end{array}\right)$

$\rightarrow \left(\text{Cylinder + piston} \right)$

$\downarrow$

System

THERMODYNAMICS

☆ Thermodynamic Variables

↳ By the help of which we can defined state of any process

⇒ $P, \underline{V}, T, →$ Three major thermodynamic variables.
$(\Delta U, \overline{\Delta H})$

⇒ Thermodynamic variables are of two type ⟶ ⌈→ State function
⌊→ Path function

⇒ Variables which only depends on initial & final positions are called state function. Ex:- ΔU,

⇒ Variables which depends on the path. Ex → ΔW

THERMODYNAMICS

♔: Reversible process

- Process occur very slowly

- In Reversible process System is always in equilibrium with Surrounding.

- In Reversible process we can again reachive the thermodynamic Variables. P

$A \rightarrow B$
$A \leftarrow B$ $\rightarrow$ $P_A, V_A T_A \rightarrow$ doesn't Change.

A
$P_A, V_A T_A$
B

V

THERMODYNAMICS

Internal Energy & change in internal energy

[Internal Energy of gas molecules is the sum of all the
energy possess by gas molecules in the form
of translational K-E, Rotational K-E & Vibrational energy

[Internal Energy of a gas Molecules is function of temperature].

$$\Delta U = \left(U_f - U_i \right) \rightarrow \left(\text{State function} \right)$$

THERMODYNAMICS

$$\Delta U_I = \Delta U_{II} = \Delta U_{III}$$

$$\Downarrow$$

$$\Delta U \rightarrow (\text{state function})$$

THERMODYNAMICS

Work done (For reversible process)

$$\int dW_{gas} = \int P \underset{\Downarrow}{A\,dx}$$

$dV \to$ change in Volume

$$\boxed{W_{gas} = \int P\,dv}$$

← $F_{ext\,agent}$

P →

. $P \cdot A$

← x —→ $\overrightarrow{dx}$

Sign - Convention

$$\boxed{\begin{array}{l} W_{by\,the\atop gas} \to +ve \\[2mm] W_{on\,the\atop gas} \to -ve \end{array}}$$

Since process is reversible

So, $P \cdot A = F_{ext\,agent}$

$$W_{ext\,agent} = \int F_{ext\,agent} \cdot dx\,\cos\pi$$

$$= -\int P\,A\,dx = \ominus \int P \cdot dv$$

A

dx

$Adx = dV$

THERMODYNAMICS

$$W = \int_{V_i}^{V_f} P \cdot dV$$

(*) During Expansion

$V_f > V_i \implies$ gas is doing work

or

Work done by the gas $\to$ +ve.

$\left(\begin{array}{l} \text{Area under} \\ \text{P-V Curve} \\ \text{gives work done} \end{array} \right)$

(*) During Compression

$V_f < V_i \implies$ Work done on the gas

$(-ve)$

$V_f > V_i \implies W \to +ve$

$V_f < V_i \implies W = -ve$

THERMODYNAMICS

Work done in a Cyclic process

$\Rightarrow \Delta U$ for all the cyclic process is zero.

(As its initial & final state is Same)

THERMODYNAMICS

$$W_{ABC} = +A_1$$

⇓

hook done by the gas

$$W_{CDA} = -A_2$$

⇓

work done on the gas.

$$W_{net} = (A_1 - A_2) = \left(\text{Area of Cyclic fig.}\right)$$

$W_{net} > 0 \Rightarrow$ if cycle is clockwise.

$W_{net} < 0 \Rightarrow$ if cycle is anticlockwise

THERMODYNAMICS

P

$2P_0$

P_0

B

$2b$

A

$2a$

C

D

Ellipse

V_0 $2V_0$ V

$W_{net} =$ Area of Cyclic fig.

$=$ Area of Ellipse

$= \pi a b$

$= \oplus \left(\dfrac{\pi P_0 V_0}{4} \right) \checkmark$

(Cycle is clockwise)

$2a = V_0$ $2b = P_0$

$a = \dfrac{V_0}{2}$ $b = \dfrac{P_0}{2}$

THERMODYNAMICS

Expansion.

$2P_0$

B

$\dfrac{3P_0}{2}$ A C

P_0 D

V_0 $2V_0$ V

$\dfrac{3P_0}{2}$ A B C

V_0 $2V_0$ V

$+$

$\dfrac{3P_0}{2}$ A C D A_2

V_0 $2V_0$ V

$W_{expansional}_{work}$ $= \begin{bmatrix} \text{Area of Semiellipse} \\ + \\ \text{Area of rectangle} \end{bmatrix}$

(+ve)

$= \dfrac{1}{2}\left(\dfrac{\pi P_0 V_0}{4}\right) + \left(\dfrac{3P_0 V_0}{2}\right)$

$W_{compressional}$

$= -\left[\left(\begin{array}{c}\text{Area of}\\\text{Rectangle}\end{array}\right) - \left(\begin{array}{c}\text{Area of}\\\text{Semiellipse}\end{array}\right)\right]$

$= -\left[\left(\dfrac{3P_0 V_0}{2} - \dfrac{\pi P_0 V_0}{8}\right)\right]$

THERMODYNAMICS

P

I

II

A

B

III

V

$$\Delta U_I = \Delta U_{II} = \Delta U_{III}$$

$$\Delta W_I > \Delta W_{II} > \Delta W_{III}$$

THERMODYNAMICS

BREAK

$6.30 \rightarrow 6.40$

First Law of Thermodynamics

(Based on Conservation of Energy)

$$dQ = dU + dW$$

$$\delta Q = \Delta U + \Delta W$$

Sign-Convention

$dQ \rightarrow$ +ve $\left(\begin{array}{c}\text{heat given} \\ \text{to the System}\end{array}\right)$

$dQ \rightarrow (-ve)$ (heat released)

$dW \rightarrow$ +ve (work done by the gas)

$dW \rightarrow$ -ve (Work done on the gas)

$dQ \rightarrow$ PA

THERMODYNAMICS

Process

$\longrightarrow$ Isobaric $(P = C)$

$\longrightarrow$ Isochoric $(V = C)$

$\longrightarrow$ Isothermal $(T = C)$

$\longrightarrow$ Adiabatic $(\Delta Q = 0)$

$\longrightarrow$ Polytropic

THERMODYNAMICS

Isobaric (P = C)

P axis / V axis diagram with P_0 horizontal line (P vs V)

V vs T line through origin with positive slope

$$PV = nRT$$
$$V = \left(\frac{nR}{P}\right)T$$
$$\Downarrow$$
Slope

P vs T diagram with P_0 horizontal arrow

V vs T diagram with two lines labeled ② and ①

$$P_1 > P_2$$

$\Rightarrow$ Molar heat Capacity $\rightarrow$ (Heat given to raise the temp of 1 mole of gas by 1°C)

$$C = \frac{1}{n}\left(\frac{dQ}{dt}\right)$$

$n = $ Mole

$C \rightarrow C_p$ for Constant pressure.

$$\left(C_p = \frac{1}{n}\frac{(dQ)_{at\ P=C}}{dt}\right)$$

Work done in isobaric process

$P, V_i, T_i \rightarrow P, V_f, T_f \quad (P = C)$

$$\int_0^W dW = \int_{V_i}^{V_f} P \cdot dV$$

$$W = P \int_{V_i}^{V_f} dV$$

$$\boxed{W = P(V_f - V_i)}$$

$PV_f = nRT_f$

$PV_i = nRT_i$

$$\boxed{W = nR(T_f - T_i)}$$

P

Isobaric Process

V_i V_f

V

$$W_{isobaric} = \text{Area of Rectangle}$$
$$= P(V_f - V_i) \checkmark$$

Frist law in isobaric process

$$(dQ) = dU + dW$$

$$nC_p dT = nC_v dT + Pdv$$

$$nC_p dT = nC_v dT + nRdT$$

$$C_p = \frac{1}{n}\frac{dQ}{dT} \quad \bigg| \quad Pdv = nRdT$$

$$dQ = nC_p dT \quad \bigg|$$

Note

$$dU \text{ For any process} = nC_v dT$$

$C_v \rightarrow$ Molar heat Capacity at Constant volume

$$\boxed{C_p = C_v + R}$$

ISOCHORIC PROCESS $(V = C)$

P (vertical axis) / V (horizontal axis) — vertical arrow line

V (vertical axis) / T (horizontal axis) — horizontal line with arrow

P (vertical axis) / T (horizontal axis) — straight line through origin

$\hookrightarrow$ slope $= \dfrac{nR}{V}$

$PV = nRT$

$P = \left(\dfrac{nR}{V}\right) T$

$\Updownarrow$

Constant

Molar heat Capacity at Constant volume

$$C_V = \frac{1}{n} \frac{(dQ)\,\text{at constant volume}}{dT}$$

Work done $= 0$

$V = $ Constant

$\Delta V = 0$

Frist Law

$$dQ = dU + \cancel{dW}^{\,0}$$

$$\boxed{dQ = dU}$$

$$\boxed{n C_V dT = dU}$$

$(\text{Valid for all process})$

Isothermal process $(T = C)$

Isotherm

$$\left(T_A = T_B = T_C = T_D = T_E = T \right)$$

$$PV = \boxed{nRT} \rightarrow \text{Constant}$$

$$\left(P = \frac{C}{V} \right)$$

$$xy = C \rightarrow \text{Rectangular hyperbola}$$

Higher isotherm are at higher temp. ✓

P

P_1

P_2

T_1

T_2

$\rightarrow V$

V_i

V

V_f

$\left(\dfrac{dP}{dV}\right)$

$P_1 V = nRT_1$.

$P_2 V = nRT_2$

$\dfrac{P_1}{P_2} = \dfrac{T_1}{T_2}$

$P_1 > P_2$

$\Rightarrow T_1 > T_2$

(✴) **Slope of isotherm**

$$PV = nRT$$

Differentiating both side w.r.t Volume   Constant

$$\dfrac{d}{dV}(PV) = \dfrac{d}{dV}(nRT)$$

$$P\dfrac{d(V)}{dV} + V\dfrac{dP}{dV} = 0$$

$$P = -V\dfrac{dP}{dV}$$

$$\dfrac{dP}{dV} = \left(-\dfrac{P}{V}\right)$$

⇓

Slope of isotherm

B is Isothermal process

$$B = -\frac{dP}{\left(\frac{dV}{V}\right)}$$

$$\boxed{B_{isothermal} = P}$$

$$B = \left(-\frac{dP}{dV}\right) \times V$$

$$B = \frac{P}{V} \times V$$

Molar heat Capacity in isothermal process

$$C = \frac{1}{n}\left(\frac{dQ}{dT}\right)$$

for isothermal $\quad dT \rightarrow 0$

$$C \rightarrow \infty$$
$$\text{isothermal}$$

A very large reservior have ∞ heat Capacity.

Work-done in isothermal process

$$PV = nRT$$

$$\underline{P} = \left(\frac{nRT}{V}\right)$$

$$P_i V_i T \longrightarrow P_f, V_f, T$$

$$P_i V_i = nRT$$

$$P_f V_f = nRT$$

$$P_i V_i = P_f V_f$$

$$\frac{P_i}{P_f} = \frac{V_f}{V_i}$$

$$W = \int_{V_i}^{V_f} P \cdot dV = nRT \int_{V_i}^{V_f} \frac{dV}{V}$$

&&

$$W = nRT \ln\left(\frac{V_f}{V_i}\right)$$

$$W = nRT \ln\left(\frac{P_i}{P_f}\right)$$

$$\Delta U_{isothermal} = 0$$

For any process

$$\Delta U = n C_v \underset{\underset{0}{\downarrow}}{\Delta T}$$
$$\;\;\;\;\underset{0}{\downarrow}$$

First Law in isothermal process

$$dQ = \overset{0}{\cancel{dU}} + dW$$

$$\boxed{dQ = dW}$$