

Esc

normal
mode

~	toggle case	!	external filter	@.	play macro	#	prev ident	\$	eol	%	goto match	^	"soft" bol	&	repeat :s	*	next ident	(begin sentence)	end sentence	_	"soft" bol down	+	next line
\.	goto mark	1	2	2		3		4		5		6		7		8		9		0	"hard" bol	-	prev line	=	auto format 3
Q	ex mode	W	next WORD	E	end WORD	R	replace mode	T.	back 'till	Y	yank line	U	undo line	I	insert at bol	O	open above	P	paste before	{	begin parag	}	end parag		
q.	record macro	w	next word	e	end word	r.	replace char	t.	'till	y	yank 1,3	u	undo	i	insert mode	o	open below	p	paste after 1	[.	misc].	misc		
A	append at eol	S	subst line	D	delete to eol	F.	"back" find char	G.	eof/ goto line	H	screen top	J	join lines	K	help	L	screen bottom	:	ex cmd line	".	reg. spec 1		bol/ goto col		
a	append	s	subst char	d	delete 1,3	f.	find char	g.	extra cmds 6	h		j		k		l	➡	;	repeat t/T/f/F	'.	goto mk. bol	\.	default leader		
Z.	quit 4	X	back-space	C	change to eol	V	visual lines	B	back WORD	N	prev (find)	M	screen mid'l	<	un-indent 3	>	indent 3	?.	find (rev.)						
Z.	extra cmds 5	X	delete char	C	change 1,3	v	visual mode	b	back word	n	next (find)	m.	set mark	,	reverse t/T/f/F	.	repeat cmd	/.	find						

motion	moves the cursor, or defines the range for an operator
command	direct action command, if red , it enters insert mode
operator	requires a motion afterwards, operates between cursor & destination
extra	special functions, requires extra input
q•	commands with a dot need a char argument afterwards

bol = beginning of line, eol = end of line,	
mk = mark, yank = copy, char = character	
parag = paragraph, cmd = command	

words: quux (foo, bar, baz) ;

WORDS: q u u x (f o o , b a r , b a z) ;

:w	(save), :q	(quit), :q!	(quit w/o saving)
:e f	(open file f)		
:%s/x/y/g	(replace 'x' by 'y' filewide),		
:h	(help in neovim), :new	(new file in neovim)	

CTRL-R: redo				
CTRL-F/-B: page up/down,				
CTRL-E/-Y: scroll line up/down,				
CTRL-V: block-visual mode				

[illegible]

- (1) use "x before a yank/paste/del command to use that register ('clipboard') (x=a..z,*) (e.g.: "ay\$ to copy rest of line to register 'a')
- (2) type in a number before any action to repeat it that number of times (e.g.: 2p, d2w, 5i, d4j)
- (3) duplicate operator to act on current line (dd = delete line, yy = yank line, >> = indent line)
- (4) ZZ to save & quit, ZQ to quit w/o saving
- (5) zt: scroll cursor to top,
zb: bottom, zz:center
- (6) gg: top of file,
gf: open file under cursor