# EXPERIMENT - 6

## Snort IDS/IPS Using TryHackMe

**Step 1: Login to Platform**

Open TryHackMe in a browser and log in using your account.

**Step 2: Open Snort Room**

Search for a Snort-related room and join it to begin the experiment.

**Step 3: Start AttackBox**

Launch the AttackBox, which provides a ready-to-use Linux environment for performing the tasks.

**Step 4: Verify Snort Installation**

Open the terminal and confirm that Snort is installed and ready to use.

**Step 5: Run Snort in IDS Mode**

Start Snort in detection mode so that it monitors network traffic and generates alerts for suspicious activity.

**Step 6: Detect Network Threats**

Perform the tasks given in the room and observe how Snort identifies and reports potential threats in real time.

**Step 7: Configure IPS Mode**

Enable prevention mode to allow Snort to block malicious traffic based on predefined rules.

**Step 8: Analyze Alerts**

Review the alerts generated by Snort and identify different types of network attacks.

| Parameter | Description |
|---|---|
| **-V / --version** | This parameter provides information about your instance version. |
| **-c** | Identifying the configuration file |
| **-T** | Snort's self-test parameter allows you to test your setup with this parameter. |
| **- q** | Quiet mode prevents Snort from displaying the default banner and initial information about your setup. |

That was easy; let's move on to the next task and continue exploring snort modes.

Answer the questions below

Run the Snort instance and check the build number.

149 ✓ Correct Answer

Test the current instance with "/etc/snort/snort.conf" file and check how many rules are loaded with the current build.

4151 ✓ Correct Answer

Test the current instance with "/etc/snort/snortv2.conf" file and check how many rules are loaded with the current build.

1 ✓ Correct Answer




Answer the questions below

Navigate to the Task-Exercises folder and run the command "./.easy.sh" and write the output

Too Easy! ✓ Correct Answer

```
WARNING: No preprocessors configured for policy 0.
12/01-21:07:57.624205 216.58.214.142 -> 192.168.175.129
ICMP TTL:128 TOS:0x0 ID:63394 IpLen:20 DgmLen:84
Type:0  Code:0  ID:15  Seq:1  ECHO REPLY
0x0000: 00 0C 29 A5 B7 A2 00 50 56 E1 9B 9D 08 00 45 00  ..)....PV.....E.
0x0010: 00 54 F7 A2 00 00 80 01 24 13 D8 3A D6 8E C0 A8  .T......$..:....
0x0020: AF 81 00 00 BE B6 00 0F 00 01 2D E4 A7 61 00 00  ..........-..a..
0x0030: 00 00 A4 20 09 00 00 00 00 00 10 11 12 13 14 15  ... ............
0x0040: 16 17 18 19 1A 1B 1C 1D 1E 1F 20 21 22 23 24 25  .......... !"#$%
0x0050: 26 27 28 29 2A 2B 2C 2D 2E 2F 30 31 32 33 34 35  &'()*+,-./012345
0x0060: 36 37                                            67

=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+=+
```

Note that you can use the parameters both in combined and separated form as follows;

- snort -v
- snort -vd
- snort -de
- snort -v -d -e
- snort -X

Make sure you understand and practice each parameter with different types of traffic and discover your favourite combination.

## Answer the questions below

You can practice the parameter combinations by using the traffic-generator script.

No answer needed

✓ Correct Answer







## Result

Snort was successfully used as an IDS/IPS to detect and prevent network threats, demonstrating real-time network security monitoring in a controlled environment.