

Name (Arabic): \_\_\_\_\_

Class: \_\_\_\_\_



FCIS – Ain Shams University  
Subject: CSW150– Structured  
Programming

Exam: (Midterm) 21/3/2018

Year: ( Spring term) 1<sup>st</sup>Year undergraduate

15
----



Instructor: Dr.Sally S.Ismail  
Offering Dept.: Bioinformatics Program  
Academic year: 2017-2018  
Duration: 45 mints


**Answer the following 3 questions:****(Total marks: 15)**

QUESTION (1) True/False. An <u>explanation</u> is required for false answers	(3 points)	5-mints	Grade
<b>(a)</b> The statement <pre>struct my_struct {     int num1, num2;     char signs[3];     double result; };</pre> allocates 20 bytes in memory.	<b>(F)</b>		0.5
<b>Answer:</b> Struct definition allocates <b>ZERO bytes</b> in memory			0.5
<b>(b)</b> It is the compiler's task to create the executable file for your program.	<b>(F)</b>		0.5
<b>Answer:</b> → It is the compiler's task to create the <b>object code</b> for your program. or → It is the compiler's task to <b>detect syntax errors</b> for your program.			0.5
<b>(c)</b> The output of the following code scrap is 3. <pre>int my2Darr[][3]= {{1,2,3},{4,5,6}}; cout&lt;&lt;my2Darr[0][2];</pre>	<b>(T)</b>		1
<b>Answer: NO EXPLANATION IS REQUIRED HERE</b>			
QUESTION (2) Code Design	(4 points)	10-mints	
What is the output from the following Pseudocode fragment?			
<pre>REPEAT (numOfElements - 1) times     SET the first unsorted element as the m     FOR each of the unsorted elements         IF element &gt; currentM             THEN set element as new m         ENDIF     ENDFOR</pre>	<b>Input: 4 2 1 5 7 9</b>  <b>Output: 9 7 5 4 2 1</b>  <b>Partial sorting descendingly → (2)</b> <b>Ascending sorting → (2)</b>		4
QUESTION (3) Code Development	(8 points)	20-mints	

Name (Arabic): \_\_\_\_\_

Class: \_\_\_\_\_

Develop an "Automatic Teller Machine (ATM) Service" program that **reads** from the user **bank account information (account number, initial amount, deposit and withdrawal)** and displays the final **amount of money in the balance**. Your Program should define a **struct** for the client information and should repeat the process for many clients until the user asks it to quit using **sentinel value 'n'**.

**Sample Run:**


```

C:\Windows\system32\cmd.exe
Welcome To ATM Banking Service
Please enter your account number, initial amount, deposited amount and the withdrawal amount
:
100 1000 500 200
your balance now is : 1300$
would you like to repeat (y/n) ? y
Please enter your account number, initial amount, deposited amount and the withdrawal amount
:
200 2000 750 150
your balance now is : 2600$
would you like to repeat (y/n) ? n
Thank you for trusting us.
Press any key to continue . . .

```

**Answer:**

Main source file

```

#include <iostream>
using namespace std;
struct ATM
{
    int AccNumber;
    double Initamount;
    double withdrawal;
    double deposit;
    double amount;
}client;
void main ()
{
    char choice;
    cout<<"Welcome To ATM Banking Service"<<endl;
    do
    {
        cout<<"Please enter your account number,
        initial amount, deposited amount and the
        withdrawal amount:"<<endl;
        cin>>client.AccNumber>>client.Initamount
        >>client.deposit>>client.withdrawal;
        client.amount=client.Initamount+client.de
        posit-client.withdrawal;
        cout<<"your balance now is :
        "<<client.amount<<"$"<<endl;
        cout<<"would you like to repeat (y/n) ?
        ";
        cin>>choice;
    }while(choice=='y');
    cout<<"Thank you for trusting us."<<endl;
}

```

- Program outline (#,main..etc) →(1)
- User Friendly output msgs (at least one)→ (1)
- Struct definition→(1)
- Variable declaration + professional names → (1)
- Sentinel value loop →(1)
- Input client info →(1)
- Balance equation →(1)
- Output →(1)

8

*With My Best Regards,*  
*Sally S. Smail*