



## Chapter 6: amVK\_ColorSpace.hh , amVK\_Surface , amVK\_Presenter , Renaming Things in amVK

### 1. amVK\_ColorSpace.hh

```
/**
 * ex. 1   amVK_IF::RGBA_8bpc_UNORM
 */
namespace amVK_ImageFormat {
    // 8bpc = 8-bits per channel
    inline constexpr VkFormat RGBA_8bpc_UNORM      = VK_FORMAT_R8G8B8A8_UNORM;    // 37
    inline constexpr VkFormat RGBA_8bpc_SNORM      = VK_FORMAT_R8G8B8A8_SNORM;    // 38
    inline constexpr VkFormat RGBA_8bpc_USCALED    = VK_FORMAT_R8G8B8A8_USCALED;  // 39
    inline constexpr VkFormat RGBA_8bpc_SSCALED    = VK_FORMAT_R8G8B8A8_SSCALED;  // 40
    inline constexpr VkFormat RGBA_8bpc_UINT       = VK_FORMAT_R8G8B8A8_UINT;     // 41
    inline constexpr VkFormat RGBA_8bpc_SINT       = VK_FORMAT_R8G8B8A8_SINT;     // 42
    inline constexpr VkFormat RGBA_8bpc_SRGB       = VK_FORMAT_R8G8B8A8_SRGB;     // 43

    // Common Depth/Stencil Formats
    inline constexpr VkFormat D32_SFLOAT           = VK_FORMAT_D32_SFLOAT;
    inline constexpr VkFormat D24_UNORM_S8_UINT   = VK_FORMAT_D24_UNORM_S8_UINT;
}
#define amVK_IF amVK_ImageFormat
#define amVK_PF amVK_ImageFormat
#define amVK_PixelFormat amVK_ImageFormat
```

- Entire Code:- [amVK\\_ColorSpace.hh](#)

### 2. amVK\_Surface

```
/**
 * VULKAN-EXT:- `VK_KHR_surface`
 *      IMPL:- `amVK_1D_SurfaceInfos`
 */
class amVK_Surface {
public:
    VkSurfaceKHR S = nullptr;    // Set in CONSTRUCTOR
    amVK_Presenter *PR = nullptr; // Set in CONSTRUCTOR

    amVK_Surface(void) {}
    amVK_Surface(VkSurfaceKHR pS);

    REY_Array<REY_Array<VkSurfaceFormatKHR>> amVK_2D_GPUs_ImageFMTs;
    REY_Array<VkSurfaceCapabilitiesKHR> amVK_1D_GPUs_SurfCAP;
```

```

    bool called_GetPhysicalDeviceSurfaceFormatsKHR = false;
    bool called_GetPhysicalDeviceSurfaceCapabilitiesKHR = false;
    void      GetPhysicalDeviceSurfaceInfo(void);
    void      GetPhysicalDeviceSurfaceCapabilitiesKHR(void);
};

```

- Entire Code:- [4.guide.chapter6.3.Surface.hh](#)

### 3. amVK\_Presenter

```

class amVK_Presenter {
public:
    amVK_Surface *S = nullptr;
    amVK_SwapChain *SC = nullptr;
    amVK_RenderPass *RP = nullptr;
    // SC.VkDevice = RP.VkDevice
    amVK_Device *D = nullptr;
    VkPhysicalDevice GPU = nullptr;
    // amVK_Device.m_PD = this->GPU;
    amVK_GPU_Index GPU_Index = 0;

public:
    void bind_Device(amVK_Device *D);
    amVK_Presenter (amVK_Surface* pS) {this->S = pS;}

public:
    amVK_SwapChain* create_SwapChain(void);
    amVK_RenderPass* create_RenderPass(void);
    // Defined currently inside amVK_SwapChain.cpp

    void refresh_SurfCaps(void) {
this->S->GetPhysicalDeviceSurfaceCapabilitiesKHR(); }
    VkSurfaceCapabilitiesKHR* fetched_SurfCaps(void) {
        return &( this->S->amVK_1D_GPUs_SurfCAP[this->GPU_Index] );
    }
};

```

- Entire Code:- [4.guide.chapter6.3.Surface.hh](#)

## 4. amVK Naming Conventions 😊

### 1. Calling Vulkan Library Functions:-

```
bool called_GetPhysicalDeviceSurfaceFormatsKHR = false;
bool called_GetPhysicalDeviceSurfaceCapabilitiesKHR = false;
void      GetPhysicalDeviceSurfaceInfo(void);
void      GetPhysicalDeviceSurfaceCapabilitiesKHR(void);
```

### 2. vkCreateZZZ() wrappers

```
amVK_SwapChain {
    void CreateSwapChain(void) {
        VkResult return_code = vkCreateSwapchainKHR(this->D->m_device, &CI, nullptr, &this->SC);
        amVK_return_code_log( "vkCreateSwapchainKHR()" );    // above variable "return_code" can
        not be named smth else
    }
}
```

### 3. amVK\_Object /Instance-Creation

```
amVK_SwapChain* amVK_Presenter::create_SwapChain(void);
```

### 4. amVK\_Object::Functions()

```
amVK_SwapChain*   create_SwapChain(void);           // Creates amVK_Object
amVK_RenderPass*  create_RenderPass(void);          // Creates amVK_Object
void              refresh_SurfCaps(void);           // SurfCapabilities changes if Window is
Resized
VkSurfaceCapabilitiesKHR* fetched_SurfCaps(void);    // Returns the REFRESHED/FETCHED element

void              amVK_SwapChain::sync_SurfCaps(void); /** Refreshes & Syncs `SurfaceCapabilites` */
void              amVK_SwapChain::konf_Images(
    VkFormat IF,
    VkColorSpaceKHR CS,
    VkImageUsageFlagBits IU,
    bool autoFallback = true
)
void              amVK_SwapChain::konf_Compositing(
    VkPresentModeKHR PM,
    amVK_CompositeClipping CC,
    VkCompositeAlphaFlagBitsKHR CA
);
void              amVK_SwapChain::konf_ImageSharingMode(VkSharingMode ISM);
VkFormat          amVK_SwapChain::active_PixelFormat(void)      {return
CI.imageFormat;}
VkColorSpaceKHR   amVK_SwapChain::active_ColorSpace (void)      {return
CI.imageColorSpace;}
```

## 5. VkObject Variables

```
class amVK_Image {
public:
    amVK_Device *D = nullptr;
    VkImage      vk_Image = nullptr;
    VkImageView  vk_ImageView = nullptr;
};

class amVK_FrameBuffer {
public:
    amVK_Presenter *PR = nullptr;      // Basically, Parent Pointer
    VkFramebuffer vk_FrameBuffer = nullptr;
};

class amVK_RenderPass {
public:
    amVK_Presenter *PR = nullptr;      // Basically, Parent Pointer
    VkRenderPass   vk_RenderPass = nullptr;
};

class amVK_Surface {
public:
    amVK_Presenter *PR = nullptr;      // Created in CONSTRUCTOR
    VkSurfaceKHR    vk_SurfaceKHR = nullptr;    // Set in CONSTRUCTOR
}
```