Instance Variable and Method

Consider the following class:

```
public class Account {
  public int points;
  public double balance;
}
```

Show the output of the following sequence of statements:

1	`public class TesterBank {`
2	`  public static void main(String[] args){`
3	`    Account acc1 = new Account();`
4	`    Account acc2 = new Account();`
5	`    acc1.points = 35;`
6	`    acc1.balance = 550.5;`
7	`    System.out.println(acc1.points);`
8	`    System.out.println(acc1.balance);`
9	`    acc2.balance = acc1.balance - 300;`
10	`    System.out.println(acc2.balance);`
11	`    acc2.points = acc1.points++;`
12	`    System.out.println(acc1.points);`
13	`    acc2 = acc1;`
14	`    System.out.println(acc2.points);`
15	`    System.out.println(acc2.balance);`
16	`    acc2.points++;`
17	`    acc2.balance += 100;`
18	`    System.out.println(acc1.points);`
19	`    System.out.println(acc1.balance);`
20	`    acc1.points = ++acc2.points;`
21	`    System.out.println(acc2.points);`
22	`    System.out.println(acc2.balance);`
23	`  }`
24	`}`

OUTPUT

```
1   public class Trace1 {
2      public int p = 3, y = 2, sum;
3      public void methodA(){
4          int x = 0, y = 0;
5          y = y + this.y;
6          x = sum + 2 + p;
7          sum = x + methodB(p, y) + this.y;
8          System.out.println(x + " " + y+ " " + sum);
9      }
10     public int methodB(int p, int n){
11         int x = 0;
12         y = this.y + (++p);
13         x = x + 2 + n;
14         sum = sum + x + y;
15         System.out.println(x + " " + y+ " " + sum);
16         return sum;
17     }
18  }
```

Driver code:

```
public class Tester1 {
  public static void main(String [] args){
    Trace1 t1 = new Trace1();
    t1.methodA();
    Trace1 t2 = new Trace1();
    t1.methodA();
    System.out.println(t2.methodB(2,3));
   }
}
```

Outputs		
x	y	Sum

Write the code in java for the **"Vehicle"** class. The tester class and the output is given below:

Tester class	Output

`public class TesterVehicle{`
`  public static void main(String [] args){`
`  Vehicle car = new Vehicle();`
`  System.out.println("Attributes of car object:");`
`  System.out.println(car.type);`
`  System.out.println(car.wheels);`
`  System.out.println(car.color);`
`  System.out.println("=========");`
`  Vehicle bike = new Vehicle();`
`  bike.type = "Motor bike";`
`  bike.wheels = 2;`
`  bike.color = "Red";`
`  System.out.println("Attributes of bike object:");`
`  System.out.println(bike.type);`
`  System.out.println(bike.wheels);`
`  System.out.println(bike.color);`
`  }`
`}`
	`Attributes of car object:`
	`Car`
	`4`
	`White`
	`=========`
	`Attributes of bike object:`
	`Motor bike`
	`2`
	`Red`

Driver Code	Output

`public class TesterCourse{`
`  public static void main(String[] args) {`
`  Course c1 = new Course();`
`  Course c2 = new Course();`
`  System.out.println("========== 1 ==========");`
`  c1.createCourse("Programming Language I", "CSE110", 3);`
`  c1.displayCourse();`
`  System.out.println("========== 2 ==========");`
`  c2.createCourse("Data Structures", "CSE220", 3);`
`  c2.displayCourse();`
`  System.out.println("========== 3 ==========");`
`  c1.updateCourse("Programming Language II", "CSE111", 3);`
`  c1.displayCourse();`
`  }`
`}`
	`========== 1 ==========`
	`Course Name: Programming Language I`
	`Course Code: CSE110`
	`Course Credit: 3`
	`========== 2 ==========`
	`Course Name: Data Structures`
	`Course Code: CSE220`
	`Course Credit: 3`
	`========== 3 ==========`
	`Course Name: Programming Language II`
	`Course Code: CSE111`
	`Course Credit: 3`

Create a **Dog** class so that the tester code generates the given output:

Driver Code	Expected Output

`public class TesterDog{`
`  public static void main (String[] args) {`
`  Dog scooby = new Dog();`
`  Dog oldie = new Dog();`
`  Dog goofy = new Dog();`
 	
`  scooby.changeName("Scooby");`
`  goofy.changeName("Goofy");`
 	
`  System.out.println("1. ==========");`
`  System.out.println(scooby.bark());`
`  System.out.println("2. ==========");`
`  System.out.println(oldie.bark());`
`  System.out.println("3. ==========");`
`  oldie.changeColor("White");`
`  System.out.println("4. ==========");`
`  System.out.println(oldie.bark());`
`  System.out.println("5. ==========");`
`  System.out.println(goofy.bark());`
`  System.out.println("6. ==========");`
`  scooby.changeColor("Brown");`
`  System.out.println("7. ==========");`
`  System.out.println(scooby.bark());`
`  System.out.println("8. ==========");`
`  goofy.changeColor("Black");`
`  }`
`}`
	`1. ==========`
	`Scooby is barking`
	`2. ==========`
	`A dog is barking`
	`3. ==========`
	`This dog is White`
	`4. ==========`
	`White dog is barking`
	`5. ==========`
	`Goofy is barking`
	`6. ==========`
	`Scooby is Brown`
	`7. ==========`
	`Scooby the Brown dog is barking`
	`8. ==========`
	`Goofy is Black`

Design the **Reader** class in such a way so that the following code provides the expected output.

Variables => name, cap, String array,

Driver Code	Expected Output

`public class Reader_tester {`
`  public static void main(String[] args){`
`  Reader r1 = new Reader();`
`  Reader r2 = new Reader();`
 	
`  r1.createReader("Albert", 2);`
`  r2.createReader("Issac", 5);`
 	
`  System.out.println("1 ==========");`
`  r1.readerInfo();`
 	
`  System.out.println("2 ==========");`
`  r2.addBook("Java");`
`  r2.addBook("Python");`
`  r2.addBook("C++");`
`  r2.readerInfo();`
 	
`  System.out.println("3 ==========");`
`  r1.addBook("C#");`
`  r1.addBook("Rust");`
`  r1.addBook("GoLang");`
 	
`  System.out.println("4 ==========");`
`  r1.increaseCapacity(5);`
`  r1.addBook("Python");`
 	
`  System.out.println("5 ==========");`
`  r1.readerInfo();`
`  }`
`}`
	`1 ==========`
	`Name: Albert`
	`Capacity: 2`
	`Books:`
	`No books added yet`
	`2 ==========`
	`Name: Issac`
	`Capacity: 5`
	`Books:`
	`Book 1: Java`
	`Book 2: Python`
	`Book 3: C++`
	`3 ==========`
	`No more space for new book`
	`4 ==========`
	`Albert's capacity increased to 5`
	`5 ==========`
	`Name: Albert`
	`Capacity: 5`
	`Books:`
	`Book 1: C#`
	`Book 2: Rust`
	`Book 3: Python`

Method and Constructor Overloading

```
1  public class A{
2   public int temp = 3, sum = 9, y = 4, x = 0;
3   public A(){
4     int sum = 7;
5     y = temp - 5;
6     sum = temp + 2;
7     this.x = sum + --temp + y;
8   }
9   public A(int y, int temp){
10    y = temp - 1 + x;
11    sum = temp + 2 - x;
12    temp -= 2;
13  }
14  public void methodA(int m, int n){
15    int x = 0;
16    y = y + methodB(x,m) + m;
17    x = this.x + 2 + ++n;
18    sum = sum + y + methodB(n);
19    System.out.println(x + " " + y+ " " + sum);
20  }
21  public int methodB(int m, int n){
22    int y = 0;
23    this.y = y + this.y + m;
24    x = this.y + 2 + temp - n;
25    sum = x + y + this.sum;
26    System.out.println(y+ " "+ temp + " " + sum);
27    return y;
28  }
29  public int methodB(int x){
30    this.x = x + this.y;
31    x -= y + 2 + temp;
32    sum = x + y + this.sum;
33    return sum;
34  }
```

35	}

Driver Code	Output		

public class Tester {
  public static void main(String args[]){
  A a1 = new A();
  A a2 = new A(-5,-7);
  a1.methodA(1, 2);
  a2.methodA(1, 4);
  }
}			

Design the **Course** class with the necessary properties so that the given output is produced for the provided driver code.

Driver Class

```
public class CourseTester{
  public static void main(String [] args){
    Course c1 = new Course("PL II", "CS11");
    System.out.println("--------1--------");
    System.out.println(c1.printDetails());
    System.out.println("--------2--------");
    c1.addContent("Overloading");
    System.out.println(c1.printDetails());
    System.out.println("--------3--------");
    c1.addContent("Encapsulation");
    c1.addContent("Static", "Polymorphism");
    System.out.println(c1.printDetails());
    System.out.println("--------4--------");
    c1.addContent("Inheritance");
    System.out.println("--------5--------");
    Course c2 = new Course("DS", "CS22");
    c2.addContent("Stack");
    c2.addContent("Recursion","Tree");
    c2.addContent("Heap","Hashing");
    System.out.println("--------6--------");
    System.out.println(c2.printDetails());
    System.out.println("--------7--------");
    Course c3 = new Course("OS");
    c3.addContent("Scheduling");
    System.out.println("--------8--------");
    c3.addContent(new String[]{"Segmentation", "Process",
"Interrupt","Concurrency","Multithreading"});
    System.out.println("--------9--------");
    System.out.println(c3.printDetails());
  }
}
```

Output

```
--------1--------
Course details:
Course Name: PL II
Course Code: CS11
Course Syllabus:
No content yet.
--------2--------
Overloading was added.
Course details:
Course Name: PL II
Course Code: CS11
Course Syllabus:
Overloading
--------3--------
Encapsulation was added.
Static was added.
Polymorphism was added.
Course details:
Course Name: PL II
Course Code: CS11
Course Syllabus:
Overloading, Encapsulation, Static,
Polymorphism
--------4--------
Cannot add more content
--------5--------
Stack was added.
Recursion was added.
Tree was added.
Heap was added.
Cannot add more content
--------6--------
Course details:
Course Name: DS
Course Code: CS22
Course Syllabus:
Stack, Recursion, Tree, Heap
--------7--------
Scheduling was added
--------8--------
Segmentation was added
Process was added
Interrupt was added
Cannot add more content
--------9--------
Course details:
Course Name: OS
Course Code: Undefined
Course Syllabus:
Scheduling, Segmentation, Process,
Interrupt
```

Driver

```java
public class ClubTester {
   public static void main(String[] args) {
       Club club1 = new Club();
       System.out.println("1================");
       System.out.println(club1.approveClub("Makers
Club",4,10000, 3));
       System.out.println("2================");
       System.out.println(club1.approveClub("Makers
Club",10,10000, 3));
       System.out.println("3================");
       club1.info();
       System.out.println("4================");
       club1.createEvent("Exhibit", 1099, 5);
       System.out.println("5================");
       club1.createEvent("Impromptu", 8700, 6);
       System.out.println("6================");
       club1.recruitMember(5);
       System.out.println("7================");
       club1.createEvent("Impromptu", 8700, 6);
       System.out.println("8================");
       club1.info();
       System.out.println("9================");
       club1.createEvent("Potluck", 1200, 3);
       System.out.println("10================");
       club1.createEvent("Potluck", 100, 3);
       System.out.println("11================");
       club1.info();
       System.out.println("12================");
       club1.createEvent("Speech", 100, 2);
       System.out.println("13================");
       club1.endEvent("Exhibit");
       System.out.println("14================");
       club1.info();
       System.out.println("15================");
       club1.createEvent("Speech",100, 2);
   }
}
```

Output

```
1================
A club must have at least 5 members
2================
New club, Makers Club, created with
10 members.
3================
Name of the club: Makers Club
Non-working Members: 10
Current Budget: 10000.0
No events yet.
4================
New event, "Exhibit"has started!
5 out of 10 available members are
now working.
5================
Need 1 more member(s) to arrange.
6================
New members recruited
Total non-working members now are
10
7================
New event, "Impromptu"has started!
6 out of 10 available members are
now working.
8================
Name of the club: Makers Club
Non-working Members: 4
Current Budget: 201.0
Current events:
Exhibit
Impromptu
9================
Not enough budget.
10================
New event, "Potluck"has started!
3 out of 4 available members are
now working.
11================
Name of the club: Makers Club
Non-working Members: 1
Current Budget: 101.0
Current events:
Exhibit
Impromptu
Potluck
12================
Need 1 more member(s) to arrange.
13================
Exhibit has ended!
6 members are free now.
14================
Name of the club: Makers Club
```

	Non-working Members: 6 Current Budget: 101.0 Current events: Impromptu Potluck 15========== New event, "Speech"has started! 2 out of 6 available members are now working.

Solution:

```java
public class Club {
 public String name;
 public int member;
 public double budget;
 public int events;

 public String eventName[];
 public int eventMem[];

 public String approveClub(String n, int m, double budget, int cap) {
   if (m >= 5) {
     name = n;
     member = m;
     this.budget = budget;
     events = cap;
     eventName = new String[cap];
     eventMem = new int[cap];
     return "New club, " + name + ", created with " + member + " members.";
   } else {
     return "A club must have at least 5 members";
   }
 }

 public void info() {
   System.out.println("Name of the club: " + name);
   System.out.println("Non-working Members: " + member);
   System.out.println("Current Budget: " + budget);
   if (events == eventName.length)
     System.out.println("No events yet.");
   else {
     System.out.println("Current events: ");
     for (int i = 0; i < eventName.length; i++) {
       if (eventName[i] != null) {
         System.out.println(eventName[i]);
       }
     }
   }
 }

 public void createEvent(String ename, double ebud, int emem) {
   if (budget < ebud) {
     System.out.println("Not enough budget.");
```

```java
    } else if (member < emem) {
      System.out.println("Need " + (emem - member) + " more member(s) to arrange.");
    } else if (events == 0) {
      System.out.println("Only " + eventName.length + " events can be created.");
    } else {
      System.out.println("New event, \"" + ename + "\"has started!\n" + emem + " out of " + member
+ " available members are now working.");
      for (int i = 0; i < eventName.length; i++) {
        if (eventName[i] == null) {
          eventName[i] = ename;
          eventMem[i] = emem;
          member = member - emem;
          budget = budget - ebud;
          events--;
          break;
        }
      }
    }
  }

  public void recruitMember(int m) {
    member += m;
    System.out.println("New members recruited\n" +
            "Total non-working members now are " + member);
  }

  public void endEvent(String ename) {
    for (int i = 0; i < eventName.length; i++) {
      if (eventName[i] != null && eventName[i].equals(ename)) {
        eventName[i] = null;
        member = member + eventMem[i];
        eventMem[i] = 0;
        events++;
        break;
      }
    }
    System.out.println(ename + " has ended!\n" +
            member + " members are free now.");
  }
}
```

Reference Passing

Constructor with multiclass

A team can have a maximum of 4 players

Driver	Output

`public class TeamTester {`
`  public static void main(String[] args) {`
`  Player p1 = new Player("Sakep", 37, 200);`
`  Player p2 = new Player("Tamem", 35, 180);`
`  p1.details();`
`  System.out.println("=======1=======");`
`  p2.details();`
`  System.out.println("=======2=======");`
`  p1.addRival(p2);`
`  p2.age  = 36;`
`  p2.total = 195;`
`  System.out.println("=======3=======");`
`  p1.showRival();`
`  System.out.println("=======4=======");`
 	
`  Team ban = new Team();`
`  ban.updateName("Bangladesh");`
`  System.out.println("=======5=======");`
`  ban.addPlayer(p1);`
`  System.out.println("=======6=======");`
`  ban.addPlayer(p2);`
`  System.out.println("=======7=======");`
`  ban.details();`
`  System.out.println("=======8=======");`
`  Team aus = new Team("Australia");`
`  Player p3 = new Player("Ponting", 50, 300);`
`  aus.addPlayer(p3);`
`  Player p4 = new Player("Lee", 49, 200);`
`  aus.addPlayer(p4);`
`  aus.details();`
`  }`
`}`
	`Name: Sakep`
	`Age: 37, Total matches: 200`
	`=======1=======`
	`Name: Tamem`
	`Age: 35, Total matches: 180`
	`=======2=======`
	`=======3=======`
	`Rival of Sakep is Tamem`
	`Rival's stats:`
	`Name: Tamem`
	`Age: 36, Total matches: 195`
	`=======4=======`
	
	`=======5=======`
	`Player Sakep added`
	`=======6=======`
	`Player Tamem added`
	`=======7=======`
	`Team: Bangladesh`
	`List of players:`
	`Name: Sakep`
	`Age: 37, Total Matches: 200`
	`Name: Tamem`
	`Age: 36, Total Matches: 195`
	`=======8=======`
	`Player Ponting added`
	`Player Lee added`
	`Team: Australia`
	`List of players:`
	`Name: Ponting`
	`Age: 50, Total Matches: 300`
	`Name: Lee`
	`Age: 49, Total Matches: 200`

```
public class B{
  public int x = 3, y = 5, temp = -5, sum = 2;
  public B(){
    y = temp + 3 ;
    sum = 3 + temp + 2;
    temp -= 2;
  }
  public B(B b){
    sum = b.sum;
    x = b.x + 2;
    b.methodB(2,3);
    sum += x;
  }
  public void methodA(int m, int n){
    int x = 2;
    y = y + m + (temp++);
    x = x + 5 +  n;
    sum = sum + x + y;
    System.out.println(x + " " + y+ " " + sum);
  }
  public void methodB(int m, int n){
    int  y = 0;
    y = y + this.y;
    x = this.y + 2 + temp;
    methodA(x, y);
    sum = x + y + sum;
    System.out.println(x + " " + y+ " " + sum);
  }
}
```

```
public class Tester {
  public static void main(String args []){
    B b1 = new B();
    B b2 = new B(b1);
    b1.methodA(1, 2);
    b2.methodB(3, 2);
  }
}
```

Outputs		

Multi Class + Encapsulation

Design the required class/es so that the following output is generated.

- You may assume that to access the gym, a member must have an active membership card, and his/her home branch must match the branch of the gym.
- Additionally, the default maximum capacity of a gym is 2.
- All attributes of the member class must be private.

Driver Code

```java
public class GymMemberTester {
  public static void main(String[] args) {
    Member m1 = new Member("Luffy", "Dressrosa");
    System.out.println("1===============");
    Member m2 = new Member("Zoro", "Wano");
    Member m3 = new Member("Jimbe", "Dressrosa");
    m1.showDetails();
    m2.showDetails();
    System.out.println("2===============");
    m3.showDetails();
    System.out.println("3===============");
    Gym g1 = new Gym("Dressrosa");
    Gym g2 = new Gym("Wano", 5);
    g1.showDetails();
    g2.showDetails();
    System.out.println("4===============");
    m2.activateMembership();
    m3.activateMembership();
    System.out.println("5===============");
    m2.showDetails();
    m3.showDetails();
    System.out.println("6===============");
    g1.checkIn();
    System.out.println("7===============");
    g1.checkIn(m1, m2);
    System.out.println("8===============");
    m1.activateMembership();
    m2.updateBranch("Dressrosa");
    m1.showDetails();
    m2.showDetails();
    System.out.println("9===============");
    g1.checkIn(m1);
    g1.checkIn(m2, m3);
    System.out.println("10===============");
    g1.showDetails();
  }
```

Output

```
1===============
Member Name: Luffy
Home Branch: Dressrosa
Membership Active? false
Member Name: Zoro
Home Branch: Wano
Membership Active? false
2===============
Member Name: Jimbe
Home Branch: Dressrosa
Membership Active? false
3===============
Gym Branch: Dressrosa
Members Checked In: 0 (Max: 2)
No members inside
Gym Branch: Wano
Members Checked In: 0 (Max: 5)
No members inside
4===============
5===============
Member Name: Zoro
Home Branch: Wano
Membership Active? true
Member Name: Jimbe
Home Branch: Dressrosa
Membership Active? true
6===============
No members given
7===============
Your membership is inactive!
You are at the wrong branch!
8===============
Member Name: Luffy
Home Branch: Dressrosa
Membership Active? true
Member Name: Zoro
Home Branch: Dressrosa
Membership Active? true
9===============
Luffy checked in.
Zoro checked in.
Gym is full!
10===============
Gym Branch: Dressrosa
```

}	Members Checked In: 2 (Max: 2) Members Inside: ---------- Member Name: Luffy Home Branch: Dressrosa Membership Active? true ---------- Member Name: Zoro Home Branch: Dressrosa Membership Active? true

```
1   public class ExamClass {
2       public int ques;
3       public int sum;
4       public void methodA() {
5           System.out.println(ques + " " + 0 + " " + 0);
6       }
7   }
8   class QuizA {
9       public int x, y;
10      public int sum = 1;
11      public QuizA(int x, int y) {
12          this.x = y;
13          this.y = x;
14      }
15      public void methodA() {
16          int x = 3;
17          y = this.y + x;
18          ExamClass exam = new ExamClass();
19          exam.sum = x;
20          exam.ques = this.y;
21          x = this.x + x + exam.sum;
22          this.y = this.sum + methodB(exam.ques, exam);
23          System.out.println(x + " " + this.y + " " + sum);
24          sum = x % 2 + this.x;
25          y = x + y + exam.sum;
26          System.out.println(x + " " + y + " " + sum);
27      }
28      public int methodB(int x1, ExamClass x2) {
29          int y = 0;
30          y = this.y + x2.sum;
31          x2.ques = x1 + x2.ques;
32          sum = sum + x + y;
33          System.out.println(this.x + " " + this.y + " " + sum);
34          return x2.sum;
35      }
36  }
```

Driver Code	Output		

`public class QuizTesterA{`
`  public static void main(String []args){`
`  QuizA q1 = new QuizA(3,4);`
`  q1.methodA();`
`  }`
`}`			

Design the **Vaccine** and **Person** class so that the following expected output is generated.
[N.B: Students will get vaccines on a priority basis. So, age doesn't matter for students. All **attributes of Vaccine** class should be **Private**.**]**

Driver Code

```
public class VaccineTester {
  public static void main(String[] args) {
    Vaccine astra = new Vaccine("AstraZeneca", "UK", 60);
    Vaccine modr = new Vaccine("Moderna", "UK", 30);
    Vaccine sin = new Vaccine("Sinopharm", "China", 30);

    Person p1 = new Person("Bob", 21, "Student");
    System.out.println("1================");
    p1.pushVaccine(astra);
    System.out.println("2================");
    p1.showDetail();
    System.out.println("3================");
    p1.pushVaccine(sin, "2nd Dose");
    System.out.println("4================");
    p1.pushVaccine(astra, "2nd Dose");
    System.out.println("5================");
    p1.showDetail();
    System.out.println("6================");
    p1.pushVaccine(astra, "2nd Dose");
    System.out.println("7================");
    p1.showDetail();
    System.out.println("8================");

    Person p2 = new Person("Carol", 23, "Actor");
    System.out.println("9================");
    p2.pushVaccine(sin);
    System.out.println("10================");

    Person p3 = new Person("David", 34);
    System.out.println("11================");
    p3.pushVaccine(modr, "2nd Dose");
    System.out.println("12================");
    p3.pushVaccine(modr, "1st Dose");
    System.out.println("13================");
    p3.showDetail();
    System.out.println("14================");
    p3.pushVaccine(modr, "2nd Dose");
  }
}
```

Output

```
1================
1st dose done for Bob
2================
Name: Bob, Age: 21, Type: Student
Vaccine name: AstraZeneca
1st dose: Given
2nd dose: Please come after 60 days
3================
Sorry Bob, you can't take 2 different
vaccines
4================
2nd dose done for Bob
5================
Name: Bob, Age: 21, Type: Student
Vaccine name: AstraZeneca
1st dose: Given
2nd dose: Given
6================
Sorry Bob, you already received both doses.
7================
Name: Bob, Age: 21, Type: Student
Vaccine name: AstraZeneca
1st dose: Given
2nd dose: Given
8================
9================
Sorry Carol, Minimum age for taking
vaccines is 25 years now.
10================
11================
Sorry David, invalid dose request.
12================
1st dose done for David
13================
Name: David, Age: 34, Type: General Citizen
Vaccine name: Moderna
1st dose: Given
2nd dose: Please come after 30 days
14================
2nd dose done for David
```

Static

```
1  public class B{
2    public static int x;
3    public int y = 4;
4    public int temp = -5;
5    public int sum = 2;
6    public B(){
7      y = temp + 3 ;
8      sum = 3 + temp + 3;
9      temp-=2;
10   }
11   public B(B b){
12     sum = b.sum;
13     x = b.x + 3;
14     b.methodB(1,3);
15     sum += x;
16   }
17    public void methodA(int m, int n){
18     int x = 2;
19     y = y + m + (temp++);
20     x = x + 7 +  n;
21     sum = sum + x + y;
22     System.out.println(x + " " + y+ " " + sum);
23   }
24   public void methodB(int m, int n){
25     int  y = 0;
26     y = y + this.y;
27     x = this.y + 3 + temp;
28     methodA(x, y);
29     sum = x + y + sum;
30     System.out.println(x + " " + y+ " " + sum);
31   }
32 }
```

```
B b1 = new B();
B b2 = new B(b1);
b1.methodA(3, 2);
b2.methodB(1, 2);
```

x	y	sum

```
1  class Task{
2   public static int x;
3   public int y;
4   public Task(){
5     x = this.x + 5;
6   }
7   public Task(int x){
8     this();
9     this.x = x + 10;
10  }
11  public static void met(Task [] t){
12    int x = t[0].met(t[1]) + t[1].x++;
13    int y = ++x + t[1].met(t[0]);
14    System.out.println(x + " " + y);
15  }
16  public int met(Task t){
17    int x = (int)(t.x % 2 - y + 2);
18    t.y = x + this.y;
19    System.out.println(x + " " +t.y);
20    return x;
21  }
22 }
23
24 public class Tester{
25  public static void met(Task[]t){
26    Task.met(t);
27  }
28  public static void main(String[] args) {
29    Task t1 = new Task(1);
30    Task t2 = new Task(2);
31    Task [] ta = {t1, t2};
32    met(ta);
33  }
34 }
```

Design the **Desktop** and **Game** class such that the following outputs are produced.
*All attributes of Game class must be **private**.*

Driver Code	Output

public class DesktopTester{
public static void main(String[] args){
Game g1 = new Game("Valorant", 100);
Game g2 = new Game("GTA V", 200);
Game g3 = new Game("FC 25", 300);
Game g4 = new Game("MineCraft", 150);
Game g5 = new Game("Overwatch", 70);
System.out.println("1==========");
System.out.println("User Count: " + Desktop.userCount);
System.out.println("2==========");
Desktop.displayInfo();
System.out.println("3==========");
Desktop user1 = new Desktop("Clark");
System.out.println("4==========");
Desktop user2 = new Desktop("Bruce");
System.out.println("5==========");
user2.installGame(g1);
System.out.println("6==========");
Desktop.displayInfo();
System.out.println("7==========");
user1.installGame(g2);
user2.installGame(g3);
user1.installGame(g4);
user2.installGame(g5);
System.out.println("8==========");
Desktop.displayInfo();
System.out.println("9==========");
System.out.println("User Count: " + Desktop.userCount);
System.out.println("10==========");
Desktop user3 = new Desktop("Barry");
System.out.println("11==========");
System.out.println("User Count: " + Desktop.userCount);
}
}
	1==========
	User Count: 0
	2==========
	Desktop Info:
	Storage: 512 GB
	No games installed!
	3==========
	Clark(ID: 1) logged in!
	4==========
	Bruce(ID: 2) logged in!
	5==========
	Valorant installed successfully!
	6==========
	Desktop Info:
	Storage: 412 GB
	Games installed:
	1. Valorant (100 GB) - Installed by: Bruce(ID: 2)
	7==========
	GTA V installed successfully!
	Not enough storage!
	MineCraft installed successfully!
	Cannot install more than 3 games!
	8==========
	Desktop Info:
	Storage: 62 GB
	Games installed:
	1. Valorant (100 GB) - Installed by: Bruce(ID: 2)
	2. GTA V (200 GB) - Installed by: Clark(ID: 1)
	3. MineCraft (150 GB) - Installed by: Clark(ID: 1)
	9==========
	User Count: 2
	10==========
	Barry(ID: 3) logged in!
	11==========
	User Count: 3

Inheritance

```
1  public class A {
2   static int temp = 4;
3   static int x = -10;
4   int sum, y;
5   public A() {
6     y = temp - 2;
7     sum = temp + 1;
8     temp -= 2;
9   }
10  public void methodA(int m, int n) {
11    y = y + m + (temp++);
12    x = x + 1 + n;
13    sum = sum + x + y;
14    System.out.println(x + " " + y + " " + sum);
15  }
16 }
17 class B extends A {
18  static int x = 0;
19  int sum = -6;
20  public B() {
21    sum = 0;
22    y = temp + 3;
23    super.sum = 3 + temp + 2;
24    temp -= 2;
25  }
26  public B(B b) {
27    sum = b.sum + super.sum;
28    x = b.x + 1;
29    b.methodB(2, 3);
30    y += x;
31  }
32  public void methodB(int m, int n) {
33    int y = 0;
34    y = y + this.y;
35    x = y + 2 + (++temp);
36    methodA(x, y);
37    sum = x + y + sum;
38    System.out.println(x + " " + y + " " + sum);
39  }
40 }
```

```
public class Tester {
    public static void main(String [] args) {
        A a1 = new A();
        B b1 = new B();
        B b2 = new B(b1);
        b1.methodA(2, 3);
        b2.methodB(3, 8);
    }
```

Output:		
x	y	sum

}			

Design the **Manager** and **Developer** class derived from the **Employee** class with appropriate attributes and properties so that the driver code can generate the output given below. [**Hint**:

Manager:

1. Adds a bonus to the base salary if the manager works more than 40 hours.
2. If the manager works more than 100 hours, the full amount is approved; if they work more than 80 hours, half the amount is approved. Otherwise, the increment is denied.

Developer:

1. Adds $700 to the base salary if the developer works with Java programming language.]

Driver Code and Parent Class

```java
public class EmployeeTester {
  public static void main(String[] args) {
    Manager neymar = new Manager("Neymar",1000, 45, 10);
    Developer messi = new Developer("Messi",1000,50,"Java");
    Developer chiesa = new Developer("Chiesa", 1000, 50, "Javascript");
    neymar.calculateSalary();
    System.out.println("1.==========");
    System.out.println(neymar);
    System.out.println("2.==========");
    neymar.requestIncrement(100);
    System.out.println("3.==========");
    neymar.setHoursWorked(85);
    neymar.requestIncrement(100);
    System.out.println("4.==========");
    neymar.calculateSalary();
    System.out.println("5.==========");
    System.out.println(neymar);
    System.out.println("6.==========");
    messi.calculateSalary();
    System.out.println("7.==========");
    System.out.println(messi);
    System.out.println("8.==========");
    chiesa.calculateSalary();
    System.out.println("9.==========");
    System.out.println(chiesa);
  }
}
class Employee {
  private String name;
  private double baseSalary;
  private int hoursWorked;
  public Employee(String name, double baseSalary, int hoursWorked){
    this.name = name;
    this.baseSalary = baseSalary;
    this.hoursWorked = hoursWorked;
  }
  public double getBaseSalary() {
    return baseSalary;
  }
  public void setBaseSalary(double baseSalary) {
    this.baseSalary = baseSalary;
  }
  public int getHoursWorked() {
    return hoursWorked;
  }
  public void setHoursWorked(int hoursWorked) {
    this.hoursWorked = hoursWorked;
  }
  @Override
  public String toString() {
    return "Name: " + name +
            "\nBase Salary: $" + baseSalary +
            "\nWork Hours: " + hoursWorked;
  }
}
```

Output

```
1.==========
Name: Neymar
Base Salary: $1000.0
Work Hours: 45
Bonus: 10.0 %
Final Salary: $1100.0
2.==========
Increment denied.
3.==========
$50 Increment approved.
4.==========
5.==========
Name: Neymar
Base Salary: $1050.0
Work Hours: 85
Bonus: 10.0 %
Final Salary: $1155.0
6.==========
7.==========
Name: Messi
Base Salary: $1000.0
Work Hours: 50
Language: Java
Final Salary: $1700.0
8.==========
Name: Chiesa
Base Salary: $1000.0
Work Hours: 50
Language: Javascript
Final Salary: $1000.0
```

```java
public class A {
    public int x = 3, y = 5;
    public static int sum = 14;
    public A(int y) {
        this.y = ++y;
        sum = sum + this.y + y;
        x += this.y + this.methodA(sum, y);
    }
    public int methodA(int x, int y) {
        sum += x % y;
        this.y = this.y + 2 + (sum/3);
        y = y + 3 + x;
        System.out.println(x + " " + this.y + " " + sum);
        return this.y+y;
    }
}
public class B extends A {
    public static int y = 8;
    public int sum = 11;
    public B(int a, int b) {
        super(a + b);
        y = a + b + 3;
        this.sum = A.sum + y;
        System.out.println(A.sum + " " + super.y + " " + this.sum);
    }
    public int methodA(int y, int z) {
        int temp = x * 2 - y / 2;
        y = B.y + super.y;
        this.sum = sum + temp;
        super.sum = (z++) + y;
        System.out.println(y + " " + z + " " + sum);
        return sum + this.sum;
    }
}
```

Driver Code

```java
A box1 = new A(15);
B box2 = new B(6, 2);
```

Outputs