Learning to Rank on the Cranfield Collection

Information Retrieval — Programming Assignment III

Group: Quad Query

1 Group details

Name	Roll number
Hrishikesh Tiwari	22CH3FP39
Shshank Mittal	22CS30051
Rishit Garg	22CS30045
Parth Patil	22CS30041

2 Problem statement

The goal is to learn ranking functions for the Cranfield collection from human relevance judgments, instead of tuning them by hand. The collection has 1400 abstracts from aeronautics, 225 queries and graded relevance judgments. The learned rankers are evaluated on held-out queries with precision, recall and F1. The assignment asks for two methods:

- **Method A: Boolean weighted zone scoring.** A document's score is a weighted sum of Boolean match scores over its zones (title, author, bibliography, body):

$$\text{score}(d, q) = \sum_{i=1}^{4} g_i \, s_i(d, q), \qquad g_i \in [0, 1], \quad \sum_i g_i = 1. \tag{1}$$

  The weights g_i are learned by grid search from the relevance judgments.

- **Method B: real-valued weights with a linear SVM.** Each query–document pair is described by a feature vector $\psi(d, q)$, using the LETOR feature list given in the assignment. A linear SVM learns a weight vector $\mathbf{w}$, and documents are ranked by $\mathbf{w}^\top \psi(d, q)$.

For each test query, the system outputs a ranked list of documents and the set of documents it considers relevant (the top k of the list). Both are evaluated against the human judgments.

3 Implementation details

The system is written in Python 3. It uses `numpy` for all index and feature computation, `scikit-learn` for the SVM (`LinearSVC`) and `nltk` only for the Porter stemmer. Table 1 shows the code layout.

File	Contents
`src/parser_qq.py`	parsers for `cran.all.1400`, `cran.qry`, `cranqrel`
`src/preprocessing.py`	tokenising, stopword removal, Porter stemming
`src/dataset.py`	term-count matrix per zone, idf, ranking helper, query splits
`src/evals.py`	P/R/F1@k, MAP, nDCG@10, cut-off tuning, TREC run files
`src/method_a/`	Boolean zone scores and grid search of zone weights
`src/method_b/`	66 query–document features and linear SVM training
`main.py`	all experiments; ranking of unseen queries with the final models
`report/make_figures.py`	figures from `results/summary.json`

Table 1: Code layout.

3.1 Data and preprocessing

- **Zones.** The document fields `.T`, `.A`, `.B` and `.W` become the zones *title*, *author*, *bib* and *body*. A fifth stream, *all*, is the four zones joined together.
- **Query numbering.** The `.I` numbers in `cran.qry` are not $1, \ldots, 225$ (some values are skipped). `cranqrel` refers to queries by their *position* in the file, so queries are numbered $1, \ldots, 225$ in the order they appear.
- **Placeholder judgments.** `cranqrel` has one line per query with code -1. These are placeholders, not judgments, and are dropped. That leaves 1612 judgments with codes 1–4, about 7.2 relevant documents per query.
- **Text processing.** Text is lowercased and split into alphanumeric tokens. Stopwords and one-letter tokens are removed, and the remaining tokens are Porter-stemmed, giving 6588 distinct stems. Queries go through the same pipeline, and a repeated query term is counted once. Queries average about 10 stems.
- **Index.** Each zone is stored as a dense term $\times$ document count matrix (6588×1400). The features of a query are then numpy operations on the rows of its terms, and features for all 225 queries are computed in a few seconds. The idf is $\log \frac{N+1}{\mathrm{df}+0.5}$.
- **Relevance.** Any judged document (codes 1–4) is relevant, and every other document is non-relevant. Where graded relevance is used (Ranking SVM, nDCG), the gain is $5 -$ code: 4 for "complete answer" down to 1 for "minimum interest", and 0 for unjudged documents.

3.2 Method A: Boolean weighted zone scoring

Boolean match functions. Two Boolean functions $s_i(d, q)$ are compared:

- **or** (the textbook definition): $s_i = 1$ if *any* query term occurs in zone i, and 0 otherwise.
- **term** (per-term Boolean): with $s_i(t) = 1$ if term t occurs in zone i,

$$s_i(d, q) = \frac{1}{|q|} \sum_{t \in q} s_i(t), \tag{2}$$

  the fraction of query terms present in the zone. This is ranked Boolean matching applied one term at a time. It still uses only presence or absence, never frequencies, but a document that matches more query terms scores higher.

Grid search. The weights are found by exhaustive search over every weight vector on the 4-dimensional simplex with step 0.05, which gives 1771 candidates. Two objectives are compared:

- **mse** (the lecture formulation). Relevant documents are quantised as $r = 1$ and non-relevant ones as $r = 0$, and the total squared error is minimised:

$$\varepsilon(g) = \sum_j \big(r(d_j, q_j) - \mathrm{score}(d_j, q_j)\big)^2. \tag{3}$$

The training triples are every relevant document of each training query, plus three sampled non-relevant documents per relevant one. Negatives are sampled only from documents that match at least one query term, because a document with no match scores 0 under every g and adds nothing to the search.

- **map**. The objective is the mean average precision of the ranking that g produces on the training queries. This optimises the ranking directly. All 1771 candidates are evaluated together in vectorised form, and ties count as half a rank.

Ties in the final ranking are broken by document id.

3.3 Method B: real-valued weights with a linear SVM

Features. All 22 features from the assignment are computed for each of three streams: title, body and the whole document. That gives $22 \times 3 = 66$ features per query–document pair. In Table 2, tf_t is the count of query term t in the stream, L is the stream length, and the aggregates are taken over the query terms.

#	Feature	Definition
1	query term number	number of query terms present in the stream
2	query term ratio	feature 1 divided by $\lvert q \rvert$
3	stream length	L (tokens after preprocessing)
4	idf	$\sum \mathrm{idf}(t)$ over query terms present in the stream
5–9	tf: sum, min, max, mean, variance	aggregates of tf_t
10–14	normalised tf: sum … variance	aggregates of tf_t / L
15–19	tf·idf: sum … variance	aggregates of $\mathrm{tf}_t \cdot \mathrm{idf}(t)$
20	Boolean model	1 if any query term is present
21	vector space model	cosine of the $(1 + \log \mathrm{tf})$·idf document vector and the idf query vector
22	BM25	Okapi BM25 with $k_1 = 1.2$, $b = 0.75$

Table 2: Features per stream (the list from the assignment).

The "idf" feature is summed only over the query terms that occur in the document. In LETOR it is the sum over all query terms, which is the same for every document of a query and would become 0 after per-query normalisation. The Boolean model uses "any term matches", because an "all terms match" version is 0 for almost every document when queries have about 10 terms. Every feature is min–max normalised *per query* (LETOR "QueryLevelNorm"), so each weight compares documents of the same query.

Learning. Two linear SVM formulations are trained with `LinearSVC` (hinge loss with L2 regularisation):

- **Pointwise SVM.** Each pair $(\psi(d, q), \text{relevant or not})$ is one training example. Only about 0.5% of the pairs are relevant, so class weights are balanced. Documents are ranked by $\mathbf{w}^\top \psi + b$.
- **Pairwise Ranking SVM.** For two documents of the same query with different grades, the difference vector

$$\Phi(d_i, d_j, q) = \psi(d_i, q) - \psi(d_j, q) \tag{4}$$

  is labelled $+1$ if d_i is more relevant and -1 otherwise. The grades give the order code $1 \succ 2 \succ 3 \succ 4 \succ$ unjudged. At most 2000 pairs are sampled per query, and half of them have their sign flipped so that both classes are present. The SVM has no intercept, and documents are ranked by $\mathbf{w}^\top \psi$.

Every document in the collection is scored. The regularisation parameter C is chosen from $\{10^{-4}, 10^{-3}, 10^{-2}, 10^{-1},$ by 5-fold cross-validation *on the training queries*, with MAP as the criterion. The test queries are never used for model selection.

3.4 Output and evaluation

- For each test query, the top 100 documents are written in TREC format (`qid Q0 docid rank score tag`) to `results/method_*_test_results.txt`.
- The documents returned as relevant are the top k of the ranking, where k is the value in $1, \ldots, 50$ that maximises mean F1@k on the *training* queries. These result sets are in `results/method_*_test_relevant.txt`.
- Measures are averaged over queries: precision, recall and F1 at $k = 5, 10, 20$ and at the tuned k. MAP and nDCG@10 (graded) are reported as additional measures of ranking quality.
- `python main.py predict A|B <queries> <out>` ranks unseen queries with the final models, which are retrained on all 225 queries.

4 Plan of experiments

1. **Split.** The 225 judged queries are shuffled with a fixed seed (42) and split 70/30 into 157 training and 68 test queries. All learning, including the weights, C and the cut-off k, uses only the training queries.
2. **Method A.** Two Boolean functions (or, term) × two objectives (mse, map). The learned weights and the objective along the grid are inspected, and each variant is evaluated on the test queries.
3. **Method B.** The pointwise SVM and the Ranking SVM, each with C chosen by inner cross-validation, are evaluated on the test queries. The learned feature weights are inspected.
4. **Baseline.** BM25 on the whole document, which is the strongest hand-built ranker that the same features can provide.
5. **Robustness.** 5-fold cross-validation over all 225 queries for the main systems, to check that the result on a single split holds.
6. **Final models.** The chosen configurations are retrained on all 225 queries (`models/*.json`) and used to rank the unknown test queries.
7. **Extra checks.** Log-transformed and z-scored features instead of min–max, and 8000 instead of 2000 pairs per query.

5 Results

5.1 Held-out test queries

Run	P	R	F1	P@10	R@10	F1@10	MAP	nDCG@10
A or / mse	0.0235	0.1038	0.0371	0.0368	0.0737	0.0472	0.0595	0.0489
A or / map	0.0294	0.1163	0.0438	0.0456	0.0963	0.0588	0.0704	0.0613
A term / mse	0.1891	0.2606	0.1984	0.1559	0.2908	0.1844	0.2241	0.2770
A term / map	0.1868	0.3488	0.2211	0.1868	0.3488	0.2211	0.2701	0.3371
B pointwise SVM	0.2710	0.3485	0.2739	0.2265	0.4097	0.2644	0.3194	0.3938
B Ranking SVM	**0.2815**	**0.3618**	**0.2853**	**0.2294**	**0.4131**	**0.2675**	**0.3245**	**0.3991**
BM25 baseline	0.2689	0.3464	0.2749	0.2235	0.3939	0.2608	0.3148	0.3832

Table 3: Results on the 68 test queries. P, R and F1 (without @) are for the set of documents returned as relevant, i.e. the top k, where k is tuned on the training queries for each run ($k = 10$ for A term/map; $k = 7$ for Method B and BM25). Bold rows are the final configuration of each method.

Run	P@5	R@5	F1@5	P@20	R@20	F1@20
Method A (term / map)	0.2588	0.2642	0.2368	0.1294	0.4500	0.1864
Method B pointwise SVM	0.3206	0.3099	0.2837	0.1529	0.5219	0.2190
Method B Ranking SVM	0.3324	0.3148	0.2906	0.1544	0.5277	0.2213
BM25 baseline	0.3118	0.3059	0.2796	0.1456	0.5003	0.2090

Table 4: Precision, recall and F1 at cut-offs 5 and 20 on the test queries.




Figure 1: Precision, recall and F1 against the cut-off k on the test queries.

5.2 Cross-validation over all queries

System	5-fold CV MAP
Method A (term / map)	0.2738
Method B pointwise SVM	0.3273
Method B Ranking SVM	0.3260
BM25 baseline	0.3192

Table 5: MAP averaged over five query folds covering all 225 judged queries.

5.3 Method A: learned zone weights

Variant	g_{title}	g_{author}	g_{bib}	g_{body}
or / mse	0.40	0.40	0.15	0.05
or / map	0.20	0.10	0.05	0.65
term / mse	0.20	0.00	0.00	0.80
term / map	0.50	0.05	0.00	0.45

Table 6: Zone weights learned on the 157 training queries (grid step 0.05). Retraining term/map on all 225 queries gives the same weights.




Figure 2: Learned zone weights for the four Method A variants.




Figure 3: Training objectives for the per-term Boolean function along the title/body edge of the simplex ($g_{\text{author}} = g_{\text{bib}} = 0$, $g_{\text{body}} = 1 - g_{\text{title}}$). This is the four-zone version of choosing g in the two-zone example from the lecture. Left: total squared error (lower is better). Right: training MAP (higher is better).

5.4 Method B: model selection and learned weights

Inner 5-fold cross-validation on the training queries gave the following MAP for each C:

C	10^{-4}	10^{-3}	10^{-2}	10^{-1}	1
Pointwise SVM	**0.3303**	0.3207	0.3182	0.3170	0.3153
Ranking SVM	**0.3290**	0.3284	0.3211	0.3156	0.3137

Table 7: Inner cross-validation MAP for each C. $C = 10^{-4}$ was chosen for both SVMs.




Figure 4: The 18 largest-magnitude weights of the Ranking SVM. Features are normalised per query, so the weights can be compared directly. Blue: positive. Red: negative.




Figure 5: Per-query difference in AP (top 50) from the BM25 baseline on the test queries, sorted. The Ranking SVM beats BM25 on 41 queries and loses on 19. Method A beats it on 25 and loses on 33.

6 Discussion of results

6.1 Method A

The textbook "any term" Boolean function does not work on Cranfield. Its test MAP is only 0.070. Cranfield queries are long natural-language questions, about 10 stems after stopword removal. Almost every document matches some query term in its body, and many match in the title too. With four Boolean zones, the score can take only $2^4 = 16$ values, so the ranking is mostly a large tie broken by document id. The learned weights are also unstable. Under mse, author and bibliography get large weights (0.40 and 0.15): those zones almost never match, and a score of 0 is the "correct" prediction for most of the non-relevant training examples.

Counting matched terms per zone fixes this. The per-term Boolean function still uses only presence and absence, but it counts how many query terms each zone covers. Test MAP rises from 0.070 to 0.270 and F1@10 from 0.059 to 0.221.

The learned weights are easy to interpret. Title and body carry almost all of the weight, and author and bibliography get about 0, because queries never mention authors or journals. Under

the MAP objective the title gets about half of the weight, even though in Cranfield the abstract repeats the title. A title match is a strong signal for such a short field.

The squared-error objective and the ranking objective disagree. mse chooses $(g_{\text{title}}, g_{\text{body}}) = (0.20, 0.80)$, while MAP chooses $(0.50, 0.45)$. Squared error asks the score to *equal* 0 or 1, which a convex combination of match fractions cannot do, and the many negatives dominate it. Ranking only needs relevant documents to score *higher* than non-relevant ones. The MAP objective does better on the test queries (MAP 0.270 vs. 0.224, F1 0.221 vs. 0.198). This illustrates the lecture's point that ranking is better treated as ordinal regression than as classification or regression. Fig. 3 also shows that the MAP landscape is flat for $g_{\text{title}} \in [0.35, 0.65]$, so the coarse grid used in the lecture would find essentially the same optimum.

Method A stays below BM25 (MAP 0.270 vs. 0.315). Presence and absence cannot express term frequency, document length or term rarity (idf), which are exactly what BM25 adds.

6.2 Method B

The Ranking SVM is the best system on the test queries. It reaches MAP 0.325, nDCG@10 0.399 and F1 0.285 at the tuned cut-off, against 0.315, 0.383 and 0.275 for BM25. It improves AP on 41 of the 68 test queries and hurts 19 (Fig. 5). In cross-validation over all queries, both SVMs again beat BM25, by about 0.007–0.008 MAP (Table 5).

The gain over BM25 is small, and that is expected. All 66 features are functions of the same query-term statistics, and BM25 already combines tf, idf and document length in a well-tuned non-linear way. The learned model (Fig. 4) amounts to: use BM25 and the vector-space score on the body and the whole document, reward documents that match rare query terms (the idf of matched terms) and that have a high maximum tf·idf, and penalise long documents. A linear SVM can only re-weight evidence that BM25 already uses. Larger gains would need different evidence, such as term proximity, phrase matches or query expansion, which the feature list does not contain. The extra checks support this: log or z-score normalisation and more pairs per query all changed cross-validation MAP by less than 0.005. The limit is the feature set, not the optimiser.

Pairwise vs. pointwise. The Ranking SVM uses the graded judgments and only has to order documents within a query, so it should have an advantage. It wins on the test split (MAP 0.325 vs. 0.319, F1 0.285 vs. 0.274), but in cross-validation the two are tied (0.3260 vs. 0.3273). Per-query normalisation already removes most of the differences between queries that pairwise learning is meant to handle, and binary relevance carries most of the signal on this collection.

Strong regularisation helps. Both SVMs chose the smallest C tried (10^{-4}), and MAP drops steadily as C grows (Table 7). With about 150 training queries and highly correlated features (tf, normalised tf, tf·idf and BM25 of the same stream), a small C spreads the weight across correlated features instead of fitting noise. Since the optimum is at the edge of the grid, a slightly smaller C might help a little. The curve is already flattening, so we expect the difference to be small.

6.3 Precision, recall and the cut-off

Cranfield queries have about 7 relevant documents each, so as k grows, precision falls quickly and recall rises (Fig. 1). F1 peaks at a small k. The cut-off tuned on the training queries ($k = 7$ for Method B) gives test precision 0.282, recall 0.362 and F1 0.285: about two of the seven returned documents are relevant. The absolute numbers are modest because Cranfield is hard for lexical matching (abstracts often paraphrase the question in other technical terms) and because "minimum interest" documents (code 4) also count as relevant.

6.4 Conclusion

Both methods learn sensible weights from the relevance judgments. For Boolean zone scoring, the choice of Boolean function and of a ranking-aware objective matters far more than the grid resolution, and the learned weights confirm that title and body carry the evidence. The Ranking SVM on the LETOR features gives the best results and beats the strongest hand-built baseline (BM25) consistently, though only slightly. Pairwise and pointwise SVMs perform about the same.

A How to run

```
python3 -m venv irenv
source irenv/bin/activate
pip install -r requirements.txt

python main.py                                    # all experiments (8-10 min)
python main.py predict B queries.qry run_B.txt  # rank unseen queries
python report/make_figures.py                     # regenerate figures/
```

The query file for `predict` must be in Cranfield format (`.I` and `.W` lines). Queries are numbered by their order in the file. The output is the top 100 documents per query in TREC format. Full instructions are in `README.md`.