

CSE141 INTRODUCTION TO PROGRAMMING

Final Examination

Max Marks: 50

Time Allowed: 3 hours

Answer the questions in the spaces provided on the question sheets.
Please give clear and rigorous answers. Be to the point. Show your work.

Name: _____

ERP: _____

Question:	True/False	MCQ's	Trace/Debug	Methods	Arrays	Recursion	Classes	Total
Marks:	10	9	11	5	5	5	5	50
Score:								

Question 1: True/False 10 marks

True/False questions. Circle the correct answer.

- (a) **T F** A single `std::cout` statement in a C++ program could result in multiple lines of output.
- (b) **T F** Multiple `std::cout` statements in a C++ program could result in a single line of output.
- (c) **T F** Variable names in C++ must have at least one upper-case letter.
- (d) **T F** To end a C++ program both the `break` or the `exit` statement may be used.
- (e) **T F** An if-else statement could be rewritten using two if statements without an else.
- (f) **T F** The following statements give a run-time error in C++:

```
std::string name = "123";
if (name.length() == 3) {
std::cout << name[2] << std::endl;
}
```

- (g) **T F** The output of the following statements is: 3 Done

```
int x = 2;
int y = 1;
std::cout << x << y;
std::cout << " Done" << std::endl;
```

- (h) **T F** To check and see if the value of variable `x` is between 3 and 9 we could use:

```
int x = 4;
if( 3 < x < 9) {
std::cout << "x is between 3 and 9" << std::endl;
}
```

(i) **T F** The output of the following lines of code is: One Done

```
int x = 2;  
if( x = 1)  
std::cout<<"One ";  
std::cout<<"Done";
```

(j) **T F** The output of the statement below is: 1.7

```
int x = 5;  
int y = 3;  
double answer = 0.0;  
answer = x / y;  
std::cout<< setprecision(1) << answer << std::endl;
```

Question 2: MCQ's9 marks

Circle the correct answer

- (a) [1½ marks] Consider the program segment given below. (Remember that the % operator is the modulus operator, which gives the remainder after integer division.) Its output is:

```
int i = 1;
while (i <= 30) {
    i++;
    cout << i;
    if (i % 2 == 0) {
        cout << endl;
    }
    i++;
}
```

- i. All the numbers from 1 to 30, with a line break after the number 10
 - ii. Even numbers from 1 to 30 all one one line
 - iii. Odd numbers from 1 to 30, each on its own line
 - iv. Even numbers from 1 to 30, each on its own line
 - v. None of the above
- (b) [2 marks] Consider method `second` shown below, which itself uses method `first`. For positive numbers, how would you best describe its return value?

```
int first(int x, int y) {
    int z=0;
    for (int i=0; i<y; i++) {
        z += x;
    }
    return z;
}
```

```
int second(int x, int y) {
    int z=1;
    for (int i=0; i<y; i++) {
        z = first( z, x);
    }
    return z;
}
```

- i. $x + y$
- ii. $x * x$
- iii. $x * y$
- iv. x^y
- v. None of the above

(c) [1½ marks] The output of the following code in C++ is equal to:

```
int value = 2;
int limit = 5;
int result = 1;
for(int x=0; x<limit; x++) {
    result = result * value;
}
std::cout<<result;
```

- i. $2 * 5$
- ii. $2 + 5$
- iii. 25
- iv. 32
- v. None of the above

(d) [1 mark] If we start with the array 6 1 14 10 5 12 11 9, which sorting algorithms will encounter 1 5 6 10 14 12 11 9 during the sorting process?

- i. Insertion sort
- ii. Mergesort
- iii. All of the above
- iv. None of the above

(e) [1 mark] In worst-case, the number of steps taken by *binary search* when applied on an array of size N is proportional to

- i. constant
- ii. $\log N$
- iii. N
- iv. $N \log N$
- v. N^2

Question 3: Trace/Debug11 marks

(a) [2 marks] Point out any errors in the following statements.

Statement	Error (if any)
<code>float = 3.14*2;</code>	
<code>float stu marks = 40.5;</code>	
<code>FirstName = 'Donald';</code>	
<code>char n = '7';</code>	

(b) [2 marks] Consider the following method:

```

void mystery(int n) {
    if (n > 100) {
        std::cout<<n;
    } else {
        mystery(2 * n);
        std::cout<<" , " + n;
    }
}

```

For each of the following calls, indicate the output that is produced by the method:

i. `mystery(60);`ii. `mystery(41);`

.....

.....

.....

(c) [1½ marks] What is the output of the following :

```

void main() {
    int result = mystery2(348);
    std::cout<<"Result is : "<<result;
}

int mystery2(int num) {
    if (num < 10)
        return num;
    else
        return num%10 + mystery2(num/10);
}

```

.....

.....

.....

(d) [2 marks] Consider the following method, `mystery3`:

```
void mystery3(vector<int> a, vector<int> b) {  
    for (int i = 0; i < a.length; i++) {  
        a[i] += b[b.length - 1 - i];  
    }  
}
```

What are the values of the elements in array `x` after the following code executes?

```
Vector<int> x = {1, 3, 5, 7, 9};  
Vector<int> y = {1, 4, 9, 16, 25};  
mystery3(x, y);
```

.....
.....

(e) [1 mark] What does the following code fragment print?

```
String string1 = "hello";  
String string2 = string1;  
string1 = "world";  
std::cout<<string1;  
std::cout<<string2;
```

.....
.....

(f) [1 mark] What does the following code fragment print?

```
std::string s = "Hello World";  
for (size_t i = 0; i < s.length(); ++i) {  
    s[i] = std::toupper(s[i]);  
}  
std::string sub = s.substr(6, 5);  
std::cout << s << std::endl;  
std::cout << sub << std::endl;
```

.....
.....

(g) [1½ marks] What does the following recursive function return?

```
string mystery4(String s) {  
    int N = s.length();  
    if (N <= 1) return s;  
    String a = s.substr(0, N/2); String  
    b = s.substr(N/2, N);  
    return mystery4(b) + mystery4(a);  
}
```

.....
.....

Question 4: Methods 5 marks

- (a) [2½ marks] Write a method called `isSorted` that given an array of integers returns **true** if array is sorted in ascending order and **false** otherwise.

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

- (b) [2½ marks] Write a static method called `sumTo` that accepts an integer parameter n and returns a real number representing the sum of the first n reciprocals. In other words, `sumTo(n)` returns $(1 + 1/2 + 1/3 + 1/4 + \dots + 1/n)$. For example, `sumTo(2)` should return 1.5. The method should return 0.0 if it is passed the value ≤ 0 .

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

Write a **recursive** method called `doubleDigits` that accepts an integer n as a parameter and returns the integer obtained by replacing every digit of n with two of that digit. For example, `doubleDigits(348)` should return 334488. The call `doubleDigits(x)` for $x \leq 0$ should return 0.

This image shows a full page of a document template designed for handwritten notes or essays. It features approximately 30 evenly spaced horizontal lines across the entire width of the page. The lines are thin and light gray, providing a guide for writing without being distracting. There are no margins, headers, footers, or other markings present on the page.

