



OpenShift Container Platform 4.12

Web console

Getting started with the web console in OpenShift Container Platform

OpenShift Container Platform 4.12 Web console

Getting started with the web console in OpenShift Container Platform

Legal Notice

Copyright © 2023 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This document provides instructions for accessing and customizing the OpenShift Container Platform web console.

Table of Contents

CHAPTER 1. WEB CONSOLE OVERVIEW	7
1.1. ABOUT THE ADMINISTRATOR PERSPECTIVE IN THE WEB CONSOLE	7
1.2. ABOUT THE DEVELOPER PERSPECTIVE IN THE WEB CONSOLE	7
1.3. ACCESSING THE PERSPECTIVES	8
CHAPTER 2. ACCESSING THE WEB CONSOLE	10
2.1. PREREQUISITES	10
2.2. UNDERSTANDING AND ACCESSING THE WEB CONSOLE	10
2.3. MULTICLUSTER CONSOLE	10
2.3.1. Enabling multicluster in the web console	10
CHAPTER 3. USING THE OPENSIFT CONTAINER PLATFORM DASHBOARD TO GET CLUSTER INFORMATION	13
3.1. ABOUT THE OPENSIFT CONTAINER PLATFORM DASHBOARDS PAGE	13
CHAPTER 4. ADDING USER PREFERENCES	15
4.1. SETTING USER PREFERENCES	15
CHAPTER 5. CONFIGURING THE WEB CONSOLE IN OPENSIFT CONTAINER PLATFORM	16
5.1. PREREQUISITES	16
5.2. CONFIGURING THE WEB CONSOLE	16
CHAPTER 6. CUSTOMIZING THE WEB CONSOLE IN OPENSIFT CONTAINER PLATFORM	17
6.1. ADDING A CUSTOM LOGO AND PRODUCT NAME	17
6.2. CREATING CUSTOM LINKS IN THE WEB CONSOLE	18
6.3. CUSTOMIZING CONSOLE ROUTES	19
6.3.1. Customizing the console route	19
6.3.2. Customizing the download route	20
6.4. CUSTOMIZING THE LOGIN PAGE	21
6.5. DEFINING A TEMPLATE FOR AN EXTERNAL LOG LINK	22
6.6. CREATING CUSTOM NOTIFICATION BANNERS	23
6.7. CUSTOMIZING CLI DOWNLOADS	23
6.8. ADDING YAML EXAMPLES TO KUBERNETES RESOURCES	24
6.9. CUSTOMIZING USER PERSPECTIVES	25
6.9.1. Customizing a perspective using YAML view	25
6.9.2. Customizing a perspective using form view	27
6.10. DEVELOPER CATALOG AND SUB-CATALOG CUSTOMIZATION	27
6.10.1. Customizing a developer catalog or its sub-catalogs using the YAML view	28
6.10.2. Customizing a developer catalog or its sub-catalogs using the form view	29
6.10.2.1. Example YAML file changes	29
CHAPTER 7. DYNAMIC PLUGINS	31
7.1. OVERVIEW OF DYNAMIC PLUGINS	31
7.1.1. About dynamic plugins	31
7.1.2. Key features	31
7.1.3. General guidelines	31
PatternFly 4 guidelines	31
7.2. GETTING STARTED WITH DYNAMIC PLUGINS	32
7.2.1. Dynamic plugin development	32
7.3. DEPLOY YOUR PLUGIN ON A CLUSTER	32
7.3.1. Build an image with Docker	33
7.3.2. Deploy your plugin on a cluster	33
7.3.3. Disabling your plugin in the browser	35

7.4. DYNAMIC PLUGIN EXAMPLE	35
7.4.1. Adding a tab to the pods page	35
7.5. DYNAMIC PLUGIN REFERENCE	37
7.5.1. Dynamic plugin extension types	37
console.action/filter	37
console.action/group	37
console.action/provider	38
console.action/resource-provider	38
console.alert-action	39
console.catalog/item-filter	39
console.catalog/item-metadata	39
console.catalog/item-provider	40
console.catalog/item-type	40
console.catalog/item-type-metadata	41
console.cluster-overview/inventory-item	41
console.cluster-overview/multiline-utilization-item	41
console.cluster-overview/utilization-item	42
console.context-provider	42
console.dashboards/card	43
console.dashboards/overview/activity/resource	43
console.dashboards/overview/detail/item	43
console.dashboards/overview/health/operator	44
console.dashboards/overview/health/prometheus	44
console.dashboards/overview/health/resource	45
console.dashboards/overview/health/url	46
console.dashboards/overview/inventory/item	46
console.dashboards/overview/inventory/item/group	47
console.dashboards/overview/inventory/item/replacement	47
console.dashboards/overview/prometheus/activity/resource	47
console.dashboards/project/overview/item	48
console.dashboards/tab	48
console.file-upload	49
console.flag	49
console.flag/hookProvider	49
console.flag/model	49
console.global-config	49
console.model-metadata	50
console.navigation/href	51
console.navigation/resource-cluster	52
console.navigation/resource-ns	53
console.navigation/section	54
console.navigation/separator	55
console.page/resource/details	55
console.page/resource/list	56
console.page/route	56
console.page/route/standalone	57
console.perspective	57
console.project-overview/inventory-item	58
console.project-overview/utilization-item	58
console.pvc/alert	59
console.pvc/create-prop	59
console.pvc/delete	59
console.pvc/status	59

console.redux-reducer	60
console.resource/create	60
console.storage-provider	60
console.tab/horizontalNav	61
console.telemetry/listener	61
console.topology/adapter/build	61
console.topology/adapter/network	61
console.topology/adapter/pod	62
console.topology/component/factory	62
console.topology/create/connector	62
console.topology/data/factory	62
console.topology/decorator/provider	63
console.topology/details/resource-alert	63
console.topology/details/resource-link	64
console.topology/details/tab	64
console.topology/details/tab-section	64
console.topology/display/filters	65
console.topology/relationship/provider	65
console.user-preference/group	66
console.user-preference/item	66
console.yaml-template	67
dev-console.add/action	67
dev-console.add/action-group	68
dev-console.import/environment	68
console.page/resource/tab	68
7.5.2. OpenShift Container Platform console API	69
useActivePerspective	69
GreenCheckCircleIcon	69
RedExclamationCircleIcon	70
YellowExclamationTriangleIcon	70
BlueInfoCircleIcon	70
ErrorStatus	71
InfoStatus	71
ProgressStatus	71
SuccessStatus	72
checkAccess	72
useAccessReview	72
useResolvedExtensions	72
HorizontalNav	73
VirtualizedTable	73
TableData	74
useActiveColumns	75
ListPageHeader	75
ListPageCreate	76
ListPageCreateLink	76
ListPageCreateButton	77
ListPageCreateDropdown	77
ListPageFilter	78
useListPageFilter	79
ResourceLink	79
ResourceIcon	80
useK8sModel	81
useK8sModels	81

useK8sWatchResource	81
useK8sWatchResources	81
consoleFetch	82
consoleFetchJSON	82
consoleFetchText	83
getConsoleRequestHeaders	83
k8sGetResource	83
k8sCreateResource	84
k8sUpdateResource	84
k8sPatchResource	85
k8sDeleteResource	85
k8sListResource	86
k8sListResourceItems	86
getAPIVersionForModel	86
getGroupVersionKindForResource	86
getGroupVersionKindForModel	87
StatusPopupSection	87
StatusPopupItem	87
Overview	88
OverviewGrid	88
InventoryItem	88
InventoryItemTitle	89
InventoryItemBody	89
InventoryItemStatus	89
InventoryItemLoading	90
useFlag	90
YAMLEditor	90
ResourceYAMLEditor	91
ResourceEventStream	92
usePrometheusPoll	92
Timestamp	93
useModal	93
ActionServiceProvider	93
NamespaceBar	94
ErrorBoundaryFallbackPage	94
PerspectiveContext	95
useAccessReviewAllowed	95
useSafetyFirst	95
7.5.3. Troubleshooting your dynamic plugin	96
CHAPTER 8. ABOUT THE WEB TERMINAL IN THE WEB CONSOLE	98
8.1. INSTALLING THE WEB TERMINAL	98
8.2. USING THE WEB TERMINAL	99
8.3. UNINSTALLING THE WEB TERMINAL	99
8.3.1. Removing the Web Terminal Operator and the custom resources that support it	100
8.3.2. Deleting the DevWorkspace Operator dependency	100
CHAPTER 9. DISABLING THE WEB CONSOLE IN OPENSIFT CONTAINER PLATFORM	104
9.1. PREREQUISITES	104
9.2. DISABLING THE WEB CONSOLE	104
CHAPTER 10. CREATING QUICK START TUTORIALS IN THE WEB CONSOLE	105
10.1. UNDERSTANDING QUICK STARTS	105
10.2. QUICK START USER WORKFLOW	105

10.3. QUICK START COMPONENTS	106
10.4. CONTRIBUTING QUICK STARTS	106
10.4.1. Viewing the quick start API documentation	107
10.4.2. Mapping the elements in the quick start to the quick start CR	107
10.4.2.1. conclusion element	107
10.4.2.2. description element	108
10.4.2.3. displayName element	109
10.4.2.4. durationMinutes element	110
10.4.2.5. icon element	111
10.4.2.6. introduction element	112
10.4.3. Adding a custom icon to a quick start	115
10.4.4. Limiting access to a quick start	115
10.4.5. Linking to other quick starts	115
10.4.6. Supported tags for quick starts	116
10.4.7. Quick start highlighting markdown reference	116
10.4.7.1. Perspective switcher	117
10.4.7.2. Administrator perspective navigation links	117
10.4.7.3. Developer perspective navigation links	117
10.4.7.4. Common navigation links	117
10.4.7.5. Masthead links	117
10.4.8. Code snippet markdown reference	117
10.4.8.1. Syntax for inline code snippets	118
10.4.8.2. Syntax for multi-line code snippets	118
10.5. QUICK START CONTENT GUIDELINES	118
10.5.1. Card copy	118
10.5.2. Introduction	118
10.5.3. Task steps	119
10.5.4. Check your work module	121
10.5.5. Formatting UI elements	121
10.6. ADDITIONAL RESOURCES	121

CHAPTER 1. WEB CONSOLE OVERVIEW

The Red Hat OpenShift Container Platform web console provides a graphical user interface to visualize your project data and perform administrative, management, and troubleshooting tasks. The web console runs as pods on the control plane nodes in the openshift-console project. It is managed by a **console-operator** pod. Both **Administrator** and **Developer** perspectives are supported.

Both **Administrator** and **Developer** perspectives enable you to create quick start tutorials for OpenShift Container Platform. A quick start is a guided tutorial with user tasks and is useful for getting oriented with an application, Operator, or other product offering.

1.1. ABOUT THE ADMINISTRATOR PERSPECTIVE IN THE WEB CONSOLE

The **Administrator** perspective enables you to view the cluster inventory, capacity, general and specific utilization information, and the stream of important events, all of which help you to simplify planning and troubleshooting tasks. Both project administrators and cluster administrators can view the **Administrator** perspective.

Cluster administrators can also open an embedded command line terminal instance with the web terminal Operator in OpenShift Container Platform 4.7 and later.



NOTE

The default web console perspective that is shown depends on the role of the user. The **Administrator** perspective is displayed by default if the user is recognized as an administrator.

The **Administrator** perspective provides workflows specific to administrator use cases, such as the ability to:

- Manage workload, storage, networking, and cluster settings.
- Install and manage Operators using the Operator Hub.
- Add identity providers that allow users to log in and manage user access through roles and role bindings.
- View and manage a variety of advanced settings such as cluster updates, partial cluster updates, cluster Operators, custom resource definitions (CRDs), role bindings, and resource quotas.
- Access and manage monitoring features such as metrics, alerts, and monitoring dashboards.
- View and manage logging, metrics, and high-status information about the cluster.
- Visually interact with applications, components, and services associated with the **Administrator** perspective in OpenShift Container Platform.

Additional resources


See [About the web terminal in the web console](#) for more information on the web terminal Operator.

1.2. ABOUT THE DEVELOPER PERSPECTIVE IN THE WEB CONSOLE

The **Developer** perspective offers several built-in ways to deploy applications, services, and databases. In the **Developer** perspective, you can:

- View real-time visualization of rolling and recreating rollouts on the component.
- View the application status, resource utilization, project event streaming, and quota consumption.
- Share your project with others.
- Troubleshoot problems with your applications by running Prometheus Query Language (PromQL) queries on your project and examining the metrics visualized on a plot. The metrics provide information about the state of a cluster and any user-defined workloads that you are monitoring.

Cluster administrators can also open an embedded command line terminal instance in the web console in OpenShift Container Platform 4.7 and later.



NOTE

The default web console perspective that is shown depends on the role of the user. The **Developer** perspective is displayed by default if the user is recognised as a developer.

The **Developer** perspective provides workflows specific to developer use cases, such as the ability to:

- Create and deploy applications on OpenShift Container Platform by importing existing codebases, images, and container files.
- Visually interact with applications, components, and services associated with them within a project and monitor their deployment and build status.
- Group components within an application and connect the components within and across applications.
- Integrate serverless capabilities (Technology Preview).
- Create workspaces to edit your application code using Eclipse Che.

You can use the **Topology** view to display applications, components, and workloads of your project. If you have no workloads in the project, the **Topology** view will show some links to create or import them. You can also use the **Quick Search** to import components directly.

Additional Resources

See [Viewing application composition using the Topology](#) view for more information on using the **Topology** view in **Developer** perspective.

1.3. ACCESSING THE PERSPECTIVES

You can access the **Administrator** and **Developer** perspective from the web console as follows:

Prerequisites

To access a perspective, ensure that you have logged in to the web console. Your default perspective is automatically determined by the permission of the users. The **Administrator** perspective is selected for users with access to all projects, while the **Developer** perspective is selected for users with limited

access to their own projects

Additional Resources

See [Adding User Preferences](#) for more information on changing perspectives.

Procedure

1. Use the perspective switcher to switch to the **Administrator** or **Developer** perspective.
2. Select an existing project from the **Project** drop-down list. You can also create a new project from this dropdown.



NOTE

You can use the perspective switcher only as **cluster-admin**.

Additional resources

- [Learn more about Cluster Administrator](#)
- [Overview of the **Administrator** perspective](#)
- [Creating and deploying applications on OpenShift Container Platform using the **Developer** perspective](#)
- [Viewing the applications in your project, verifying their deployment status, and interacting with them in the **Topology** view](#)
- [Viewing cluster information](#)
- [Configuring the web console](#)
- [Customizing the web console](#)
- [Launching an embedded command line terminal instance in the web console](#)
- [Creating quick start tutorials](#)
- [Disabling the web console](#)

CHAPTER 2. ACCESSING THE WEB CONSOLE

The OpenShift Container Platform web console is a user interface accessible from a web browser. Developers can use the web console to visualize, browse, and manage the contents of projects.

2.1. PREREQUISITES

- JavaScript must be enabled to use the web console. For the best experience, use a web browser that supports [WebSockets](#).
- Review the [OpenShift Container Platform 4.x Tested Integrations](#) page before you create the supporting infrastructure for your cluster.

2.2. UNDERSTANDING AND ACCESSING THE WEB CONSOLE

The web console runs as a pod on the master. The static assets required to run the web console are served by the pod. After OpenShift Container Platform is successfully installed using **openshift-install create cluster**, find the URL for the web console and login credentials for your installed cluster in the CLI output of the installation program. For example:

Example output

```
INFO Install complete!
INFO Run 'export KUBECONFIG=<your working directory>/auth/kubeconfig' to manage the cluster
with 'oc', the OpenShift CLI.
INFO The cluster is ready when 'oc login -u kubeadmin -p <provided>' succeeds (wait a few minutes).
INFO Access the OpenShift web-console here: https://console-openshift-
console.apps.demo1.openshift4-beta-abcorp.com
INFO Login to the console with user: kubeadmin, password: <provided>
```


Use those details to log in and access the web console.

For existing clusters that you did not install, you can use **oc whoami --show-console** to see the web console URL.

2.3. MULTICLUSTER CONSOLE

The multicluster console provides a single interface with consistent design for the hybrid cloud console. If you enable the feature, you can switch between Advanced Cluster Management (ACM) and the cluster console in the same browser tab. It provides a simplified and consistent design that allows for shared components.

2.3.1. Enabling multicluster in the web console



IMPORTANT

Multicluster console is a Technology Preview feature only. Technology Preview features are not supported with Red Hat production service level agreements (SLAs) and might not be functionally complete. Red Hat does not recommend using them in production. These features provide early access to upcoming product features, enabling customers to test functionality and provide feedback during the development process.

For more information about the support scope of Red Hat Technology Preview features, see <https://access.redhat.com/support/offerings/techpreview/>.

Prerequisites

- Your cluster must be using the latest version of OpenShift Container Platform.
- You must have [Red Hat Advanced Cluster Management \(ACM\) for Kubernetes 2.5](#) or the [multicluster engine \(MCE\) Operator](#) installed.
- You must have administrator privileges.



WARNING

Do not set this feature gate on production clusters. You will not be able to upgrade your cluster after applying the feature gate, and it cannot be undone.

Procedure

1. Log in to the OpenShift Container Platform web console using your credentials.
2. Enable ACM in the administrator perspective by navigating from **Administration** → **Cluster Settings** → **Configuration** → **Console console.operator.openshift.io** → **Console Plugins** and click **Enable** for **acm**.
3. A pop-up window will appear notifying you that updating the enablement of this console plugin will prompt for the console to be refreshed once it has been updated. Select **Enable** and click **Save**.
4. Repeat the previous two steps for the **mce** console plugin immediately after enabling **acm**.
5. A pop-up window that states that a web console update is available will appear a few moments after you enable. Click **Refresh the web console** in the pop-up window to update.



NOTE


You might see the pop-up window to refresh the web console twice if the second redeployment has not occurred by the time you click **Refresh the web console**.

- **local-cluster** and **All Clusters** is now visible above the perspectives in the navigation section.

6. Enable the feature gate by navigating from **Administration** → **Cluster Settings** → **Configuration** → **FeatureGate**, and edit the YAML template as follows:

```
spec:  
  featureSet: TechPreviewNoUpgrade
```

7. Click **Save** to enable the multicluster console for all clusters.



IMPORTANT

After you save, this feature is enabled and cannot be undone.

Additional resources

- [Enabling feature sets using the web console](#)

CHAPTER 3. USING THE OPENSIFT CONTAINER PLATFORM DASHBOARD TO GET CLUSTER INFORMATION

Access the OpenShift Container Platform dashboard, which captures high-level information about the cluster, by navigating to **Home** → **Dashboards** → **Overview** from the OpenShift Container Platform web console.

The OpenShift Container Platform dashboard provides various cluster information, captured in individual dashboard cards.

3.1. ABOUT THE OPENSIFT CONTAINER PLATFORM DASHBOARDS PAGE

The OpenShift Container Platform dashboard consists of the following cards:

- **Details** provides a brief overview of informational cluster details. Status include **ok**, **error**, **warning**, **in progress**, and **unknown**. Resources can add custom status names.
 - Cluster ID
 - Provider
 - Version
- **Cluster Inventory** details number of resources and associated statuses. It is helpful when intervention is required to resolve problems, including information about:
 - Number of nodes
 - Number of pods
 - Persistent storage volume claims
 - Bare metal hosts in the cluster, listed according to their state (only available in **metal3** environment).
- **Cluster Capacity** charts help administrators understand when additional resources are required in the cluster. The charts contain an inner ring that displays current consumption, while an outer ring displays thresholds configured for the resource, including information about:
 - CPU time
 - Memory allocation
 - Storage consumed
 - Network resources consumed
- **Cluster Utilization** shows the capacity of various resources over a specified period of time, to help administrators understand the scale and frequency of high resource consumption.
- **Events** lists messages related to recent activity in the cluster, such as pod creation or virtual machine migration to another host.

- **Top Consumers** helps administrators understand how cluster resources are consumed. Click on a resource to jump to a detailed page listing pods and nodes that consume the largest amount of the specified cluster resource (CPU, memory, or storage).

CHAPTER 4. ADDING USER PREFERENCES

You can change the default preferences for your profile to meet your requirements. You can set your default project, topology view (graph or list), editing medium (form or YAML), language preferences, and resource type.

The changes made to the user preferences are automatically saved.

4.1. SETTING USER PREFERENCES

You can set the default user preferences for your cluster.

Procedure

1. Log in to the OpenShift Container Platform web console using your login credentials.
2. Use the masthead to access the user preferences under the user profile.
3. In the **General** section:
 - a. In the **Perspective** field, you can set the default perspective you want to be logged in to. You can select the **Administrator** or the **Developer** perspective as required. If a perspective is not selected, you are logged into the perspective you last visited.
 - b. In the **Project** field, select a project you want to work in. The console will default to the project every time you log in.
 - c. In the **Topology** field, you can set the topology view to default to the graph or list view. If not selected, the console defaults to the last view you used.
 - d. In the **Create/Edit resource method** field, you can set a preference for creating or editing a resource. If both the form and YAML options are available, the console defaults to your selection.
4. In the **Language** section, select **Default browser language** to use the default browser language settings. Otherwise, select the language that you want to use for the console.
5. In the **Applications** section:
 - a. You can view the default **Resource type**. For example, if the OpenShift Serverless Operator is installed, the default resource type is **Serverless Deployment**. Otherwise, the default resource type is **Deployment**.
 - b. You can select another resource type to be the default resource type from the **Resource Type** field.

CHAPTER 5. CONFIGURING THE WEB CONSOLE IN OPENSHIFT CONTAINER PLATFORM

You can modify the OpenShift Container Platform web console to set a logout redirect URL or disable the console.

5.1. PREREQUISITES

- Deploy an OpenShift Container Platform cluster.

5.2. CONFIGURING THE WEB CONSOLE

You can configure the web console settings by editing the **console.config.openshift.io** resource.

- Edit the **console.config.openshift.io** resource:

```
$ oc edit console.config.openshift.io cluster
```

The following example displays the sample resource definition for the console:

```
apiVersion: config.openshift.io/v1
kind: Console
metadata:
  name: cluster
spec:
  authentication:
    logoutRedirect: "" 1
status:
  consoleURL: "" 2
```

- 1 Specify the URL of the page to load when a user logs out of the web console. If you do not specify a value, the user returns to the login page for the web console. Specifying a **logoutRedirect** URL allows your users to perform single logout (SLO) through the identity provider to destroy their single sign-on session.
- 2 The web console URL. To update this to a custom value, see **Customizing the web console URL**.

CHAPTER 6. CUSTOMIZING THE WEB CONSOLE IN OPENSHIFT CONTAINER PLATFORM

You can customize the OpenShift Container Platform web console to set a custom logo, product name, links, notifications, and command line downloads. This is especially helpful if you need to tailor the web console to meet specific corporate or government requirements.

6.1. ADDING A CUSTOM LOGO AND PRODUCT NAME

You can create custom branding by adding a custom logo or custom product name. You can set both or one without the other, as these settings are independent of each other.

Prerequisites

- You must have administrator privileges.
- Create a file of the logo that you want to use. The logo can be a file in any common image format, including GIF, JPG, PNG, or SVG, and is constrained to a **max-height** of **60px**.

Procedure

1. Import your logo file into a config map in the **openshift-config** namespace:

```
$ oc create configmap console-custom-logo --from-file /path/to/console-custom-logo.png -n openshift-config
```

TIP

You can alternatively apply the following YAML to create the config map:

```
apiVersion: v1
kind: ConfigMap
metadata:
  name: console-custom-logo
  namespace: openshift-config
binaryData:
  console-custom-logo.png: <base64-encoded_logo> ... 1
```

1

Provide a valid base64-encoded logo.

2. Edit the web console's Operator configuration to include **customLogoFile** and **customProductName**:

```
$ oc edit consoles.operator.openshift.io cluster
```

```
apiVersion: operator.openshift.io/v1
kind: Console
metadata:
  name: cluster
spec:
  customization:
    customLogoFile:
```

```
key: console-custom-logo.png
name: console-custom-logo
customProductName: My Console
```

Once the Operator configuration is updated, it will sync the custom logo config map into the console namespace, mount it to the console pod, and redeploy.

3. Check for success. If there are any issues, the console cluster Operator will report a **Degraded** status, and the console Operator configuration will also report a **CustomLogoDegraded** status, but with reasons like **KeyOrFilenameInvalid** or **NoImageProvided**.

To check the **clusteroperator**, run:

```
$ oc get clusteroperator console -o yaml
```

To check the console Operator configuration, run:

```
$ oc get consoles.operator.openshift.io -o yaml
```

6.2. CREATING CUSTOM LINKS IN THE WEB CONSOLE

Prerequisites

- You must have administrator privileges.

Procedure

1. From **Administration** → **Custom Resource Definitions**, click on **ConsoleLink**.
2. Select **Instances** tab
3. Click **Create Console Link** and edit the file:

```
apiVersion: console.openshift.io/v1
kind: ConsoleLink
metadata:
  name: example
spec:
  href: 'https://www.example.com'
  location: HelpMenu 1
  text: Link 1
```

- 1** Valid location settings are **HelpMenu**, **UserMenu**, **ApplicationMenu**, and **NamespaceDashboard**.

To make the custom link appear in all namespaces, follow this example:

```
apiVersion: console.openshift.io/v1
kind: ConsoleLink
metadata:
  name: namespaced-dashboard-link-for-all-namespaces
spec:
```

```
href: 'https://www.example.com'
location: NamespaceDashboard
text: This appears in all namespaces
```

To make the custom link appear in only some namespaces, follow this example:

```
apiVersion: console.openshift.io/v1
kind: ConsoleLink
metadata:
  name: namespaced-dashboard-for-some-namespaces
spec:
  href: 'https://www.example.com'
  location: NamespaceDashboard
  # This text will appear in a box called "Launcher" under "namespace" or "project" in the web
  console
  text: Custom Link Text
  namespaceDashboard:
    namespaces:
      # for these specific namespaces
      - my-namespace
      - your-namespace
      - other-namespace
```

To make the custom link appear in the application menu, follow this example:

```
apiVersion: console.openshift.io/v1
kind: ConsoleLink
metadata:
  name: application-menu-link-1
spec:
  href: 'https://www.example.com'
  location: ApplicationMenu
  text: Link 1
  applicationMenu:
    section: My New Section
    # image that is 24x24 in size
    imageURL: https://via.placeholder.com/24
```

4. Click **Save** to apply your changes.

6.3. CUSTOMIZING CONSOLE ROUTES

For **console** and **downloads** routes, custom routes functionality uses the **ingress** config route configuration API. If the **console** custom route is set up in both the **ingress** config and **console-operator** config, then the new **ingress** config custom route configuration takes precedent. The route configuration with the **console-operator** config is deprecated.

6.3.1. Customizing the console route

You can customize the console route by setting the custom hostname and TLS certificate in the **spec.componentRoutes** field of the cluster **Ingress** configuration.

Prerequisites

- You have logged in to the cluster as a user with administrative privileges.
- You have created a secret in the **openshift-config** namespace containing the TLS certificate and key. This is required if the domain for the custom hostname suffix does not match the cluster domain suffix. The secret is optional if the suffix matches.

TIP

You can create a TLS secret by using the **oc create secret tls** command.

Procedure

1. Edit the cluster **Ingress** configuration:

```
$ oc edit ingress.config.openshift.io cluster
```

2. Set the custom hostname and optionally the serving certificate and key:

```
apiVersion: config.openshift.io/v1
kind: Ingress
metadata:
  name: cluster
spec:
  componentRoutes:
    - name: console
      namespace: openshift-console
      hostname: <custom_hostname> 1
      servingCertKeyPairSecret:
        name: <secret_name> 2
```

1

The custom hostname.

2

Reference to a secret in the **openshift-config** namespace that contains a TLS certificate (**tls.crt**) and key (**tls.key**). This is required if the domain for the custom hostname suffix does not match the cluster domain suffix. The secret is optional if the suffix matches.

3. Save the file to apply the changes.

6.3.2. Customizing the download route

You can customize the download route by setting the custom hostname and TLS certificate in the **spec.componentRoutes** field of the cluster **Ingress** configuration.

Prerequisites

- You have logged in to the cluster as a user with administrative privileges.
- You have created a secret in the **openshift-config** namespace containing the TLS certificate and key. This is required if the domain for the custom hostname suffix does not match the cluster domain suffix. The secret is optional if the suffix matches.

TIP

You can create a TLS secret by using the **oc create secret tls** command.

Procedure

1. Edit the cluster **Ingress** configuration:

```
$ oc edit ingress.config.openshift.io cluster
```

2. Set the custom hostname and optionally the serving certificate and key:

```
apiVersion: config.openshift.io/v1
kind: Ingress
metadata:
  name: cluster
spec:
  componentRoutes:
    - name: downloads
      namespace: openshift-console
      hostname: <custom_hostname> 1
  servingCertKeyPairSecret:
    name: <secret_name> 2
```

1

The custom hostname.


2

Reference to a secret in the **openshift-config** namespace that contains a TLS certificate (**tls.crt**) and key (**tls.key**). This is required if the domain for the custom hostname suffix does not match the cluster domain suffix. The secret is optional if the suffix matches.

3. Save the file to apply the changes.

6.4. CUSTOMIZING THE LOGIN PAGE

Create Terms of Service information with custom login pages. Custom login pages can also be helpful if you use a third-party login provider, such as GitHub or Google, to show users a branded page that they trust and expect before being redirected to the authentication provider. You can also render custom error pages during the authentication process.

**NOTE**

Customizing the error template is limited to identity providers (IDPs) that use redirects, such as request header and OIDC-based IDPs. It does not have an effect on IDPs that use direct password authentication, such as LDAP and htpasswd.

Prerequisites

- You must have administrator privileges.

Procedure

1. Run the following commands to create templates you can modify:

```
$ oc adm create-login-template > login.html
```

```
$ oc adm create-provider-selection-template > providers.html
```

```
$ oc adm create-error-template > errors.html
```

2. Create the secrets:

```
$ oc create secret generic login-template --from-file=login.html -n openshift-config
```

```
$ oc create secret generic providers-template --from-file=providers.html -n openshift-config
```

```
$ oc create secret generic error-template --from-file=errors.html -n openshift-config
```

3. Run:

```
$ oc edit oauths cluster
```

4. Update the specification:

```
spec:
  templates:
    error:
      name: error-template
    login:
      name: login-template
    providerSelection:
      name: providers-template
```

Run **oc explain oauths.spec.templates** to understand the options.

6.5. DEFINING A TEMPLATE FOR AN EXTERNAL LOG LINK

If you are connected to a service that helps you browse your logs, but you need to generate URLs in a particular way, then you can define a template for your link.

Prerequisites

- You must have administrator privileges.

Procedure

1. From **Administration** → **Custom Resource Definitions**, click on **ConsoleExternalLogLink**.
2. Select **Instances** tab
3. Click **Create Console External Log Link** and edit the file:

```
apiVersion: console.openshift.io/v1
kind: ConsoleExternalLogLink
metadata:
```

```

name: example
spec:
  hrefTemplate: >-
    https://example.com/logs?
resourceName=${resourceName}&containerName=${containerName}&resourceNamespace=${
resourceNamespace}&podLabels=${podLabels}
  text: Example Logs

```

6.6. CREATING CUSTOM NOTIFICATION BANNERS

Prerequisites

- You must have administrator privileges.

Procedure

1. From **Administration** → **Custom Resource Definitions**, click on **ConsoleNotification**.
2. Select **Instances** tab
3. Click **Create Console Notification** and edit the file:

```

apiVersion: console.openshift.io/v1
kind: ConsoleNotification
metadata:
  name: example
spec:
  text: This is an example notification message with an optional link.
  location: BannerTop 1
  link:
    href: 'https://www.example.com'
    text: Optional link text
  color: '#fff'
  backgroundColor: '#0088ce'

```

- 1** Valid location settings are **BannerTop**, **BannerBottom**, and **BannerTopBottom**.

4. Click **Create** to apply your changes.

6.7. CUSTOMIZING CLI DOWNLOADS

You can configure links for downloading the CLI with custom link text and URLs, which can point directly to file packages or to an external page that provides the packages.

Prerequisites

- You must have administrator privileges.

Procedure

1. Navigate to **Administration** → **Custom Resource Definitions**
2. Select **ConsoleCLIDownload** from the list of Custom Resource Definitions (CRDs).

3. Click the **YAML** tab, and then make your edits:

```
apiVersion: console.openshift.io/v1
kind: ConsoleCLIDownload
metadata:
  name: example-cli-download-links-for-foo
spec:
  description: |
    This is an example of download links for foo
  displayName: example-foo
  links:
    - href: 'https://www.example.com/public/foo.tar'
      text: foo for linux
    - href: 'https://www.example.com/public/foo.mac.zip'
      text: foo for mac
    - href: 'https://www.example.com/public/foo.win.zip'
      text: foo for windows
```

4. Click the **Save** button.

6.8. ADDING YAML EXAMPLES TO KUBERNETES RESOURCES

You can dynamically add YAML examples to any Kubernetes resources at any time.

Prerequisites

- You must have cluster administrator privileges.

Procedure

1. From **Administration** → **Custom Resource Definitions**, click on **ConsoleYAMLSample**.
2. Click **YAML** and edit the file:

```
apiVersion: console.openshift.io/v1
kind: ConsoleYAMLSample
metadata:
  name: example
spec:
  targetResource:
    apiVersion: batch/v1
    kind: Job
  title: Example Job
  description: An example Job YAML sample
  yaml: |
    apiVersion: batch/v1
    kind: Job
    metadata:
      name: countdown
    spec:
      template:
        metadata:
          name: countdown
        spec:
          containers:
```

```
- name: counter
  image: centos:7
  command:
    - "bin/bash"
    - "-c"
    - "for i in 9 8 7 6 5 4 3 2 1 ; do echo $i ; done"
  restartPolicy: Never
```

Use **spec.snippet** to indicate that the YAML sample is not the full YAML resource definition, but a fragment that can be inserted into the existing YAML document at the user's cursor.

3. Click **Save**.

6.9. CUSTOMIZING USER PERSPECTIVES

The OpenShift Container Platform web console provides two perspectives by default, **Administrator** and **Developer**. You might have more perspectives available depending on installed console plugins. As a cluster administrator, you can show or hide a perspective for all users or for a specific user role. Customizing perspectives ensures that users can view only the perspectives that are applicable to their role and tasks. For example, you can hide the **Administrator** perspective from unprivileged users so that they cannot manage cluster resources, users, and projects. Similarly, you can show the **Developer** perspective to users with the developer role so that they can create, deploy, and monitor applications.

You can also customize the perspective visibility for users based on role-based access control (RBAC). For example, if you customize a perspective for monitoring purposes, which requires specific permissions, you can define that the perspective is visible only to users with required permissions.

Each perspective includes the following mandatory parameters, which you can edit in the YAML view:

- **id**: Defines the ID of the perspective to show or hide
- **visibility**: Defines the state of the perspective along with access review checks, if needed
- **state**: Defines whether the perspective is enabled, disabled, or needs an access review check



NOTE

By default, all perspectives are enabled. When you customize the user perspective, your changes are applicable to the entire cluster.

6.9.1. Customizing a perspective using YAML view

Prerequisites

- You must have administrator privileges.

Procedure

1. In the **Administrator** perspective, navigate to **Administration → Cluster Settings**.
2. Select the **Configuration** tab and click the **Console (operator.openshift.io)** resource.
3. Click the **YAML** tab and make your customization:

- a. To enable or disable a perspective, insert the snippet for **Add user perspectives** and edit the YAML code as needed:

```
apiVersion: operator.openshift.io/v1
kind: Console
metadata:
  name: cluster
spec:
  customization:
    perspectives:
      - id: admin
        visibility:
          state: Enabled
      - id: dev
        visibility:
          state: Enabled
```

- b. To hide a perspective based on RBAC permissions, insert the snippet for **Hide user perspectives** and edit the YAML code as needed:

```
apiVersion: operator.openshift.io/v1
kind: Console
metadata:
  name: cluster
spec:
  customization:
    perspectives:
      - id: admin
        requiresAccessReview:
          - group: rbac.authorization.k8s.io
            resource: clusterroles
            verb: list
      - id: dev
        state: Enabled
```

- c. To customize a perspective based on your needs, create your own YAML snippet:

```
apiVersion: operator.openshift.io/v1
kind: Console
metadata:
  name: cluster
spec:
  customization:
    perspectives:
      - id: admin
        visibility:
          state: AccessReview
        accessReview:
          missing:
            - resource: deployment
              verb: list
          required:
            - resource: namespaces
              verb: list
```

```
- id: dev
visibility:
state: Enabled
```

4. Click **Save**.


6.9.2. Customizing a perspective using form view

Prerequisites

- You must have administrator privileges.

Procedure

1. In the **Administrator** perspective, navigate to **Administration → Cluster Settings**.
2. Select the **Configuration** tab and click the **Console (operator.openshift.io)** resource.
3. Click **Actions → Customize** on the right side of the page.
4. In the **General** settings, customize the perspective by selecting one of the following options from the dropdown list:
 - **Enabled:** Enables the perspective for all users
 - **Only visible for privileged users:** Enables the perspective for users who can list all namespaces
 - **Only visible for unprivileged users:** Enables the perspective for users who cannot list all namespaces
 - **Disabled:** Disables the perspective for all users
 A notification opens to confirm that your changes are saved.



NOTE

When you customize the user perspective, your changes are automatically saved and take effect after a browser refresh.

6.10. DEVELOPER CATALOG AND SUB-CATALOG CUSTOMIZATION

As a cluster administrator, you have the ability to organize and manage the Developer catalog or its sub-catalogs. You can enable or disable the sub-catalog types or disable the entire developer catalog.

The **developerCatalog.types** object includes the following parameters that you must define in a snippet to use them in the YAML view:

- **state**: Defines if a list of developer catalog types should be enabled or disabled.
- **enabled**: Defines a list of developer catalog types (sub-catalogs) that are visible to users.
- **disabled**: Defines a list of developer catalog types (sub-catalogs) that are not visible to users.

You can enable or disable the following developer catalog types (sub-catalogs) using the YAML view or the form view.

- **Builder Images**
- **Templates**
- **Devfiles**
- **Samples**
- **Helm Charts**
- **Event Sources**
- **Event Sinks**
- **Operator Backed**

6.10.1. Customizing a developer catalog or its sub-catalogs using the YAML view

You can customize a developer catalog by editing the YAML content in the YAML view.

Prerequisites

- An OpenShift web console session with cluster administrator privileges.

Procedure

1. In the **Administrator** perspective of the web console, navigate to **Administration → Cluster Settings**.
2. Select the **Configuration** tab, click the **Console (operator.openshift.io)** resource and view the **Details** page.
3. Click the **YAML** tab to open the editor and edit the YAML content as needed.
For example, to disable a developer catalog type, insert the following snippet that defines a list of disabled developer catalog resources:

```
apiVersion: operator.openshift.io/v1
kind: Console
metadata:
  name: cluster
...
spec:
  customization:
    developerCatalog:
```



```
categories:
types:
  state: Disabled
  disabled:
    - BuilderImage
    - Devfile
    - HelmChart
  ...
```

4. Click **Save**.



NOTE

By default, the developer catalog types are enabled in the Administrator view of the Web Console.

6.10.2. Customizing a developer catalog or its sub-catalogs using the form view

You can customize a developer catalog by using the form view in the Web Console.

Prerequisites

- An OpenShift web console session with cluster administrator privileges.

Procedure

1. In the **Administrator** perspective, navigate to **Administration → Cluster Settings**.
2. Select the **Configuration** tab and click the **Console (operator.openshift.io)** resource.
3. Click **Actions → Customize**.
4. In the respective sections, enable or disable the items in the list.

Verification

After you have customized the developer catalog, your changes are automatically saved in the system and take effect in the browser after a refresh.



Saved.

This config update requires a console rollout, this can take up to a minute and require a browser refresh.



NOTE

You can use a similar procedure to customize Web UI items such as Quick starts, Cluster roles, and Actions.

6.10.2.1. Example YAML file changes

You can dynamically add the following snippets in the YAML editor for customizing a developer catalog.

Use the following snippet to display all the sub-catalogs by setting the *state* type to **Enabled**.

```
apiVersion: operator.openshift.io/v1
kind: Console
metadata:
  name: cluster
...
spec:
  customization:
    developerCatalog:
      categories:
      types:
      state: Enabled
```

Use the following snippet to disable all sub-catalogs by setting the *state* type to **Disabled**:

```
apiVersion: operator.openshift.io/v1
kind: Console
metadata:
  name: cluster
...
spec:
  customization:
    developerCatalog:
      categories:
      types:
      state: Disabled
```

Use the following snippet when a cluster administrator defines a list of sub-catalogs, which are enabled in the Web Console.

```
apiVersion: operator.openshift.io/v1
kind: Console
metadata:
  name: cluster
...
spec:
  customization:
    developerCatalog:
      categories:
      types:
      state: Enabled
      enabled:
        - BuilderImage
        - Devfile
        - HelmChart
        - ...
```

CHAPTER 7. DYNAMIC PLUGINS

7.1. OVERVIEW OF DYNAMIC PLUGINS

7.1.1. About dynamic plugins

A dynamic plugin allows you to add custom pages and other extensions to your interface at runtime. The **ConsolePlugin** custom resource registers plugins with the console, and a cluster administrator enables plugins in the **console-operator** configuration.

7.1.2. Key features

A dynamic plugin allows you to make the following customizations to the OpenShift Container Platform experience:

- Add custom pages.
- Add perspectives beyond administrator and developer.
- Add navigation items.
- Add tabs and actions to resource pages.

7.1.3. General guidelines

When creating your plugin, follow these general guidelines:

- **Node.js** and **yarn** are required to build and run your plugin.
- Prefix your CSS class names with your plugin name to avoid collisions. For example, **my-plugin__heading** and **my-plugin__icon**.
- Maintain a consistent look, feel, and behavior with other console pages.
- Follow [react-i18next](#) localization guidelines when creating your plugin. You can use the **useTranslation** hook like the one in the following example:

```
const Header: React.FC = () => {
  const { t } = useTranslation('plugin__console-demo-plugin');
  return <h1>{t('Hello, World!')}</h1>;
};
```

- Avoid selectors that could affect markup outside of your plugins components, such as element selectors. These are not APIs and are subject to change. Using them might break your plugin. Avoid selectors like element selectors that could affect markup outside of your plugins components.

PatternFly 4 guidelines

When creating your plugin, follow these guidelines for using PatternFly:

- Use [PatternFly4](#) components and PatternFly CSS variables. Core PatternFly components are available through the SDK. Using PatternFly components and variables help your plugin look consistent in future console versions.

- Make your plugin accessible by following [PatternFly's accessibility fundamentals](#).
- Avoid using other CSS libraries such as Bootstrap or Tailwind. They can conflict with PatternFly and will not match the console look and feel.

7.2. GETTING STARTED WITH DYNAMIC PLUGINS

To get started using the dynamic plugin, you must set up your environment to write a new OpenShift Container Platform dynamic plugin. For an example of how to write a new plugin, see [Adding a tab to the pods page](#).

7.2.1. Dynamic plugin development

You can run the plugin using a local development environment. The OpenShift Container Platform web console runs in a container connected to the cluster you have logged into.

Prerequisites

- You must have an OpenShift cluster running.
- You must have the OpenShift CLI (**oc**) installed.
- You must have [yarn](#) installed.
- You must have [Docker](#) v3.2.0 or newer or [Podman](#) installed and running.

Procedure

1. In your terminal, run the following command to install the dependencies for your plugin using yarn.

```
$ yarn install
```

2. After installing, run the following command to start yarn.

```
$ yarn run start
```

3. In another terminal window, login to the OpenShift Container Platform through the CLI.

```
$ oc login
```

4. Run the OpenShift Container Platform web console in a container connected to the cluster you have logged into by running the following command:

```
$ yarn run start-console
```

Verification

- Visit localhost:9000 to view the running plugin. Inspect the value of **window.SERVER_FLAGS.consolePlugins** to see the list of plugins which load at runtime.

7.3. DEPLOY YOUR PLUGIN ON A CLUSTER

You can deploy the plugin to a OpenShift Container Platform cluster.

7.3.1. Build an image with Docker

To deploy your plugin on a cluster, you need to build an image and push it to an image registry.

Procedure

1. Build the image with the following command:

```
$ docker build -t quay.io/my-repository/my-plugin:latest .
```

2. Optional: If you want to test your image, run the following command:

```
$ docker run -it --rm -d -p 9001:80 quay.io/my-repository/my-plugin:latest
```

3. Push the image by running the following command:

```
$ docker push quay.io/my-repository/my-plugin:latest
```

7.3.2. Deploy your plugin on a cluster

After pushing an image with your changes to a registry, you can deploy the plugin to a cluster.

Procedure

1. To deploy your plugin to a cluster, install a Helm chart with the name of the plugin as the Helm release name into a new namespace or an existing namespace as specified by the **-n** command-line option. Provide the location of the image within the **plugin.image** parameter by using the following command:

```
$ helm upgrade -i my-plugin charts/openshift-console-plugin -n my-plugin-namespace --create-namespace --set plugin.image=my-plugin-image-location
```

Where:

n <my-plugin-namespace>

Specifies an existing namespace to deploy your plugin into.

--create-namespace

Optional: If deploying to a new namespace, use this parameter.

--set plugin.image=my-plugin-image-location

Specifies the location of the image within the **plugin.image** parameter.

2. Optional: You can specify any additional parameters by using the set of supported parameters in the **charts/openshift-console-plugin/values.yaml** file.

```
plugin:
  name: ""
  description: ""
  image: ""
  imagePullPolicy: IfNotPresent
```

```

replicas: 2
port: 9443
securityContext:
  enabled: true
podSecurityContext:
  enabled: true
  runAsNonRoot: true
  seccompProfile:
    type: RuntimeDefault
containerSecurityContext:
  enabled: true
  allowPrivilegeEscalation: false
capabilities:
  drop:
    - ALL
resources:
  requests:
    cpu: 10m
    memory: 50Mi
basePath: /
certificateSecretName: ""
serviceAccount:
  create: true
  annotations: {}
  name: ""
patcherServiceAccount:
  create: true
  annotations: {}
  name: ""
jobs:
  patchConsoles:
    enabled: true
    image: "registry.redhat.io/openshift4/ose-tools-
rhel8@sha256:e44074f21e0cca6464e50cb6ff934747e0bd11162ea01d522433a1a1ae116103"
  podSecurityContext:
    enabled: true
    runAsNonRoot: true
    seccompProfile:
      type: RuntimeDefault
  containerSecurityContext:
    enabled: true
    allowPrivilegeEscalation: false
  capabilities:
    drop:
      - ALL
  resources:
    requests:
      cpu: 10m
      memory: 50Mi

```

Verification

You can see the list of the enabled plugins on the **Overview** page or by navigating from **Administration** → **Cluster Settings** → **Configuration** → **Console operator.openshift.io** → **Console plugins**.

**NOTE**

It can take a few minutes for the new plugin configuration to appear. If you do not see your plugin, you might need to refresh your browser if the plugin was recently enabled. If you receive any errors at runtime, check the JS console in browser developer tools to look for any errors in your plugin code.

7.3.3. Disabling your plugin in the browser

Console users can use the **disable-plugins** query parameter to disable specific or all dynamic plugins that would normally get loaded at run-time.

Procedure

- To disable a specific plugin(s), remove the plugin you want to disable from the comma-separated list of plugin names.
- To disable all plugins, leave an empty string in the **disable-plugins** query parameter.

**NOTE**

Cluster administrators can disable plugins in the **Cluster Settings** page of the web console

7.4. DYNAMIC PLUGIN EXAMPLE

Before working through the example, verify that the plugin is working by following the steps in [Dynamic plugin development](#)

7.4.1. Adding a tab to the pods page


There are different customizations you can make to the OpenShift Container Platform web console. The following procedure adds a tab to the **Pod details** page as an example extension to your plugin.

**NOTE**

The OpenShift Container Platform web console runs in a container connected to the cluster you have logged into. See "Dynamic plugin development" for information to test the plugin before creating your own.

Procedure

1. Visit the [console-plugin-template](#) repository containing a template for creating plugins in a new tab.

**IMPORTANT**

Custom plugin code is not supported by Red Hat. Only [Cooperative community support](#) is available for your plugin.

2. Select the **Use this template** dropdown button and select **Create new repository** from the dropdown list to create a GitHub repository.

3. Re-name the new repository with the name of your plugin.
4. Clone your copied repository to your local machine so you can edit the code.
5. Edit the plugin metadata in the **consolePlugin** declaration of **package.json**.

```
"consolePlugin": {
  "name": "my-plugin", 1
  "version": "0.0.1", 2
  "displayName": "My Plugin", 3
  "description": "Enjoy this shiny, new console plugin!", 4
  "exposedModules": {
    "ExamplePage": "./components/ExamplePage"
  },
  "dependencies": {
    "@console/pluginAPI": "/"
  }
}
```

- 1 Update the name of your plugin.
- 2 Update the version.
- 3 Update the display name for your plugin.
- 4 Update the description with a synopsis about your plugin.

6. Add the following to the **console-extensions.json** file:

```
{
  "type": "console.tab/horizontalNav",
  "properties": {
    "page": {
      "name": "Example Tab",
      "href": "example"
    },
    "model": {
      "group": "core",
      "version": "v1",
      "kind": "Pod"
    },
    "component": { "$codeRef": "ExampleTab" }
  }
}
```

7. Edit the **package.json** file to include the following changes:

```
"exposedModules": {
  "ExamplePage": "./components/ExamplePage",
  "ExampleTab": "./components/ExampleTab"
}
```

8. Write a message to display on a new custom tab on the **Pods** page by creating a new file **src/components/ExampleTab.tsx** and adding the following script:


```
import * as React from 'react';

export default function ExampleTab() {
  return (
    <p>This is a custom tab added to a resource using a dynamic plugin.</p>
  );
}
```

Verification

- Visit a **Pod** page to view the added tab.

7.5. DYNAMIC PLUGIN REFERENCE

You can add extensions that allow you to customize your plugin. Those extensions are then loaded to the console at run-time.

7.5.1. Dynamic plugin extension types

console.action/filter

ActionFilter can be used to filter an action.

Name	Value Type	Optional	Description
contextId	string	no	The context ID helps to narrow the scope of contributed actions to a particular area of the application. Examples include topology and helm .
filter	CodeRef<(scope: any, action: Action) ⇒ boolean>	no	A function that will filter actions based on some conditions. scope : The scope in which actions should be provided for. A hook might be required if you want to remove the ModifyCount action from a deployment with a horizontal pod autoscaler (HPA).

console.action/group

ActionGroup contributes an action group that can also be a submenu.

Name	Value Type	Optional	Description
------	------------	----------	-------------

Name	Value Type	Optional	Description
id	string	no	ID used to identify the action section.
label	string	yes	The label to display in the UI. Required for submenus.
submenu	boolean	yes	Whether this group should be displayed as submenu.
insertBefore	string string[]	yes	Insert this item before the item referenced here. For arrays, the first one found in order is used.
insertAfter	string string[]	yes	Insert this item after the item referenced here. For arrays, the first one found in order is used. The insertBefore value takes precedence.

console.action/provider

ActionProvider contributes a hook that returns list of actions for specific context.

Name	Value Type	Optional	Description
contextId	string	no	The context ID helps to narrow the scope of contributed actions to a particular area of the application. Examples include topology and helm .
provider	CodeRef<Extension Hook<Action[], any>>	no	A React hook that returns actions for the given scope. If contextId = resource , then the scope will always be a Kubernetes resource object.

console.action/resource-provider

ResourceActionProvider contributes a hook that returns list of actions for specific resource model.

Name	Value Type	Optional	Description
model	ExtensionK8sKindVersionModel	no	The model for which this provider provides actions for.
provider	CodeRef<ExtensionHook<Action[], any>>	no	A react hook which returns actions for the given resource model

console.alert-action

Name	Value Type	Optional	Description
alert	string	no	
text	string	no	
action	CodeRef<(alert: any) ⇒ void>	no	

console.catalog/item-filter

Name	Value Type	Optional	Description
catalogId	string string[]	no	The unique identifier for the catalog this provider contributes to.
type	string	no	Type ID for the catalog item type.
filter	CodeRef<(item: CatalogItem) ⇒ boolean>	no	Filters items of a specific type. Value is a function that takes CatalogItem[] and returns a subset based on the filter criteria.

console.catalog/item-metadata

Name	Value Type	Optional	Description
catalogId	string string[]	no	The unique identifier for the catalog this provider contributes to.
type	string	no	Type ID for the catalog item type.

Name	Value Type	Optional	Description
provider	CodeRef<ExtensionHook<CatalogItemMetadataProviderFunction, CatalogExtensionHookOptions>>	no	A hook which returns a function that will be used to provide metadata to catalog items of a specific type.

console.catalog/item-provider

Name	Value Type	Optional	Description
catalogId	string string[]	no	The unique identifier for the catalog this provider contributes to.
type	string	no	Type ID for the catalog item type.
title	string	no	Title for the catalog item provider
provider	CodeRef<ExtensionHook<CatalogItem<any>[], CatalogExtensionHookOptions>>	no	Fetch items and normalize it for the catalog. Value is a react effect hook.
priority	number	yes	Priority for this provider. Defaults to 0 . Higher priority providers may override catalog items provided by other providers.

console.catalog/item-type

Name	Value Type	Optional	Description
type	string	no	Type for the catalog item.
title	string	no	Title for the catalog item.
catalogDescription	string CodeRef<React.ReactNode>	yes	Description for the type specific catalog.

Name	Value Type	Optional	Description
typeDescription	string	yes	Description for the catalog item type.
filters	CatalogItemAttribute []	yes	Custom filters specific to the catalog item.
groupings	CatalogItemAttribute []	yes	Custom groupings specific to the catalog item.

console.catalog/item-type-metadata

Name	Value Type	Optional	Description
type	string	no	Type for the catalog item.
filters	CatalogItemAttribute []	yes	Custom filters specific to the catalog item.
groupings	CatalogItemAttribute []	yes	Custom groupings specific to the catalog item.

console.cluster-overview/inventory-item

Adds a new inventory item into cluster overview page.

Name	Value Type	Optional	Description
component	CodeRef<React.ComponentType<{}>>	no	The component to be rendered.

console.cluster-overview/multiline-utilization-item

Adds a new cluster overview multi-line utilization item.

Name	Value Type	Optional	Description
title	string	no	The title of the utilization item.
getUtilizationQueries	CodeRef<GetMultilineQueries>	no	Prometheus utilization query.
humanize	CodeRef<Humanize>	no	Convert Prometheus data to human-readable form.

Name	Value Type	Optional	Description
TopConsumerPopovers	CodeRef<React.ComponentType<TopConsumerPopoverProps>[]>	yes	Shows Top consumer popover instead of plain value

console.cluster-overview/utilization-item

Adds a new cluster overview utilization item.

Name	Value Type	Optional	Description
title	string	no	The title of the utilization item.
getUtilizationQuery	CodeRef<GetQuery>	no	Prometheus utilization query.
humanize	CodeRef<Humanize>	no	Convert Prometheus data to human-readable form.
getTotalQuery	CodeRef<GetQuery>	yes	Prometheus total query.
getRequestQuery	CodeRef<GetQuery>	yes	Prometheus request query.
getLimitQuery	CodeRef<GetQuery>	yes	Prometheus limit query.
TopConsumerPopover	CodeRef<React.ComponentType<TopConsumerPopoverProps>>	yes	Shows Top consumer popover instead of plain value

console.context-provider

Adds a new React context provider to the web console application root.

Name	Value Type	Optional	Description
provider	CodeRef<Provider<T>>	no	Context Provider component.
useValueHook	CodeRef<() ⇒ T>	no	Hook for the Context value.

console.dashboards/card

Adds a new dashboard card.

Name	Value Type	Optional	Description
tab	string	no	The ID of the dashboard tab to which the card will be added.
position	'LEFT' 'RIGHT' 'MAIN'	no	The grid position of the card on the dashboard.
component	CodeRef<React.ComponentType<{}>>	no	Dashboard card component.
span	OverviewCardSpan	yes	Card's vertical span in the column. Ignored for small screens; defaults to 12 .

console.dashboards/overview/activity/resource

Adds an activity to the Activity Card of Overview Dashboard where the triggering of activity is based on watching a Kubernetes resource.

Name	Value Type	Optional	Description
k8sResource	CodeRef<FirehoseResource & { isList: true; }>	no	The utilization item to be replaced.
component	CodeRef<React.ComponentType<K8sActivityProps<T>>>	no	The action component.
isActivity	CodeRef<(resource: T) ⇒ boolean>	yes	Function which determines if the given resource represents the action. If not defined, every resource represents activity.
getTimestamp	CodeRef<(resource: T) ⇒ Date>	yes	Time stamp for the given action, which will be used for ordering.

console.dashboards/overview/detail/item

Adds an item to the **Details** card of **Overview** dashboard.

Name	Value Type	Optional	Description
component	CodeRef<React.ComponentType<{}>>	no	The value, based on the DetailItem component

console.dashboards/overview/health/operator

Adds a health subsystem to the status card of the **Overview** dashboard, where the source of status is a Kubernetes REST API.

Name	Value Type	Optional	Description
title	string	no	Title of Operators section in the pop-up menu.
resources	CodeRef<FirehoseResource[]>	no	Kubernetes resources which will be fetched and passed to healthHandler .
getOperatorsWithStatuses	CodeRef<GetOperatorsWithStatuses<T>>	yes	Resolves status for the Operators.
operatorRowLoader	CodeRef<React.ComponentType<OperatorRowProps<T>>>	yes	Loader for pop-up row component.
viewAllLink	string	yes	Links to all resources page. If not provided, then a list page of the first resource from resources prop is used.

console.dashboards/overview/health/prometheus

Adds a health subsystem to the status card of Overview dashboard where the source of status is Prometheus.

Name	Value Type	Optional	Description
title	string	no	The display name of the subsystem.
queries	string[]	no	The Prometheus queries
healthHandler	CodeRef<PrometheusHealthHandler>	no	Resolve the subsystem's health.

Name	Value Type	Optional	Description
additionalResource	CodeRef<FirehoseResource>	yes	Additional resource which will be fetched and passed to healthHandler .
popupComponent	CodeRef<React.ComponentType<PrometheusHealthPopupProps>>	yes	Loader for pop-up menu content. If defined, a health item is represented as a link, which opens a pop-up menu with the given content.
popupTitle	string	yes	The title of the popover.
disallowedControlPlaneTopology	string[]	yes	Control plane topology for which the subsystem should be hidden.

console.dashboards/overview/health/resource

Adds a health subsystem to the status card of Overview dashboard where the source of status is a Kubernetes Resource.

Name	Value Type	Optional	Description
title	string	no	The display name of the subsystem.
resources	CodeRef<WatchK8sResources<T>>	no	Kubernetes resources that will be fetched and passed to healthHandler .
healthHandler	CodeRef<ResourceHealthHandler<T>>	no	Resolve the subsystem's health.
popupComponent	CodeRef<WatchK8sResults<T>>	yes	Loader for pop-up menu content. If defined, a health item is represented as a link, which opens a pop-up menu with the given content.
popupTitle	string	yes	The title of the popover.

console.dashboards/overview/health/url

Adds a health subsystem to the status card of Overview dashboard where the source of status is a Kubernetes REST API.

Name	Value Type	Optional	Description
title	string	no	The display name of the subsystem.
url	string	no	The URL to fetch data from. It will be prefixed with base Kubernetes URL.
healthHandler	<code>`CodeRef<URLHealthHandler<T, K8sResourceCommon>>`</code>	<code>K8sResourceCommon[]>>`</code>	no
Resolve the subsystem's health.	additionalResource	CodeRef<FirehoseResource>	yes
Additional resource which will be fetched and passed to healthHandler .	popupComponent	CodeRef<React.ComponentType<{ healthResult?: T; healthResultError?: any; k8sResult?: FirehoseResult<R>; }>>	yes
Loader for popup content. If defined, a health item will be represented as a link which opens popup with given content.	popupTitle	string	yes

console.dashboards/overview/inventory/item

Adds a resource tile to the overview inventory card.

Name	Value Type	Optional	Description
model	CodeRef<T>	no	The model for resource which will be fetched. Used to get the model's label or abbr .
mapper	CodeRef<StatusGroupMapper<T, R>>	yes	Function which maps various statuses to groups.

Name	Value Type	Optional	Description
additionalResources	CodeRef<WatchK8sResources<R>>	yes	Additional resources which will be fetched and passed to the mapper function.

console.dashboards/overview/inventory/item/group

Adds an inventory status group.

Name	Value Type	Optional	Description
id	string	no	The id of the status group.
icon	CodeRef<React.ReactElement<any, string React.JSXElementConstructor<any>>>	no	React component representing the status group icon.

console.dashboards/overview/inventory/item/replacement

Replaces an overview inventory card.

Name	Value Type	Optional	Description
model	CodeRef<T>	no	The model for resource which will be fetched. Used to get the model's label or abbr .
mapper	CodeRef<StatusGroupMapper<T, R>>	yes	Function which maps various statuses to groups.
additionalResources	CodeRef<WatchK8sResources<R>>	yes	Additional resources which will be fetched and passed to the mapper function.

console.dashboards/overview/prometheus/activity/resource

Adds an activity to the Activity Card of Prometheus Overview Dashboard where the triggering of activity is based on watching a Kubernetes resource.

Name	Value Type	Optional	Description
------	------------	----------	-------------

Name	Value Type	Optional	Description
queries	string[]	no	Queries to watch
component	CodeRef<React.ComponentType<PrometheusActivityProps>>	no	The action component.
isActivity	CodeRef<(results: PrometheusResponse[]) => boolean>	yes	Function which determines if the given resource represents the action. If not defined, every resource represents activity.

console.dashboards/project/overview/item

Adds a resource tile to the project overview inventory card.

Name	Value Type	Optional	Description
model	CodeRef<T>	no	The model for resource which will be fetched. Used to get the model's label or abbr .
mapper	CodeRef<StatusGroupMapper<T, R>>	yes	Function which maps various statuses to groups.
additionalResources	CodeRef<WatchK8sResources<R>>	yes	Additional resources which will be fetched and passed to the mapper function.

console.dashboards/tab

Adds a new dashboard tab, placed after the **Overview** tab.

Name	Value Type	Optional	Description
id	string	no	A unique tab identifier, used as tab link href and when adding cards to this tab.
navSection	'home' 'storage'	no	Navigation section to which the tab belongs to.
title	string	no	The title of the tab.

Name	Value Type	Optional	Description
------	------------	----------	-------------

console.file-upload

Name	Value Type	Optional	Description
fileExtensions	string[]	no	Supported file extensions.
handler	CodeRef<FileUpload Handler>	no	Function which handles the file drop action.

console.flag

Gives full control over the web console feature flags.

Name	Value Type	Optional	Description
handler	CodeRef<FeatureFlagHandler>	no	Used to set or unset arbitrary feature flags.

console.flag/hookProvider

Gives full control over the web console feature flags with hook handlers.

Name	Value Type	Optional	Description
handler	CodeRef<FeatureFlagHandler>	no	Used to set or unset arbitrary feature flags.

console.flag/model

Adds a new web console feature flag driven by the presence of a CRD on the cluster.

Name	Value Type	Optional	Description
flag	string	no	The name of the flag to set once the CRD is detected.
model	ExtensionK8sModel	no	The model which refers to a CustomResourceDefinition .

console.global-config

Name	Value Type	Optional	Description
id	string	no	Unique identifier for the cluster config resource instance.
name	string	no	The name of the cluster config resource instance.
model	ExtensionK8sModel	no	The model which refers to a cluster config resource.
namespace	string	no	The namespace of the cluster config resource instance.

console.model-metadata

Customize the display of models by overriding values retrieved and generated through API discovery.

Name	Value Type	Optional	Description
model	ExtensionK8sGroup Model	no	The model to customize. May specify only a group, or optional version and kind.
badge	ModelBadge	yes	Whether to consider this model reference as Technology Preview or Developer Preview.
color	string	yes	The color to associate to this model.
label	string	yes	Override the label. Requires kind be provided.
labelPlural	string	yes	Override the plural label. Requires kind be provided.

Name	Value Type	Optional	Description
abbr	string	yes	Customize the abbreviation. Defaults to all uppercase characters in kind , up to 4 characters long. Requires that kind is provided.

console.navigation/href

Name	Value Type	Optional	Description
id	string	no	A unique identifier for this item.
name	string	no	The name of this item.
href	string	no	The link href value.
perspective	string	yes	The perspective ID to which this item belongs to. If not specified, contributes to the default perspective.
section	string	yes	Navigation section to which this item belongs to. If not specified, render this item as a top level link.
dataAttributes	{ [key: string]: string; }	yes	Adds data attributes to the DOM.
startsWith	string[]	yes	Mark this item as active when the URL starts with one of these paths.
insertBefore	string string[]	yes	Insert this item before the item referenced here. For arrays, the first one found in order is used.

Name	Value Type	Optional	Description
insertAfter	string string[]	yes	Insert this item after the item referenced here. For arrays, the first one found in order is used. insertBefore takes precedence.
namespaced	boolean	yes	If true , adds /ns/active-namespace to the end.
prefixNamespaced	boolean	yes	If true , adds /k8s/ns/active-namespace to the beginning

console.navigation/resource-cluster

Name	Value Type	Optional	Description
id	string	no	A unique identifier for this item.
model	ExtensionK8sModel	no	The model for which this navigation item links to.
perspective	string	yes	The perspective ID to which this item belongs to. If not specified, contributes to the default perspective.
section	string	yes	Navigation section to which this item belongs to. If not specified, render this item as a top-level link.
dataAttributes	{ [key: string]: string; }	yes	Adds data attributes to the DOM.
startsWith	string[]	yes	Mark this item as active when the URL starts with one of these paths.

Name	Value Type	Optional	Description
insertBefore	string string[]	yes	Insert this item before the item referenced here. For arrays, the first one found in order is used.
insertAfter	string string[]	yes	Insert this item after the item referenced here. For arrays, the first one found in order is used. insertBefore takes precedence.
name	string	yes	Overrides the default name. If not supplied the name of the link will equal the plural value of the model.

console.navigation/resource-ns

Name	Value Type	Optional	Description
id	string	no	A unique identifier for this item.
model	ExtensionK8sModel	no	The model for which this navigation item links to.
perspective	string	yes	The perspective ID to which this item belongs to. If not specified, contributes to the default perspective.
section	string	yes	Navigation section to which this item belongs to. If not specified, render this item as a top-level link.
dataAttributes	{ [key: string]: string; }	yes	Adds data attributes to the DOM.
startsWith	string[]	yes	Mark this item as active when the URL starts with one of these paths.

Name	Value Type	Optional	Description
insertBefore	string string[]	yes	Insert this item before the item referenced here. For arrays, the first one found in order is used.
insertAfter	string string[]	yes	Insert this item after the item referenced here. For arrays, the first one found in order is used. insertBefore takes precedence.
name	string	yes	Overrides the default name. If not supplied the name of the link will equal the plural value of the model.

console.navigation/section

Name	Value Type	Optional	Description
id	string	no	A unique identifier for this item.
perspective	string	yes	The perspective ID to which this item belongs to. If not specified, contributes to the default perspective.
dataAttributes	{ [key: string]: string; }	yes	Adds data attributes to the DOM.
insertBefore	string string[]	yes	Insert this item before the item referenced here. For arrays, the first one found in order is used.
insertAfter	string string[]	yes	Insert this item after the item referenced here. For arrays, the first one found in order is used. insertBefore takes precedence.

Name	Value Type	Optional	Description
name	string	yes	Name of this section. If not supplied, only a separator will be shown above the section.

console.navigation/separator

Name	Value Type	Optional	Description
id	string	no	A unique identifier for this item.
perspective	string	yes	The perspective ID to which this item belongs to. If not specified, contributes to the default perspective.
section	string	yes	Navigation section to which this item belongs to. If not specified, render this item as a top level link.
dataAttributes	{ [key: string]: string; }	yes	Adds data attributes to the DOM.
insertBefore	string string[]	yes	Insert this item before the item referenced here. For arrays, the first one found in order is used.
insertAfter	string string[]	yes	Insert this item after the item referenced here. For arrays, the first one found in order is used. insertBefore takes precedence.

console.page/resource/details

Name	Value Type	Optional	Description
model	ExtensionK8sGroup KindModel	no	The model for which this resource page links to.

Name	Value Type	Optional	Description
component	CodeRef<React.ComponentType<{ match: match<{}>; namespace: string; model: ExtensionK8sModel; }>>	no	The component to be rendered when the route matches.

console.page/resource/list

Adds new resource list page to Console router.

Name	Value Type	Optional	Description
model	ExtensionK8sGroup KindModel	no	The model for which this resource page links to.
component	CodeRef<React.ComponentType<{ match: match<{}>; namespace: string; model: ExtensionK8sModel; }>>	no	The component to be rendered when the route matches.

console.page/route

Adds a new page to the web console router. See [React Router](#).

Name	Value Type	Optional	Description
component	CodeRef<React.ComponentType<RouteComponentProps<{}>, StaticContext, any>>>	no	The component to be rendered when the route matches.
path	string string[]	no	Valid URL path or array of paths that path-to-regexp@^1.7.0 understands.
perspective	string	yes	The perspective to which this page belongs to. If not specified, contributes to all perspectives.

Name	Value Type	Optional	Description
exact	boolean	yes	When true, will only match if the path matches the location.pathname exactly.

console.page/route/standalone

Adds a new standalone page, rendered outside the common page layout, to the web console router. See [React Router](#).

Name	Value Type	Optional	Description
component	CodeRef<React.ComponentType<RouteComponentProps<{}>, StaticContext, any>>>	no	The component to be rendered when the route matches.
path	string string[]	no	Valid URL path or array of paths that path-to-regexp@^1.7.0 understands.
exact	boolean	yes	When true, will only match if the path matches the location.pathname exactly.

console.perspective

Name	Value Type	Optional	Description
id	string	no	The perspective identifier.
name	string	no	The perspective display name.
icon	CodeRef<LazyComponent>	no	The perspective display icon.
landingPageURL	CodeRef<(flags: { [key: string]: boolean; }, isFirstVisit: boolean) ⇒ string>	no	The function to get perspective landing page URL.

Name	Value Type	Optional	Description
importRedirectURL	CodeRef<(namespace: string) ⇒ string>	no	The function to get redirect URL for import flow.
default	boolean	yes	Whether the perspective is the default. There can only be one default.
defaultPins	ExtensionK8sModel[]	yes	Default pinned resources on the nav
usePerspectiveDetection	CodeRef<() ⇒ [boolean, boolean]>	yes	The hook to detect default perspective

console.project-overview/inventory-item

Adds a new inventory item into the **Project Overview** page.

Name	Value Type	Optional	Description
component	CodeRef<React.ComponentType<{ projectName: string; }>>	no	The component to be rendered.

console.project-overview/utilization-item

Adds a new project overview utilization item.

Name	Value Type	Optional	Description
title	string	no	The title of the utilization item.
getUtilizationQuery	CodeRef<GetProjectQuery>	no	Prometheus utilization query.
humanize	CodeRef<Humanize>	no	Convert Prometheus data to human-readable form.
getTotalQuery	CodeRef<GetProjectQuery>	yes	Prometheus total query.
getRequestQuery	CodeRef<GetProjectQuery>	yes	Prometheus request query.

Name	Value Type	Optional	Description
getLimitQuery	CodeRef<GetProjectQuery>	yes	Prometheus limit query.
TopConsumerPopover	CodeRef<React.ComponentType<TopConsumerPopoverProps>>	yes	Shows the top consumer popover instead of plain value.

console.pvc/alert

Name	Value Type	Optional	Description
alert	CodeRef<React.ComponentType<{ pvc: K8sResourceComm on; }>>	no	The alert component.

console.pvc/create-prop

Name	Value Type	Optional	Description
label	string	no	Label for the create prop action.
path	string	no	Path for the create prop action.

console.pvc/delete

Name	Value Type	Optional	Description
predicate	CodeRef<(pvc: K8sResourceComm on) ⇒ boolean>	no	Predicate that tells whether to use the extension or not.
onPVCKill	CodeRef<(pvc: K8sResourceComm on) ⇒ Promise<void>>	no	Method for the PVC delete operation.
alert	CodeRef<React.ComponentType<{ pvc: K8sResourceComm on; }>>	no	Alert component to show additional information.

console.pvc/status

Name	Value Type	Optional	Description
priority	number	no	Priority for the status component. A larger value means higher priority.
status	CodeRef<React.ComponentType<{ pvc: K8sResourceComm on; }>>	no	The status component.
predicate	CodeRef<(pvc: K8sResourceComm on) ⇒ boolean>	no	Predicate that tells whether to render the status component or not.

console.redux-reducer

Adds new reducer to Console Redux store which operates on **plugins.<scope>** substate.

Name	Value Type	Optional	Description
scope	string	no	The key to represent the reducer-managed substate within the Redux state object.
reducer	CodeRef<Reducer<any, AnyAction>>	no	The reducer function, operating on the reducer-managed substate.

console.resource/create

Name	Value Type	Optional	Description
model	ExtensionK8sModel	no	The model for which this create resource page will be rendered.
component	CodeRef<React.ComponentType<Create ResourceComponentProps>>	no	The component to be rendered when the model matches

console.storage-provider

Name	Value Type	Optional	Description
name	string	no	
Component	CodeRef<React.ComponentType<Partial<RouteComponentProps<{}>, StaticContext, any>>>>	no	

console.tab/horizontalNav

Name	Value Type	Optional	Description
model	ExtensionK8sKindVersionModel	no	The model for which this provider show tab.
page	{ name: string; href: string; }	no	The page to be show in horizontal tab. It takes tab name as name and href of the tab
component	CodeRef<React.ComponentType<PageComponentProps<K8sResourceCommon>>>	no	The component to be rendered when the route matches.

console.telemetry/listener

Name	Value Type	Optional	Description
listener	CodeRef<TelemetryEventListener>	no	Listen for telemetry events

console.topology/adapters/build

BuildAdapter contributes an adapter to adapt element to data that can be used by the **Build** component.

Name	Value Type	Optional	Description
adapt	`CodeRef<(element: GraphElement) => AdapterDataType<BuildConfigData>	undefined`	no

console.topology/adapters/network

NetworkAdapater contributes an adapter to adapt element to data that can be used by the **Networking** component.

Name	Value Type	Optional	Description
adapt	<code>`CodeRef<(element: GraphElement) => NetworkAdapterType`</code>	undefined	no

console.topology/adapter/pod

PodAdapter contributes an adapter to adapt element to data that can be used by the **Pod** component.

Name	Value Type	Optional	Description
adapt	<code>`CodeRef<(element: GraphElement) => AdapterDataType<Pods AdapterDataType>`</code>	undefined	no

console.topology/component/factory

Getter for a **ViewComponentFactory**.

Name	Value Type	Optional	Description
getFactory	<code>CodeRef<ViewComponentFactory></code>	no	Getter for a ViewComponentFactory .

console.topology/create/connector

Getter for the create connector function.

Name	Value Type	Optional	Description
getCreateConnector	<code>CodeRef<CreateConnectorGetter></code>	no	Getter for the create connector function.

console.topology/data/factory

Topology Data Model Factory Extension

Name	Value Type	Optional	Description
id	string	no	Unique ID for the factory.
priority	number	no	Priority for the factory

Name	Value Type	Optional	Description
resources	WatchK8sResources Generic	yes	Resources to be fetched from useK8sWatchResources hook.
workloadKeys	string[]	yes	Keys in resources containing workloads.
getDataModel	CodeRef<TopologyDataModelGetter>	yes	Getter for the data model factory.
isResourceDepicted	CodeRef<TopologyDataModelDepicted>	yes	Getter for function to determine if a resource is depicted by this model factory.
getDataModelReconciler	CodeRef<TopologyDataModelReconciler>	yes	Getter for function to reconcile data model after all extensions' models have loaded.

console.topology/decorator/provider

Topology Decorator Provider Extension

Name	Value Type	Optional	Description
id	string	no	
priority	number	no	
quadrant	TopologyQuadrant	no	
decorator	CodeRef<TopologyDecoratorGetter>	no	

console.topology/details/resource-alert

DetailsResourceAlert contributes an alert for specific topology context or graph element.

Name	Value Type	Optional	Description
id	string	no	The ID of this alert. Used to save state if the alert should not be shown after dismissed.

Name	Value Type	Optional	Description
contentProvider	<code>`CodeRef<(element: GraphElement) => DetailsResourceAlertContent`</code>	no	

console.topology/details/resource-link

DetailsResourceLink contributes a link for specific topology context or graph element.

Name	Value Type	Optional	Description
link	<code>`CodeRef<(element: GraphElement) => React.Component`</code>	no	
Return the resource link if provided, otherwise undefined. Use the ResourceIcon and ResourceLink properties for styles.	priority	number	yes

console.topology/details/tab

DetailsTab contributes a tab for the topology details panel.

Name	Value Type	Optional	Description
id	string	no	A unique identifier for this details tab.
label	string	no	The tab label to display in the UI.
insertBefore	string string[]	yes	Insert this item before the item referenced here. For arrays, the first one found in order is used.
insertAfter	string string[]	yes	Insert this item after the item referenced here. For arrays, the first one found in order is used. The insertBefore value takes precedence.

console.topology/details/tab-section

DetailsTabSection contributes a section for a specific tab in the topology details panel.

Name	Value Type	Optional	Description
id	string	no	A unique identifier for this details tab section.
tab	string	no	The parent tab ID that this section should contribute to.
provider	CodeRef<DetailsTabSectionExtensionHook>	no	A hook that returns a component, or if null or undefined renders in the topology sidebar.SDK component: <Section title=\{\}\>... padded area
section	<code>`CodeRef<(element: GraphElement, renderNull?: () => null) => React.Component`</code>	undefined>	no
@deprecated Fallback if no provider is defined. renderNull is a no-op already.	insertBefore	string string[]	yes
Insert this item before the item referenced here.For arrays, the first one found in order is used.	insertAfter	string string[]	yes

console.topology/display/filters

Topology Display Filters Extension

Name	Value Type	Optional	Description
getTopologyFilters	CodeRef<() => TopologyDisplayOption[]>	no	
applyDisplayOptions	CodeRef<TopologyApplyDisplayOptions>	no	

console.topology/relationship/provider

Topology relationship provider connector extension

Name	Value Type	Optional	Description
provides	CodeRef<RelationshipProviderProvides>	no	
tooltip	string	no	
create	CodeRef<RelationshipProviderCreate>	no	
priority	number	no	

console.user-preference/group

Name	Value Type	Optional	Description
id	string	no	ID used to identify the user preference group.
label	string	no	The label of the user preference group
insertBefore	string	yes	ID of user preference group before which this group should be placed
insertAfter	string	yes	ID of user preference group after which this group should be placed

console.user-preference/item

Name	Value Type	Optional	Description
id	string	no	ID used to identify the user preference item and referenced in insertAfter and insertBefore to define the item order.
label	string	no	The label of the user preference
description	string	no	The description of the user preference.

Name	Value Type	Optional	Description
field	UserPreferenceField	no	The input field options used to render the values to set the user preference.
groupId	string	yes	IDs used to identify the user preference groups the item would belong to.
insertBefore	string	yes	ID of user preference item before which this item should be placed
insertAfter	string	yes	ID of user preference item after which this item should be placed

console.yaml-template

YAML templates for editing resources via the yaml editor.

Name	Value Type	Optional	Description
model	ExtensionK8sModel	no	Model associated with the template.
template	CodeRef<string>	no	The YAML template.
name	string	no	The name of the template. Use the name default to mark this as the default template.

dev-console.add/action

Name	Value Type	Optional	Description
id	string	no	ID used to identify the action.
label	string	no	The label of the action
description	string	no	The description of the action.
href	string	no	The href to navigate to.

Name	Value Type	Optional	Description
groupId	string	yes	IDs used to identify the action groups the action would belong to.
icon	CodeRef<React.ReactNode>	yes	The perspective display icon.
accessReview	AccessReviewResourceAttributes[]	yes	Optional access review to control the visibility or enablement of the action.

dev-console.add/action-group

Name	Value Type	Optional	Description
id	string	no	ID used to identify the action group.
name	string	no	The title of the action group
insertBefore	string	yes	ID of action group before which this group should be placed
insertAfter	string	yes	ID of action group after which this group should be placed

dev-console.import/environment

Name	Value Type	Optional	Description
imageStreamName	string	no	Name of the image stream to provide custom environment variables for
imageStreamTags	string[]	no	List of supported image stream tags
environments	ImageEnvironment[]	no	List of environment variables

console.page/resource/tab

Deprecated. Use **console.tab/horizontalNav** instead. Adds a new resource tab page to Console router.

Name	Value Type	Optional	Description
model	ExtensionK8sGroupKindModel	no	The model for which this resource page links to.
component	CodeRef<React.ComponentType<RouteComponentProps<{}, StaticContext, any>>>	no	The component to be rendered when the route matches.
name	string	no	The name of the tab.
href	string	yes	The optional href for the tab link. If not provided, the first path is used.
exact	boolean	yes	When true, will only match if the path matches the location.pathname exactly.

7.5.2. OpenShift Container Platform console API

useActivePerspective

Hook that provides the currently active perspective and a callback for setting the active perspective. It returns a tuple containing the current active perspective and setter callback.

```
const Component: React.FC = (props) => {
  const [activePerspective, setActivePerspective] = useActivePerspective();
  return <select
    value={activePerspective}
    onChange={(e) => setActivePerspective(e.target.value)}
  >
    {
      // ...perspective options
    }
  </select>
}
```

GreenCheckCircleIcon

Component for displaying a green check mark circle icon.

```
<GreenCheckCircleIcon title="Healthy" />
```

Parameter Name	Description
className	(optional) additional class name for the component

Parameter Name	Description
title	(optional) icon title
size	(optional) icon size: ('sm', 'md', 'lg', 'xl')

RedExclamationCircleIcon

Component for displaying a red exclamation mark circle icon.

```
<RedExclamationCircleIcon title="Failed" />
```

Parameter Name	Description
className	(optional) additional class name for the component
title	(optional) icon title
size	(optional) icon size: ('sm', 'md', 'lg', 'xl')

YellowExclamationTriangleIcon

Component for displaying a yellow triangle exclamation icon.

```
<YellowExclamationTriangleIcon title="Warning" />
```

Parameter Name	Description
className	(optional) additional class name for the component
title	(optional) icon title
size	(optional) icon size: ('sm', 'md', 'lg', 'xl')

BlueInfoCircleIcon

Component for displaying a blue info circle icon.

```
<BlueInfoCircleIcon title="Info" />
```

Parameter Name	Description
className	(optional) additional class name for the component
title	(optional) icon title
size	(optional) icon size: ('sm', 'md', 'lg', 'xl')

ErrorStatus

Component for displaying an error status popover.

```
<ErrorStatus title={errorMsg} />
```

Parameter Name	Description
title	(optional) status text
iconOnly	(optional) if true, only displays icon
noTooltip	(optional) if true, tooltip won't be displayed
className	(optional) additional class name for the component
popoverTitle	(optional) title for popover

InfoStatus

Component for displaying an information status popover.

```
<InfoStatus title={infoMsg} />
```

Parameter Name	Description
title	(optional) status text
iconOnly	(optional) if true, only displays icon
noTooltip	(optional) if true, tooltip won't be displayed
className	(optional) additional class name for the component
popoverTitle	(optional) title for popover

ProgressStatus

Component for displaying a progressing status popover.

```
<ProgressStatus title={progressMsg} />
```

Parameter Name	Description
title	(optional) status text
iconOnly	(optional) if true, only displays icon
noTooltip	(optional) if true, tooltip won't be displayed

Parameter Name	Description
className	(optional) additional class name for the component
popoverTitle	(optional) title for popover

SuccessStatus

Component for displaying a success status popover.

```
<SuccessStatus title={successMsg} />
```

Parameter Name	Description
title	(optional) status text
iconOnly	(optional) if true, only displays icon
noTooltip	(optional) if true, tooltip won't be displayed
className	(optional) additional class name for the component
popoverTitle	(optional) title for popover

checkAccess

Provides information about user access to a given resource. It returns an object with resource access information.

Parameter Name	Description
resourceAttributes	resource attributes for access review
impersonate	impersonation details

useAccessReview

Hook that provides information about user access to a given resource. It returns an array with **isAllowed** and **loading** values.

Parameter Name	Description
resourceAttributes	resource attributes for access review
impersonate	impersonation details

useResolvedExtensions

React hook for consuming Console extensions with resolved **CodeRef** properties. This hook accepts the

same argument(s) as **useExtensions** hook and returns an adapted list of extension instances, resolving all code references within each extension's properties. Initially, the hook returns an empty array. Once the resolution is complete, the React component is re-rendered with the hook returning an adapted list of extensions. When the list of matching extensions changes, the resolution is restarted. The hook will continue to return the previous result until the resolution completes. The hook's result elements are guaranteed to be referentially stable across re-renders. It returns a tuple containing a list of adapted extension instances with resolved code references, a boolean flag indicating whether the resolution is complete, and a list of errors detected during the resolution.

```
const [navItemExtensions, navItemsResolved] = useResolvedExtensions<NavItem>(isNavItem);
// process adapted extensions and render your component
```

Parameter Name	Description
typeGuards	A list of callbacks that each accept a dynamic plugin extension as an argument and return a boolean flag indicating whether or not the extension meets desired type constraints

HorizontalNav

A component that creates a Navigation bar for a page.- Routing is handled as part of the component.- **console.tab/horizontalNav** can be used to add additional content to any horizontal nav.

```
const HomePage: React.FC = (props) => {
  const page = {
    href: '/home',
    name: 'Home',
    component: () => <>Home</>
  }
  return <HorizontalNav match={props.match} pages={[page]} />
}
```

Parameter Name	Description
resource	The resource associated with this Navigation, an object of K8sResourceCommon type
pages	An array of page objects
match	match object provided by React Router

VirtualizedTable

A component for making virtualized tables.

```
const MachineList: React.FC<MachineListProps> = (props) => {
  return (
    <VirtualizedTable<MachineKind>
      {...props}
      aria-label='Machines'
      columns={getMachineColumns}
    />
  )
}
```

```

    Row={getMachineTableRow}
  />
);
}

```

Parameter Name	Description
data	data for table
loaded	flag indicating data is loaded
loadError	error object if issue loading data
columns	column setup
Row	row setup
unfilteredData	original data without filter
NoDataEmptyMsg	(optional) no data empty message component
EmptyMsg	(optional) empty message component
scrollNode	(optional) function to handle scroll
label	(optional) label for table
ariaLabel	(optional) aria label
gridBreakPoint	sizing of how to break up grid for responsiveness
onSelect	(optional) function for handling select of table
rowData	(optional) data specific to row

TableData

Component for displaying table data within a table row.

```

const PodRow: React.FC<RowProps<K8sResourceCommon>> = ({ obj, activeColumnIDs }) => {
  return (
    <>
      <TableData id={columns[0].id} activeColumnIDs={activeColumnIDs}>
        <ResourceLink kind="Pod" name={obj.metadata.name} namespace={obj.metadata.namespace} />
      </TableData>
      <TableData id={columns[1].id} activeColumnIDs={activeColumnIDs}>
        <ResourceLink kind="Namespace" name={obj.metadata.namespace} />
      </TableData>
    </>
  );
}

```

```

    </>
  );
};

```

Parameter Name	Description
id	unique id for table
activeColumnIDs	active columns
className	(optional) option class name for styling

useActiveColumns

A hook that provides a list of user-selected active TableColumns.

```

// See implementation for more details on TableColumn type
const [activeColumns, userSettingsLoaded] = useActiveColumns({
  columns,
  showNamespaceOverride: false,
  columnManagementID,
});
return userSettingsAreLoaded ? <VirtualizedTable columns= {activeColumns} {...otherProps} /> :
null

```

Parameter Name	Description
options	Which are passed as a key-value map
<code>options.columns</code>	<code>{TableColumn[]}</code> options.columns - An array of all available TableColumns
<code>options.showNamespaceOverride</code>	<code>{boolean}</code> [options.showNamespaceOverride] - (optional) If true, a namespace column will be included, regardless of column management selections
<code>options.columnManagementID</code>	<code>{string}</code> [options.columnManagementID] - (optional) A unique id used to persist and retrieve column management selections to and from user settings. Usually a 'group _{version} kind' string for a resource.

A tuple containing the current user selected active columns (a subset of options.columns), and a boolean flag indicating whether user settings have been loaded.

ListPageHeader

Component for generating a page header.

```

const exampleList: React.FC = () => {
  return (

```

```

    <>
    <ListPageHeader title="Example List Page"/>
  </>
);
};

```

Parameter Name	Description
title	heading title
helpText	(optional) help section as react node
badge	(optional) badge icon as react node

ListPageCreate

Component for adding a create button for a specific resource kind that automatically generates a link to the create YAML for this resource.

```

const exampleList: React.FC<MyProps> = () => {
  return (
    <>
    <ListPageHeader title="Example Pod List Page"/>
    <ListPageCreate groupVersionKind="Pod">Create Pod</ListPageCreate>
    </ListPageHeader>
    </>
  );
};

```

Parameter Name	Description
groupVersionKind	the resource group/version/kind to represent

ListPageCreateLink

Component for creating a stylized link.

```

const exampleList: React.FC<MyProps> = () => {
  return (
    <>
    <ListPageHeader title="Example Pod List Page"/>
    <ListPageCreateLink to={'/link/to/my/page'}>Create Item</ListPageCreateLink>
    </ListPageHeader>
    </>
  );
};

```

Parameter Name	Description
to	string location where link should direct

Parameter Name	Description
createAccessReview	(optional) object with namespace and kind used to determine access
children	(optional) children for the component

ListPageCreateButton

Component for creating button.

```
const exampleList: React.FC<MyProps> = () => {
  return (
    <>
      <ListPageHeader title="Example Pod List Page"/>
      <ListPageCreateButton createAccessReview={access}>Create Pod</ListPageCreateButton>
    </ListPageHeader>
    </>
  );
};
```

Parameter Name	Description
createAccessReview	(optional) object with namespace and kind used to determine access
pfButtonProps	(optional) Patternfly Button props

ListPageCreateDropdown

Component for creating a dropdown wrapped with permissions check.

```
const exampleList: React.FC<MyProps> = () => {
  const items = {
    SAVE: 'Save',
    DELETE: 'Delete',
  }
  return (
    <>
      <ListPageHeader title="Example Pod List Page"/>
      <ListPageCreateDropdown createAccessReview={access} items=
        {items}>Actions</ListPageCreateDropdown>
    </ListPageHeader>
    </>
  );
};
```

Parameter Name	Description
items	key:ReactNode pairs of items to display in dropdown component

Parameter Name	Description
onClick	callback function for click on dropdown items
createAccessReview	(optional) object with namespace and kind used to determine access
children	(optional) children for the dropdown toggle

ListPageFilter

Component that generates filter for list page.

```
// See implementation for more details on RowFilter and FilterValue types
const [staticData, filteredData, onFilterChange] = useListPageFilter(
  data,
  rowFilters,
  staticFilters,
);
// ListPageFilter updates filter state based on user interaction and resulting filtered data can be
// rendered in an independent component.
return (
  <>
    <ListPageHeader .../>
    <ListPageBody>
      <ListPageFilter data={staticData} onFilterChange={onFilterChange} />
      <List data={filteredData} />
    </ListPageBody>
  </>
)
```

Parameter Name	Description
data	An array of data points
loaded	indicates that data has loaded
onFilterChange	callback function for when filter is updated
rowFilters	(optional) An array of RowFilter elements that define the available filter options
nameFilterPlaceholder	(optional) placeholder for name filter
labelFilterPlaceholder	(optional) placeholder for label filter
hideLabelFilter	(optional) only shows the name filter instead of both name and label filter

Parameter Name	Description
hideNameLabelFilter	(optional) hides both name and label filter
columnLayout	(optional) column layout object
hideColumnManagement	(optional) flag to hide the column management

useListPageFilter

A hook that manages filter state for the ListPageFilter component. It returns a tuple containing the data filtered by all static filters, the data filtered by all static and row filters, and a callback that updates rowFilters.

```
// See implementation for more details on RowFilter and FilterValue types
const [staticData, filteredData, onFilterChange] = useListPageFilter(
  data,
  rowFilters,
  staticFilters,
);
// ListPageFilter updates filter state based on user interaction and resulting filtered data can be
// rendered in an independent component.
return (
  <>
    <ListPageHeader .../>
    <ListPageBody>
      <ListPageFilter data={staticData} onFilterChange={onFilterChange} />
      <List data={filteredData} />
    </ListPageBody>
  </>
)
```

Parameter Name	Description
data	An array of data points
rowFilters	(optional) An array of RowFilter elements that define the available filter options
staticFilters	(optional) An array of FilterValue elements that are statically applied to the data

ResourceLink

Component that creates a link to a specific resource type with an icon badge.

```
<ResourceLink
  kind="Pod"
  name="testPod"
  title={metadata.uid}
/>
```

Parameter Name	Description
kind	(optional) the kind of resource i.e. Pod, Deployment, Namespace
groupVersionKind	(optional) object with group, version, and kind
className	(optional) class style for component
displayName	(optional) display name for component, overwrites the resource name if set
inline	(optional) flag to create icon badge and name inline with children
linkTo	(optional) flag to create a Link object - defaults to true
name	(optional) name of resource
namespace	(optional) specific namespace for the kind resource to link to
hideIcon	(optional) flag to hide the icon badge
title	(optional) title for the link object (not displayed)
dataTest	(optional) identifier for testing
onClick	(optional) callback function for when component is clicked
truncate	(optional) flag to truncate the link if too long

ResourceIcon

Component that creates an icon badge for a specific resource type.

```
<ResourceIcon kind="Pod"/>
```

Parameter Name	Description
kind	(optional) the kind of resource i.e. Pod, Deployment, Namespace
groupVersionKind	(optional) object with group, version, and kind

Parameter Name	Description
className	(optional) class style for component

useK8sModel

Hook that retrieves the k8s model for provided K8sGroupVersionKind from redux. It returns an array with the first item as k8s model and second item as **inFlight** status.

```
const Component: React.FC = () => {
  const [model, inFlight] = useK8sModel({ group: 'app'; version: 'v1'; kind: 'Deployment' });
  return ...
}
```

Parameter Name	Description
groupVersionKind	group, version, kind of k8s resource <code>\{@link K8sGroupVersionKind\}</code> is preferred alternatively can pass reference for group, version, kind which is deprecated i.e groupversionkind <code>\{@link K8sResourceKindReference\}</code> .

useK8sModels

Hook that retrieves all current k8s models from redux. It returns an array with the first item as the list of k8s model and second item as **inFlight** status.

```
const Component: React.FC = () => {
  const [models, inFlight] = UseK8sModels();
  return ...
}
```

useK8sWatchResource

Hook that retrieves the k8s resource along with status for loaded and error. It returns an array with first item as resource(s), second item as loaded status and third item as error state if any.

```
const Component: React.FC = () => {
  const watchRes = {
    ...
  }
  const [data, loaded, error] = useK8sWatchResource(watchRes)
  return ...
}
```

Parameter Name	Description
initResource	options needed to watch for resource.

useK8sWatchResources

Hook that retrieves the k8s resources along with their respective status for loaded and error. It returns a map where keys are as provided in initResources and value has three properties data, loaded and error.

```
const Component: React.FC = () => {
  const watchResources = {
    'deployment': {...},
    'pod': {...}
    ...
  }
  const {deployment, pod} = useK8sWatchResources(watchResources)
  return ...
}
```

Parameter Name	Description
initResources	resources need to be watched as key-value pair, wherein key will be unique to resource and value will be options needed to watch for the respective resource.

consoleFetch

A custom wrapper around **fetch** that adds console specific headers and allows for retries and timeouts. It also validates the response status code and throws appropriate error or logs out the user if required. It returns a promise that resolves to the response.

Parameter Name	Description
url	The URL to fetch
options	The options to pass to fetch
timeout	The timeout in milliseconds

consoleFetchJSON

A custom wrapper around **fetch** that adds console specific headers and allows for retries and timeouts. It also validates the response status code and throws appropriate error or logs out the user if required. It returns the response as a JSON object. Uses **consoleFetch** internally. It returns a promise that resolves to the response as JSON object.

Parameter Name	Description
url	The URL to fetch
method	The HTTP method to use. Defaults to GET
options	The options to pass to fetch
timeout	The timeout in milliseconds
cluster	The name of the cluster to make the request to. Defaults to the active cluster the user has selected

consoleFetchText

A custom wrapper around **fetch** that adds console specific headers and allows for retries and timeouts. It also validates the response status code and throws appropriate error or logs out the user if required. It returns the response as a text. Uses **consoleFetch** internally. It returns a promise that resolves to the response as text.

Parameter Name	Description
url	The URL to fetch
options	The options to pass to fetch
timeout	The timeout in milliseconds
cluster	The name of the cluster to make the request to. Defaults to the active cluster the user has selected

getConsoleRequestHeaders

A function that creates impersonation and multicluster related headers for API requests using current redux state. it returns an object containing the appropriate impersonation and clustr reqest headers, based on redux state.

Parameter Name	Description
targetCluster	override the current active cluster with the provided targetCluster

k8sGetResource

It fetches a resource from the cluster, based on the provided options. If the name is provided it returns one resource else it returns all the resources matching the model. It returns a promise that resolves to the response as JSON object with a resource if the name is provided else it returns all the resources matching the model. In case of failure, the promise gets rejected with HTTP error response.

Parameter Name	Description
options	Which are passed as key-value pairs in the map
``	options.model - k8s model
``	options.name - The name of the resource, if not provided then it'll look for all the resources matching the model.
``	options.ns - The namespace to look into, should not be specified for cluster-scoped resources.
``	options.path - Appends as subpath if provided

Parameter Name	Description
``	options.queryParams - The query parameters to be included in the URL.
``	options.requestInit - The fetch init object to use. This can have request headers, method, redirect, etc. See more (link: https://microsoft.github.io/PowerBI-JavaScript/interfaces/node_modules_typedoc_node_modules_typescript_lib_lib_dom_d.requestinit.html)

k8sCreateResource

It creates a resource in the cluster, based on the provided options. It returns a promise that resolves to the response of the resource created. In case of failure promise gets rejected with HTTP error response.

Parameter Name	Description
options	Which are passed as key-value pairs in the map
``	options.model - k8s model
``	options.data - payload for the resource to be created
``	options.path - Appends as subpath if provided
``	options.queryParams - The query parameters to be included in the URL.

k8sUpdateResource

It updates the entire resource in the cluster, based on provided options. When a client needs to replace an existing resource entirely, they can use k8sUpdate. Alternatively can use k8sPatch to perform the partial update. It returns a promise that resolves to the response of the resource updated. In case of failure promise gets rejected with HTTP error response.

Parameter Name	Description
options	which are passed as key-value pair in the map
``	options.model - k8s model
``	options.data - payload for the k8s resource to be updated
``	options.ns - namespace to look into, it should not be specified for cluster-scoped resources.
``	options.name - resource name to be updated.

Parameter Name	Description
``	options.path - Appends as subpath if provided
``	options.queryParams - The query parameters to be included in the URL.

k8sPatchResource

It patches any resource in the cluster, based on provided options. When a client needs to perform the partial update, they can use `k8sPatch`. Alternatively can use `k8sUpdate` to replace an existing resource entirely. See more [Data Tracker](#). It returns a promise that resolves to the response of the resource patched. In case of failure promise gets rejected with HTTP error response.

Parameter Name	Description
options	Which are passed as key-value pairs in the map.
``	options.model - k8s model
``	options.resource - The resource to be patched.
``	options.data - Only the data to be patched on existing resource with the operation, path, and value.
``	options.path - Appends as subpath if provided.
``	options.queryParams - The query parameters to be included in the URL.

k8sDeleteResource

It deletes resources from the cluster, based on the provided model, resource. The garbage collection works based on 'Foreground'|'Background', can be configured with `propagationPolicy` property in provided model or passed in json. It returns a promise that resolves to the response of kind Status. In case of failure promise gets rejected with HTTP error response.

```
{ kind: 'DeleteOptions', apiVersion: 'v1', propagationPolicy }
```

Parameter Name	Description
options	which are passed as key-value pair in the map.
``	options.model - k8s model
``	options.resource - The resource to be deleted.
``	options.path - Appends as subpath if provided

Parameter Name	Description
``	options.queryParams - The query parameters to be included in the URL.
``	options.requestInit - The fetch init object to use. This can have request headers, method, redirect, etc. See more \{@link https://microsoft.github.io/PowerBI-JavaScript/interfaces/node_modules_typedoc_node_modules_typescript_lib_lib_dom_d.requestinit.html }
``	options.json - Can control garbage collection of resources explicitly if provided else will default to model's "propagationPolicy".

k8sListResource

Lists the resources as an array in the cluster, based on provided options. It returns a promise that resolves to the response.

Parameter Name	Description
options	Which are passed as key-value pairs in the map
``	options.model - k8s model
``	options.queryParams - The query parameters to be included in the URL and can pass label selector's as well with key "labelSelector".
``	options.requestInit - The fetch init object to use. This can have request headers, method, redirect, etc. See more \{@link https://microsoft.github.io/PowerBI-JavaScript/interfaces/node_modules_typedoc_node_modules_typescript_lib_lib_dom_d.requestinit.html }

k8sListResourceItems

Same interface as \{@link k8sListResource} but returns the sub items. It returns the apiVersion for the model i.e **group/version**.

getAPIVersionForModel

Provides apiVersion for a k8s model.

Parameter Name	Description
model	k8s model

getGroupVersionKindForResource

Provides a group, version, and kind for a resource. It returns the group, version, kind for the provided resource. If the resource does not have an API group, group "core" will be returned. If the resource has an invalid apiVersion then it'll throw Error.

Parameter Name	Description
resource	k8s resource

getGroupVersionKindForModel

Provides a group, version, and kind for a k8s model. This returns the group, version, kind for the provided model. If the model does not have an apiGroup, group "core" will be returned.

Parameter Name	Description
model	k8s model

StatusPopupSection

Component that shows the status in a popup window. Helpful component for building **console.dashboards/overview/health/resource** extensions.

```
<StatusPopupSection
  firstColumn={
    <>
      <span>{title}</span>
      <span className="text-secondary">
        My Example Item
      </span>
    </>
  }
  secondColumn='Status'
>
```

Parameter Name	Description
firstColumn	values for first column of popup
secondColumn	(optional) values for second column of popup
children	(optional) children for the popup

StatusPopupItem

Status element used in status popup; used in **StatusPopupSection**.

```
<StatusPopupSection
  firstColumn='Example'
  secondColumn='Status'
>
  <StatusPopupItem icon={healthStateMapping[MCGMetrics.state]?.icon}>
    Complete
```

```

</StatusPopuItem>
<StatusPopuItem icon={healthStateMapping[RGWMetrics.state]?.icon}>
  Pending
</StatusPopuItem>
</StatusPopupSection>

```

Parameter Name	Description
value	(optional) text value to display
icon	(optional) icon to display
children	child elements

Overview

Creates a wrapper component for a dashboard.

```

<Overview>
  <OverviewGrid mainCards={mainCards} leftCards={leftCards} rightCards={rightCards} />
</Overview>

```

Parameter Name	Description
className	(optional) style class for div
children	(optional) elements of the dashboard

OverviewGrid

Creates a grid of card elements for a dashboard; used within **Overview**.

```

<Overview>
  <OverviewGrid mainCards={mainCards} leftCards={leftCards} rightCards={rightCards} />
</Overview>

```

Parameter Name	Description
mainCards	cards for grid
leftCards	(optional) cards for left side of grid
rightCards	(optional) cards for right side of grid

InventoryItem

Creates an inventory card item.

```

return (
  <InventoryItem>

```

```

    <InventoryItemTitle>{title}</InventoryItemTitle>
    <InventoryItemBody error={loadError}>
      {loaded && <InventoryItemStatus count={workerNodes.length} icon={<MonitoringIcon />} />}
    </InventoryItemBody>
  </InventoryItem>
)

```

Parameter Name	Description
children	elements to render inside the item

InventoryItemTitle

Creates a title for an inventory card item; used within **InventoryItem**.

```

return (
  <InventoryItem>
    <InventoryItemTitle>{title}</InventoryItemTitle>
    <InventoryItemBody error={loadError}>
      {loaded && <InventoryItemStatus count={workerNodes.length} icon={<MonitoringIcon />} />}
    </InventoryItemBody>
  </InventoryItem>
)

```

Parameter Name	Description
children	elements to render inside the title

InventoryItemBody

Creates the body of an inventory card; used within **InventoryCard** and can be used with **InventoryTitle**.

```

return (
  <InventoryItem>
    <InventoryItemTitle>{title}</InventoryItemTitle>
    <InventoryItemBody error={loadError}>
      {loaded && <InventoryItemStatus count={workerNodes.length} icon={<MonitoringIcon />} />}
    </InventoryItemBody>
  </InventoryItem>
)

```

Parameter Name	Description
children	elements to render inside the Inventory Card or title
error	elements of the div

InventoryItemStatus

Creates a count and icon for an inventory card with optional link address; used within **InventoryItemBody**

```

return (
  <InventoryItem>
    <InventoryItemTitle>{title}</InventoryItemTitle>
    <InventoryItemBody error={loadError}>
      {loaded && <InventoryItemStatus count={workerNodes.length} icon={<MonitoringIcon />} />}
    </InventoryItemBody>
  </InventoryItem>
)

```

Parameter Name	Description
count	count for display
icon	icon for display
linkTo	(optional) link address

InventoryItemLoading

Creates a skeleton container for when an inventory card is loading; used with **InventoryItem** and related components

```

if (loadError) {
  title = <Link to={workerNodesLink}>{t('Worker Nodes')}</Link>;
} else if (!loaded) {
  title = <><InventoryItemLoading /><Link to={workerNodesLink}>{t('Worker Nodes')}</Link></>;
}
return (
  <InventoryItem>
    <InventoryItemTitle>{title}</InventoryItemTitle>
  </InventoryItem>
)

```

useFlag

Hook that returns the given feature flag from FLAGS redux state. It returns the boolean value of the requested feature flag or undefined.

Parameter Name	Description
flag	The feature flag to return

YAMLEditor

A basic lazy loaded YAML editor with hover help and completion.

```

<React.Suspense fallback={<LoadingBox />>
  <YAMLEditor
    value={code}
  />
</React.Suspense>

```

Parameter Name	Description
value	String representing the yaml code to render.
options	Monaco editor options. For more details, please, visit https://microsoft.github.io/monaco-editor/api/interfaces/monaco.editor.IStandaloneEditorConstructionOptions.html .
minHeight	Minimum editor height in valid CSS height values.
showShortcuts	Boolean to show shortcuts on top of the editor.
toolbarLinks	Array of ReactNode rendered on the toolbar links section on top of the editor.
onChange	Callback for on code change event.
onSave	Callback called when the command CTRL / CMD + S is triggered.
ref	React reference to { editor?: IStandaloneCodeEditor } . Using the 'editor' property, you are able to access to all methods to control the editor. For more information, visit https://microsoft.github.io/monaco-editor/api/interfaces/monaco.editor.IStandaloneCodeEditor.html .

ResourceYAMLEditor

A lazy loaded YAML editor for Kubernetes resources with hover help and completion. The component use the YAMLEditor and add on top of it more functionality like resource update handling, alerts, save, cancel and reload buttons, accessibility and more. Unless **onSave** callback is provided, the resource update is automatically handled. It should be wrapped in a React.Suspense component.

```

<React.Suspense fallback=<LoadingBox />>
  <ResourceYAMLEditor
    initialResource={resource}
    header="Create resource"
    onSave={(content) => updateResource(content)}
  />
</React.Suspense>

```

Parameter Name	Description
----------------	-------------

Parameter Name	Description
initialResource	YAML/Object representing a resource to be shown by the editor. This prop is used only during the initial render
header	Add a header on top of the YAML editor
onSave	Callback for the Save button. Passing it will override the default update performed on the resource by the editor

ResourceEventStream

A component to show events related to a particular resource.

```
const [resource, loaded, loadError] = useK8sWatchResource(clusterResource);
return <ResourceEventStream resource={resource} />
```

Parameter Name	Description
resource	An object whose related events should be shown.

usePrometheusPoll

Sets up a poll to Prometheus for a single query. It returns a tuple containing the query response, a boolean flag indicating whether the response has completed, and any errors encountered during the request or post-processing of the request.

Parameter Name	Description
<code>endpoint</code>	<code>{PrometheusEndpoint} props.endpoint</code> - one of the PrometheusEndpoint (label, query, range, rules, targets)
<code>query</code>	<code>{string} [props.query]</code> - (optional) Prometheus query string. If empty or undefined, polling is not started.
<code>delay</code>	<code>{number} [props.delay]</code> - (optional) polling delay interval (ms)
<code>endTime</code>	<code>{number} [props.endTime]</code> - (optional) for QUERY_RANGE endpoint, end of the query range
<code>samples</code>	<code>{number} [props.samples]</code> - (optional) for QUERY_RANGE endpoint

Parameter Name	Description
<code>``</code>	<code>{number} [options.timespan]</code> - (optional) for <code>QUERY_RANGE</code> endpoint
<code>``</code>	<code>{string} [options.namespace]</code> - (optional) a search param to append
<code>``</code>	<code>{string} [options.timeout]</code> - (optional) a search param to append

Timestamp

A component to render timestamp. The timestamps are synchronized between individual instances of the Timestamp component. The provided timestamp is formatted according to user locale.

Parameter Name	Description
timestamp	the timestamp to render. Format is expected to be ISO 8601 (used by Kubernetes), epoch timestamp, or an instance of a Date.
simple	render simple version of the component omitting icon and tooltip.
omitSuffix	formats the date omitting the suffix.
className	additional class name for the component.

useModal

A hook to launch Modals.

```
const context: AppPage: React.FC = () => {  
  const [launchModal] = useModal();  
  const  
  onClick = () => launchModal(ModalComponent);  
  return (  
    <Button onClick=  
      {onClick}>Launch a Modal</Button>  
  )  
}
```

ActionServiceProvider

Component that allows to receive contributions from other plugins for the **console.action/provider** extension type.

```
const context: ActionContext = { 'a-context-id': { dataFromDynamicPlugin } };  
  
...  
  
<ActionServiceProvider context={context}>  
  {{{ actions, options, loaded }}} =>  
    loaded && (  
      <ActionMenu actions={actions} options={options} variant={ActionMenuVariant.DROPDOWN}  
    />  
  )  
</ActionServiceProvider>
```

```

    )
  }
</ActionServiceProvider>

```

Parameter Name	Description
context	Object with contextId and optional plugin data

NamespaceBar

A component that renders a horizontal toolbar with a namespace dropdown menu in the leftmost position. Additional components can be passed in as children and will be rendered to the right of the namespace dropdown. This component is designed to be used at the top of the page. It should be used on pages where the user needs to be able to change the active namespace, such as on pages with k8s resources.

```

const logNamespaceChange = (namespace) => console.log(`New namespace: ${namespace}`);

...

<NamespaceBar onNamespaceChange={logNamespaceChange}>
  <NamespaceBarApplicationSelector />
</NamespaceBar>
<Page>

...

```

Parameter Name	Description
onNamespaceChange	(optional) A function that is executed when a namespace option is selected. It accepts the new namespace in the form of a string as its only argument. The active namespace is updated automatically when an option is selected, but additional logic can be applied via this function. When the namespace is changed, the namespace parameter in the URL will be changed from the previous namespace to the newly selected namespace.
isDisabled	(optional) A boolean flag that disables the namespace dropdown if set to true. This option only applies to the namespace dropdown and has no effect on child components.
children	(optional) Additional elements to be rendered inside the toolbar to the right of the namespace dropdown.

ErrorBoundaryFallbackPage

Creates full page ErrorBoundaryFallbackPage component to display the "Oh no! Something went wrong." message along with the stack trace and other helpful debugging information. This is to be used in conjunction with an component.

```
//in ErrorBoundary component
return (
  if (this.state.hasError) {
    return <ErrorBoundaryFallbackPage errorMessage={errorString} componentStack=
{componentStackString}
    stack={stackTraceString} title={errorString}/>;
  }

  return this.props.children;
)
```

Parameter Name	Description
errorMessage	text description of the error message
componentStack	component trace of the exception
stack	stack trace of the exception
title	title to render as the header of the error boundary page

PerspectiveContext

@deprecated - use the provided **usePerspectiveContext** insteadCreates the perspective context.

Parameter Name	Description
PerspectiveContextType	object with active perspective and setter

useAccessReviewAllowed

@deprecated - Use useAccessReview from @console/dynamic-plugin-sdk instead.Hook that provides allowed status about user access to a given resource. It returns the **isAllowed** boolean value.

Parameter Name	Description
resourceAttributes	resource attributes for access review
impersonate	impersonation details

useSafetyFirst

@deprecated - This hook is not related to console functionality.Hook that ensures a safe asynchronous setting of React state in case a given component could be unmounted. It returns an array with a pair of state value and it's set function.

Parameter Name	Description
initialState	initial state value

7.5.3. Troubleshooting your dynamic plugin

Refer to this list of troubleshooting tips if you run into issues loading your plugin.

- Verify that you have enabled your plugin in the console Operator configuration and your plugin name is the output by running the following command:


```
$ oc get console.operator.openshift.io cluster -o jsonpath='{.spec.plugins}'
```

 - Verify the enabled plugins on the status card of the **Overview** page in the **Administrator perspective**. You will need to refresh your browser if the plugin was recently enabled.
- Verify your plugin service is healthy by:
 - Verifying your plugin pod status is running and your containers are ready.
 - Verifying the service label selector matches the pod and the target port is correct.
 - Curl the **plugin-manifest.json** from the service in a terminal on the console pod or another pod on the cluster.
- Verify your **ConsolePlugin** resource name (**consolePlugin.name**) matches the plugin name used in **package.json**.
- Verify your service name, namespace, port, and path are declared correctly in the **ConsolePlugin** resource.
- Verify your plugin service uses HTTPS and service serving certificates.
- Verify any certificates or connection errors in the console pod logs.
- Verify the feature flag your plugin relies on is not disabled.
- Verify your plugin does not have any **consolePlugin.dependencies** in **package.json** that are not met.
 - This can include console version dependencies or dependencies on other plugins. Filter the JS console in your browser for your plugin's name to see messages that are logged.
- Verify there are no typos in the nav extension perspective or section IDs.
 - Your plugin may be loaded, but nav items missing if IDs are incorrect. Try navigating to a plugin page directly by editing the URL.
- Verify there are no network policies that are blocking traffic from the console pod to your plugin service.
 - If necessary, adjust network policies to allow console pods in the openshift-console namespace to make requests to your service.
- Verify the list of dynamic plugins to be loaded in your browser in the **Console** tab of the developer tools browser.
 - Evaluate **window.SERVER_FLAGS.consolePlugins** to see the dynamic plugin on the Console frontend.

Additional resources

Understanding service serving certificates

CHAPTER 8. ABOUT THE WEB TERMINAL IN THE WEB CONSOLE

You can launch an embedded command line terminal instance in the web console. You must first install the Web Terminal Operator to use the web terminal.



NOTE

Cluster administrators can access the web terminal in OpenShift Container Platform 4.7 and later.

This terminal instance is preinstalled with common CLI tools for interacting with the cluster, such as **oc**, **kubectlo**, **odo**, **kn**, **tkn**, **helm**, **kubens**, **subctl**, and **kubectx**. It also has the context of the project you are working on and automatically logs you in using your credentials.

8.1. INSTALLING THE WEB TERMINAL

You can install the web terminal using the Web Terminal Operator listed in the OpenShift Container Platform OperatorHub. When you install the Web Terminal Operator, the custom resource definitions (CRDs) that are required for the command line configuration, such as the **DevWorkspace** CRD, are automatically installed. The web console creates the required resources when you open the web terminal.

Prerequisites

- Access to an OpenShift Container Platform cluster using an account with **cluster-admin** permissions.

Procedure

1. In the **Administrator** perspective of the web console, navigate to **Operators → OperatorHub**.
2. Use the **Filter by keyword** box to search for the **Web Terminal** Operator in the catalog, and then click the **Web Terminal** tile.
3. Read the brief description about the Operator on the **Web Terminal** page, and then click **Install**.
4. On the **Install Operator** page, retain the default values for all fields.
 - The **fast** option in the **Update Channel** menu enables installation of the latest release of the Web Terminal Operator.
 - The **All namespaces on the cluster** option in the **Installation Mode** menu enables the Operator to watch and be available to all namespaces in the cluster.
 - The **openshift-operators** option in the **Installed Namespace** menu installs the Operator in the default **openshift-operators** namespace.
 - The **Automatic** option in the **Approval Strategy** menu ensures that the future upgrades to the Operator are handled automatically by the Operator Lifecycle Manager.
5. Click **Install**.

6. In the **Installed Operators** page, click the **View Operator** to verify that the Operator is listed on the **Installed Operators** page.




NOTE

Prior to OpenShift Container Platform 4.8, the Web Terminal Operator bundled all its functionality in a single Operator. As of OpenShift Container Platform 4.8, the Web Terminal Operator installs the DevWorkspace Operator as a dependency to provide the same features.

7. After the Operator is installed, refresh your page to see the command line terminal icon on the upper right of the console.

8.2. USING THE WEB TERMINAL

After the Web Terminal Operator is installed, you can use the web terminal as follows:

1. To launch the web terminal, click the command line terminal icon () on the upper right of the console. A web terminal instance is displayed in the **Command line terminal** pane. This instance is automatically logged in with your credentials.
2. Select the project where the **DevWorkspace** CR must be created from the **Project** drop-down list. By default, the current project is selected.



NOTE

- The **DevWorkspace** CR is created only if it does not already exist.
- The **openshift-terminal** project is the default project used for cluster administrators. They do not have the option to choose another project.

3. Click **Start** to initialize the web terminal using the selected project.
After the web terminal is initialized, you can use the preinstalled CLI tools like **oc**, **kubectl**, **odo**, **kn**, **tkn**, **helm**, **kubens**, **subctl**, and **kubectx** in the web terminal.
4. Click + to open multiple tabs within web terminal in the console.



NOTE

- You can re-run commands by selecting them from the list of commands you have run in the terminal. These commands persist across multiple terminal sessions.
- The web terminal remains open until you close it or you close the browser window or tab.

8.3. UNINSTALLING THE WEB TERMINAL

Uninstalling the web terminal is a two-step process:

1. Uninstall the Web Terminal Operator and related custom resources (CRs) that were added when you installed the Operator.

2. Uninstall the DevWorkspace Operator and its related custom resources that were added as a dependency of the Web Terminal Operator.

Uninstalling the Web Terminal Operator does not remove any of its custom resource definitions (CRDs) or managed resources that are created when the Operator is installed. These components must be manually uninstalled for security purposes. Removing these components also allows you to save cluster resources by ensuring that terminals do not idle when the Operator is uninstalled.

Prerequisites

- Access to an OpenShift Container Platform cluster using an account with **cluster-admin** permissions.

8.3.1. Removing the Web Terminal Operator and the custom resources that support it


Use the console and the CLI to delete any existing web terminals and CRs that were created during the installation of the Web Terminal Operator.



NOTE

Prior to OpenShift Container Platform 4.8, the Web Terminal Operator used different CRDs to provide Web Terminal capabilities. To uninstall versions 1.2.1 and below of the Web Terminal Operator, refer to the documentation for OpenShift Container Platform 4.7.

Procedure

1. Uninstall the Web Terminal Operator using the web console:
 - a. In the **Administrator** perspective of the web console, navigate to **Operators → Installed Operators**.
 - b. Scroll the filter list or type a keyword into the **Filter by name** box to find the **Web Terminal Operator**.
 - c. Click the Options menu  for the Web Terminal Operator, and then select **Uninstall Operator**.
 - d. In the **Uninstall Operator** confirmation dialog box, click **Uninstall** to remove the Operator, Operator deployments, and pods from the cluster. The Operator stops running and no longer receives updates.
2. Remove the CRs used by the Operator.

```
$ oc delete devworkspaces.workspace.devfile.io --all-namespaces \
  --selector 'console.openshift.io/terminal=true' --wait
```

```
$ oc delete devworkspacetemplates.workspace.devfile.io --all-namespaces \
  --selector 'console.openshift.io/terminal=true' --wait
```

8.3.2. Deleting the DevWorkspace Operator dependency

Use the CLI to delete the custom resource definitions (CRDs) and additional resources that are created during installation of the Web Terminal Operator.



IMPORTANT

The DevWorkspace Operator functions as a standalone Operator and may be required as a dependency for other Operators installed on the cluster (for example, the Red Hat OpenShift Dev Spaces Operator may depend on it). Follow the steps below only if you are sure the DevWorkspace Operator is no longer needed.

Procedure

1. Remove the **DevWorkspace** custom resources used by the Operator, along with any related Kubernetes objects, such as deployments.

```
$ oc delete devworkspaces.workspace.devfile.io --all-namespaces --all --wait
```

```
$ oc delete devworkspaceroutings.controller.devfile.io --all-namespaces --all --wait
```



WARNING

If this step is not complete, finalizers make it difficult to fully uninstall the Operator easily.

2. Remove the CRDs used by the Operator:



WARNING

The DevWorkspace Operator provides custom resource definitions (CRDs) that use conversion webhooks. Failing to remove these CRDs can cause issues on the cluster.

```
$ oc delete customresourcedefinitions.apiextensions.k8s.io  
devworkspaceroutings.controller.devfile.io
```

```
$ oc delete customresourcedefinitions.apiextensions.k8s.io  
devworkspaces.workspace.devfile.io
```

```
$ oc delete customresourcedefinitions.apiextensions.k8s.io  
devworkspacetemplates.workspace.devfile.io
```

```
$ oc delete customresourcedefinitions.apiextensions.k8s.io
devworkspaceoperatorconfigs.controller.devfile.io
```

3. Verify that all involved custom resource definitions are removed. The following command should not display any result.

```
$ oc get customresourcedefinitions.apiextensions.k8s.io | grep "devfile.io"
```

4. Remove the **devworkspace-webhook-server** deployment, mutating, and validating webhooks:

```
$ oc delete deployment/devworkspace-webhook-server -n openshift-operators
```

```
$ oc delete mutatingwebhookconfigurations controller.devfile.io
```

```
$ oc delete validatingwebhookconfigurations controller.devfile.io
```



NOTE

If you remove the **devworkspace-webhook-server** deployment without removing the mutating and validating webhooks, you will not be able to use **oc exec** commands to run commands in a container on the cluster. After you remove the webhooks you will be able to use the **oc exec** commands again.

5. Remove any remaining services, secrets, and config maps. Depending on the installation, some resources included in the following command may not exist on the cluster.

```
$ oc delete all --selector app.kubernetes.io/part-of=devworkspace-
operator,app.kubernetes.io/name=devworkspace-webhook-server -n openshift-operators
```

```
$ oc delete serviceaccounts devworkspace-webhook-server -n openshift-operators
```

```
$ oc delete configmap devworkspace-controller -n openshift-operators
```

```
$ oc delete clusterrole devworkspace-webhook-server
```

```
$ oc delete clusterrolebinding devworkspace-webhook-server
```

6. Uninstall the Operator using the web console:

- a. In the **Administrator** perspective of the web console, navigate to **Operators → Installed Operators**.
- b. Scroll the filter list or type a keyword into the **Filter by name** box to find the **DevWorkspace** Operator.



- c. Click the Options menu for the DevWorkspace Operator, and then select **Uninstall Operator**.

- d. In the **Uninstall Operator** confirmation dialog box, click **Uninstall** to remove the Operator, Operator deployments, and pods from the cluster. The Operator stops running and no longer receives updates.

CHAPTER 9. DISABLING THE WEB CONSOLE IN OPENSIFT CONTAINER PLATFORM

You can disable the OpenShift Container Platform web console.

9.1. PREREQUISITES

- Deploy an OpenShift Container Platform cluster.

9.2. DISABLING THE WEB CONSOLE

You can disable the web console by editing the **consoles.operator.openshift.io** resource.

- Edit the **consoles.operator.openshift.io** resource:

```
$ oc edit consoles.operator.openshift.io cluster
```

The following example displays the parameters from this resource that you can modify:

```
apiVersion: operator.openshift.io/v1
kind: Console
metadata:
  name: cluster
spec:
  managementState: Removed 1
```

- 1 Set the **managementState** parameter value to **Removed** to disable the web console. The other valid values for this parameter are **Managed**, which enables the console under the cluster's control, and **Unmanaged**, which means that you are taking control of web console management.

CHAPTER 10. CREATING QUICK START TUTORIALS IN THE WEB CONSOLE

If you are creating quick start tutorials for the OpenShift Container Platform web console, follow these guidelines to maintain a consistent user experience across all quick starts.

10.1. UNDERSTANDING QUICK STARTS

A quick start is a guided tutorial with user tasks. In the web console, you can access quick starts under the **Help** menu. They are especially useful for getting oriented with an application, Operator, or other product offering.

A quick start primarily consists of tasks and steps. Each task has multiple steps, and each quick start has multiple tasks. For example:

- Task 1
 - Step 1
 - Step 2
 - Step 3
- Task 2
 - Step 1
 - Step 2
 - Step 3
- Task 3
 - Step 1
 - Step 2
 - Step 3

10.2. QUICK START USER WORKFLOW

When you interact with an existing quick start tutorial, this is the expected workflow experience:

1. In the **Administrator** or **Developer** perspective, click the **Help icon** and select **Quick Starts**.
2. Click a quick start card.
3. In the panel that appears, click **Start**.
4. Complete the on-screen instructions, then click **Next**.
5. In the **Check your work** module that appears, answer the question to confirm that you successfully completed the task.
 - a. If you select **Yes**, click **Next** to continue to the next task.

- b. If you select **No**, repeat the task instructions and check your work again.
6. Repeat steps 1 through 6 above to complete the remaining tasks in the quick start.
7. After completing the final task, click **Close** to close the quick start.

10.3. QUICK START COMPONENTS

A quick start consists of the following sections:

- **Card:** The catalog tile that provides the basic information of the quick start, including title, description, time commitment, and completion status
- **Introduction:** A brief overview of the goal and tasks of the quick start
- **Task headings:** Hyper-linked titles for each task in the quick start
- **Check your work module** A module for a user to confirm that they completed a task successfully before advancing to the next task in the quick start
- **Hints:** An animation to help users identify specific areas of the product
- **Buttons**
 - **Next and back buttons** Buttons for navigating the steps and modules within each task of a quick start
 - **Final screen buttons** Buttons for closing the quick start, going back to previous tasks within the quick start, and viewing all quick starts

The main content area of a quick start includes the following sections:

- **Card copy**
- **Introduction**
- **Task steps**
- **Modals and in-app messaging**
- **Check your work module**

10.4. CONTRIBUTING QUICK STARTS

OpenShift Container Platform introduces the quick start custom resource, which is defined by a **ConsoleQuickStart** object. Operators and administrators can use this resource to contribute quick starts to the cluster.

Prerequisites

- You must have cluster administrator privileges.

Procedure

1. To create a new quick start, run:

```
$ oc get -o yaml consolequickstart spring-with-s2i > my-quick-start.yaml
```

2. Run:

```
$ oc create -f my-quick-start.yaml
```

3. Update the YAML file using the guidance outlined in this documentation.

4. Save your edits.

10.4.1. Viewing the quick start API documentation

Procedure

- To see the quick start API documentation, run:

```
$ oc explain consolequickstarts
```

Run **oc explain -h** for more information about **oc explain** usage.

10.4.2. Mapping the elements in the quick start to the quick start CR

This section helps you visually map parts of the quick start custom resource (CR) with where they appear in the quick start within the web console.

10.4.2.1. conclusion element

Viewing the conclusion element in the YAML file

```
...
summary:
  failed: Try the steps again.
  success: Your Spring application is running.
title: Run the Spring application
conclusion: >-
  Your Spring application is deployed and ready. 1
```

1 conclusion text

Viewing the conclusion element in the web console

The conclusion appears in the last section of the quick start.

Get started with Spring 10 minutes



- 1 Create a Spring application
- 2 View the build status
- 3 View the associated Git repository
- 4 View the pod status
- 5 Change the deployment icon to Spring
- 6 Run the Spring application

Your Spring application is deployed and ready.

10.4.2.2. description element

Viewing the description element in the YAML file

```
apiVersion: console.openshift.io/v1
kind: ConsoleQuickStart
metadata:
  name: spring-with-s2i
spec:
  description: 'Import a Spring Application from git, build, and deploy it onto OpenShift.' 1
  ...
```

1 description text

Viewing the description element in the web console

The description appears on the introductory tile of the quick start on the **Quick Starts** page.



Get started with Spring

🕒 10 minutes

Import a Spring Application from git, build, and deploy it onto OpenShift.

10.4.2.3. displayName element

Viewing the displayName element in the YAML file

```
apiVersion: console.openshift.io/v1
kind: ConsoleQuickStart
metadata:
  name: spring-with-s2i
spec:
  description: 'Import a Spring Application from git, build, and deploy it onto OpenShift.'
  displayName: Get started with Spring 1
  durationMinutes: 10
```

1 **displayName** text.

Viewing the displayName element in the web console

The display name appears on the introductory tile of the quick start on the **Quick Starts** page.



Get started with Spring

🕒 10 minutes

Import a Spring Application from git, build, and deploy it onto OpenShift.

10.4.2.4. durationMinutes element

Viewing the durationMinutes element in the YAML file

```
apiVersion: console.openshift.io/v1
kind: ConsoleQuickStart
metadata:
  name: spring-with-s2i
spec:
  description: 'Import a Spring Application from git, build, and deploy it onto OpenShift.'
  displayName: Get started with Spring
  durationMinutes: 10 ❶
```

- ❶ **durationMinutes** value, in minutes. This value defines how long the quick start should take to complete.

Viewing the durationMinutes element in the web console

The duration minutes element appears on the introductory tile of the quick start on the **Quick Starts** page.

🕒 10 minutes

111

```

0LjctMzAuMTUsNDkuNzctNDAuMTFhMjEyLDIxMiwwLDAsMSw2NS45My0yNS43M0ExOTgsMTk4LDA
sMCwXLDUxMiwxMTYuMjdhMTk2LjExLDE5Ni4xMSwwLDAsMSwzMiwwLjFjNC41LjKxLDkuMzYsMi4wN
wxNC41MywzLjUyLDYwLjQxLDIwLjQ4LDg0LjkyLDkxLjA1LTQ3LjQ0LDI0OC4wNi0yOC43NSwzNC4x
Mi0xNDAuNywxOTQuODQtMTg0LjY2LDI2OC40MmE2MzAuODYsNjMwLjg2LDAsMCwwLTMzLjlyLD
U4LjMyQzI3NiwwNTUuMzQsMjY1LjQsNTk4LDI2NS40LDUyMC4yOSwyNjUuNCwzNDAuNjEsMzExLjY
5LDI0MC43NCwzNjQuMTUsMTg1LjIzWiIvPjxwYXRoIGNsYXNzPSJjbHMtMyIgZD0iTTUyNy41NCwzO
DQuODNjODQuMDYtOTkuNywxMTYuMDYtMTc3LjI4LDk1LjlyLTlzMCA3NCwzMS42MiwwLjY5LDI0LD
E5LjIsMzcuMDYsMzEuMTMsNTluNDgsNTUuNSw5OC43OCwzNTUuMzgsOTguNzgsMzM1LjA3LDAs
NzcuNzEtMTAuNiwxMzUuMDUtMjcuNzcsMTc3LjRhNjI4LjczLDYyOC43MywwLDAsMC0zMy4yMy01OC
4zMmMtMzktNjUuMjYtMTMxLjQ1LTE5OS0xNzEuOTMtMjUyLjI3QzUyNi4zMwzODYuMjksNTI3LDM4
NS41MiwwMjcuNTQsMzg0LjgzWiIvPjxwYXRoIGNsYXNzPSJjbHMtNCIgZD0iTTEzNC41OCw5MDguM
DdoLS4wNmEuMzkuMzksMCwwLDEtLjI3LS4xMwMtMTE5LjUyLTEyMS4wNy0xNTUtMjg3LjQtNDcuN
TQtNDA0LjU4LDM0LjYzLTQxLjE0LDEyMC0xNTEuNiwyMDluNzUtMjYyLjE5LTMuMTMsNy02LjEyLDE
0LjI1LTguOTIsMjEuNjktMjQuMzQsNjQuNDUtMzYuNjcsMTQ0LjMyLTM2LjY3LDIzNy40MSwwLDU2LjU
zLDUuNTgsMTA2LDE2LjU5LDE0Ny4xNEEzMDcuNDksMzA3LjQ5LDAsMCwwLDI4MC45MSw3MjND
MjM3LDgxNi44OCwyMTYuOTMsODkzLjKzLDEzNC41OCw5MDguMDdali8+PHBhdGggY2xhc3M9ImN
scy01liBkPSJNNTgzLjQzLDgxMy43OUm1NjAuMTgsNzI3LjcyLDUxMiwwNjQuMTUsNTEyLDY2NC4xN
XMtNDguMTcsNjMuNTctNzEuNDMsMTQ5LjY0Yy00OC40NS02Ljc0LTEwMC45MS0yNy41Mi0xMzUu
NjYtOTEuMThhNjQ1LjY4LDY0NS42OCwwLDAsMSwzOS41Ny03MS41NGwuMjEtLjMyLjE5LS4zM2M
zOC02My42MywzMjYuNC0xOTEuMzcsMTY3LjEyLTI0NS42NiwwMC43MSw1NC4yOCwzMjkuMSwXO
DIsMTY3LjEyLDE0NS42NmwwMTkuMzMuMjEuMzJhNjQ1LjY4LDY0NS42OCwwLDAsMSwzOS41Nyw
3MS41NEM2ODQuMzQsNzg2LjI3LDYzMS44OCw4MDcuMDUsNTgzLjQzLDgxMy43OVoiLz48cGF0a
CBjbGFzc20iY2xzLTQiIGQ9Ik04ODkuNzUsOTA4YS4zOS4zOSwwLDAsMS0uMjcuMTFoLS4wNkM4M
DcuMDcsODkzLjKzLDE4NywwMTYuODgsNzQzLjA5LDEyMzEuMDcuNDksMzA3LjQ5LDAsMCwwLDIwL
jQ1LTU1LjU0YzExLTQxLjExLDE2LjU5LTkwLjYxLDE2LjU5LTE0Ny4xNCwwLTkzLjA4LTEyLjMzLDE3M
y0zNi42Ni0yMzcuNHEtNC4yMi0xMS4xNi04LjKzLTlxdjODluNzUsOTAuNTksMTY4LjEyLDEwMS4wNS
wyMDluNzUsMjYyLjE5QzEwNDQuNzksNjIwLjU2LDEwMDkuMjcsNzg2Ljg5LDg4OS43NSw5MDhali8+
PC9zdmccCg==

```

...

- 1 The icon defined as a base64 value.

Viewing the icon element in the web console

The icon appears on the introductory tile of the quick start on the **Quick Starts** page.



Get started with Spring

🕒 10 minutes

Import a Spring Application from git,
build, and deploy it onto OpenShift.

Viewing the introduction element in the YAML file

```
...
introduction: >- 1
  **Spring** is a Java framework for building applications based on a distributed microservices
  architecture.

  - Spring enables easy packaging and configuration of Spring applications into a self-contained
  executable application which can be easily deployed as a container to OpenShift.

  - Spring applications can integrate OpenShift capabilities to provide a natural "Spring on
  OpenShift" developer experience for both existing and net-new Spring applications. For example:

  - Externalized configuration using Kubernetes ConfigMaps and integration with Spring Cloud
  Kubernetes

  - Service discovery using Kubernetes Services

  - Load balancing with Replication Controllers

  - Kubernetes health probes and integration with Spring Actuator

  - Metrics: Prometheus, Grafana, and integration with Spring Cloud Sleuth

  - Distributed tracing with Istio & Jaeger tracing

  - Developer tooling through Red Hat OpenShift and Red Hat CodeReady developer tooling to
  quickly scaffold new Spring projects, gain access to familiar Spring APIs in your favorite IDE, and
  deploy to Red Hat OpenShift
...
```

1 The introduction introduces the quick start and lists the tasks within it.

Viewing the introduction element in the web console

After clicking a quick start card, a side panel slides in that introduces the quick start and lists the tasks within it.

Get started with Spring 10 minutes



Spring is a Java framework for building applications based on a distributed microservices architecture.

- Spring enables easy packaging and configuration of Spring applications into a self-contained executable application which can be easily deployed as a container to OpenShift.
- Spring applications can integrate OpenShift capabilities to provide a natural "Spring on OpenShift" developer experience for both existing and net-new Spring applications. For example:
 - Externalized configuration using Kubernetes ConfigMaps and integration with Spring Cloud Kubernetes
 - Service discovery using Kubernetes Services
 - Load balancing with Replication Controllers
 - Kubernetes health probes and integration with Spring Actuator
 - Metrics: Prometheus, Grafana, and integration with Spring Cloud Sleuth
 - Distributed tracing with Istio & Jaeger tracing
- Developer tooling through Red Hat OpenShift and Red Hat CodeReady developer tooling to quickly scaffold new Spring projects, gain access to familiar Spring APIs in your favorite IDE, and deploy to Red Hat OpenShift

In this quick start, you will complete 6 tasks:

- 1 [Create a Spring application](#)
- 2 [View the build status](#)
- 3 [View the associated Git repository](#)
- 4 [View the pod status](#)
- 5 [Change the deployment icon to Spring](#)
- 6 [Run the Spring application](#)

Start

10.4.3. Adding a custom icon to a quick start

A default icon is provided for all quick starts. You can provide your own custom icon.

Procedure

1. Find the **.svg** file that you want to use as your custom icon.
2. Use an [online tool to convert the text to base64](#) .
3. In the YAML file, add **icon: >-**, then on the next line include **data:image/svg+xml;base64** followed by the output from the base64 conversion. For example:

```
icon: >-
data:image/svg+xml;base64,PHN2ZyB4bWxucz0iaHR0cDovL3d3dy53My5vcmcvMjAwMC9zdmcilHJvbGU9ImltZylddmld.
```

10.4.4. Limiting access to a quick start

Not all quick starts should be available for everyone. The **accessReviewResources** section of the YAML file provides the ability to limit access to the quick start.

To only allow the user to access the quick start if they have the ability to create **HelmChartRepository** resources, use the following configuration:

```
accessReviewResources:
- group: helm.openshift.io
  resource: helmchartrepositories
  verb: create
```

To only allow the user to access the quick start if they have the ability to list Operator groups and package manifests, thus ability to install Operators, use the following configuration:

```
accessReviewResources:
- group: operators.coreos.com
  resource: operatorgroups
  verb: list
- group: packages.operators.coreos.com
  resource: packagemanifests
  verb: list
```

10.4.5. Linking to other quick starts

Procedure

- In the **nextQuickStart** section of the YAML file, provide the **name**, not the **displayName**, of the quick start to which you want to link. For example:

```
nextQuickStart:
- add-healthchecks
```

10.4.6. Supported tags for quick starts

Write your quick start content in markdown using these tags. The markdown is converted to HTML.

Tag	Description
'b',	Defines bold text.
'img',	Embeds an image.
'i',	Defines italic text.
'strike',	Defines strike-through text.
's',	Defines smaller text
'del',	Defines smaller text.
'em',	Defines emphasized text.
'strong',	Defines important text.
'a',	Defines an anchor tag.
'p',	Defines paragraph text.
'h1',	Defines a level 1 heading.
'h2',	Defines a level 2 heading.
'h3',	Defines a level 3 heading.
'h4',	Defines a level 4 heading.
'ul',	Defines an unordered list.
'ol',	Defines an ordered list.
'li',	Defines a list item.
'code',	Defines a text as code.
'pre',	Defines a block of preformatted text.
'button',	Defines a button in text.

10.4.7. Quick start highlighting markdown reference

The highlighting, or hint, feature enables Quick Starts to contain a link that can highlight and animate a component of the web console.

The markdown syntax contains:

- Bracketed link text
- The **highlight** keyword, followed by the ID of the element that you want to animate

10.4.7.1. Perspective switcher

```
[Perspective switcher]{{highlight qs-perspective-switcher}}
```

10.4.7.2. Administrator perspective navigation links

```
[Home]{{highlight qs-nav-home}}
[Operators]{{highlight qs-nav-operators}}
[Workloads]{{highlight qs-nav-workloads}}
[Serverless]{{highlight qs-nav-serverless}}
[Networking]{{highlight qs-nav-networking}}
[Storage]{{highlight qs-nav-storage}}
[Service catalog]{{highlight qs-nav-servicecatalog}}
[Compute]{{highlight qs-nav-compute}}
[User management]{{highlight qs-nav-usermanagement}}
[Administration]{{highlight qs-nav-administration}}
```

10.4.7.3. Developer perspective navigation links

```
[Add]{{highlight qs-nav-add}}
[Topology]{{highlight qs-nav-topology}}
[Search]{{highlight qs-nav-search}}
[Project]{{highlight qs-nav-project}}
[Helm]{{highlight qs-nav-helm}}
```

10.4.7.4. Common navigation links

```
[Builds]{{highlight qs-nav-builds}}
[Pipelines]{{highlight qs-nav-pipelines}}
[Monitoring]{{highlight qs-nav-monitoring}}
```

10.4.7.5. Masthead links

```
[CloudShell]{{highlight qs-masthead-cloudshell}}
[Utility Menu]{{highlight qs-masthead-utilitymenu}}
[User Menu]{{highlight qs-masthead-usermenu}}
[Applications]{{highlight qs-masthead-applications}}
[Import]{{highlight qs-masthead-import}}
[Help]{{highlight qs-masthead-help}}
[Notifications]{{highlight qs-masthead-notifications}}
```

10.4.8. Code snippet markdown reference

You can execute a CLI code snippet when it is included in a quick start from the web console. To use this feature, you must first install the Web Terminal Operator. The web terminal and code snippet actions that execute in the web terminal are not present if you do not install the Web Terminal Operator. Alternatively, you can copy a code snippet to the clipboard regardless of whether you have the Web Terminal Operator installed or not.

10.4.8.1. Syntax for inline code snippets

```
`code block`{{copy}}
`code block`{{execute}}
```



NOTE

If the **execute** syntax is used, the **Copy to clipboard** action is present whether you have the Web Terminal Operator installed or not.

10.4.8.2. Syntax for multi-line code snippets

```
```
multi line code block
```{{copy}}

```
multi line code block
```{{execute}}
```

10.5. QUICK START CONTENT GUIDELINES

10.5.1. Card copy

You can customize the title and description on a quick start card, but you cannot customize the status.

- Keep your description to one to two sentences.
- Start with a verb and communicate the goal of the user. Correct example:

Create a serverless application.

10.5.2. Introduction

After clicking a quick start card, a side panel slides in that introduces the quick start and lists the tasks within it.

- Make your introduction content clear, concise, informative, and friendly.
- State the outcome of the quick start. A user should understand the purpose of the quick start before they begin.
- Give action to the user, not the quick start.
 - **Correct example:**

In this quick start, you will deploy a sample application to {product-title}.

- **Incorrect example:**

This quick start shows you how to deploy a sample application to {product-title}.

- The introduction should be a maximum of four to five sentences, depending on the complexity of the feature. A long introduction can overwhelm the user.
- List the quick start tasks after the introduction content, and start each task with a verb. Do not specify the number of tasks because the copy would need to be updated every time a task is added or removed.

- **Correct example:**

Tasks to complete: Create a serverless application; Connect an event source; Force a new revision

- **Incorrect example:**

You will complete these 3 tasks: Creating a serverless application; Connecting an event source; Forcing a new revision

10.5.3. Task steps

After the user clicks **Start**, a series of steps appears that they must perform to complete the quick start.

Follow these general guidelines when writing task steps:

- Use "Click" for buttons and labels. Use "Select" for checkboxes, radio buttons, and drop-down menus.
- Use "Click" instead of "Click on"

- **Correct example:**

Click OK.

- **Incorrect example:**

Click on the OK button.

- Tell users how to navigate between **Administrator** and **Developer** perspectives. Even if you think a user might already be in the appropriate perspective, give them instructions on how to get there so that they are definitely where they need to be.

Examples:

Enter the Developer perspective: In the main navigation, click the dropdown menu and select Developer.

Enter the Administrator perspective: In the main navigation, click the dropdown menu and select Admin.

- Use the "Location, action" structure. Tell a user where to go before telling them what to do.

- **Correct example:**
 - In the node.js deployment, hover over the icon.
- **Incorrect example:**
 - Hover over the icon in the node.js deployment.
- Keep your product terminology capitalization consistent.
- If you must specify a menu type or list as a dropdown, write "dropdown" as one word without a hyphen.
- Clearly distinguish between a user action and additional information on product functionality.
 - **User action:**
 - Change the time range of the dashboard by clicking the dropdown menu and selecting time range.
 - **Additional information:**
 - To look at data in a specific time frame, you can change the time range of the dashboard.
- Avoid directional language, like "In the top-right corner, click the icon". Directional language becomes outdated every time UI layouts change. Also, a direction for desktop users might not be accurate for users with a different screen size. Instead, identify something using its name.
 - **Correct example:**
 - In the navigation menu, click Settings.
 - **Incorrect example:**
 - In the left-hand menu, click Settings.
- Do not identify items by color alone, like "Click the gray circle". Color identifiers are not useful for sight-limited users, especially colorblind users. Instead, identify an item using its name or copy, like button copy.
 - **Correct example:**
 - The success message indicates a connection.
 - **Incorrect example:**
 - The message with a green icon indicates a connection.
- Use the second-person point of view, you, consistently:
 - **Correct example:**
 - Set up your environment.

- **Incorrect example:**

Let's set up our environment.

10.5.4. Check your work module

- After a user completes a step, a **Check your work** module appears. This module prompts the user to answer a yes or no question about the step results, which gives them the opportunity to review their work. For this module, you only need to write a single yes or no question.
 - If the user answers **Yes**, a check mark will appear.
 - If the user answers **No**, an error message appears with a link to relevant documentation, if necessary. The user then has the opportunity to go back and try again.

10.5.5. Formatting UI elements

Format UI elements using these guidelines:

- Copy for buttons, dropdowns, tabs, fields, and other UI controls: Write the copy as it appears in the UI and bold it.
- All other UI elements—including page, window, and panel names: Write the copy as it appears in the UI and bold it.
- Code or user-entered text: Use monospaced font.
- Hints: If a hint to a navigation or masthead element is included, style the text as you would a link.
- CLI commands: Use monospaced font.
- In running text, use a bold, monospaced font for a command.
- If a parameter or option is a variable value, use an italic monospaced font.
- Use a bold, monospaced font for the parameter and a monospaced font for the option.

10.6. ADDITIONAL RESOURCES

- For voice and tone requirements, refer to [PatternFly's brand voice and tone guidelines](#).
- For other UX content guidance, refer to all areas of [PatternFly's UX writing style guide](#).