

Workshop: Implementing Multi-Layer Container and Kubernetes Security for Automated DevSecOps

Agenda:

- DevSecOps Intro
- Lab Info and walkthrough
- Lab 1 - 3
- Break
- Lab 4 - 5
- Q & A


Workshop Info:

Get a lab env: <Insert GuidGrabber client link>

Activation Key:

Lab Guide: <http://bit.ly/rht-security-workshop>

Built-in container runtime protection SELinux and Security Context Constraints



Latest container exploit (runc) can be blocked by SELinux

February 28, 2019 | Dan Walsh

[< Back to all posts](#)

Tags: [Security](#), [Containers](#)


A flaw in runc ([CVE-2019-5736](#)), announced last week, allows container processes to "escape" their containment and execute programs on the host operating system. The good news is that well-configured SELinux can stop it.

<https://www.redhat.com/en/blog/latest-container-exploit-runc-can-be-blocked-selinux>

Security Context Constraint Admission controller

- ▶ By default, containers cannot run with privilege on OpenShift (restricted SCC)
- ▶ Limit access to SCC's that relax policies
 - anyuid, privileged
- ▶ Avoid modifying default policies
- ▶ Create custom policies when necessary and scope access appropriately
- ▶ Design containers with SCC's in mind
- ▶ Test third party containers for supportability

NetworkPolicy




Example Policies

- Allow all traffic inside the project
- Allow traffic from green to gray
- Allow traffic to purple on 8080


```
apiVersion: extensions/v1beta1
kind: NetworkPolicy
metadata:
  name: allow-to-purple-on-8080
spec:
  podSelector:
    matchLabels:
      color: purple
  ingress:
    - ports:
        - protocol: tcp
          port: 8080
```

Projects isolate applications across teams, groups and departments




Enforced with IAM & RBAC

Integrate Security in your CI/CD Pipeline



CONTAINER IMAGE SIGNING




Verify provenance of images

Supports multiple signatures

Registry independent

Enforce signatures at node level via
signing trust policy

IMAGE SIGNING IN PRACTICE



CUSTOM RESOURCE DEFINITIONS

Custom Resource Definitions (CRD's) extend OpenShift capabilities by allowing users to define their own resources



Image signing operator monitors *ImageSigningRequest* resources and takes action based on defined state

Image and signing key

Operator provides feedback on resulting state after signing action in *status* field

Red Hat Summit

May 10-11, 2022

<https://www.redhat.com/en/summit>

Below is a collection of briefs, ebooks, and collateral aligned to a variety of security subtopics. These can be handed out at your workshop if in-person, shared with attendees during the workshop, or sent out as a followup to attendees.

<https://red.ht/securityinfo>

- Detail: [A layered approach to container and Kubernetes security](#)
- Detail: [Definitive guide to Red Hat OpenShift security](#)
- E-book: [Red Hat OpenShift security guide](#)
- E-book: [State of Kubernetes security report](#)
- E-book: [Boost Hybrid Cloud Security](#)
- E-book: [Application development security](#)
- Whitepaper: [Kubernetes-native security](#)
- Whitepaper: [A definitive guide to achieving DevSecOps in Kubernetes environments](#)
- E-book: [Architecting for HIPAA Security Rule](#)
- Datasheet: [Red Hat Advanced Cluster Security for Kubernetes](#)

Thank you

Red Hat is the world's leading provider of enterprise open source software solutions. Award-winning support, training, and consulting services make

Red Hat a trusted adviser to the Fortune 500.



linkedin.com/company/red-hat



youtube.com/user/RedHatVideos



facebook.com/redhatinc



twitter.com/RedHat