
# Backup and Disaster Recovery

Optional subheading



# BACKUP an OPENSHIFT Cluster






## **Backup Solutions for Red Hat OpenShift**

#### **Business Continuity**


OpenShift OADP 1.1 - Native backup utility with 4.12





- Application level (Namespace), consistent backups with OADP
- CLI based **scheduling and management** of backups
- **Built-in data mover** enables CSI-based storage snapshots to be backed up to a remote S3 compatible object store.
  - Plugable DataMover support is Tech Preview (ie. VolSync)
- Supports all OpenShift storage provisioners that also support
   CSI Snapshots

#### **OADP** Operator



OpenShift API for Data Protection (OADP) supports the following features:

#### **Backup**

You can back up all resources in your cluster or you can filter the resources by type, namespace, or label.

OADP backs up Kubernetes objects and internal images by saving them as an archive file on object storage. Restore

You can restore resources and PVs from a backup. You can restore all objects in a backup or filter the restored objects by namespace, PV, or label.

#### **Schedule**

You can schedule backups at specified intervals.

#### Hooks

You can use hooks to run commands in a container on a pod



## Business Continuity and Disaster recovery



## OCP Application Backup – Key Components

3<sup>rd</sup> party backup Applications

Backup CLI



OADP operator
















- Third party backup Applications /native CLI
  - Handles Backup policy management, backup scheduling, retention and restore management and data movement
- OADP OpenShift App Data Protection API
  - Enables namespace or label scoped backups with all ensuing cluster resources and application data (PVs)
  - Ensures OCP version independence and works across storage providers (via pluq-ins)
- ODF PV Snapshots via CSI
  - PV/PVC backups of ODF volumes through standard CSI interfaces
  - Can be used with or without OADP



## Resiliency Solutions for different service level objectives



- Comprehensive protection solutions against wide spectrum of failures
- Beyond Data Protection --> Full Application protection
- Resiliency built into the platform Available to all stateful and stateless applications on OpenShift
- OCP + ODF + ACM integrated stack lends towards Automated and Simplified Application granular protection



### OCP Integrated, Full Stack DR Protection

Multi-Site Multi Cluster Manager





#### **RHACM**

ODR Hub Operator –
 Orchestrates & Automates
 DR operations across clusters

Platform





 ODR Cluster Operator -Manages and synchronizes cluster meta data and application data

Persistence Layer





- Asynchronous replication of Application volumes – or-
- Synchronous Mirroring of Application volumes


- Easy configuration DR across cluster and sites as part of application deployment
- Automated DR Failover and Failback operations reduces RTO
- Manage and Monitor DR across clusters and Apps
- Same consistent DR operations for both Metro-DR and Regional-DR
- Both Application Data and State is protected and used for Application granular protection
- Consistent Data replication or mirroring or both based on infrastructure and desired protection.



## OCP Cluster HA + DR for stateful Applications







#### **Cluster HA**


#### Regional-DR

#### Metro-DR

Topology	Single OCP+ODF clusters deployed over multiple AZs in a single region	Multi OCP + ODF clusters spread over multiple regions	Multi OCP clusters + single external ODF stretched cluster deployed over low latency networks
RTO (Downtime)	RTO=0 (Continuous)*	RTO = minutes DR Automation from ACM+ODF reduces RTO	RTO = minutes DR Automation from ACM+ODF reduces RTO
RPO (Data loss exposure)	RPO=0 No Data loss due due to Synchronous mirroring of ODF data	RPO > 0; Usually 5 min or higher Depends upon network bandwidth & change rate	RPO=0 No Data loss due due to Synchronous mirroring of ODF data
Infra Requirements	Multi-AZ supported public clouds (vSphere support in OCP 4.10)	All ODF supported platforms No network latency limits	On-prem only (vSphere, bare metal) <10ms network latency between sites  vooooooo

## OpenShift in vSphere is Zone Aware

- Create highly-available OpenShift clusters in vSphere with installer provisioned infrastructure (IPI)
- Applies zonal tags (regions and zones) to multiple vCenter datacenters and clusters in a single vCenter
- Excludes User Provisioned infrastructure (UPI) deployments





V0000000

## Thank you

Red Hat is the world's leading provider of enterprise open source software solutions. Award-winning support, training, and consulting services make Red Hat a trusted adviser to the Fortune 500.

- in linkedin.com/company/red-hat
- youtube.com/user/RedHatVideos
- facebook.com/redhatinc
- **y** twitter.com/RedHat

