

ROS2 for ATOSFleetManagement Cheat Sheet

```
# ROS2 for ATOSFleetManagement Cheat Sheet
```

```
## 1) Source environment
```

```
```bash
source /opt/ros/humble/setup.bash
source /home/sepast/atos_ws/install/setup.bash
```
```

```
## 2) Build only needed packages
```

```
```bash
cd /home/sepast/atos_ws
colcon build --packages-select atos atos_gui --symlink-install
```
```

```
## 3) Start ATOSFleetManagement
```

```
```bash
ros2 launch atos launch_atosfleetmanagement.py insecure:=True
```
```

```
## 4) List running nodes
```

```
```bash
ros2 node list
```
```

```
## 5) List topics
```

```
```bash
ros2 topic list
```
```

```
## 6) Inspect COT topic data
```

```
```bash
ros2 topic echo /atos/truck_objects/cot
```
```

```
## 7) Publish a test COT message
```

```
```bash
ros2 topic pub /atos/truck_objects/cot std_msgs/msg/String "data: 'id=truck_1;distance_m=1000;tcp_conne
```
```

```
## 8) Publish two trucks close enough to trigger speed limit
```

```
```bash
ros2 topic pub /atos/truck_objects/cot std_msgs/msg/String "data: 'id=truck_1;distance_m=1000;tcp_conne
ros2 topic pub /atos/truck_objects/cot std_msgs/msg/String "data: 'id=truck_2;distance_m=1300;tcp_conne
```
```

```
## 9) Watch speed commands from TruckObjectControl
```

```
```bash
ros2 topic echo /atos/truck_objects/speed_command
```
```

```
## 10) Quick behavior check
```

```
- Gap `< 400 m` => target speed `30 km/h`
- Gap `< 200 m` => target speed `0 km/h`
```

```
## 11) Open GUI
```

```
- URL: `http://localhost:3000`
```

```
## 12) Stop all launched nodes
```

```
- Press `Ctrl+C` in the launch terminal.
```