Experiment - 9

Topology:

PC - 1 Configuration:

Router - 1 Configuration:


```
Router - 1                                         —    □    ×

Physical    Config    CLI

               IOS Command Line Interface

Router>enable
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#hostname R1
R1(config)#enable secret P1
R1(config)#interface Fa0/0
R1(config-if)#ip address 10.0.0.1 255.0.0.0
R1(config-if)#noshut
                   ^
% Invalid input detected at '^' marker.

R1(config-if)#no shut

R1(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed
state to up

R1(config-if)#line vty 0 5
R1(config-line)#login
% Login disabled on line 132, until 'password' is set
% Login disabled on line 133, until 'password' is set
% Login disabled on line 134, until 'password' is set
% Login disabled on line 135, until 'password' is set
% Login disabled on line 136, until 'password' is set
% Login disabled on line 137, until 'password' is set
R1(config-line)#password P0
R1(config-line)#exit
R1(config)#exit
R1#
%SYS-5-CONFIG_I: Configured from console by console

R1#wr
Building configuration...
[OK]
R1#

                                        Copy           Paste
```

PC - 1 (Command Prompt):

Password for User Access Verification is: **P0**
Password for enable is: **P1**