

2. Data Discovery

Cob Staines

2025-04-07

Table of contents

Motivation	2
R	2
Load packages	2
Establish database connection	2
Load database metadata	2
Data structure: Schemas, tables, columns and rows	2
Metadata: Data about data	3
Table Metadata	3
Column metadata	3
Our first(?) data table	5
Disconnect	6
Python	6
Load packages	6
Establish database connection	7
Load database metadata	7
Data structure: Schemas, tables, columns and rows	7
Metadata: Data about data	7
Table Metadata	7
Column metadata	9
Our first(?) data table	11
Disconnect	13
DBeaver	13
Load database metadata	13
Data structure: Schemas, tables, columns and rows	13
Metadata: Data about data	14
Table Metadata	15
Column metadata	15
Schema sructure	17

Our first data table	17
--------------------------------	----

This tutorial is available as a [.qmd on Github](#).

Motivation

- Explore what data are currently available on the database
- Identify structure of data of interest to inform access

R

Let's set up our environment to get ready to explore the database.

Load packages

```
# minimal packages for RIBBiTR DB data discovery
librarian::shelf(tidyverse, dbplyr, RPostgres, DBI, RIBBiTR-BII/ribbitrrr)
```

Establish database connection

```
# establish database connection
dbcon <- hopToDB("ribbitr")
```

Connecting to 'ribbitr'... Success!

Load database metadata

Data structure: Schemas, tables, columns and rows

The RIBBiTR database is organized into “schemas” (think of these as folders), which can contain any number of tables. Each table consists of columns (“variables”) and rows (“entries”).

Metadata: Data about data

We keep track of information regarding what tables, and columns exist in the database, and what information they are designed to describe, using table and column metadata. To begin our process of data discovery, let's learn what tables are present in the data by loading the table metadata.

Table Metadata

```
# load table "all_tables" from schema "public"
mdt <- tbl(dbcon, Id("public", "all_tables")) %>%
  collect()
```

Some basic database commands

Before we take a look at the metadata you just pulled, let's understand the command we just ran.

- `dplyr::tbl()` - This function is used to create a “lazy” table from a data source. To specify the source, we provide the database connection `dbcon`, as well as a pointer or “address” for the table of interest using the `Id()` function. A “lazy” table means that the data only pulled when explicitly asked for. See `collect()` below.
- `dbplyr::Id()` - This function is a pointer to pass hierarchical table identifiers (you can think of this as an address for a given table). In this case we use it to generate an pointer for the table “all_tables” in schema “public”.
- `dplyr::collect()` - the `tbl()` function generates a “lazy” table, which is basically a shopping list for the data you want to pull. In order to actually pull the data from the server to your local machine (ie. “do the shopping”) we need to pipe in the `collect()` function.

Also try: Run the code above without `collect()`, to see what a lazy table looks like.

Now let's take a look at the table metadata to explore what schemas and tables exist.

```
view(mdt)
```

Column metadata

Suppose our interest is in the `survey_data` schema. Let's take a closer look at the tables here by collecting metadata on table columns in this schema.

```
# load table "all_columns" from schema "public"
mdc <- tbl(dbcon, Id("public", "all_columns")) %>%
  filter(table_schema == "survey_data") %>%
  collect()
```

Notice we used the `dplyr::filter()` command on the lazy table *before* running `collect()`. This effectively revised the shopping list before going to the store, rather than bringing home the entire store and then filtering for what you want in your kitchen. Much less (computationally) expensive!

Let's check out the column metadata, and see what you can learn.

```
view(mdc)

# list the columns in our column-metadata table
colnames(mdc)
```

```
[1] "table_schema"      "table_name"
[3] "column_name"       "definition"
[5] "units"             "accuracy"
[7] "scale"             "format"
[9] "reviewed"          "natural_key"
[11] "primary_key"       "foreign_key"
[13] "unique"            "is_nullable"
[15] "data_type"         "character_maximum_length"
[17] "numeric_precision" "datetime_precision"
[19] "column_default"    "ordinal_position"
[21] "pg_description"    "key_type"
[23] "fkey_ref_schema"   "fkey_ref_table"
[25] "fkey_ref_column"
```

Curious about what a certain metadata column means? There's metadata for that (metametadata?)!

```
# view metadata on metadata columns
view(mdc %>% filter(table_name == "metadata_columns"))
```

A few columns to point out:

- definition
- units
- data_type
- natural key

(more on keys later)

Our first(?) data table

Ok, let's try to apply some of what we have learned by pulling directly from a data table. We can begin by taking a look at the visual encounter surveys (VES).

```
# create lazy table for ves (visual encounter survey) table
db_ves <- tbl(dbcon, Id("survey_data", "ves"))
```

Do these functions look familiar? Turns out, we were pulling data all along! Of course, this is a lazy table (ie. shopping list) so it doesn't look like data yet. Let's see what we can learn from it before going to the store to collect the data.

What columns the table contains:

```
# return columns of lazy table
colnames(db_ves)
```

```
[1] "taxon_ves"           "count_ves"           "ves_transect_m"
[4] "microhabitat_type"   "life_stage"          "sex"
[7] "comments_ves"        "microhabitat_detailed" "observer_ves"
[10] "visual_animal_state" "ves_id"               "survey_id"
```

How many total rows a table contains:

```
# count rows
db_ves %>%
  count() %>%
  pull()
```

```
integer64
[1] 30124
```

The pull() function executes a query to return a single column or variable, synonymous with the collect() function which returns a collection of variables as a table.

We can also count rows using the summarise() and n() functions. While slightly more complicated, this will carry over into more colicated queries later.

So, how many rows after filtering for unknown species:

```
# count rows with known taxa
db_ves %>%
  filter(!is.na(taxon_ves)) %>%
  summarise(row_count = n()) %>%
  pull(row_count)
```

```
integer64
[1] 29949
```

How many rows corresponding to a each life stage:

```
# count rows by life stage
db_ves %>%
  select(life_stage) %>%
  group_by(life_stage) %>%
  summarise(row_count = n()) %>%
  arrange(desc(row_count)) %>%
  collect()
```

```
# A tibble: 8 x 2
  life_stage    row_count
  <chr>         <int64>
1 tadpole         10568
2 adult           9831
3 subadult        7380
4 <NA>            1591
5 eggmass          655
6 juvenile         76
7 egg              16
8 metamorphosed     7
```

Disconnect

Reinforcing best practice by disconnecting from the server.

```
dbDisconnect(dbcon)
```

Python

Let's set up our environment to get ready to explore the database.

Load packages

```
# minimal packages for Python DB data discovery
import ibis
from ibis import _
import pandas as pd
import dbconfig
```

Establish database connection

```
# Establish database connection
dbcon = ibis.postgres.connect(**dbconfig.ribbitr)
```

Load database metadata

Data structure: Schemas, tables, columns and rows

The RIBBiTR database is organized into “schemas” (think of these as folders), which can contain any number of tables. Each table consists of columns (“variables”) and rows (“entries”).

Metadata: Data about data

We keep track of information regarding what tables, and columns exist in the database, and what information they are designed to describe, using table and column metadata. To begin our process of data discovery, let’s learn what tables are present in the data by loading the table metadata.

Table Metadata

```
# load table "all_tables" from schema "public"
mdt = dbcon.table(database = "public", name = "all_tables").to_pandas()
```

Some basic database commands

Before we take a look at the metadata you just pulled, let’s understand the command we just ran.

- `ibis.table()` - This function is used to create a “lazy” table from a data source. To specify the source, we modify the database connection `dbcon`. We specify the schema for the table as `public` (note `ibis` calls this “database”), as well as the table name `all_tables`. A “lazy” table means that the data only pulled when explicitly asked for. See `execute()` below.
- `ibis.to_pandas()` - the `table()` function generates a “lazy” table, which is basically a shopping list for the data you want to pull. In order to actually pull the data from the server to your local machine (ie. “do the shopping”) we need to collect the lazy table by chaining the `to_pandas()` function.

Also try: Run the code above without `to_pandas()`, to see what an uncollected lazy table looks like.

Now let’s take a look at the table metadata to explore what schemas and tables exist.

```
print(mdt)
```

```

      table_schema ...      table_description
0  microclimate_data ... data logger lookup table (one logger contains ...
1  microclimate_data ... Column-specific definitions and metadata ("dat...
2  microclimate_data ... Table-specific definitions and metadata ("data...
3  microclimate_data ...      microclimate sensor lookup table
4  microclimate_data ...      Dew point time series data table
5  microclimate_data ...      Illuminance time series data table
6  microclimate_data ...      Relative humidity time series data table
7  microclimate_data ...      Temperature time series data table
8      survey_data ...      None
9      survey_data ...      None
10     survey_data ... Table-specific definitions and metadata ("data...
11     survey_data ...      Results from mucosome-Bd-inhibition assays
12     survey_data ...      Region lookup table
13     survey_data ...      None
14     survey_data ... sample lookup table for tracking sample result...
15     survey_data ...      Field site lookup table
16     survey_data ... Tracking of human interventions, manipulations...
17     survey_data ...      Field survey lookup table
18     survey_data ...      Taxonomy lookup table
19     survey_data ...      Field survey visual observations
20     survey_data ...      None
21     survey_data ...      None
22     survey_data ...      Field visit lookup table
23     survey_data ...      None
24     survey_data ...      None
25     survey_data ...      None
26     survey_data ...      Field survey aural observations

```



```

27      survey_data ...      Isolate Bd strains for use wihtin RIBBiTR
28      survey_data ...      Results from Bd qPCR assays
29      survey_data ...      Field survey capture observations
30      survey_data ...      Capture-mark-recapture codes for tracking of m...
31      survey_data ...      Country lookup table
32      survey_data ...      eDNA sample collection and filtering
33      survey_data ...      Field survey environmental observations
34      survey_data ...      laboratory lookup table -- use to identify who...
35      survey_data ...      Column-specific definitions and metadata ("dat...

```

[36 rows x 4 columns]

Column metadata

Suppose our interest is in the `survey_data` schema. Let's take a closer look at the tables here by collecting metadata on table columns in this schema.

```

# load table "all_columns" from schema "public"
mdc = (
    dbcon.table(database="public", name="all_columns")
    .filter(_.table_schema == 'survey_data')
    .to_pandas()
)

```

Notice we used the `ibis.filter()` command on the lazy table *before* calling `to_pandas()`. This effectively revised the shopping list before going to the store, rather than bringing home the entire store and then filtering for what you want in your kitchen. Much less (computationally) expensive!

Let's check out the column metadata, and see what you can learn.

```

# view dataframe
print(mdc)

```

	table_schema	table_name	...	fkey_ref_table	fkey_ref_column
0	survey_data	bd_qpcr_results	...	None	None
1	survey_data	capture	...	None	None
2	survey_data	metadata_columns	...	None	None
3	survey_data	metadata_columns	...	None	None
4	survey_data	bd_qpcr_results	...	None	None
..
441	survey_data	bd_isolate	...	None	None
442	survey_data	bd_isolate	...	None	None
443	survey_data	bd_isolate	...	lab	lab_id

```

444 survey_data mucosome_results ...          lab          lab_id
445 survey_data mucosome_results ...      bd_isolate  bd_isolate_id

```

```
[446 rows x 25 columns]
```

```

# list the columns in our column-metadata table
mdc.columns

```

```

Index(['table_schema', 'table_name', 'column_name', 'definition', 'units',
      'accuracy', 'scale', 'format', 'reviewed', 'natural_key', 'primary_key',
      'foreign_key', 'unique', 'is_nullable', 'data_type',
      'character_maximum_length', 'numeric_precision', 'datetime_precision',
      'column_default', 'ordinal_position', 'pg_description', 'key_type',
      'fkey_ref_schema', 'fkey_ref_table', 'fkey_ref_column'],
      dtype='object')

```

Curious about what a certain metadata column means? There's metadata for that (metametadata?)!

```

# view metadata on metadata columns
metameta = mdc[mdc['table_name'] == 'metadata_columns']
print(metameta)

```

	table_schema	table_name	...	fkey_ref_table	fkey_ref_column
2	survey_data	metadata_columns	...	None	None
3	survey_data	metadata_columns	...	None	None
9	survey_data	metadata_columns	...	None	None
34	survey_data	metadata_columns	...	None	None
57	survey_data	metadata_columns	...	None	None
91	survey_data	metadata_columns	...	None	None
246	survey_data	metadata_columns	...	None	None
247	survey_data	metadata_columns	...	None	None
248	survey_data	metadata_columns	...	None	None
304	survey_data	metadata_columns	...	None	None
305	survey_data	metadata_columns	...	None	None
306	survey_data	metadata_columns	...	None	None
307	survey_data	metadata_columns	...	None	None
308	survey_data	metadata_columns	...	None	None
309	survey_data	metadata_columns	...	None	None
310	survey_data	metadata_columns	...	None	None
311	survey_data	metadata_columns	...	None	None
312	survey_data	metadata_columns	...	None	None
313	survey_data	metadata_columns	...	None	None

314	survey_data	metadata_columns	...	None	None
342	survey_data	metadata_columns	...	None	None
348	survey_data	metadata_columns	...	None	None
373	survey_data	metadata_columns	...	None	None
388	survey_data	metadata_columns	...	None	None
389	survey_data	metadata_columns	...	None	None

[25 rows x 25 columns]

A few columns to point out:

- definition
- units
- data_type
- natural key

(more on keys later)

Our first(?) data table

Ok, let's try to apply some of what we have learned by pulling directly from a data table. We can begin by taking a look at the visual encounter surveys (VES).

```
# create lazy table for ves (visual encounter survey) table
db_ves = dbcon.table(database="survey_data", name="ves")
```

Do these functions look familiar? Turns out, we were pulling data all along! Of course, this is a lazy table (ie. shopping list) so it doesn't look like data yet. Let's see what we can learn from it before going to the store to collect the data.

What columns the table contains:

```
# return columns of lazy table
db_ves.columns
```

```
['taxon_ves', 'count_ves', 'ves_transect_m', 'microhabitat_type', 'life_stage', 'sex', 'comm
```

How many total rows a table contains:

```
# count rows
(db_ves
 .count()
 .execute())
```

30124

The `ibis.execute()` function executes a query and returns the result, regardless of the format. This is synonymous with the `to_pandas()` function which returns query results as a pandas dataframe where possible.

How many rows after filtering for unknown species:

```
# count rows with known taxa
filtered_row_count = (
    db_ves
    .filter(_.taxon_ves.notnull())
    .count()
    .execute()

print(filtered_row_count)
```

29949

How many rows corresponding to a each life stage:

```
# count rows by life stage
life_stage_counts = (
    db_ves.group_by('life_stage')
    .aggregate(row_count=_.count())
    .order_by(_.row_count.desc())
    .to_pandas()
)

print(life_stage_counts)
```

	life_stage	row_count
0	tadpole	10568
1	adult	9831
2	subadult	7380
3	None	1591
4	eggmass	655
5	juvenile	76
6	egg	16
7	metamorphosed	7

Disconnect

Reinforcing best practice by disconnecting from the server.

```
# close connection  
dbcon.disconnect()
```

DBeaver

Double-click on the `ribbitr` connection in the “Database Navigator” panel to begin your connection. Once connected you should be able to navigate a dropdown menu to explore the connection.

Load database metadata

Data structure: Schemas, tables, columns and rows

The RIBBiTR database is organized into “schemas” (think of these as folders), which can contain any number of tables. Each table consists of columns (“variables”) and rows (“entries”). You can explore this structure through the dropdown menu in the “Database Navigator” panel on the left.





Figure 1: Navigate to Databases -> ribbitr -> Schemas

Metadata: Data about data

We keep track of information regarding what tables, and columns exist in the database, and what information they are designed to describe, using table and column metadata. To begin our process of data discovery, let's learn what tables are present in the data by loading the table metadata.

Table Metadata




The screenshot shows the DBeaver 24.2.4 interface. The left sidebar displays a tree view of the database structure, with the 'public' schema and 'all_tables' view selected. The main panel shows a table with columns: 'table schema', 'table name', 'column count', and 'table description'. The table contains 28 rows of data, including tables from the 'bay_area' and 'survey_data' schemas. The status bar at the bottom indicates '63 row(s) fetched - 0.152s (0.002s fetch), on 2024-11-07 at 12:57:48'.

	table schema	table name	column count	table description
1	bay_area	amphib_dissect	41	[NULL]
2	bay_area	amphib_parasite	11	[NULL]
3	bay_area	water_quality_info	27	[NULL]
4	bay_area	site	25	[NULL]
5	bay_area	wetland_info	25	[NULL]
6	bay_area	bd_results	25	[NULL]
7	bay_area	net_info	11	[NULL]
8	bay_area	net_species	14	[NULL]
9	bay_area	metadata_tables	4	[NULL]
10	bay_area	metadata_columns	19	[NULL]
11	survey_data	brazil_landscape_microbiome	14	[NULL]
12	survey_data	brazil_landscape_habitat	38	[NULL]
13	survey_data	amp_totals_gia	16	[NULL]
14	survey_data	ves	12	[NULL]
15	survey_data	site	13	[NULL]
16	survey_data	visit	7	[NULL]
17	survey_data	aural	12	[NULL]
18	survey_data	location	2	[NULL]
19	survey_data	region	3	[NULL]
20	survey_data	survey	58	[NULL]
21	survey_data	serdp_bd_genomic	6	[NULL]
22	survey_data	serdp_newt_microbiome_mucosome_antifungal	28	[NULL]
23	survey_data	cmr	2	[NULL]
24	survey_data	temp_shiny_bd	2	[NULL]
25	survey_data	metadata_tables	4	[NULL]
26	survey_data	metadata_columns	19	[NULL]
27	survey_data	capture	53	[NULL]
28	survey_data	amp_lookup	1	[NULL]

See what you can learn about the tables in the database from the table metadata.

Column metadata

Suppose our interest is in the `survey_data` schema. Let's take a closer look at the tables here by collecting metadata on table columns in this schema.



Click on the dropdown arrow next to `table_schema`, click on `Order by table_schema ASC`. Repeat for the `table_name` and `column_name` columns.

Scroll down until you see rows with `table_schema = survey_data`. Explore a table of interest to see what you can learn.

Curious about what a certain metadata column means? There's metadata for that (metametadata?)! Scroll down to `table_name = metadata_columns` to learn what the different columns in the current table mean.

A few columns to point out:

- definition
- units
- data_type
- natural key

(more on keys later)

Schema structure





Figure 2: Navigate to Databases -> ribbitr -> Schemas -> survey_data. Right-click and select View Schema. Select the ER Diagram tab.

This shows a diagram of the different tables within the `survey_data` schema, as well as their columns and any relationships between tables. This is a useful visual reference for later, when we begin joining tables.

Our first data table

To begin looking at data, let's navigate to the visual encounter surveys (VES).



This is your first look at field data within the database! From here you can explore organizing the data by columns, as well as exporting the table to a .csv.

<- 1. Connection Setup | 3. Data Pulling ->