

 Authentication	none
 Source Code	shell

APIREST NOISYSTEM

```
# Install the command line client
$ pip install coreapi-cli
```

api

client > list

GET /api/client/

⇌ Interact

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api client list
```

client > create

POST /api/client/

⇌ Interact

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
ruc <div>required</div>	
usuario <div>required</div>	
password <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api client create -p ruc=... -p usuario=... -p password=...
```

client > read

GET

 /api/client/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this Cliente.

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api client read -p id=...
```

client > update

PUT

 /api/client/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this Cliente.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
ruc <div>required</div>	
usuario <div>required</div>	
password <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api client update -p id=... -p ruc=... -p usuario=... -p password=...
```

client > partial_update

PATCH

 /api/client/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this Cliente.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
ruc	
usuario	
password	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api client partial_update -p id=... -p ruc=... -p usuario=... -p password=...
```

client > delete

DELETE

 /api/client/{id}/

↔ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this Cliente.

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api client delete -p id=...
```

client > read_0

GET

 /api/client/{ruc}/{usuario}/{password}/

↔ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
ruc <div>required</div>	
usuario <div>required</div>	
password <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api client read_0 -p ruc=... -p usuario=... -p password=...
```

product > list

GET

/api/product/

⇌

Interact

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api product list
```

product > create

POST

/api/product/

⇌

Interact

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
producto <div>required</div>	
descripcion <div>required</div>	
stok <div>required</div>	
precio <div>required</div>	
descuento <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api product create -p producto=... -p descripcion=... -p stok=... -p precio=...
```

product > read

GET

 /api/product/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this Producto.

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api product read -p id=...
```

product > update

PUT

 /api/product/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this Producto.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
producto <div>required</div>	
descripcion <div>required</div>	
stok <div>required</div>	
precio <div>required</div>	
descuento <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api product update -p id=... -p producto=... -p descripcion=... -p stok=... -p
```

product > partial_update

PATCH

/api/product/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this Producto.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
producto	
descripcion	
stok	
precio	
descuento	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api product partial_update -p id=... -p producto=... -p descripcion=... -p sto
```

product > delete

DELETE

/api/product/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this Producto.

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action api product delete -p id=...
```

setting

config > list

GET /setting/config/

⇌ Interact

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action setting config list
```

config > create

POST /setting/config/

⇌ Interact

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
backgroundColor <div>required</div>	
forengroudColor <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action setting config create -p backgroundColor=... -p forengroudColor=...
```

config > read

GET /setting/config/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this config.

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action setting config read -p id=...
```

config > update

PUT

 /setting/config/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this config.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
backgroundColor <div>required</div>	
forengroudColor <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action setting config update -p id=... -p backgroundColor=... -p forengroudColor=...
```

config > partial_update

PATCH

 /setting/config/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this config.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
backgroundColor	
forengroudColor	


```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action setting config partial_update -p id=... -p backgroundColor=... -p forengroudCc
```

config > delete

DELETE

/setting/config/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this config.

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action setting config delete -p id=...
```