

# RIG Intelligence API

A read API over your provisioned intelligence scope — news articles, newspaper cuttings, and YouTube — with directed sentiment, grouped stories, geography, briefings, and programmatic control of your own coverage scope.

| VERSION                   | BASE URL                       |
|---------------------------|--------------------------------|
| v1                        | https://api.rig360media.com/v1 |
| PREPARED FOR              | PROTOCOL                       |
| Telangana CM & Government | HTTPS · JSON · Bearer key      |
| ISSUED                    | ENDPOINTS                      |
| 9 July 2026               | 28 · self-service scope        |

## – Contents

---

[1 Overview & how it works](#)

---

[2 Authentication & your key](#)

---

[3 Conventions — envelope, errors, paging, limits](#)

---

[4 The three content pillars & field dictionary](#)

---

[5 Managing your scope \(self-service\)](#)

---

[6 Entities](#)

---

[7 Articles \(news\)](#)

---

[8 Newspapers \(cuttings\)](#)

---

[9 YouTube transcripts \(on-demand\)](#)

---

[10 Stories \(grouped coverage\)](#)

---

[11 Briefings](#)

---

[12 Geography](#)

---

[13 Analytics & sentiment](#)

---

[14 Webhooks](#)

---

[15 Usage & quota](#)

---

[16 Common workflows](#)

---

# 1 Overview & how it works

---

What the API gives you and the one idea that governs all of it.

The RIG Intelligence API is a **read API over your provisioned intelligence scope**. Every request returns coverage and analytics drawn from three underlying content pillars — **news articles**, **newspaper cuttings**, and **YouTube** — enriched with directed sentiment, entity resolution, grouped stories, district geography, and daily briefings. You can also **manage your own scope** (the entities, keywords, regions and mutes you track) programmatically.

**One idea to remember: your key is your scope.** Every endpoint is automatically filtered to what your organisation is provisioned for. Nothing you pass in a request can widen that — an out-of-scope entity, article, or district returns the same `404` as one that doesn't exist. This is what lets you share the API across your team without any request accidentally reaching another tenant's data.

## Content vs. analytics

Everything the API exposes is either **content** (a specific article / cutting / clip) or an **aggregate** computed over that content (sentiment, topic counts, coverage volume, stories, geo). Every aggregate is **drillable** — it returns the IDs of the items behind the number, which you can fetch individually.

## Base URL

```
https://api.rig360media.com/v1
```

A same-origin alias is also available at `https://desk.rig360media.com/osint/v1` for browser-based tools that need to avoid CORS. Both route to the identical API.

## 2 Authentication & your key

Bearer-token auth. Your key encodes your organisation and your limits.

Every request must carry your API key in the `Authorization` header:

```
curl https://api.rig360media.com/v1/entities \
-H "Authorization: Bearer rig_live_YOUR_KEY_HERE"
```

An `X-API-Key: rig_live_...` header is also accepted if a Bearer header is inconvenient in your stack.

| KEY PREFIX                | ENVIRONMENT | NOTES                                         |
|---------------------------|-------------|-----------------------------------------------|
| <code>rig_live_...</code> | Production  | Live data, counts against your monthly quota. |
| <code>rig_test_...</code> | Sandbox     | Same API surface for integration testing.     |

**Your key is delivered separately.** For security, the secret is never included in this document — it is sent to you once, over a secure channel. We store only a one-way hash of it, so it cannot be re-displayed; if it is ever lost or exposed, we revoke and reissue. Treat it like a password: never commit it to source control or paste it into shared tools.

**Your key is a management key.** Your organisation's key carries the `can_manage` capability, which means you can configure your own scope through the API (see §5) — add or remove any entity or keyword yourself, on demand, without waiting on us.

### Failed authentication

A missing, malformed, revoked, or expired key returns an identical terse `401` — the API never reveals which of those it was, so a leaked key can't be probed for its state.

```
{ "error": { "code": "unauthorized", "message": "Invalid or missing API key", "status": 401 } }
```

## 3 Conventions

Read once; these hold across every endpoint.

### Response envelope

Every successful response is wrapped in a `data` field; list endpoints add a `meta` block with counts and paging.

```
{
  "data": { ... },           // the payload – object or array
  "meta": { "count": 20, "next_cursor": "eyJ0Ijo..." } // on list endpoints
}
```

Every error uses the same shape:

```
{ "error": { "code": "bad_request", "message": "human-readable reason", "status": 400 } }
```

### Status codes

| CODE | MEANING                                                                 |
|------|-------------------------------------------------------------------------|
| 200  | Success.                                                                |
| 400  | Malformed request (bad date, bad body). Message explains what.          |
| 401  | Missing / invalid key.                                                  |
| 404  | Not found <i>or</i> out of your scope — deliberately indistinguishable. |
| 422  | A query parameter failed validation (wrong enum / type).                |
| 429  | Rate limit exceeded — see the <code>X-RateLimit-*</code> headers.       |

### Pagination

List endpoints are cursor-paged. When more results exist, `meta.next_cursor` is non-null; pass it back as `?cursor=` for the next page. The newspapers feed uses a timestamp cursor `?before=` returned as `meta.next_before`. A null cursor means the last page.

### Time windows & limits

| PARAMETER                       | DEFAULT | BOUNDS                                        |
|---------------------------------|---------|-----------------------------------------------|
| <code>window</code> (days back) | 7       | 1–90                                          |
| <code>limit</code> (page size)  | 20      | 1–100 (larger asks are clamped, not rejected) |

### Rate limits & quota

Each response carries `X-RateLimit-Limit`, `X-RateLimit-Remaining`, and `X-RateLimit-Reset` (per-minute window). Monthly consumption is tracked against your quota and is readable any time at `GET /v1/usage`.

## 4 The three content pillars

All content — and every aggregate — comes from these three. Full field dictionary below.

| PILLAR            | WHAT IT IS                                    | HOW YOU ACCESS IT                                                                     |
|-------------------|-----------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Articles</b>   | News / web coverage, stored & translated      | Filterable feed + single item; richest shape                                          |
| <b>Newspapers</b> | Print newspaper cuttings, stored & translated | Feed + single item, full text                                                         |
| <b>YouTube</b>    | Broadcast/video coverage                      | <b>Keyword-driven:</b> discover via a query, then fetch the full transcript on demand |

### Article fields

The article object (also used for story timelines, entity coverage, and district drill-downs):

| FIELD                                                           | MEANING                                                                                       |
|-----------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| <code>id</code>                                                 | Article identifier (UUID).                                                                    |
| <code>headline</code>                                           | Title, in the source language.                                                                |
| <code>summary</code> / <code>full_text</code>                   | English (translation-preferred) summary and body.                                             |
| <code>summary_original</code> / <code>full_text_original</code> | Native-language summary and body (Telugu / Urdu / Hindi ...).                                 |
| <code>source</code>                                             | Outlet name.                                                                                  |
| <code>language</code>                                           | Source-language tag (e.g. <code>te</code> , <code>en</code> ).                                |
| <code>url</code>                                                | Link to the original.                                                                         |
| <code>geo</code>                                                | Primary place (district / region), where detected.                                            |
| <code>story_id</code>                                           | The grouped story this belongs to (if any) — see §10.                                         |
| <code>sentiment</code>                                          | <code>{ label: supportive neutral critical, intensity: 0-1 }</code> . Null when unclassified. |
| <code>source_flags</code>                                       | <code>{ low_credibility, political_lean }</code> — provenance signals (see below).            |
| <code>api_ready</code>                                          | True once the item has cleared full enrichment.                                               |
| <code>published_at</code> / <code>last_updated</code>           | Timestamps (ISO-8601 UTC).                                                                    |
| <code>entities</code>                                           | On single-item lookups: entities mentioned, within your scope — <code>{id,name,type}</code> . |

**Source flags are provenance, not a verdict.** `political_lean` is only present when an outlet is classified (left ... right); `low_credibility` marks outlets on a curated low-credibility/state-propaganda list. Absence is not an endorsement, and neither flag is a claim about a specific article's truth.

### Newspaper (cutting) fields

`id`, `headline` / `headline_original`, `subheadline`, `full_text` / `full_text_original`, `source`, `section`, `language`, `geo`, `page_number`, `edition_date`.

### YouTube (clip) fields

`id`, `video_id`, `title`, `channel`, `url`, `published_at`, `language`, `transcript_source`, `segment_count`, and the assembled `transcript`. See §9 for the on-demand access rule.

## 5 Managing your scope

---

Your key can configure its own coverage — add any entity or keyword, any time.

Your **scope** is the set of things the API filters everything to: provisioned **entities**, free-text **keywords**, **topics**, **regions**, **mute\_terms**, and per-keyword **priorities**. Because your key carries `can_manage`, you control all of it programmatically — you never need to wait on us to add an entity or keyword.

### GET /v1/scope

Read your current provisioned scope.

#### EXAMPLE RESPONSE

```
{
  "data": {
    "all_entities": false,
    "entity_ids": ["d2da8f86-...-b1ecf5a8d62d", "9a70e644-...-1a9e68aae1ed"],
    "topics": [], "keywords": ["irrigation project", "kaleshwaram"],
    "regions": ["Telangana"], "languages": [], "mute_terms": ["horoscope"],
    "keyword_priorities": { "kaleshwaram": 5 },
    "can_manage": true
  }
}
```



## PATCH /v1/scope MANAGEMENT KEY

Add or remove items from your scope. All fields optional; send only what you're changing.

### BODY FIELDS

| FIELD                                                        | EFFECT                                                                                                                                              |
|--------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>add_entities</code>                                    | Add entities — <b>by name or by id</b> . A name is resolved to a known entity; if it matches none, it's added as a keyword instead (never dropped). |
| <code>remove_entities</code>                                 | Remove entity ids from scope.                                                                                                                       |
| <code>add_keywords</code> / <code>remove_keywords</code>     | Arbitrary free-text terms — no dictionary needed.                                                                                                   |
| <code>add_topics</code> / <code>remove_topics</code>         | Topic filters.                                                                                                                                      |
| <code>add_regions</code> / <code>remove_regions</code>       | Region names (e.g. <code>Telangana</code> ).                                                                                                        |
| <code>add_mute_terms</code> / <code>remove_mute_terms</code> | Terms to suppress from your feeds.                                                                                                                  |
| <code>keyword_priorities</code>                              | Map of <code>keyword → integer weight</code> (merged in).                                                                                           |
| <code>languages</code>                                       | Replaces the language allow-list.                                                                                                                   |

### EXAMPLE REQUEST

```
curl -X PATCH https://api.rig360media.com/v1/scope \
-H "Authorization: Bearer rig_live_..." -H "Content-Type: application/json" \
-d '{ "add_entities": ["K. T. Rama Rao", "Some New Local Leader"],
      "add_keywords": ["kaleshwaram"], "add_regions": ["Telangana"]} '
```

### EXAMPLE RESPONSE — NAMES RESOLVED, UNKNOWN KEPT AS KEYWORDS

```
{
  "data": {
    "all_entities": false,
    "entity_ids": ["...", "d2da8f86-...-b1ecf5a8d62d"],
    "keywords": ["kaleshwaram", "some new local leader"],
    "regions": ["Telangana"],
    "resolved_entities": [ { "name": "K. T. Rama Rao", "entity_id": "d2da8f86-...-b1ecf5a8d62d" } ],
    "added_as_keywords": ["Some New Local Leader"]
  }
}
```

**Nothing you ask to track is ever silently dropped.** Give `add_entities` a name we recognise and it becomes a resolved entity (best, indexed matching); give it something we don't recognise and it's added as a free-text keyword. The response tells you exactly which happened via `resolved_entities` and `added_as_keywords` .

## POST /v1/scope/purge MANAGEMENT KEY

Clear your scope and webhook subscriptions. Requires an explicit confirmation flag in the body.

## 6 Entities

Your provisioned people, organisations and places — and everything said about them.

### GET /v1/entities

List the entities in your scope.

```
{ "data": [ { "id": "d2da8f86-...", "name": "K. T. Rama Rao", "type": "person" },
            { "id": "9a70e644-...", "name": "Revanth Reddy", "type": "person" } ],
  "meta": { "count": 2 } }
```

### GET /v1/entities/{entity\_id}

Profile of one entity, with a 7-day coverage + sentiment snapshot.

```
{
  "data": {
    "id": "d2da8f86-...", "name": "K. T. Rama Rao", "type": "person",
    "snapshot": { "coverage_7d": 198,
                  "sentiment_7d": { "supportive": 28, "neutral": 73, "critical": 50 } }
  }
}
```

### GET /v1/entities/{entity\_id}/coverage

Unified recent coverage about one entity across all three pillars.

QUERY

**pillar** = all | articles | clips | cuttings · **window**, **limit**, **language**, **source**

EXAMPLE RESPONSE (ARTICLE ITEM SHOWN IN FULL)

```
{
  "data": [
    {
      "type": "article",
      "id": "384ab9ab-...",
      "headline": "సంపన్న రాష్ట్రం.. కేటీఆర్ కామెంట్స్",
      "summary": "**KCR's visionary leadership receives international recognition** ...",
      "full_text": "Wealthy State.. KTR's comments on World Bank recognition ...",
      "summary_original": "కేటీఆర్ దార్శనిక నాయకత్వానికి అంతర్జాతీయ గుర్తింపు ...",
      "source": "V6 Velugu", "language": "te",
      "url": "https://www.v6velugu.com/ktr-says-world-bank-recognition-...",
      "geo": "Telangana", "story_id": null,
      "sentiment": { "label": "supportive", "intensity": 0.9 },
      "source_flags": { "low_credibility": false },
      "published_at": "2026-07-09T02:03:00+00:00"
    }
  ],
  "meta": { "count": 3, "pillars": ["article", "clip", "cutting"] }
}
```

# 7 Articles (news)

The filterable coverage feed and single-item lookup.

## GET /v1/articles

Filterable feed of news coverage in your scope, newest first.

### QUERY PARAMETERS

| PARAM                           | MEANING                                                                 |
|---------------------------------|-------------------------------------------------------------------------|
| entity                          | One or more of your entity ids (repeatable). Narrows to those entities. |
| topic                           | Topic filter(s), repeatable.                                            |
| sentiment                       | supportive   neutral   critical.                                        |
| source                          | Outlet name(s) — drill down from /analytics/outlets.                    |
| match                           | any (OR, default) or all (AND) across filters.                          |
| language, window, limit, cursor | Standard (see §3).                                                      |

### EXAMPLE — SUPPORTIVE KTR COVERAGE

```
curl "https://api.rig360media.com/v1/articles?entity=d2da8f86-...&sentiment=supportive&limit=20" \
-H "Authorization: Bearer rig_live_..."
```

Returns an array of article objects (see §4) plus meta.next\_cursor.

## GET /v1/articles/{article\_id}

A single article with the full 16-field shape and its in-scope entities[].

## 8 Newspapers (cuttings)

Print newspaper coverage with full text — native and English.

**GET** `/v1/cuttings`

Scoped feed of newspaper cuttings, newest first. Timestamp-paged via `?before=`.

EXAMPLE RESPONSE

```
{
  "data": [
    {
      "type": "cutting", "id": "f3be735c-...",
      "headline": "హాకర్ల తొలగింపులో ఉద్రిక్తత",
      "headline_original": "హాకర్ల తొలగింపులో ఉద్రిక్తత", "subheadline": null,
      "full_text": "కర్త తొలగింపులో ఉద్రిక్తత ... బీసెంట్ రోడ్డులో హాకర్ల తోపుడు బళ్లు ...",
      "full_text_original": "కర్త తొలగింపులో ఉద్రిక్తత ...",
      "source": "Sakshi", "section": "Local", "language": "te",
      "geo": null, "page_number": 9, "edition_date": "2026-07-09"
    }
  ],
  "meta": { "count": 2, "next_before": "2026-07-09T03:23:44+00:00" }
}
```

**GET** `/v1/cuttings/{cutting_id}`

One cutting with full native + English text — same shape as a feed item.

## 9 YouTube transcripts

Keyword-driven and on-demand: discover a clip via a query, then read its full transcript.

**YouTube is on-demand, not a browsable feed.** There is deliberately no "list all clips" endpoint. You first **surface** clips with a keyword or entity query ( `/analytics/keyword-sentiment?pillars=clips` , `/analytics/sentiment?include_youtube=true` , or an entity's `coverage?pillar=clips` ). Those return `clip_ids` . You may then fetch the full transcript of any clip you surfaced, within a rolling 24-hour window. A clip you never surfaced — or one surfaced by another organisation — returns `404` .

### Step 1 — surface clips with a query

```
curl "https://api.rig360media.com/v1/analytics/keyword-sentiment?
keyword=Revanth+Reddy&pillars=clips&window=45" \
-H "Authorization: Bearer rig_live_..."

→ { "data": { "keyword": "revanth reddy", "n_matched": 80, "n_scored": 62,
  "stance": { "positive": 11, "negative": 30, "neutral": 21 },
  "stance_score": -0.306,
  "clip_ids": ["9693", "9673", ...], "pillars": "clips", "partial": true } }
```

### Step 2 — fetch the full transcript

**GET** `/v1/clips/{clip_id}` **ON-DEMAND · 24H WINDOW**

The full transcript of a clip you surfaced, assembled from its timed segments.

```
{
  "data": {
    "type": "clip", "id": "9693", "video_id": "oLpqNGFPMZA",
    "title": "Ghantaravam 9 AM | Full Bulletin | 9th July 2026 @etvtelangana",
    "channel": "ETV Telangana",
    "url": "https://www.youtube.com/watch?v=oLpqNGFPMZA",
    "published_at": "2026-07-09T04:18:32+00:00",
    "language": "en", "transcript_source": "auto_captions",
    "segment_count": 14,
    "transcript": "Greetings, welcome to Ghantaravam. First, the main points. West Asia turned
into a battlefield ... government measures to alleviate the hardships ..."
  }
}
```

## 10 Stories (grouped coverage)

The same event across many outlets, collapsed into one surfaceable story — scoped to you.

### GET /v1/stories

Surfaceable grouped stories ( $\geq 3$  independent outlets), scoped to your entities and/or regions. Optional `?entity=`, `?country=` (ISO-2), `?cursor=`, `?limit=`.

EXAMPLE RESPONSE (SHAPE)

```
{
  "data": [
    {
      "id": "2bc19b56-...", "title": "...", "topic": "INTERNATIONAL",
      "subject_country": "IN", "subject_region": "...",
      "article_count": 306, "outlets": 291,
      "top_outlets": ["TASS - Defence", "gCaptain", ...],
      "languages": { "en": 1080, "te": 13, "hi": 20, ... },
      "importance": 182.0,
      "representative_article_id": "1dd6a23b-...",
      "first_seen": "2026-04-16T17:03:15+00:00",
      "last_updated": "2026-06-16T10:27:44+00:00"
    }
  ],
  "meta": { "count": 2, "next_cursor": "eyJ0IjoiMTc5Ii..." }
}
```

`outlets` is the de-duplicated independent-outlet count; `importance` ranks the story within your scope.

### GET /v1/stories/{story\_id}

One story: the card above, plus a full `outlets_breakdown` and a chronological `timeline[]` of member articles (each a full 16-field article object, with `is_representative`).

## 11 Briefings

A structured "what's happening in your world" digest, grouped by topic.

`GET /V1/BRIEF/TODAY`

`GET /V1/BRIEF/SITUATION`

`GET /V1/BRIEF/DAILY`

**today** and **daily** rank by importance; **situation** orders by recency. All accept `?limit=`; **daily** accepts `?date=YYYY-MM-DD`.

```
{
  "data": {
    "kind": "today", "ordering": "importance", "date": "2026-07-09",
    "summary": "5 developments across your scope, in 1 topics.",
    "sections": [
      { "title": "INTERNATIONAL",
        "stories": [
          { "story_id": "2bc19b56-...", "title": "...", "outlets": 291,
            "article_count": 306, "representative_article_id": "1dd6a23b-..." }
        ] }
    ]
  }
}
```

## 12 Geography

District-level coverage across your provisioned states.

### GET /v1/geo/coverage

Coverage counts by state and district within your scope ( `?window=` ).

```
{
  "data": {
    "window_days": 7,
    "states": [
      { "state_code": "TG", "articles": 4751,
        "districts": [ { "id": "hyderabad", "name": "HYDERABAD", "articles": 1186 },
                      { "id": "warangal", "name": "WARANGAL", "articles": 402 } ] }
    ]
  }
}
```

District geography currently covers Telangana & Andhra Pradesh.

### GET /v1/geo/district/{district\_id}

One district: its counts plus recent articles (full article objects). Out-of-scope states return 404.



## 13 Analytics & sentiment

Directed sentiment, per-outlet lean, topic mix, coverage volume, and arbitrary-keyword sentiment.

### Directed sentiment

**GET** /v1/analytics/sentiment

Two-field sentiment toward an entity (by id **or** name), split by pillar, with a daily trend. Add `?include_youtube=true` to append an on-demand YouTube pillar.

EXAMPLE – SENTIMENT TOWARD K. T. RAMA RAO

```
{
  "data": {
    "subject": "K. T. Rama Rao", "window_days": 7,
    "total": 151,
    "split": { "supportive": 28, "neutral": 73, "critical": 50 },
    "net_lean": -0.1457,
    "impact": { "positive": 23, "negative": 26, "neutral": 23, "not_relevant": 79 },
    "by_pillar": {
      "articles": { "total": 148, "split": { "supportive": 28, "neutral": 71, "critical": 49 },
        "net_lean": -0.1419 },
      "newspaper": { "total": 3, "split": { "supportive": 0, "neutral": 2, "critical": 1 },
        "net_lean": -0.3333 }
    },
    "daily": [ { "date": "2026-07-02", "supportive": 1, "neutral": 11, "critical": 12 }, ... ]
  }
}
```

**Two fields, not one.** `stance` (surfaced as the supportive/neutral/critical `split`) is the *tone* of coverage; `impact` is whether events are *good or bad for the subject* by consequence. `net_lean` = (supportive – critical) ÷ total. Figures are a classified, entity-linked sample.

### Per-outlet lean

**GET** /v1/analytics/outlets

Which outlets cover an entity most, and their net lean toward it. `?entity=` (id), `?window=`, `?limit=`.

```
{ "data": { "subject": "K. T. Rama Rao", "window_days": 7,
  "outlets": [ { "name": "Namasthe Telangana", "count": 72, "net_lean": 0.0517 },
    { "name": "Mana Telangana", "count": 20, "net_lean": -0.3333 } ] } }
```

### Topics & volume

**GET** /V1/ANALYTICS/TOPICS

**GET** /V1/ANALYTICS/COVERAGE

```
topics → { "data": { "window_days": 7, "topics": [ { "name": "INTERNATIONAL", "count": 12428 }, ... ]
} }
coverage → { "data": { "total": 350326, "daily": [ { "date": "2026-06-26", "count": 27660 }, ... ],
  "window_days": 14 } }
```

## Keyword sentiment (arbitrary term, on-demand)

**GET** /v1/analytics/keyword-sentiment

Live two-field sentiment for **any** word or phrase — it need not be a provisioned entity. `?keyword=`, `?pillars=articles|clips|both`, `?scope=true` to constrain to your entities/region, `?window=`. Returns `article_ids` / `clip_ids` for drill-down.

Because results are live-scored, the first call for a term takes a few seconds; identical article-only queries are cached. `partial:true` means scoring hit its time budget and returned the newest matches.

# 14 Webhooks

Push alerts to your endpoint when new coverage matches a filter.

## POST /v1/webhooks

Subscribe an `https://` endpoint to events, optionally filtered by entity / topic / sentiment. The signing `secret` is returned **once**, here only.

### REQUEST & RESPONSE

```
POST /v1/webhooks
{ "url": "https://your-host.gov.in/rig-hook",
  "events": ["new_coverage", "critical_sentiment"],
  "filter": { "entity": "d2da8f86-..." } }

→ { "data": {
  "id": "5515379e-...", "url": "https://your-host.gov.in/rig-hook",
  "filter": { "entity": "d2da8f86-...", "sentiment": "critical" },
  "events": ["new_coverage", "critical_sentiment"],
  "is_active": true,
  "secret": "whsec_5d001f05982f1ce8...3bb677aa" } }
```

### EVENTS

| EVENT                                                 | STATUS                                                                                       |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------|
| <code>new_coverage</code>                             | Delivered — new matching item in your scope.                                                 |
| <code>critical_sentiment</code>                       | Delivered — new critical-sentiment coverage (adds a <code>sentiment=critical</code> filter). |
| <code>spike</code> , <code>high_priority_story</code> | Accepted & stored; detectors rolling out (returned under <code>events_pending</code> ).      |

**Verifying delivery.** Each POST to your endpoint is signed `X-RIG-Signature: sha256=HMAC(secret, body)`. Recompute the HMAC over the raw body with your `whsec_...` secret and compare, to confirm authenticity.

- GET /V1/WEBHOOKS
- DELETE /V1/WEBHOOKS/{ID}

List returns your subscriptions (without secrets). Delete is scoped to your org (up to 25 webhooks).

## 15 Usage & quota

---

Your own consumption against your monthly quota.

**GET** /v1/usage

Current-period request count, quota, remaining, and your top endpoints.

```
{
  "data": {
    "period": "2026-07", "requests": 17, "quota": 1000000, "remaining": 999983,
    "by_endpoint": [ { "endpoint": "/v1/articles", "requests": 6 },
                     { "endpoint": "/v1/analytics/sentiment", "requests": 3 }, ... ]
  }
}
```

## 16 Common workflows

---

End-to-end sequences that combine the endpoints above.

### A. Provision your scope, then read your world

1. `PATCH /v1/scope` with your entities (by name), keywords and region.
2. `GET /v1/brief/today` for the grouped digest, or `GET /v1/articles` for the raw feed.
3. `GET /v1/stories` for the multi-outlet stories in your scope.

### B. Sentiment on an entity — and the coverage behind it

1. `GET /v1/analytics/sentiment?entity=<name-or-id>` → the split + daily trend.
2. `GET /v1/articles?entity=<id>&sentiment=critical` → the critical articles driving it.
3. `GET /v1/analytics/outlets?entity=<id>` → which outlets are most negative.

### C. Find YouTube coverage of a topic, then read a transcript

1. `GET /v1/analytics/keyword-sentiment?keyword=<term>&pillars=clips` → `clip_ids`.
2. `GET /v1/clips/<clip_id>` → the full transcript (within 24h of surfacing).

### D. Real-time alerting

1. `POST /v1/webhooks` with `events:["critical_sentiment"]` filtered to your key entities.
2. Verify each delivery's `X-RIG-Signature`, then act on the payload.

---

RIG Intelligence · Partner Integration Reference · v1 · Issued 9 July 2026 · **Confidential — not for redistribution**. Questions & key delivery are handled through your RIG account contact.