

```
// Wood cutting model, finite state, "action-oriented" DSL style.
//
// (Potential) differences to actual machine model/optimization problem
// (to be considered in reduction of original problem):
//
// - the model processes *exactly* NUM input boards and produces *exactly*
//   NUM output boards (can be solved by additional parameters ibnum and obnum)
// - the number of forbidden zones is fixed to FNUM
// - the "Reorder" actions may have a different granularity than the actual ones
// - the "ReorderBoards" and "ReorderPieces" actions may leave a board/piece
//   in the buffer which is not considered in the optimization problem
// - the "Assembly" actions are performed on all pieces, even those that
//   may be not necessary any more to complete the desired number of beams
//   (this can be easily handled by introducing an additional state variable
//   that counts the number of beams produced)
//
system WoodCutting
{
  const LEN: Int; // maximum length of a board
  type Length = Int[0,LEN];
  type Interval = Record[from:Length,to:Length];

  // "good" intervals are not considered (have to be removed before)
  // also for a "curved" interval both endpoints are explicitly given
  type BoardIntervalType = { bad, curved };
  type BoardInterval = Record[type:IntervalType,interval:Interval];

  const BINUM: Int; // maximum number of intervals per board
  type BoardIntervalIndex = Int[0,BINUM];
  type BoardIntervals = Array[BINUM,BoardInterval];
  type Board = Record[length:Length,bintnum:BoardIntervalIndex,bints:BoardIntervals];

  const CNUM: Int = BINUM*2; // maximum number of cuts per board
  type CutIndex = Int[0,CNUM];
  type Cuts = Array[CNUM,Length];

  const NUM: Int; // number of boards
  type BoardIndex = Int[0,NUM];
  type Boards = Array[NUM,Board];

  type InPiece = Record[good:Bool, length:Length];
  type OutPiece = Length;

  const PLEN: Int; // minimal length of pieces

  const PNUM: Int = NUM*(CNUM+1); // maximum number of pieces
  type PieceIndex = Int[0,PNUM];
  type InPieces = Array[PNUM,InPiece];
  type OutPieces = Array[PNUM,OutPiece];

  // can be used to limit the decision search space
  const RBDNUM = NUM+1; // number of reordering boards decisions (<= BNUM+1)
  const CBDNUM = NUM; // number of cutting boards decisions (<= BNUM)
  const FPDNUM = PNUM; // number of filtering pieces decisions (<= PNUM)
```

```

const RPDNUM = PNUM+1; // number of reordering pieces decisions (<= PNUM+1)
const APDNUM = PNUM;   // number of assembling decisions (<= PNUM)

const FNUM: Int; // maximum number of forbidden intervals
type ForbiddenIndex = Int[0,FNUM];
type ForbiddenIntervals = Array[FNUM,Interval];

const BLEN: Int;           // desired length of a beam
type BeamLength = Int[0,BLEN]; // actual length of beam
const BDEPTH: Int;         // desired number of layers
type BeamDepth = Int[0,BDEPTH]; // actual number of layers
const BNUM: Int;           // maximum number of pieces per beam
type BeamIndex = Int[0,BNUM]; // actual number of pieces
type BeamLengths = Array[PNUM,BeamLength];
const DIST: Length;        // minimum distance between two cuts

type Cost = Real; // need not be bounded

// the production line (consisting of multiple "stages")
pipeline Main(
  // input
  in inboards: Boards,

  // state (preserved from previous executions)
  in bempty0: Bool,
  in buffer0: Board,
  in pempty0: Bool,
  in pBuffer0: Board,

  // other parameters and cost
  in fints: ForbiddenIntervals,
  inout cost: Cost
)
{
  // requirement on input (add it to solver?)
  // constraint forall i:BoardIndex.
  //   value board: Board = inboards[i];
  //   forall j:BoardIntervalIndex with j < board.bintnum.
  //     value bint:BoardInterval = board.bints[j];
  //     bint.interval.from < bint.interval.to && // intervals are not empty
  //     if j+1 < board.bintnum
  //       then bint.interval.to <= board.bints[j+1].interval.from
  //       else bint.interval.to <= board.length;

  var bempty: Bool = bempty0;
  var buffer: Board = buffer0;
  var pempty: Bool = pempty0;
  var pBuffer: Board = pBuffer0;
  val outboards: OutBoards; // unconstrained at indices >= obnum
  var obnum: OutBoardIndex = 0;
  val inpieces: InPieces; // unconstrained at indices >= ipnum
  var ipnum: InPieceIndex = 0;
  val outpieces: OutPieces; // unconstrained at indices >= ipnum
  var opnum: InPieceIndex = 0;

```

```
in apieces: OutPieces; // unconstrained at indices >= apnum
var apnum: OutPieceIndex = 0;

// try at most RBDNUM reorder board decisions (if no action is possible,
// perform a "dummy" action that leaves the state unchanged)
// as a result with have *exactly* NUM boards in "outboards"
// (may leave one board in "buffer")
for i: Int[0, RBDNUM-1] do
{
  try ReorderBoards(i, inboards, outboards, obnum, bempty, buffer);
}

// should be ensured by above
// constraint obnum = NUM;

// make exactly CBDNUM cut boards decisions (each with at most CNUM cut positions)
// generates "ipnum" pieces in "inpieces"
for i: Int[0, CBDNUM-1] do
{
  Cut(i, outboards, inpieces, ipnum);
}

// try at most FPDNUM filtering decisions
// generates "opnum" pieces in "outpieces"
for i: Int[0, FPDNUM-1] do
{
  try Filter(i, inpieces, ipnum, outpieces, opnum, cost);
}

// try at most RPDNUM reordering decisions (if no action is possible,
// perform a "dummy" action that leaves the state unchanged)
// as a result with have *exactly* "opnum" = "apnum" pieces in "apieces"
// (may leave one piece in "pbuffer")
for i: Int[0, RPDNUM-1] do
{
  try ReorderPieces(i, outpieces, opnum, apieces, apnum, pempty, pbuffer);
}

// should be ensured by above
// constraint apnum = opnum;

// try at most APDNUM assembly decisions
// (exactly "apnum" scheduling decisions *must* be performed)
val blens: BeamLengths;
var blen: BeamLength = 0;
var bnum: BeamIndex = 0;
var bdepth: BeamDepth = 0;
var bnum0: BeamIndex = 0;
for i: Int[0, APDNUM-1] do
{
  try Assembly(i, apieces, apnum, fints, blens, blen, bnum, bdepth, bnum0);
}
}
```

```
// the first reordering stage
stage ReorderBoards(
  in i: BoardIndex,
  in inboards: Boards,
  in outboards: Boards, // unconstrained at indices >= obnum
  inout obnum: BoardIndex,
  inout bempty: Bool,
  inout buffer: Board
)
{
  requires i < NUM && obnum < NUM;
  action forward()
  {
    in board: Board = inboards[i];
    outboards[obnum] = board; // equality, not assignment!
    obnum' = obnum+1;
    unchanged bempty, buffer;
  }
  action moveout()
  requires i < NUM && (bempty || obnum < NUM);
  {
    in board: Board = inboards[i];
    !bempty => outboards[obnum] = board;
    obnum' = if bempty then obnum else obnum+1;
    bempty' = false;
    buffer' = board;
  }
  action movein()
  requires i = NUM && !bempty;
  {
    outboards[obnum] = buffer;
    obnum' = obnum+1;
    bempty' = true;
    // buffer' can be arbitrary
  }
}

// the cutting stage
stage Cut(
  in i: BoardIndex,
  in outboards: Boards,
  in inpieces: InPieces, // unconstrained at indices >= ipnum
  inout ipnum: PieceIndex
)
{
  action cut(cnum: CutIndex, cuts: Cuts)
  {
    val board: Board = outboards[i];
    // only allowed cuts
    constraint forall j: CutIndex with j < cnum.
      // cuts are strictly ordered
      val start: Length = if j = 0 then 0 else cut[j-1];
      start < cut[j] && (j = cnum-1 => cut[j] < board.length) &&
      // cuts are not strictly within bad intervals
  }
}
```

```

    !exists k: BoardIntervalIndex with k < board.bintsnum.
    val bint: BoardInterval = boards.bints[k].
    bint.type = bad &&
    bint.interval.from < cut[j] && cut[j] < bint.interval.to;
// all necessary cuts
constraint forall k: BoardIntervalIndex with k < board.bintsnum.
    val bint: BoardInterval = board.bints[k];
    if bint.type = curved then
        exists j: CutIndex with j < cnum.
        bint.interval.from <= cuts[j] && cuts[j] <= bint.interval.to;
    else // if bint.type = bad then
        // enforce cut at bad part intervals (could be relaxed)
        exists j: CutIndex with j < cnum-1.
        bint.interval.from = cut[j] && bint.interval.to = cut[j+1];
// the resulting piece (can be combined with "only allowed cuts")
constraint forall j: CutIndex with j < cnum.
    var inpiece: InPiece = inpieces[ipnum+j];
    val start: Length = if j = 0 then 0 else cut[j-1];
    inpiece.length = cut[j]-start &&
    inpiece.good =
        // assume here cuts at bad part intervals (could be relaxed)
        ~exists k: BoardIndex with k < board.bintsnum.
        val bint: BoardInterval = boards.bints[k].
        bint.type = bad && start = bint.interval.from;
    ipnum' = ipnum+cnum;
}
}

// the filtering stage
stage Filter(
    in i: PieceIndex,
    in inpieces: InPieces,
    in ipnum: PieceIndex,
    in outpieces: OutPieces, // unconstrained at indices >= opnum
    inout opnum: OutPieceIndex,
    inout cost: Cost;
)
{
    requires i < ipnum;
    action keep()
    {
        val piece: Piece = inpieces[i];
        constraint piece.good && piece.length >= PLEN;
        outpieces[opnum] = piece.length; // equality, not assignment!
        opnum' = opnum+1;
        unchanged cost;
    }
    requires i < ipnum;
    action discard()
    {
        val piece: Piece = inpieces[i];
        cost' = if piece.good then cost+piece.length else cost;
        unchanged opnum;
    }
}

```

```
}

// the second reordering stage
stage ReorderPieces(
  in i: PieceIndex,
  in outpieces: OutPieces,
  in opnum: PieceIndex,
  in apieces: OutPieces, // unconstrained at indices >= apnum
  inout apnum: PieceIndex,
  inout pempty: Bool,
  inout pBuffer: Piece
)
{
  action forward()
  requires i < opnum && apnum < PNUM;
  {
    val piece: OutPiece = outpieces[i];
    apieces[apnum] = piece; // equality, not assignment!
    apnum' = apnum+1;
    unchanged pempty, pBuffer;
  }
  action moveout()
  requires i < opnum && (pempty || apnum < PNUM);
  {
    val piece: InPiece = outpieces[i];
    !pempty => apieces[apnum] = pBuffer;
    apnum' = if pempty then apnum else apnum+1;
    pempty' = false;
    pBuffer' = piece;
  }
  action movein()
  requires i = opnum && !pempty;
  {
    apieces[apnum] = pBuffer;
    apnum' = apnum+1;
    pempty' = true;
    // pBuffer' can be arbitrary
  }
}

// the assembly stage
stage Assembly(
  in i: PieceIndex,
  in apieces: OutPieces,
  in apnum: PieceIndex,
  in fints: ForbiddenIntervals,
  in blens: BeamLengths, // unconstrained at indices >= i
  inout blen: BeamLength,
  inout bnum: BeamIndex,
  inout bdepth: BeamDepth,
  inout bnum0: BeamIndex
)
{
  action accept()
```

```
requires i < apnum;
{
  val blen0: BeamLength = blen+apieces[i];
  blens[i] = blen0;
  constraint blen0 <= BLEN;
  constraint !exists j:ForbiddenIndex with j < FNUM.
    fints[j].from <= blen0 && blen0 <= fints[j].to;
  constraint forall j:BeamIndex with j < bnum0.
    value diff: BeamLength = blen0-blens[i-bnum-bnum0+j];
    DIFF <= if diff >= 0 then diff else -diff;
  if blen0 < BLEN then
    blen' = blen0;
    bnum' = bnum+1;
    unchanged bdepth, bnum0;
  else
    blen' = 0;
    bnum' = 0;
    if bdepth < BDEPTH-1 then
      bdepth' = bdepth+1;
      bnum0' = bnum;
    else
      bdepth' = 0;
      bnum0' = 0;
  }
}
```