

1. Recon & Access
(a) information-gathering
Query: “Retrieve computer data from the domain 'corp.local' while resolving IP addresses of computer objects via nslookup on the domain controller.” Tool_name: impacket-GetADComputers Optional_args: {"--resolveIP": null} Positional_args: ["corp.local"] GT_cmd: impacket-GetADComputers --resolveIP corp.local
(b) 802-11
Query: "List all wireless devices and their block status using rfkill with JSON output format.” Tool_name: rfkill Optional_args: {"--json -J": null} Positional_args: ["list"] GT_cmd: rfkill --json list
(c) rfid
Query: “Scan for high-frequency RFID tags and display their type and UID.” Tool_name: proxmark3 Optional_args: {"--cmd": "hf search"} Positional_args: ["/dev/ttyACM0"] GT_cmd: proxmark3 /dev/ttyACM0 --cmd "hf search"
(d) bluetooth
Query: “Start scanning for nearby Bluetooth devices and display their addresses and names.” Tool_name: bluetoothctl Optional_args: {} Positional_args: ["scan“, "on"] GT_cmd: bluetoothctl scan on
(e) sdr
Query: “Use rtlSDR-scanner to scan from 100 MHz to 200 MHz with 5 sweeps, saving results to output.rfs.csv.” Tool_name: rtlSDR-scanner Optional_args: {"--end -e": "200", "--start -s": "100", "--sweeps -w": "5"} Positional_args: ["output.rfs.csv"], GT_cmd: rtlSDR-scanner --end 200 --start 100 --sweeps 5 output.rfs.csv
(f) social-engineering
Query: “Create an access point on channel 6 with ESSID 'TotallyNotATrap', enable the Caffe Latte WEP attack, set the WEP flag in beacons to 1, and use interface wlan0mon.” Tool_name: airbase-ng Optional_args: {"--channel -c": "6", "--essid -e": "TotallyNotATrap", "--caffe-latte": null, "--wep-flags": "1"} Positional_args: ["wlan0mon"] GT_cmd: airbase-ng --channel 6 --essid TotallyNotATrap --caffe-latte --wep-flags 1 wlan0mon

2. Vulnerability Analysis
(a) vulnerability
Query: “Enumerate all installed plugins on the WordPress site at http://wordpress.local” Tool_name: wpscan Optional_args: {"--enumerate": "p", "--url": "http://wordpress.local"} Positional_args: [] GT_cmd: wpscan --enumerate p --url http://wordpress.local
(b) fuzzing
Query: “Run llvm-reduce on ‘crash.ll’ with the interestingness test named ‘repro.sh’, passing ‘--arg1 value1’ to the test script, and limit reductions to 2 threads.” Tool_name: llvm-reduce Optional_args: {"-j": "2", "--test": "repro.sh", "--test-arg": "--arg1 value1"} Positional_args: ["crash.ll"] GT_cmd: llvm-reduce -j 2 --test repro.sh --test-arg '-arg1 value1' crash.ll
(c) web
Query: “Scan http://test.site using wafw00f with maximum verbosity and do not follow HTTP redirects.” Tool_name: wafw00f Optional_args: {"--noredirect -r": null, "--verbose -v": null} Positional_args: ["http://test.site"] GT_cmd: wafw00f --noredirect --verbose http://test.site

(d) database
Query: "Use sqlmap to enumerate all databases available on the backend database of the vulnerable web application at http://test.site/item.php?id=1.” Tool_name: sqlmap Optional_args: {"-u": "http://test.site/item.php?id=1", "--dbs": null} Positional_args: [] GT_cmd: sqlmap -u "http://test.site/item.php?id=1" --dbs
(e) voip
Query: "Run rtpinertsound with the -v flag on the stapler.wav file found in /usr/share/rtpinertsound/.” Tool_name: rtpinertsound Optional_args: {"--verbose -v": null} Positional_args: ["/usr/share/rtpinertsound/stapler.wav"] GT_cmd: rtpinertsound --verbose /usr/share/rtpinertsound/stapler.wav

3. Exploitation & Delivery ALIAS
(a) exploitation
Query: “Enumerate all installed plugins on the WordPress site at http://wordpress.local” Tool_name: wpscan Optional_args: {"--enumerate": "p", "--url": "http://wordpress.local"} Positional_args: [] GT_cmd: wpscan --enumerate p --url http://wordpress.local
(b) sniffing-spoofing
Query: "Use webspy to monitor HTTP traffic from the host 192.168.1.100 using the default network interface.” Tool_name: webspy Optional_args: {} Positional_args: ["192.168.1.100"] GT_cmd: webspy 192.168.1.100
(c) hardware
Query: "Use qemu-system-arm to emulate a system with 2 CPU threads, 1024 MB RAM, and load the device tree blob 'board.dtb’.” Tool_name: qemu-system-arm Optional_args: {"-smp": "2", "-m": "1024", "-dtb": "board.dtb"} Positional_args: [] GT_cmd: qemu-system-arm -smp 2 -m 1024 -dtb board.dtb
(d) wireless
Query: "Use sakis3g to initiate an interactive connection session.” Tool_name: sakis3g Optional_args: {"--interactive": null} Positional_args: ["connect"] GT_cmd: sakis3g --interactive connect

4. Post-exploit. & Lateral Movement
(a) post-exploitation
Query: “Display the privileges of user 'eve' as they would apply to the command 'cat /etc/shadow', using non-interactive mode.” Tool_name: sudo Optional_args: {"--list -l": null, "--non-interactive -n": null, "--other-user -U": "eve"} Positional_args: ["cat", "/etc/shadow"] GT_cmd: sudo --list --non-interactive -U eve cat /etc/shadow
(b) passwords
Query: "Run ncrack with maximum speed template (-T5), targeting SSH on 10.0.0.5, using usernames from users.txt and passwords from pass.txt, and stop after first successful login." Tool_name: ncrack Optional_args: {"-f": null, "-T": "5", "-P": "pass.txt", "-U": "users.txt"} Positional_args: ["ssh://10.0.0.5"] GT_cmd: ncrack -f -T5 -P pass.txt -U users.txt ssh://10.0.0.5

4. Post-exploit. & Lateral Movement
(c) windows-resources
Query: "Parse the Windows SAM registry hive to enumerate local user accounts for forensic analysis.” Tool_name: regripper Optional_args: {"-r": "SAM", "-p": "samparse"} Positional_args: [] GT_cmd: regripper -r SAM -p samparse
(d) crypto-stego
Query: "Extract encrypted hidden data from secret.jpg using steghide with the passphrase mypassword.” Tool_name: steghide Optional_args: {"-sf": "secret.jpg", "-p": "mypassword"} Positional_args: ["extract"] GT_cmd: steghide extract -sf secret.jpg -p mypassword

5. Defense Analysis & Reporting
(a) reverse-engineering
Query: "Disassemble the dex file app.dex into smali files in the directory 'output_smali', forcing overwrite if it already exists." Tool_name: d2j-baksmali Optional_args: {"--force -f": null, "--output -o": "output_smali"} Positional_args: ["app.dex"] GT_cmd: d2j-baksmali --force --output output_smali app.dex
(b) forensics
Query: "Convert 'malware.dex' to Java without decoding any resources and suppress all source decompilation, saving only the resource-less structure.“ Tool_name: jadx Optional_args: {"--no-res -r": null, "--no-src -s": null} Positional_args: ["malware.dex"] GT_cmd: jadx --no-res --no-src malware.dex
(c) reporting
Query: "Record my desktop with a delay of 5 seconds before starting, output the video as 'demo.ogv', and disable sound recording.” Tool_name: recordmydesktop Optional_args: {"--delay": "5", "--no-sound": null, "--output -o": "demo.ogv"} Positional_args: [] GT_cmd: recordmydesktop --delay 5 --no-sound --output demo.ogv
(d) gpu
Query: "Crack SHA1 password hashes from hashes.txt using GPU device 0 and the wordlist wordlist.txt with oclgausscrack.“ Tool_name: oclgausscrack Optional_args: {"-d": "0", "-t": "sha1"} Positional_args: ["hashes.txt", "wordlist.txt"] GT_cmd: oclgausscrack -d 0 -t sha1 hashes.txt wordlist.txt