

## Deep Learning for Business

Basics of Deep Learning Neural Networks

# NN (Neural Network)


## Neural Network

### DL (Deep Learning) Technology

- NN (Neural Network) or ANN (Artificial NN)
  - NNs start with one Neuron (Nerve Cell)
- In DL, intelligence is obtained from data using
  - CNN (Convolutional Neural Network)
  - RNN (Recurrent Neural Network)


# Neural Network

## Neuron (Nerve Cell)




# Neural Network

## Neuron (Nerve Cell)



# Neural Network


## Neuron Signal Transfer



## Deep Learning & Machine Learning

### Neuron with Threshold Logic Unit

– W. McCulloch & W. Pitts (1943) model



## Deep Learning & Machine Learning

### Activation Function

- Hard output binary values (0 or 1) result from the Threshold T activation function


$$\text{Output} = \begin{cases} 1 & \text{if } y > T \\ 0 & \text{Otherwise} \end{cases}$$

- Soft output values can be made by using one of the following activation functions (instead of the Threshold T)

## Big Data Intelligence, DL & ML

### Activation Function types


- Logistic sigmoid  $\sigma(y) = \frac{1}{1 + \exp(-y)}$



## Big Data Intelligence, DL & ML

### Activation Function types


- Softplus  $\zeta(y) = \log(1 + \exp(y))$



## Big Data Intelligence, DL & ML

### Activation Function types

- ReLU (Rectified Linear Unit)  $g(y) = \max(0, y)$



## Big Data Intelligence, DL & ML

### Soft Output Activation Functions

- Logistic sigmoid  $\sigma(y) = \frac{1}{1 + \exp(-y)}$
- Softplus  $\zeta(y) = \log(1 + \exp(y))$
- ReLU (Rectified Linear Unit)  
 $g(y) = \max(0, y)$

## Neural Network Terminology

### Perceptron

- ML (Machine Learning) algorithm that conducts supervised learning of linear (binary) classification
- Perceptrons are trained to determine if an input (vector or scalar value) belongs to one class or another

## Neural Network Terminology

### MLP (Multi-Layer Perceptron)

- Feed forward NN (Neural Network) that is formed of multiple layers of perceptrons, where each layer may use multiple perceptrons in parallel
- MLPs use BP (Back Propagation) based supervised learning to train the outputs (to accurately conduct nonlinear classification)

## Neural Network Terminology

### SoftMax

- Logistic function that maps a K dimensional vector (e.g., a set of K data inputs) of real values to values in the range of 0~1 such that all values of the vector add up to 1
- ML (Machine Learning) NNs (Neural Networks) often use the Softmax function to enhance the accuracy of the classification process

## Neural Network Terminology

### SoftMax transfer example

- Original Inputs:  $a_1, a_2, a_3$

$$\text{– SoftMax Outputs } \left\{ \begin{array}{l} \tilde{a}_1 = \frac{e^{a_1}}{e^{a_1} + e^{a_2} + e^{a_3}} \\ \tilde{a}_2 = \frac{e^{a_2}}{e^{a_1} + e^{a_2} + e^{a_3}} \\ \tilde{a}_3 = \frac{e^{a_3}}{e^{a_1} + e^{a_2} + e^{a_3}} \end{array} \right.$$

- Constraint Satisfied:  $(\tilde{a}_1 + \tilde{a}_2 + \tilde{a}_3) = 1$

## Neural Network Terminology

### SoftMax transfer example

$$\left. \begin{array}{l} a_1=9 \\ a_2=20 \\ a_3=25 \end{array} \right\} \rightarrow \left\{ \begin{array}{l} \tilde{a}_1=0.00000011178 \\ \tilde{a}_2=0.00669285018 \\ \tilde{a}_3=0.99330703804 \end{array} \right.$$

- $(\tilde{a}_1 + \tilde{a}_2 + \tilde{a}_3) = 1$
- Weights ( $w_1, w_2, w_3$ ) and SoftMax values ( $\tilde{a}_1, \tilde{a}_2, \tilde{a}_3$ ) combined

$$w_1\tilde{a}_1 + w_2\tilde{a}_2 + w_3\tilde{a}_3$$



## Neural Network Terminology

### AutoEncoder

- AutoEncoder (AutoAssociator) is a NN used to learn the characteristics of a data set such that the representation (encoding) dimensionality can be reduced
- Simplest form of an AutoEncoder is a feedforward non-recurrent neural network

## Deep Learning for Business

### Basics of Deep Learning Neural Networks

## References

## References

- I. Goodfellow, Y. Bengio, and A. Courville, Deep Learning. book in preparation, MIT Press, [www.deeplearningbook.org](http://www.deeplearningbook.org), 2016.
- D. Silver, A. Huang, C. J. Maddison, A. Guez, L. Sifre, G. Van Den Driessche, J. Schrittwieser, I. Antonoglou, V. Panneershelvam, M. Lanctot, S. Dieleman, D. Grewe, J. Nham, N. Kalchbrenner, I. Sutskever, T. Lillicrap, M. Leach, K. Kavukcuoglu, T. Graepel & S. Dieleman, "Mastering the game of Go with deep neural networks and tree search," Nature, vol. 529, no. 7587, pp. 484-489, 28 Jan. 2016.
- Jared Hillam, "What is Hadoop?: SQL Comparison," YouTube, <https://www.youtube.com/watch?v=MfF750YVDxM>
- Wikipedia, <http://www.wikipedia.org>
- Nvidia, <https://blogs.nvidia.com/blog/2016/07/29/whats-difference-artificial-intelligence-machine-learning-deep-learning-ai/>

## References

### Image sources

- Neuron  
By Dhp1080, svg adaptation by Actam (Image:Neuron.svg) [CC BY-SA 3.0 (<http://creativecommons.org/licenses/by-sa/3.0/>) or GFDL (<http://www.gnu.org/copyleft/fdl.html>)], via Wikimedia Commons
- By Nicolas.Rougier (Own work) [GFDL (<http://www.gnu.org/copyleft/fdl.html>), CC-BY-SA-3.0 (<http://creativecommons.org/licenses/by-sa/3.0/>) or CC BY-SA 2.5-2.0-1.0 (<http://creativecommons.org/licenses/by-sa/2.5-2.0-1.0/>)], via Wikimedia Commons
- By Copyright (c) 2003 Nicolas P. Rougier (Nicolas P. Rougier) [GPL (<http://www.gnu.org/licenses/gpl.html>)], via Wikimedia Commons

## References

### Image sources

- By Donarreiskoffer (Self-photographed) [GFDL (<http://www.gnu.org/copyleft/fdl.html>) or CC-BY-SA-3.0 (<http://creativecommons.org/licenses/by-sa/3.0/>)], via Wikimedia Commons:[//commons.wikimedia.org/w/index.php?curid=43383](https://commons.wikimedia.org/w/index.php?curid=43383)
- By David Lapetina (Own work) [GFDL (<http://www.gnu.org/copyleft/fdl.html>) or CC BY-SA 3.0 (<http://creativecommons.org/licenses/by-sa/3.0/>)], via Wikimedia Commons