RIT VEXU Core API

Generated by Doxygen 1.13.2

١	Core	•
	1.1 Getting Started	2
	1.2 Features	2
2	Hierarchical Index	3
	2.1 Class Hierarchy	3
3	Class Index	5
	3.1 Class List	5
4	Class Documentation	8
	4.1 Async Class Reference	8
	4.1.1 Detailed Description	9
	4.2 AutoChooser Class Reference	9
	4.2.1 Detailed Description	9
	4.2.2 Constructor & Destructor Documentation	9
	4.2.3 Member Function Documentation	10
	4.2.4 Member Data Documentation	10
	4.3 BasicSolenoidSet Class Reference	10
	4.3.1 Detailed Description	11
	4.3.2 Constructor & Destructor Documentation	11
	4.3.3 Member Function Documentation	11
	4.4 BasicSpinCommand Class Reference	11
	4.4.1 Detailed Description	12
	4.4.2 Constructor & Destructor Documentation	12
	4.4.3 Member Function Documentation	12
	4.5 BasicStopCommand Class Reference	13
	4.5.1 Detailed Description	13
	4.5.2 Constructor & Destructor Documentation	13
	4.5.3 Member Function Documentation	13
	4.6 Branch Class Reference	14
	4.6.1 Detailed Description	14
	4.7 screen::ButtonWidget Class Reference	14
	4.7.1 Detailed Description	14
	4.7.2 Constructor & Destructor Documentation	14
	4.7.3 Member Function Documentation	15
	4.8 CommandController Class Reference	16
	4.8.1 Detailed Description	16
	4.8.2 Constructor & Destructor Documentation	16
	4.8.3 Member Function Documentation	16
	4.9 Condition Class Reference	18
	4.9.1 Detailed Description	19
	4.10 CustomEncoder Class Reference	19

4.10.1 Detailed Description	
4.10.2 Constructor & Destructor Documentation	
4.10.3 Member Function Documentation	
4.11 DelayCommand Class Reference	
4.11.1 Detailed Description	
4.11.2 Constructor & Destructor Documentation	
4.11.3 Member Function Documentation	
4.12 DriveForwardCommand Class Reference	
4.12.1 Detailed Description	
4.12.2 Constructor & Destructor Documentation	
4.12.3 Member Function Documentation	
4.13 DriveStopCommand Class Reference	
4.13.1 Detailed Description	
4.13.2 Constructor & Destructor Documentation	
4.13.3 Member Function Documentation	
4.14 DriveToPointCommand Class Reference	
4.14.1 Detailed Description	
4.14.2 Constructor & Destructor Documentation	
4.14.3 Member Function Documentation	
4.15 AutoChooser::entry_t Struct Reference	
4.15.1 Detailed Description	
4.15.2 Member Data Documentation	
4.16 ExponentialMovingAverage Class Reference	
4.16.1 Detailed Description	
4.16.2 Constructor & Destructor Documentation	
4.16.3 Member Function Documentation	
4.17 Feedback Class Reference	
4.17.1 Detailed Description	
4.17.2 Member Function Documentation	
4.18 FeedForward Class Reference	
4.18.1 Detailed Description	
4.18.2 Constructor & Destructor Documentation	
4.18.3 Member Function Documentation	
4.19 FeedForward::ff_config_t Struct Reference	
4.19.1 Detailed Description	
4.19.2 Member Data Documentation	
4.20 Filter Class Reference	
4.20.1 Detailed Description	
4.21 Flywheel Class Reference	
4.21.1 Detailed Description	
4.21.2 Constructor & Destructor Documentation	
4.21.3 Member Function Documentation	

4.21.4 Friends And Related Symbol Documentation	37
4.22 FlywheelStopCommand Class Reference	37
4.22.1 Detailed Description	37
4.22.2 Constructor & Destructor Documentation	37
4.22.3 Member Function Documentation	38
4.23 FlywheelStopMotorsCommand Class Reference	38
4.23.1 Detailed Description	38
4.23.2 Constructor & Destructor Documentation	38
4.23.3 Member Function Documentation	39
4.24 FlywheelStopNonTasksCommand Class Reference	39
4.24.1 Detailed Description	39
4.25 FunctionCommand Class Reference	39
4.25.1 Detailed Description	39
4.26 FunctionCondition Class Reference	40
4.26.1 Detailed Description	40
4.27 screen::FunctionPage Class Reference	40
4.27.1 Detailed Description	41
4.27.2 Constructor & Destructor Documentation	41
4.27.3 Member Function Documentation	41
4.28 GenericAuto Class Reference	42
4.28.1 Detailed Description	42
4.28.2 Member Function Documentation	42
4.29 PurePursuit::hermite_point Struct Reference	43
4.29.1 Detailed Description	44
4.30 IfTimePassed Class Reference	44
4.30.1 Detailed Description	44
4.31 InOrder Class Reference	44
4.31.1 Detailed Description	44
4.32 Lift $<$ T $>$ Class Template Reference	45
4.32.1 Detailed Description	45
4.32.2 Constructor & Destructor Documentation	45
4.32.3 Member Function Documentation	46
4.33 Lift< T >::lift_cfg_t Struct Reference	49
4.33.1 Detailed Description	49
4.34 Logger Class Reference	49
4.34.1 Detailed Description	50
4.34.2 Constructor & Destructor Documentation	50
4.34.3 Member Function Documentation	50
4.35 MotionController::m_profile_cfg_t Struct Reference	52
4.35.1 Detailed Description	52
$4.36\ StateMachine < System,\ IDType,\ Message,\ delay_ms,\ do_log>::MaybeMessage\ Class\ Reference\ .$	53
4.36.1 Detailed Description	53

4.36.2 Constructor & Destructor Documentation	53
4.36.3 Member Function Documentation	54
4.37 MecanumDrive Class Reference	54
4.37.1 Detailed Description	55
4.37.2 Constructor & Destructor Documentation	55
4.37.3 Member Function Documentation	55
4.38 MecanumDrive::mecanumdrive_config_t Struct Reference	57
4.38.1 Detailed Description	57
4.39 motion_t Struct Reference	57
4.39.1 Detailed Description	58
4.40 MotionController Class Reference	58
4.40.1 Detailed Description	59
4.40.2 Constructor & Destructor Documentation	59
4.40.3 Member Function Documentation	59
4.41 MovingAverage Class Reference	62
4.41.1 Detailed Description	62
4.41.2 Constructor & Destructor Documentation	62
4.41.3 Member Function Documentation	63
4.42 Odometry3Wheel Class Reference	64
4.42.1 Detailed Description	65
4.42.2 Constructor & Destructor Documentation	65
4.42.3 Member Function Documentation	65
4.43 Odometry3Wheel::odometry3wheel_cfg_t Struct Reference	66
4.43.1 Detailed Description	66
4.43.2 Member Data Documentation	66
4.44 OdometryBase Class Reference	67
4.44.1 Detailed Description	68
4.44.2 Constructor & Destructor Documentation	68
4.44.3 Member Function Documentation	68
4.44.4 Member Data Documentation	71
4.45 screen::OdometryPage Class Reference	72
4.45.1 Detailed Description	73
4.45.2 Constructor & Destructor Documentation	73
4.45.3 Member Function Documentation	73
4.46 OdometrySerial Class Reference	74
4.46.1 Detailed Description	75
4.46.2 Constructor & Destructor Documentation	75
4.46.3 Member Function Documentation	75
4.47 OdometryTank Class Reference	78
4.47.1 Detailed Description	79
4.47.2 Constructor & Destructor Documentation	79
4.47.3 Member Function Documentation	81

4.48 OdomSetPosition Class Reference	 	81
4.48.1 Detailed Description	 	81
4.48.2 Constructor & Destructor Documentation	 	81
4.48.3 Member Function Documentation	 	82
4.49 screen::Page Class Reference	 	82
4.49.1 Detailed Description	 	83
4.49.2 Member Function Documentation	 	83
4.50 Parallel Class Reference	 	83
4.50.1 Detailed Description	 	84
4.51 PurePursuit::Path Class Reference	 	84
4.51.1 Detailed Description	 	84
4.51.2 Constructor & Destructor Documentation	 	84
4.51.3 Member Function Documentation	 	84
4.52 PID Class Reference	 	85
4.52.1 Detailed Description	 	86
4.52.2 Member Enumeration Documentation	 	86
4.52.3 Constructor & Destructor Documentation	 	86
4.52.4 Member Function Documentation	 	87
4.52.5 Member Data Documentation	 	89
4.53 PID::pid_config_t Struct Reference	 	90
4.53.1 Detailed Description	 	90
4.53.2 Member Data Documentation	 	90
4.54 screen::PIDPage Class Reference	 	91
4.54.1 Detailed Description	 	91
4.54.2 Constructor & Destructor Documentation	 	91
4.54.3 Member Function Documentation	 	92
4.55 Pose2d Class Reference	 	92
4.55.1 Detailed Description	 	93
4.55.2 Constructor & Destructor Documentation	 	93
4.55.3 Member Function Documentation	 	95
4.55.4 Friends And Related Symbol Documentation	 	99
4.56 PurePursuitCommand Class Reference	 	99
4.56.1 Detailed Description	 	99
4.56.2 Constructor & Destructor Documentation	 	99
4.56.3 Member Function Documentation	 	100
4.57 Rect Struct Reference	 	100
4.57.1 Detailed Description	 	100
4.58 robot_specs_t Struct Reference	 	100
4.58.1 Detailed Description	 	101
4.58.2 Member Data Documentation	 	101
4.59 Rotation2d Class Reference	 	101
4.59.1 Detailed Description	 	102

4	59.2 Constructor & Destructor Documentation	102
4	59.3 Member Function Documentation	103
4	59.4 Friends And Related Symbol Documentation	108
4.60 sc	reen::ScreenData Struct Reference	109
4	60.1 Detailed Description	109
4.61 S	rializer Class Reference	109
4	61.1 Detailed Description	109
4	61.2 Constructor & Destructor Documentation	110
4	61.3 Member Function Documentation	111
4.62 sc	reen::SliderWidget Class Reference	113
4	62.1 Detailed Description	114
4	62.2 Constructor & Destructor Documentation	114
4	62.3 Member Function Documentation	114
4.63 S	inRPMCommand Class Reference	115
4	63.1 Detailed Description	115
4	63.2 Constructor & Destructor Documentation	115
4	63.3 Member Function Documentation	116
4.64 P	rePursuit::spline Struct Reference	116
4	64.1 Detailed Description	116
4.65 S	ateMachine< System, IDType, Message, delay_ms, do_log >::State Struct Reference	116
4	65.1 Detailed Description	116
4.66 S	ateMachine $<$ System, IDType, Message, delay_ms, do_log $>$ Class Template Reference 1	117
	ateMachine< System, IDType, Message, delay_ms, do_log > Class Template Reference	
4		117
4	66.1 Detailed Description	117 118
4 4 4	66.1 Detailed Description	117 118 118
4.67 sc	66.1 Detailed Description	117 118 118 119
4.67 so	66.1 Detailed Description	117 118 118 119
4.67 sc 4	66.1 Detailed Description	1117 1118 1118 1119 1119
4.67 sc 4	66.1 Detailed Description	1117 1118 1119 1119 1119
4.67 sc 4 4.68 Ta	66.1 Detailed Description	1117 1118 1118 1119 1119 1119
4.67 sc 4 4.68 Ta 4	66.1 Detailed Description 66.2 Constructor & Destructor Documentation 66.3 Member Function Documentation reen::StatsPage Class Reference 67.1 Detailed Description 67.2 Constructor & Destructor Documentation 67.3 Member Function Documentation keBackHalf Class Reference	1117 1118 1119 1119 1119 1120
4.67 sc 4 4.68 Ta 4	66.1 Detailed Description	1117 1118 1119 1119 1119 1120 1121
4.67 sc 4 4.68 Ta 4 4.69 Ta	66.1 Detailed Description 66.2 Constructor & Destructor Documentation 66.3 Member Function Documentation reen::StatsPage Class Reference 67.1 Detailed Description 67.2 Constructor & Destructor Documentation 67.3 Member Function Documentation 67.3 Member Function Documentation 68.1 Detailed Description 68.2 Member Function Documentation	1117 1118 1119 1119 1119 1120 1121
4.67 sc 4 4.68 Ta 4 4.69 Ta 4	66.1 Detailed Description 66.2 Constructor & Destructor Documentation 66.3 Member Function Documentation reen::StatsPage Class Reference 67.1 Detailed Description 67.2 Constructor & Destructor Documentation 67.3 Member Function Documentation 68.4 Member Function Documentation 68.5 Member Function Documentation 68.6 Member Function Documentation 68.7 Detailed Description 68.8 Member Function Documentation 68.9 Member Function Documentation	117 118 118 119 119 112 121 123
4.67 sc 4 4.68 Ta 4 4.69 Ta 4	66.1 Detailed Description 66.2 Constructor & Destructor Documentation 66.3 Member Function Documentation 66.3 Member Function Documentation 67.1 Detailed Description 67.2 Constructor & Destructor Documentation 67.3 Member Function Documentation 68.4 Detailed Description 68.5 Member Function Documentation 68.6 Member Function Documentation 68.7 Detailed Description 68.8 Member Function Documentation 68.9 Member Function Documentation 68.1 Detailed Description 68.2 Member Function Documentation 68.3 Member Function Documentation 68.4 Detailed Description	117 118 118 119 119 119 1120 1121 1123
4.67 sc 4 4.68 Ta 4 4.69 Ta 4	66.1 Detailed Description 66.2 Constructor & Destructor Documentation 66.3 Member Function Documentation reen::StatsPage Class Reference 67.1 Detailed Description 67.2 Constructor & Destructor Documentation 67.3 Member Function Documentation 68.4 Member Function Documentation 68.5 Member Function Documentation 68.6 Member Function Documentation 68.7 Detailed Description 68.8 Member Function Documentation 68.9 Member Function Documentation 68.1 Detailed Description 68.2 Member Function Documentation 68.3 Member Function Documentation 68.4 Member Function Documentation	117 118 118 1119 1119 1120 1121 1123 1123
4.67 sc 4 4.68 Ta 4 4.69 Ta 4 4.69 Ta 4	66.1 Detailed Description 66.2 Constructor & Destructor Documentation 66.3 Member Function Documentation reen::StatsPage Class Reference 67.1 Detailed Description 67.2 Constructor & Destructor Documentation 67.3 Member Function Documentation 68.1 Detailed Description 68.2 Member Function Documentation 68.1 Detailed Description 68.2 Member Function Documentation 69.2 Member Enunction Documentation 69.3 Constructor & Destructor Documentation 69.3 Constructor & Destructor Documentation	117 118 119 119 119 120 120 123 123
4.67 sc 4 4.68 Ta 4 4.69 Ta 4 4.70 trs	66.1 Detailed Description 66.2 Constructor & Destructor Documentation 66.3 Member Function Documentation 7 reen::StatsPage Class Reference 67.1 Detailed Description 67.2 Constructor & Destructor Documentation 67.3 Member Function Documentation 68.4 Detailed Description 68.2 Member Function Documentation 68.1 Detailed Description 68.2 Member Function Documentation 68.3 Member Function Documentation 69.4 Member Enumeration Documentation 69.3 Constructor & Destructor Documentation 69.4 Member Function Documentation	117 118 119 119 119 120 121 123 123 123
4.67 sc 4 4.68 Ta 4 4.69 Ta 4 4.70 tra 4	66.1 Detailed Description 66.2 Constructor & Destructor Documentation 66.3 Member Function Documentation reen::StatsPage Class Reference 67.1 Detailed Description 67.2 Constructor & Destructor Documentation 67.3 Member Function Documentation 68.4 Member Function Documentation 68.2 Member Function Documentation 68.2 Member Function Documentation 68.2 Member Function Documentation 68.2 Member Function Documentation 69.1 Detailed Description 69.2 Member Enumeration Documentation 69.3 Constructor & Destructor Documentation 69.4 Member Function Documentation 69.4 Member Function Documentation 69.5 Member Function Documentation 69.6 Member Function Documentation 69.7 Detailed Description 69.8 Member Function Documentation 69.9 Member Function Documentation 69.1 Detailed Description 69.2 Member Function Documentation 69.3 Constructor & Destructor Documentation 69.4 Member Function Documentation 69.5 Member Function Documentation 69.6 Member Function Documentation 69.7 Detailed Description	117 118 118 119 119 112 112 112 112 113 113
4.67 sc 4 4.68 Ta 4 4.69 Ta 4 4.70 tra 4	66.1 Detailed Description 66.2 Constructor & Destructor Documentation 66.3 Member Function Documentation 7 reen::StatsPage Class Reference 67.1 Detailed Description 67.2 Constructor & Destructor Documentation 67.3 Member Function Documentation 67.3 Member Function Documentation 68.1 Detailed Description 68.2 Member Function Documentation 68.2 Member Function Documentation 69.1 Detailed Description 69.1 Detailed Description 69.2 Member Enumeration Documentation 69.3 Constructor & Destructor Documentation 69.4 Member Function Documentation 69.4 Member Function Documentation 69.4 Member Function Documentation 69.5 Constructor & Destructor Documentation 69.6 Member Function Documentation 69.7 Detailed Description	117 118 118 119 119 112 112 112 112 113 113

1 Core 1

Index		157
	4.78.3 Member Function Documentation	155
	4.78.2 Constructor & Destructor Documentation	155
	4.78.1 Detailed Description	
4.78	WaitUntilUpToSpeedCommand Class Reference	
	4.77.1 Detailed Description	155
4.77	WaitUntilCondition Class Reference	154
	4.76.4 Friends And Related Symbol Documentation	154
	4.76.3 Member Function Documentation	153
	4.76.2 Constructor & Destructor Documentation	152
	4.76.1 Detailed Description	152
4.76	Twist2d Class Reference	151
	4.75.3 Member Function Documentation	151
	4.75.2 Constructor & Destructor Documentation	150
	4.75.1 Detailed Description	150
4.75	TurnToHeadingCommand Class Reference	150
	4.74.3 Member Function Documentation	150
	4.74.2 Constructor & Destructor Documentation	149
	4.74.1 Detailed Description	149
4.74	TurnDegreesCommand Class Reference	149
	4.73.3 Member Function Documentation	147
	4.73.2 Constructor & Destructor Documentation	147
	4.73.1 Detailed Description	
4.73	TrapezoidProfile Class Reference	
	4.72.4 Friends And Related Symbol Documentation	
	4.72.3 Member Function Documentation	141
	4.72.2 Constructor & Destructor Documentation	140
	4.72.1 Detailed Description	140
4.72	Translation2d Class Reference	
	4.71.4 Friends And Related Symbol Documentation	139
	4.71.3 Member Function Documentation	
	4.71.2 Constructor & Destructor Documentation	134

1 Core

This is the host repository for the custom VEX libraries used by the RIT VEXU team

Automatically updated documentation is available at here. There is also a downloadable reference manual.

1.1 Getting Started

If you just want to start a project with Core, make a fork of the Fork Template and follow it's instructions. To setup core for an existing project:

- 1. Create a new vex project (using the VSCode extension or other methods)
- 2. Initialize a git repository for the project
- 3. Execute git subtree add --prefix=core https://github.com/RIT-VEX-U/← Core.git main
- 4. Update the vex Makefile (or any other build system) to know about the core files (core/src for source files, core/include for headers) (See here for an example)
- 5. Enable Eigen (Latest supported version is 3.4.0):
 - mkdir vendor
 - git submodule add https://gitlab.com/libeigen/eigen.git vendor/eigen
 - cd vendor/eigen
 - git checkout 3.4.0
 - Add the following to the makefile to give Core access to the library: INC += -Ivendor/eigen (See here for an example)

If you only wish to use a single version of Core, you can simply clone core/ into your project and add the core source and header files to your makefile.

1.2 Features

Here is the current feature list this repo provides:

Subsystems (See Wiki/Subsystems):

- · Tank drivetrain (user control / autonomous)
- Mecanum drivetrain (user control / autonomous)
- Odometry
 - Tank (Differential)
 - N-Pod
- Flywheel
- Lift
- · Custom encoders

Utilities (See Wiki/Utilites):

- · PID controller
- FeedForward controller
- · Trapezoidal motion profile controller
- Pure Pursuit
- · Generic auto program builder
- · Auto program UI selector
- Mathematical classes (Vector2D, Moving Average)

2 Hierarchical Index

2 Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Async	8
BasicSolenoidSet	10
BasicSpinCommand	11
BasicStopCommand	13
Branch	14
screen::ButtonWidget	14
CommandController	16
Condition	18
FunctionCondition	40
IfTimePassed	44
CustomEncoder	19
DelayCommand	2 1
DriveForwardCommand	22
DriveStopCommand	23
DriveToPointCommand	24
AutoChooser::entry_t	26
Feedback	28
MotionController	58
PID	85
TakeBackHalf	120
FeedForward	30
FeedForward::ff_config_t	32
Filter	33
ExponentialMovingAverage	26
MovingAverage	62
Flywheel	33
FlywheelStopCommand	37
FlywheelStopMotorsCommand	38

FlywheelStopNonTasksCommand	39
FunctionCommand	39
GenericAuto	42
PurePursuit::hermite_point	43
InOrder	44
Lift <t></t>	45
Lift< T >::lift_cfg_t	49
Logger	49
MotionController::m_profile_cfg_t	52
StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage	53
MecanumDrive	54
MecanumDrive::mecanumdrive_config_t	57
motion_t	57
Odometry3Wheel::odometry3wheel_cfg_t	66
OdometryBase	67
Odometry3Wheel	64
OdometrySerial	74
OdometryTank	78
OdomSetPosition	81
screen::Page	82
AutoChooser	9
screen::FunctionPage	40
screen::OdometryPage	72
screen::PIDPage	91
screen::StatsPage	119
Parallel	83
PurePursuit::Path	84
PID::pid_config_t	90
Pose2d	92
PurePursuitCommand	99
Rect	100
robot_specs_t	100

3 Class Index 5

Rotation2d	101
screen::ScreenData	109
Serializer	109
screen::SliderWidget	113
SpinRPMCommand	115
PurePursuit::spline	116
StateMachine < System, IDType, Message, delay_ms, do_log >::State	116
${\bf StateMachine} < {\bf System, IDType, Message, delay_ms, do_log} >$	117
TankDrive	122
tracking_wheel_cfg_t	132
Transform2d	133
Translation2d	139
TrapezoidProfile	146
TurnDegreesCommand	149
TurnToHeadingCommand	150
Twist2d	151
WaitUntilCondition	154
WaitUntilUpToSpeedCommand	155

3 Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Async Async runs a command asynchronously will simply let it go and never look back THIS HAS A VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT	8
AutoChooser	9
BasicSolenoidSet	10
BasicSpinCommand	11
BasicStopCommand	13
Branch Branch chooses from multiple options at runtime. the function decider returns an index into the choices vector If you wish to make no choice and skip this section, return NO_CHOICE; any choice that is out of bounds set to NO_CHOICE	14

Widget that does something when you tap it. The function is only called once when you first tap it	14
CommandController	16
Condition	18
CustomEncoder	19
DelayCommand	21
DriveForwardCommand	22
DriveStopCommand	23
DriveToPointCommand	24
AutoChooser::entry_t	26
Exponential Moving Average	26
Feedback	28
FeedForward	30
FeedForward::ff_config_t	32
Filter	33
Flywheel	33
FlywheelStopCommand	37
FlywheelStopMotorsCommand	38
FlywheelStopNonTasksCommand	39
FunctionCommand	39
FunctionCondition FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime	40
screen::FunctionPage Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything	40
GenericAuto	42
PurePursuit::hermite_point	43
IfTimePassed IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time_s	44
InOrder InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?	44
Lift< T >	45

3.1 Class List 7

Lift< T >::lift_cfg_t	49
Logger Class to simplify writing to files	49
MotionController::m_profile_cfg_t	52
StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage MaybeMessage a message of Message type or nothing MaybeMessage m = {}; // empty MaybeMessage m = Message::EnumField1	53
MecanumDrive	54
MecanumDrive::mecanumdrive_config_t	57
motion_t	57
MotionController	58
MovingAverage	62
Odometry3Wheel	64
Odometry3Wheel::odometry3wheel_cfg_t	66
OdometryBase	67
screen::OdometryPage Page that shows odometry position and rotation and a map (if an sd card with the file is on)	72
OdometrySerial	74
OdometryTank	78
OdomSetPosition	81
screen::Page Page describes one part of the screen slideshow	82
Parallel Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on_timeout on all children continue	83
PurePursuit::Path	84
PID	85
PID::pid_config_t	90
screen::PIDPage PIDPage provides a way to tune a pid controller on the screen	91
Pose2d	92
PurePursuitCommand	99
Rect	100
robot_specs_t	100
Rotation2d	101

screen::ScreenData	
Holds the data that will be passed to the screen thread you probably shouldnt have to use it	109
Serializer	
Serializes Arbitrary data to a file on the SD Card	109
screen::SliderWidget	
Widget that updates a double value. Updates by reference so watch out for race conditions cuz	
the screen stuff lives on another thread	113
SpinRPMCommand	115
PurePursuit::spline	116
StateMachine < System, IDType, Message, delay_ms, do_log >::State	116
StateMachine< System, IDType, Message, delay_ms, do_log >	
State Machine :)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024	
Over Under game for our overly complex intake-cata subsystem (see there for an example)	
The statemachine runs in a background thread and a user thread can interact with it through	
current_state and send_message	117
screen::StatsPage	
Draws motor stats and battery stats to the screen	119
TakeBackHalf	
A velocity controller	120
TankDrive	122
tracking_wheel_cfg_t	132
Transform2d	133
Translation2d	139
TrapezoidProfile	146
TurnDegreesCommand	149
TurnToHeadingCommand	150
Twist2d	151
WaitUntilCondition	
Waits until the condition is true	154
WaitUntilUpToSpeedCommand	155

4 Class Documentation

4.1 Async Class Reference

Async runs a command asynchronously will simply let it go and never look back THIS HAS A VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT.

#include <auto_command.h>

4.1.1 Detailed Description

Async runs a command asynchronously will simply let it go and never look back THIS HAS A VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT.


The documentation for this class was generated from the following files:

- auto_command.h
- · auto_command.cpp

4.2 AutoChooser Class Reference

```
#include <auto_chooser.h>
```

Inheritance diagram for AutoChooser:



Classes

struct entry_t

Public Member Functions

- AutoChooser (std::vector< std::string > paths, size t def=0)
- size_t get_choice ()

Protected Attributes

- size_t choice
- std::vector< entry_t > list

4.2.1 Detailed Description

Autochooser is a utility to make selecting robot autonomous programs easier source: RIT VexU Wiki During a season, we usually code between 4 and 6 autonomous programs. Most teams will change their entire robot program as a way of choosing autonomi but this may cause issues if you have an emergency patch to upload during a competition. This class was built as a way of using the robot screen to list autonomous programs, and the touchscreen to select them.

4.2.2 Constructor & Destructor Documentation

AutoChooser()

```
AutoChooser::AutoChooser (
          std::vector< std::string > paths,
          size_t def = 0)
```

Initialize the auto-chooser. This class places a choice menu on the brain screen, so the driver can choose which autonomous to run.

brain the brain on which to draw the selection boxes

4.2.3 Member Function Documentation

get_choice()

```
size_t AutoChooser::get_choice ()
```

Get the currently selected auto choice

Returns

the identifier to the auto path

Return the selected autonomous

4.2.4 Member Data Documentation

choice

```
size_t AutoChooser::choice [protected]
```

the current choice of auto

list

```
std::vector<entry_t> AutoChooser::list [protected]
```

< a list of all possible auto choices

The documentation for this class was generated from the following files:

- auto_chooser.h
- · auto_chooser.cpp

4.3 BasicSolenoidSet Class Reference

```
#include <basic_command.h>
```

Public Member Functions

BasicSolenoidSet (vex::pneumatics &solenoid, bool setting)

Construct a new BasicSolenoidSet Command.

· bool run () override

Runs the BasicSolenoidSet Overrides run command from AutoCommand.

4.3.1 Detailed Description

AutoCommand wrapper class for BasicSolenoidSet Using the Vex hardware functions

4.3.2 Constructor & Destructor Documentation

BasicSolenoidSet()

Construct a new BasicSolenoidSet Command.

Parameters

solenoid	Solenoid being set
setting	Setting of the solenoid in boolean (true,false)

4.3.3 Member Function Documentation

run()

```
bool BasicSolenoidSet::run () [override]
```

Runs the BasicSolenoidSet Overrides run command from AutoCommand.

Returns

True Command runs once

The documentation for this class was generated from the following files:

- · basic command.h
- · basic_command.cpp

4.4 BasicSpinCommand Class Reference

```
#include <basic_command.h>
```

Public Member Functions

 BasicSpinCommand (vex::motor &motor, vex::directionType dir, BasicSpinCommand::type setting, double power)

Construct a new BasicSpinCommand.

• bool run () override

Runs the BasicSpinCommand Overrides run from Auto Command.

4.4.1 Detailed Description

AutoCommand wrapper class for BasicSpinCommand using the vex hardware functions

4.4.2 Constructor & Destructor Documentation

BasicSpinCommand()

```
BasicSpinCommand::BasicSpinCommand (
    vex::motor & motor,
    vex::directionType dir,
    BasicSpinCommand::type setting,
    double power)
```

Construct a new BasicSpinCommand.

a BasicMotorSpin Command

Parameters

motor	Motor to spin
direc	Direction of motor spin
setting	Power setting in volts,percentage,velocity
power	Value of desired power
motor	Motor port to spin
dir	Direction for spining
setting	Power setting in volts,percentage,velocity
power	Value of desired power

4.4.3 Member Function Documentation

run()

```
bool BasicSpinCommand::run () [override]
```

Runs the BasicSpinCommand Overrides run from Auto Command.

Run the BasicSpinCommand Overrides run from Auto Command.

Returns

True Async running command

True Command runs once

The documentation for this class was generated from the following files:

- basic_command.h
- basic_command.cpp

4.5 BasicStopCommand Class Reference

```
#include <basic_command.h>
```

Public Member Functions

BasicStopCommand (vex::motor &motor, vex::brakeType setting)

Construct a new BasicMotorStop Command.

• bool run () override

Runs the BasicMotorStop Command Overrides run command from AutoCommand.

4.5.1 Detailed Description

AutoCommand wrapper class for BasicStopCommand Using the Vex hardware functions

4.5.2 Constructor & Destructor Documentation

BasicStopCommand()

Construct a new BasicMotorStop Command.

Construct a BasicMotorStop Command.

Parameters

motor	The motor to stop
setting	The brake setting for the motor
motor	Motor to stop
setting	Braketype setting brake,coast,hold

4.5.3 Member Function Documentation

run()

```
bool BasicStopCommand::run () [override]
```

Runs the BasicMotorStop Command Overrides run command from AutoCommand.

Runs the BasicMotorStop command Ovverides run command from AutoCommand.

Returns

True Command runs once

The documentation for this class was generated from the following files:

- basic_command.h
- basic_command.cpp

4.6 Branch Class Reference

Branch chooses from multiple options at runtime. the function decider returns an index into the choices vector If you wish to make no choice and skip this section, return NO_CHOICE; any choice that is out of bounds set to NO CHOICE.

```
#include <auto command.h>
```

4.6.1 Detailed Description

Branch chooses from multiple options at runtime. the function decider returns an index into the choices vector If you wish to make no choice and skip this section, return NO_CHOICE; any choice that is out of bounds set to NO CHOICE.

The documentation for this class was generated from the following files:

- auto_command.h
- · auto_command.cpp

4.7 screen::ButtonWidget Class Reference

Widget that does something when you tap it. The function is only called once when you first tap it.

```
#include <screen.h>
```

Public Member Functions

- ButtonWidget (std::function < void(void) > onpress, Rect rect, std::string name)
 Create a Button widget.
- ButtonWidget (void(*onpress)(), Rect rect, std::string name)

Create a Button widget.

• bool update (bool was pressed, int x, int y)

responds to user input

• void **draw** (vex::brain::lcd &, bool first_draw, unsigned int frame_number)

draws the button to the screen

4.7.1 Detailed Description

Widget that does something when you tap it. The function is only called once when you first tap it.

4.7.2 Constructor & Destructor Documentation

ButtonWidget() [1/2]

Create a Button widget.

onpress	the function to be called when the button is tapped
rect	the area the button should take up on the screen
name	the label put on the button

ButtonWidget() [2/2]

Create a Button widget.

Parameters

onpress	the function to be called when the button is tapped
rect	the area the button should take up on the screen
name	the label put on the button

4.7.3 Member Function Documentation

update()

```
bool screen::ButtonWidget::update (
          bool was_pressed,
          int x,
          int y)
```

responds to user input

Parameters

was_pressed	if the screen is pressed
X	x position if the screen was pressed
У	y position if the screen was pressed

Returns

true if the button was pressed

The documentation for this class was generated from the following files:

- screen.h
- screen.cpp

4.8 CommandController Class Reference

```
#include <command_controller.h>
```

Public Member Functions

• CommandController ()

Create an empty CommandController. Add Command with CommandController::add()

CommandController (std::initializer list< AutoCommand * > cmds)

Create a CommandController with commands pre added. More can be added with CommandController::add()

- void add (std::vector< AutoCommand * > cmds)
- void add (AutoCommand *cmd, double timeout_seconds=10.0)
- void add (std::vector< AutoCommand * > cmds, double timeout_sec)
- void add delay (int ms)
- void add_cancel_func (std::function< bool(void)> true_if_cancel)

add_cancel_func specifies that when this func evaluates to true, to cancel the command controller

- void run ()
- bool last_command_timed_out ()

4.8.1 Detailed Description

File: command_controller.h Desc: A CommandController manages the AutoCommands that make up an autonomous route. The AutoCommands are kept in a queue and get executed and removed from the queue in FIFO order.

4.8.2 Constructor & Destructor Documentation

CommandController()

Create a CommandController with commands pre added. More can be added with CommandController::add()

Parameters

cmds

4.8.3 Member Function Documentation

add() [1/3]

File: command_controller.cpp Desc: A CommandController manages the AutoCommands that make up an autonomous route. The AutoCommands are kept in a queue and get executed and removed from the queue in FIFO order. Adds a command to the queue

cmd	the AutoCommand we want to add to our list
timeout_seconds	the number of seconds we will let the command run for. If it exceeds this, we cancel it and
	run on_timeout

add() [2/3]

```
void CommandController::add ( {\tt std::vector} < {\tt AutoCommand} \ * \ > \ cmds)
```

Adds a command to the queue

Parameters

cmd	the AutoCommand we want to add to our list
timeout_seconds	the number of seconds we will let the command run for. If it exceeds this, we cancel it and
	run on_timeout. if it is <= 0 no time out will be applied

Add multiple commands to the queue. No timeout here.

Parameters

cmds	the AutoCommands we want to add to our list
------	---

add() [3/3]

```
void CommandController::add (
    std::vector< AutoCommand * > cmds,
    double timeout_sec)
```

Add multiple commands to the queue. No timeout here.

Parameters

cmds	the AutoCommands we want to add to our list Add multiple commands to the queue. No timeout
	here.
cmds	the AutoCommands we want to add to our list
timeout_sec	timeout in seconds to apply to all commands if they are still the default

Add multiple commands to the queue. No timeout here.

Parameters

cmds	the AutoCommands we want to add to our list
timeout	timeout in seconds to apply to all commands if they are still the default

add_cancel_func()

```
\label{lem:commandController::add_cancel_func (std::function< bool(void)> true\_if\_cancel)} \\
```

add_cancel_func specifies that when this func evaluates to true, to cancel the command controller

true_if_cancel	a function that returns true when we want to cancel the command controller
----------------	--

add_delay()

Adds a command that will delay progression of the queue

Parameters

ms - number of milliseconds to wait before continuing execution of autonomous

last_command_timed_out()

```
bool CommandController::last_command_timed_out ()
```

last_command_timed_out tells how the last command ended Use this if you want to make decisions based on the end of the last command

Returns

true if the last command timed out. false if it finished regularly

run()

```
void CommandController::run ()
```

Begin execution of the queue Execute and remove commands in FIFO order


The documentation for this class was generated from the following files:

- · command_controller.h
- command_controller.cpp

4.9 Condition Class Reference

```
#include <auto_command.h>
```

Inheritance diagram for Condition:



4.9.1 Detailed Description

File: auto_command.h Desc: Interface for module-specifc commands A Condition is a function that returns true or false is_even is a predicate that would return true if a number is even For our purposes, a Condition is a choice to be made at runtime drive_sys.reached_point(10, 30) is a predicate time.has_elapsed(10, vex::seconds) is a predicate extend this class for different choices you wish to make

The documentation for this class was generated from the following files:

- · auto command.h
- · auto_command.cpp

4.10 CustomEncoder Class Reference

```
#include <custom_encoder.h>
```

Public Member Functions

- CustomEncoder (vex::triport::port &port, double ticks per rev)
- void setRotation (double val, vex::rotationUnits units)
- void setPosition (double val, vex::rotationUnits units)
- double rotation (vex::rotationUnits units)
- double position (vex::rotationUnits units)
- double velocity (vex::velocityUnits units)

4.10.1 Detailed Description

A wrapper class for the vex encoder that allows the use of 3rd party encoders with different tick-per-revolution values.

4.10.2 Constructor & Destructor Documentation

CustomEncoder()

Construct an encoder with a custom number of ticks

Parameters

port	the triport port on the brain the encoder is plugged into
ticks_per_rev	the number of ticks the encoder will report for one revolution

4.10.3 Member Function Documentation

position()

get the position that the encoder is at

units	the unit we want the return value to be in
-------	--

Returns

the position of the encoder in the units specified

rotation()

get the rotation that the encoder is at

Parameters

ı	units	the unit we want the return value to be in
---	-------	--

Returns

the rotation of the encoder in the units specified

setPosition()

sets the stored position of the encoder. Any further movements will be from this value

Parameters

val	the numerical value of the position we are setting to
units	the unit of val

setRotation()

sets the stored rotation of the encoder. Any further movements will be from this value

Parameters

val	the numerical value of the angle we are setting to
units	the unit of val

velocity()

get the velocity that the encoder is moving at

units the unit we want the return value to be in

Returns

the velocity of the encoder in the units specified

The documentation for this class was generated from the following files:

- · custom_encoder.h
- custom_encoder.cpp

4.11 DelayCommand Class Reference

```
#include <delay_command.h>
```

Public Member Functions

- DelayCommand (int ms)
- bool run () override

4.11.1 Detailed Description

File: delay_command.h Desc: A DelayCommand will make the robot wait the set amount of milliseconds before continuing execution of the autonomous route

4.11.2 Constructor & Destructor Documentation

DelayCommand()

Construct a delay command

Parameters

ms the number of milliseconds to delay for

4.11.3 Member Function Documentation

run()

```
bool DelayCommand::run () [inline], [override]
```

Delays for the amount of milliseconds stored in the command Overrides run from AutoCommand

Returns

true when complete

The documentation for this class was generated from the following file:

· delay_command.h

4.12 DriveForwardCommand Class Reference

```
#include <drive commands.h>
```

Public Member Functions

- DriveForwardCommand (TankDrive &drive_sys, Feedback &feedback, double inches, directionType dir, double max_speed=1, double end_speed=0)
- bool run () override
- · void on_timeout () override

4.12.1 Detailed Description

AutoCommand wrapper class for the drive_forward function in the TankDrive class

4.12.2 Constructor & Destructor Documentation

DriveForwardCommand()

File: drive_commands.h Desc: Holds all the AutoCommand subclasses that wrap (currently) TankDrive functions

Currently includes:

- drive_forward
- turn_degrees
- · drive to point
- · turn_to_heading
- stop

Also holds AutoCommand subclasses that wrap OdometryBase functions

Currently includes:

set_position Construct a DriveForward Command

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the drive
inches	how far forward to drive
dir	the direction to drive
max_speed	0 -> 1 percentage of the drive systems speed to drive at

4.12.3 Member Function Documentation

on_timeout()

```
void DriveForwardCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we timeout

run()

```
bool DriveForwardCommand::run () [override]
```

Run drive_forward Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive commands.h
- drive_commands.cpp

4.13 DriveStopCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- DriveStopCommand (TankDrive &drive_sys)
- bool run () override

4.13.1 Detailed Description

AutoCommand wrapper class for the stop() function in the TankDrive class

4.13.2 Constructor & Destructor Documentation

DriveStopCommand()

Construct a DriveStop Command

drive_sys	the drive system we are commanding
-----------	------------------------------------

4.13.3 Member Function Documentation

run()

```
bool DriveStopCommand::run () [override]
```

Stop the drive system Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

Stop the drive train Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive_commands.h
- · drive_commands.cpp

4.14 DriveToPointCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- DriveToPointCommand (TankDrive &drive_sys, Feedback &feedback, double x, double y, directionType dir, double max_speed=1, double end_speed=0)
- DriveToPointCommand (TankDrive &drive_sys, Feedback &feedback, Translation2d translation, directionType dir, double max_speed=1, double end_speed=0)
- bool run () override

4.14.1 Detailed Description

AutoCommand wrapper class for the drive_to_point function in the TankDrive class

4.14.2 Constructor & Destructor Documentation

DriveToPointCommand() [1/2]

Construct a DriveForward Command

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the drive
X	where to drive in the x dimension
У	where to drive in the y dimension
dir	the direction to drive
max_speed	0 -> 1 percentage of the drive systems speed to drive at

DriveToPointCommand() [2/2]

Construct a DriveForward Command

Parameters

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the drive
translation	the point to drive to
dir	the direction to drive
max_speed	0 -> 1 percentage of the drive systems speed to drive at

4.14.3 Member Function Documentation

run()

```
bool DriveToPointCommand::run () [override]
```

Run drive_to_point Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- drive_commands.h
- · drive_commands.cpp

4.15 AutoChooser::entry_t Struct Reference

#include <auto_chooser.h>

Public Attributes

• std::string name

4.15.1 Detailed Description

entry_t is a datatype used to store information that the chooser knows about an auto selection button

4.15.2 Member Data Documentation

name

```
std::string AutoChooser::entry_t::name
```

name of the auto repretsented by the block

The documentation for this struct was generated from the following file:

· auto_chooser.h

4.16 Exponential Moving Average Class Reference

```
#include <moving_average.h>
```

 $Inheritance\ diagram\ for\ Exponential Moving Average:$



Public Member Functions

- ExponentialMovingAverage (int buffer_size)
- ExponentialMovingAverage (int buffer_size, double starting_value)
- · void add_entry (double n) override
- double get_value () const override
- int get_size ()

4.16.1 Detailed Description

ExponentialMovingAverage

An exponential moving average is a way of smoothing out noisy data. For many sensor readings, the noise is roughly symmetric around the actual value. This means that if you collect enough samples those that are too high are cancelled out by the samples that are too low leaving the real value.

A simple mobing average lags significantly with time as it has to counteract old samples. An exponential moving average keeps more up to date by weighting newer readings higher than older readings so it is more up to date while also still smoothed.

The ExponentialMovingAverage class provides an simple interface to do this smoothing from our noisy sensor values.

4.16.2 Constructor & Destructor Documentation

ExponentialMovingAverage() [1/2]

Create a moving average calculator with 0 as the default value

Parameters

buffer_size	The size of the buffer. The number of samples that constitute a valid reading
-------------	---

ExponentialMovingAverage() [2/2]

Create a moving average calculator with a specified default value

Parameters

buffer_size	The size of the buffer. The number of samples that constitute a valid reading
starting_value	The value that the average will be before any data is added

4.16.3 Member Function Documentation

add_entry()

Add a reading to the buffer Before: [1 1 2 2 3 3] => 2 $^{\land}$ After: [2 1 2 2 3 3] => 2.16 $^{\land}$

n the sample that will be added to the moving average.

Implements Filter.

get_size()

```
int ExponentialMovingAverage::get_size ()
```

How many samples the average is made from

Returns

the number of samples used to calculate this average

get_value()

```
double ExponentialMovingAverage::get_value () const [override], [virtual]
```

Returns the average based off of all the samples collected so far

Returns

the calculated average. sum(samples)/numsamples

How many samples the average is made from

Returns

the number of samples used to calculate this average

Implements Filter.


The documentation for this class was generated from the following files:

- · moving_average.h
- · moving_average.cpp

4.17 Feedback Class Reference

```
#include <feedback_base.h>
```

Inheritance diagram for Feedback:



Public Member Functions

- virtual void init (double start_pt, double set_pt)=0
- virtual double update (double val)=0
- virtual double get ()=0
- virtual void set_limits (double lower, double upper)=0
- virtual bool is_on_target ()=0

4.17.1 Detailed Description

Interface so that subsystems can easily switch between feedback loops

Author

Ryan McGee

Date

9/25/2022

4.17.2 Member Function Documentation

get()

```
virtual double Feedback::get () [pure virtual]
```

Returns

the last saved result from the feedback controller

Implemented in MotionController, PID, and TakeBackHalf.

init()

Initialize the feedback controller for a movement

Parameters

	start_pt	the current sensor value		
	set_pt	where the sensor value should be		
	start_vel	Movement starting velocity		
	end_vel	Movement ending velocity		

Implemented in MotionController, PID, and TakeBackHalf.

is_on_target()

```
virtual bool Feedback::is_on_target () [pure virtual]
```

Returns

true if the feedback controller has reached it's setpoint

Implemented in MotionController, PID, and TakeBackHalf.

set_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

Parameters

lower	Upper limit
upper	Lower limit

Implemented in MotionController, PID, and TakeBackHalf.

update()

Iterate the feedback loop once with an updated sensor value

Parameters

val value from th	ne sensor
-------------------	-----------

Returns

feedback loop result

Implemented in MotionController, PID, and TakeBackHalf.

The documentation for this class was generated from the following file:

· feedback_base.h

4.18 FeedForward Class Reference

#include <feedforward.h>

Classes

· struct ff_config_t

Public Member Functions

- FeedForward (ff_config_t &cfg)
- double calculate (double v, double a, double pid ref=0.0)

Perform the feedforward calculation.

4.18.1 Detailed Description

FeedForward

Stores the feedfoward constants, and allows for quick computation. Feedfoward should be used in systems that require smooth precise movements and have high inertia, such as drivetrains and lifts.

This is best used alongside a PID loop, with the form: output = pid.get() + feedforward.calculate(v, a);

In this case, the feedforward does the majority of the heavy lifting, and the pid loop only corrects for inconsistencies

For information about tuning feedforward, I reccommend looking at this post: $https://www. \leftarrow chiefdelphi.com/t/paper-frc-drivetrain-characterization/160915$ (yes I know it's for FRC but trust me, it's useful)

Author

Ryan McGee

Date

6/13/2022

4.18.2 Constructor & Destructor Documentation

FeedForward()

Creates a FeedForward object.

Parameters

```
cfg | Configuration Struct for tuning
```

4.18.3 Member Function Documentation

calculate()

Perform the feedforward calculation.

This calculation is the equation: F = kG + kS*sgn(v) + kV*v + kA*a

ι	/	Requested velocity of system
ć	3	Requested acceleration of system

Returns

A feedforward that should closely represent the system if tuned correctly

The documentation for this class was generated from the following file:

· feedforward.h

4.19 FeedForward::ff_config_t Struct Reference

#include <feedforward.h>

Public Attributes

- double kS
- double kV
- double kA
- double kG

4.19.1 Detailed Description

ff_config_t holds the parameters to make the theoretical model of a real world system equation is of the form kS if the system is not stopped, 0 otherwise

- kV * desired velocity
- · kA * desired acceleration
- kG

4.19.2 Member Data Documentation

kΑ

```
double FeedForward::ff_config_t::kA
```

kA - Acceleration coefficient: the power required to change the mechanism's speed. Multiplied by the requested acceleration.

kG

```
double FeedForward::ff_config_t::kG
```

kG - Gravity coefficient: only needed for lifts. The power required to overcome gravity and stay at steady state.

kS

```
double FeedForward::ff_config_t::kS
```

Coefficient to overcome static friction: the point at which the motor *starts* to move.

k۷

```
double FeedForward::ff_config_t::kV
```

Veclocity coefficient: the power required to keep the mechanism in motion. Multiplied by the requested velocity.

The documentation for this struct was generated from the following file:

· feedforward.h

4.20 Filter Class Reference

```
#include <moving_average.h>
```

Inheritance diagram for Filter:



4.20.1 Detailed Description

Interface for filters Use add_entry to supply data and get_value to retrieve the filtered value

The documentation for this class was generated from the following file:

· moving_average.h

4.21 Flywheel Class Reference

#include <flywheel.h>

Public Member Functions

- Flywheel (vex::motor_group &motors, Feedback &feedback, FeedForward &helper, const double ratio, Filter &filt)
- double get_target () const
- double getRPM () const
- vex::motor group & get motors () const
- void spin_manual (double speed, directionType dir=fwd)
- void spin_rpm (double rpm)
- void stop ()
- bool is_on_target ()

check if the feedback controller thinks the flywheel is on target

• screen::Page * Page () const

Creates a page displaying info about the flywheel.

AutoCommand * SpinRpmCmd (int rpm)

Creates a new auto command to spin the flywheel at the desired velocity.

AutoCommand * WaitUntilUpToSpeedCmd ()

Creates a new auto command that will hold until the flywheel has its target as defined by its feedback controller.

Friends

int spinRPMTask (void *wheelPointer)

4.21.1 Detailed Description

a Flywheel class that handles all control of a high inertia spinning disk It gives multiple options for what control system to use in order to control wheel velocity and functions alerting the user when the flywheel is up to speed. Flywheel is a set and forget class. Once you create it you can call spin_rpm or stop on it at any time and it will take all necessary steps to accomplish this

4.21.2 Constructor & Destructor Documentation

Flywheel()

Create the Flywheel object using PID + feedforward for control.

Parameters

motors	pointer to the motors on the fly wheel
feedback	a feedback controleller
helper	a feedforward config (only kV is used) to help the feedback controller along
ratio	ratio of the gears from the motor to the flywheel just multiplies the velocity
filter	the filter to use to smooth noisy motor readings

4.21.3 Member Function Documentation

```
get_motors()
```

```
motor_group & Flywheel::get_motors () const
```

Returns the motors

Returns

the motors used to run the flywheel

get_target()

```
double Flywheel::get_target () const
```

Return the target_rpm that the flywheel is currently trying to achieve

Returns

target_rpm the target rpm

Return the current value that the target_rpm should be set to

getRPM()

```
double Flywheel::getRPM () const
```

return the velocity of the flywheel

is_on_target()

```
bool Flywheel::is_on_target () [inline]
```

check if the feedback controller thinks the flywheel is on target

Returns

true if on target

Page()

```
screen::Page * Flywheel::Page () const
```

Creates a page displaying info about the flywheel.

Returns

the page should be used for `screen::start_screen(screen, {fw.Page()});

spin_manual()

Spin motors using voltage; defaults forward at 12 volts FOR USE BY OPCONTROL AND AUTONOMOUS - this only applies if the target_rpm thread is not running

speed	- speed (between -1 and 1) to set the motor
dir	- direction that the motor moves in; defaults to forward

Spin motors using voltage; defaults forward at 12 volts FOR USE BY OPCONTROL AND AUTONOMOUS - this only applies if the RPM thread is not running

Parameters

speed	- speed (between -1 and 1) to set the motor
dir	- direction that the motor moves in; defaults to forward

spin_rpm()

starts or sets the target_rpm thread at new value what control scheme is dependent on control_style

Parameters

	rpm	- the target_rpm we want to spin at	
--	-----	-------------------------------------	--

starts or sets the RPM thread at new value what control scheme is dependent on control_style

Parameters

```
input_rpm - set the current RPM
```

SpinRpmCmd()

Creates a new auto command to spin the flywheel at the desired velocity.

Parameters

rpm	the rpm to spin at

Returns

an auto command to add to a command controller

stop()

```
void Flywheel::stop ()
```

Stops the motors. If manually spinning, this will do nothing just call spin_mainual(0.0) to send 0 volts stop the RPM thread and the wheel

WaitUntilUpToSpeedCmd()

```
AutoCommand * Flywheel::WaitUntilUpToSpeedCmd () [inline]
```

Creates a new auto command that will hold until the flywheel has its target as defined by its feedback controller.

Returns

an auto command to add to a command controller

4.21.4 Friends And Related Symbol Documentation

spinRPMTask

Runs a thread that keeps track of updating flywheel RPM and controlling it accordingly

The documentation for this class was generated from the following files:

- flywheel.h
- · flywheel.cpp

4.22 FlywheelStopCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- FlywheelStopCommand (Flywheel &flywheel)
- · bool run () override

4.22.1 Detailed Description

AutoCommand wrapper class for the stop function in the Flywheel class

4.22.2 Constructor & Destructor Documentation

FlywheelStopCommand()

```
\label{limits} FlywheelStopCommand:: FlywheelStopCommand ( \\ Flywheel \& flywheel)
```

Construct a FlywheelStopCommand

flywheel	the flywheel system we are commanding
----------	---------------------------------------

4.22.3 Member Function Documentation

run()

```
bool FlywheelStopCommand::run () [override]
```

Run stop Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- flywheel_commands.h
- flywheel_commands.cpp

4.23 FlywheelStopMotorsCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- FlywheelStopMotorsCommand (Flywheel &flywheel)
- bool run () override

4.23.1 Detailed Description

AutoCommand wrapper class for the stopMotors function in the Flywheel class

4.23.2 Constructor & Destructor Documentation

FlywheelStopMotorsCommand()

```
\label{lem:flywheelStopMotorsCommand::FlywheelStopMotorsCommand (} Flywheel & flywheel)
```

Construct a FlywheeStopMotors Command

flywheel the flywheel system we are commanding

4.23.3 Member Function Documentation

run()

bool FlywheelStopMotorsCommand::run () [override]

Run stop Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · flywheel commands.h
- flywheel_commands.cpp

4.24 FlywheelStopNonTasksCommand Class Reference

#include <flywheel_commands.h>

4.24.1 Detailed Description

AutoCommand wrapper class for the stopNonTasks function in the Flywheel class

The documentation for this class was generated from the following files:

- · flywheel_commands.h
- flywheel_commands.cpp

4.25 FunctionCommand Class Reference

#include <auto_command.h>

4.25.1 Detailed Description

FunctionCommand is fun and good way to do simple things Printing, launching nukes, and other quick and dirty one time things

The documentation for this class was generated from the following file:


· auto_command.h

4.26 FunctionCondition Class Reference

FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime.

```
#include <auto_command.h>
```

Inheritance diagram for FunctionCondition:



4.26.1 Detailed Description

FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime.

The documentation for this class was generated from the following files:

- · auto command.h
- · auto_command.cpp

4.27 screen::FunctionPage Class Reference

Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything.

```
#include <screen.h>
```

Inheritance diagram for screen::FunctionPage:



Public Member Functions

- FunctionPage (update_func_t update_f, draw_func_t draw_t)
 Creates a function page.
- void update (bool was_pressed, int x, int y) override
 update uses the supplied update function to update this page
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

draw uses the supplied draw function to draw to the screen

4.27.1 Detailed Description

Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything.

4.27.2 Constructor & Destructor Documentation

FunctionPage()

Creates a function page.

FunctionPage.

Parameters

update⊷	the function called every tick to respond to user input or do data collection
_f	
draw_t	the function called to draw to the screen
update⇔	drawing function
_f	
draw_f	drawing function

4.27.3 Member Function Documentation

draw()

draw uses the supplied draw function to draw to the screen

See also

Page::draw

Reimplemented from screen::Page.

update()

update uses the supplied update function to update this page

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:

- · screen.h
- · screen.cpp

4.28 GenericAuto Class Reference

```
#include <generic_auto.h>
```

Public Member Functions

- bool run (bool blocking)
- void add (state ptr new state)
- void add_async (state_ptr async_state)
- void add_delay (int ms)

4.28.1 Detailed Description

GenericAuto provides a pleasant interface for organizing an auto path steps of the path can be added with add() and when ready, calling run() will begin executing the path

4.28.2 Member Function Documentation

add()

Add a new state to the autonomous via function point of type "bool (ptr*)()"

Parameters

```
new_state the function to run
```

add async()

Add a new state to the autonomous via function point of type "bool (ptr*)()" that will run asynchronously

add_delay()

```
void GenericAuto::add_delay (
          int ms)
```

add_delay adds a period where the auto system will simply wait for the specified time

Parameters

ms	how long to wait in milliseconds
----	----------------------------------

run()

```
bool GenericAuto::run (
          bool blocking)
```

The method that runs the autonomous. If 'blocking' is true, then this method will run through every state until it finished.

If blocking is false, then assuming every state is also non-blocking, the method will run through the current state in the list and return immediately.

Parameters

blocking	Whether or not to block the thread until all states have run
----------	--

Returns

true after all states have finished.

The documentation for this class was generated from the following files:

- · generic_auto.h
- · generic_auto.cpp

4.29 PurePursuit::hermite_point Struct Reference

```
#include <pure_pursuit.h>
```

4.29.1 Detailed Description

a position along the hermite path contains a position and orientation information that the robot would be at at this point

The documentation for this struct was generated from the following file:

· pure pursuit.h

4.30 IfTimePassed Class Reference

IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time_s.

```
#include <auto_command.h>
```

Inheritance diagram for IfTimePassed:



4.30.1 Detailed Description

IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time s.

The documentation for this class was generated from the following files:

- · auto command.h
- · auto_command.cpp

4.31 InOrder Class Reference

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

```
#include <auto_command.h>
```

4.31.1 Detailed Description

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

The documentation for this class was generated from the following files:

- auto_command.h
- · auto_command.cpp

4.32 Lift< T > Class Template Reference

```
#include <lift.h>
```

Classes

· struct lift_cfg_t

Public Member Functions

- Lift (motor_group &lift_motors, lift_cfg_t &lift_cfg, map< T, double > &setpoint_map, limit *homing_← switch=NULL)
- void control_continuous (bool up_ctrl, bool down_ctrl)
- void control_manual (bool up_btn, bool down_btn, int volt_up, int volt_down)
- void control setpoints (bool up step, bool down step, vector< T > pos list)
- bool set position (T pos)
- bool set_setpoint (double val)
- double get_setpoint ()
- void hold ()
- void home ()
- bool get_async ()
- void set_async (bool val)
- void set_sensor_function (double(*fn_ptr)(void))
- void set_sensor_reset (void(*fn_ptr)(void))

4.32.1 Detailed Description

```
template<typename T> class Lift< T >
```

LIFT A general class for lifts (e.g. 4bar, dr4bar, linear, etc) Uses a PID to hold the lift at a certain height under load, and to move the lift to different heights

Author

Ryan McGee

4.32.2 Constructor & Destructor Documentation

Lift()

Construct the Lift object and begin the background task that controls the lift.

Usage example: /code{.cpp} enum Positions {UP, MID, DOWN}; map<Positions, double> setpt_map { {DOWN, 0.0}, {MID, 0.5}, {UP, 1.0} }; Lift<Positions> my_lift(motors, lift_cfg, setpt_map); /endcode

lift_motors	A set of motors, all set that positive rotation correlates with the lift going up			
lift_cfg	Lift characterization information; PID tunings and movement speeds			
setpoint_map	A map of enum type T, in which each enum entry corresponds to a different lift height			

4.32.3 Member Function Documentation

control_continuous()

Control the lift with an "up" button and a "down" button. Use PID to hold the lift when letting go.

Parameters

up_ctrl	Button controlling the "UP" motion
down_ctrl	Button controlling the "DOWN" motion

control_manual()

Control the lift with manual controls (no holding voltage)

Parameters

up_btn	Raise the lift when true
down_btn	Lower the lift when true
volt_up	Motor voltage when raising the lift
volt_down	Motor voltage when lowering the lift

control_setpoints()

Control the lift in "steps". When the "up" button is pressed, the lift will go to the next position as defined by pos_list. Order matters!

up_step	A button that increments the position of the lift.
down_step	A button that decrements the position of the lift.
pos_list	A list of positions for the lift to go through. The higher the index, the higher the lift should be (generally).

get_async()

```
template<typename T>
bool Lift< T >::get_async () [inline]
```

Returns

whether or not the background thread is running the lift

get_setpoint()

```
template<typename T>
double Lift< T >::get_setpoint () [inline]
```

Returns

The current setpoint for the lift

hold()

```
template<typename T>
void Lift< T >::hold () [inline]
```

Target the class's setpoint. Calculate the PID output and set the lift motors accordingly.

home()

```
template<typename T>
void Lift< T >::home () [inline]
```

A blocking function that automatically homes the lift based on a sensor or hard stop, and sets the position to 0. A watchdog times out after 3 seconds, to avoid damage.

set_async()

Enables or disables the background task. Note that running the control functions, or set_position functions will immediately re-enable the task for autonomous use.

val Whether or not the background thread should run the lift

set_position()

Enable the background task, and send the lift to a position, specified by the setpoint map from the constructor.

Parameters

```
pos A lift position enum type
```

Returns

True if the pid has reached the setpoint

set_sensor_function()

Creates a custom hook for any other type of sensor to be used on the lift. Example: $/code\{.cpp\}$ my_lift.set_ \leftarrow sensor_function([](){return my_sensor.position();}); $/code\{.cpp\}$ my_lift.set_ \leftarrow

Parameters

```
fn_ptr | Pointer to custom sensor function
```

set_sensor_reset()

Creates a custom hook to reset the sensor used in set_sensor_function(). Example: $/code{.cpp}$ my_lift.set_ \leftarrow sensor_reset(my_sensor.resetPosition); $/code{.cpp}$

set_setpoint()

Manually set a setpoint value for the lift PID to go to.

val Lift setpoint, in motor revolutions or sensor units defined by get_sensor. Cannot be outside the softstops.

Returns

True if the pid has reached the setpoint

The documentation for this class was generated from the following file:

• lift.h

4.33 Lift< T >::lift_cfg_t Struct Reference

```
#include <lift.h>
```

4.33.1 Detailed Description

```
template<typename T> struct Lift< T>::lift_cfg_t
```

lift_cfg_t holds the physical parameter specifications of a lify system. includes:

- · maximum speeds for the system
- · softstops to stop the lift from hitting the hard stops too hard

The documentation for this struct was generated from the following file:

• lift.h

4.34 Logger Class Reference

Class to simplify writing to files.

```
#include <logger.h>
```

Public Member Functions

• Logger (const std::string &filename)

Create a logger that will save to a file.

• Logger (const Logger &I)=delete

copying not allowed

• Logger & operator= (const Logger &I)=delete

copying not allowed

void Log (const std::string &s)

Write a string to the log.

void Log (LogLevel level, const std::string &s)

Write a string to the log with a loglevel.

• void LogIn (const std::string &s)

Write a string and newline to the log.

void LogIn (LogLevel level, const std::string &s)

Write a string and a newline to the log with a loglevel.

void Logf (const char *fmt,...)

Write a formatted string to the log.

• void Logf (LogLevel level, const char *fmt,...)

Write a formatted string to the log with a loglevel.

Static Public Attributes

static constexpr int MAX_FORMAT_LEN = 512
 maximum size for a string to be before it's written

4.34.1 Detailed Description

Class to simplify writing to files.

4.34.2 Constructor & Destructor Documentation

Logger()

Create a logger that will save to a file.

Parameters

filename the file to save to

4.34.3 Member Function Documentation

Log() [1/2]

Write a string to the log.

```
s the string to write
```

Log() [2/2]

```
void Logger::Log (
          LogLevel level,
          const std::string & s)
```

Write a string to the log with a loglevel.

Parameters

level	the level to write. DEBUG, NOTICE, WARNING, ERROR, CRITICAL, TIME
s	the string to write

Logf() [1/2]

Write a formatted string to the log.

Parameters

fmt	the format string (like printf)
	the args

Logf() [2/2]

```
void Logger::Logf (
            LogLevel level,
            const char * fmt,
            ...)
```

Write a formatted string to the log with a loglevel.

Parameters

level	the level to write. DEBUG, NOTICE, WARNING, ERROR, CRITICAL, TIME
fmt	the format string (like printf)
	the args

LogIn() [1/2]

Write a string and newline to the log.

```
s the string to write
```

LogIn() [2/2]

Write a string and a newline to the log with a loglevel.

Parameters

lev	el the	level to write	. DEBUG,	NOTICE,	WARNING,	ERROR,	CRITICAL,	TIME
s	the	string to writ	е					

The documentation for this class was generated from the following files:

- · logger.h
- logger.cpp

4.35 MotionController::m_profile_cfg_t Struct Reference

```
#include <motion_controller.h>
```

Public Attributes

• double max_v

the maximum velocity the robot can drive

double accel

the most acceleration the robot can do

• PID::pid_config_t pid_cfg

configuration parameters for the internal PID controller

FeedForward::ff_config_t ff_cfg

configuration parameters for the internal

4.35.1 Detailed Description

m_profile_config holds all data the motion controller uses to plan paths When motion pofile is given a target to drive to, max_v and accel are used to make the trapezoid profile instructing the controller how to drive pid_cfg, ff_cfg are used to find the motor outputs necessary to execute this path

The documentation for this struct was generated from the following file:

· motion_controller.h

4.36 StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage Class Reference

MaybeMessage a message of Message type or nothing MaybeMessage $m = \{\}$; // empty MaybeMessag

```
#include <state_machine.h>
```

Public Member Functions

MaybeMessage ()

Empty message - when theres no message.

MaybeMessage (Message msg)

Create a maybemessage with a message.

• bool has_message ()

check if the message is here

Message message ()

Get the message stored. The return value is invalid unless has_message returned true.

4.36.1 Detailed Description

template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log = false> class StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage

MaybeMessage a message of Message type or nothing MaybeMessage $m = \{\}$; // empty MaybeMessag

4.36.2 Constructor & Destructor Documentation

MaybeMessage()

Create a maybemessage with a message.

Parameters

msg the message to hold on to

4.36.3 Member Function Documentation

has_message()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
bool StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage::has_message ()
[inline]
```

check if the message is here

Returns

true if there is a message

message()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
Message StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage::message ()
[inline]
```

Get the message stored. The return value is invalid unless has message returned true.

Returns

The message if it exists. Undefined otherwise

The documentation for this class was generated from the following file:

state_machine.h

4.37 MecanumDrive Class Reference

```
#include <mecanum_drive.h>
```

Classes

· struct mecanumdrive_config_t

Public Member Functions

- MecanumDrive (vex::motor &left_front, vex::motor &right_front, vex::motor &left_rear, vex::motor &right_rear, vex::rotation *lateral_wheel=NULL, vex::inertial *imu=NULL, mecanumdrive_config_t *config=NULL)
- void drive raw (double direction deg, double magnitude, double rotation)
- void drive (double left_y, double left_x, double right_x, int power=2)
- bool auto drive (double inches, double direction, double speed, bool gyro correction=true)
- bool auto_turn (double degrees, double speed, bool ignore_imu=false)

4.37.1 Detailed Description

A class representing the Mecanum drivetrain. Contains 4 motors, a possible IMU (intertial), and a possible undriven perpendicular wheel.

4.37.2 Constructor & Destructor Documentation

MecanumDrive()

```
MecanumDrive::MecanumDrive (
    vex::motor & left_front,
    vex::motor & right_front,
    vex::motor & left_rear,
    vex::motor & right_rear,
    vex::rotation * lateral_wheel = NULL,
    vex::inertial * imu = NULL,
    mecanumdrive_config_t * config = NULL)
```

Create the Mecanum drivetrain object

4.37.3 Member Function Documentation

auto drive()

Drive the robot in a straight line automatically. If the inertial was declared in the constructor, use it to correct while driving. If the lateral wheel was declared in the constructor, use it for more accurate positioning while strafing.

Parameters

inches	How far the robot should drive, in inches
direction	What direction the robot should travel in, in degrees. 0 is forward, +/-180 is reverse, clockwise is positive.
speed	The maximum speed the robot should travel, in percent: -1.0->+1.0
gyro_correction	=true Whether or not to use the gyro to help correct while driving. Will always be false if no gyro was declared in the constructor.

Drive the robot in a straight line automatically. If the inertial was declared in the constructor, use it to correct while driving. If the lateral wheel was declared in the constructor, use it for more accurate positioning while strafing.

Parameters

inches	How far the robot should drive, in inches
direction	What direction the robot should travel in, in degrees. 0 is forward, +/-180 is reverse, clockwise is positive.
speed	The maximum speed the robot should travel, in percent: -1.0->+1.0
gyro_correction	= true Whether or not to use the gyro to help correct while driving. Will always be false if no gyro was declared in the constructor.

Returns

Whether or not the maneuver is complete.

auto_turn()

Autonomously turn the robot X degrees over it's center point. Uses a closed loop for control.

Parameters

degrees	How many degrees to rotate the robot. Clockwise postive.	
speed	What percentage to run the motors at: 0.0 -> 1.0	
ignore_imu	=false Whether or not to use the Inertial for determining angle. Will instead use circumference	
	formula + robot's wheelbase + encoders to determine.	

Returns

whether or not the robot has finished the maneuver

Autonomously turn the robot X degrees over it's center point. Uses a closed loop for control.

Parameters

degrees	How many degrees to rotate the robot. Clockwise postive.
speed	What percentage to run the motors at: 0.0 -> 1.0
ignore_imu	= false Whether or not to use the Inertial for determining angle. Will instead use circumference
	formula + robot's wheelbase + encoders to determine.

Returns

whether or not the robot has finished the maneuver

drive()

Drive the robot with a mecanum-style / arcade drive. Inputs are in percent (-100.0 -> 100.0) straight from the controller. Controls are mixed, so the robot can drive forward / strafe / rotate all at the same time.

Parameters

left_y	left joystick, Y axis (forward / backwards)
left_x	left joystick, X axis (strafe left / right)
right←	right joystick, X axis (rotation left / right)
_X	
power	=2 how much of a "curve" there should be on drive controls; better for low speed maneuvers. Leave
	blank for a default curve of 2 (higher means more fidelity)

Drive the robot with a mecanum-style / arcade drive. Inputs are in percent (-100.0 -> 100.0) straight from the controller. Controls are mixed, so the robot can drive forward / strafe / rotate all at the same time.

left_y	left joystick, Y axis (forward / backwards)
left_x	left joystick, X axis (strafe left / right)
right←	right joystick, X axis (rotation left / right)
_X	
power	= 2 how much of a "curve" there should be on drive controls; better for low speed maneuvers. Leave
	blank for a default curve of 2 (higher means more fidelity)

drive_raw()

Drive the robot using vectors. This handles all the math required for mecanum control.

Parameters

direction_deg	the direction to drive the robot, in degrees. 0 is forward, 180 is back, clockwise is positive, counterclockwise is negative.
magnitude	How fast the robot should drive, in percent: 0.0->1.0
rotation	How fast the robot should rotate, in percent: -1.0->+1.0

The documentation for this class was generated from the following files:

- · mecanum_drive.h
- · mecanum_drive.cpp

4.38 MecanumDrive::mecanumdrive_config_t Struct Reference

```
#include <mecanum_drive.h>
```

4.38.1 Detailed Description

Configure the Mecanum drive PID tunings and robot configurations

The documentation for this struct was generated from the following file:

· mecanum_drive.h

4.39 motion_t Struct Reference

#include <trapezoid_profile.h>

Public Attributes

· double pos

1d position at this point in time

• double vel

1d velocity at this point in time

double accel

1d acceleration at this point in time

4.39.1 Detailed Description

motion_t is a description of 1 dimensional motion at a point in time.


The documentation for this struct was generated from the following file:

· trapezoid_profile.h

4.40 MotionController Class Reference

```
#include <motion_controller.h>
```

Inheritance diagram for MotionController:



Classes

• struct m_profile_cfg_t

Public Member Functions

• MotionController (m_profile_cfg_t &config)

Construct a new Motion Controller object.

• void init (double start_pt, double end_pt) override

Initialize the motion profile for a new movement This will also reset the PID and profile timers.

• double update (double sensor_val) override

Update the motion profile with a new sensor value.

- · double get () override
- void set_limits (double lower, double upper) override
- bool is_on_target () override
- motion_t get_motion () const

Static Public Member Functions

• static FeedForward::ff_config_t tune_feedforward (TankDrive &drive, OdometryTank &odometry, double pct=0.6, double duration=2)

4.40.1 Detailed Description

Motion Controller class

This class defines a top-level motion profile, which can act as an intermediate between a subsystem class and the motors themselves

This takes the constants kS, kV, kA, kP, kI, kD, max_v and acceleration and wraps around a feedforward, PID and trapezoid profile. It does so with the following formula:

out = feedfoward.calculate(motion_profile.get(time_s)) + pid.get(motion_profile.get(time_s))

For PID and Feedforward specific formulae, see pid.h, feedforward.h, and trapezoid_profile.h

Author

Ryan McGee

Date

7/13/2022

4.40.2 Constructor & Destructor Documentation

MotionController()

Construct a new Motion Controller object.

Parameters

config

The definition of how the robot is able to move max_v Maximum velocity the movement is capable of accel Acceleration / deceleration of the movement pid_cfg Definitions of kP, kI, and kD ff_cfg Definitions of kS, kV, and kA

4.40.3 Member Function Documentation

get()

```
double MotionController::get () [override], [virtual]
```

Returns

the last saved result from the feedback controller

Implements Feedback.

get_motion()

```
motion_t MotionController::get_motion () const
```

Returns

The current postion, velocity and acceleration setpoints

init()

Initialize the motion profile for a new movement This will also reset the PID and profile timers.

Parameters

start⊷	Movement starting position
_pt	
end_pt	Movement ending posiiton

Implements Feedback.

is_on_target()

```
bool MotionController::is_on_target () [override], [virtual]
```

Returns

Whether or not the movement has finished, and the PID confirms it is on target

Implements Feedback.

set_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied. if limits are applied, the controller will not target any value below lower or above upper

Parameters

lower	upper limit
upper	lower limiet

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

lower	Upper limit
upper	Lower limit

Implements Feedback.

tune_feedforward()

This method attempts to characterize the robot's drivetrain and automatically tune the feedforward. It does this by first calculating the kS (voltage to overcome static friction) by slowly increasing the voltage until it moves.

Next is kV (voltage to sustain a certain velocity), where the robot will record it's steady-state velocity at 'pct' speed.

Finally, kA (voltage needed to accelerate by a certain rate), where the robot will record the entire movement's velocity and acceleration, record a plot of [X=(pct-kV*V-kS), Y=(Acceleration)] along the movement, and since kA*Accel = pct-kV*V-kS, the reciprocal of the linear regression is the kA value.

Parameters

drive	The tankdrive to operate on
odometry	The robot's odometry subsystem
pct	Maximum velocity in percent (0->1.0)
duration	Amount of time the robot should be moving for the test

Returns

A tuned feedforward object

update()

Update the motion profile with a new sensor value.

Parameters

sensor_val	Value from the sensor
------------	-----------------------

Returns

the motor input generated from the motion profile

Implements Feedback.

The documentation for this class was generated from the following files:

- · motion_controller.h
- motion_controller.cpp

4.41 MovingAverage Class Reference

```
#include <moving_average.h>
```

Inheritance diagram for MovingAverage:



Public Member Functions

- MovingAverage (int buffer_size)
- MovingAverage (int buffer size, double starting value)
- void add_entry (double n) override
- · double get value () const override
- int get_size () const

4.41.1 Detailed Description

MovingAverage

A moving average is a way of smoothing out noisy data. For many sensor readings, the noise is roughly symmetric around the actual value. This means that if you collect enough samples those that are too high are cancelled out by the samples that are too low leaving the real value.

The MovingAverage class provides a simple interface to do this smoothing from our noisy sensor values.

WARNING: because we need a lot of samples to get the actual value, the value given by the MovingAverage will 'lag' behind the actual value that the sensor is reading. Using a MovingAverage is thus a tradeoff between accuracy and lag time (more samples) vs. less accuracy and faster updating (less samples).

4.41.2 Constructor & Destructor Documentation

MovingAverage() [1/2]

Create a moving average calculator with 0 as the default value

Parameters

buffer_size The size of the buffer. The number of samples that constitute a valid reading

MovingAverage() [2/2]

```
MovingAverage::MovingAverage (
          int buffer_size,
          double starting_value)
```

Create a moving average calculator with a specified default value

buffer_size	The size of the buffer. The number of samples that constitute a valid reading
starting_value	The value that the average will be before any data is added

4.41.3 Member Function Documentation

add_entry()

Add a reading to the buffer Before: [1 1 2 2 3 3] => 2 $^{\wedge}$ After: [2 1 2 2 3 3] => 2.16 $^{\wedge}$

Parameters

n the sample that will be added to the moving average.

Implements Filter.

get_size()

```
int MovingAverage::get_size () const
```

How many samples the average is made from

Returns

the number of samples used to calculate this average

get_value()

```
double MovingAverage::get_value () const [override], [virtual]
```

Returns the average based off of all the samples collected so far

Returns

the calculated average. sum(samples)/numsamples

How many samples the average is made from

Returns

the number of samples used to calculate this average

Implements Filter.


The documentation for this class was generated from the following files:

- · moving_average.h
- moving_average.cpp

4.42 Odometry3Wheel Class Reference

#include <odometry_3wheel.h>

Inheritance diagram for Odometry3Wheel:



Classes

struct odometry3wheel_cfg_t

Public Member Functions

- Odometry3Wheel (CustomEncoder &lside_fwd, CustomEncoder &rside_fwd, CustomEncoder &off_axis, odometry3wheel_cfg_t &cfg, bool is_async=true)
- Pose2d update () override
- void tune (vex::controller &con, TankDrive &drive)

Public Member Functions inherited from OdometryBase

- OdometryBase (bool is_async)
- virtual Pose2d get_position (void)
- virtual void set_position (const Pose2d &newpos=zero_pos)
- void end async ()
- virtual double get_speed ()
- virtual double get_accel ()
- double get_angular_speed_deg ()
- double get_angular_accel_deg ()

Additional Inherited Members

Static Public Member Functions inherited from OdometryBase

- static int background_task (void *ptr)
- static double smallest_angle (double start_deg, double end_deg)

Public Attributes inherited from OdometryBase

• bool end_task = false

end_task is true if we instruct the odometry thread to shut down

- vex::task * handle
- vex::mutex mut
- · Pose2d current pos
- · double speed
- double accel
- double ang_speed_deg
- double ang_accel_deg

4.42.1 Detailed Description

Odometry3Wheel

This class handles the code for a standard 3-pod odometry setup, where there are 3 "pods" made up of undriven (dead) wheels connected to encoders in the following configuration:

Where O is the center of rotation. The robot will monitor the changes in rotation of these wheels and calculate the robot's X, Y and rotation on the field.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

Author

Ryan McGee

Date

Oct 31 2022

4.42.2 Constructor & Destructor Documentation

Odometry3Wheel()

Construct a new Odometry 3 Wheel object

Parameters

lside_fwd	left-side encoder reference
rside_fwd	right-side encoder reference
off_axis	off-axis (perpendicular) encoder reference
cfg	robot odometry configuration
is_async	true to constantly run in the background

4.42.3 Member Function Documentation

tune()

A guided tuning process to automatically find tuning parameters. This method is blocking, and returns when tuning has finished. Follow the instructions on the controller to complete the tuning process

con	Controller reference, for screen and button control
drive	Drivetrain reference for robot control

A guided tuning process to automatically find tuning parameters. This method is blocking, and returns when tuning has finished. Follow the instructions on the controller to complete the tuning process

It is assumed the gear ratio and encoder PPR have been set correctly

update()

```
Pose2d Odometry3Wheel::update () [override], [virtual]
```

Update the current position of the robot once, using the current state of the encoders and the previous known location

Returns

the robot's updated position

Implements OdometryBase.

The documentation for this class was generated from the following files:

- · odometry_3wheel.h
- · odometry_3wheel.cpp

4.43 Odometry3Wheel::odometry3wheel cfg t Struct Reference

```
#include <odometry_3wheel.h>
```

Public Attributes

- double wheelbase_dist
- · double off axis center dist
- double wheel_diam

4.43.1 Detailed Description

odometry3wheel_cfg_t holds all the specifications for how to calculate position with 3 encoders See the core wiki for what exactly each of these parameters measures

4.43.2 Member Data Documentation

off_axis_center_dist

```
double Odometry3Wheel::odometry3wheel_cfg_t::off_axis_center_dist
```

distance from the center of the robot to the center off axis wheel

wheel_diam

```
\verb|double Odometry3Wheel::odometry3wheel\_cfg\_t::wheel\_diam|\\
```

the diameter of the tracking wheel

wheelbase_dist

```
double Odometry3Wheel::odometry3wheel_cfg_t::wheelbase_dist
```

distance from the center of the left wheel to the center of the right wheel


The documentation for this struct was generated from the following file:

· odometry_3wheel.h

4.44 OdometryBase Class Reference

```
#include <odometry_base.h>
```

Inheritance diagram for OdometryBase:



Public Member Functions

- OdometryBase (bool is_async)
- virtual Pose2d get_position (void)
- virtual void set_position (const Pose2d &newpos=zero_pos)
- virtual Pose2d update ()=0
- void end async ()
- virtual double get_speed ()
- virtual double get_accel ()
- double get_angular_speed_deg ()
- double get_angular_accel_deg ()

Static Public Member Functions

- static int background_task (void *ptr)
- static double smallest_angle (double start_deg, double end_deg)

Public Attributes

• bool end_task = false

end_task is true if we instruct the odometry thread to shut down

- vex::task * handle
- vex::mutex mut
- Pose2d current pos
- · double speed
- double accel
- double ang_speed_deg
- double ang_accel_deg

4.44.1 Detailed Description

OdometryBase

This base class contains all the shared code between different implementations of odometry. It handles the asynchronous management, position input/output and basic math functions, and holds positional types specific to field orientation.

All future odometry implementations should extend this file and redefine update() function.

Author

Ryan McGee

Date

Aug 11 2021

4.44.2 Constructor & Destructor Documentation

OdometryBase()

Construct a new Odometry Base object

Parameters

is_async True to run constantly in the background, false to call update() manually

4.44.3 Member Function Documentation

background_task()

Function that runs in the background task. This function pointer is passed to the vex::task constructor.

ptr | Pointer to OdometryBase object

Returns

Required integer return code. Unused.

end_async()

```
void OdometryBase::end_async ()
```

End the background task. Cannot be restarted. If the user wants to end the thread but keep the data up to date, they must run the update() function manually from then on.

get_accel()

```
double OdometryBase::get_accel () [virtual]
```

Get the current acceleration

Returns

the acceleration rate of the robot (inch/s^2)

get_angular_accel_deg()

```
double OdometryBase::get_angular_accel_deg ()
```

Get the current angular acceleration in degrees

Returns

the angular acceleration at which we are turning (deg/s^2)

get_angular_speed_deg()

```
double OdometryBase::get_angular_speed_deg ()
```

Get the current angular speed in degrees

Returns

the angular velocity at which we are turning (deg/s)

get_position()

Gets the current position and rotation

Returns

the position that the odometry believes the robot is at

Gets the current position and rotation

Reimplemented in OdometrySerial.

get_speed()

```
double OdometryBase::get_speed () [virtual]
```

Get the current speed

Returns

the speed at which the robot is moving and grooving (inch/s)

set_position()

Sets the current position of the robot

Parameters

newpos	the new position that the odometry will believe it is at
--------	--

Sets the current position of the robot

Reimplemented in OdometrySerial, and OdometryTank.

smallest_angle()

Get the smallest difference in angle between a start heading and end heading. Returns the difference between -180 degrees and +180 degrees, representing the robot turning left or right, respectively.

start_deg	intitial angle (degrees)
end_deg	final angle (degrees)

Returns

the smallest angle from the initial to the final angle. This takes into account the wrapping of rotations around 360 degrees

Get the smallest difference in angle between a start heading and end heading. Returns the difference between -180 degrees and +180 degrees, representing the robot turning left or right, respectively.

update()

```
virtual Pose2d OdometryBase::update () [pure virtual]
```

Update the current position on the field based on the sensors

Returns

the location that the robot is at after the odometry does its calculations

Implemented in Odometry3Wheel, OdometrySerial, and OdometryTank.

4.44.4 Member Data Documentation

accel

```
double OdometryBase::accel
```

the rate at which we are accelerating (inch/s^2)

ang_accel_deg

```
double OdometryBase::ang_accel_deg
```

the rate at which we are accelerating our turn (deg/s^2)

ang_speed_deg

```
double OdometryBase::ang_speed_deg
```

the speed at which we are turning (deg/s)

current_pos

```
Pose2d OdometryBase::current_pos
```

Current position of the robot in terms of x,y,rotation

handle

```
vex::task* OdometryBase::handle
```

handle to the vex task that is running the odometry code

mut

```
vex::mutex OdometryBase::mut
```

Mutex to control multithreading

speed

```
double OdometryBase::speed
```

the speed at which we are travelling (inch/s)

The documentation for this class was generated from the following files:


- · odometry_base.h
- · odometry_base.cpp

4.45 screen::OdometryPage Class Reference

a page that shows odometry position and rotation and a map (if an sd card with the file is on)

```
#include <screen.h>
```

Inheritance diagram for screen::OdometryPage:



Public Member Functions

- OdometryPage (OdometryBase &odom, double robot_width, double robot_height, bool do_trail)

 Create an odometry trail. Make sure odometry is initilized before now.
- void update (bool was_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

4.45.1 Detailed Description

a page that shows odometry position and rotation and a map (if an sd card with the file is on)

4.45.2 Constructor & Destructor Documentation

OdometryPage()

```
screen::OdometryPage::OdometryPage (
    OdometryBase & odom,
    double robot_width,
    double robot_height,
    bool do_trail)
```

Create an odometry trail. Make sure odometry is initilized before now.

Parameters

odom	the odometry system to monitor	
robot_width	the width (side to side) of the robot in inches. Used for visualization	
robot_height	the robot_height (front to back) of the robot in inches. Used for visualization	
do_trail	whether or not to calculate and draw the trail. Drawing and storing takes a very <i>slight</i> extra amount of processing power	

4.45.3 Member Function Documentation

draw()

See also

Page::draw

Reimplemented from screen::Page.

update()

```
void screen::OdometryPage::update (
          bool was_pressed,
          int x,
          int y) [override], [virtual]
```

See also

Page::update

Reimplemented from screen::Page.


The documentation for this class was generated from the following files:

- screen.h
- screen.cpp

4.46 OdometrySerial Class Reference

#include <odometry_serial.h>

Inheritance diagram for OdometrySerial:



Public Member Functions

- OdometrySerial (bool is_async, bool calc_vel_acc_on_brain, Pose2d initial_pose, Pose2d sensor_offset, int32_t port, int32_t baudrate)
- void send_config (const Pose2d &initial_pose, const Pose2d &sensor_offset, const bool &calc_vel_acc_on
 — _brain)
- · Pose2d update () override
- void set position (const Pose2d &new pose) override
- int receive_cobs_packet (uint32_t port, uint8_t *buffer, size_t buffer_size)
- Pose2d get_position (void) override
- Pose2d get pose2d (void)
- size_t cobs_decode (const uint8_t *buffer, size_t length, void *data)
- size_t cobs_encode (const void *data, size_t length, uint8_t *buffer)

Public Member Functions inherited from OdometryBase

- OdometryBase (bool is async)
- void end_async ()
- double get_angular_speed_deg ()
- double get_angular_accel_deg ()

Additional Inherited Members

Static Public Member Functions inherited from OdometryBase

- static int background_task (void *ptr)
- static double smallest_angle (double start_deg, double end_deg)

Public Attributes inherited from OdometryBase

• bool end_task = false

end_task is true if we instruct the odometry thread to shut down

- vex::task * handle
- vex::mutex mut
- · Pose2d current pos
- · double speed
- double accel
- · double ang speed deg
- double ang_accel_deg

4.46.1 Detailed Description

OdometrySerial

This class handles the code for an odometry setup where calculations are done on an external coprocessor. Data is sent to the brain via smart port, using a generic serial (UART) connection.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

```
https://rit.enterprise.slack.com/files/U04112Y5RB6/F080M01KPA5/predictperpindiculars2.4pdf 2024-2025 Notebook: Entries/Software Entries/Localization/N-Pod Odometry
```

Author

Jack Cammarata

Date

Jan 16 2025

4.46.2 Constructor & Destructor Documentation

OdometrySerial()

```
OdometrySerial::OdometrySerial (
          bool is_async,
          bool calc_vel_acc_on_brain,
          Pose2d initial_pose,
          Pose2d sensor_offset,
          int32_t port,
          int32_t baudrate)
```

Construct a new Odometry Serial Object

OdometrySerial

This class handles the code for an odometry setup where calculations are done on an external coprocessor. Data is sent to the brain via smart port, using a generic serial (UART) connection.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

```
https://rit.enterprise.slack.com/files/U04112Y5RB6/F080M01KPA5/predictperpindiculars2.cpdf 2024-2025 Notebook: Entries/Software Entries/Localization/N-Pod Odometry
```

Author

Jack Cammarata

Date

Jan 16 2025 Construct a new Odometry Serial Object

4.46.3 Member Function Documentation

cobs decode()

COBS decode data from buffer

buffer	Pointer to encoded input bytes
length	Number of bytes to decode
data	Pointer to decoded output data

Returns

Number of bytes successfully decoded

Note

Stops decoding if delimiter byte is found

cobs_encode()

COBS encode data to buffer

Parameters

data	Pointer to input data to encode
length	Number of bytes to encode
buffer	Pointer to encoded output buffer

Returns

Encoded buffer length in bytes

Note

Does not output delimiter byte

get_pose2d()

Gets the current position and rotation

Returns

the position that the odometry believes the robot is at

get_position()

Gets the current position and rotation

Returns

the position that the odometry believes the robot is at

Reimplemented from OdometryBase.

receive_cobs_packet()

Attempts to recieve an entire packet encoded with COBS, stops at delimiter or there's a buffer overflow

Parameters

port	the port number the serial is plugged into, counts from 0 instead of 1
buffer	pointer to a uint8_t[] where we put the data
buffer_size	length in bytes of the buffer

Returns

0 success

send_config()

Send

set_position()

Resets the position and rotational data to the input.

Resets the position and rotational data to the input.

new_pose	the pose to set the odometry to
----------	---------------------------------

Reimplemented from OdometryBase.

update()

```
Pose2d OdometrySerial::update () [override], [virtual]
```

Update the current position of the robot once by reading a single packet from the serial port

Returns

the robot's updated position

Update the current position of the robot once by reading a single packet from the serial port, then updating all over values, velocity, accel

Returns

the robot's updated position

Implements OdometryBase.


The documentation for this class was generated from the following files:

- · odometry_serial.h
- · odometry_serial.cpp

4.47 OdometryTank Class Reference

```
#include <odometry_tank.h>
```

Inheritance diagram for OdometryTank:



Public Member Functions

- OdometryTank (CustomEncoder &left_custom_enc, CustomEncoder &right_custom_enc, robot_specs_t &config, vex::inertial *imu=NULL, bool is_async=true)
- Pose2d update () override
- void set_position (const Pose2d &newpos=zero_pos) override

Public Member Functions inherited from OdometryBase

- OdometryBase (bool is_async)
- virtual Pose2d get_position (void)
- void end async ()
- virtual double get_speed ()
- virtual double get_accel ()
- double get_angular_speed_deg ()
- double get_angular_accel_deg ()

Additional Inherited Members

Static Public Member Functions inherited from OdometryBase

- static int background_task (void *ptr)
- static double smallest_angle (double start_deg, double end_deg)

Public Attributes inherited from OdometryBase

- bool end_task = false
 - end_task is true if we instruct the odometry thread to shut down
- vex::task * handle
- vex::mutex mut
- Pose2d current_pos
- double speed
- · double accel
- · double ang_speed_deg
- · double ang accel deg

4.47.1 Detailed Description

OdometryTank defines an odometry system for a tank drivetrain This requires encoders in the same orientation as the drive wheels Odometry is a "start and forget" subsystem, which means once it's created and configured, it will constantly run in the background and track the robot's X, Y and rotation coordinates.

4.47.2 Constructor & Destructor Documentation

OdometryTank() [1/3]

Initialize the Odometry module, calculating position from the drive motors.

left_side	The left motors	
right_side	The right motors	
config	the specifications that supply the odometry with descriptions of the robot. See robot_specs_t for what is contained	
imu	The robot's inertial sensor. If not included, rotation is calculated from the encoders.	
is_async	If true, position will be updated in the background continuously. If false, the programmer will have to manually call update().	

OdometryTank() [2/3]

Initialize the Odometry module, calculating position from the drive motors.

Parameters

left_custom_enc	The left custom encoder
right_custom_enc	The right custom encoder
config	the specifications that supply the odometry with descriptions of the robot. See robot_specs_t for what is contained
imu	The robot's inertial sensor. If not included, rotation is calculated from the encoders.
is_async	If true, position will be updated in the background continuously. If false, the programmer will have to manually call update().

OdometryTank() [3/3]

```
OdometryTank::OdometryTank (
    vex::encoder & left_vex_enc,
    vex::encoder & right_vex_enc,
    robot_specs_t & config,
    vex::inertial * imu = NULL,
    bool is_async = true)
```

Initialize the Odometry module, calculating position from the drive motors.

Parameters

left_vex_enc	The left vex encoder
right_vex_enc	The right vex encoder
config	the specifications that supply the odometry with descriptions of the robot. See robot_specs_t for what is contained
imu	The robot's inertial sensor. If not included, rotation is calculated from the encoders.
is_async	If true, position will be updated in the background continuously. If false, the programmer will have to manually call update().

4.47.3 Member Function Documentation

set_position()

set position tells the odometry to place itself at a position

Parameters

	newpos	the position the odometry will take
--	--------	-------------------------------------

Resets the position and rotational data to the input.

Reimplemented from OdometryBase.

update()

```
Pose2d OdometryTank::update () [override], [virtual]
```

Update the current position on the field based on the sensors

Returns

the position that odometry has calculated itself to be at

Update, store and return the current position of the robot. Only use if not initializing with a separate thread. Implements OdometryBase.

The documentation for this class was generated from the following files:

- · odometry_tank.h
- · odometry_tank.cpp

4.48 OdomSetPosition Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- OdomSetPosition (OdometryBase &odom, const Pose2d &newpos=OdometryBase::zero pos)
- · bool run () override

4.48.1 Detailed Description

AutoCommand wrapper class for the set_position function in the Odometry class

4.48.2 Constructor & Destructor Documentation

OdomSetPosition()

```
OdomSetPosition::OdomSetPosition (
         OdometryBase & odom,
         const Pose2d & newpos = OdometryBase::zero_pos)
```

constructs a new OdomSetPosition command

odom the odometry system we are set		the odometry system we are setting
ne	vpos	the position we are telling the odometry to take. defaults to $(0, 0)$, angle = 90

Construct an Odometry set pos

Parameters

odom	the odometry system we are setting
newpos	the now position to set the odometry to

4.48.3 Member Function Documentation

run()

```
bool OdomSetPosition::run () [override]
```

Run set_position Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:


- drive_commands.h
- drive_commands.cpp

4.49 screen::Page Class Reference

Page describes one part of the screen slideshow.

```
#include <screen.h>
```

Inheritance diagram for screen::Page:



Public Member Functions

- virtual void update (bool was_pressed, int x, int y)

 collect data, respond to screen input, do fast things (runs at 50hz even if you're not focused on this Page (only drawn page gets touch updates))
- virtual void draw (vex::brain::lcd &screen, bool first_draw, unsigned int frame_number)

 draw stored data to the screen (runs at 10 hz and only runs if this page is in front)

4.49.1 Detailed Description

Page describes one part of the screen slideshow.

4.49.2 Member Function Documentation

draw()

draw stored data to the screen (runs at 10 hz and only runs if this page is in front)

Parameters

first_draw	true if we just switched to this page
frame_number	frame of drawing we are on (basically an animation tick)

Reimplemented in screen::FunctionPage, screen::OdometryPage, screen::PIDPage, and screen::StatsPage.

update()

```
virtual void screen::Page::update (
          bool was_pressed,
          int x,
          int y) [virtual]
```

collect data, respond to screen input, do fast things (runs at 50hz even if you're not focused on this Page (only drawn page gets touch updates))

Parameters

was_pressed	true if the screen has been pressed
X	x position of screen press (if the screen was pressed)
У	y position of screen press (if the screen was pressed)

Reimplemented in screen::FunctionPage, screen::OdometryPage, screen::PIDPage, and screen::StatsPage.

The documentation for this class was generated from the following file:

· screen.h

4.50 Parallel Class Reference

Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on_timeout on all children continue.

```
#include <auto_command.h>
```

4.50.1 Detailed Description

Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on_timeout on all children continue.

The documentation for this class was generated from the following files:

- · auto command.h
- · auto_command.cpp

4.51 PurePursuit::Path Class Reference

```
#include <pure_pursuit.h>
```

Public Member Functions

```
• Path (std::vector< Translation2d > points, double radius)
```

- const std::vector< Translation2d > get_points ()
- double get_radius ()
- bool is_valid ()

4.51.1 Detailed Description

Wrapper for a vector of points, checking if any of the points are too close for pure pursuit

4.51.2 Constructor & Destructor Documentation

Path()

Create a Path

Parameters

points	the points that make up the path
radius	the lookahead radius for pure pursuit

4.51.3 Member Function Documentation

get_points()

```
const std::vector< Translation2d > PurePursuit::Path::get_points ()
```

Get the points associated with this Path

4.52 PID Class Reference 85

get_radius()

```
double PurePursuit::Path::get_radius ()
```

Get the radius associated with this Path

is_valid()

```
bool PurePursuit::Path::is_valid ()
```

Get whether this path will behave as expected

The documentation for this class was generated from the following files:

- pure_pursuit.h
- pure_pursuit.cpp

4.52 PID Class Reference

```
#include <pid.h>
```

Inheritance diagram for PID:



Classes

• struct pid_config_t

Public Types

• enum ERROR TYPE

Public Member Functions

- PID (pid_config_t &config)
- void init (double start_pt, double set_pt) override
- double update (double sensor_val) override
- double update (double sensor_val, double v_setpt)
- double get_sensor_val () const

gets the sensor value that we were last updated with

- double get () override
- void set_limits (double lower, double upper) override
- bool is_on_target () override
- void reset ()
- double get_error ()
- double get_target () const
- void set_target (double target)

Public Attributes

• pid_config_t & config

4.52.1 Detailed Description

PID Class

Defines a standard feedback loop using the constants kP, kI, kD, deadband, and on_target_time. The formula is:

```
out = kP*error + kI*integral(d Error) + kD*(dError/dt)
```

The PID object will determine it is "on target" when the error is within the deadband, for a duration of on_target_time

Author

Ryan McGee

Date

4/3/2020

4.52.2 Member Enumeration Documentation

ERROR_TYPE

```
enum PID::ERROR_TYPE
```

An enum to distinguish between a linear and angular caluclation of PID error.

4.52.3 Constructor & Destructor Documentation

PID()

Create the PID object

Parameters

config the configuration data for this controller

Create the PID object

4.52 PID Class Reference 87

4.52.4 Member Function Documentation

```
get()
```

```
double PID::get () [override], [virtual]
```

Gets the current PID out value, from when update() was last run

Returns

the Out value of the controller (voltage, RPM, whatever the PID controller is controlling)

Gets the current PID out value, from when update() was last run

Implements Feedback.

get error()

```
double PID::get_error ()
```

Get the delta between the current sensor data and the target

Returns

the error calculated. how it is calculated depends on error_method specified in pid_config_t

Get the delta between the current sensor data and the target

get_sensor_val()

```
double PID::get_sensor_val () const
```

gets the sensor value that we were last updated with

Returns

sensor_val

get_target()

```
double PID::get_target () const
```

Get the PID's target

Returns

the target the PID controller is trying to achieve

init()

Inherited from Feedback for interoperability. Update the setpoint and reset integral accumulation

start_pt can be safely ignored in this feedback controller

start_pt	commpletely ignored for PID. necessary to satisfy Feedback base
set_pt	sets the target of the PID controller
start_vel completely ignored for PID. necessary to satisfy Feedback	
end_vel	sets the target end velocity of the PID controller

Implements Feedback.

is_on_target()

```
bool PID::is_on_target () [override], [virtual]
```

Checks if the PID controller is on target.

Returns

true if the loop is within [deadband] for [on_target_time] seconds

Returns true if the loop is within [deadband] for [on_target_time] seconds

Implements Feedback.

reset()

```
void PID::reset ()
```

Reset the PID loop by resetting time since 0 and accumulated error.

set_limits()

Set the limits on the PID out. The PID out will "clip" itself to be between the limits.

Parameters

lower	the lower limit. the PID controller will never command the output go below lower
upper	the upper limit. the PID controller will never command the output go higher than upper

Set the limits on the PID out. The PID out will "clip" itself to be between the limits.

Implements Feedback.

set_target()

Set the target for the PID loop, where the robot is trying to end up

4.52 PID Class Reference 89

Parameters

target	the sensor reading we would like to achieve
larget	The sensor reading we would like to deflicte

Set the target for the PID loop, where the robot is trying to end up

update() [1/2]

Update the PID loop by taking the time difference from last update, and running the PID formula with the new sensor data

Parameters

	sensor_val	the distance, angle, encoder position or whatever it is we are measuring	
--	------------	--	--

Returns

the new output. What would be returned by PID::get()

Implements Feedback.

update() [2/2]

Update the PID loop by taking the time difference from last update, and running the PID formula with the new sensor data

Parameters

sensor_val	the distance, angle, encoder position or whatever it is we are measuring
v_setpt	Expected velocity setpoint, to subtract from the D term (for velocity control)

Returns

the new output. What would be returned by PID::get()

4.52.5 Member Data Documentation

config

```
pid_config_t& PID::config
```

configuration struct for this controller. see pid_config_t for information about what this contains

The documentation for this class was generated from the following files:

- pid.h
- pid.cpp

4.53 PID::pid_config_t Struct Reference

```
#include <pid.h>
```

Public Attributes

• double p

proportional coeffecient p * error()

• double i

integral coeffecient i * integral(error)

· double d

derivitave coeffecient d * derivative(error)

· double deadband

at what threshold are we close enough to be finished

- · double on target time
- ERROR_TYPE error_method

4.53.1 Detailed Description

pid_config_t holds the configuration parameters for a pid controller In addition to the constant of proportional, integral and derivative, these parameters include:

- · deadband -
- on_target_time for how long do we have to be at the target to stop As well, pid_config_t holds an error type which determines whether errors should be calculated as if the sensor position is a measure of distance or an angle

4.53.2 Member Data Documentation

error_method

```
ERROR_TYPE PID::pid_config_t::error_method
```

Linear or angular. wheter to do error as a simple subtraction or to wrap

on_target_time

```
double PID::pid_config_t::on_target_time
```

the time in seconds that we have to be on target for to say we are officially at the target

The documentation for this struct was generated from the following file:


• pid.h

4.54 screen::PIDPage Class Reference

PIDPage provides a way to tune a pid controller on the screen.

```
#include <screen.h>
```

Inheritance diagram for screen::PIDPage:



Public Member Functions

- PIDPage (PID &pid, std::string name, std::function < void(void) > onchange=[]() {})
 Create a PIDPage.
- void update (bool was_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

4.54.1 Detailed Description

PIDPage provides a way to tune a pid controller on the screen.

4.54.2 Constructor & Destructor Documentation

PIDPage()

```
screen::PIDPage::PIDPage (
          PID & pid,
          std::string name,
          std::function< void(void) > onchange = []() {})
```

Create a PIDPage.

Parameters

pid	the pid controller we're changing
name	a name to recognize this pid controller if we've got multiple pid screens
onchange	a function that is called when a tuning parameter is changed. If you need to update stuff on that change register a handler here

4.54.3 Member Function Documentation

draw()

See also

Page::draw

Reimplemented from screen::Page.

update()

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:

- screen.h
- screen.cpp

4.55 Pose2d Class Reference

```
#include <pose2d.h>
```

Public Member Functions

- constexpr Pose2d ()
- Pose2d (const Translation2d &translation, const Rotation2d &rotation)
- Pose2d (const double &x, const double &y, const Rotation2d &rotation)
- Pose2d (const double &x, const double &y, const double &radians)
- Pose2d (const Translation2d &translation, const double &radians)
- Pose2d (const Eigen::Vector3d &pose_vector)
- Translation2d translation () const
- double x () const
- void setX (double x)
- double y () const
- void setY (double y)
- Rotation2d rotation () const
- void setRotationRad (double rotRad)
- void setRotationDeg (double rotDeg)
- bool operator== (const Pose2d other) const
- Pose2d operator* (const double &scalar) const
- Pose2d operator/ (const double &scalar) const
- Pose2d operator+ (const Transform2d &transform) const
- Transform2d operator- (const Pose2d &other) const
- Pose2d relative_to (const Pose2d &other) const
- Pose2d transform by (const Transform2d &transform) const
- Pose2d exp (const Twist2d &twist) const
- Twist2d log (const Pose2d &end_pose) const

Friends

std::ostream & operator<< (std::ostream &os, const Pose2d &pose)

4.55.1 Detailed Description

Class representing a pose in 2d space with x, y, and rotational components

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

4.55.2 Constructor & Destructor Documentation

```
Pose2d() [1/6]
```

```
Pose2d::Pose2d () [inline], [constexpr]
```

Default Constructor for Pose2d

Pose2d() [2/6]

Constructs a pose with given translation and rotation components.

translation	translational component.
rotation	rotational component.

Pose2d() [3/6]

Constructs a pose with given translation and rotation components.

Parameters

X	x component.
У	y component.
rotation	rotational component.

Pose2d() [4/6]

Constructs a pose with given translation and rotation components.

Parameters

X	x component.
У	y component.
radians	rotational component in radians.

Pose2d() [5/6]

Constructs a pose with given translation and rotation components.

Parameters

translation	translational component.
radians	rotational component in radians.

Pose2d() [6/6]

Constructs a pose with given translation and rotation components.

pose_vector	vector of the form [x, y, theta].
-------------	-----------------------------------

4.55.3 Member Function Documentation

exp()

Applies a twist (pose delta) to a pose by including first order dynamics of heading.

When applying a twist, imagine a constant angular velocity, the translational components must be rotated into the global frame at every point along the twist, simply adding the deltas does not do this, and using euler integration results in some error. This is the analytic solution that that problem.

Can also be thought of more simply as applying a twist as following an arc rather than a straight line.

See this document for more information on the pose exponential and its derivation. https://file.

tavsys.net/control/controls-engineering-in-frc.pdf#section.10.2

Parameters

old_pose	The pose to which the twist will be applied.
twist	The twist, represents a pose delta.

Returns

new pose that has been moved forward according to the twist.

log()

The inverse of the pose exponential.

Determines the twist required to go from this pose to the given end pose. suppose you have Pose2d a, Twist2d twist if a.exp(twist) = b then a.log(b) = twist

Parameters

```
end_pose the end pose to find the mapping to.
```

Returns

the twist required to go from this pose to the given end

operator*()

Multiplies this pose by a scalar. Simply multiplies each component.

scalar	the scalar value to multiply by.
--------	----------------------------------

operator+()

Adds a transform to this pose. Transforms the pose in the pose's frame.

Parameters

transform
transform

operator-()

Subtracts one pose from another to find the transform between them.

Parameters

other	the pose to subtract.
-------	-----------------------

operator/()

Divides this pose by a scalar. Simply divides each component.

Parameters

sca	lar	the scalar value to divide by.

operator==()

Compares this to another pose.

other	the other pose to compare to.	
-------	-------------------------------	--

Returns

true if each of the components are within 1e-9 of each other.

relative_to()

Finds the pose equivalent to this pose relative to another arbitrary pose rather than the origin.

Parameters

other	the pose representing the new origin.
-------	---------------------------------------

Returns

this pose relative to another pose.

rotation()

```
Rotation2d Pose2d::rotation () const
```

Returns the rotational component.

Returns

the rotational component.

setRotationDeg()

sets the ration value of the rotational component in Degrees

setRotationRad()

sets the ration value of the rotational component in Radians

setX()

sets the x value of the translational component.

setY()

sets the y value of the translational component.

transform_by()

Adds a transform to this pose. Simply adds each component.

Parameters

```
transform the change in pose.
```

Returns

the pose after being transformed.

translation()

```
Translation2d Pose2d::translation () const
```

Returns the translational component.

Returns

the translational component.

x()

```
double Pose2d::x () const
```

Returns the x value of the translational component.

Returns

the x value of the translational component.

y()

```
double Pose2d::y () const
```

Returns the y value of the translational component.

Returns

the y value of the translational component.

4.55.4 Friends And Related Symbol Documentation

operator<<

Sends a pose to an output stream. Ex. std::cout << pose;

prints "Pose2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"

The documentation for this class was generated from the following files:

- · pose2d.h
- · pose2d.cpp

4.56 PurePursuitCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- PurePursuitCommand (TankDrive &drive_sys, Feedback &feedback, PurePursuit::Path path, directionType dir, double max_speed=1, double end_speed=0)
- bool run () override
- void on_timeout () override

4.56.1 Detailed Description

Autocommand wrapper class for pure pursuit function in the TankDrive class

4.56.2 Constructor & Destructor Documentation

PurePursuitCommand()

Construct a Pure Pursuit AutoCommand

path	The list of coordinates to follow, in order
dir	Run the bot forwards or backwards
feedback	The feedback controller determining speed
max_speed	Limit the speed of the robot (for pid / pidff feedbacks)

4.56.3 Member Function Documentation

on_timeout()

```
void PurePursuitCommand::on_timeout () [override]
```

Reset the drive system when it times out

run()

```
bool PurePursuitCommand::run () [override]
```

Direct call to TankDrive::pure_pursuit

The documentation for this class was generated from the following files:

- · drive_commands.h
- drive_commands.cpp

4.57 Rect Struct Reference

```
#include <geometry.h>
```

4.57.1 Detailed Description

Describes a Rectangle with a minimum and maximum point

The documentation for this struct was generated from the following file:

• geometry.h

4.58 robot_specs_t Struct Reference

```
#include <robot_specs.h>
```

Public Attributes

· double robot_radius

if you were to draw a circle with this radius, the robot would be entirely contained within it

• double odom_wheel_diam

the diameter of the wheels used for

double odom_gear_ratio

the ratio of the odometry wheel to the encoder reading odometry data

double dist_between_wheels

the distance between centers of the central drive wheels

- · double drive_correction_cutoff
- Feedback * drive feedback

the default feedback for autonomous driving

Feedback * turn_feedback

the defualt feedback for autonomous turning

PID::pid_config_t correction_pid

the pid controller to keep the robot driving in as straight a line as possible

4.58.1 Detailed Description

Main robot characterization struct. This will be passed to all the major subsystems that require info about the robot. All distance measurements are in inches.

4.58.2 Member Data Documentation

drive_correction_cutoff

```
double robot_specs_t::drive_correction_cutoff
```

the distance at which to stop trying to turn towards the target. If we are less than this value, we can continue driving forward to minimize our distance but will not try to spin around to point directly at the target

The documentation for this struct was generated from the following file:

· robot_specs.h

4.59 Rotation2d Class Reference

#include <rotation2d.h>

Public Member Functions

- constexpr Rotation2d ()
- Rotation2d (const double &radians)
- Rotation2d (const double &x, const double &y)
- Rotation2d (const Translation2d &translation)
- double radians () const
- void setRad (double radRot)
- double degrees () const
- void setDeg (double degRot)
- double revolutions () const
- double f_cos () const
- double f_sin () const
- double f_tan () const
- Eigen::Matrix2d rotation_matrix () const
- double wrapped radians 180 () const
- double wrapped_degrees_180 () const
- double wrapped_revolutions_180 () const
- double wrapped_radians_360 () const
- double wrapped_degrees_360 () const
- double wrapped revolutions 360 () const
- Rotation2d operator+ (const Rotation2d &other) const
- Rotation2d operator- (const Rotation2d &other) const
- Rotation2d operator- () const
- Rotation2d operator* (const double &scalar) const
- Rotation2d operator/ (const double &scalar) const
- bool operator== (const Rotation2d &other) const

Friends

std::ostream & operator<< (std::ostream &os, const Rotation2d &rotation)

4.59.1 Detailed Description

Class representing a rotation in 2d space. Stores theta in radians, as well as cos and sin.

Internally this angle is stored continuously, however there are functions that return wrapped angles: "180" is from [-pi, pi), [-180, 180), [-0.5, 0.5) "360" is from [0, 2pi), [0, 360), [0, 1)

4.59.2 Constructor & Destructor Documentation

Rotation2d() [1/4]

```
Rotation2d::Rotation2d () [inline], [constexpr]
```

Default Constructor for Rotation2d

Rotation2d() [2/4]

```
Rotation2d::Rotation2d (

const double & radians)
```

Constructs a rotation with the given value in radians.

radians the value of the rotation in radians.

Rotation2d() [3/4]

Constructs a rotation given x and y values. Does not have to be normalized. The angle from the x axis to the point.

```
[theta] = [atan2(y, x)]
```

Parameters

X	the x value of the point
у	the y value of the point

Rotation2d() [4/4]

Constructs a rotation given x and y values in the form of a Translation2d. Does not have to be normalized. The angle from the x axis to the point.

```
[theta] = [atan2(y, x)]
```

Parameters

translation

4.59.3 Member Function Documentation

degrees()

```
double Rotation2d::degrees () const
```

Returns the degree angle value.

Returns

the degree angle value.

f_cos()

```
double Rotation2d::f_cos () const
```

Returns the cosine of the angle value.

Returns

the cosine of the angle value

f_sin()

```
double Rotation2d::f_sin () const
```

Returns the sine of the angle value.

Returns

the sine of the angle value.

f_tan()

```
double Rotation2d::f_tan () const
```

Returns the tangent of the angle value.

Returns

the tangent of the angle value.

operator*()

Multiplies this rotation by a scalar.

Parameters

scalar	the scalar value to multiply the rotation by.
--------	---

Returns

the rotation multiplied by the scalar.

operator+()

Adds the values of two rotations using a rotation matrix

 $[new_cos] = [other.cos, -other.sin][cos] \\ [new_sin] = [other.sin, other.cos][sin] \\ new_value = atan2(new_sin, new_cos) \\ [new_cos] \\ [new_sin] = [other.sin, other.cos][sin] \\ [new_value] = atan2(new_sin, new_cos) \\ [new_sin] \\ [new_sin] = [other.sin, other.sin][sin] \\ [new_sin] = [other.sin, other.sin, other$

other	the other rotation to add to this rotation.
-------	---

Returns

the sum of the two rotations.

Adds the values of two rotations using a rotation matrix.

[new_cos] = [other.cos, -other.sin][cos] [new_sin] = [other.sin, other.cos][sin] new_value = atan2(new_sin, new_cos)

Parameters

other	the other rotation to add to this rotation.

Returns

the sum of the two rotations.

operator-() [1/2]

```
Rotation2d Rotation2d::operator- () const
```

Takes the inverse of this rotation by flipping it. Equivalent to adding 180 degrees.

Returns

this inverse of the rotation.

Takes the inverse of this rotation by flipping it.

Returns

this inverse of the rotation.

operator-() [2/2]

Subtracts the values of two rotations.

Parameters

other	the other rotation to subtract from this rotation.
-------	--

Returns

the difference between the two rotations.

operator/()

Divides this rotation by a scalar.

scalar	the scalar value to divide the rotation by.
--------	---

Returns

the rotation divided by the scalar.

operator==()

Compares two rotations. Returns true if their values are within 1e-9 radians of each other, to account for floating point error.

Parameters

Returns

whether the values of the rotations are within 1e-9 radians of each other

radians()

```
double Rotation2d::radians () const
```

Returns the radian angle value.

Returns

the radian angle value.

revolutions()

```
double Rotation2d::revolutions () const
```

Returns the revolution angle value.

Returns

the revolution angle value.

rotation_matrix()

```
Eigen::Matrix2d Rotation2d::rotation_matrix () const
```

Returns the rotation matrix equivalent to this rotation [cos, -sin] R = [sin, cos]

Returns

the rotation matrix equivalent to this rotation

setDeg()

sets the angle value in degrees

setRad()

sets the angle value in radians

wrapped_degrees_180()

```
double Rotation2d::wrapped_degrees_180 () const
```

Returns the degree angle value, wrapped from [-180, 180).

Returns

the degree angle value, wrapped from [-180, 180)

wrapped_degrees_360()

```
double Rotation2d::wrapped_degrees_360 () const
```

Returns the degree angle value, wrapped from [0, 360).

Returns

the degree angle value, wrapped from [0, 360)

wrapped_radians_180()

```
double Rotation2d::wrapped_radians_180 () const
```

Returns the radian angle value, wrapped from [-pi, pi).

Returns

the radian angle value, wrapped from [-pi, pi)

wrapped_radians_360()

```
double Rotation2d::wrapped_radians_360 () const
```

Returns the radian angle value, wrapped from [0, 2pi).

Returns

the radian angle value, wrapped from [0, 2pi)

wrapped_revolutions_180()

```
double Rotation2d::wrapped_revolutions_180 () const
```

Returns the revolution angle value, wrapped from [-0.5, 0.5).

Returns

the revolution angle value, wrapped from [-0.5, 0.5)

wrapped_revolutions_360()

```
double Rotation2d::wrapped_revolutions_360 () const
```

Returns the revolution angle value, wrapped from [0, 1).

Returns

the revolution angle value, wrapped from [0, 1)

4.59.4 Friends And Related Symbol Documentation

operator<<

Sends a rotation to an output stream. Ex. std::cout << rotation;

```
prints "Rotation2d[rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- rotation2d.h
- rotation2d.cpp

4.60 screen::ScreenData Struct Reference

The ScreenData class holds the data that will be passed to the screen thread you probably shouldnt have to use it.

4.60.1 Detailed Description

The ScreenData class holds the data that will be passed to the screen thread you probably shouldnt have to use it.

The documentation for this struct was generated from the following file:

· screen.cpp

4.61 Serializer Class Reference

Serializes Arbitrary data to a file on the SD Card.

```
#include <serializer.h>
```

Public Member Functions

∼Serializer ()

Save and close upon destruction (bc of vex, this doesnt always get called when the program ends. To be sure, call save_to_disk)

Serializer (const std::string &filename, bool flush_always=true)

create a Serializer

• void save_to_disk () const

saves current Serializer state to disk

• void set_int (const std::string &name, int i)

Setters - not saved until save_to_disk is called.

void set_bool (const std::string &name, bool b)

sets a bool by the name of name to b. If flush_always == true, this will save to the sd card

void set_double (const std::string &name, double d)

sets a double by the name of name to d. If flush_always == true, this will save to the sd card

void set_string (const std::string &name, std::string str)

sets a string by the name of name to s. If flush_always == true, this will save to the sd card

int int_or (const std::string &name, int otherwise)

gets a value stored in the serializer. If not found, sets the value to otherwise

• bool bool_or (const std::string &name, bool otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

double double_or (const std::string &name, double otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

• std::string string_or (const std::string &name, std::string otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

4.61.1 Detailed Description

Serializes Arbitrary data to a file on the SD Card.

4.61.2 Constructor & Destructor Documentation

Serializer()

create a Serializer

filename	the file to read from. If filename does not exist we will create that file	
flush_always	If true, after every write flush to a file. If false, you are responsible for calling save_to_disk	

4.61.3 Member Function Documentation

bool_or()

gets a value stored in the serializer. If not, sets the value to otherwise

Parameters

name	name of value
otherwise	value if the name is not specified

Returns

the value if found or otherwise

double_or()

gets a value stored in the serializer. If not, sets the value to otherwise

Parameters

name	name of value
otherwise	value if the name is not specified

Returns

the value if found or otherwise

int_or()

gets a value stored in the serializer. If not found, sets the value to otherwise

Getters Return value if it exists in the serializer

name	name of value
otherwise	value if the name is not specified

Returns

the value if found or otherwise

save_to_disk()

```
void Serializer::save_to_disk () const
```

saves current Serializer state to disk

forms data bytes then saves to filename this was openned with

set_bool()

sets a bool by the name of name to b. If flush_always == true, this will save to the sd card

Parameters

name	name of bool
b	value of bool

set_double()

sets a double by the name of name to d. If flush_always == true, this will save to the sd card

Parameters

name	name of double
d	value of double

set_int()

Setters - not saved until save_to_disk is called.

sets an integer by the name of name to i. If flush_always == true, this will save to the sd card

name	name of integer
i	value of integer

set_string()

sets a string by the name of name to s. If flush_always == true, this will save to the sd card

Parameters

name	name of string
i	value of string

string_or()

gets a value stored in the serializer. If not, sets the value to otherwise

Parameters

name	name of value
otherwise	value if the name is not specified

Returns

the value if found or otherwise

The documentation for this class was generated from the following files:

- serializer.h
- · serializer.cpp

4.62 screen::SliderWidget Class Reference

Widget that updates a double value. Updates by reference so watch out for race conditions cuz the screen stuff lives on another thread.

```
#include <screen.h>
```

Public Member Functions

• SliderWidget (double &val, double low, double high, Rect rect, std::string name)

Creates a slider widget.

bool update (bool was_pressed, int x, int y)

responds to user input

• void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number)

Page::draws the slide to the screen

4.62.1 Detailed Description

Widget that updates a double value. Updates by reference so watch out for race conditions cuz the screen stuff lives on another thread.

4.62.2 Constructor & Destructor Documentation

SliderWidget()

Creates a slider widget.

Parameters

val	reference to the value to modify
low	minimum value to go to
high	maximum value to go to
rect	rect to draw it
name	name of the value

4.62.3 Member Function Documentation

update()

```
bool screen::SliderWidget::update (
          bool was_pressed,
          int x,
          int y)
```

responds to user input

Parameters

was_pressed	if the screen is pressed
X	x position if the screen was pressed
У	y position if the screen was pressed

Returns

true if the value updated

The documentation for this class was generated from the following files:

- · screen.h
- · screen.cpp

4.63 SpinRPMCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- SpinRPMCommand (Flywheel &flywheel, int rpm)
- bool run () override

4.63.1 Detailed Description

File: flywheel_commands.h Desc: [insert meaningful desc] AutoCommand wrapper class for the spin_rpm function in the Flywheel class

4.63.2 Constructor & Destructor Documentation

SpinRPMCommand()

Construct a SpinRPM Command

Parameters

flywheel	the flywheel sys to command
rpm	the rpm that we should spin at

File: flywheel_commands.cpp Desc: [insert meaningful desc]

4.63.3 Member Function Documentation

run()

```
bool SpinRPMCommand::run () [override]
```

Run spin manual Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- flywheel_commands.h
- flywheel_commands.cpp

4.64 PurePursuit::spline Struct Reference

```
#include <pure_pursuit.h>
```

4.64.1 Detailed Description

Represents a piece of a cubic spline with $s(x) = a(x-xi)^3 + b(x-xi)^2 + c(x-xi) + d$ The x_start and x_end shows where the equation is valid.

The documentation for this struct was generated from the following file:

· pure_pursuit.h

4.65 StateMachine< System, IDType, Message, delay_ms, do_log >::State Struct Reference

```
#include <state_machine.h>
```

4.65.1 Detailed Description

template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log = false> struct StateMachine< System, IDType, Message, delay_ms, do_log >::State

Abstract class that all states for this machine must inherit from States MUST override respond() and id() in order to function correctly (the compiler won't have it any other way)

The documentation for this struct was generated from the following file:

state_machine.h

4.66 StateMachine< System, IDType, Message, delay_ms, do_log > Class Template Reference

State Machine:)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024 Over Under game for our overly complex intake-cata subsystem (see there for an example) The statemachine runs in a background thread and a user thread can interact with it through current_state and send_message.

#include <state_machine.h>

Classes

class MaybeMessage

MaybeMessage a message of Message type or nothing MaybeMessage $m = \{\}$; // empty MaybeMessage m = Message::EnumField1.

• struct State

Public Member Functions

StateMachine (State *initial)

Construct a state machine and immediatly start running it.

• IDType current_state () const

retrieve the current state of the state machine. This is safe to call from external threads

void send_message (Message msg)

send a message to the state machine from outside

4.66.1 Detailed Description

template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log = false> class StateMachine< System, IDType, Message, delay_ms, do_log >

State Machine :)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024 Over Under game for our overly complex intake-cata subsystem (see there for an example) The statemachine runs in a background thread and a user thread can interact with it through current_state and send_message.

Designwise: the System class should hold onto any motors, feedback controllers, etc that are persistent in the system States themselves should hold any data that *only* that state needs. For example if a state should be exitted after a certain amount of time, it should hold a timer rather than the System holding that timer. (see Junder from 2024 for an example of this design)

Template Parameters

System	The system that this is the base class of class Thing: public StateMachine <thing> @tparam IDType The ID enum that recognizes states. Hint hint, use anenum class`</thing>	
Message	the message enum that a state or an outside can send and that states respond to	
delay_ms	the delay to wait between each state processing to allow other threads to work	
do_log	true if you want print statements describing incoming messages and current states. If true, it is expected that IDType and Message have a function called to_string that takes them as its only parameter and returns a std::string	

4.66.2 Constructor & Destructor Documentation

StateMachine()

Construct a state machine and immediatly start running it.

Parameters

ine will begin in	initial the state that the	initial	
ine will begin in	initial the state that the	initial	

4.66.3 Member Function Documentation

current_state()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
IDType StateMachine< System, IDType, Message, delay_ms, do_log >::current_state () const
[inline]
```

retrieve the current state of the state machine. This is safe to call from external threads

Returns

the current state

send_message()

send a message to the state machine from outside

Parameters

```
msg the message to send This is safe to call from external threads
```

The documentation for this class was generated from the following file:


· state_machine.h

4.67 screen::StatsPage Class Reference

Draws motor stats and battery stats to the screen.

```
#include <screen.h>
```

Inheritance diagram for screen::StatsPage:



Public Member Functions

- StatsPage (std::map< std::string, vex::motor & > motors)
 Creates a stats page.
- void update (bool was_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

4.67.1 Detailed Description

Draws motor stats and battery stats to the screen.

4.67.2 Constructor & Destructor Documentation

StatsPage()

Creates a stats page.

Parameters

motors a map of string to motor that we want to draw on this page

4.67.3 Member Function Documentation

draw()

See also

Page::draw

Reimplemented from screen::Page.

update()

```
void screen::StatsPage::update (
          bool was_pressed,
          int x,
          int y) [override], [virtual]
```

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:


- screen.h
- · screen.cpp

4.68 TakeBackHalf Class Reference

A velocity controller.

```
#include <take_back_half.h>
```

Inheritance diagram for TakeBackHalf:



Public Member Functions

- void init (double start_pt, double set_pt)
- double update (double val) override
- double get () override
- void set_limits (double lower, double upper) override
- bool is_on_target () override

Public Attributes

 double TBH_gain tuned parameter

4.68.1 Detailed Description

A velocity controller.

Warning

If you try to use this as a position controller, it will fail.

4.68.2 Member Function Documentation

get()

```
double TakeBackHalf::get () [override], [virtual]
```

Returns

the last saved result from the feedback controller

Implements Feedback.

init()

Initialize the feedback controller for a movement

Parameters

start_pt	the current sensor value
set_pt	where the sensor value should be
start_vel	Movement starting velocity (IGNORED)

Implements Feedback.

is_on_target()

```
bool TakeBackHalf::is_on_target () [override], [virtual]
```

Returns

true if the feedback controller has reached it's setpoint

Implements Feedback.

set_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

lower	Upper limit
upper	Lower limit

Implements Feedback.

update()

Iterate the feedback loop once with an updated sensor value

Parameters 4 8 1

```
val value from the sensor
```

Returns

feedback loop result

Implements Feedback.

The documentation for this class was generated from the following files:

- take_back_half.h
- take_back_half.cpp

4.69 TankDrive Class Reference

```
#include <tank_drive.h>
```

Public Types

• enum class BrakeType { None , ZeroVelocity , Smart , TurnOnly }

Public Member Functions

- TankDrive (motor_group &left_motors, motor_group &right_motors, robot_specs_t &config, OdometryBase *odom=NULL)
- void stop ()
- Pose2d get position ()
- void drive tank (double left, double right, int power=1, BrakeType bt=BrakeType::None)
- void drive tank raw (double left, double right)
- void drive_arcade (double forward_back, double left_right, int power=1, BrakeType bt=BrakeType::None)
- bool drive_forward (double inches, directionType dir, Feedback &feedback, double max_speed=1, double end speed=0)
- bool drive_forward (double inches, directionType dir, double max_speed=1, double end_speed=0)
- bool turn_degrees (double degrees, Feedback &feedback, double max_speed=1, double end_speed=0)
- bool turn degrees (double degrees, double max speed=1, double end speed=0)
- bool drive_to_point (double x, double y, vex::directionType dir, Feedback &feedback, double max_speed=1, double end_speed=0)
- bool drive_to_point (double x, double y, vex::directionType dir, double max_speed=1, double end_speed=0)
- bool turn_to_heading (double heading_deg, double max_speed=1, double end_speed=0)
- void reset_auto ()
- bool pure_pursuit (PurePursuit::Path path, directionType dir, Feedback &feedback, double max_speed=1, double end_speed=0)

Static Public Member Functions

static double modify_inputs (double input, int power=2)

4.69.1 Detailed Description

TankDrive is a class to run a tank drive system. A tank drive system, sometimes called differential drive, has a motor (or group of synchronized motors) on the left and right side

4.69.2 Member Enumeration Documentation

BrakeType

```
enum class TankDrive::BrakeType [strong]
```

Enumerator

None	just send 0 volts to the motors
ZeroVelocity	try to bring the robot to rest. But don't try to hold position
Smart	bring the robot to rest and once it's stopped, try to hold that position

4.69.3 Constructor & Destructor Documentation

TankDrive()

Create the

left_motors	left side drive motors
right_motors	right side drive motors
config	the configuration specification defining physical dimensions about the robot. See robot_specs_t for more info
odom	an odometry system to track position and rotation. this is necessary to execute autonomous paths

4.69.4 Member Function Documentation

drive_arcade()

Drive the robot using arcade style controls. forward_back controls the linear motion, left_right controls the turning.

forward_back and left_right are in "percent": -1.0 -> 1.0

Parameters

forward_back	the percent to move forward or backward
left_right	the percent to turn left or right
power	modifies the input velocities left^power, right^power
bt	breaktype. What to do if the driver lets go of the sticks

Drive the robot using arcade style controls. forward_back controls the linear motion, left_right controls the turning. left_motors and right_motors are in "percent": -1.0 -> 1.0

drive_forward() [1/2]

Autonomously drive the robot forward a certain distance

Parameters

inches	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
dir	the direction we want to travel forward and backward
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Autonomously drive the robot forward a certain distance

inches	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
dir	the direction we want to travel forward and backward
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true if we have finished driving to our point

drive_forward() [2/2]

Use odometry to drive forward a certain distance using a custom feedback controller

Returns whether or not the robot has reached it's destination.

Parameters

inches	the distance to drive forward
dir	the direction we want to travel forward and backward
feedback	the custom feedback controller we will use to travel. controls the rate at which we accelerate and
	drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true when we have reached our target distance

Use odometry to drive forward a certain distance using a custom feedback controller

Returns whether or not the robot has reached it's destination.

Parameters

inches	the distance to drive forward
dir	the direction we want to travel forward and backward
feedback	the custom feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

drive_tank()

Drive the robot using differential style controls. left_motors controls the left motors, right_motors controls the right motors.

left_motors and right_motors are in "percent": -1.0 -> 1.0 $\,$

Parameters

left	the percent to run the left motors
right	the percent to run the right motors
power	modifies the input velocities left^power, right^power
bt	breaktype. What to do if the driver lets go of the sticks

drive_tank_raw()

Drive the robot raw-ly

Parameters

left	the percent to run the left motors (-1, 1)
right	the percent to run the right motors (-1, 1)

drive_to_point() [1/2]

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot. Here we use the default feedback controller from the drive_sys

Returns whether or not the robot has reached it's destination.

Parameters

X	the x position of the target
У	the y position of the target

dir	the direction we want to travel forward and backward
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot. Here we use the default feedback controller from the drive_sys

Returns whether or not the robot has reached it's destination.

Parameters

X	the x position of the target
У	the y position of the target
dir	the direction we want to travel forward and backward
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true if we have reached our target point

drive_to_point() [2/2]

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot.

Returns whether or not the robot has reached it's destination.

Parameters

X	the x position of the target
У	the y position of the target
dir	the direction we want to travel forward and backward
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot.

Returns whether or not the robot has reached it's destination.

X	the x position of the target
У	the y position of the target
dir	the direction we want to travel forward and backward
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true if we have reached our target point

get_position()

```
Pose2d TankDrive::get_position ()
```

Returns the Robot position as a Pose2d

modify_inputs()

Create a curve for the inputs, so that drivers have more control at lower speeds. Curves are exponential, with the default being squaring the inputs.

Parameters

input	the input before modification
power	the power to raise input to

Returns

input ^ power (accounts for negative inputs and odd numbered powers)

Modify the inputs from the controller by squaring / cubing, etc Allows for better control of the robot at slower speeds

Parameters

input	the input signal -1 -> 1
power	the power to raise the signal to

Returns

input^power accounting for any sign issues that would arise with this naive solution

pure_pursuit()

Drive the robot autonomously using a pure-pursuit algorithm - Input path with a set of waypoints - the robot will attempt to follow the points while cutting corners (radius) to save time (compared to stop / turn / start)

Parameters

path	The list of coordinates to follow, in order
dir	Run the bot forwards or backwards
feedback	The feedback controller determining speed
max_speed	Limit the speed of the robot (for pid / pidff feedbacks)
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

True when the path is complete

Drive the robot autonomously using a pure-pursuit algorithm - Input path with a set of waypoints - the robot will attempt to follow the points while cutting corners (radius) to save time (compared to stop / turn / start)

Parameters

path	The list of coordinates to follow, in order
dir	Run the bot forwards or backwards
feedback	The feedback controller determining speed
max_speed	Limit the speed of the robot (for pid / pidff feedbacks)

Returns

True when the path is complete

reset_auto()

```
void TankDrive::reset_auto ()
```

Reset the initialization for autonomous drive functions

stop()

```
void TankDrive::stop ()
```

Stops rotation of all the motors using their "brake mode"

turn_degrees() [1/2]

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses the defualt turning feedback of the drive system.

Parameters

	degrees	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
	max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
Ī	end_speed	the movement profile will attempt to reach this velocity by its completion

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses the defualt turning feedback of the drive system.

Parameters

degrees	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true if we turned te target number of degrees

turn_degrees() [2/2]

Autonomously turn the robot X degrees counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses PID + Feedforward for it's control.

Parameters

degrees	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses the specified feedback for it's control.

degrees	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true if we have turned our target number of degrees

turn_to_heading() [1/2]

Turn the robot in place to an exact heading relative to the field. 0 is forward. Uses the defualt turn feedback of the drive system

Parameters

heading_deg	the heading to which we will turn
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Turn the robot in place to an exact heading relative to the field. 0 is forward. Uses the defualt turn feedback of the drive system

Parameters

heading_deg	the heading to which we will turn
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true if we have reached our target heading

turn_to_heading() [2/2]

Turn the robot in place to an exact heading relative to the field. 0 is forward.

heading_deg	the heading to which we will turn
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Turn the robot in place to an exact heading relative to the field. 0 is forward.

Parameters

heading_deg	the heading to which we will turn
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true if we have reached our target heading

The documentation for this class was generated from the following files:

- · tank_drive.h
- · tank_drive.cpp

4.70 tracking_wheel_cfg_t Struct Reference

#include <odometry_nwheel.h>

Public Attributes

- double x
- double y
- · double theta rad
- · double radius

4.70.1 Detailed Description

OdometryNWheel

This class handles the code for an N-pod odometry setup, where there are N < WHEELS > free spinning omni wheels (dead wheels) placed in any known configuration on the robot.

Example of a possible wheel configuration:

$$+Y$$
 ------ $^{\wedge}$ $| === | | | | | | | | | | | | | | | === | | ------ | +------- > + X$

Where O is the center of rotation. The robot will monitor the changes in rotation of these wheels, use this to calculate a pose delta, then integrate the deltas over time to determine the robot's position.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

https://rit.enterprise.slack.com/files/U04112Y5RB6/F080M01KPA5/predictperpindiculars2.epdf 2024-2025 Notebook: Entries/Software Entries/Localization/N-Pod Odometry

Author

Jack Cammarata, Richie Sommers

Date

Nov 14 2024 tracking_wheel_cfg_t holds all the specifications for a single tracking wheel The units for x, y, and radius will determine the units of the position estimate

4.70.2 Member Data Documentation

radius

```
double tracking_wheel_cfg_t::radius
```

radius of the wheel

theta_rad

```
double tracking_wheel_cfg_t::theta_rad
```

angle between wheel direction and x axis in the robot frame

X

```
double tracking_wheel_cfg_t::x
```

x position of the center of the wheel

у

```
double tracking_wheel_cfg_t::y
```

y position of the center of the wheel

The documentation for this struct was generated from the following file:

• odometry_nwheel.h

4.71 Transform2d Class Reference

```
#include <transform2d.h>
```

Public Member Functions

- constexpr Transform2d ()
- Transform2d (const Translation2d &translation, const Rotation2d &rotation)
- Transform2d (const double &x, const double &y, const Rotation2d &rotation)
- Transform2d (const double &x, const double &y, const double &radians)
- Transform2d (const Translation2d &translation, const double &radians)
- Transform2d (const Eigen::Vector3d &transform_vector)
- Transform2d (const Pose2d &start, const Pose2d &end)
- Translation2d translation () const
- double x () const
- double y () const
- · Rotation2d rotation () const
- Transform2d inverse () const
- Transform2d operator* (const double &scalar) const
- Transform2d operator/ (const double &scalar) const
- Transform2d operator- () const
- bool operator== (const Transform2d & other) const

Friends

• std::ostream & operator<< (std::ostream &os, const Transform2d &transform)

4.71.1 Detailed Description

Class representing a transformation of a pose2d, or a linear difference between the components of poses.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

4.71.2 Constructor & Destructor Documentation

Transform2d() [1/7]

```
Transform2d::Transform2d () [constexpr]
```

Default Constructor for Transform2d

Transform2d() [2/7]

Constructs a transform given translation and rotation components.

Parameters

translation	the translational component of the transform.
rotation	the rotational component of the transform.

Transform2d() [3/7]

Constructs a transform given translation and rotation components.

Χ	the x component of the transform.
У	the y component of the transform.
rotation	the rotational component of the transform.

Transform2d() [4/7]

Constructs a transform given translation and rotation components.

Parameters

X	the x component of the transform.
У	the y component of the transform.
radians	the rotational component of the transform in radians.

Transform2d() [5/7]

Constructs a transform given translation and rotation components.

Parameters

translation	the translational component of the transform.
radians	the rotational component of the transform in radians.

Transform2d() [6/7]

Constructs a transform given translation and rotation components given as a vector.

Parameters

transform_vector	vector of the form [x, y, theta]
------------------	----------------------------------

Transform2d() [7/7]

Constructs a transform given translation and rotation components.

translation	the translational component of the transform.
rotation	the rotational component of the transform.

4.71.3 Member Function Documentation

inverse()

```
Transform2d Transform2d::inverse () const
```

Inverts the transform.

Returns

the inverted transform.

operator*()

Multiplies this transform by a scalar.

Parameters

scalar	the scalar to multiply this transform by.

operator-()

```
Transform2d Transform2d::operator- () const
```

Inverts the transform.

Returns

the inverted transform.

operator/()

Divides this transform by a scalar.

scalar	the scalar to divide this transform by.
--------	---

operator==()

Compares this to another transform.

Parameters

other the ot	ner transform to compare to.
other the ot	ner transform to compare to.

Returns

true if the components are within 1e-9 of each other.

rotation()

```
Rotation2d Transform2d::rotation () const
```

Returns the rotational component of the transform.

Returns

the rotational component of the transform.

translation()

```
Translation2d Transform2d::translation () const
```

Returns the translational component of the transform.

Returns

the translational component of the transform.

x()

```
double Transform2d::x () const
```

Returns the x component of the transform.

Returns

the x component of the transform.

y()

```
double Transform2d::y () const
```

Returns the y component of the transform.

Returns

the y component of the transform.

4.71.4 Friends And Related Symbol Documentation

operator <<

Sends a transform to an output stream. Ex. std::cout << transform;

prints "Transform2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"

The documentation for this class was generated from the following files:

- · transform2d.h
- · transform2d.cpp

4.72 Translation2d Class Reference

#include <translation2d.h>

Public Member Functions

- constexpr Translation2d ()
- Translation2d (const double &x, const double &y)
- Translation2d (const Eigen::Vector2d &vector)
- Translation2d (const double &r, const Rotation2d &theta)
- double x () const
- void setX (double x)
- double y () const
- void setY (double y)
- Rotation2d theta () const
- Eigen::Vector2d as_vector () const
- double get_mag () const
- · double norm () const
- Translation2d normalize () const
- double distance (const Translation2d &other) const
- Translation2d rotate_by (const Rotation2d &rotation) const
- Translation2d rotate_around (const Translation2d &other, const Rotation2d &rotation) const
- Translation2d operator+ (const Translation2d &other) const
- Translation2d operator- (const Translation2d &other) const
- Translation2d operator- () const
- Translation2d operator* (const double &scalar) const
- Translation2d operator/ (const double &scalar) const
- double operator* (const Translation2d &other) const
- bool operator== (const Translation2d &other) const

Friends

• std::ostream & operator<< (std::ostream &os, const Translation2d &translation)

4.72.1 Detailed Description

Class representing a point in 2d space with x and y coordinates.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

4.72.2 Constructor & Destructor Documentation

Translation2d() [1/4]

```
Translation2d::Translation2d () [inline], [constexpr]
```

Default Constructor for Translation2d

Translation2d() [2/4]

Constructs a Translation2d with the given x and y values.

Parameters

Χ	The x component of the translation.
у	The y component of the translation.

Translation2d() [3/4]

Constructs a Translation2d with the values from the given vector.

Parameters

<i>Vector</i>	The vector whose values will be used.

Translation2d() [4/4]

Constructs a Translation2d given polar coordinates of the form (r, theta).

r	The radius (magnitude) of the vector.
theta	The angle (direction) of the vector.

4.72.3 Member Function Documentation

as_vector()

```
Eigen::Vector2d Translation2d::as_vector () const
```

Returns the vector as an Eigen::Vector2d.

Returns

Eigen::Vector2d with the same values as the translation.

distance()

Returns the distance between two translations.

Returns

the distance between two translations.

get_mag()

```
double Translation2d::get_mag () const
```

Returns

the magnitide of the directions if it were a vector

norm()

```
double Translation2d::norm () const
```

Returns the norm/radius/magnitude/distance from origin.

Returns

the norm of the translation.

normalize()

```
Translation2d Translation2d::normalize () const
```

Changes the translation so that it has a vector magnitude of 1

Returns

the norm of the translation.

Returns a translation so that it has a vector magnitude of 1

Returns

the norm of the translation.

operator*() [1/2]

Returns this translation multiplied by a scalar.

```
[x] = [x] * [scalar] [y] = [y] * [scalar]
```

Parameters

scalar	the scalar to multiply by.
--------	----------------------------

Returns

this translation multiplied by a scalar.

operator*() [2/2]

Returns the dot product of two translations.

```
[scalar] = [x][otherx] + [y][othery]
```

Parameters

other the other translation to find the dot product with.

Returns

the scalar valued dot product.

operator+()

Returns the sum of two translations.

$$[x] = [x] + [otherx]; [y] = [y] + [othery];$$

other	the other translation to add to this translation.	
-------	---	--

Returns

the sum of the two translations.

operator-() [1/2]

```
Translation2d Translation2d::operator- () const
```

Returns the inverse of this translation. Equivalent to flipping the vector across the origin.

$$[x] = [-x][y] = [-y]$$

Returns

the inverse of this translation.

operator-() [2/2]

Returns the difference of two translations.

$$[x] = [x] - [otherx] [y] = [y] - [othery]$$

Parameters

other	the translation to subtract from this translation.

Returns

the difference of the two translations.

operator/()

Returns this translation divided by a scalar.

$$[x] = [x] / [scalar] [y] = [y] / [scalar]$$

Returns

this translation divided by a scalar.

operator==()

Compares two translations. Returns true if their components are each within 1e-9, to account for floating point error.

Parameters

other	the translation to compare to.
-------	--------------------------------

Returns

whether the two translations are equal.

rotate_around()

Applies a rotation to this translation around another given point.

```
[x] = [\cos, -\sin][x - otherx] + [otherx][y] = [\sin, \cos][y - othery] + [othery]
```

Parameters

other	the center of rotation.
rotation	the angle amount the translation will be rotated.

Returns

the translation that has been rotated.

rotate_by()

Applies a rotation to this translation around the origin.

Equivalent to multiplying a vector by a rotation matrix: $x = [\cos, -\sin][x] y = [\sin, \cos][y]$

rotation	the angle amount the translation will be rotated.

Returns

the new translation that has been rotated around the origin.

setX()

Sets the x value of the translation.

setY()

```
void Translation2d::setY ( double y)
```

Sets the y value of the translation.

theta()

```
Rotation2d Translation2d::theta () const
```

Returns the angle of the translation.

Returns

the angle of the translation.

x()

```
double Translation2d::x () const
```

Returns the x value of the translation.

Returns

the x value of the translation.

y()

```
double Translation2d::y () const
```

Returns the y value of the translation.

Returns

the y value of the translation.

4.72.4 Friends And Related Symbol Documentation

operator<<

Sends a translation to an output stream. Ex. std::cout << translation;

```
prints "Translation2d[x: (value), y: (value)]"
```

Sends a translation to an output stream. Ex. std::cout << translation;

```
prints "Translation2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- translation2d.h
- translation2d.cpp

4.73 TrapezoidProfile Class Reference

```
#include <trapezoid_profile.h>
```

Public Member Functions

- TrapezoidProfile (double max_v, double accel)
 - Construct a new Trapezoid Profile object.
- motion_t calculate (double time_s)

Run the trapezoidal profile based on the time that's ellapsed.

- void set_endpts (double start, double end)
- void set_accel (double accel)
- void set_max_v (double max_v)
- double get_movement_time ()

4.73.1 Detailed Description

Trapezoid Profile

This is a motion profile defined by an acceleration, maximum velocity, start point and end point. Using this information, a parametric function is generated, with a period of acceleration, constant velocity, and deceleration. The velocity graph looks like a trapezoid, giving it it's name.

If the maximum velocity is set high enough, this will become a S-curve profile, with only acceleration and deceleration.

This class is designed for use in properly modelling the motion of the robots to create a feedfoward and target for PID. Acceleration and Maximum velocity should be measured on the robot and tuned down slightly to account for battery drop.

Here are the equations graphed for ease of understanding: https://www.desmos.com/calculator/rkm3ivulyk

Author

Ryan McGee

Date

7/12/2022

4.73.2 Constructor & Destructor Documentation

TrapezoidProfile()

Construct a new Trapezoid Profile object.

Parameters

max↔ _v	Maximum velocity the robot can run at
accel	Maximum acceleration of the robot

4.73.3 Member Function Documentation

calculate()

Run the trapezoidal profile based on the time that's ellapsed.

time←	Time since start of movement
_s	

Returns

motion_t Position, velocity and acceleration

get_movement_time()

```
double TrapezoidProfile::get_movement_time ()
```

uses the kinematic equations to and specified accel and max_v to figure out how long moving along the profile would take

Returns

the time the path will take to travel

set_accel()

set_accel sets the acceleration this profile will use (the left and right legs of the trapezoid)

Parameters

accel the acceleration	n amount to use
------------------------	-----------------

set_endpts()

set_endpts defines a start and end position

Parameters

start	the starting position of the path
end	the ending position of the path

set_max_v()

sets the maximum velocity for the profile (the height of the top of the trapezoid)

max⊷	the maximum velocity the robot can travel at
_v	

The documentation for this class was generated from the following files:

- · trapezoid_profile.h
- trapezoid_profile.cpp

4.74 TurnDegreesCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- TurnDegreesCommand (TankDrive &drive_sys, Feedback &feedback, double degrees, double max_speed=1, double end_speed=0)
- bool run () override
- void on_timeout () override

4.74.1 Detailed Description

AutoCommand wrapper class for the turn_degrees function in the TankDrive class

4.74.2 Constructor & Destructor Documentation

TurnDegreesCommand()

Construct a TurnDegreesCommand Command

Parameters

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the turn
degrees	how many degrees to rotate
max_speed	0 -> 1 percentage of the drive systems speed to drive at

4.74.3 Member Function Documentation

on_timeout()

```
void TurnDegreesCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we timeout

run()

```
bool TurnDegreesCommand::run () [override]
```

Run turn_degrees Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive_commands.h
- drive_commands.cpp

4.75 TurnToHeadingCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- TurnToHeadingCommand (TankDrive &drive_sys, Feedback &feedback, double heading_deg, double speed=1, double end_speed=0)
- bool run () override
- void on_timeout () override

4.75.1 Detailed Description

AutoCommand wrapper class for the turn to heading() function in the TankDrive class

4.75.2 Constructor & Destructor Documentation

TurnToHeadingCommand()

Construct a TurnToHeadingCommand Command

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the drive
heading_deg	the heading to turn to in degrees
max_speed	0 -> 1 percentage of the drive systems speed to drive at

4.75.3 Member Function Documentation

on_timeout()

```
void TurnToHeadingCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we don't hit our target

run()

```
bool TurnToHeadingCommand::run () [override]
```

Run turn_to_heading Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive_commands.h
- · drive_commands.cpp

4.76 Twist2d Class Reference

#include <twist2d.h>

Public Member Functions

- constexpr Twist2d ()
- Twist2d (const double &dx, const double &dy, const double &dtheta)
- Twist2d (const Eigen::Vector3d &twist_vector)
- · double dx () const
- · double dy () const
- double dtheta () const
- bool operator== (const Twist2d &other) const
- Twist2d operator* (const double &scalar) const
- Twist2d operator/ (const double &scalar) const

Friends

• std::ostream & operator<< (std::ostream &os, const Twist2d &twist)

4.76.1 Detailed Description

Class representing a difference between two poses, more specifically a distance along an arc from a pose.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

4.76.2 Constructor & Destructor Documentation

Twist2d() [1/3]

```
Twist2d::Twist2d () [constexpr]
```

Default Constructor for Twist2d

Twist2d() [2/3]

Constructs a twist with given translation and angle deltas.

Parameters

dx	the linear dx component.
dy	the linear dy component.
dtheta	the angular dtheta component.

Twist2d() [3/3]

Constructs a twist with given translation and angle deltas.

Parameters

4	
I twist vector	vector of the form [dx, dy, dtheta]
	[

4.76.3 Member Function Documentation

dtheta()

```
double Twist2d::dtheta () const
```

Returns the angular dtheta component.

Returns

the angular dtheta component.

dx()

```
double Twist2d::dx () const
```

Returns the linear dx component.

Returns

the linear dx component.

dy()

```
double Twist2d::dy () const
```

Returns the linear dy component.

Returns

the linear dy component.

operator*()

Multiplies this twist by a scalar.

Parameters

operator/()

Divides this twist by a scalar.

scalar	the scalar value to divide by.
--------	--------------------------------

operator==()

Compares this to another twist.

Parameters

Returns

true if each of the components are within 1e-9 of each other.

4.76.4 Friends And Related Symbol Documentation

operator<<

Sends a twist to an output stream. Ex. std::cout << twist;

```
prints "Twist2d[dx: (value), dy: (value), drad: (radians)]"
```

Sends a twist to an output stream. Ex. std::cout << twist;

```
prints "Twist2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- twist2d.h
- twist2d.cpp

4.77 WaitUntilCondition Class Reference

Waits until the condition is true.

```
#include <auto_command.h>
```

4.77.1 Detailed Description

Waits until the condition is true.

The documentation for this class was generated from the following file:

· auto_command.h

4.78 WaitUntilUpToSpeedCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- WaitUntilUpToSpeedCommand (Flywheel &flywheel, int threshold_rpm)
- bool run () override

4.78.1 Detailed Description

AutoCommand that listens to the Flywheel and waits until it is at its target speed +/- the specified threshold

4.78.2 Constructor & Destructor Documentation

WaitUntilUpToSpeedCommand()

Creat a WaitUntilUpToSpeedCommand

Parameters

flywheel	the flywheel system we are commanding
threshold_rpm	the threshold over and under the flywheel target RPM that we define to be acceptable

4.78.3 Member Function Documentation

run()

```
bool WaitUntilUpToSpeedCommand::run () [override]
```

Run spin_manual Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · flywheel commands.h
- flywheel_commands.cpp

Index

accel	choice
OdometryBase, 71	AutoChooser, 10
add	cobs_decode
CommandController, 16, 17	OdometrySerial, 75
GenericAuto, 42	cobs_encode
add_async	OdometrySerial, 76
GenericAuto, 42	CommandController, 16
add_cancel_func	add, 16, 17
CommandController, 17	add_cancel_func, 17
add_delay	add_delay, 18
CommandController, 18	CommandController, 16
GenericAuto, 43	last_command_timed_out, 18
add_entry	run, 18
ExponentialMovingAverage, 27	Condition, 18
MovingAverage, 63	config
ang_accel_deg	PID, 89
OdometryBase, 71	control_continuous
ang_speed_deg	
OdometryBase, 71	control_manual
as vector	Lift< T >, 46
Translation2d, 141	control_setpoints
Async, 8	Lift < T >, 46
auto_drive	Core, 1
MecanumDrive, 55	current pos
auto turn	OdometryBase, 71
MecanumDrive, 55	current_state
AutoChooser, 9	StateMachine System, IDType, Message, de-
AutoChooser, 9	lay_ms, do_log >, 118
choice, 10	CustomEncoder, 19
get_choice, 10	CustomEncoder, 19
list, 10	position, 19
AutoChooser::entry_t, 26	rotation, 20
name, 26	setPosition, 20
namo, 20	setRotation, 20
background_task	velocity, 20
OdometryBase, 68	voiciny, 20
BasicSolenoidSet, 10	degrees
BasicSolenoidSet, 11	Rotation2d, 103
run, 11	DelayCommand, 21
BasicSpinCommand, 11	DelayCommand, 21
BasicSpinCommand, 12	run, 22
run, 12	distance
BasicStopCommand, 13	Translation2d, 141
BasicStopCommand, 13	double_or
run, 13	Serializer, 111
bool or	draw
Serializer, 111	screen::FunctionPage, 41
BrakeType	screen::OdometryPage, 73
TankDrive, 123	screen::Page, 83
Branch, 14	screen::PIDPage, 92
ButtonWidget	screen::StatsPage, 119
screen::ButtonWidget, 14, 15	drive
COTOCIII. Dattori Wiagot, 17, 10	MecanumDrive, 56
calculate	drive_arcade
FeedForward, 31	TankDrive, 124
TrapezoidProfile, 147	Tambiro, ILI

drive_correction_cutoff	kA, 32
robot_specs_t, 101	kG, 32
drive_forward	kS, 32
TankDrive, 124, 125	kV, 33
drive_raw	Filter, 33
MecanumDrive, 57	Flywheel, 33
drive_tank	Flywheel, 34
TankDrive, 125	get motors, 35
drive_tank_raw	get target, 35
TankDrive, 126	getRPM, 35
drive_to_point	is_on_target, 35
TankDrive, 126, 127	Page, 35
DriveForwardCommand, 22	spin_manual, 35
DriveForwardCommand, 22	spin_rpm, 36
on_timeout, 23	SpinRpmCmd, 36
run, 23	spinRPMTask, 37
DriveStopCommand, 23	stop, 36
DriveStopCommand, 23	WaitUntilUpToSpeedCmd, 37
run, 24	FlywheelStopCommand, 37
	•
DriveToPointCommand, 24	FlywheelStopCommand, 37
DriveToPointCommand, 24, 25	run, 38
run, 25	FlywheelStopMotorsCommand, 38
dtheta	FlywheelStopMotorsCommand, 38
Twist2d, 153	run, 39
dx	FlywheelStopNonTasksCommand, 39
Twist2d, 153	FunctionCommand, 39
dy	FunctionCondition, 40
Twist2d, 153	FunctionPage
	screen::FunctionPage, 41
1	
end_async	Canadia Auta 10
OdometryBase, 69	GenericAuto, 42
OdometryBase, 69 error_method	add, 42
OdometryBase, 69 error_method PID::pid_config_t, 90	add, 42 add_async, 42
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE	add, 42 add_async, 42 add_delay, 43
OdometryBase, 69 error_method PID::pid_config_t, 90	add, 42 add_async, 42 add_delay, 43 run, 43
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE	add, 42 add_async, 42 add_delay, 43 run, 43 get
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin Rotation2d, 104	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69 get_async
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin Rotation2d, 104 f_tan	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69 get_async Lift< T >, 47
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin Rotation2d, 104 f_tan Rotation2d, 104	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69 get_async Lift< T >, 47 get_choice
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin Rotation2d, 104 f_tan Rotation2d, 104 Feedback, 28	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69 get_async Lift< T >, 47 get_choice AutoChooser, 10 get_error
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin Rotation2d, 104 f_tan Rotation2d, 104 Feedback, 28 get, 29	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69 get_async Lift< T >, 47 get_choice AutoChooser, 10 get_error PID, 87
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin Rotation2d, 104 f_tan Rotation2d, 104 Feedback, 28 get, 29 init, 29	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69 get_async Lift< T >, 47 get_choice AutoChooser, 10 get_error PID, 87 get_mag
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin Rotation2d, 104 f_tan Rotation2d, 104 Feedback, 28 get, 29 init, 29 is_on_target, 29	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69 get_async Lift< T >, 47 get_choice AutoChooser, 10 get_error PID, 87 get_mag Translation2d, 141
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin Rotation2d, 104 f_tan Rotation2d, 104 Feedback, 28 get, 29 init, 29 is_on_target, 29 set_limits, 30 update, 30	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69 get_async Lift< T >, 47 get_choice AutoChooser, 10 get_error PID, 87 get_mag Translation2d, 141 get_motion
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin Rotation2d, 104 f_tan Rotation2d, 104 Feedback, 28 get, 29 init, 29 is_on_target, 29 set_limits, 30 update, 30 FeedForward, 30	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69 get_async Lift< T >, 47 get_choice AutoChooser, 10 get_error PID, 87 get_mag Translation2d, 141 get_motion MotionController, 59
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin Rotation2d, 104 f_tan Rotation2d, 104 Feedback, 28 get, 29 init, 29 is_on_target, 29 set_limits, 30 update, 30 FeedForward, 30 calculate, 31	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69 get_async Lift< T >, 47 get_choice AutoChooser, 10 get_error PID, 87 get_mag Translation2d, 141 get_motion MotionController, 59 get_motors
OdometryBase, 69 error_method PID::pid_config_t, 90 ERROR_TYPE PID, 86 exp Pose2d, 95 ExponentialMovingAverage, 26 add_entry, 27 ExponentialMovingAverage, 27 get_size, 28 get_value, 28 f_cos Rotation2d, 103 f_sin Rotation2d, 104 f_tan Rotation2d, 104 Feedback, 28 get, 29 init, 29 is_on_target, 29 set_limits, 30 update, 30 FeedForward, 30	add, 42 add_async, 42 add_delay, 43 run, 43 get Feedback, 29 MotionController, 59 PID, 87 TakeBackHalf, 121 get_accel OdometryBase, 69 get_angular_accel_deg OdometryBase, 69 get_angular_speed_deg OdometryBase, 69 get_async Lift< T >, 47 get_choice AutoChooser, 10 get_error PID, 87 get_mag Translation2d, 141 get_motion MotionController, 59

TrapezoidProfile, 148	kA
get_points	FeedForward::ff_config_t, 32
PurePursuit::Path, 84	kG
get_pose2d	FeedForward::ff_config_t, 32
OdometrySerial, 76	kS
get_position	FeedForward::ff_config_t, 32
OdometryBase, 69	kV
OdometrySerial, 76	FeedForward::ff_config_t, 33
TankDrive, 128	
get_radius	last_command_timed_out
PurePursuit::Path, 84	CommandController, 18
get_sensor_val	Lift
PID, 87	Lift < T >, 45
get_setpoint	Lift< T >, 45
Lift< T >, 47	control_continuous, 46
get_size	control_manual, 46
ExponentialMovingAverage, 28	control_setpoints, 46
MovingAverage, 63	get_async, 47
get_speed	get_setpoint, 47
OdometryBase, 70	hold, 47
get_target	home, 47
Flywheel, 35	Lift, 45
PID, 87	set_async, 47
get value	set_position, 48
ExponentialMovingAverage, 28	set_sensor_function, 48
MovingAverage, 63	set_sensor_reset, 48
getRPM	set_setpoint, 48
Flywheel, 35	Lift< T >::lift_cfg_t, 49
1 19 111001, 00	list
handle	AutoChooser, 10
OdometryBase, 72	Log
has_message	Logger, 50, 51
StateMachine< System, IDType, Message, de-	log
lay_ms, do_log >::MaybeMessage, 54	Pose2d, 95
hold	Logf
Lift < T >, 47	Logger, 51
home	Logger, 49
Lift< T >, 47	Log, 50, 51
	Logf, 51
IfTimePassed, 44	Logger, 50
init	LogIn, 51, 52
Feedback, 29	LogIn
MotionController, 60	Logger, 51, 52
PID, 87	
TakeBackHalf, 121	MaybeMessage
InOrder, 44	StateMachine < System, IDType, Message, de-
int_or	lay_ms, do_log >::MaybeMessage, 53
Serializer, 111	MecanumDrive, 54
inverse	auto_drive, 55
Transform2d, 137	auto_turn, 55
is_on_target	drive, 56
Feedback, 29	drive_raw, 57
Flywheel, 35	MecanumDrive, 55
MotionController, 60	MecanumDrive::mecanumdrive_config_t, 57
PID, 88	message
TakeBackHalf, 121	StateMachine < System, IDType, Message, de-
is_valid	lay_ms, do_log >::MaybeMessage, 54
PurePursuit::Path, 85	modify_inputs TankDrive, 128

motion_t, 57	cobs_encode, 76
MotionController, 58	get_pose2d, 76
get, 59	get_position, 76
get_motion, 59	OdometrySerial, 75
init, 60	receive_cobs_packet, 77
is_on_target, 60	send_config, 77
MotionController, 59	set_position, 77
set_limits, 60	update, 78
tune_feedforward, 61	OdometryTank, 78
update, 61	OdometryTank, 79, 80
MotionController::m_profile_cfg_t, 52	set_position, 81
MovingAverage, 62	update, 81
add_entry, 63	OdomSetPosition, 81
get_size, 63	OdomSetPosition, 81
get_value, 63	run, 82
MovingAverage, 62	off_axis_center_dist
mut	Odometry3Wheel::odometry3wheel_cfg_t, 66
OdometryBase, 72	on_target_time
odomoti y Baoo, 72	PID::pid_config_t, 90
name	on_timeout
AutoChooser::entry t, 26	DriveForwardCommand, 23
None	PurePursuitCommand, 100
TankDrive, 123	TurnDegreesCommand, 150
norm	
Translation2d, 141	TurnToHeadingCommand, 151
normalize	operator<<
	Pose2d, 99
Translation2d, 141	Rotation2d, 108
Odometry3Wheel, 64	Transform2d, 139
Odometry3Wheel, 65	Translation2d, 146
tune, 65	Twist2d, 154
	operator+
update, 66	Pose2d, 96
Odometry3Wheel::odometry3wheel_cfg_t, 66	Rotation2d, 104
off_axis_center_dist, 66	Translation2d, 142
wheel_diam, 66	operator-
wheelbase_dist, 67	Pose2d, 96
OdometryBase, 67	Rotation2d, 105
accel, 71	Transform2d, 137
ang_accel_deg, 71	Translation2d, 143
ang_speed_deg, 71	operator/
background_task, 68	Pose2d, 96
current_pos, 71	Rotation2d, 105
end_async, 69	Transform2d, 137
get_accel, 69	Translation2d, 143
get_angular_accel_deg, 69	Twist2d, 153
get_angular_speed_deg, 69	operator==
get_position, 69	Pose2d, 96
get_speed, 70	Rotation2d, 106
handle, 72	Transform2d, 138
mut, 72	Translation2d, 144
OdometryBase, 68	Twist2d, 154
set_position, 70	•
smallest_angle, 70	operator*
speed, 72	Pose2d, 95
update, 71	Rotation2d, 104
OdometryPage	Transform2d, 137
screen::OdometryPage, 73	Translation2d, 142
OdometrySerial, 74	Twist2d, 153
cobs_decode, 75	Paga
oobs_uecoue, /o	Page

FI 1 1 0F	,
Flywheel, 35	radians
Parallel, 83	Rotation2d, 106
Path	radius
PurePursuit::Path, 84	tracking_wheel_cfg_t, 133
PID, 85	receive_cobs_packet
config, 89	OdometrySerial, 77
ERROR_TYPE, 86	Rect, 100
get, 87	relative_to
get_error, 87	Pose2d, 97
get_sensor_val, 87	reset
get_target, 87	PID, 88
init, 87	reset_auto
is_on_target, 88	TankDrive, 129
PID, 86	revolutions
reset, 88	Rotation2d, 106
set_limits, 88	robot_specs_t, 100
set_target, 88	drive_correction_cutoff, 101
update, 89	rotate_around
PID::pid_config_t, 90	Translation2d, 144
error_method, 90	rotate_by
on_target_time, 90	Translation2d, 144
PIDPage	rotation
screen::PIDPage, 91	CustomEncoder, 20
Pose2d, 92	Pose2d, 97
exp, 95	Transform2d, 138
log, 95	Rotation2d, 101
operator<<, 99	degrees, 103
operator+, 96	f_cos, 103
operator-, 96	f_sin, 104
operator/, 96	f_tan, 104
operator==, 96	operator<<, 108
operator*, 95	operator+, 104
Pose2d, 93, 94	operator-, 105
relative_to, 97	operator/, 105
rotation, 97	operator==, 106
setRotationDeg, 97	operator*, 104
setRotationRad, 97	radians, 106
setX, 97	revolutions, 106
setY, 98	Rotation2d, 102, 103
transform_by, 98	rotation_matrix, 106
translation, 98	setDeg, 107
x, 98	setRad, 107
y, 98	wrapped_degrees_180, 107
position	wrapped_degrees_360, 107
CustomEncoder, 19	wrapped_radians_180, 107
pure_pursuit	wrapped_radians_360, 108
TankDrive, 128	wrapped_revolutions_180, 108
PurePursuit::hermite_point, 43	wrapped_revolutions_360, 108
PurePursuit::Path, 84	rotation_matrix
get_points, 84	Rotation2d, 106
get_radius, 84	run
is_valid, 85	BasicSolenoidSet, 11
Path, 84	BasicSpinCommand, 12
PurePursuit::spline, 116	BasicStopCommand, 13
PurePursuitCommand, 99	CommandController, 18
on_timeout, 100	DelayCommand, 22
PurePursuitCommand, 99	DriveForwardCommand, 23
run, 100	DriveStopCommand, 24

DriveToPointCommand, 25 FlywheelStopCommand, 38 FlywheelStopMotorsCommand, 39 GenericAuto, 43 OdomSetPosition, 82 PurePursuitCommand, 100 SpinRPMCommand, 116 TurnDegreesCommand, 151 WaitUntilUpToSpeedCommand, 155 save_to_disk Serializer, 112 screen::ButtonWidget, 14 ButtonWidget, 14, 15 update, 15 screen::FunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 83 screen::PIDPage, 91 draw, 92 PIDPage, 91 update, 92 screen::ScreenData, 109 screen::SiderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine < System, IDType, Message, delay_ms, do_log >, 118 Serializer, 110 set_bool, 112 set_double Serializer, 112 set_double Set_aclouble Serializer, 112 set_limits Feedback, 30 MotionController, 60 PID, 88 set_max TakeBackHalf, 121 set_limits Feedback, 30 MotionController, 60 PID, 88 set_max TakeBackHalf, 121 set_limits Feedback, 30 MotionController, 60 PID, 88 set_senscr_reset Lift < T >, 48 set_senscr_reset Lift < T >, 48 set_sensor_reset Lift < T >,
FlywheelStopMotorsCommand, 39 GenericAuto, 43 Serializer, 112 Set_endpts
GenericAuto, 43
GenericAuto, 43
OdomSetPosition, 82 PurePursuitCommand, 100 SpinRPMCommand, 116 TurnDegreesCommand, 150 TurnToHeadingCommand, 151 WaitUntilUpToSpeedCommand, 155 save_to_disk Serializer, 112 screen::ButtonWidget, 14 ButtonWidget, 14, 15 update, 15 screen::FunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 screen::Page, 82 draw, 83 update, 83 screen::PIDPage, 91 draw, 92 PIDPage, 91 draw, 92 PIDPage, 91 draw, 92 Screen::SirderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 int_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 set_int Serializer, 112 set_int Serializer, 112 set_limits Set_limits Serializer, 112 set_limits TakeBackHalf, 121 set_look, 30 MotionController, 60 PID, 88 TakeBackHalf, 121 set_look, 30 MotionController, 60 PID, 88 set_sensor_function Li
PurePursuitCommand, 100
SpinRPMCommand, 116 TurnDegreesCommand, 150 TurnToHeadingCommand, 151 WaitUntilUpToSpeedCommand, 155 save_to_disk Serializer, 112 screen::ButtonWidget, 14 ButtonWidget, 14, 15 update, 15 screen::FunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 screen::OdometryPage, 72 draw, 73 update, 73 screen::Page, 82 draw, 83 update, 83 screen::PIDPage, 91 draw, 92 PIDPage, 91 draw, 92 PIDPage, 91 draw, 92 pricen::SiderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 draw, 119 StatsPage, 119 draw, 119 StatsPage, 119 draw, 119 StatsPage, 119 draw, 119 StateMachine< System, IDType, Message, delay, message StateMachine< System, IDType, Message, delay, message, delay, message, delay, message StateMachine< System, IDType, Message, delay, message, delay, message, delay, message, delay, message StateMachine< System, IDType, Message, delay, message,
TurnDegreesCommand, 150 TurnToHeadingCommand, 151 WaitUntilUpToSpeedCommand, 155 Save_to_disk Serializer, 112 Screen::ButtonWidget, 14 ButtonWidget, 14, 15 update, 15 screen::ChunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 Screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 Screen::Page, 82 draw, 83 update, 83 Screen::PIDPage, 91 draw, 92 PIDPage, 91 update, 92 Screen::ScreenData, 109 screen::SliderWidget, 114 update, 114 screen::SliderWidget, 113 SliderWidget, 114 update, 119 StatsPage, 119 update, 119 StatsPage, 119 update, 119 Send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 110 set_limits Feedback, 30 MotionController, 60 PID, 88 Set_max_v TrapezoidProfile, 148 set_position Lift< 7 >, 48 OdometrySase, 70 Set sensor_reset Lift< T >, 48 set_sensor_function Lift< T >, 48 set_sensor_reset Lift< T >, 48 set_sensor_function Lift< T >, 48 set_sensor_function Lift< T >, 48 set_sensor_reset Lift< T >, 48 set_sensor_function Lift< T >, 48 set_sensor_reset Lift< T >, 48 set_
TurnToHeadingCommand, 151 WaitUntilUpToSpeedCommand, 155 Save_to_disk Serializer, 112 Screen::ButtonWidget, 14 ButtonWidget, 14, 15 update, 15 Screen::FunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 Screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 Screen::Page, 82 draw, 83 update, 83 Screen::PIDPage, 91 update, 92 PIDPage, 91 update, 14 Screen::StatesPage, 119 draw, 119 StatsPage, 119 draw, 119 StatsPage, 119 draw, 119 StatsPage, 119 draw, 119 Set_limits Feedback, 30 MotionController, 60 PID, 88 TakeBackHalf, 121 set_max \ TrapezoidProfile, 148 set_position Lift< T >, 48 Set_sensor_function Lift< T >, 48 Set_sensor_feset Lift< T >, 48 Set_sensor_feset Lift< T >, 48 Set_sensor_feset Lift< T >, 48 Set_seriont Lift< T >, 48 Set_sensor_function Clift< T >, 48 Set_sensor_feset Lift< T >, 48 Set_sensor_feset
WaitUntilUpToSpeedCommand, 155 Seedback, 30 MotionController, 60 PID, 88 TakeBackHalf, 121 Setems: FunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 Screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 Screen::Page, 82 draw, 83 update, 83 Screen::BlDPage, 91 update, 92 PIDPage, 91 update, 14 Screen::ScreenData, 109 Screen::ScreenData, 109 Screen::ScreenData, 119 draw, 119 StatsPage, 119 update, 114 screen::ScreenData, 109 ScreenData, 109 ScreenData, 109 ScreenData, 109 ScreenData, 109
Save_to_disk
save_to_disk Serializer, 112 screen::ButtonWidget, 14 ButtonWidget, 14, 15 update, 15 screen::FunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 screen::Page, 82 draw, 83 update, 83 screen::PIDPage, 91 draw, 92 PIDPage, 91 draw, 92 PIDPage, 91 draw, 92 Screen::ScreenData, 109 screen::SliderWidget, 113 SliderWidget, 114 update, 119 set_senser, ease lay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 Set_max_v TrapezoidProfile, 148 set_position Lift< T >, 48 set_position Lift< T >, 48 set_sensor_function Lift< T >,
Serializer, 112 screen::ButtonWidget, 14 ButtonWidget, 14, 15 update, 15 screen::FunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 screen::Plage, 82 draw, 83 update, 83 screen::PlDPage, 91 draw, 92 PlDPage, 91 update, 92 screen::SiderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, lay_ms, do_log >, 118 Serializer, 100 bool_or, 111 int_or, 111 save_to_clisk, 112 Set_max_v TrapezoidProfile, 148 set_sensor_feret Lift < T <, 48 set_sensor_feret Lift < T <, 48 set_sensor_feret Lift
screen::ButtonWidget, 14 ButtonWidget, 14, 15 update, 15 screen::FunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 Screen::Page, 82 draw, 83 update, 83 screen::PlDPage, 91 draw, 92 PIDPage, 91 draw, 92 PIDPage, 91 update, 92 screen::SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_clisk, 112 Serializer, 110 set_bool, 112 set_double, 114 set_position Lift< T >, 48 set_sensor_reset Lift< T >, 48 set_sensor_tolon clodemetryBase, 70 odometryBase, 70 odometryBase, 70 set_max v TrapezoidProfile, 14 set_position Lift< T >, 48 se
ButtonWidget, 14, 15 update, 15 screen::FunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 screen::PlDPage, 91 draw, 92 PIDPage, 91 update, 92 screen::StatePage, 119 draw, 119 StatsPage, 119 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine < System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 TrapezoidProfile, 148 set_position Lift < T >, 48 OdometryBase, 70
ButtonWidget, 14, 15 update, 15 screen::FunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 screen::Page, 82 draw, 83 update, 83 screen::PIDPage, 91 draw, 92 PIDPage, 91 update, 92 screen::ScreenData, 109 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 114 screen::StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 110 set_bool, 112 set_double, 112 TrapezoidProfile, 148 set_position Lift< T >, 48 OdometryBase, 70
update, 15 screen::FunctionPage, 40 draw, 41 FunctionPage, 41 update, 41 screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 screen::PlDPage, 82 draw, 83 update, 83 screen::PlDPage, 91 draw, 92 PlDPage, 91 update, 92 screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 int_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 set
screen::FunctionPage, 40 Lift< T >, 48 draw, 41 OdometryBase, 70 FunctionPage, 41 OdometrySerial, 77 update, 41 Screen::OdometryPage, 72 draw, 73 Set_sensor_function OdometryPage, 73 Lift < T >, 48 update, 73 Lift < T >, 48 screen::Page, 82 Lift < T >, 48 draw, 83 Lift < T >, 48 update, 73 Lift < T >, 48 screen::Page, 82 Lift < T >, 48 draw, 83 Lift < T >, 48 update, 73 Lift < T >, 48 set_serpoint Lift < T >, 48 set_setpoint Lift < T >, 48 <
draw, 41 FunctionPage, 41 update, 41 Screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 83 Update, 83 Update, 83 Update, 83 Update, 83 Update, 91 Update, 92 Update, 92 Update, 92 Update, 92 Update, 92 Update, 114 Update, 114 Update, 114 Update, 114 Update, 114 Update, 119 Update
FunctionPage, 41 update, 41 screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 Screen::Page, 82 draw, 83 update, 83 screen::PIDPage, 91 draw, 92 PIDPage, 91 update, 92 screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 int_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 set_double, 112 set_double, 112 set_sensor_function Lift < T >, 48 set_sensor_reset Lift < T >, 48 set_setpoint Lift < T >,
update, 41 screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 screen::Page, 82 draw, 83 update, 83 screen::PIDPage, 91 draw, 92 PIDPage, 91 update, 92 screen::ScreenData, 109 screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometryPage, 73 setRotationDeg StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 100 setRod lay_ms, do_log >, 118 Serializer, 110 set_bool, 112 set_double, 112 Set_draw, 13 set_sensor_function Lift< T >, 48 set_sensor_reset Lift< T >, 48 set_sende
screen::OdometryPage, 72 draw, 73 OdometryPage, 73 update, 73 screen::Page, 82 draw, 83 update, 83 screen::PIDPage, 91 draw, 92 PIDPage, 91 update, 92 screen::ScreenData, 109 screen::SdatsPage, 119 draw, 119 StatsPage, 119 update, 114 screen::StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 set_sensor_function Lift< T >, 48 set_sensor_reset Lift< T >, 48 set_setpoint Lift< T >, 48 set_setpoint Lift< T >, 48 set_sensor_reset Lift< T >, 48 set_sensor_reset Lift< T >, 48 set_sensor_function Lift< T >, 48 set_sensor_fuction Lift< T >, 48 set_sensor_fuction Lift< T >, 48 set_sensor_fuction Li
draw, 73
OdometryPage, 73 update, 73 update, 73 screen::Page, 82 draw, 83 update, 83 screen::PIDPage, 91 draw, 92 PIDPage, 91 update, 92 screen::ScreenData, 109 screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine < System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 int_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 Set_sensor_reset Lift < T >, 48 set_setpoint Lift < T >, 48 set_setp
update, 73 screen::Page, 82 draw, 83 update, 83 screen::PIDPage, 91 draw, 92 PIDPage, 91 update, 92 screen::ScreenData, 109 screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 int_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 Serializer, 101 set_bool, 112 set_dret Lift< T >, 48 set_setpoint
screen::Page, 82 draw, 83 update, 83 screen::PIDPage, 91 draw, 92 PIDPage, 91 update, 92 screen::ScreenData, 109 screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 int_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 set_string Serializer, 113 set_target PID, 88 setDeg Rotation2d, 107 setPosition CustomEncoder, 20 setRad Rotation2d, 107 setRotation CustomEncoder, 20 setRotationDeg Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
draw, 83
Lift < T > , 48
update, 83 set_string screen::PIDPage, 91 Serializer, 113 draw, 92 pIDPage, 91 pID, 88 update, 92 setDeg screen::ScreenData, 109 Rotation2d, 107 screen::SliderWidget, 113 setPosition SliderWidget, 114 CustomEncoder, 20 update, 114 setRad screen::StatsPage, 119 Rotation2d, 107 draw, 119 setRotation StatsPage, 119 CustomEncoder, 20 update, 119 setRotationDeg setRotation CustomEncoder, 20 setRotationDeg Pose2d, 97 setRotationDeg Pose2d, 97 setX Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY bool_or, 111 soetPose2d, 98 int_or, 111 save_to_disk, 112 Serializer, 110 screen::SliderWidget set_adouble, 112 smallest_angle OdometryBase, 70
screen::PIDPage, 91 draw, 92 PIDPage, 91 update, 92 screen::ScreenData, 109 screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 Serializer, 29 Serializer, 109 Serializer, 100 set_lay_ms, do_log >, 118 Serializer, 110 set_bool, 112 set_double, 112 Serializer, 20 Serializer, 100 Serializer, 100 Serializer, 100 Serializer, 110 set_bool, 112 set_double, 112 Serializer, 100 Serializer, 100 Serializer, 110 set_bool, 112 set_double, 112 Serializer, 20 Serializer, 100 Serializer, 110 Se
draw, 92 PIDPage, 91 update, 92 screen::ScreenData, 109 screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 Set Larget PID, 88 setDeg Rotation2d, 107 setPosition CustomEncoder, 20 setRad Rotation2d, 107 setRotation CustomEncoder, 20 setRotationDeg Pose2d, 97 setRotationRad Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 13 smallest_angle OdometryBase, 70
PIDPage, 91 update, 92 screen::ScreenData, 109 screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 PID, 88 setDeg Rotation2d, 107 setPosition CustomEncoder, 20 setRad Rotation2d, 107 setRotation CustomEncoder, 20 setRotationDeg Pose2d, 97 setRotationRad Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 screen::SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
update, 92 screen::ScreenData, 109 screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine < System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_double, 112 set_double, 117 setPosition CustomEncoder, 20 setRotation CustomEncoder, 20 setRotati
screen::ScreenData, 109 screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine < System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 SetRotation CustomEncoder, 20 setRotationDeg Pose2d, 97 setRotationRad Pose2d, 97 setX Pose2d, 97 Translation2d, 145 SetY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
screen::SliderWidget, 113 SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 SetPosition CustomEncoder, 20 setRotationDeg Pose2d, 97 setRotationRad Pose2d, 97 setX Pose2d, 97 Translation2d, 145 SetY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
SliderWidget, 114 update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 SetRotation CustomEncoder, 20 setRotationDeg Pose2d, 97 setRotationRad Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
update, 114 screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 SetRotation CustomEncoder, 20 setRotationDeg Pose2d, 97 setRotationRad Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
screen::StatsPage, 119 draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 SetRotation CustomEncoder, 20 setRotationDeg Pose2d, 97 setRotationRad Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
draw, 119 StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 SetRotationDeg Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
StatsPage, 119 update, 119 send_config OdometrySerial, 77 send_message StateMachine < System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 CustomEncoder, 20 setRotationDeg Pose2d, 97 setRotationRad Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
update, 119 send_config OdometrySerial, 77 send_message StateMachine < System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 SetRotationDeg Pose2d, 97 setRotationRad Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
update, 119 send_config OdometrySerial, 77 setRotationDeg Pose2d, 97 setRotationRad Pose2d, 97 setRotationRad Pose2d, 97 setX lay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 setRotationDeg Pose2d, 97 setRotationRad Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
send_config OdometrySerial, 77 setRotationRad Pose2d, 97 setRotationRad Pose2d, 97 StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 double_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 SetRotationRad Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
OdometrySerial, 77 send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 int_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 SetRotationRad Pose2d, 97 setX Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
send_message StateMachine< System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 int_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 Serializer, 12 Serializer, 12 Serializer, 13 Serializer, 14 Serializer, 15 Serializer, 16 Serializer, 17 Serializ
StateMachine System, IDType, Message, delay_ms, do_log >, 118 Serializer, 109 bool_or, 111 double_or, 111 int_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 Set_A Pose2d, 97 Translation2d, 145 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
lay_ms, do_log >, 118 Pose2d, 97 Serializer, 109 bool_or, 111 double_or, 111 setY Pose2d, 98 int_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
Serializer, 109 Translation2d, 145 bool_or, 111 setY double_or, 111 Pose2d, 98 int_or, 111 Translation2d, 145 save_to_disk, 112 SliderWidget Serializer, 110 screen::SliderWidget, 11 set_bool, 112 smallest_angle OdometryBase, 70
bool_or, 111 double_or, 111 setY int_or, 111 save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 bool_or, 111 setY Pose2d, 98 Translation2d, 145 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
double_or, 111 Pose2d, 98 int_or, 111 Translation2d, 145 save_to_disk, 112 SliderWidget Serializer, 110 set_bool, 112 set_double, 112 Smallest_angle set_double, 112 OdometryBase, 70
int_or, 111 Translation2d, 145 save_to_disk, 112 SliderWidget Serializer, 110 set_bool, 112 set_double, 112 Smallest_angle set_double, 112 OdometryBase, 70
save_to_disk, 112 Serializer, 110 set_bool, 112 set_double, 112 SliderWidget screen::SliderWidget, 11 smallest_angle OdometryBase, 70
Serializer, 110 screen::SliderWidget, 11 set_bool, 112 smallest_angle set_double, 112 OdometryBase, 70
set_bool, 112 smallest_angle set_double, 112 OdometryBase, 70
set_double, 112 OdometryBase, 70
set_double, 112 OdometryBase, 70
set_int, 112 Smart
set_string, 113 TankDrive, 123
string_or, 113 speed
ant and
T : ID (I) 440
IIADEZUIUFIUIIE, 140
. Spin_manda
set_async Flywheel, 35 Lift< T >, 47

spin_rpm	tracking_wheel_cfg_t, 133
Flywheel, 36	tracking_wheel_cfg_t, 132
SpinRpmCmd	radius, 133
Flywheel, 36	theta_rad, 133
SpinRPMCommand, 115	x, 133
run, 116	y, 133
SpinRPMCommand, 115	Transform2d, 133
spinRPMTask	inverse, 137
Flywheel, 37	operator<<, 139
StateMachine	operator-, 137
StateMachine System, IDType, Message, de-	operator/, 137
lay_ms, do_log >, 118	operator==, 138
StateMachine < System, IDType, Message, delay_ms, do_log >, 117	operator*, 137 rotation, 138
current_state, 118	Transform2d, 134, 136
send_message, 118	translation, 138
StateMachine, 118	x, 138
StateMachine System, IDType, Message, delay_ms,	y, 138
do_log >::MaybeMessage, 53	transform_by
has_message, 54	Pose2d, 98
MaybeMessage, 53	translation
message, 54	Pose2d, 98
StateMachine System, IDType, Message, delay ms,	Transform2d, 138
do_log >::State, 116	Translation2d, 139
StatsPage	as_vector, 141
screen::StatsPage, 119	distance, 141
stop	get_mag, 141
Flywheel, 36	norm, 141
TankDrive, 129	normalize, 141
string_or	operator<<, 146
Serializer, 113	operator+, 142
	operator-, 143
TakeBackHalf, 120	operator/, 143
get, 121	operator==, 144
init, 121	operator*, 142
is_on_target, 121	rotate_around, 144
set_limits, 121	rotate_by, 144
update, 122	setX, 145
TankDrive, 122	setY, 145
BrakeType, 123	theta, 145
drive_arcade, 124	Translation2d, 140
drive_forward, 124, 125	x, 145
drive_tank, 125	y, 145
drive_tank_raw, 126 drive_to_point, 126, 127	TrapezoidProfile, 146
get_position, 128	calculate, 147
modify_inputs, 128	get_movement_time, 148
None, 123	set_accel, 148
pure_pursuit, 128	set_endpts, 148
reset_auto, 129	set_max_v, 148
Smart, 123	TrapezoidProfile, 147
stop, 129	tune
TankDrive, 123	Odometry3Wheel, 65
turn_degrees, 129, 130	tune_feedforward
turn_to_heading, 131	MotionController, 61
ZeroVelocity, 123	turn_degrees
theta	TankDrive, 129, 130
Translation2d, 145	turn_to_heading TankDrive, 131
theta_rad	iainDilve, 131
-	

TurnDegreesCommand, 149		Rotation2d, 108
on_timeout, 150		,
run, 150	Χ	
TurnDegreesCommand, 149		Pose2d, 98
TurnToHeadingCommand, 150		tracking_wheel_cfg_t, 133
on_timeout, 151		Transform2d, 138
run, 151		Translation2d, 145
TurnToHeadingCommand, 150		
Twist2d, 151	У	
dtheta, 153		Pose2d, 98
dx, 153		tracking_wheel_cfg_t, 133
dy, 153		Transform2d, 138
operator<<, 154		Translation2d, 145
operator/, 153	70.00	Valacity
operator==, 154	Zero	Velocity
operator*, 153		TankDrive, 123
Twist2d, 152		
update		
Feedback, 30		
MotionController, 61		
Odometry3Wheel, 66		
OdometryBase, 71		
OdometrySerial, 78		
OdometryTank, 81		
PID, 89		
screen::ButtonWidget, 15		
screen::FunctionPage, 41		
screen::OdometryPage, 73		
screen::Page, 83		
screen::PIDPage, 92		
screen::SliderWidget, 114		
screen::StatsPage, 119		
TakeBackHalf, 122		
velocity		
velocity CustomEncoder, 20		
GustomEncoder, 20		
WaitUntilCondition, 154		
WaitUntilUpToSpeedCmd		
Flywheel, 37		
WaitUntilUpToSpeedCommand, 155		
run, 155		
WaitUntilUpToSpeedCommand, 155		
wheel diam		
Odometry3Wheel::odometry3wheel_cfg_t, 66		
wheelbase_dist		
Odometry3Wheel::odometry3wheel_cfg_t, 67		
wrapped_degrees_180		
Rotation2d, 107		
wrapped_degrees_360		
Rotation2d, 107		
wrapped_radians_180		
Rotation2d, 107		
wrapped_radians_360		
Rotation2d, 108		
wrapped_revolutions_180		
Rotation2d, 108		
wrapped_revolutions_360		