RIT VEXU Core API

Generated by Doxygen 1.13.2

| ١ | Core | • |
|---|--|----|
| | 1.1 Getting Started | 2 |
| | 1.2 Features | 2 |
| 2 | Hierarchical Index | 3 |
| | 2.1 Class Hierarchy | 3 |
| 3 | Class Index | 5 |
| | 3.1 Class List | 5 |
| 4 | Class Documentation | 8 |
| | 4.1 Async Class Reference | 8 |
| | 4.1.1 Detailed Description | 9 |
| | 4.2 AutoChooser Class Reference | 9 |
| | 4.2.1 Detailed Description | 9 |
| | 4.2.2 Constructor & Destructor Documentation | 9 |
| | 4.2.3 Member Function Documentation | 10 |
| | 4.2.4 Member Data Documentation | 10 |
| | 4.3 BasicSolenoidSet Class Reference | 10 |
| | 4.3.1 Detailed Description | 11 |
| | 4.3.2 Constructor & Destructor Documentation | 11 |
| | 4.3.3 Member Function Documentation | 11 |
| | 4.4 BasicSpinCommand Class Reference | 11 |
| | 4.4.1 Detailed Description | 12 |
| | 4.4.2 Constructor & Destructor Documentation | 12 |
| | 4.4.3 Member Function Documentation | 12 |
| | 4.5 BasicStopCommand Class Reference | 13 |
| | 4.5.1 Detailed Description | 13 |
| | 4.5.2 Constructor & Destructor Documentation | 13 |
| | 4.5.3 Member Function Documentation | 13 |
| | 4.6 Branch Class Reference | 14 |
| | 4.6.1 Detailed Description | 14 |
| | 4.7 screen::ButtonWidget Class Reference | 14 |
| | 4.7.1 Detailed Description | 14 |
| | 4.7.2 Constructor & Destructor Documentation | 14 |
| | 4.7.3 Member Function Documentation | 15 |
| | 4.8 CommandController Class Reference | 16 |
| | 4.8.1 Detailed Description | 16 |
| | 4.8.2 Constructor & Destructor Documentation | 16 |
| | 4.8.3 Member Function Documentation | 16 |
| | 4.9 Condition Class Reference | 18 |
| | 4.9.1 Detailed Description | 19 |
| | 4.10 CustomEncoder Class Reference | 19 |

| 4.10.1 Detailed Description | |
|--|--|
| 4.10.2 Constructor & Destructor Documentation | |
| 4.10.3 Member Function Documentation | |
| 4.11 DelayCommand Class Reference | |
| 4.11.1 Detailed Description | |
| 4.11.2 Constructor & Destructor Documentation | |
| 4.11.3 Member Function Documentation | |
| 4.12 DriveForwardCommand Class Reference | |
| 4.12.1 Detailed Description | |
| 4.12.2 Constructor & Destructor Documentation | |
| 4.12.3 Member Function Documentation | |
| 4.13 DriveStopCommand Class Reference | |
| 4.13.1 Detailed Description | |
| 4.13.2 Constructor & Destructor Documentation | |
| 4.13.3 Member Function Documentation | |
| 4.14 DriveToPointCommand Class Reference | |
| 4.14.1 Detailed Description | |
| 4.14.2 Constructor & Destructor Documentation | |
| 4.14.3 Member Function Documentation | |
| 4.15 AutoChooser::entry_t Struct Reference | |
| 4.15.1 Detailed Description | |
| 4.15.2 Member Data Documentation | |
| 4.16 ExponentialMovingAverage Class Reference | |
| 4.16.1 Detailed Description | |
| 4.16.2 Constructor & Destructor Documentation | |
| 4.16.3 Member Function Documentation | |
| 4.17 Feedback Class Reference | |
| 4.17.1 Detailed Description | |
| 4.17.2 Member Function Documentation | |
| 4.18 FeedForward Class Reference | |
| 4.18.1 Detailed Description | |
| 4.18.2 Constructor & Destructor Documentation | |
| 4.18.3 Member Function Documentation | |
| 4.19 FeedForward::ff_config_t Struct Reference | |
| 4.19.1 Detailed Description | |
| 4.19.2 Member Data Documentation | |
| 4.20 Filter Class Reference | |
| 4.20.1 Detailed Description | |
| 4.21 Flywheel Class Reference | |
| 4.21.1 Detailed Description | |
| 4.21.2 Constructor & Destructor Documentation | |
| 4.21.3 Member Function Documentation | |

| 4.21.4 Friends And Related Symbol Documentation | 37 |
|---|----|
| 4.22 FlywheelStopCommand Class Reference | 37 |
| 4.22.1 Detailed Description | 37 |
| 4.22.2 Constructor & Destructor Documentation | 37 |
| 4.22.3 Member Function Documentation | 38 |
| 4.23 FlywheelStopMotorsCommand Class Reference | 38 |
| 4.23.1 Detailed Description | 38 |
| 4.23.2 Constructor & Destructor Documentation | 38 |
| 4.23.3 Member Function Documentation | 39 |
| 4.24 FlywheelStopNonTasksCommand Class Reference | 39 |
| 4.24.1 Detailed Description | 39 |
| 4.25 FunctionCommand Class Reference | 39 |
| 4.25.1 Detailed Description | 39 |
| 4.26 FunctionCondition Class Reference | 40 |
| 4.26.1 Detailed Description | 40 |
| 4.27 screen::FunctionPage Class Reference | 40 |
| 4.27.1 Detailed Description | 41 |
| 4.27.2 Constructor & Destructor Documentation | 41 |
| 4.27.3 Member Function Documentation | 41 |
| 4.28 GenericAuto Class Reference | 42 |
| 4.28.1 Detailed Description | 42 |
| 4.28.2 Member Function Documentation | 42 |
| 4.29 PurePursuit::hermite_point Struct Reference | 43 |
| 4.29.1 Detailed Description | 44 |
| 4.30 IfTimePassed Class Reference | 44 |
| 4.30.1 Detailed Description | 44 |
| 4.31 InOrder Class Reference | 44 |
| 4.31.1 Detailed Description | 44 |
| 4.32 Lift $<$ T $>$ Class Template Reference | 45 |
| 4.32.1 Detailed Description | 45 |
| 4.32.2 Constructor & Destructor Documentation | 45 |
| 4.32.3 Member Function Documentation | 46 |
| 4.33 Lift< T >::lift_cfg_t Struct Reference | 49 |
| 4.33.1 Detailed Description | 49 |
| 4.34 Logger Class Reference | 49 |
| 4.34.1 Detailed Description | 50 |
| 4.34.2 Constructor & Destructor Documentation | 50 |
| 4.34.3 Member Function Documentation | 50 |
| 4.35 MotionController::m_profile_cfg_t Struct Reference | 52 |
| 4.35.1 Detailed Description | 52 |
| $4.36\ StateMachine < System,\ IDType,\ Message,\ delay_ms,\ do_log > :: MaybeMessage\ Class\ Reference\ .$ | 53 |
| 4.36.1 Detailed Description | 53 |

| 4.36.2 Constructor & Destructor Documentation | 53 |
|--|----|
| 4.36.3 Member Function Documentation | 54 |
| 4.37 MecanumDrive Class Reference | 54 |
| 4.37.1 Detailed Description | 55 |
| 4.37.2 Constructor & Destructor Documentation | 55 |
| 4.37.3 Member Function Documentation | 55 |
| 4.38 MecanumDrive::mecanumdrive_config_t Struct Reference | 57 |
| 4.38.1 Detailed Description | 57 |
| 4.39 motion_t Struct Reference | 57 |
| 4.39.1 Detailed Description | 58 |
| 4.40 MotionController Class Reference | 58 |
| 4.40.1 Detailed Description | 59 |
| 4.40.2 Constructor & Destructor Documentation | 59 |
| 4.40.3 Member Function Documentation | 59 |
| 4.41 MovingAverage Class Reference | 62 |
| 4.41.1 Detailed Description | 62 |
| 4.41.2 Constructor & Destructor Documentation | 62 |
| 4.41.3 Member Function Documentation | 63 |
| 4.42 Odometry3Wheel Class Reference | 64 |
| 4.42.1 Detailed Description | 65 |
| 4.42.2 Constructor & Destructor Documentation | 65 |
| 4.42.3 Member Function Documentation | 66 |
| 4.43 Odometry3Wheel::odometry3wheel_cfg_t Struct Reference | 67 |
| 4.43.1 Detailed Description | 67 |
| 4.43.2 Member Data Documentation | 67 |
| 4.44 OdometryBase Class Reference | 67 |
| 4.44.1 Detailed Description | 68 |
| 4.44.2 Constructor & Destructor Documentation | 69 |
| 4.44.3 Member Function Documentation | 69 |
| 4.44.4 Member Data Documentation | 72 |
| 4.45 screen::OdometryPage Class Reference | 74 |
| 4.45.1 Detailed Description | 74 |
| 4.45.2 Constructor & Destructor Documentation | 74 |
| 4.45.3 Member Function Documentation | 75 |
| 4.46 OdometryTank Class Reference | 75 |
| 4.46.1 Detailed Description | 77 |
| 4.46.2 Constructor & Destructor Documentation | 77 |
| 4.46.3 Member Function Documentation | 78 |
| 4.47 OdomSetPosition Class Reference | 79 |
| 4.47.1 Detailed Description | 79 |
| 4.47.2 Constructor & Destructor Documentation | 79 |
| 4.47.3 Member Function Documentation | 70 |

| 4.48 screen::Page Class Reference | 80 |
|---|-----|
| 4.48.1 Detailed Description | 80 |
| 4.48.2 Member Function Documentation | 80 |
| 4.49 Parallel Class Reference | 81 |
| 4.49.1 Detailed Description | 81 |
| 4.50 PurePursuit::Path Class Reference | 81 |
| 4.50.1 Detailed Description | 81 |
| 4.50.2 Constructor & Destructor Documentation | 81 |
| 4.50.3 Member Function Documentation | 82 |
| 4.51 PID Class Reference | 82 |
| 4.51.1 Detailed Description | 83 |
| 4.51.2 Member Enumeration Documentation | 83 |
| 4.51.3 Constructor & Destructor Documentation | 83 |
| 4.51.4 Member Function Documentation | 84 |
| 4.51.5 Member Data Documentation | 87 |
| 4.52 PID::pid_config_t Struct Reference | 88 |
| 4.52.1 Detailed Description | 88 |
| 4.52.2 Member Data Documentation | 88 |
| 4.53 screen::PIDPage Class Reference | 89 |
| 4.53.1 Detailed Description | 89 |
| 4.53.2 Constructor & Destructor Documentation | 89 |
| 4.53.3 Member Function Documentation | 90 |
| 4.54 point_t Struct Reference | 90 |
| 4.54.1 Detailed Description | 91 |
| 4.54.2 Member Function Documentation | 91 |
| 4.55 Pose2d Class Reference | 92 |
| 4.55.1 Detailed Description | 92 |
| 4.55.2 Constructor & Destructor Documentation | 92 |
| 4.55.3 Member Function Documentation | 94 |
| 4.55.4 Friends And Related Symbol Documentation | 97 |
| 4.56 pose_t Struct Reference | 98 |
| 4.56.1 Detailed Description | 98 |
| 4.57 PurePursuitCommand Class Reference | 98 |
| 4.57.1 Detailed Description | 98 |
| 4.57.2 Constructor & Destructor Documentation | 98 |
| 4.57.3 Member Function Documentation | 99 |
| 4.58 robot_specs_t Struct Reference | 99 |
| 4.58.1 Detailed Description | 100 |
| 4.58.2 Member Data Documentation | 100 |
| 4.59 Rotation2d Class Reference | 100 |
| 4.59.1 Detailed Description | 101 |
| 4.59.2 Constructor & Destructor Documentation | 101 |

| 4.59.3 Member Function Documentation | 102 |
|--|-----|
| 4.59.4 Friends And Related Symbol Documentation | 106 |
| 4.60 screen::ScreenData Struct Reference | 107 |
| 4.60.1 Detailed Description | 107 |
| 4.61 Serializer Class Reference | 107 |
| 4.61.1 Detailed Description | 107 |
| 4.61.2 Constructor & Destructor Documentation | 108 |
| 4.61.3 Member Function Documentation | 109 |
| 4.62 screen::SliderWidget Class Reference | 111 |
| 4.62.1 Detailed Description | 112 |
| 4.62.2 Constructor & Destructor Documentation | 112 |
| 4.62.3 Member Function Documentation | 112 |
| 4.63 SpinRPMCommand Class Reference | 113 |
| 4.63.1 Detailed Description | 113 |
| 4.63.2 Constructor & Destructor Documentation | 113 |
| 4.63.3 Member Function Documentation | 114 |
| 4.64 PurePursuit::spline Struct Reference | 114 |
| 4.64.1 Detailed Description | 114 |
| 4.65 StateMachine< System, IDType, Message, delay_ms, do_log >::State Struct Reference | 114 |
| 4.65.1 Detailed Description | 114 |
| $\textbf{4.66 StateMachine} < \textbf{System, IDType, Message, delay_ms, do_log} > \textbf{Class Template Reference} \; . \; . \; . \; . \; .$ | 115 |
| 4.66.1 Detailed Description | 115 |
| 4.66.2 Constructor & Destructor Documentation | 116 |
| 4.66.3 Member Function Documentation | 116 |
| 4.67 screen::StatsPage Class Reference | 117 |
| 4.67.1 Detailed Description | 117 |
| 4.67.2 Constructor & Destructor Documentation | 117 |
| 4.67.3 Member Function Documentation | 117 |
| 4.68 TakeBackHalf Class Reference | 118 |
| 4.68.1 Detailed Description | 118 |
| 4.68.2 Member Function Documentation | 119 |
| 4.69 TankDrive Class Reference | 120 |
| 4.69.1 Detailed Description | 121 |
| 4.69.2 Member Enumeration Documentation | 121 |
| 4.69.3 Constructor & Destructor Documentation | 121 |
| 4.69.4 Member Function Documentation | 122 |
| 4.70 tracking_wheel_cfg_t Struct Reference | 131 |
| 4.70.1 Detailed Description | 131 |
| 4.70.2 Member Data Documentation | 131 |
| 4.71 Transform2d Class Reference | 132 |
| 4.71.1 Detailed Description | 133 |
| 4.71.2 Constructor & Destructor Documentation | 133 |

1 Core 1

| | 4.71.3 Member Function Documentation | 135 |
|-------|---|-----|
| | 4.71.4 Friends And Related Symbol Documentation | 137 |
| 4.72 | Translation2d Class Reference | 137 |
| | 4.72.1 Detailed Description | 138 |
| | 4.72.2 Constructor & Destructor Documentation | 138 |
| | 4.72.3 Member Function Documentation | 139 |
| | 4.72.4 Friends And Related Symbol Documentation | 143 |
| 4.73 | TrapezoidProfile Class Reference | 143 |
| | 4.73.1 Detailed Description | 144 |
| | 4.73.2 Constructor & Destructor Documentation | 144 |
| | 4.73.3 Member Function Documentation | 144 |
| 4.74 | TurnDegreesCommand Class Reference | 146 |
| | 4.74.1 Detailed Description | 146 |
| | 4.74.2 Constructor & Destructor Documentation | 146 |
| | 4.74.3 Member Function Documentation | 147 |
| 4.75 | TurnToHeadingCommand Class Reference | 147 |
| | 4.75.1 Detailed Description | 147 |
| | 4.75.2 Constructor & Destructor Documentation | 147 |
| | 4.75.3 Member Function Documentation | 148 |
| 4.76 | Twist2d Class Reference | 148 |
| | 4.76.1 Detailed Description | 149 |
| | 4.76.2 Constructor & Destructor Documentation | 149 |
| | 4.76.3 Member Function Documentation | 149 |
| | 4.76.4 Friends And Related Symbol Documentation | 151 |
| 4.77 | Vector2D Class Reference | 151 |
| | 4.77.1 Detailed Description | 152 |
| | 4.77.2 Constructor & Destructor Documentation | 152 |
| | 4.77.3 Member Function Documentation | 152 |
| 4.78 | WaitUntilCondition Class Reference | 155 |
| | 4.78.1 Detailed Description | 155 |
| 4.79 | WaitUntilUpToSpeedCommand Class Reference | 155 |
| | 4.79.1 Detailed Description | 155 |
| | 4.79.2 Constructor & Destructor Documentation | 155 |
| | 4.79.3 Member Function Documentation | 155 |
| Index | | 157 |

1 Core

This is the host repository for the custom VEX libraries used by the RIT VEXU team

Automatically updated documentation is available at here. There is also a downloadable reference
manual.

1.1 Getting Started

If you just want to start a project with Core, make a fork of the Fork Template and follow it's instructions. To setup core for an existing project:

- 1. Create a new vex project (using the VSCode extension or other methods)
- 2. Initialize a git repository for the project
- 3. Execute git subtree add --prefix=core git@github.com:RIT-VEX-U/Core.git main
- 4. Update the vex Makefile (or any other build system) to know about the core files (core/src for source files, core/include for headers) (See here for an example)
- 5. Enable Eigen (Latest supported version is 3.4.0):
 - mkdir vendor
 - git submodule add https://gitlab.com/libeigen/eigen.git vendor/eigen
 - cd vendor/eigen
 - git checkout 3.4.0
 - Add the following to the makefile to give Core access to the library: INC += -Ivendor/eigen (See here for an example)

If you only wish to use a single version of Core, you can simply clone core/ into your project and add the core source and header files to your makefile.

1.2 Features

Here is the current feature list this repo provides:

Subsystems (See Wiki/Subsystems):

- · Tank drivetrain (user control / autonomous)
- Mecanum drivetrain (user control / autonomous)
- Odometry
 - Tank (Differential)
 - N-Pod
- Flywheel
- Lift
- · Custom encoders

Utilities (See Wiki/Utilites):

- · PID controller
- FeedForward controller
- · Trapezoidal motion profile controller
- · Pure Pursuit
- · Generic auto program builder
- · Auto program UI selector
- Mathematical classes (Vector2D, Moving Average)

2 Hierarchical Index

2 Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

| Async | 8 |
|---------------------------|------------|
| BasicSolenoidSet | 10 |
| BasicSpinCommand | 11 |
| BasicStopCommand | 13 |
| Branch | 14 |
| screen::ButtonWidget | 14 |
| CommandController | 16 |
| Condition | 18 |
| FunctionCondition | 40 |
| IfTimePassed | 44 |
| CustomEncoder | 19 |
| DelayCommand | 2 1 |
| DriveForwardCommand | 22 |
| DriveStopCommand | 23 |
| DriveToPointCommand | 24 |
| AutoChooser::entry_t | 26 |
| Feedback | 28 |
| MotionController | 58 |
| PID | 82 |
| TakeBackHalf | 118 |
| FeedForward | 30 |
| FeedForward::ff_config_t | 32 |
| Filter | 33 |
| ExponentialMovingAverage | 26 |
| MovingAverage | 62 |
| Flywheel | 33 |
| FlywheelStopCommand | 37 |
| FlywheelStopMotorsCommand | 38 |

| FlywheelStopNonTasksCommand | 39 |
|--|-----|
| FunctionCommand | 39 |
| GenericAuto | 42 |
| PurePursuit::hermite_point | 43 |
| InOrder | 44 |
| Lift <t></t> | 45 |
| Lift< T >::lift_cfg_t | 49 |
| Logger | 49 |
| MotionController::m_profile_cfg_t | 52 |
| StateMachine < System, IDType, Message, delay_ms, do_log >::MaybeMessage | 53 |
| MecanumDrive | 54 |
| MecanumDrive::mecanumdrive_config_t | 57 |
| motion_t | 57 |
| Odometry3Wheel::odometry3wheel_cfg_t | 67 |
| OdometryBase | 67 |
| Odometry3Wheel | 64 |
| OdometryTank | 75 |
| OdomSetPosition | 79 |
| screen::Page | 80 |
| AutoChooser | 9 |
| screen::FunctionPage | 40 |
| screen::OdometryPage | 74 |
| screen::PIDPage | 89 |
| screen::StatsPage | 117 |
| Parallel | 81 |
| PurePursuit::Path | 81 |
| PID::pid_config_t | 88 |
| point_t | 90 |
| Pose2d | 92 |
| pose_t | 98 |
| PurePursuitCommand | 98 |
| robot_specs_t | 99 |

3 Class Index 5

| Rotation2d | 100 |
|--|-----|
| screen::ScreenData | 107 |
| Serializer | 107 |
| screen::SliderWidget | 111 |
| SpinRPMCommand | 113 |
| PurePursuit::spline | 114 |
| StateMachine< System, IDType, Message, delay_ms, do_log >::State | 114 |
| ${\bf State Machine < System, IDType, Message, delay_ms, do_log>}$ | 115 |
| TankDrive | 120 |
| tracking_wheel_cfg_t | 131 |
| Transform2d | 132 |
| Translation2d | 137 |
| TrapezoidProfile | 143 |
| TurnDegreesCommand | 146 |
| TurnToHeadingCommand | 147 |
| Twist2d | 148 |
| Vector2D | 151 |
| WaitUntilCondition | 155 |
| WaitUntilUpToSpeedCommand | 155 |
| | |

3 Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

| Async Async runs a command asynchronously will simply let it go and never look back THIS HAS A VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT | 8 |
|--|----|
| AutoChooser | 9 |
| BasicSolenoidSet | 10 |
| BasicSpinCommand | 11 |
| BasicStopCommand | 13 |
| Branch Branch chooses from multiple options at runtime. the function decider returns an index into the choices vector If you wish to make no choice and skip this section, return NO_CHOICE; any choice that is out of bounds set to NO_CHOICE | 14 |

| Widget that does something when you tap it. The function is only called once when you first tap it | 14 |
|---|----|
| CommandController | 16 |
| Condition | 18 |
| CustomEncoder | 19 |
| DelayCommand | 21 |
| DriveForwardCommand | 22 |
| DriveStopCommand | 23 |
| DriveToPointCommand | 24 |
| AutoChooser::entry_t | 26 |
| Exponential Moving Average | 26 |
| Feedback | 28 |
| FeedForward | 30 |
| FeedForward::ff_config_t | 32 |
| Filter | 33 |
| Flywheel | 33 |
| FlywheelStopCommand | 37 |
| FlywheelStopMotorsCommand | 38 |
| FlywheelStopNonTasksCommand | 39 |
| FunctionCommand | 39 |
| FunctionCondition FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime | 40 |
| screen::FunctionPage Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything | 40 |
| GenericAuto | 42 |
| PurePursuit::hermite_point | 43 |
| IfTimePassed IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time_s | 44 |
| InOrder InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts? | 44 |
| Lift< T > | 45 |

3.1 Class List 7

| Lift< T >::lift_cfg_t | 49 |
|--|-----|
| Logger Class to simplify writing to files | 49 |
| MotionController::m_profile_cfg_t | 52 |
| StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage MaybeMessage a message of Message type or nothing MaybeMessage m = {}; // empty MaybeMessage m = Message::EnumField1 | 53 |
| MecanumDrive | 54 |
| MecanumDrive::mecanumdrive_config_t | 57 |
| motion_t | 57 |
| MotionController | 58 |
| MovingAverage | 62 |
| Odometry3Wheel | 64 |
| Odometry3Wheel::odometry3wheel_cfg_t | 67 |
| OdometryBase | 67 |
| screen::OdometryPage Page that shows odometry position and rotation and a map (if an sd card with the file is on) | 74 |
| OdometryTank | 75 |
| OdomSetPosition | 79 |
| screen::Page Page describes one part of the screen slideshow | 80 |
| Parallel Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on_timeout on all children continue | 81 |
| PurePursuit::Path | 81 |
| PID | 82 |
| PID::pid_config_t | 88 |
| screen::PIDPage PIDPage provides a way to tune a pid controller on the screen | 89 |
| point_t | 90 |
| Pose2d | 92 |
| pose_t | 98 |
| PurePursuitCommand | 98 |
| robot_specs_t | 99 |
| Rotation2d | 100 |

| screen::ScreenData Holds the data that will be passed to the screen thread you probably shouldnt have to use it | 107 |
|--|-----|
| Serializer Serializes Arbitrary data to a file on the SD Card | 107 |
| screen::SliderWidget Widget that updates a double value. Updates by reference so watch out for race conditions cuz the screen stuff lives on another thread | 111 |
| SpinRPMCommand | 113 |
| PurePursuit::spline | 114 |
| StateMachine< System, IDType, Message, delay_ms, do_log >::State | 114 |
| StateMachine < System, IDType, Message, delay_ms, do_log > State Machine :)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024 Over Under game for our overly complex intake-cata subsystem (see there for an example) The statemachine runs in a background thread and a user thread can interact with it through current_state and send_message | 115 |
| screen::StatsPage Draws motor stats and battery stats to the screen | 117 |
| TakeBackHalf A velocity controller | 118 |
| TankDrive | 120 |
| tracking_wheel_cfg_t | 131 |
| Transform2d | 132 |
| Translation2d | 137 |
| TrapezoidProfile | 143 |
| TurnDegreesCommand | 146 |
| TurnToHeadingCommand | 147 |
| Twist2d | 148 |
| Vector2D | 151 |
| WaitUntilCondition Waits until the condition is true | 155 |
| WaitUntilUpToSpeedCommand | 155 |

4 Class Documentation

4.1 Async Class Reference

Async runs a command asynchronously will simply let it go and never look back THIS HAS A VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT.

#include <auto_command.h>

4.1.1 Detailed Description

Async runs a command asynchronously will simply let it go and never look back THIS HAS A VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT.


The documentation for this class was generated from the following files:

- auto_command.h
- · auto_command.cpp

4.2 AutoChooser Class Reference

```
#include <auto_chooser.h>
```

Inheritance diagram for AutoChooser:



Classes

struct entry_t

Public Member Functions

- AutoChooser (std::vector< std::string > paths, size t def=0)
- size_t get_choice ()

Protected Attributes

- size_t choice
- std::vector< entry_t > list

4.2.1 Detailed Description

Autochooser is a utility to make selecting robot autonomous programs easier source: RIT VexU Wiki During a season, we usually code between 4 and 6 autonomous programs. Most teams will change their entire robot program as a way of choosing autonomi but this may cause issues if you have an emergency patch to upload during a competition. This class was built as a way of using the robot screen to list autonomous programs, and the touchscreen to select them.

4.2.2 Constructor & Destructor Documentation

AutoChooser()

```
AutoChooser::AutoChooser (
          std::vector< std::string > paths,
          size_t def = 0)
```

Initialize the auto-chooser. This class places a choice menu on the brain screen, so the driver can choose which autonomous to run.

brain the brain on which to draw the selection boxes

4.2.3 Member Function Documentation

get_choice()

```
size_t AutoChooser::get_choice ()
```

Get the currently selected auto choice

Returns

the identifier to the auto path

Return the selected autonomous

4.2.4 Member Data Documentation

choice

```
size_t AutoChooser::choice [protected]
```

the current choice of auto

list

```
std::vector<entry_t> AutoChooser::list [protected]
```

< a list of all possible auto choices

The documentation for this class was generated from the following files:

- auto_chooser.h
- · auto_chooser.cpp

4.3 BasicSolenoidSet Class Reference

```
#include <basic_command.h>
```

Public Member Functions

BasicSolenoidSet (vex::pneumatics &solenoid, bool setting)

Construct a new BasicSolenoidSet Command.

· bool run () override

Runs the BasicSolenoidSet Overrides run command from AutoCommand.

4.3.1 Detailed Description

AutoCommand wrapper class for BasicSolenoidSet Using the Vex hardware functions

4.3.2 Constructor & Destructor Documentation

BasicSolenoidSet()

Construct a new BasicSolenoidSet Command.

Parameters

| solenoid | Solenoid being set |
|----------|---|
| setting | Setting of the solenoid in boolean (true,false) |

4.3.3 Member Function Documentation

run()

```
bool BasicSolenoidSet::run () [override]
```

Runs the BasicSolenoidSet Overrides run command from AutoCommand.

Returns

True Command runs once

The documentation for this class was generated from the following files:

- · basic command.h
- · basic_command.cpp

4.4 BasicSpinCommand Class Reference

```
#include <basic_command.h>
```

Public Member Functions

 BasicSpinCommand (vex::motor &motor, vex::directionType dir, BasicSpinCommand::type setting, double power)

Construct a new BasicSpinCommand.

• bool run () override

Runs the BasicSpinCommand Overrides run from Auto Command.

4.4.1 Detailed Description

AutoCommand wrapper class for BasicSpinCommand using the vex hardware functions

4.4.2 Constructor & Destructor Documentation

BasicSpinCommand()

```
BasicSpinCommand::BasicSpinCommand (
    vex::motor & motor,
    vex::directionType dir,
    BasicSpinCommand::type setting,
    double power)
```

Construct a new BasicSpinCommand.

a BasicMotorSpin Command

Parameters

| motor | Motor to spin |
|---------|--|
| direc | Direction of motor spin |
| setting | Power setting in volts,percentage,velocity |
| power | Value of desired power |
| motor | Motor port to spin |
| dir | Direction for spining |
| setting | Power setting in volts,percentage,velocity |
| power | Value of desired power |

4.4.3 Member Function Documentation

run()

```
bool BasicSpinCommand::run () [override]
```

Runs the BasicSpinCommand Overrides run from Auto Command.

Run the BasicSpinCommand Overrides run from Auto Command.

Returns

True Async running command

True Command runs once

The documentation for this class was generated from the following files:

- basic_command.h
- basic_command.cpp

4.5 BasicStopCommand Class Reference

```
#include <basic_command.h>
```

Public Member Functions

BasicStopCommand (vex::motor &motor, vex::brakeType setting)

Construct a new BasicMotorStop Command.

• bool run () override

Runs the BasicMotorStop Command Overrides run command from AutoCommand.

4.5.1 Detailed Description

AutoCommand wrapper class for BasicStopCommand Using the Vex hardware functions

4.5.2 Constructor & Destructor Documentation

BasicStopCommand()

Construct a new BasicMotorStop Command.

Construct a BasicMotorStop Command.

Parameters

| motor | The motor to stop |
|---------|------------------------------------|
| setting | The brake setting for the motor |
| motor | Motor to stop |
| setting | Braketype setting brake,coast,hold |

4.5.3 Member Function Documentation

run()

```
bool BasicStopCommand::run () [override]
```

Runs the BasicMotorStop Command Overrides run command from AutoCommand.

Runs the BasicMotorStop command Ovverides run command from AutoCommand.

Returns

True Command runs once

The documentation for this class was generated from the following files:

- basic_command.h
- basic_command.cpp

4.6 Branch Class Reference

Branch chooses from multiple options at runtime. the function decider returns an index into the choices vector If you wish to make no choice and skip this section, return NO_CHOICE; any choice that is out of bounds set to NO_CHOICE.

```
#include <auto command.h>
```

4.6.1 Detailed Description

Branch chooses from multiple options at runtime. the function decider returns an index into the choices vector If you wish to make no choice and skip this section, return NO_CHOICE; any choice that is out of bounds set to NO CHOICE.

The documentation for this class was generated from the following files:

- auto_command.h
- · auto_command.cpp

4.7 screen::ButtonWidget Class Reference

Widget that does something when you tap it. The function is only called once when you first tap it.

```
#include <screen.h>
```

Public Member Functions

- ButtonWidget (std::function < void(void) > onpress, Rect rect, std::string name)
 Create a Button widget.
- ButtonWidget (void(*onpress)(), Rect rect, std::string name)

Create a Button widget.

• bool update (bool was pressed, int x, int y)

responds to user input

• void **draw** (vex::brain::lcd &, bool first_draw, unsigned int frame_number)

draws the button to the screen

4.7.1 Detailed Description

Widget that does something when you tap it. The function is only called once when you first tap it.

4.7.2 Constructor & Destructor Documentation

ButtonWidget() [1/2]

Create a Button widget.

| onpress | the function to be called when the button is tapped |
|---------|---|
| rect | the area the button should take up on the screen |
| name | the label put on the button |

ButtonWidget() [2/2]

Create a Button widget.

Parameters

| onpress | the function to be called when the button is tapped |
|---------|---|
| rect | the area the button should take up on the screen |
| name | the label put on the button |

4.7.3 Member Function Documentation

update()

```
bool screen::ButtonWidget::update (
          bool was_pressed,
          int x,
          int y)
```

responds to user input

Parameters

| was_pressed | if the screen is pressed |
|-------------|--------------------------------------|
| X | x position if the screen was pressed |
| У | y position if the screen was pressed |

Returns

true if the button was pressed

The documentation for this class was generated from the following files:

- screen.h
- screen.cpp

4.8 CommandController Class Reference

```
#include <command_controller.h>
```

Public Member Functions

• CommandController ()

Create an empty CommandController. Add Command with CommandController::add()

CommandController (std::initializer list< AutoCommand * > cmds)

Create a CommandController with commands pre added. More can be added with CommandController::add()

- void add (std::vector< AutoCommand * > cmds)
- void add (AutoCommand *cmd, double timeout_seconds=10.0)
- void add (std::vector< AutoCommand * > cmds, double timeout_sec)
- void add delay (int ms)
- void add_cancel_func (std::function< bool(void)> true_if_cancel)

add_cancel_func specifies that when this func evaluates to true, to cancel the command controller

- void run ()
- bool last_command_timed_out ()

4.8.1 Detailed Description

File: command_controller.h Desc: A CommandController manages the AutoCommands that make up an autonomous route. The AutoCommands are kept in a queue and get executed and removed from the queue in FIFO order.

4.8.2 Constructor & Destructor Documentation

CommandController()

Create a CommandController with commands pre added. More can be added with CommandController::add()

Parameters

cmds

4.8.3 Member Function Documentation

add() [1/3]

File: command_controller.cpp Desc: A CommandController manages the AutoCommands that make up an autonomous route. The AutoCommands are kept in a queue and get executed and removed from the queue in FIFO order. Adds a command to the queue

| cmd | the AutoCommand we want to add to our list |
|-----------------|---|
| timeout_seconds | the number of seconds we will let the command run for. If it exceeds this, we cancel it and |
| | run on_timeout |

add() [2/3]

```
void CommandController::add ( {\tt std::vector} < {\tt AutoCommand} \ * \ > \ cmds)
```

Adds a command to the queue

Parameters

| cmd | the AutoCommand we want to add to our list |
|-----------------|---|
| timeout_seconds | the number of seconds we will let the command run for. If it exceeds this, we cancel it and |
| | run on_timeout. if it is <= 0 no time out will be applied |

Add multiple commands to the queue. No timeout here.

Parameters

| cmds | the AutoCommands we want to add to our list |
|------|---|
|------|---|

add() [3/3]

```
void CommandController::add (
    std::vector< AutoCommand * > cmds,
    double timeout_sec)
```

Add multiple commands to the queue. No timeout here.

Parameters

| cmds | the AutoCommands we want to add to our list Add multiple commands to the queue. No timeout |
|-------------|--|
| | here. |
| cmds | the AutoCommands we want to add to our list |
| timeout_sec | timeout in seconds to apply to all commands if they are still the default |

Add multiple commands to the queue. No timeout here.

Parameters

| cmds | the AutoCommands we want to add to our list |
|---------|---|
| timeout | timeout in seconds to apply to all commands if they are still the default |

add_cancel_func()

```
\label{lem:commandController::add_cancel_func (std::function< bool(void)> true\_if\_cancel)} \\
```

add_cancel_func specifies that when this func evaluates to true, to cancel the command controller

| true_if_cancel | a function that returns true when we want to cancel the command controller |
|----------------|--|
|----------------|--|

add_delay()

Adds a command that will delay progression of the queue

Parameters

ms - number of milliseconds to wait before continuing execution of autonomous

last_command_timed_out()

```
bool CommandController::last_command_timed_out ()
```

last_command_timed_out tells how the last command ended Use this if you want to make decisions based on the end of the last command

Returns

true if the last command timed out. false if it finished regularly

run()

```
void CommandController::run ()
```

Begin execution of the queue Execute and remove commands in FIFO order


The documentation for this class was generated from the following files:

- · command_controller.h
- command_controller.cpp

4.9 Condition Class Reference

```
#include <auto_command.h>
```

Inheritance diagram for Condition:



4.9.1 Detailed Description

File: auto_command.h Desc: Interface for module-specifc commands A Condition is a function that returns true or false is_even is a predicate that would return true if a number is even For our purposes, a Condition is a choice to be made at runtime drive_sys.reached_point(10, 30) is a predicate time.has_elapsed(10, vex::seconds) is a predicate extend this class for different choices you wish to make

The documentation for this class was generated from the following files:

- · auto command.h
- · auto_command.cpp

4.10 CustomEncoder Class Reference

```
#include <custom_encoder.h>
```

Public Member Functions

- CustomEncoder (vex::triport::port &port, double ticks per rev)
- void setRotation (double val, vex::rotationUnits units)
- void setPosition (double val, vex::rotationUnits units)
- double rotation (vex::rotationUnits units)
- double position (vex::rotationUnits units)
- double velocity (vex::velocityUnits units)

4.10.1 Detailed Description

A wrapper class for the vex encoder that allows the use of 3rd party encoders with different tick-per-revolution values.

4.10.2 Constructor & Destructor Documentation

CustomEncoder()

Construct an encoder with a custom number of ticks

Parameters

| port | the triport port on the brain the encoder is plugged into |
|---------------|--|
| ticks_per_rev | the number of ticks the encoder will report for one revolution |

4.10.3 Member Function Documentation

position()

get the position that the encoder is at

| units | the unit we want the return value to be in |
|-------|--|
|-------|--|

Returns

the position of the encoder in the units specified

rotation()

get the rotation that the encoder is at

Parameters

| ı | units | the unit we want the return value to be in |
|---|-------|--|
|---|-------|--|

Returns

the rotation of the encoder in the units specified

setPosition()

sets the stored position of the encoder. Any further movements will be from this value

Parameters

| val | the numerical value of the position we are setting to |
|-------|---|
| units | the unit of val |

setRotation()

sets the stored rotation of the encoder. Any further movements will be from this value

Parameters

| val | the numerical value of the angle we are setting to |
|-------|--|
| units | the unit of val |

velocity()

get the velocity that the encoder is moving at

units the unit we want the return value to be in

Returns

the velocity of the encoder in the units specified

The documentation for this class was generated from the following files:

- · custom_encoder.h
- custom_encoder.cpp

4.11 DelayCommand Class Reference

```
#include <delay_command.h>
```

Public Member Functions

- DelayCommand (int ms)
- bool run () override

4.11.1 Detailed Description

File: delay_command.h Desc: A DelayCommand will make the robot wait the set amount of milliseconds before continuing execution of the autonomous route

4.11.2 Constructor & Destructor Documentation

DelayCommand()

Construct a delay command

Parameters

ms the number of milliseconds to delay for

4.11.3 Member Function Documentation

run()

```
bool DelayCommand::run () [inline], [override]
```

Delays for the amount of milliseconds stored in the command Overrides run from AutoCommand

Returns

true when complete

The documentation for this class was generated from the following file:

· delay_command.h

4.12 DriveForwardCommand Class Reference

```
#include <drive commands.h>
```

Public Member Functions

- DriveForwardCommand (TankDrive &drive_sys, Feedback &feedback, double inches, directionType dir, double max_speed=1, double end_speed=0)
- bool run () override
- · void on_timeout () override

4.12.1 Detailed Description

AutoCommand wrapper class for the drive_forward function in the TankDrive class

4.12.2 Constructor & Destructor Documentation

DriveForwardCommand()

File: drive_commands.h Desc: Holds all the AutoCommand subclasses that wrap (currently) TankDrive functions

Currently includes:

- drive_forward
- turn_degrees
- · drive to point
- · turn_to_heading
- stop

Also holds AutoCommand subclasses that wrap OdometryBase functions

Currently includes:

set_position Construct a DriveForward Command

| drive_sys | the drive system we are commanding |
|-----------|---|
| feedback | the feedback controller we are using to execute the drive |
| inches | how far forward to drive |
| dir | the direction to drive |
| max_speed | 0 -> 1 percentage of the drive systems speed to drive at |

4.12.3 Member Function Documentation

on_timeout()

```
void DriveForwardCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we timeout

run()

```
bool DriveForwardCommand::run () [override]
```

Run drive_forward Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive commands.h
- drive_commands.cpp

4.13 DriveStopCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- DriveStopCommand (TankDrive &drive_sys)
- bool run () override

4.13.1 Detailed Description

AutoCommand wrapper class for the stop() function in the TankDrive class

4.13.2 Constructor & Destructor Documentation

DriveStopCommand()

Construct a DriveStop Command

| drive_sys | the drive system we are commanding | |
|-----------|------------------------------------|--|
|-----------|------------------------------------|--|

4.13.3 Member Function Documentation

run()

```
bool DriveStopCommand::run () [override]
```

Stop the drive system Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

Stop the drive train Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive_commands.h
- · drive_commands.cpp

4.14 DriveToPointCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- DriveToPointCommand (TankDrive &drive_sys, Feedback &feedback, double x, double y, directionType dir, double max_speed=1, double end_speed=0)
- DriveToPointCommand (TankDrive &drive_sys, Feedback &feedback, point_t point, directionType dir, double max speed=1, double end speed=0)
- bool run () override

4.14.1 Detailed Description

AutoCommand wrapper class for the drive_to_point function in the TankDrive class

4.14.2 Constructor & Destructor Documentation

DriveToPointCommand() [1/2]

Construct a DriveForward Command

| drive_sys | the drive system we are commanding |
|-----------|---|
| feedback | the feedback controller we are using to execute the drive |
| X | where to drive in the x dimension |
| У | where to drive in the y dimension |
| dir | the direction to drive |
| max_speed | 0 -> 1 percentage of the drive systems speed to drive at |

DriveToPointCommand() [2/2]

Construct a DriveForward Command

Parameters

| drive_sys | the drive system we are commanding |
|-----------|---|
| feedback | the feedback controller we are using to execute the drive |
| point | the point to drive to |
| dir | the direction to drive |
| max_speed | 0 -> 1 percentage of the drive systems speed to drive at |

4.14.3 Member Function Documentation

run()

```
bool DriveToPointCommand::run () [override]
```

Run drive_to_point Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- drive_commands.h
- · drive_commands.cpp

4.15 AutoChooser::entry_t Struct Reference

#include <auto_chooser.h>

Public Attributes

• std::string name

4.15.1 Detailed Description

entry_t is a datatype used to store information that the chooser knows about an auto selection button

4.15.2 Member Data Documentation

name

```
std::string AutoChooser::entry_t::name
```

name of the auto repretsented by the block

The documentation for this struct was generated from the following file:

· auto_chooser.h

4.16 Exponential Moving Average Class Reference

```
#include <moving_average.h>
```

 $Inheritance\ diagram\ for\ Exponential Moving Average:$



Public Member Functions

- ExponentialMovingAverage (int buffer_size)
- ExponentialMovingAverage (int buffer_size, double starting_value)
- · void add_entry (double n) override
- double get_value () const override
- int get_size ()

4.16.1 Detailed Description

ExponentialMovingAverage

An exponential moving average is a way of smoothing out noisy data. For many sensor readings, the noise is roughly symmetric around the actual value. This means that if you collect enough samples those that are too high are cancelled out by the samples that are too low leaving the real value.

A simple mobing average lags significantly with time as it has to counteract old samples. An exponential moving average keeps more up to date by weighting newer readings higher than older readings so it is more up to date while also still smoothed.

The ExponentialMovingAverage class provides an simple interface to do this smoothing from our noisy sensor values.

4.16.2 Constructor & Destructor Documentation

ExponentialMovingAverage() [1/2]

Create a moving average calculator with 0 as the default value

Parameters

| buffer_size | The size of the buffer. The number of samples that constitute a valid reading |
|-------------|---|
|-------------|---|

ExponentialMovingAverage() [2/2]

Create a moving average calculator with a specified default value

Parameters

| buffer_size | The size of the buffer. The number of samples that constitute a valid reading |
|----------------|---|
| starting_value | The value that the average will be before any data is added |

4.16.3 Member Function Documentation

add_entry()

Add a reading to the buffer Before: [1 1 2 2 3 3] => 2 $^{\land}$ After: [2 1 2 2 3 3] => 2.16 $^{\land}$

n the sample that will be added to the moving average.

Implements Filter.

get_size()

```
int ExponentialMovingAverage::get_size ()
```

How many samples the average is made from

Returns

the number of samples used to calculate this average

get_value()

```
double ExponentialMovingAverage::get_value () const [override], [virtual]
```

Returns the average based off of all the samples collected so far

Returns

the calculated average. sum(samples)/numsamples

How many samples the average is made from

Returns

the number of samples used to calculate this average

Implements Filter.


The documentation for this class was generated from the following files:

- · moving_average.h
- · moving_average.cpp

4.17 Feedback Class Reference

```
#include <feedback_base.h>
```

Inheritance diagram for Feedback:



Public Member Functions

- virtual void init (double start_pt, double set_pt)=0
- virtual double update (double val)=0
- virtual double get ()=0
- virtual void set_limits (double lower, double upper)=0
- virtual bool is_on_target ()=0

4.17.1 Detailed Description

Interface so that subsystems can easily switch between feedback loops

Author

Ryan McGee

Date

9/25/2022

4.17.2 Member Function Documentation

get()

```
virtual double Feedback::get () [pure virtual]
```

Returns

the last saved result from the feedback controller

Implemented in MotionController, PID, and TakeBackHalf.

init()

Initialize the feedback controller for a movement

Parameters

| | start_pt | the current sensor value | | |
|--|-----------|----------------------------------|--|--|
| | set_pt | where the sensor value should be | | |
| | start_vel | Movement starting velocity | | |
| | end_vel | Movement ending velocity | | |

Implemented in MotionController, PID, and TakeBackHalf.

is_on_target()

```
virtual bool Feedback::is_on_target () [pure virtual]
```

Returns

true if the feedback controller has reached it's setpoint

Implemented in MotionController, PID, and TakeBackHalf.

set_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

Parameters

| lower | Upper limit |
|-------|-------------|
| upper | Lower limit |

Implemented in MotionController, PID, and TakeBackHalf.

update()

Iterate the feedback loop once with an updated sensor value

Parameters

| val value from th | ne sensor |
|-------------------|-----------|
|-------------------|-----------|

Returns

feedback loop result

Implemented in MotionController, PID, and TakeBackHalf.

The documentation for this class was generated from the following file:

· feedback_base.h

4.18 FeedForward Class Reference

#include <feedforward.h>

Classes

· struct ff_config_t

Public Member Functions

- FeedForward (ff_config_t &cfg)
- double calculate (double v, double a, double pid ref=0.0)

Perform the feedforward calculation.

4.18.1 Detailed Description

FeedForward

Stores the feedfoward constants, and allows for quick computation. Feedfoward should be used in systems that require smooth precise movements and have high inertia, such as drivetrains and lifts.

This is best used alongside a PID loop, with the form: output = pid.get() + feedforward.calculate(v, a);

In this case, the feedforward does the majority of the heavy lifting, and the pid loop only corrects for inconsistencies

For information about tuning feedforward, I reccommend looking at this post: $https://www. \leftarrow chiefdelphi.com/t/paper-frc-drivetrain-characterization/160915$ (yes I know it's for FRC but trust me, it's useful)

Author

Ryan McGee

Date

6/13/2022

4.18.2 Constructor & Destructor Documentation

FeedForward()

Creates a FeedForward object.

Parameters

```
cfg | Configuration Struct for tuning
```

4.18.3 Member Function Documentation

calculate()

Perform the feedforward calculation.

This calculation is the equation: F = kG + kS*sgn(v) + kV*v + kA*a

| ι | / | Requested velocity of system |
|---|---|----------------------------------|
| ć | 3 | Requested acceleration of system |

Returns

A feedforward that should closely represent the system if tuned correctly

The documentation for this class was generated from the following file:

· feedforward.h

4.19 FeedForward::ff_config_t Struct Reference

#include <feedforward.h>

Public Attributes

- double kS
- double kV
- double kA
- double kG

4.19.1 Detailed Description

ff_config_t holds the parameters to make the theoretical model of a real world system equation is of the form kS if the system is not stopped, 0 otherwise

- kV * desired velocity
- · kA * desired acceleration
- kG

4.19.2 Member Data Documentation

kΑ

```
double FeedForward::ff_config_t::kA
```

kA - Acceleration coefficient: the power required to change the mechanism's speed. Multiplied by the requested acceleration.

kG

```
double FeedForward::ff_config_t::kG
```

kG - Gravity coefficient: only needed for lifts. The power required to overcome gravity and stay at steady state.

kS

```
double FeedForward::ff_config_t::kS
```

Coefficient to overcome static friction: the point at which the motor *starts* to move.

k۷

```
double FeedForward::ff_config_t::kV
```

Veclocity coefficient: the power required to keep the mechanism in motion. Multiplied by the requested velocity.

The documentation for this struct was generated from the following file:

· feedforward.h

4.20 Filter Class Reference

```
#include <moving_average.h>
```

Inheritance diagram for Filter:



4.20.1 Detailed Description

Interface for filters Use add_entry to supply data and get_value to retrieve the filtered value

The documentation for this class was generated from the following file:

· moving_average.h

4.21 Flywheel Class Reference

#include <flywheel.h>

Public Member Functions

- Flywheel (vex::motor_group &motors, Feedback &feedback, FeedForward &helper, const double ratio, Filter &filt)
- double get_target () const
- double getRPM () const
- vex::motor group & get motors () const
- void spin_manual (double speed, directionType dir=fwd)
- void spin_rpm (double rpm)
- void stop ()
- bool is_on_target ()

check if the feedback controller thinks the flywheel is on target

• screen::Page * Page () const

Creates a page displaying info about the flywheel.

AutoCommand * SpinRpmCmd (int rpm)

Creates a new auto command to spin the flywheel at the desired velocity.

AutoCommand * WaitUntilUpToSpeedCmd ()

Creates a new auto command that will hold until the flywheel has its target as defined by its feedback controller.

Friends

int spinRPMTask (void *wheelPointer)

4.21.1 Detailed Description

a Flywheel class that handles all control of a high inertia spinning disk It gives multiple options for what control system to use in order to control wheel velocity and functions alerting the user when the flywheel is up to speed. Flywheel is a set and forget class. Once you create it you can call spin_rpm or stop on it at any time and it will take all necessary steps to accomplish this

4.21.2 Constructor & Destructor Documentation

Flywheel()

Create the Flywheel object using PID + feedforward for control.

Parameters

| motors | pointer to the motors on the fly wheel |
|----------|--|
| feedback | a feedback controleller |
| helper | a feedforward config (only kV is used) to help the feedback controller along |
| ratio | ratio of the gears from the motor to the flywheel just multiplies the velocity |
| filter | the filter to use to smooth noisy motor readings |

4.21.3 Member Function Documentation

```
get_motors()
```

```
motor_group & Flywheel::get_motors () const
```

Returns the motors

Returns

the motors used to run the flywheel

get_target()

```
double Flywheel::get_target () const
```

Return the target_rpm that the flywheel is currently trying to achieve

Returns

target_rpm the target rpm

Return the current value that the target_rpm should be set to

getRPM()

```
double Flywheel::getRPM () const
```

return the velocity of the flywheel

is_on_target()

```
bool Flywheel::is_on_target () [inline]
```

check if the feedback controller thinks the flywheel is on target

Returns

true if on target

Page()

```
screen::Page * Flywheel::Page () const
```

Creates a page displaying info about the flywheel.

Returns

the page should be used for `screen::start_screen(screen, {fw.Page()});

spin_manual()

Spin motors using voltage; defaults forward at 12 volts FOR USE BY OPCONTROL AND AUTONOMOUS - this only applies if the target_rpm thread is not running

| speed | - speed (between -1 and 1) to set the motor |
|-------|--|
| dir | - direction that the motor moves in; defaults to forward |

Spin motors using voltage; defaults forward at 12 volts FOR USE BY OPCONTROL AND AUTONOMOUS - this only applies if the RPM thread is not running

Parameters

| speed | - speed (between -1 and 1) to set the motor |
|-------|--|
| dir | - direction that the motor moves in; defaults to forward |

spin_rpm()

starts or sets the target_rpm thread at new value what control scheme is dependent on control_style

Parameters

| | rpm | - the target_rpm we want to spin at | |
|--|-----|-------------------------------------|--|
|--|-----|-------------------------------------|--|

starts or sets the RPM thread at new value what control scheme is dependent on control_style

Parameters

```
input_rpm - set the current RPM
```

SpinRpmCmd()

Creates a new auto command to spin the flywheel at the desired velocity.

Parameters

| rpm | the rpm to spin at |
|-----|--------------------|

Returns

an auto command to add to a command controller

stop()

```
void Flywheel::stop ()
```

Stops the motors. If manually spinning, this will do nothing just call spin_mainual(0.0) to send 0 volts stop the RPM thread and the wheel

WaitUntilUpToSpeedCmd()

```
AutoCommand * Flywheel::WaitUntilUpToSpeedCmd () [inline]
```

Creates a new auto command that will hold until the flywheel has its target as defined by its feedback controller.

Returns

an auto command to add to a command controller

4.21.4 Friends And Related Symbol Documentation

spinRPMTask

Runs a thread that keeps track of updating flywheel RPM and controlling it accordingly

The documentation for this class was generated from the following files:

- flywheel.h
- · flywheel.cpp

4.22 FlywheelStopCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- FlywheelStopCommand (Flywheel &flywheel)
- · bool run () override

4.22.1 Detailed Description

AutoCommand wrapper class for the stop function in the Flywheel class

4.22.2 Constructor & Destructor Documentation

FlywheelStopCommand()

```
\label{limits} FlywheelStopCommand:: FlywheelStopCommand ( \\ Flywheel \& flywheel)
```

Construct a FlywheelStopCommand

| flywheel | the flywheel system we are commanding |
|----------|---------------------------------------|
|----------|---------------------------------------|

4.22.3 Member Function Documentation

run()

```
bool FlywheelStopCommand::run () [override]
```

Run stop Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- flywheel_commands.h
- flywheel_commands.cpp

4.23 FlywheelStopMotorsCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- FlywheelStopMotorsCommand (Flywheel &flywheel)
- bool run () override

4.23.1 Detailed Description

AutoCommand wrapper class for the stopMotors function in the Flywheel class

4.23.2 Constructor & Destructor Documentation

FlywheelStopMotorsCommand()

```
\label{lem:flywheelStopMotorsCommand::FlywheelStopMotorsCommand (} Flywheel & flywheel)
```

Construct a FlywheeStopMotors Command

flywheel the flywheel system we are commanding

4.23.3 Member Function Documentation

run()

bool FlywheelStopMotorsCommand::run () [override]

Run stop Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · flywheel commands.h
- flywheel_commands.cpp

4.24 FlywheelStopNonTasksCommand Class Reference

#include <flywheel_commands.h>

4.24.1 Detailed Description

AutoCommand wrapper class for the stopNonTasks function in the Flywheel class

The documentation for this class was generated from the following files:

- · flywheel_commands.h
- flywheel_commands.cpp

4.25 FunctionCommand Class Reference

#include <auto_command.h>

4.25.1 Detailed Description

FunctionCommand is fun and good way to do simple things Printing, launching nukes, and other quick and dirty one time things

The documentation for this class was generated from the following file:


· auto_command.h

4.26 FunctionCondition Class Reference

FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime.

```
#include <auto_command.h>
```

Inheritance diagram for FunctionCondition:



4.26.1 Detailed Description

FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime.

The documentation for this class was generated from the following files:

- · auto command.h
- · auto_command.cpp

4.27 screen::FunctionPage Class Reference

Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything.

```
#include <screen.h>
```

Inheritance diagram for screen::FunctionPage:



Public Member Functions

- FunctionPage (update_func_t update_f, draw_func_t draw_t)
 Creates a function page.
- void update (bool was_pressed, int x, int y) override
 update uses the supplied update function to update this page
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

draw uses the supplied draw function to draw to the screen

4.27.1 Detailed Description

Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything.

4.27.2 Constructor & Destructor Documentation

FunctionPage()

Creates a function page.

FunctionPage.

Parameters

| update⊷ | the function called every tick to respond to user input or do data collection |
|---------|---|
| _f | |
| draw_t | the function called to draw to the screen |
| update⇔ | drawing function |
| _f | |
| draw_f | drawing function |

4.27.3 Member Function Documentation

draw()

draw uses the supplied draw function to draw to the screen

See also

Page::draw

Reimplemented from screen::Page.

update()

update uses the supplied update function to update this page

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:

- · screen.h
- · screen.cpp

4.28 GenericAuto Class Reference

```
#include <generic_auto.h>
```

Public Member Functions

- bool run (bool blocking)
- void add (state ptr new state)
- void add_async (state_ptr async_state)
- void add_delay (int ms)

4.28.1 Detailed Description

GenericAuto provides a pleasant interface for organizing an auto path steps of the path can be added with add() and when ready, calling run() will begin executing the path

4.28.2 Member Function Documentation

add()

Add a new state to the autonomous via function point of type "bool (ptr*)()"

Parameters

```
new_state the function to run
```

add async()

Add a new state to the autonomous via function point of type "bool (ptr*)()" that will run asynchronously

add_delay()

```
void GenericAuto::add_delay (
          int ms)
```

add_delay adds a period where the auto system will simply wait for the specified time

Parameters

| ms | how long to wait in milliseconds |
|----|----------------------------------|
|----|----------------------------------|

run()

```
bool GenericAuto::run (
          bool blocking)
```

The method that runs the autonomous. If 'blocking' is true, then this method will run through every state until it finished.

If blocking is false, then assuming every state is also non-blocking, the method will run through the current state in the list and return immediately.

Parameters

| blocking | Whether or not to block the thread until all states have run |
|----------|--|
|----------|--|

Returns

true after all states have finished.

The documentation for this class was generated from the following files:

- · generic_auto.h
- · generic_auto.cpp

4.29 PurePursuit::hermite_point Struct Reference

```
#include <pure_pursuit.h>
```

4.29.1 Detailed Description

a position along the hermite path contains a position and orientation information that the robot would be at at this point

The documentation for this struct was generated from the following file:

· pure pursuit.h

4.30 IfTimePassed Class Reference

IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time_s.

```
#include <auto_command.h>
```

Inheritance diagram for IfTimePassed:



4.30.1 Detailed Description

IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time s.

The documentation for this class was generated from the following files:

- · auto command.h
- · auto_command.cpp

4.31 InOrder Class Reference

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

```
#include <auto_command.h>
```

4.31.1 Detailed Description

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

The documentation for this class was generated from the following files:

- auto_command.h
- · auto_command.cpp

4.32 Lift< T > Class Template Reference

```
#include <lift.h>
```

Classes

· struct lift_cfg_t

Public Member Functions

- Lift (motor_group &lift_motors, lift_cfg_t &lift_cfg, map< T, double > &setpoint_map, limit *homing_← switch=NULL)
- void control_continuous (bool up_ctrl, bool down_ctrl)
- void control_manual (bool up_btn, bool down_btn, int volt_up, int volt_down)
- void control setpoints (bool up step, bool down step, vector< T > pos list)
- bool set position (T pos)
- bool set_setpoint (double val)
- double get_setpoint ()
- void hold ()
- void home ()
- bool get_async ()
- void set_async (bool val)
- void set_sensor_function (double(*fn_ptr)(void))
- void set_sensor_reset (void(*fn_ptr)(void))

4.32.1 Detailed Description

```
template<typename T> class Lift< T >
```

LIFT A general class for lifts (e.g. 4bar, dr4bar, linear, etc) Uses a PID to hold the lift at a certain height under load, and to move the lift to different heights

Author

Ryan McGee

4.32.2 Constructor & Destructor Documentation

Lift()

Construct the Lift object and begin the background task that controls the lift.

Usage example: /code{.cpp} enum Positions {UP, MID, DOWN}; map<Positions, double> setpt_map { {DOWN, 0.0}, {MID, 0.5}, {UP, 1.0} }; Lift<Positions> my_lift(motors, lift_cfg, setpt_map); /endcode

| lift_motors | A set of motors, all set that positive rotation correlates with the lift going up | | | |
|--------------|---|--|--|--|
| lift_cfg | Lift characterization information; PID tunings and movement speeds | | | |
| setpoint_map | A map of enum type T, in which each enum entry corresponds to a different lift height | | | |

4.32.3 Member Function Documentation

control_continuous()

Control the lift with an "up" button and a "down" button. Use PID to hold the lift when letting go.

Parameters

| up_ctrl | Button controlling the "UP" motion |
|-----------|--------------------------------------|
| down_ctrl | Button controlling the "DOWN" motion |

control_manual()

Control the lift with manual controls (no holding voltage)

Parameters

| up_btn | Raise the lift when true |
|-----------|--------------------------------------|
| down_btn | Lower the lift when true |
| volt_up | Motor voltage when raising the lift |
| volt_down | Motor voltage when lowering the lift |

control_setpoints()

Control the lift in "steps". When the "up" button is pressed, the lift will go to the next position as defined by pos_list. Order matters!

| up_step | A button that increments the position of the lift. |
|-----------|--|
| down_step | A button that decrements the position of the lift. |
| pos_list | A list of positions for the lift to go through. The higher the index, the higher the lift should be (generally). |

get_async()

```
template<typename T>
bool Lift< T >::get_async () [inline]
```

Returns

whether or not the background thread is running the lift

get_setpoint()

```
template<typename T>
double Lift< T >::get_setpoint () [inline]
```

Returns

The current setpoint for the lift

hold()

```
template<typename T>
void Lift< T >::hold () [inline]
```

Target the class's setpoint. Calculate the PID output and set the lift motors accordingly.

home()

```
template<typename T>
void Lift< T >::home () [inline]
```

A blocking function that automatically homes the lift based on a sensor or hard stop, and sets the position to 0. A watchdog times out after 3 seconds, to avoid damage.

set_async()

Enables or disables the background task. Note that running the control functions, or set_position functions will immediately re-enable the task for autonomous use.

val Whether or not the background thread should run the lift

set_position()

Enable the background task, and send the lift to a position, specified by the setpoint map from the constructor.

Parameters

```
pos A lift position enum type
```

Returns

True if the pid has reached the setpoint

set_sensor_function()

Creates a custom hook for any other type of sensor to be used on the lift. Example: $/code\{.cpp\}$ my_lift.set_ \leftarrow sensor_function([](){return my_sensor.position();}); $/code\{.cpp\}$ my_lift.set_ \leftarrow

Parameters

```
fn_ptr | Pointer to custom sensor function
```

set_sensor_reset()

Creates a custom hook to reset the sensor used in set_sensor_function(). Example: $/code{.cpp}$ my_lift.set_ \leftarrow sensor_reset(my_sensor.resetPosition); $/code{.cpp}$

set_setpoint()

Manually set a setpoint value for the lift PID to go to.

val Lift setpoint, in motor revolutions or sensor units defined by get_sensor. Cannot be outside the softstops.

Returns

True if the pid has reached the setpoint

The documentation for this class was generated from the following file:

• lift.h

4.33 Lift< T >::lift_cfg_t Struct Reference

```
#include <lift.h>
```

4.33.1 Detailed Description

```
template<typename T> struct Lift< T>::lift_cfg_t
```

lift_cfg_t holds the physical parameter specifications of a lify system. includes:

- · maximum speeds for the system
- · softstops to stop the lift from hitting the hard stops too hard

The documentation for this struct was generated from the following file:

• lift.h

4.34 Logger Class Reference

Class to simplify writing to files.

```
#include <logger.h>
```

Public Member Functions

• Logger (const std::string &filename)

Create a logger that will save to a file.

• Logger (const Logger &I)=delete

copying not allowed

• Logger & operator= (const Logger &I)=delete

copying not allowed

void Log (const std::string &s)

Write a string to the log.

void Log (LogLevel level, const std::string &s)

Write a string to the log with a loglevel.

• void LogIn (const std::string &s)

Write a string and newline to the log.

void LogIn (LogLevel level, const std::string &s)

Write a string and a newline to the log with a loglevel.

void Logf (const char *fmt,...)

Write a formatted string to the log.

• void Logf (LogLevel level, const char *fmt,...)

Write a formatted string to the log with a loglevel.

Static Public Attributes

static constexpr int MAX_FORMAT_LEN = 512
 maximum size for a string to be before it's written

4.34.1 Detailed Description

Class to simplify writing to files.

4.34.2 Constructor & Destructor Documentation

Logger()

Create a logger that will save to a file.

Parameters

filename the file to save to

4.34.3 Member Function Documentation

Log() [1/2]

Write a string to the log.

```
s the string to write
```

Log() [2/2]

```
void Logger::Log (
          LogLevel level,
          const std::string & s)
```

Write a string to the log with a loglevel.

Parameters

| level | the level to write. DEBUG, NOTICE, WARNING, ERROR, CRITICAL, TIME |
|-------|---|
| s | the string to write |

Logf() [1/2]

Write a formatted string to the log.

Parameters

| fmt | the format string (like printf) |
|-----|---------------------------------|
| | the args |

Logf() [2/2]

```
void Logger::Logf (
            LogLevel level,
            const char * fmt,
            ...)
```

Write a formatted string to the log with a loglevel.

Parameters

| level | the level to write. DEBUG, NOTICE, WARNING, ERROR, CRITICAL, TIME |
|-------|---|
| fmt | the format string (like printf) |
| | the args |

LogIn() [1/2]

Write a string and newline to the log.

```
s the string to write
```

LogIn() [2/2]

Write a string and a newline to the log with a loglevel.

Parameters

| lev | el the | level to write | . DEBUG, | NOTICE, | WARNING, | ERROR, | CRITICAL, | TIME |
|-----|--------|----------------|----------|---------|----------|--------|-----------|------|
| s | the | string to writ | е | | | | | |

The documentation for this class was generated from the following files:

- · logger.h
- logger.cpp

4.35 MotionController::m_profile_cfg_t Struct Reference

```
#include <motion_controller.h>
```

Public Attributes

• double max_v

the maximum velocity the robot can drive

double accel

the most acceleration the robot can do

• PID::pid_config_t pid_cfg

configuration parameters for the internal PID controller

FeedForward::ff_config_t ff_cfg

configuration parameters for the internal

4.35.1 Detailed Description

m_profile_config holds all data the motion controller uses to plan paths When motion pofile is given a target to drive to, max_v and accel are used to make the trapezoid profile instructing the controller how to drive pid_cfg, ff_cfg are used to find the motor outputs necessary to execute this path

The documentation for this struct was generated from the following file:

· motion_controller.h

4.36 StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage Class Reference

MaybeMessage a message of Message type or nothing MaybeMessage $m = \{\}$; // empty MaybeMessag

```
#include <state_machine.h>
```

Public Member Functions

MaybeMessage ()

Empty message - when theres no message.

MaybeMessage (Message msg)

Create a maybemessage with a message.

• bool has_message ()

check if the message is here

Message message ()

Get the message stored. The return value is invalid unless has_message returned true.

4.36.1 Detailed Description

template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log = false> class StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage

MaybeMessage a message of Message type or nothing MaybeMessage $m = \{\}$; // empty MaybeMessag

4.36.2 Constructor & Destructor Documentation

MaybeMessage()

Create a maybemessage with a message.

Parameters

msg the message to hold on to

4.36.3 Member Function Documentation

has message()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
bool StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage::has_message ()
[inline]
```

check if the message is here

Returns

true if there is a message

message()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
Message StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage::message ()
[inline]
```

Get the message stored. The return value is invalid unless has message returned true.

Returns

The message if it exists. Undefined otherwise

The documentation for this class was generated from the following file:

state_machine.h

4.37 MecanumDrive Class Reference

```
#include <mecanum_drive.h>
```

Classes

· struct mecanumdrive_config_t

Public Member Functions

- MecanumDrive (vex::motor &left_front, vex::motor &right_front, vex::motor &left_rear, vex::motor &right_rear, vex::rotation *lateral_wheel=NULL, vex::inertial *imu=NULL, mecanumdrive_config_t *config=NULL)
- void drive raw (double direction deg, double magnitude, double rotation)
- void drive (double left_y, double left_x, double right_x, int power=2)
- bool auto drive (double inches, double direction, double speed, bool gyro correction=true)
- bool auto_turn (double degrees, double speed, bool ignore_imu=false)

4.37.1 Detailed Description

A class representing the Mecanum drivetrain. Contains 4 motors, a possible IMU (intertial), and a possible undriven perpendicular wheel.

4.37.2 Constructor & Destructor Documentation

MecanumDrive()

```
MecanumDrive::MecanumDrive (
    vex::motor & left_front,
    vex::motor & right_front,
    vex::motor & left_rear,
    vex::motor & right_rear,
    vex::rotation * lateral_wheel = NULL,
    vex::inertial * imu = NULL,
    mecanumdrive_config_t * config = NULL)
```

Create the Mecanum drivetrain object

4.37.3 Member Function Documentation

auto drive()

Drive the robot in a straight line automatically. If the inertial was declared in the constructor, use it to correct while driving. If the lateral wheel was declared in the constructor, use it for more accurate positioning while strafing.

Parameters

| inches | How far the robot should drive, in inches |
|-----------------|--|
| direction | What direction the robot should travel in, in degrees. 0 is forward, +/-180 is reverse, clockwise is positive. |
| speed | The maximum speed the robot should travel, in percent: -1.0->+1.0 |
| gyro_correction | =true Whether or not to use the gyro to help correct while driving. Will always be false if no gyro was declared in the constructor. |

Drive the robot in a straight line automatically. If the inertial was declared in the constructor, use it to correct while driving. If the lateral wheel was declared in the constructor, use it for more accurate positioning while strafing.

Parameters

| inches | How far the robot should drive, in inches |
|-----------------|---|
| direction | What direction the robot should travel in, in degrees. 0 is forward, +/-180 is reverse, clockwise is positive. |
| speed | The maximum speed the robot should travel, in percent: -1.0->+1.0 |
| gyro_correction | = true Whether or not to use the gyro to help correct while driving. Will always be false if no gyro was declared in the constructor. |

Returns

Whether or not the maneuver is complete.

auto_turn()

Autonomously turn the robot X degrees over it's center point. Uses a closed loop for control.

Parameters

| degrees | How many degrees to rotate the robot. Clockwise postive. | |
|------------|---|--|
| speed | What percentage to run the motors at: 0.0 -> 1.0 | |
| ignore_imu | =false Whether or not to use the Inertial for determining angle. Will instead use circumference | |
| | formula + robot's wheelbase + encoders to determine. | |

Returns

whether or not the robot has finished the maneuver

Autonomously turn the robot X degrees over it's center point. Uses a closed loop for control.

Parameters

| degrees | How many degrees to rotate the robot. Clockwise postive. | |
|------------|--|--|
| speed | What percentage to run the motors at: 0.0 -> 1.0 | |
| ignore_imu | = false Whether or not to use the Inertial for determining angle. Will instead use circumference | |
| | formula + robot's wheelbase + encoders to determine. | |

Returns

whether or not the robot has finished the maneuver

drive()

Drive the robot with a mecanum-style / arcade drive. Inputs are in percent (-100.0 -> 100.0) straight from the controller. Controls are mixed, so the robot can drive forward / strafe / rotate all at the same time.

Parameters

| left_y | left joystick, Y axis (forward / backwards) |
|--------|---|
| left_x | left joystick, X axis (strafe left / right) |
| right← | right joystick, X axis (rotation left / right) |
| _X | |
| power | =2 how much of a "curve" there should be on drive controls; better for low speed maneuvers. Leave |
| | blank for a default curve of 2 (higher means more fidelity) |

Drive the robot with a mecanum-style / arcade drive. Inputs are in percent (-100.0 -> 100.0) straight from the controller. Controls are mixed, so the robot can drive forward / strafe / rotate all at the same time.

| left_y | left joystick, Y axis (forward / backwards) |
|--------|--|
| left_x | left joystick, X axis (strafe left / right) |
| right← | right joystick, X axis (rotation left / right) |
| _X | |
| power | = 2 how much of a "curve" there should be on drive controls; better for low speed maneuvers. Leave |
| | blank for a default curve of 2 (higher means more fidelity) |

drive_raw()

Drive the robot using vectors. This handles all the math required for mecanum control.

Parameters

| direction_deg | the direction to drive the robot, in degrees. 0 is forward, 180 is back, clockwise is positive, counterclockwise is negative. |
|---------------|---|
| magnitude | How fast the robot should drive, in percent: 0.0->1.0 |
| rotation | How fast the robot should rotate, in percent: -1.0->+1.0 |

The documentation for this class was generated from the following files:

- · mecanum_drive.h
- · mecanum_drive.cpp

4.38 MecanumDrive::mecanumdrive_config_t Struct Reference

```
#include <mecanum_drive.h>
```

4.38.1 Detailed Description

Configure the Mecanum drive PID tunings and robot configurations

The documentation for this struct was generated from the following file:

· mecanum_drive.h

4.39 motion_t Struct Reference

#include <trapezoid_profile.h>

Public Attributes

· double pos

1d position at this point in time

• double vel

1d velocity at this point in time

double accel

1d acceleration at this point in time

4.39.1 Detailed Description

motion_t is a description of 1 dimensional motion at a point in time.


The documentation for this struct was generated from the following file:

· trapezoid_profile.h

4.40 MotionController Class Reference

```
#include <motion_controller.h>
```

Inheritance diagram for MotionController:



Classes

• struct m_profile_cfg_t

Public Member Functions

• MotionController (m_profile_cfg_t &config)

Construct a new Motion Controller object.

• void init (double start_pt, double end_pt) override

Initialize the motion profile for a new movement This will also reset the PID and profile timers.

• double update (double sensor_val) override

Update the motion profile with a new sensor value.

- · double get () override
- void set_limits (double lower, double upper) override
- bool is_on_target () override
- motion_t get_motion () const

Static Public Member Functions

• static FeedForward::ff_config_t tune_feedforward (TankDrive &drive, OdometryTank &odometry, double pct=0.6, double duration=2)

4.40.1 Detailed Description

Motion Controller class

This class defines a top-level motion profile, which can act as an intermediate between a subsystem class and the motors themselves

This takes the constants kS, kV, kA, kP, kI, kD, max_v and acceleration and wraps around a feedforward, PID and trapezoid profile. It does so with the following formula:

out = feedfoward.calculate(motion_profile.get(time_s)) + pid.get(motion_profile.get(time_s))

For PID and Feedforward specific formulae, see pid.h, feedforward.h, and trapezoid_profile.h

Author

Ryan McGee

Date

7/13/2022

4.40.2 Constructor & Destructor Documentation

MotionController()

Construct a new Motion Controller object.

Parameters

config

The definition of how the robot is able to move max_v Maximum velocity the movement is capable of accel Acceleration / deceleration of the movement pid_cfg Definitions of kP, kI, and kD ff_cfg Definitions of kS, kV, and kA

4.40.3 Member Function Documentation

get()

```
double MotionController::get () [override], [virtual]
```

Returns

the last saved result from the feedback controller

Implements Feedback.

get_motion()

```
motion_t MotionController::get_motion () const
```

Returns

The current postion, velocity and acceleration setpoints

init()

Initialize the motion profile for a new movement This will also reset the PID and profile timers.

Parameters

| start⊷ | Movement starting position |
|--------|----------------------------|
| _pt | |
| end_pt | Movement ending posiiton |

Implements Feedback.

is_on_target()

```
bool MotionController::is_on_target () [override], [virtual]
```

Returns

Whether or not the movement has finished, and the PID confirms it is on target

Implements Feedback.

set_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied. if limits are applied, the controller will not target any value below lower or above upper

Parameters

| lower | upper limit |
|-------|--------------|
| upper | lower limiet |

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

| lower | Upper limit |
|-------|-------------|
| upper | Lower limit |

Implements Feedback.

tune_feedforward()

This method attempts to characterize the robot's drivetrain and automatically tune the feedforward. It does this by first calculating the kS (voltage to overcome static friction) by slowly increasing the voltage until it moves.

Next is kV (voltage to sustain a certain velocity), where the robot will record it's steady-state velocity at 'pct' speed.

Finally, kA (voltage needed to accelerate by a certain rate), where the robot will record the entire movement's velocity and acceleration, record a plot of [X=(pct-kV*V-kS), Y=(Acceleration)] along the movement, and since kA*Accel = pct-kV*V-kS, the reciprocal of the linear regression is the kA value.

Parameters

| drive | The tankdrive to operate on | |
|----------|--|--|
| odometry | The robot's odometry subsystem | |
| pct | Maximum velocity in percent (0->1.0) | |
| duration | Amount of time the robot should be moving for the test | |

Returns

A tuned feedforward object

update()

Update the motion profile with a new sensor value.

Parameters

| sensor_val | Value from the sensor |
|------------|-----------------------|
|------------|-----------------------|

Returns

the motor input generated from the motion profile

Implements Feedback.

The documentation for this class was generated from the following files:

- · motion_controller.h
- motion_controller.cpp

4.41 MovingAverage Class Reference

```
#include <moving_average.h>
```

Inheritance diagram for MovingAverage:



Public Member Functions

- MovingAverage (int buffer_size)
- MovingAverage (int buffer size, double starting value)
- void add_entry (double n) override
- · double get value () const override
- int get_size () const

4.41.1 Detailed Description

MovingAverage

A moving average is a way of smoothing out noisy data. For many sensor readings, the noise is roughly symmetric around the actual value. This means that if you collect enough samples those that are too high are cancelled out by the samples that are too low leaving the real value.

The MovingAverage class provides a simple interface to do this smoothing from our noisy sensor values.

WARNING: because we need a lot of samples to get the actual value, the value given by the MovingAverage will 'lag' behind the actual value that the sensor is reading. Using a MovingAverage is thus a tradeoff between accuracy and lag time (more samples) vs. less accuracy and faster updating (less samples).

4.41.2 Constructor & Destructor Documentation

MovingAverage() [1/2]

Create a moving average calculator with 0 as the default value

Parameters

buffer_size The size of the buffer. The number of samples that constitute a valid reading

MovingAverage() [2/2]

```
MovingAverage::MovingAverage (
          int buffer_size,
          double starting_value)
```

Create a moving average calculator with a specified default value

| buffer_size | The size of the buffer. The number of samples that constitute a valid reading |
|----------------|---|
| starting_value | The value that the average will be before any data is added |

4.41.3 Member Function Documentation

add_entry()

Add a reading to the buffer Before: [1 1 2 2 3 3] => 2 $^{\wedge}$ After: [2 1 2 2 3 3] => 2.16 $^{\wedge}$

Parameters

n the sample that will be added to the moving average.

Implements Filter.

get_size()

```
int MovingAverage::get_size () const
```

How many samples the average is made from

Returns

the number of samples used to calculate this average

get_value()

```
double MovingAverage::get_value () const [override], [virtual]
```

Returns the average based off of all the samples collected so far

Returns

the calculated average. sum(samples)/numsamples

How many samples the average is made from

Returns

the number of samples used to calculate this average

Implements Filter.


The documentation for this class was generated from the following files:

- · moving_average.h
- moving_average.cpp

4.42 Odometry3Wheel Class Reference

#include <odometry_3wheel.h>

Inheritance diagram for Odometry3Wheel:



Classes

· struct odometry3wheel_cfg_t

Public Member Functions

- Odometry3Wheel (CustomEncoder &lside_fwd, CustomEncoder &rside_fwd, CustomEncoder &off_axis, odometry3wheel_cfg_t &cfg, bool is_async=true)
- pose t update () override
- void tune (vex::controller &con, TankDrive &drive)

Public Member Functions inherited from OdometryBase

- OdometryBase (bool is async)
- virtual pose_t get_position (void)
- virtual void set_position (const pose_t &newpos=zero_pos)
- void end_async ()
- double get_speed ()
- double get accel ()
- double get_angular_speed_deg ()
- double get_angular_accel_deg ()

Additional Inherited Members

Static Public Member Functions inherited from OdometryBase

- static int background_task (void *ptr)
- static double pos_diff (pose_t start_pos, pose_t end_pos)
- static double rot_diff (pose_t pos1, pose_t pos2)
- static double smallest_angle (double start_deg, double end_deg)
- static pose t pose exponential (const Eigen::Vector3d old pose, const Eigen::Vector3d twist)

Public Attributes inherited from OdometryBase

• bool end_task = false

end_task is true if we instruct the odometry thread to shut down

Static Public Attributes inherited from OdometryBase

static constexpr pose_t zero_pos = {.x = 0.0L, .y = 0.0L, .rot = 90.0L}

Protected Attributes inherited from OdometryBase

- vex::task * handle
- vex::mutex mut
- · pose t current pos
- double speed
- · double accel
- double ang_speed_deg
- double ang_accel_deg

4.42.1 Detailed Description

Odometry3Wheel

This class handles the code for a standard 3-pod odometry setup, where there are 3 "pods" made up of undriven (dead) wheels connected to encoders in the following configuration:

Where O is the center of rotation. The robot will monitor the changes in rotation of these wheels and calculate the robot's X, Y and rotation on the field.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

Author

Ryan McGee

Date

Oct 31 2022

4.42.2 Constructor & Destructor Documentation

Odometry3Wheel()

Construct a new Odometry 3 Wheel object

| lside_fwd | left-side encoder reference |
|-----------|--|
| rside_fwd | right-side encoder reference |
| off_axis | off-axis (perpendicular) encoder reference |
| cfg | robot odometry configuration |
| is_async | true to constantly run in the background |

4.42.3 Member Function Documentation

tune()

A guided tuning process to automatically find tuning parameters. This method is blocking, and returns when tuning has finished. Follow the instructions on the controller to complete the tuning process

Parameters

| con | Controller reference, for screen and button control |
|-------|---|
| drive | Drivetrain reference for robot control |

A guided tuning process to automatically find tuning parameters. This method is blocking, and returns when tuning has finished. Follow the instructions on the controller to complete the tuning process

It is assumed the gear ratio and encoder PPR have been set correctly

update()

```
pose_t Odometry3Wheel::update () [override], [virtual]
```

Update the current position of the robot once, using the current state of the encoders and the previous known location

Returns

the robot's updated position

Implements OdometryBase.

The documentation for this class was generated from the following files:

- · odometry_3wheel.h
- · odometry_3wheel.cpp

4.43 Odometry3Wheel::odometry3wheel_cfg_t Struct Reference

#include <odometry_3wheel.h>

Public Attributes

- double wheelbase_dist
- double off_axis_center_dist
- · double wheel diam

4.43.1 Detailed Description

odometry3wheel_cfg_t holds all the specifications for how to calculate position with 3 encoders See the core wiki for what exactly each of these parameters measures

4.43.2 Member Data Documentation

off_axis_center_dist

double Odometry3Wheel::odometry3wheel_cfg_t::off_axis_center_dist

distance from the center of the robot to the center off axis wheel

wheel_diam

double Odometry3Wheel::odometry3wheel_cfg_t::wheel_diam

the diameter of the tracking wheel

wheelbase_dist

double Odometry3Wheel::odometry3wheel_cfg_t::wheelbase_dist

distance from the center of the left wheel to the center of the right wheel


The documentation for this struct was generated from the following file:

· odometry_3wheel.h

4.44 OdometryBase Class Reference

#include <odometry_base.h>

Inheritance diagram for OdometryBase:



Public Member Functions

- OdometryBase (bool is_async)
- virtual pose t get position (void)
- virtual void set_position (const pose_t &newpos=zero_pos)
- virtual pose_t update ()=0
- void end_async ()
- double get speed ()
- double get accel ()
- double get_angular_speed_deg ()
- double get_angular_accel_deg ()

Static Public Member Functions

- static int background_task (void *ptr)
- static double pos_diff (pose_t start_pos, pose_t end_pos)
- static double rot_diff (pose_t pos1, pose_t pos2)
- static double smallest_angle (double start_deg, double end_deg)
- static pose_t pose_exponential (const Eigen::Vector3d old_pose, const Eigen::Vector3d twist)

Public Attributes

• bool end_task = false

end_task is true if we instruct the odometry thread to shut down

Static Public Attributes

static constexpr pose_t zero_pos = {.x = 0.0L, .y = 0.0L, .rot = 90.0L}

Protected Attributes

- vex::task * handle
- vex::mutex mut
- pose_t current_pos
- double speed
- double accel
- double ang_speed_deg
- double ang_accel_deg

4.44.1 Detailed Description

OdometryBase

This base class contains all the shared code between different implementations of odometry. It handles the asynchronous management, position input/output and basic math functions, and holds positional types specific to field orientation.

All future odometry implementations should extend this file and redefine update() function.

Author

Ryan McGee

Date

Aug 11 2021

4.44.2 Constructor & Destructor Documentation

OdometryBase()

```
OdometryBase::OdometryBase (
          bool is_async)
```

Construct a new Odometry Base object

Parameters

is_async True to run constantly in the background, false to call update() manually

4.44.3 Member Function Documentation

background_task()

Function that runs in the background task. This function pointer is passed to the vex::task constructor.

Parameters

ptr | Pointer to OdometryBase object

Returns

Required integer return code. Unused.

end_async()

```
void OdometryBase::end_async ()
```

End the background task. Cannot be restarted. If the user wants to end the thread but keep the data up to date, they must run the update() function manually from then on.

get_accel()

```
double OdometryBase::get_accel ()
```

Get the current acceleration

Returns

the acceleration rate of the robot (inch/s^2)

get_angular_accel_deg()

```
double OdometryBase::get_angular_accel_deg ()
```

Get the current angular acceleration in degrees

Returns

the angular acceleration at which we are turning (deg/s $^{\wedge}$ 2)

get_angular_speed_deg()

```
double OdometryBase::get_angular_speed_deg ()
```

Get the current angular speed in degrees

Returns

the angular velocity at which we are turning (deg/s)

get_position()

Gets the current position and rotation

Returns

the position that the odometry believes the robot is at

Gets the current position and rotation

get_speed()

```
double OdometryBase::get_speed ()
```

Get the current speed

Returns

the speed at which the robot is moving and grooving (inch/s)

pos_diff()

Get the distance between two points

| start_pos | distance from this point |
|-----------|--------------------------|
| end_pos | to this point |

Returns

the euclidean distance between start_pos and end_pos

pose_exponential()

Applies a twist (pose delta) to a pose by including first order dynamics of heading. Can be thought of as applying a twist as following an arc rather than a straight line.

 $\verb|https://file.tavsys.net/control/controls-engineering-in-frc.pdf\\| \$section. \leftarrow 10.2$

Parameters

| old_pose | The pose to which the twist will be applied |
|----------|---|
| twist | The twist, represents a pose delta |

rot_diff()

Get the change in rotation between two points

Parameters

| pos1 | position with initial rotation |
|------|--------------------------------|
| pos2 | position with final rotation |

Returns

change in rotation between pos1 and pos2

Get the change in rotation between two points

set_position()

Sets the current position of the robot

| newpos | the new position that the odometry will believe it is at |
|--------|--|
|--------|--|

Sets the current position of the robot

Reimplemented in OdometryTank.

smallest_angle()

Get the smallest difference in angle between a start heading and end heading. Returns the difference between -180 degrees and +180 degrees, representing the robot turning left or right, respectively.

Parameters

| start_deg | intitial angle (degrees) |
|-----------|--------------------------|
| end_deg | final angle (degrees) |

Returns

the smallest angle from the initial to the final angle. This takes into account the wrapping of rotations around 360 degrees

Get the smallest difference in angle between a start heading and end heading. Returns the difference between -180 degrees and +180 degrees, representing the robot turning left or right, respectively.

update()

```
virtual pose_t OdometryBase::update () [pure virtual]
```

Update the current position on the field based on the sensors

Returns

the location that the robot is at after the odometry does its calculations

Implemented in Odometry3Wheel, and OdometryTank.

4.44.4 Member Data Documentation

accel

```
double OdometryBase::accel [protected]
```

the rate at which we are accelerating (inch/s^2)

ang_accel_deg

```
double OdometryBase::ang_accel_deg [protected]
```

the rate at which we are accelerating our turn (deg/s^2)

ang_speed_deg

```
double OdometryBase::ang_speed_deg [protected]
```

the speed at which we are turning (deg/s)

current_pos

```
pose_t OdometryBase::current_pos [protected]
```

Current position of the robot in terms of x,y,rotation

handle

```
vex::task* OdometryBase::handle [protected]
```

handle to the vex task that is running the odometry code

mut

```
vex::mutex OdometryBase::mut [protected]
```

Mutex to control multithreading

speed

```
double OdometryBase::speed [protected]
```

the speed at which we are travelling (inch/s)

zero_pos

```
pose_t OdometryBase::zero_pos = {.x = 0.0L, .y = 0.0L, .rot = 90.0L} [inline], [static],
[constexpr]
```

Zeroed position. X=0, Y=0, Rotation= 90 degrees

The documentation for this class was generated from the following files:


- · odometry_base.h
- odometry_base.cpp

4.45 screen::OdometryPage Class Reference

a page that shows odometry position and rotation and a map (if an sd card with the file is on)

```
#include <screen.h>
```

Inheritance diagram for screen::OdometryPage:



Public Member Functions

- OdometryPage (OdometryBase &odom, double robot_width, double robot_height, bool do_trail)
 Create an odometry trail. Make sure odometry is initilized before now.
- void update (bool was_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

4.45.1 Detailed Description

a page that shows odometry position and rotation and a map (if an sd card with the file is on)

4.45.2 Constructor & Destructor Documentation

OdometryPage()

```
screen::OdometryPage::OdometryPage (
    OdometryBase & odom,
    double robot_width,
    double robot_height,
    bool do_trail)
```

Create an odometry trail. Make sure odometry is initilized before now.

Parameters

| odom | the odometry system to monitor |
|--------------|---|
| robot_width | the width (side to side) of the robot in inches. Used for visualization |
| robot_height | the robot_height (front to back) of the robot in inches. Used for visualization |
| do_trail | whether or not to calculate and draw the trail. Drawing and storing takes a very <i>slight</i> extra amount of processing power |

4.45.3 Member Function Documentation

draw()

See also

Page::draw

Reimplemented from screen::Page.

update()

```
void screen::OdometryPage::update (
          bool was_pressed,
          int x,
          int y) [override], [virtual]
```

See also

Page::update

Reimplemented from screen::Page.


The documentation for this class was generated from the following files:

- screen.h
- screen.cpp

4.46 OdometryTank Class Reference

```
#include <odometry_tank.h>
```

Inheritance diagram for OdometryTank:



Public Member Functions

- OdometryTank (CustomEncoder &left_custom_enc, CustomEncoder &right_custom_enc, robot_specs_t &config, vex::inertial *imu=NULL, bool is_async=true)
- pose_t update () override
- void set_position (const pose_t &newpos=zero_pos) override

Public Member Functions inherited from OdometryBase

- OdometryBase (bool is_async)
- virtual pose_t get_position (void)
- void end async ()
- double get_speed ()
- double get_accel ()
- double get_angular_speed_deg ()
- double get_angular_accel_deg ()

Additional Inherited Members

Static Public Member Functions inherited from OdometryBase

- static int background task (void *ptr)
- static double pos_diff (pose_t start_pos, pose_t end_pos)
- static double rot diff (pose t pos1, pose t pos2)
- static double smallest angle (double start deg, double end deg)
- static pose_t pose_exponential (const Eigen::Vector3d old_pose, const Eigen::Vector3d twist)

Public Attributes inherited from OdometryBase

• bool end_task = false

end_task is true if we instruct the odometry thread to shut down

Static Public Attributes inherited from OdometryBase

• static constexpr pose t zero pos = {.x = 0.0L, .y = 0.0L, .rot = 90.0L}

Protected Attributes inherited from OdometryBase

- vex::task * handle
- vex::mutex mut
- pose_t current_pos
- double speed
- double accel
- · double and speed deg
- double ang_accel_deg

4.46.1 Detailed Description

OdometryTank defines an odometry system for a tank drivetrain This requires encoders in the same orientation as the drive wheels Odometry is a "start and forget" subsystem, which means once it's created and configured, it will constantly run in the background and track the robot's X, Y and rotation coordinates.

4.46.2 Constructor & Destructor Documentation

OdometryTank() [1/3]

```
OdometryTank::OdometryTank (
    vex::motor_group & left_side,
    vex::motor_group & right_side,
    robot_specs_t & config,
    vex::inertial * imu = NULL,
    bool is_async = true)
```

Initialize the Odometry module, calculating position from the drive motors.

Parameters

| left_side | The left motors |
|------------|---|
| right_side | The right motors |
| config | the specifications that supply the odometry with descriptions of the robot. See robot_specs_t for what is contained |
| imu | The robot's inertial sensor. If not included, rotation is calculated from the encoders. |
| is_async | If true, position will be updated in the background continuously. If false, the programmer will have to manually call update(). |

OdometryTank() [2/3]

Initialize the Odometry module, calculating position from the drive motors.

Parameters

| left_custom_enc | The left custom encoder |
|------------------|---|
| right_custom_enc | The right custom encoder |
| config | the specifications that supply the odometry with descriptions of the robot. See robot_specs_t for what is contained |
| imu | The robot's inertial sensor. If not included, rotation is calculated from the encoders. |
| is_async | If true, position will be updated in the background continuously. If false, the programmer will have to manually call update(). |

OdometryTank() [3/3]

```
OdometryTank::OdometryTank (
    vex::encoder & left_vex_enc,
    vex::encoder & right_vex_enc,
    robot_specs_t & config,
    vex::inertial * imu = NULL,
    bool is_async = true)
```

Initialize the Odometry module, calculating position from the drive motors.

Parameters

| left_vex_enc | The left vex encoder |
|---------------|---|
| right_vex_enc | The right vex encoder |
| config | the specifications that supply the odometry with descriptions of the robot. See robot_specs_t for what is contained |
| imu | The robot's inertial sensor. If not included, rotation is calculated from the encoders. |
| is_async | If true, position will be updated in the background continuously. If false, the programmer will have to manually call update(). |

4.46.3 Member Function Documentation

set_position()

set_position tells the odometry to place itself at a position

Parameters

| newpos | the position the odometry will take |
|--------|-------------------------------------|
| newpos | the position the odometry will take |

Resets the position and rotational data to the input.

Reimplemented from OdometryBase.

update()

```
pose_t OdometryTank::update () [override], [virtual]
```

Update the current position on the field based on the sensors

Returns

the position that odometry has calculated itself to be at

Update, store and return the current position of the robot. Only use if not initializing with a separate thread.

Implements OdometryBase.

The documentation for this class was generated from the following files:

- odometry_tank.h
- odometry_tank.cpp

4.47 OdomSetPosition Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- OdomSetPosition (OdometryBase &odom, const pose_t &newpos=OdometryBase::zero_pos)
- · bool run () override

4.47.1 Detailed Description

AutoCommand wrapper class for the set_position function in the Odometry class

4.47.2 Constructor & Destructor Documentation

OdomSetPosition()

```
OdomSetPosition::OdomSetPosition (
         OdometryBase & odom,
         const pose_t & newpos = OdometryBase::zero_pos)
```

constructs a new OdomSetPosition command

Parameters

| 00 | dom | the odometry system we are setting |
|----|-------|---|
| ne | ewpos | the position we are telling the odometry to take. defaults to $(0, 0)$, angle = 90 |

Construct an Odometry set pos

Parameters

| odom | the odometry system we are setting |
|--------|---|
| newpos | the now position to set the odometry to |

4.47.3 Member Function Documentation

run()

```
bool OdomSetPosition::run () [override]
```

Run set_position Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:


- drive_commands.h
- drive_commands.cpp

4.48 screen::Page Class Reference

Page describes one part of the screen slideshow.

```
#include <screen.h>
```

Inheritance diagram for screen::Page:



Public Member Functions

- virtual void update (bool was_pressed, int x, int y)

 collect data, respond to screen input, do fast things (runs at 50hz even if you're not focused on this Page (only drawn page gets touch updates))
- virtual void draw (vex::brain::lcd &screen, bool first_draw, unsigned int frame_number) draw stored data to the screen (runs at 10 hz and only runs if this page is in front)

4.48.1 Detailed Description

Page describes one part of the screen slideshow.

4.48.2 Member Function Documentation

draw()

draw stored data to the screen (runs at 10 hz and only runs if this page is in front)

Parameters

| first_draw | true if we just switched to this page | |
|--------------|--|---|
| frame_number | frame of drawing we are on (basically an animation tick) | l |

Reimplemented in screen::FunctionPage, screen::OdometryPage, screen::PIDPage, and screen::StatsPage.

update()

collect data, respond to screen input, do fast things (runs at 50hz even if you're not focused on this Page (only drawn page gets touch updates))

| was_pressed | true if the screen has been pressed |
|-------------|--|
| X | x position of screen press (if the screen was pressed) |
| У | y position of screen press (if the screen was pressed) |

Reimplemented in screen::FunctionPage, screen::OdometryPage, screen::PIDPage, and screen::StatsPage.

The documentation for this class was generated from the following file:

· screen.h

4.49 Parallel Class Reference

Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on_timeout on all children continue.

```
#include <auto_command.h>
```

4.49.1 Detailed Description

Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on_timeout on all children continue.

The documentation for this class was generated from the following files:

- · auto_command.h
- auto_command.cpp

4.50 PurePursuit::Path Class Reference

```
#include <pure_pursuit.h>
```

Public Member Functions

- Path (std::vector < point_t > points, double radius)
- std::vector< point_t > get_points ()
- double get_radius ()
- bool is_valid ()

4.50.1 Detailed Description

Wrapper for a vector of points, checking if any of the points are too close for pure pursuit

4.50.2 Constructor & Destructor Documentation

Path()

```
PurePursuit::Path::Path (
          std::vector< point_t > points,
          double radius)
```

Create a Path

| points | the points that make up the path |
|--------|---------------------------------------|
| radius | the lookahead radius for pure pursuit |

4.50.3 Member Function Documentation

get_points()

```
std::vector< point_t > PurePursuit::Path::get_points ()
```

Get the points associated with this Path

get_radius()

```
double PurePursuit::Path::get_radius ()
```

Get the radius associated with this Path

is_valid()

```
bool PurePursuit::Path::is_valid ()
```

Get whether this path will behave as expected

The documentation for this class was generated from the following files:

- pure_pursuit.h
- pure_pursuit.cpp

4.51 PID Class Reference

```
#include <pid.h>
```

Inheritance diagram for PID:



Classes

• struct pid_config_t

4.51 PID Class Reference 83

Public Types

• enum ERROR TYPE

Public Member Functions

- PID (pid_config_t &config)
- · void init (double start_pt, double set_pt) override
- double update (double sensor_val) override
- double update (double sensor_val, double v_setpt)
- double get_sensor_val () const

gets the sensor value that we were last updated with

- · double get () override
- void set_limits (double lower, double upper) override
- bool is_on_target () override
- void reset ()
- double get_error ()
- · double get_target () const
- · void set target (double target)

Public Attributes

· pid_config_t & config

4.51.1 Detailed Description

PID Class

The PID object will determine it is "on target" when the error is within the deadband, for a duration of on target time

Author

Ryan McGee

Date

4/3/2020

4.51.2 Member Enumeration Documentation

out = kP*error + kI*integral(d Error) + kD*(dError/dt)

ERROR_TYPE

```
enum PID::ERROR_TYPE
```

An enum to distinguish between a linear and angular caluclation of PID error.

4.51.3 Constructor & Destructor Documentation

PID()

Create the PID object

config the configuration data for this controller

Create the PID object

4.51.4 Member Function Documentation

get()

```
double PID::get () [override], [virtual]
```

Gets the current PID out value, from when update() was last run

Returns

the Out value of the controller (voltage, RPM, whatever the PID controller is controlling)

Gets the current PID out value, from when update() was last run

Implements Feedback.

get_error()

```
double PID::get_error ()
```

Get the delta between the current sensor data and the target

Returns

the error calculated. how it is calculated depends on error_method specified in pid_config_t

Get the delta between the current sensor data and the target

get_sensor_val()

```
double PID::get_sensor_val () const
```

gets the sensor value that we were last updated with

Returns

sensor_val

4.51 PID Class Reference 85

get_target()

```
double PID::get_target () const
```

Get the PID's target

Returns

the target the PID controller is trying to achieve

init()

Inherited from Feedback for interoperability. Update the setpoint and reset integral accumulation

start_pt can be safely ignored in this feedback controller

| start_pt | commpletely ignored for PID. necessary to satisfy Feedback base |
|-----------|---|
| set_pt | sets the target of the PID controller |
| start_vel | completely ignored for PID. necessary to satisfy Feedback base |
| end_vel | sets the target end velocity of the PID controller |

Implements Feedback.

is_on_target()

```
bool PID::is_on_target () [override], [virtual]
```

Checks if the PID controller is on target.

Returns

true if the loop is within [deadband] for [on_target_time] seconds

Returns true if the loop is within [deadband] for [on_target_time] seconds

Implements Feedback.

reset()

```
void PID::reset ()
```

Reset the PID loop by resetting time since 0 and accumulated error.

set_limits()

Set the limits on the PID out. The PID out will "clip" itself to be between the limits.

Parameters

| lower | the lower limit. the PID controller will never command the output go below lower |
|-------|--|
| upper | the upper limit. the PID controller will never command the output go higher than upper |

Set the limits on the PID out. The PID out will "clip" itself to be between the limits.

Implements Feedback.

set_target()

Set the target for the PID loop, where the robot is trying to end up

4.51 PID Class Reference 87

Parameters

| target | the sensor reading we would like to achieve |
|--------|--|
| larget | The sensor reading we would like to deflicte |

Set the target for the PID loop, where the robot is trying to end up

update() [1/2]

Update the PID loop by taking the time difference from last update, and running the PID formula with the new sensor data

Parameters

Returns

the new output. What would be returned by PID::get()

Implements Feedback.

update() [2/2]

Update the PID loop by taking the time difference from last update, and running the PID formula with the new sensor data

Parameters

| sensor_val | the distance, angle, encoder position or whatever it is we are measuring |
|------------|--|
| v_setpt | Expected velocity setpoint, to subtract from the D term (for velocity control) |

Returns

the new output. What would be returned by PID::get()

4.51.5 Member Data Documentation

config

```
pid_config_t& PID::config
```

configuration struct for this controller. see pid_config_t for information about what this contains

The documentation for this class was generated from the following files:

- pid.h
- pid.cpp

4.52 PID::pid_config_t Struct Reference

```
#include <pid.h>
```

Public Attributes

• double p

proportional coeffecient p * error()

• double i

integral coeffecient i * integral(error)

· double d

derivitave coeffecient d * derivative(error)

· double deadband

at what threshold are we close enough to be finished

- · double on target time
- ERROR_TYPE error_method

4.52.1 Detailed Description

pid_config_t holds the configuration parameters for a pid controller In addition to the constant of proportional, integral and derivative, these parameters include:

- · deadband -
- on_target_time for how long do we have to be at the target to stop As well, pid_config_t holds an error type which determines whether errors should be calculated as if the sensor position is a measure of distance or an angle

4.52.2 Member Data Documentation

error_method

```
ERROR_TYPE PID::pid_config_t::error_method
```

Linear or angular. wheter to do error as a simple subtraction or to wrap

on_target_time

```
double PID::pid_config_t::on_target_time
```

the time in seconds that we have to be on target for to say we are officially at the target

The documentation for this struct was generated from the following file:


• pid.h

4.53 screen::PIDPage Class Reference

PIDPage provides a way to tune a pid controller on the screen.

```
#include <screen.h>
```

Inheritance diagram for screen::PIDPage:



Public Member Functions

- PIDPage (PID &pid, std::string name, std::function < void(void) > onchange=[]() {})
 Create a PIDPage.
- void update (bool was_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

4.53.1 Detailed Description

PIDPage provides a way to tune a pid controller on the screen.

4.53.2 Constructor & Destructor Documentation

PIDPage()

```
screen::PIDPage::PIDPage (
          PID & pid,
          std::string name,
          std::function< void(void) > onchange = []() {})
```

Create a PIDPage.

Parameters

| pid | the pid controller we're changing |
|----------|--|
| name | a name to recognize this pid controller if we've got multiple pid screens |
| onchange | a function that is called when a tuning parameter is changed. If you need to update stuff on that change register a handler here |

4.53.3 Member Function Documentation

draw()

See also

Page::draw

Reimplemented from screen::Page.

update()

```
void screen::PIDPage::update (
          bool was_pressed,
          int x,
          int y) [override], [virtual]
```

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:

- screen.h
- screen.cpp

4.54 point_t Struct Reference

```
#include <geometry.h>
```

Public Member Functions

- double dist (const point_t other) const
- point_t operator+ (const point_t &other) const
- point_t operator- (const point_t &other) const

Public Attributes

• double **x**

the x position in space

• double y

the y position in space

4.54.1 Detailed Description

Data structure representing an X,Y coordinate

4.54.2 Member Function Documentation

dist()

dist calculates the euclidian distance between this point and another point using the pythagorean theorem

Parameters

| other | the point to measure the distance from |
|-------|--|
|-------|--|

Returns

the euclidian distance between this and other

operator+()

Vector2D addition operation on points

Parameters

| other | the point to add on to this |
|-------|-----------------------------|

Returns

```
this + other (this.x + other.x, this.y + other.y)
```

operator-()

Vector2D subtraction operation on points

Parameters

| other the point_t to subtract from this |
|---|
|---|

Returns

```
this - other (this.x - other.x, this.y - other.y)
```

The documentation for this struct was generated from the following file:

· geometry.h

4.55 Pose2d Class Reference

```
#include <pose2d.h>
```

Public Member Functions

- Pose2d (const Translation2d &translation, const Rotation2d &rotation)
- Pose2d (const double &x, const double &y, const Rotation2d &rotation)
- Pose2d (const double &x, const double &y, const double &radians)
- Pose2d (const Translation2d &translation, const double &radians)
- Pose2d (const Eigen::Vector3d &pose vector)
- Translation2d translation () const
- · double x () const
- double y () const
- · Rotation2d rotation () const
- bool operator== (const Pose2d other) const
- Pose2d operator* (const double &scalar) const
- · Pose2d operator/ (const double &scalar) const
- Pose2d operator+ (const Transform2d &transform) const
- Transform2d operator- (const Pose2d &other) const
- Pose2d relative_to (const Pose2d &other) const
- Pose2d transform by (const Transform2d &transform) const
- Pose2d exp (const Twist2d &twist) const
- Twist2d log (const Pose2d &end pose) const

Friends

std::ostream & operator<< (std::ostream &os, const Pose2d &pose)

4.55.1 Detailed Description

Class representing a pose in 2d space with x, y, and rotational components

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

4.55.2 Constructor & Destructor Documentation

Pose2d() [1/5]

Constructs a pose with given translation and rotation components.

Parameters

| translation | translational component. |
|-------------|--------------------------|
| rotation | rotational component. |

Pose2d() [2/5]

Constructs a pose with given translation and rotation components.

Parameters

| X | x component. |
|----------|-----------------------|
| У | y component. |
| rotation | rotational component. |

Pose2d() [3/5]

```
Pose2d::Pose2d (

const double & x,

const double & y,

const double & radians)
```

Constructs a pose with given translation and rotation components.

Parameters

| X | x component. |
|---------|----------------------------------|
| У | y component. |
| radians | rotational component in radians. |

Pose2d() [4/5]

Constructs a pose with given translation and rotation components.

Parameters

| translation | translational component. |
|-------------|----------------------------------|
| radians | rotational component in radians. |

Pose2d() [5/5]

Constructs a pose with given translation and rotation components.

| pose_vector vector of the form [x, y, theta]. |
|---|
|---|

4.55.3 Member Function Documentation

exp()

```
Pose2d Pose2d::exp (

const Twist2d & twist) const
```

Applies a twist (pose delta) to a pose by including first order dynamics of heading.

When applying a twist, imagine a constant angular velocity, the translational components must be rotated into the global frame at every point along the twist, simply adding the deltas does not do this, and using euler integration results in some error. This is the analytic solution that that problem.

Can also be thought of more simply as applying a twist as following an arc rather than a straight line.

See this document for more information on the pose exponential and its derivation. https://file.

tavsys.net/control/controls-engineering-in-frc.pdf#section.10.2

Parameters

| old_pose | The pose to which the twist will be applied. |
|----------|--|
| twist | The twist, represents a pose delta. |

Returns

new pose that has been moved forward according to the twist.

log()

The inverse of the pose exponential.

Determines the twist required to go from this pose to the given end pose. suppose you have Pose2d a, Twist2d twist if a.exp(twist) = b then a.log(b) = twist

Parameters

```
end_pose the end pose to find the mapping to.
```

Returns

the twist required to go from this pose to the given end

operator*()

Multiplies this pose by a scalar. Simply multiplies each component.

| scalar | the scalar value to multiply by. |
|--------|----------------------------------|
|--------|----------------------------------|

operator+()

Adds a transform to this pose. Transforms the pose in the pose's frame.

Parameters

| transform | the change in pose. |
|-----------|---------------------|
|-----------|---------------------|

operator-()

Subtracts one pose from another to find the transform between them.

Parameters

| other | the pose to subtract. |
|-------|-----------------------|
|-------|-----------------------|

operator/()

Divides this pose by a scalar. Simply divides each component.

Parameters

```
scalar the scalar value to divide by.
```

operator==()

Compares this to another pose.

| other the other pose to compare to |
|------------------------------------|
|------------------------------------|

Returns

true if each of the components are within 1e-9 of each other.

relative_to()

Finds the pose equivalent to this pose relative to another arbitrary pose rather than the origin.

Parameters

| other | the pose representing the new origin. |
|-------|---------------------------------------|
|-------|---------------------------------------|

Returns

this pose relative to another pose.

rotation()

```
Rotation2d Pose2d::rotation () const
```

Returns the rotational component.

Returns

the rotational component.

transform_by()

Adds a transform to this pose. Simply adds each component.

Parameters

| transform | the change in pose. |
|-----------|---------------------|
| | 3 - |

Returns

the pose after being transformed.

translation()

```
Translation2d Pose2d::translation () const
```

Returns the translational component.

Returns

the translational component.

x()

```
double Pose2d::x () const
```

Returns the x value of the translational component.

Returns

the x value of the translational component.

y()

```
double Pose2d::y () const
```

Returns the y value of the translational component.

Returns

the y value of the translational component.

4.55.4 Friends And Related Symbol Documentation

operator <<

Sends a pose to an output stream. Ex. std::cout << pose;

```
prints "Pose2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- · pose2d.h
- · pose2d.cpp

4.56 pose_t Struct Reference

```
#include <geometry.h>
```

Public Attributes

double x

x position in the world

• double y

y position in the world

• double rot

rotation in the world

4.56.1 Detailed Description

Describes a single position and rotation

The documentation for this struct was generated from the following file:

• geometry.h

4.57 PurePursuitCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- PurePursuitCommand (TankDrive &drive_sys, Feedback &feedback, PurePursuit::Path path, directionType dir, double max_speed=1, double end_speed=0)
- bool run () override
- void on_timeout () override

4.57.1 Detailed Description

Autocommand wrapper class for pure pursuit function in the TankDrive class

4.57.2 Constructor & Destructor Documentation

PurePursuitCommand()

Construct a Pure Pursuit AutoCommand

| path | The list of coordinates to follow, in order |
|-----------|--|
| dir | Run the bot forwards or backwards |
| feedback | The feedback controller determining speed |
| max_speed | Limit the speed of the robot (for pid / pidff feedbacks) |

4.57.3 Member Function Documentation

on_timeout()

```
void PurePursuitCommand::on_timeout () [override]
```

Reset the drive system when it times out

run()

```
bool PurePursuitCommand::run () [override]
```

Direct call to TankDrive::pure_pursuit

The documentation for this class was generated from the following files:

- · drive_commands.h
- drive_commands.cpp

4.58 robot_specs_t Struct Reference

```
#include <robot_specs.h>
```

Public Attributes

· double robot_radius

if you were to draw a circle with this radius, the robot would be entirely contained within it

• double odom_wheel_diam

the diameter of the wheels used for

double odom_gear_ratio

the ratio of the odometry wheel to the encoder reading odometry data

double dist_between_wheels

the distance between centers of the central drive wheels

- · double drive correction cutoff
- Feedback * drive_feedback

the default feedback for autonomous driving

Feedback * turn_feedback

the defualt feedback for autonomous turning

PID::pid_config_t correction_pid

the pid controller to keep the robot driving in as straight a line as possible

4.58.1 Detailed Description

Main robot characterization struct. This will be passed to all the major subsystems that require info about the robot. All distance measurements are in inches.

4.58.2 Member Data Documentation

drive_correction_cutoff

```
double robot_specs_t::drive_correction_cutoff
```

the distance at which to stop trying to turn towards the target. If we are less than this value, we can continue driving forward to minimize our distance but will not try to spin around to point directly at the target

The documentation for this struct was generated from the following file:

· robot_specs.h

4.59 Rotation2d Class Reference

#include <rotation2d.h>

Public Member Functions

- Rotation2d (const double &radians)
- Rotation2d (const double &x, const double &y)
- Rotation2d (const Translation2d &translation)
- double radians () const
- double degrees () const
- · double revolutions () const
- double f_cos () const
- double f_sin () const
- double f_tan () const
- Eigen::Matrix2d rotation_matrix () const
- double wrapped_radians_180 () const
- double wrapped_degrees_180 () const
- double wrapped_revolutions_180 () const
- double wrapped_radians_360 () const
- double wrapped_degrees_360 () const
- double wrapped_revolutions_360 () const
- Rotation2d operator+ (const Rotation2d &other) const
- · Rotation2d operator- (const Rotation2d &other) const
- Rotation2d operator- () const
- Rotation2d operator* (const double &scalar) const
- Rotation2d operator/ (const double &scalar) const
- bool operator== (const Rotation2d &other) const

Friends

• std::ostream & operator<< (std::ostream &os, const Rotation2d &rotation)

4.59.1 Detailed Description

Class representing a rotation in 2d space. Stores theta in radians, as well as cos and sin.

Internally this angle is stored continuously, however there are functions that return wrapped angles: "180" is from [-pi, pi), [-180, 180), [-0.5, 0.5) "360" is from [0, 2pi), [0, 360), [0, 1)

4.59.2 Constructor & Destructor Documentation

Rotation2d() [1/3]

Constructs a rotation with the given value in radians.

Parameters

radians the value of the rotation in radians.

Rotation2d() [2/3]

Constructs a rotation given x and y values. Does not have to be normalized. The angle from the x axis to the point.

```
[theta] = [atan2(y, x)]
```

Parameters

| Х | the x value of the point |
|---|--------------------------|
| У | the y value of the point |

Rotation2d() [3/3]

Constructs a rotation given x and y values in the form of a Translation2d. Does not have to be normalized. The angle from the x axis to the point.

```
[theta] = [atan2(y, x)]
```

Parameters

translation

4.59.3 Member Function Documentation

degrees()

```
double Rotation2d::degrees () const
```

Returns the degree angle value.

Returns

the degree angle value.

f_cos()

```
double Rotation2d::f_cos () const
```

Returns the cosine of the angle value.

Returns

the cosine of the angle value

f_sin()

```
double Rotation2d::f_sin () const
```

Returns the sine of the angle value.

Returns

the sine of the angle value.

f_tan()

```
double Rotation2d::f_tan () const
```

Returns the tangent of the angle value.

Returns

the tangent of the angle value.

operator*()

```
Rotation2d Rotation2d::operator* (

const double & scalar) const
```

Multiplies this rotation by a scalar.

| scalar | the scalar value to multiply the rotation by. |
|--------|---|
|--------|---|

Returns

the rotation multiplied by the scalar.

operator+()

Adds the values of two rotations using a rotation matrix

[new_cos] = [other.cos, -other.sin][cos] [new_sin] = [other.sin, other.cos][sin] new_value = atan2(new_sin, new_cos)

Parameters

Returns

the sum of the two rotations.

Adds the values of two rotations using a rotation matrix.

[new_cos] = [other.cos, -other.sin][cos] [new_sin] = [other.sin, other.cos][sin] new_value = atan2(new_sin, new_cos)

Parameters

| other | the other rotation to add to this rotation. |
|-------|---|
|-------|---|

Returns

the sum of the two rotations.

operator-() [1/2]

```
Rotation2d Rotation2d::operator- () const
```

Takes the inverse of this rotation by flipping it. Equivalent to adding 180 degrees.

Returns

this inverse of the rotation.

Takes the inverse of this rotation by flipping it.

Returns

this inverse of the rotation.

operator-() [2/2]

Subtracts the values of two rotations.

| other the other rotation to subtract from this rotation. |
|--|
|--|

Returns

the difference between the two rotations.

operator/()

Divides this rotation by a scalar.

Parameters

| scalar | the scalar value to divide the rotation by. |
|--------|---|
|--------|---|

Returns

the rotation divided by the scalar.

operator==()

Compares two rotations. Returns true if their values are within 1e-9 radians of each other, to account for floating point error.

Parameters

| other | the other rotation to compare to |
|-------|----------------------------------|
|-------|----------------------------------|

Returns

whether the values of the rotations are within 1e-9 radians of each other

radians()

```
double Rotation2d::radians () const
```

Returns the radian angle value.

Returns

the radian angle value.

revolutions()

```
double Rotation2d::revolutions () const
```

Returns the revolution angle value.

Returns

the revolution angle value.

rotation_matrix()

```
Eigen::Matrix2d Rotation2d::rotation_matrix () const
```

Returns the rotation matrix equivalent to this rotation [cos, -sin] R = [sin, cos]

Returns

the rotation matrix equivalent to this rotation

wrapped_degrees_180()

```
double Rotation2d::wrapped_degrees_180 () const
```

Returns the degree angle value, wrapped from [-180, 180).

Returns

the degree angle value, wrapped from [-180, 180)

wrapped_degrees_360()

```
double Rotation2d::wrapped_degrees_360 () const
```

Returns the degree angle value, wrapped from [0, 360).

Returns

the degree angle value, wrapped from [0, 360)

wrapped_radians_180()

```
double Rotation2d::wrapped_radians_180 () const
```

Returns the radian angle value, wrapped from [-pi, pi).

Returns

the radian angle value, wrapped from [-pi, pi)

wrapped_radians_360()

```
double Rotation2d::wrapped_radians_360 () const
```

Returns the radian angle value, wrapped from [0, 2pi).

Returns

the radian angle value, wrapped from [0, 2pi)

wrapped_revolutions_180()

```
double Rotation2d::wrapped_revolutions_180 () const
```

Returns the revolution angle value, wrapped from [-0.5, 0.5).

Returns

the revolution angle value, wrapped from [-0.5, 0.5)

wrapped_revolutions_360()

```
double Rotation2d::wrapped_revolutions_360 () const
```

Returns the revolution angle value, wrapped from [0, 1).

Returns

the revolution angle value, wrapped from [0, 1)

4.59.4 Friends And Related Symbol Documentation

operator<<

Sends a rotation to an output stream. Ex. std::cout << rotation;

```
prints "Rotation2d[rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- · rotation2d.h
- · rotation2d.cpp

4.60 screen::ScreenData Struct Reference

The ScreenData class holds the data that will be passed to the screen thread you probably shouldnt have to use it.

4.60.1 Detailed Description

The ScreenData class holds the data that will be passed to the screen thread you probably shouldnt have to use it.

The documentation for this struct was generated from the following file:

· screen.cpp

4.61 Serializer Class Reference

Serializes Arbitrary data to a file on the SD Card.

```
#include <serializer.h>
```

Public Member Functions

∼Serializer ()

Save and close upon destruction (bc of vex, this doesnt always get called when the program ends. To be sure, call save_to_disk)

Serializer (const std::string &filename, bool flush_always=true)

create a Serializer

• void save_to_disk () const

saves current Serializer state to disk

• void set_int (const std::string &name, int i)

Setters - not saved until save_to_disk is called.

void set_bool (const std::string &name, bool b)

sets a bool by the name of name to b. If flush_always == true, this will save to the sd card

void set_double (const std::string &name, double d)

sets a double by the name of name to d. If flush_always == true, this will save to the sd card

void set_string (const std::string &name, std::string str)

sets a string by the name of name to s. If flush_always == true, this will save to the sd card

int int_or (const std::string &name, int otherwise)

gets a value stored in the serializer. If not found, sets the value to otherwise

• bool bool_or (const std::string &name, bool otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

double double_or (const std::string &name, double otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

std::string string_or (const std::string &name, std::string otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

4.61.1 Detailed Description

Serializes Arbitrary data to a file on the SD Card.

4.61.2 Constructor & Destructor Documentation

Serializer()

create a Serializer

| filename | the file to read from. If filename does not exist we will create that file |
|--------------|--|
| flush_always | If true, after every write flush to a file. If false, you are responsible for calling save_to_disk |

4.61.3 Member Function Documentation

bool_or()

gets a value stored in the serializer. If not, sets the value to otherwise

Parameters

| name | name of value |
|-----------|------------------------------------|
| otherwise | value if the name is not specified |

Returns

the value if found or otherwise

double_or()

gets a value stored in the serializer. If not, sets the value to otherwise

Parameters

| name | name of value |
|-----------|------------------------------------|
| otherwise | value if the name is not specified |

Returns

the value if found or otherwise

int_or()

gets a value stored in the serializer. If not found, sets the value to otherwise

Getters Return value if it exists in the serializer

| name | name of value |
|-----------|------------------------------------|
| otherwise | value if the name is not specified |

Returns

the value if found or otherwise

save_to_disk()

```
void Serializer::save_to_disk () const
```

saves current Serializer state to disk

forms data bytes then saves to filename this was openned with

set_bool()

sets a bool by the name of name to b. If flush_always == true, this will save to the sd card

Parameters

| name | name of bool |
|------|---------------|
| b | value of bool |

set_double()

sets a double by the name of name to d. If flush_always == true, this will save to the sd card

Parameters

| name | name of double |
|------|-----------------|
| d | value of double |

set_int()

Setters - not saved until save_to_disk is called.

sets an integer by the name of name to i. If flush_always == true, this will save to the sd card

| name | name of integer |
|------|------------------|
| i | value of integer |

set_string()

sets a string by the name of name to s. If flush_always == true, this will save to the sd card

Parameters

| name | name of string |
|------|-----------------|
| i | value of string |

string_or()

gets a value stored in the serializer. If not, sets the value to otherwise

Parameters

| name | name of value |
|-----------|------------------------------------|
| otherwise | value if the name is not specified |

Returns

the value if found or otherwise

The documentation for this class was generated from the following files:

- · serializer.h
- · serializer.cpp

4.62 screen::SliderWidget Class Reference

Widget that updates a double value. Updates by reference so watch out for race conditions cuz the screen stuff lives on another thread.

```
#include <screen.h>
```

Public Member Functions

• SliderWidget (double &val, double low, double high, Rect rect, std::string name)

Creates a slider widget.

bool update (bool was_pressed, int x, int y)

responds to user input

• void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number)

Page::draws the slide to the screen

4.62.1 Detailed Description

Widget that updates a double value. Updates by reference so watch out for race conditions cuz the screen stuff lives on another thread.

4.62.2 Constructor & Destructor Documentation

SliderWidget()

Creates a slider widget.

Parameters

| val | reference to the value to modify |
|------|----------------------------------|
| low | minimum value to go to |
| high | maximum value to go to |
| rect | rect to draw it |
| name | name of the value |

4.62.3 Member Function Documentation

update()

```
bool screen::SliderWidget::update (
          bool was_pressed,
          int x,
          int y)
```

responds to user input

Parameters

| was_pressed if the screen is pressed | |
|--------------------------------------|--------------------------------------|
| X | x position if the screen was pressed |
| У | y position if the screen was pressed |

Returns

true if the value updated

The documentation for this class was generated from the following files:

- · screen.h
- · screen.cpp

4.63 SpinRPMCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- SpinRPMCommand (Flywheel &flywheel, int rpm)
- bool run () override

4.63.1 Detailed Description

File: flywheel_commands.h Desc: [insert meaningful desc] AutoCommand wrapper class for the spin_rpm function in the Flywheel class

4.63.2 Constructor & Destructor Documentation

SpinRPMCommand()

Construct a SpinRPM Command

Parameters

| flywheel | the flywheel sys to command |
|----------|--------------------------------|
| rpm | the rpm that we should spin at |

File: flywheel_commands.cpp Desc: [insert meaningful desc]

4.63.3 Member Function Documentation

run()

```
bool SpinRPMCommand::run () [override]
```

Run spin manual Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- flywheel_commands.h
- flywheel_commands.cpp

4.64 PurePursuit::spline Struct Reference

```
#include <pure_pursuit.h>
```

4.64.1 Detailed Description

Represents a piece of a cubic spline with $s(x) = a(x-xi)^3 + b(x-xi)^2 + c(x-xi) + d$ The x_start and x_end shows where the equation is valid.

The documentation for this struct was generated from the following file:

· pure_pursuit.h

4.65 StateMachine< System, IDType, Message, delay_ms, do_log >::State Struct Reference

```
#include <state_machine.h>
```

4.65.1 Detailed Description

template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log = false> struct StateMachine< System, IDType, Message, delay_ms, do_log >::State

Abstract class that all states for this machine must inherit from States MUST override respond() and id() in order to function correctly (the compiler won't have it any other way)

The documentation for this struct was generated from the following file:

state_machine.h

4.66 StateMachine< System, IDType, Message, delay_ms, do_log > Class Template Reference

State Machine:)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024 Over Under game for our overly complex intake-cata subsystem (see there for an example) The statemachine runs in a background thread and a user thread can interact with it through current_state and send_message.

#include <state_machine.h>

Classes

class MaybeMessage

MaybeMessage a message of Message type or nothing MaybeMessage $m = \{\}$; // empty MaybeMessage m = Message::EnumField1.

• struct State

Public Member Functions

StateMachine (State *initial)

Construct a state machine and immediatly start running it.

• IDType current_state () const

retrieve the current state of the state machine. This is safe to call from external threads

void send_message (Message msg)

send a message to the state machine from outside

4.66.1 Detailed Description

template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log = false> class StateMachine< System, IDType, Message, delay_ms, do_log >

State Machine :)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024 Over Under game for our overly complex intake-cata subsystem (see there for an example) The statemachine runs in a background thread and a user thread can interact with it through current_state and send_message.

Designwise: the System class should hold onto any motors, feedback controllers, etc that are persistent in the system States themselves should hold any data that *only* that state needs. For example if a state should be exitted after a certain amount of time, it should hold a timer rather than the System holding that timer. (see Junder from 2024 for an example of this design)

Template Parameters

| System | The system that this is the base class of class Thing: public |
|----------|---|
| | StateMachine <thing> @tparam IDType The ID enum that recognizes</thing> |
| | states. Hint hint, use an enum class ` |
| Message | the message enum that a state or an outside can send and that states respond to |
| delay_ms | the delay to wait between each state processing to allow other threads to work |
| do_log | true if you want print statements describing incoming messages and current states. If true, it is expected that IDType and Message have a function called to_string that takes them as its only parameter and returns a std::string |

4.66.2 Constructor & Destructor Documentation

StateMachine()

Construct a state machine and immediatly start running it.

Parameters

| initial | the state that the machine will begin in |
|---------|--|
|---------|--|

4.66.3 Member Function Documentation

current_state()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
IDType StateMachine< System, IDType, Message, delay_ms, do_log >::current_state () const
[inline]
```

retrieve the current state of the state machine. This is safe to call from external threads

Returns

the current state

send_message()

send a message to the state machine from outside

Parameters

```
msg the message to send This is safe to call from external threads
```

The documentation for this class was generated from the following file:


· state_machine.h

4.67 screen::StatsPage Class Reference

Draws motor stats and battery stats to the screen.

```
#include <screen.h>
```

Inheritance diagram for screen::StatsPage:



Public Member Functions

- StatsPage (std::map< std::string, vex::motor & > motors)
 Creates a stats page.
- void update (bool was_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

4.67.1 Detailed Description

Draws motor stats and battery stats to the screen.

4.67.2 Constructor & Destructor Documentation

StatsPage()

Creates a stats page.

Parameters

motors a map of string to motor that we want to draw on this page

4.67.3 Member Function Documentation

draw()

See also

Page::draw

Reimplemented from screen::Page.

update()

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:


- screen.h
- · screen.cpp

4.68 TakeBackHalf Class Reference

A velocity controller.

```
#include <take_back_half.h>
```

Inheritance diagram for TakeBackHalf:



Public Member Functions

- void init (double start_pt, double set_pt)
- double update (double val) override
- double get () override
- void set_limits (double lower, double upper) override
- bool is_on_target () override

Public Attributes

• double **TBH_gain**

tuned parameter

4.68.1 Detailed Description

A velocity controller.

Warning

If you try to use this as a position controller, it will fail.

4.68.2 Member Function Documentation

get()

```
double TakeBackHalf::get () [override], [virtual]
```

Returns

the last saved result from the feedback controller

Implements Feedback.

init()

Initialize the feedback controller for a movement

Parameters

| start_pt | the current sensor value |
|--|----------------------------------|
| set_pt | where the sensor value should be |
| start_vel Movement starting velocity (IGNORED) | |
| | |

Implements Feedback.

is_on_target()

```
bool TakeBackHalf::is_on_target () [override], [virtual]
```

Returns

true if the feedback controller has reached it's setpoint

Implements Feedback.

set_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

| lower | Upper limit |
|-------|-------------|
| upper | Lower limit |

Implements Feedback.

update()

Iterate the feedback loop once with an updated sensor value

Parameters

```
val value from the sensor
```

Returns

feedback loop result

Implements Feedback.

The documentation for this class was generated from the following files:

- take_back_half.h
- take_back_half.cpp

4.69 TankDrive Class Reference

```
#include <tank_drive.h>
```

Public Types

• enum class BrakeType { None , ZeroVelocity , Smart , TurnOnly }

Public Member Functions

- TankDrive (motor_group &left_motors, motor_group &right_motors, robot_specs_t &config, OdometryBase *odom=NULL)
- void stop ()
- void drive tank (double left, double right, int power=1, BrakeType bt=BrakeType::None)
- void drive tank raw (double left, double right)
- void drive arcade (double forward back, double left right, int power=1, BrakeType bt=BrakeType::None)
- bool drive_forward (double inches, directionType dir, Feedback &feedback, double max_speed=1, double end speed=0)
- bool drive forward (double inches, directionType dir, double max speed=1, double end speed=0)
- bool turn_degrees (double degrees, Feedback &feedback, double max_speed=1, double end_speed=0)
- bool turn degrees (double degrees, double max speed=1, double end speed=0)
- bool drive_to_point (double x, double y, vex::directionType dir, Feedback &feedback, double max_speed=1, double end speed=0)
- bool drive_to_point (double x, double y, vex::directionType dir, double max_speed=1, double end_speed=0)
- bool turn_to_heading (double heading_deg, double max_speed=1, double end_speed=0)
- void reset_auto ()
- bool pure_pursuit (PurePursuit::Path path, directionType dir, Feedback &feedback, double max_speed=1, double end speed=0)
- bool pure pursuit (PurePursuit::Path path, directionType dir, double max speed=1, double end speed=0)

Static Public Member Functions

static double modify_inputs (double input, int power=2)

4.69.1 Detailed Description

TankDrive is a class to run a tank drive system. A tank drive system, sometimes called differential drive, has a motor (or group of synchronized motors) on the left and right side

4.69.2 Member Enumeration Documentation

BrakeType

```
enum class TankDrive::BrakeType [strong]
```

Enumerator

| None | just send 0 volts to the motors |
|--------------|--|
| ZeroVelocity | try to bring the robot to rest. But don't try to hold position |
| Smart | bring the robot to rest and once it's stopped, try to hold that position |

4.69.3 Constructor & Destructor Documentation

TankDrive()

Create the TankDrive object

| left_motors | left side drive motors |
|--------------|---|
| right_motors | right side drive motors |
| config | the configuration specification defining physical dimensions about the robot. See robot_specs_t for more info |
| odom | an odometry system to track position and rotation. this is necessary to execute autonomous paths |

4.69.4 Member Function Documentation

drive_arcade()

Drive the robot using arcade style controls. forward_back controls the linear motion, left_right controls the turning.

forward_back and left_right are in "percent": -1.0 -> 1.0

Parameters

| forward_back | the percent to move forward or backward |
|--------------|---|
| left_right | the percent to turn left or right |
| power | modifies the input velocities left^power, right^power |
| bt | breaktype. What to do if the driver lets go of the sticks |

Drive the robot using arcade style controls. forward_back controls the linear motion, left_right controls the turning. left_motors and right_motors are in "percent": -1.0 -> 1.0

drive_forward() [1/2]

Autonomously drive the robot forward a certain distance

Parameters

| inches | degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw |
|-----------|--|
| dir | the direction we want to travel forward and backward |
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Autonomously drive the robot forward a certain distance

| inches | degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw |
|-----------|--|
| dir | the direction we want to travel forward and backward |
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Returns

true if we have finished driving to our point

drive_forward() [2/2]

Use odometry to drive forward a certain distance using a custom feedback controller

Returns whether or not the robot has reached it's destination.

Parameters

| inches | the distance to drive forward |
|-----------|--|
| dir | the direction we want to travel forward and backward |
| feedback | the custom feedback controller we will use to travel. controls the rate at which we accelerate and |
| | drive. |
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Returns

true when we have reached our target distance

Use odometry to drive forward a certain distance using a custom feedback controller

Returns whether or not the robot has reached it's destination.

Parameters

| inches | the distance to drive forward |
|-----------|---|
| dir | the direction we want to travel forward and backward |
| feedback | the custom feedback controller we will use to travel. controls the rate at which we accelerate and drive. |
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

drive_tank()

Drive the robot using differential style controls. left_motors controls the left motors, right_motors controls the right motors.

left_motors and right_motors are in "percent": -1.0 -> 1.0 $\,$

Parameters

| left | the percent to run the left motors |
|-------|---|
| right | the percent to run the right motors |
| power | modifies the input velocities left^power, right^power |
| bt | breaktype. What to do if the driver lets go of the sticks |

drive_tank_raw()

Drive the robot raw-ly

Parameters

| left | the percent to run the left motors (-1, 1) |
|-------|---|
| right | the percent to run the right motors (-1, 1) |

drive_to_point() [1/2]

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot. Here we use the default feedback controller from the drive_sys

Returns whether or not the robot has reached it's destination.

Parameters

| X | the x position of the target |
|---|------------------------------|
| У | the y position of the target |

| dir | the direction we want to travel forward and backward |
|-----------|--|
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot. Here we use the default feedback controller from the drive_sys

Returns whether or not the robot has reached it's destination.

Parameters

| X | the x position of the target |
|-----------|--|
| У | the y position of the target |
| dir | the direction we want to travel forward and backward |
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Returns

true if we have reached our target point

drive_to_point() [2/2]

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot.

Returns whether or not the robot has reached it's destination.

Parameters

| Х | the x position of the target |
|-----------|--|
| У | the y position of the target |
| dir | the direction we want to travel forward and backward |
| feedback | the feedback controller we will use to travel. controls the rate at which we accelerate and drive. |
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot.

Returns whether or not the robot has reached it's destination.

| X | the x position of the target |
|-----------|--|
| У | the y position of the target |
| dir | the direction we want to travel forward and backward |
| feedback | the feedback controller we will use to travel. controls the rate at which we accelerate and drive. |
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Returns

true if we have reached our target point

modify_inputs()

Create a curve for the inputs, so that drivers have more control at lower speeds. Curves are exponential, with the default being squaring the inputs.

Parameters

| input | the input before modification | |
|-------|-------------------------------|--|
| power | the power to raise input to | |

Returns

input \(^\) power (accounts for negative inputs and odd numbered powers)

Modify the inputs from the controller by squaring / cubing, etc Allows for better control of the robot at slower speeds

Parameters

| input | the input signal -1 -> 1 |
|-------|----------------------------------|
| power | the power to raise the signal to |

Returns

input\(^power accounting for any sign issues that would arise with this naive solution

pure_pursuit() [1/2]

Drive the robot autonomously using a pure-pursuit algorithm - Input path with a set of waypoints - the robot will attempt to follow the points while cutting corners (radius) to save time (compared to stop / turn / start)

Use the default drive feedback

| path | The list of coordinates to follow, in order |
|-----------|--|
| dir | Run the bot forwards or backwards |
| max_speed | Limit the speed of the robot (for pid / pidff feedbacks) |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Returns

True when the path is complete

Drive the robot autonomously using a pure-pursuit algorithm - Input path with a set of waypoints - the robot will attempt to follow the points while cutting corners (radius) to save time (compared to stop / turn / start)

Use the default drive feedback

Parameters

| path | The list of coordinates to follow, in order |
|-----------|--|
| dir | Run the bot forwards or backwards |
| max_speed | Limit the speed of the robot (for pid / pidff feedbacks) |

Returns

True when the path is complete

pure_pursuit() [2/2]

Drive the robot autonomously using a pure-pursuit algorithm - Input path with a set of waypoints - the robot will attempt to follow the points while cutting corners (radius) to save time (compared to stop / turn / start)

Parameters

| path | The list of coordinates to follow, in order |
|-----------|--|
| dir | Run the bot forwards or backwards |
| feedback | The feedback controller determining speed |
| max_speed | Limit the speed of the robot (for pid / pidff feedbacks) |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Returns

True when the path is complete

Drive the robot autonomously using a pure-pursuit algorithm - Input path with a set of waypoints - the robot will attempt to follow the points while cutting corners (radius) to save time (compared to stop / turn / start)

| path | The list of coordinates to follow, in order |
|-----------|--|
| dir | Run the bot forwards or backwards |
| feedback | The feedback controller determining speed |
| max_speed | Limit the speed of the robot (for pid / pidff feedbacks) |

Returns

True when the path is complete

reset_auto()

```
void TankDrive::reset_auto ()
```

Reset the initialization for autonomous drive functions

stop()

```
void TankDrive::stop ()
```

Stops rotation of all the motors using their "brake mode"

turn_degrees() [1/2]

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses the defualt turning feedback of the drive system.

Parameters

| degrees | degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw |
|-----------|--|
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses the defualt turning feedback of the drive system.

| degrees | degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw |
|-----------|--|
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Returns

true if we turned te target number of degrees

turn_degrees() [2/2]

Autonomously turn the robot X degrees counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses PID + Feedforward for it's control.

Parameters

| degrees | degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw |
|-----------|--|
| feedback | the feedback controller we will use to travel. controls the rate at which we accelerate and drive. |
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses the specified feedback for it's control.

Parameters

| degrees | degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw |
|-----------|--|
| feedback | the feedback controller we will use to travel. controls the rate at which we accelerate and drive. |
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Returns

true if we have turned our target number of degrees

turn_to_heading() [1/2]

Turn the robot in place to an exact heading relative to the field. 0 is forward. Uses the defualt turn feedback of the drive system

| heading_deg | the heading to which we will turn |
|-------------|--|
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Turn the robot in place to an exact heading relative to the field. 0 is forward. Uses the defualt turn feedback of the drive system

Parameters

| heading_deg | the heading to which we will turn |
|-------------|--|
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Returns

true if we have reached our target heading

turn_to_heading() [2/2]

Turn the robot in place to an exact heading relative to the field. 0 is forward.

Parameters

| heading_deg | the heading to which we will turn |
|-------------|--|
| feedback | the feedback controller we will use to travel. controls the rate at which we accelerate and drive. |
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Turn the robot in place to an exact heading relative to the field. 0 is forward.

Parameters

| heading_deg | the heading to which we will turn |
|-------------|--|
| feedback | the feedback controller we will use to travel. controls the rate at which we accelerate and drive. |
| max_speed | the maximum percentage of robot speed at which the robot will travel. 1 = full power |
| end_speed | the movement profile will attempt to reach this velocity by its completion |

Returns

true if we have reached our target heading

The documentation for this class was generated from the following files:

- tank_drive.h
- tank_drive.cpp

4.70 tracking_wheel_cfg_t Struct Reference

#include <odometry_nwheel.h>

Public Attributes

- double x
- double y
- double theta_rad
- · double radius

4.70.1 Detailed Description

OdometryNWheel

This class handles the code for an N-pod odometry setup, where there are N < WHEELS > free spinning omni wheels (dead wheels) placed in any known configuration on the robot.

Example of a possible wheel configuration:

Where O is the center of rotation. The robot will monitor the changes in rotation of these wheels, use this to calculate a pose delta, then integrate the deltas over time to determine the robot's position.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

https://rit.enterprise.slack.com/files/U04112Y5RB6/F080M01KPA5/predictperpindiculars2.epdf 2024-2025 Notebook: Entries/Software Entries/Localization/N-Pod Odometry

Author

Jack Cammarata, Richie Sommers

Date

Nov 14 2024 tracking_wheel_cfg_t holds all the specifications for a single tracking wheel The units for x, y, and radius will determine the units of the position estimate

4.70.2 Member Data Documentation

radius

double tracking_wheel_cfg_t::radius

radius of the wheel

theta_rad

```
double tracking_wheel_cfg_t::theta_rad
```

angle between wheel direction and x axis in the robot frame

X

```
double tracking_wheel_cfg_t::x
```

x position of the center of the wheel

у

```
double tracking_wheel_cfg_t::y
```

y position of the center of the wheel

The documentation for this struct was generated from the following file:

· odometry_nwheel.h

4.71 Transform2d Class Reference

```
#include <transform2d.h>
```

Public Member Functions

- Transform2d (const Translation2d &translation, const Rotation2d &rotation)
- Transform2d (const double &x, const double &y, const Rotation2d &rotation)
- Transform2d (const double &x, const double &y, const double &radians)
- Transform2d (const Translation2d &translation, const double &radians)
- Transform2d (const Eigen::Vector3d &transform_vector)
- Transform2d (const Pose2d &start, const Pose2d &end)
- Translation2d translation () const
- double x () const
- double y () const
- · Rotation2d rotation () const
- · Transform2d inverse () const
- Transform2d operator* (const double &scalar) const
- Transform2d operator/ (const double &scalar) const
- Transform2d operator- () const
- bool operator== (const Transform2d &other) const

Friends

std::ostream & operator<< (std::ostream &os, const Transform2d &transform)

4.71.1 Detailed Description

Class representing a transformation of a pose2d, or a linear difference between the components of poses.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

4.71.2 Constructor & Destructor Documentation

Transform2d() [1/6]

Constructs a transform given translation and rotation components.

Parameters

| translation | the translational component of the transform. |
|-------------|---|
| rotation | the rotational component of the transform. |

Transform2d() [2/6]

Constructs a transform given translation and rotation components.

Parameters

| X | the x component of the transform. |
|----------|--|
| У | the y component of the transform. |
| rotation | the rotational component of the transform. |

Transform2d() [3/6]

Constructs a transform given translation and rotation components.

| X | the x component of the transform. |
|---------|---|
| У | the y component of the transform. |
| radians | the rotational component of the transform in radians. |

Transform2d() [4/6]

Constructs a transform given translation and rotation components.

Parameters

| translation | the translational component of the transform. |
|-------------|---|
| radians | the rotational component of the transform in radians. |

Transform2d() [5/6]

Constructs a transform given translation and rotation components given as a vector.

Parameters

| transform_vector | vector of the form [x, y, theta] |
|------------------|----------------------------------|
|------------------|----------------------------------|

Transform2d() [6/6]

Constructs a transform given translation and rotation components.

Parameters

| translation | the translational component of the transform. |
|-------------|---|
| rotation | the rotational component of the transform. |

4.71.3 Member Function Documentation

inverse()

```
Transform2d Transform2d::inverse () const
```

Inverts the transform.

Returns

the inverted transform.

operator*()

Multiplies this transform by a scalar.

Parameters

scalar to multiply this transform by.

operator-()

```
Transform2d Transform2d::operator- () const
```

Inverts the transform.

Returns

the inverted transform.

operator/()

Divides this transform by a scalar.

Parameters

```
scalar to divide this transform by.
```

operator==()

Compares this to another transform.

| other | the other transform to compare to. |
|-------|------------------------------------|
|-------|------------------------------------|

Returns

true if the components are within 1e-9 of each other.

rotation()

```
Rotation2d Transform2d::rotation () const
```

Returns the rotational component of the transform.

Returns

the rotational component of the transform.

translation()

```
Translation2d Transform2d::translation () const
```

Returns the translational component of the transform.

Returns

the translational component of the transform.

x()

```
double Transform2d::x () const
```

Returns the x component of the transform.

Returns

the x component of the transform.

y()

```
double Transform2d::y () const
```

Returns the y component of the transform.

Returns

the y component of the transform.

4.71.4 Friends And Related Symbol Documentation

operator<<

The documentation for this class was generated from the following files:

- · transform2d.h
- transform2d.cpp

4.72 Translation2d Class Reference

```
#include <translation2d.h>
```

Public Member Functions

- Translation2d (const double &x, const double &y)
- Translation2d (const Eigen::Vector2d &vector)
- Translation2d (const double &r, const Rotation2d &theta)
- double x () const
- · double y () const
- · Rotation2d theta () const
- Eigen::Vector2d as_vector () const
- · double norm () const
- double distance (const Translation2d &other) const
- Translation2d rotate_by (const Rotation2d &rotation) const
- Translation2d rotate_around (const Translation2d &other, const Rotation2d &rotation) const
- Translation2d operator+ (const Translation2d &other) const
- Translation2d operator- (const Translation2d &other) const
- Translation2d operator- () const
- Translation2d operator* (const double &scalar) const
- Translation2d operator/ (const double &scalar) const
- double operator* (const Translation2d &other) const
- bool operator== (const Translation2d &other) const

Friends

std::ostream & operator<< (std::ostream &os, const Translation2d &translation)

4.72.1 Detailed Description

Class representing a point in 2d space with x and y coordinates.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

4.72.2 Constructor & Destructor Documentation

Translation2d() [1/3]

```
Translation2d::Translation2d ( const double & x, const double & y)
```

Constructs a Translation2d with the given x and y values.

Parameters

| X | The x component of the translation. |
|---|-------------------------------------|
| У | The y component of the translation. |

Translation2d() [2/3]

Constructs a Translation2d with the values from the given vector.

Parameters

| vector | The vector whose values will be used. |
|--------|---------------------------------------|
|--------|---------------------------------------|

Translation2d() [3/3]

Constructs a Translation2d given polar coordinates of the form (r, theta).

Parameters

| r | The radius (magnitude) of the vector. |
|-------|---------------------------------------|
| theta | The angle (direction) of the vector. |

4.72.3 Member Function Documentation

as_vector()

```
Eigen::Vector2d Translation2d::as_vector () const
```

Returns the vector as an Eigen::Vector2d.

Returns

Eigen::Vector2d with the same values as the translation.

distance()

Returns the distance between two translations.

Returns

the distance between two translations.

norm()

```
double Translation2d::norm () const
```

Returns the norm/radius/magnitude/distance from origin.

Returns

the norm of the translation.

operator*() [1/2]

Returns this translation multiplied by a scalar.

```
[x] = [x] * [scalar] [y] = [y] * [scalar]
```

Parameters

```
scalar to multiply by.
```

Returns

this translation multiplied by a scalar.

operator*() [2/2]

Returns the dot product of two translations.

```
[scalar] = [x][otherx] + [y][othery]
```

| ther the other translation to find the dot product with. |
|--|
|--|

Returns

the scalar valued dot product.

operator+()

Returns the sum of two translations.

```
[x] = [x] + [otherx]; [y] = [y] + [othery];
```

Parameters

other the other translation to add to this translation.

Returns

the sum of the two translations.

operator-() [1/2]

```
Translation2d Translation2d::operator- () const
```

Returns the inverse of this translation. Equivalent to flipping the vector across the origin.

$$[x] = [-x][y] = [-y]$$

Returns

the inverse of this translation.

operator-() [2/2]

Returns the difference of two translations.

$$[x] = [x] - [otherx] [y] = [y] - [othery]$$

| other | the translation to subtract from this translation. |
|-------|--|
|-------|--|

Returns

the difference of the two translations.

operator/()

Returns this translation divided by a scalar.

```
[x] = [x] / [scalar] [y] = [y] / [scalar]
```

Parameters

```
scalar the scalar to divide by.
```

Returns

this translation divided by a scalar.

operator==()

Compares two translations. Returns true if their components are each within 1e-9, to account for floating point error.

Parameters

| | other | the translation to compare to. |
|--|-------|--------------------------------|
|--|-------|--------------------------------|

Returns

whether the two translations are equal.

rotate_around()

Applies a rotation to this translation around another given point.

```
[x] = [\cos, -\sin][x - otherx] + [otherx][y] = [\sin, \cos][y - othery] + [othery]
```

| other | the center of rotation. |
|----------|---|
| rotation | the angle amount the translation will be rotated. |

Returns

the translation that has been rotated.

rotate_by()

Applies a rotation to this translation around the origin.

Equivalent to multiplying a vector by a rotation matrix: $x = [\cos, -\sin][x] y = [\sin, \cos][y]$

Parameters

| rotation | the angle amount the translation will be rotated. |
|----------|---|
|----------|---|

Returns

the new translation that has been rotated around the origin.

theta()

```
Rotation2d Translation2d::theta () const
```

Returns the angle of the translation.

Returns

the angle of the translation.

x()

```
double Translation2d::x () const
```

Returns the x value of the translation.

Returns

the x value of the translation.

y()

```
double Translation2d::y () const
```

Returns the y value of the translation.

Returns

the y value of the translation.

4.72.4 Friends And Related Symbol Documentation

operator <<

Sends a translation to an output stream. Ex. std::cout << translation;

```
prints "Translation2d[x: (value), y: (value)]"
```

Sends a translation to an output stream. Ex. std::cout << translation;

```
prints "Translation2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- translation2d.h
- · translation2d.cpp

4.73 TrapezoidProfile Class Reference

```
#include <trapezoid_profile.h>
```

Public Member Functions

- TrapezoidProfile (double max_v, double accel)
 - Construct a new Trapezoid Profile object.
- motion_t calculate (double time_s)

Run the trapezoidal profile based on the time that's ellapsed.

- void set_endpts (double start, double end)
- void set_accel (double accel)
- void set_max_v (double max_v)
- double get_movement_time ()

4.73.1 Detailed Description

Trapezoid Profile

This is a motion profile defined by an acceleration, maximum velocity, start point and end point. Using this information, a parametric function is generated, with a period of acceleration, constant velocity, and deceleration. The velocity graph looks like a trapezoid, giving it it's name.

If the maximum velocity is set high enough, this will become a S-curve profile, with only acceleration and deceleration.

This class is designed for use in properly modelling the motion of the robots to create a feedfoward and target for PID. Acceleration and Maximum velocity should be measured on the robot and tuned down slightly to account for battery drop.

Here are the equations graphed for ease of understanding: https://www.desmos.com/calculator/rkm3ivulyk

Author

Ryan McGee

Date

7/12/2022

4.73.2 Constructor & Destructor Documentation

TrapezoidProfile()

Construct a new Trapezoid Profile object.

Parameters

| max⊷ _v | Maximum velocity the robot can run at |
|------------|---------------------------------------|
| accel | Maximum acceleration of the robot |

4.73.3 Member Function Documentation

calculate()

Run the trapezoidal profile based on the time that's ellapsed.

| time⊷ | Time since start of movement |
|-------|------------------------------|
| _s | |

Returns

motion_t Position, velocity and acceleration

get_movement_time()

```
double TrapezoidProfile::get_movement_time ()
```

uses the kinematic equations to and specified accel and max_v to figure out how long moving along the profile would take

Returns

the time the path will take to travel

set_accel()

set_accel sets the acceleration this profile will use (the left and right legs of the trapezoid)

Parameters

| accel | the acceleration amount to use |
|-------|--------------------------------|
|-------|--------------------------------|

set_endpts()

set_endpts defines a start and end position

Parameters

| start | the starting position of the path |
|-------|-----------------------------------|
| end | the ending position of the path |

set_max_v()

sets the maximum velocity for the profile (the height of the top of the trapezoid)

| max⊷ | the maximum velocity the robot can travel at |
|------|--|
| _v | |

The documentation for this class was generated from the following files:

- · trapezoid_profile.h
- trapezoid_profile.cpp

4.74 TurnDegreesCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- TurnDegreesCommand (TankDrive &drive_sys, Feedback &feedback, double degrees, double max_speed=1, double end speed=0)
- bool run () override
- void on_timeout () override

4.74.1 Detailed Description

AutoCommand wrapper class for the turn_degrees function in the TankDrive class

4.74.2 Constructor & Destructor Documentation

TurnDegreesCommand()

Construct a TurnDegreesCommand Command

Parameters

| | drive_sys | the drive system we are commanding | | | |
|------------------------------------|-----------|--|--|--|--|
| degrees how many degrees to rotate | | the feedback controller we are using to execute the turn | | | |
| | | how many degrees to rotate | | | |
| | | 0 -> 1 percentage of the drive systems speed to drive at | | | |

4.74.3 Member Function Documentation

on_timeout()

```
void TurnDegreesCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we timeout

run()

```
bool TurnDegreesCommand::run () [override]
```

Run turn_degrees Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive_commands.h
- drive_commands.cpp

4.75 TurnToHeadingCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- TurnToHeadingCommand (TankDrive &drive_sys, Feedback &feedback, double heading_deg, double speed=1, double end_speed=0)
- bool run () override
- · void on_timeout () override

4.75.1 Detailed Description

AutoCommand wrapper class for the turn to heading() function in the TankDrive class

4.75.2 Constructor & Destructor Documentation

TurnToHeadingCommand()

Construct a TurnToHeadingCommand Command

| drive_sys | the drive system we are commanding | | |
|--|--|--|--|
| feedback the feedback controller we are using to execute the | | | |
| heading_deg | the heading to turn to in degrees | | |
| max_speed | 0 -> 1 percentage of the drive systems speed to drive at | | |

4.75.3 Member Function Documentation

on_timeout()

```
void TurnToHeadingCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we don't hit our target

run()

```
bool TurnToHeadingCommand::run () [override]
```

Run turn_to_heading Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive_commands.h
- drive_commands.cpp

4.76 Twist2d Class Reference

```
#include <twist2d.h>
```

Public Member Functions

- Twist2d (const double &dx, const double &dy, const double &dtheta)
- Twist2d (const Eigen::Vector3d &twist_vector)
- double dx () const
- · double dy () const
- double dtheta () const
- bool operator== (const Twist2d &other) const
- Twist2d operator* (const double &scalar) const
- Twist2d operator/ (const double &scalar) const

Friends

• std::ostream & operator<< (std::ostream &os, const Twist2d &twist)

4.76.1 Detailed Description

Class representing a difference between two poses, more specifically a distance along an arc from a pose.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

4.76.2 Constructor & Destructor Documentation

Twist2d() [1/2]

Constructs a twist with given translation and angle deltas.

Parameters

| dx | the linear dx component. | | |
|--------|-------------------------------|--|--|
| dy | the linear dy component. | | |
| dtheta | the angular dtheta component. | | |

Twist2d() [2/2]

Constructs a twist with given translation and angle deltas.

Parameters

| twist_vector vector of the form [dx, dy, dtheta |
|---|
|---|

4.76.3 Member Function Documentation

dtheta()

```
double Twist2d::dtheta () const
```

Returns the angular dtheta component.

Returns

the angular dtheta component.

dx()

```
double Twist2d::dx () const
```

Returns the linear dx component.

Returns

the linear dx component.

dy()

```
double Twist2d::dy () const
```

Returns the linear dy component.

Returns

the linear dy component.

operator*()

Multiplies this twist by a scalar.

Parameters

| | scalar | the scalar value to multiply by. |
|--|--------|----------------------------------|
|--|--------|----------------------------------|

operator/()

Divides this twist by a scalar.

Parameters

| scalar | the scalar value to divide by. |
|--------|--------------------------------|

operator==()

Compares this to another twist.

Returns

true if each of the components are within 1e-9 of each other.

4.76.4 Friends And Related Symbol Documentation

operator<<

```
std::ostream & operator<< (
          std::ostream & os,
          const Twist2d & twist) [friend]</pre>
```

Sends a twist to an output stream. Ex. std::cout << twist;

```
prints "Twist2d[dx: (value), dy: (value), drad: (radians)]"
```

Sends a twist to an output stream. Ex. std::cout << twist;

```
prints "Twist2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- · twist2d.h
- · twist2d.cpp

4.77 Vector2D Class Reference

```
#include <vector2d.h>
```

Public Member Functions

- Vector2D (double dir, double mag)
- Vector2D (point_t p)
- double get_dir () const
- double get_mag () const
- double get_x () const
- double get_y () const
- Vector2D normalize ()
- point_t point ()
- Vector2D operator* (const double &x)
- Vector2D operator+ (const Vector2D &other)
- Vector2D operator- (const Vector2D &other)

4.77.1 Detailed Description

Vector2D is an x,y pair Used to represent 2D locations on the field. It can also be treated as a direction and magnitude

4.77.2 Constructor & Destructor Documentation

Vector2D() [1/2]

Construct a vector object.

Parameters

| dir | Direction, in radians. 'foward' is 0, clockwise positive when viewed from the top. |
|-----|--|
| mag | Magnitude. |

Vector2D() [2/2]

Construct a vector object from a cartesian point.

Parameters

```
p | point_t.x , point_t.y
```

4.77.3 Member Function Documentation

get_dir()

```
double Vector2D::get_dir () const
```

Get the direction of the vector, in radians. '0' is forward, clockwise positive when viewed from the top.

Use r2d() to convert.

Returns

the direction of the vetctor in radians

Get the direction of the vector, in radians. '0' is forward, clockwise positive when viewed from the top.

Use r2d() to convert.

get_mag()

```
double Vector2D::get_mag () const
```

Returns

the magnitude of the vector

Get the magnitude of the vector

get_x()

```
double Vector2D::get_x () const
```

Returns

the X component of the vector; positive to the right.

Get the X component of the vector; positive to the right.

get_y()

```
double Vector2D::get_y () const
```

Returns

the Y component of the vector, positive forward.

Get the Y component of the vector, positive forward.

normalize()

```
Vector2D Vector2D::normalize ()
```

Changes the magnitude of the vector to 1

Returns

the normalized vector

Changes the magnetude of the vector to 1

operator*()

Scales a Vector2D by a scalar with the * operator

x the value to scale the vector by

Returns

the this Vector2D scaled by x

operator+()

Add the components of two vectors together Vector2D + Vector2D = (this.x + other.x, this.y + other.y)

Parameters

other the vector to add to this

Returns

the sum of the vectors

operator-()

Subtract the components of two vectors together Vector2D - Vector2D = (this.x - other.x, this.y - other.y)

Parameters

| other the vector to s | ubtract from this |
|-----------------------|-------------------|
|-----------------------|-------------------|

Returns

the difference of the vectors

point()

```
point_t Vector2D::point ()
```

Returns a point from the vector

Returns

the point represented by the vector

Convert a direction and magnitude representation to an x, y representation

Returns

the x, y representation of the vector

The documentation for this class was generated from the following files:

- vector2d.h
- vector2d.cpp

4.78 WaitUntilCondition Class Reference

Waits until the condition is true.

```
#include <auto_command.h>
```

4.78.1 Detailed Description

Waits until the condition is true.

The documentation for this class was generated from the following file:

· auto_command.h

4.79 WaitUntilUpToSpeedCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- WaitUntilUpToSpeedCommand (Flywheel &flywheel, int threshold rpm)
- bool run () override

4.79.1 Detailed Description

AutoCommand that listens to the Flywheel and waits until it is at its target speed +/- the specified threshold

4.79.2 Constructor & Destructor Documentation

WaitUntilUpToSpeedCommand()

Creat a WaitUntilUpToSpeedCommand

Parameters

| flywheel the flywhe | | the flywheel system we are commanding |
|---------------------|---------------|--|
| | threshold_rpm | the threshold over and under the flywheel target RPM that we define to be acceptable |

4.79.3 Member Function Documentation

run()

```
bool WaitUntilUpToSpeedCommand::run () [override]
```

Run spin_manual Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · flywheel commands.h
- flywheel_commands.cpp

Index

| accel | choice |
|---|---|
| OdometryBase, 72 | AutoChooser, 10 |
| add | CommandController, 16 |
| CommandController, 16, 17 | add, 16, 17 |
| GenericAuto, 42 | add_cancel_func, 17 |
| add_async | add_delay, 18 |
| GenericAuto, 42 | CommandController, 16 |
| add_cancel_func | last_command_timed_out, 18 |
| CommandController, 17 | run, 18 |
| add_delay | Condition, 18 |
| CommandController, 18 | config |
| GenericAuto, 43 | PID, 87 |
| add_entry | control_continuous |
| ExponentialMovingAverage, 27 | |
| MovingAverage, 63 | control_manual |
| ang_accel_deg | Lift< T >, 46 |
| OdometryBase, 72 | control_setpoints |
| ang_speed_deg | Lift< T >, 46 |
| OdometryBase, 73 | Core, 1 |
| as vector | current pos |
| Translation2d, 139 | OdometryBase, 73 |
| Async, 8 | current_state |
| auto_drive | StateMachine < System, IDType, Message, de- |
| MecanumDrive, 55 | lay_ms, do_log >, 116 |
| auto turn | CustomEncoder, 19 |
| MecanumDrive, 55 | CustomEncoder, 19 |
| AutoChooser, 9 | position, 19 |
| AutoChooser, 9 | • |
| | rotation, 20 |
| choice, 10 | setPosition, 20 |
| get_choice, 10 | setRotation, 20 |
| list, 10 | velocity, 20 |
| AutoChooser::entry_t, 26 | degrees |
| name, 26 | Rotation2d, 102 |
| background_task | DelayCommand, 21 |
| OdometryBase, 69 | DelayCommand, 21 |
| - | • |
| BasicSolenoidSet, 10 | run, 22 |
| BasicSolenoidSet, 11 | dist |
| run, 11 | point_t, 91 |
| BasicSpinCommand, 11 BasicSpinCommand, 12 | distance |
| • | Translation2d, 139 |
| run, 12 | double_or |
| BasicStopCommand, 13 | Serializer, 109 |
| BasicStopCommand, 13 | draw |
| run, 13 | screen::FunctionPage, 41 |
| bool_or | screen::OdometryPage, 75 |
| Serializer, 109 | screen::Page, 80 |
| BrakeType | screen::PIDPage, 90 |
| TankDrive, 121 | screen::StatsPage, 117 |
| Branch, 14 | drive |
| ButtonWidget | MecanumDrive, 56 |
| screen::ButtonWidget, 14, 15 | drive_arcade |
| and a violate | TankDrive, 122 |
| calculate | drive_correction_cutoff |
| FeedForward, 31 TrapezoidProfile, 144 | robot_specs_t, 100 |

| drive_forward | kS, 32 |
|------------------------------|---------------------------------|
| TankDrive, 122, 123 | kV, 33 |
| drive_raw | Filter, 33 |
| MecanumDrive, 57 | Flywheel, 33 |
| drive_tank | Flywheel, 34 |
| TankDrive, 123 | get_motors, 35 |
| drive_tank_raw | get_target, 35 |
| TankDrive, 124 | getRPM, 35 |
| drive_to_point | is_on_target, 35 |
| TankDrive, 124, 125 | Page, 35 |
| DriveForwardCommand, 22 | spin_manual, 35 |
| DriveForwardCommand, 22 | spin_rpm, 36 |
| on_timeout, 23 | SpinRpmCmd, 36 |
| run, 23 | spinRPMTask, 37 |
| DriveStopCommand, 23 | stop, 36 |
| DriveStopCommand, 23 | WaitUntilUpToSpeedCmd, 37 |
| run, 24 | FlywheelStopCommand, 37 |
| DriveToPointCommand, 24 | FlywheelStopCommand, 37 |
| DriveToPointCommand, 24, 25 | run, 38 |
| run, 25 | FlywheelStopMotorsCommand, 38 |
| dtheta | FlywheelStopMotorsCommand, 38 |
| Twist2d, 149 | run, <mark>39</mark> |
| dx | FlywheelStopNonTasksCommand, 39 |
| Twist2d, 149 | FunctionCommand, 39 |
| dy | FunctionCondition, 40 |
| Twist2d, 150 | FunctionPage |
| | screen::FunctionPage, 41 |
| end_async | 0 1 4 1 10 |
| OdometryBase, 69 | GenericAuto, 42 |
| error_method | add, 42 |
| PID::pid_config_t, 88 | add_async, 42 |
| ERROR_TYPE | add_delay, 43 |
| PID, 83 | run, 43 |
| exp | get |
| Pose2d, 94 | Feedback, 29 |
| ExponentialMovingAverage, 26 | MotionController, 59 |
| add_entry, 27 | PID, 84 |
| ExponentialMovingAverage, 27 | TakeBackHalf, 119 |
| get_size, 28 | get_accel |
| get_value, 28 | OdometryBase, 69 |
| f | get_angular_accel_deg |
| f_cos | OdometryBase, 69 |
| Rotation2d, 102 | get_angular_speed_deg |
| f_sin | OdometryBase, 70 |
| Rotation2d, 102 | get_async |
| f_tan | Lift< T >, 47 |
| Rotation2d, 102 | get_choice |
| Feedback, 28 | AutoChooser, 10 |
| get, 29 | get_dir |
| init, 29 | Vector2D, 152 |
| is_on_target, 29 | get_error |
| set_limits, 30 | PID, 84 |
| update, 30 | get_mag |
| FeedForward, 30 | Vector2D, 152 |
| calculate, 31 | get_motion |
| FeedForward, 31 | MotionController, 59 |
| FeedForward::ff_config_t, 32 | get_motors |
| kA, 32 | Flywheel, 35 |
| kG, 32 | get_movement_time |
| | |

| TrapezoidProfile, 145 | kA |
|---|--|
| get_points | FeedForward::ff_config_t, 32 |
| PurePursuit::Path, 82 | kG |
| get_position | FeedForward::ff_config_t, 32 |
| OdometryBase, 70 | kS |
| get_radius | FeedForward::ff_config_t, 32 |
| PurePursuit::Path, 82 | kV |
| get_sensor_val | FeedForward::ff_config_t, 33 |
| PID, 84 | |
| get_setpoint | last_command_timed_out |
| Lift< T >, 47 | CommandController, 18 |
| get_size | Lift |
| ExponentialMovingAverage, 28 | Lift< T >, 45 |
| MovingAverage, 63 | Lift < T >, 45 |
| get_speed | control_continuous, 46 |
| OdometryBase, 70 | control_manual, 46 |
| get_target | control_setpoints, 46 |
| Flywheel, 35 | get_async, 47 |
| PID, 84 | get_setpoint, 47 |
| get_value | hold, 47 |
| ExponentialMovingAverage, 28 | home, 47 |
| MovingAverage, 63 | Lift, 45 |
| get_x | set_async, 47 |
| Vector2D, 153 | set_position, 48 |
| get_y | set_sensor_function, 48 |
| Vector2D, 153 | set_sensor_reset, 48 |
| getRPM | set_setpoint, 48 |
| Flywheel, 35 | Lift< T >::lift_cfg_t, 49 |
| | list |
| handle | AutoChooser, 10 |
| OdometryBase, 73 | Log |
| has_message | Logger, 50, 51 |
| StateMachine < System, IDType, Message, de- | log |
| lay_ms, do_log >::MaybeMessage, 54 | Pose2d, 94 |
| hold | Logf |
| Lift < T >, 47 | Logger, 51 |
| home | Logger, 49 |
| Lift< T >, 47 | Log, 50, 51 |
| IfTimePassed, 44 | Logf, 51 |
| init | Logger, 50 |
| Feedback, 29 | LogIn, 51, 52 |
| MotionController, 60 | Logger, 51, 52 |
| PID, 85 | Logger, 31, 32 |
| TakeBackHalf, 119 | MaybeMessage |
| InOrder, 44 | StateMachine< System, IDType, Message, de- |
| int_or | lay_ms, do_log >::MaybeMessage, 53 |
| Serializer, 109 | MecanumDrive, 54 |
| inverse | auto_drive, 55 |
| Transform2d, 135 | auto_turn, 55 |
| is on target | drive, 56 |
| Feedback, 29 | drive_raw, 57 |
| Flywheel, 35 | MecanumDrive, 55 |
| MotionController, 60 | MecanumDrive::mecanumdrive_config_t, 57 |
| PID, 86 | message |
| TakeBackHalf, 119 | StateMachine< System, IDType, Message, de- |
| is_valid | lay_ms, do_log >::MaybeMessage, 54 |
| PurePursuit::Path, 82 | modify_inputs |
| | TankDrive, 126 |

| motion_t, 57 | OdometryPage |
|--|--|
| MotionController, 58 | screen::OdometryPage, 74 |
| get, 59 | OdometryTank, 75 |
| get_motion, 59 | OdometryTank, 77 |
| init, 60 | set_position, 78 |
| is_on_target, 60 | update, 78 |
| MotionController, 59 | OdomSetPosition, 79 |
| set_limits, 60 | OdomSetPosition, 79 |
| tune_feedforward, 61 | run, 79 |
| update, 61 | off_axis_center_dist |
| MotionController::m_profile_cfg_t, 52 | Odometry3Wheel::odometry3wheel_cfg_t, 67 |
| MovingAverage, 62 | on_target_time |
| add_entry, 63 | PID::pid_config_t, 88 |
| get_size, 63 | on_timeout |
| get_value, 63 | DriveForwardCommand, 23 |
| MovingAverage, 62 | PurePursuitCommand, 99 |
| mut | TurnDegreesCommand, 147 |
| OdometryBase, 73 | TurnToHeadingCommand, 148 |
| odomon y Daoos, 70 | operator<< |
| name | Pose2d, 97 |
| AutoChooser::entry_t, 26 | Rotation2d, 106 |
| None | Transform2d, 137 |
| TankDrive, 121 | Translation2d, 143 |
| norm | |
| Translation2d, 139 | Twist2d, 151 |
| normalize | operator+ |
| | point_t, 91 |
| Vector2D, 153 | Pose2d, 95 |
| Odometry3Wheel, 64 | Rotation2d, 103 |
| Odometry3Wheel, 65 | Translation2d, 140 |
| tune, 66 | Vector2D, 154 |
| | operator- |
| update, 66 | point_t, 91 |
| Odometry3Wheel::odometry3wheel_cfg_t, 67 | Pose2d, 95 |
| off_axis_center_dist, 67 | Rotation2d, 103 |
| wheel_diam, 67 | Transform2d, 135 |
| wheelbase_dist, 67 | Translation2d, 140 |
| OdometryBase, 67 | Vector2D, 154 |
| accel, 72 | operator/ |
| ang_accel_deg, 72 | Pose2d, 95 |
| ang_speed_deg, 73 | Rotation2d, 104 |
| background_task, 69 | Transform2d, 135 |
| current_pos, 73 | Translation2d, 141 |
| end_async, 69 | Twist2d, 150 |
| get_accel, 69 | operator== |
| get_angular_accel_deg, 69 | Pose2d, 95 |
| get_angular_speed_deg, 70 | Rotation2d, 104 |
| get_position, 70 | Transform2d, 135 |
| get_speed, 70 | Translation2d, 141 |
| handle, 73 | Twist2d, 150 |
| mut, 73 | operator* |
| OdometryBase, 69 | Pose2d, 94 |
| pos_diff, 70 | Rotation2d, 102 |
| pose_exponential, 71 | |
| rot_diff, 71 | Transform2d, 135 |
| set_position, 71 | Translation2d, 139 |
| smallest_angle, 72 | Twist2d, 150 |
| speed, 73 | Vector2D, 153 |
| update, 72 | Page |
| zero_pos, 73 | Flywheel, 35 |
| | 1 13 1111001, 00 |

| Parallel, 81 | Path, 81 |
|---------------------------------------|------------------------------|
| Path | PurePursuit::spline, 114 |
| PurePursuit::Path, 81 | PurePursuitCommand, 98 |
| PID, 82 | on_timeout, 99 |
| config, 87 | PurePursuitCommand, 98 |
| ERROR TYPE, 83 | run, 99 |
| get, 84 | , |
| get_error, 84 | radians |
| get_sensor_val, 84 | Rotation2d, 104 |
| get_serisor_val, 64 get_target, 84 | radius |
| init, 85 | tracking_wheel_cfg_t, 131 |
| • | relative to |
| is_on_target, 86 | Pose2d, 96 |
| PID, 83 | reset |
| reset, 86 | PID, 86 |
| set_limits, 86 | reset auto |
| set_target, 86 | TankDrive, 128 |
| update, 87 | revolutions |
| PID::pid_config_t, 88 | |
| error_method, 88 | Rotation2d, 104 |
| on_target_time, 88 | robot_specs_t, 99 |
| PIDPage | drive_correction_cutoff, 100 |
| screen::PIDPage, 89 | rot_diff |
| point | OdometryBase, 71 |
| Vector2D, 154 | rotate_around |
| point_t, 90 | Translation2d, 141 |
| dist, 91 | rotate_by |
| operator+, 91 | Translation2d, 142 |
| operator-, 91 | rotation |
| pos_diff | CustomEncoder, 20 |
| OdometryBase, 70 | Pose2d, 96 |
| Pose2d, 92 | Transform2d, 136 |
| exp, 94 | Rotation2d, 100 |
| log, 94 | degrees, 102 |
| operator<<, 97 | f cos, 102 |
| • | f_sin, 102 |
| operator+, 95 | f tan, 102 |
| operator-, 95 | operator<<, 106 |
| operator/, 95 | operator+, 103 |
| operator==, 95 | operator-, 103 |
| operator*, 94 | operator/, 104 |
| Pose2d, 92, 93 | operator==, 104 |
| relative_to, 96 | operator*, 102 |
| rotation, 96 | • |
| transform_by, 96 | radians, 104 |
| translation, 96 | revolutions, 104 |
| x, 97 | Rotation2d, 101 |
| y, 97 | rotation_matrix, 105 |
| pose_exponential | wrapped_degrees_180, 105 |
| OdometryBase, 71 | wrapped_degrees_360, 105 |
| pose_t, 98 | wrapped_radians_180, 105 |
| position | wrapped_radians_360, 105 |
| CustomEncoder, 19 | wrapped_revolutions_180, 106 |
| pure_pursuit | wrapped_revolutions_360, 106 |
| TankDrive, 126, 127 | rotation_matrix |
| PurePursuit::hermite_point, 43 | Rotation2d, 105 |
| PurePursuit::Path, 81 | run |
| get_points, 82 | BasicSolenoidSet, 11 |
| get_radius, 82 | BasicSpinCommand, 12 |
| - — | BasicStopCommand, 13 |
| is_valid, 82 | CommandController, 18 |
| | |

| DelayCommand, 22 | Lift< T >, 47 |
|---|--|
| DriveForwardCommand, 23 | set_bool |
| DriveStopCommand, 24 | Serializer, 110 |
| DriveToPointCommand, 25 | set_double |
| FlywheelStopCommand, 38 | Serializer, 110 |
| FlywheelStopMotorsCommand, 39 | set_endpts |
| GenericAuto, 43 | TrapezoidProfile, 145 |
| OdomSetPosition, 79 | set_int |
| PurePursuitCommand, 99 | Serializer, 110 |
| SpinRPMCommand, 114 | set_limits |
| TurnDegreesCommand, 147 | Feedback, 30 |
| TurnToHeadingCommand, 148 | MotionController, 60 |
| WaitUntilUpToSpeedCommand, 155 | PID, 86 |
| and the distance | TakeBackHalf, 119 |
| save_to_disk | set_max_v |
| Serializer, 110 | TrapezoidProfile, 145 |
| screen::ButtonWidget, 14 | set_position |
| ButtonWidget, 14, 15 | Lift < T >, 48 |
| update, 15 | OdometryBase, 71 |
| screen::FunctionPage, 40 | OdometryTank, 78 |
| draw, 41 | set_sensor_function |
| FunctionPage, 41 | Lift < T >, 48 |
| update, 41 | set_sensor_reset |
| screen::OdometryPage, 74 | Lift < T >, 48 |
| draw, 75 | set_setpoint |
| OdometryPage, 74 | Lift < T >, 48 |
| update, 75 | set_string |
| screen::Page, 80 | Serializer, 111 |
| draw, 80 | set_target |
| update, 80 | PID, 86 |
| screen::PIDPage, 89 | setPosition |
| draw, 90 | CustomEncoder, 20 |
| PIDPage, 89 | setRotation |
| update, 90 | CustomEncoder, 20 |
| screen::ScreenData, 107 | SliderWidget |
| screen::SliderWidget, 111 | screen::SliderWidget, 112 |
| SliderWidget, 112 | smallest_angle |
| update, 112 | OdometryBase, 72 |
| screen::StatsPage, 117 | Smart |
| draw, 117 | TankDrive, 121 |
| StatsPage, 117 | speed |
| update, 117 | OdometryBase, 73 |
| send_message | spin_manual |
| StateMachine System, IDType, Message, de- | Flywheel, 35 |
| lay_ms, do_log >, 116 | spin_rpm |
| Serializer, 107 | Flywheel, 36 |
| bool_or, 109 | SpinRpmCmd |
| double_or, 109 | Flywheel, 36 |
| int_or, 109 | SpinRPMCommand, 113 |
| save_to_disk, 110 | run, 114 |
| Serializer, 108 | SpinRPMCommand, 113 |
| set_bool, 110 | spinRPMTask |
| set_double, 110 | Flywheel, 37 |
| set_int, 110 | StateMachine |
| set_string, 111 | StateMachine< System, IDType, Message, de- |
| string_or, 111 | lay_ms, do_log >, 116 |
| set_accel | StateMachine< System, IDType, Message, delay_ms, |
| TrapezoidProfile, 145 | do_log >, 115 |
| set_async | |
| | |

| current state, 116 | translation, 136 |
|---|---------------------------|
| send message, 116 | x, 136 |
| StateMachine, 116 | y, 136 |
| StateMachine System, IDType, Message, delay_ms, | transform by |
| do_log >::MaybeMessage, 53 | Pose2d, 96 |
| | |
| has_message, 54 | translation |
| MaybeMessage, 53 | Pose2d, 96 |
| message, 54 | Transform2d, 136 |
| StateMachine < System, IDType, Message, delay_ms, | Translation2d, 137 |
| do_log >::State, 114 | as_vector, 139 |
| StatsPage | distance, 139 |
| screen::StatsPage, 117 | norm, 139 |
| stop | operator<<, 143 |
| Flywheel, 36 | operator+, 140 |
| TankDrive, 128 | operator-, 140 |
| | operator/, 141 |
| string_or | • |
| Serializer, 111 | operator==, 141 |
| TakoBackHalf 119 | operator∗, 139 |
| TakeBackHalf, 118 | rotate_around, 141 |
| get, 119 | rotate_by, 142 |
| init, 119 | theta, 142 |
| is_on_target, 119 | Translation2d, 138 |
| set_limits, 119 | x, 142 |
| update, 120 | y, 142 |
| TankDrive, 120 | TrapezoidProfile, 143 |
| BrakeType, 121 | calculate, 144 |
| drive_arcade, 122 | |
| drive_forward, 122, 123 | get_movement_time, 145 |
| drive_tank, 123 | set_accel, 145 |
| | set_endpts, 145 |
| drive_tank_raw, 124 | set_max_v, 145 |
| drive_to_point, 124, 125 | TrapezoidProfile, 144 |
| modify_inputs, 126 | tune |
| None, 121 | Odometry3Wheel, 66 |
| pure_pursuit, 126, 127 | tune feedforward |
| reset_auto, 128 | MotionController, 61 |
| Smart, 121 | turn degrees |
| stop, 128 | TankDrive, 128, 129 |
| TankDrive, 121 | turn to heading |
| turn_degrees, 128, 129 | - |
| turn to heading, 129, 130 | TankDrive, 129, 130 |
| • · · | TurnDegreesCommand, 146 |
| ZeroVelocity, 121 | on_timeout, 147 |
| theta | run, 147 |
| Translation2d, 142 | TurnDegreesCommand, 146 |
| theta_rad | TurnToHeadingCommand, 147 |
| tracking_wheel_cfg_t, 131 | on_timeout, 148 |
| tracking_wheel_cfg_t, 131 | run, 148 |
| radius, 131 | TurnToHeadingCommand, 147 |
| theta_rad, 131 | Twist2d, 148 |
| x, 132 | dtheta, 149 |
| y, 132 | |
| Transform2d, 132 | dx, 149 |
| inverse, 135 | dy, 150 |
| | operator<<, 151 |
| operator 135 | operator/, 150 |
| operator-, 135 | operator==, 150 |
| operator/, 135 | operator*, 150 |
| operator==, 135 | Twist2d, 149 |
| operator*, 135 | |
| rotation, 136 | update |
| Transform2d, 133, 134 | Feedback, 30 |
| | |

```
MotionController, 61
                                                          tracking_wheel_cfg_t, 132
    Odometry3Wheel, 66
                                                          Transform2d, 136
    OdometryBase, 72
                                                          Translation2d, 142
    OdometryTank, 78
                                                      zero pos
    PID, 87
                                                          OdometryBase, 73
    screen::ButtonWidget, 15
                                                      ZeroVelocity
    screen::FunctionPage, 41
                                                          TankDrive, 121
    screen::OdometryPage, 75
    screen::Page, 80
    screen::PIDPage, 90
    screen::SliderWidget, 112
    screen::StatsPage, 117
    TakeBackHalf, 120
Vector2D, 151
    get dir, 152
    get_mag, 152
    get_x, 153
    get_y, 153
    normalize, 153
    operator+, 154
    operator-, 154
    operator*, 153
    point, 154
    Vector2D, 152
velocity
    CustomEncoder, 20
WaitUntilCondition, 155
WaitUntilUpToSpeedCmd
     Flywheel, 37
WaitUntilUpToSpeedCommand, 155
    run, 155
    WaitUntilUpToSpeedCommand, 155
wheel diam
    Odometry3Wheel::odometry3wheel_cfg_t, 67
wheelbase dist
    Odometry3Wheel::odometry3wheel cfg t, 67
wrapped_degrees_180
    Rotation2d, 105
wrapped_degrees_360
    Rotation2d, 105
wrapped radians 180
     Rotation2d, 105
wrapped_radians_360
     Rotation2d, 105
wrapped_revolutions_180
    Rotation2d, 106
wrapped_revolutions_360
     Rotation2d, 106
Х
     Pose2d, 97
    tracking_wheel_cfg_t, 132
    Transform2d, 136
    Translation2d, 142
     Pose2d, 97
```