RIT VEXU Core API

Generated by Doxygen 1.13.2

1 Core	1
1.1 Getting Started	 . 1
1.2 Features	 . 2
2 Hierarchical Index	2
2.1 Class Hierarchy	 . 2
3 Class Index	6
3.1 Class List	 . 6
4 Namespace Documentation	10
4.1 VDB Namespace Reference	 . 10
4.1.1 Detailed Description	 . 10
4.1.2 Function Documentation	 . 10
5 Class Documentation	10
5.1 VDP::AbstractDevice Class Reference	 . 10
5.1.1 Detailed Description	 . 11
5.1.2 Constructor & Destructor Documentation	 . 11
5.1.3 Member Function Documentation	 . 11
5.2 Async Class Reference	 . 12
5.2.1 Detailed Description	 . 12
5.3 AutoChooser Class Reference	 . 12
5.3.1 Detailed Description	 . 12
5.3.2 Constructor & Destructor Documentation	 . 13
5.3.3 Member Function Documentation	 . 13
5.3.4 Member Data Documentation	 . 13
5.4 BasicSolenoidSet Class Reference	 . 14
5.4.1 Detailed Description	 . 14
5.4.2 Constructor & Destructor Documentation	 . 14
5.4.3 Member Function Documentation	 . 14
5.5 BasicSpinCommand Class Reference	 . 15
5.5.1 Detailed Description	 . 15
5.5.2 Constructor & Destructor Documentation	 . 15
5.5.3 Member Function Documentation	 . 16
5.6 BasicStopCommand Class Reference	 . 16
5.6.1 Detailed Description	 . 16
5.6.2 Constructor & Destructor Documentation	 . 16
5.6.3 Member Function Documentation	 . 17
5.7 Branch Class Reference	 . 17
5.7.1 Detailed Description	
5.8 screen::ButtonWidget Class Reference	
5.8.1 Detailed Description	
5.8.2 Constructor & Destructor Documentation	 . 18

5.8.3 Member Function Documentation	19
5.9 CommandController Class Reference	19
5.9.1 Detailed Description	20
5.9.2 Constructor & Destructor Documentation	20
5.9.3 Member Function Documentation	20
5.10 Condition Class Reference	22
5.10.1 Detailed Description	22
5.11 CRC32 Class Reference	23
5.11.1 Detailed Description	23
5.11.2 Member Function Documentation	23
5.12 CustomEncoder Class Reference	25
5.12.1 Detailed Description	25
5.12.2 Constructor & Destructor Documentation	25
5.12.3 Member Function Documentation	26
5.13 DelayCommand Class Reference	27
5.13.1 Detailed Description	28
5.13.2 Constructor & Destructor Documentation	28
5.13.3 Member Function Documentation	28
5.14 DriveForwardCommand Class Reference	28
5.14.1 Detailed Description	29
5.14.2 Constructor & Destructor Documentation	29
5.14.3 Member Function Documentation	29
5.15 DriveStopCommand Class Reference	30
5.15.1 Detailed Description	30
5.15.2 Constructor & Destructor Documentation	30
5.15.3 Member Function Documentation	
5.16 DriveToPointCommand Class Reference	31
5.16.1 Detailed Description	31
5.16.2 Constructor & Destructor Documentation	31
5.16.3 Member Function Documentation	32
5.17 AutoChooser::entry_t Struct Reference	33
5.17.1 Detailed Description	33
5.17.2 Member Data Documentation	33
5.18 ExponentialMovingAverage Class Reference	33
5.18.1 Detailed Description	34
5.18.2 Constructor & Destructor Documentation	34
5.18.3 Member Function Documentation	34
5.19 Feedback Class Reference	35
5.19.1 Detailed Description	36
5.19.2 Member Function Documentation	
5.20 FeedForward Class Reference	37
5.20.1 Detailed Description	38

5.20.2 Constructor & Destructor Documentation	38
5.20.3 Member Function Documentation	38
5.21 FeedForward::ff_config_t Struct Reference	39
5.21.1 Detailed Description	39
5.21.2 Member Data Documentation	39
5.22 Filter Class Reference	40
5.22.1 Detailed Description	40
5.23 Flywheel Class Reference	40
5.23.1 Detailed Description	41
5.23.2 Constructor & Destructor Documentation	41
5.23.3 Member Function Documentation	42
5.23.4 Friends And Related Symbol Documentation	44
5.24 FlywheelStopCommand Class Reference	44
5.24.1 Detailed Description	44
5.24.2 Constructor & Destructor Documentation	44
5.24.3 Member Function Documentation	45
5.25 FlywheelStopMotorsCommand Class Reference	45
5.25.1 Detailed Description	45
5.25.2 Constructor & Destructor Documentation	45
5.25.3 Member Function Documentation	46
5.26 FlywheelStopNonTasksCommand Class Reference	46
5.26.1 Detailed Description	46
5.27 FunctionCommand Class Reference	46
5.27.1 Detailed Description	46
5.28 FunctionCondition Class Reference	47
5.28.1 Detailed Description	47
5.29 screen::FunctionPage Class Reference	47
5.29.1 Detailed Description	48
5.29.2 Constructor & Destructor Documentation	48
5.29.3 Member Function Documentation	48
5.30 GenericAuto Class Reference	49
5.30.1 Detailed Description	49
5.30.2 Member Function Documentation	49
5.31 PurePursuit::hermite_point Struct Reference	50
5.31.1 Detailed Description	51
5.32 IfTimePassed Class Reference	51
5.32.1 Detailed Description	51
5.33 InOrder Class Reference	51
5.33.1 Detailed Description	51
5.34 InterpolatingMap< KEY, VALUE > Class Template Reference	52
5.34.1 Detailed Description	52
5.34.2 Member Function Documentation	52

5.35 Lift $<$ T $>$ Class Template Reference	53
5.35.1 Detailed Description	53
5.35.2 Constructor & Destructor Documentation	54
5.35.3 Member Function Documentation	54
5.36 Lift< T >::lift_cfg_t Struct Reference	57
5.36.1 Detailed Description	57
5.37 Logger Class Reference	58
5.37.1 Detailed Description	58
5.37.2 Constructor & Destructor Documentation	58
5.37.3 Member Function Documentation	59
5.38 MotionController::m_profile_cfg_t Struct Reference	61
5.38.1 Detailed Description	61
$5.39 \; State Machine < System, \; IDType, \; Message, \; delay_ms, \; do_log > :: Maybe Message \; Class \; Reference \; .$	62
5.39.1 Detailed Description	62
5.39.2 Constructor & Destructor Documentation	62
5.39.3 Member Function Documentation	63
5.40 MecanumDrive Class Reference	63
5.40.1 Detailed Description	64
5.40.2 Constructor & Destructor Documentation	64
5.40.3 Member Function Documentation	64
5.41 MecanumDrive::mecanumdrive_config_t Struct Reference	66
5.41.1 Detailed Description	66
5.42 MotionController Class Reference	67
5.42.1 Detailed Description	67
5.42.2 Constructor & Destructor Documentation	68
5.42.3 Member Function Documentation	68
5.43 VDP::MotorDataRecord Class Reference	70
5.43.1 Detailed Description	71
5.43.2 Constructor & Destructor Documentation	71
5.43.3 Member Function Documentation	72
5.44 MovingAverage Class Reference	72
5.44.1 Detailed Description	72
5.44.2 Constructor & Destructor Documentation	72
5.44.3 Member Function Documentation	73
5.45 VDP::Number < NumT, schemaType > Class Template Reference	74
5.45.1 Detailed Description	75
5.45.2 Member Typedef Documentation	75
5.45.3 Constructor & Destructor Documentation	75
5.45.4 Member Function Documentation	76
5.46 Odometry3Wheel Class Reference	78
5.46.1 Detailed Description	79
5.46.2 Constructor & Destructor Documentation	79

5	6.46.3 Member Function Documentation	'9
5.47 O	dometry3Wheel::odometry3wheel_cfg_t Struct Reference	30
5	6.47.1 Detailed Description	30
5	3.47.2 Member Data Documentation	30
5.48 O	dometryBase Class Reference	31
5	6.48.1 Detailed Description	32
5	3.48.2 Constructor & Destructor Documentation	32
5	6.48.3 Member Function Documentation	32
5	6.48.4 Member Data Documentation	35
5.49 V	DP::OdometryControlRecord Class Reference	86
5	6.49.1 Detailed Description	37
5	3.49.2 Constructor & Destructor Documentation	37
5	3.49.3 Member Function Documentation	88
5.50 V	DP::OdometryDataRecord Class Reference	88
5	5.50.1 Detailed Description	39
5	5.50.2 Constructor & Destructor Documentation	39
5	5.50.3 Member Function Documentation	39
5.51 s	creen::OdometryPage Class Reference	90
5	5.51.1 Detailed Description	90
5	5.51.2 Constructor & Destructor Documentation	0
5	5.51.3 Member Function Documentation	1
5.52 O	dometrySerial Class Reference)1
5	5.52.1 Detailed Description	2
5	5.52.2 Constructor & Destructor Documentation	93
5	5.52.3 Member Function Documentation	93
5.53 O	dometryTank Class Reference	96
5	5.53.1 Detailed Description	7
5	5.53.2 Constructor & Destructor Documentation	7
5	5.53.3 Member Function Documentation	8
5.54 O	domSetPosition Class Reference	9
5	5.54.1 Detailed Description	9
5	5.54.2 Constructor & Destructor Documentation	9
5	5.54.3 Member Function Documentation	9
5.55 V	DP::PacketHeader Struct Reference	0
5	5.55.1 Detailed Description	0
5.56 V	DP::PacketWriter Class Reference	0
5	5.56.1 Detailed Description	0
5	5.56.2 Constructor & Destructor Documentation	0
5	5.56.3 Member Function Documentation	1
5.57 s	creen::Page Class Reference	14
5	5.57.1 Detailed Description	14
5	5.57.2 Member Function Documentation)4

5.58 Parallel Class Reference
5.58.1 Detailed Description
5.59 VDP::Part Class Reference
5.59.1 Detailed Description
5.59.2 Constructor & Destructor Documentation
5.59.3 Member Function Documentation
5.60 PurePursuit::Path Class Reference
5.60.1 Detailed Description
5.60.2 Constructor & Destructor Documentation
5.60.3 Member Function Documentation
5.61 PID Class Reference
5.61.1 Detailed Description
5.61.2 Member Enumeration Documentation
5.61.3 Constructor & Destructor Documentation
5.61.4 Member Function Documentation
5.61.5 Member Data Documentation
5.62 PID::pid_config_t Struct Reference
5.62.1 Detailed Description
5.62.2 Member Data Documentation
5.63 VDP::PIDControlRecord Class Reference
5.63.1 Detailed Description
5.63.2 Constructor & Destructor Documentation
5.63.3 Member Function Documentation
5.64 VDP::PIDDataRecord Class Reference
5.64.1 Detailed Description
5.64.2 Constructor & Destructor Documentation
5.64.3 Member Function Documentation
5.65 screen::PIDPage Class Reference
5.65.1 Detailed Description
5.65.2 Constructor & Destructor Documentation
5.65.3 Member Function Documentation
5.66 Pose2d Class Reference
5.66.1 Detailed Description
5.66.2 Constructor & Destructor Documentation
5.66.3 Member Function Documentation
5.66.4 Friends And Related Symbol Documentation
5.67 PurePursuitCommand Class Reference
5.67.1 Detailed Description
5.67.2 Constructor & Destructor Documentation
5.67.3 Member Function Documentation
5.68 VDP::Record Class Reference
5.68.1 Detailed Description

5.68.2 Constructor & Destructor Documentation	. 129
5.68.3 Member Function Documentation	. 131
5.69 Rect Struct Reference	. 132
5.69.1 Detailed Description	. 132
5.70 VDP::RegistryListener< MutexType > Class Template Reference	. 132
5.70.1 Detailed Description	. 133
5.70.2 Constructor & Destructor Documentation	. 133
5.70.3 Member Function Documentation	. 133
5.71 robot_specs_t Struct Reference	. 134
5.71.1 Detailed Description	. 135
5.71.2 Member Data Documentation	. 135
5.72 Rotation2d Class Reference	. 135
5.72.1 Detailed Description	. 136
5.72.2 Constructor & Destructor Documentation	. 136
5.72.3 Member Function Documentation	. 137
5.72.4 Friends And Related Symbol Documentation	. 142
5.73 ScaledSphericalSimplexSigmaPoints < STATES > Class Template Reference	. 142
5.73.1 Detailed Description	. 143
5.73.2 Constructor & Destructor Documentation	. 143
5.73.3 Member Function Documentation	. 143
5.74 screen::ScreenData Struct Reference	. 145
5.74.1 Detailed Description	. 145
5.75 Serializer Class Reference	. 145
5.75.1 Detailed Description	. 145
5.75.2 Constructor & Destructor Documentation	. 146
5.75.3 Member Function Documentation	. 147
5.76 screen::SliderWidget Class Reference	. 149
5.76.1 Detailed Description	. 150
5.76.2 Constructor & Destructor Documentation	. 150
5.76.3 Member Function Documentation	. 150
5.77 SpinRPMCommand Class Reference	. 151
5.77.1 Detailed Description	. 151
5.77.2 Constructor & Destructor Documentation	. 151
5.77.3 Member Function Documentation	. 152
5.78 PurePursuit::spline Struct Reference	. 152
5.78.1 Detailed Description	. 152
$5.79\ Square Root Unscented Kalman Filter < STATES,\ INPUTS,\ OUTPUTS > Class\ Template\ Reference \\ \$. 152
5.79.1 Detailed Description	. 153
5.79.2 Constructor & Destructor Documentation	. 154
5.79.3 Member Function Documentation	. 155
5.80 StateMachine< System, IDType, Message, delay_ms, do_log >::State Struct Reference	. 160
5.80.1 Detailed Description	160

5.81 StateMachine < System, IDType, Message, delay_ms, do_log > Class Template Reference 160
5.81.1 Detailed Description
5.81.2 Constructor & Destructor Documentation
5.81.3 Member Function Documentation
5.82 screen::StatsPage Class Reference
5.82.1 Detailed Description
5.82.2 Constructor & Destructor Documentation
5.82.3 Member Function Documentation
5.83 VDP::String Class Reference
5.83.1 Detailed Description
5.83.2 Constructor & Destructor Documentation
5.83.3 Member Function Documentation
5.84 TakeBackHalf Class Reference
5.84.1 Detailed Description
5.84.2 Member Function Documentation
5.85 TankDrive Class Reference
5.85.1 Detailed Description
5.85.2 Member Enumeration Documentation
5.85.3 Constructor & Destructor Documentation
5.85.4 Member Function Documentation
5.86 VDP::TimestampedRecord Class Reference
5.86.1 Detailed Description
5.86.2 Constructor & Destructor Documentation
5.86.3 Member Function Documentation
5.87 tracking_wheel_cfg_t Struct Reference
5.87.1 Detailed Description
5.87.2 Member Data Documentation
5.88 Transform2d Class Reference
5.88.1 Detailed Description
5.88.2 Constructor & Destructor Documentation
5.88.3 Member Function Documentation
5.88.4 Friends And Related Symbol Documentation
5.89 Translation2d Class Reference
5.89.1 Detailed Description
5.89.2 Constructor & Destructor Documentation
5.89.3 Member Function Documentation
5.89.4 Friends And Related Symbol Documentation
5.90 TrapezoidProfile Class Reference
5.90.1 Detailed Description
5.90.2 Constructor & Destructor Documentation
5.90.3 Member Function Documentation
5.91 TurnDegreesCommand Class Reference

1 Core 1

5.91.1 Detailed Description	 197
5.91.2 Constructor & Destructor Documentation	 198
5.91.3 Member Function Documentation	 198
5.92 TurnToHeadingCommand Class Reference	 198
5.92.1 Detailed Description	 199
5.92.2 Constructor & Destructor Documentation	 199
5.92.3 Member Function Documentation	 199
5.93 Twist2d Class Reference	 200
5.93.1 Detailed Description	 200
5.93.2 Constructor & Destructor Documentation	 200
5.93.3 Member Function Documentation	 201
5.93.4 Friends And Related Symbol Documentation	 202
5.94 WaitUntilCondition Class Reference	 202
5.94.1 Detailed Description	 203
5.95 WaitUntilUpToSpeedCommand Class Reference	 203
5.95.1 Detailed Description	 203
5.95.2 Constructor & Destructor Documentation	 203
5.95.3 Member Function Documentation	 203
Index	205

1 Core

This is the host repository for the custom VEX libraries used by the RIT VEXU team

Automatically updated documentation is available at here. There is also a downloadable reference manual.

1.1 Getting Started

If you just want to start a project with Core, make a fork of the Fork Template and follow it's instructions.

To setup core for an existing project:

- 1. Create a new vex project (using the VSCode extension or other methods)
- 2. Initialize a git repository for the project
- 3. Execute git subtree add --prefix=core https://github.com/RIT-VEX-U/ \leftarrow Core.git main
- 4. Update the vex Makefile (or any other build system) to know about the core files (core/src for source files, core/include for headers) (See here for an example)
- 5. Enable Eigen (Latest supported version is 3.4.0):
 - mkdir vendor
 - git submodule add https://gitlab.com/libeigen/eigen.git vendor/eigen

- cd vendor/eigen
- git checkout 3.4.0
- Add the following to the makefile to give Core access to the library: INC += -Ivendor/eigen (See here for an example)

If you only wish to use a single version of Core, you can simply clone core/ into your project and add the core source and header files to your makefile.

1.2 Features

Here is the current feature list this repo provides:

Subsystems (See Wiki/Subsystems):

- · Tank drivetrain (user control / autonomous)
- · Mecanum drivetrain (user control / autonomous)
- · Odometry
 - Tank (Differential)
 - N-Pod
- Flywheel
- Lift
- · Custom encoders

Utilities (See Wiki/Utilites):

- PID controller
- FeedForward controller
- · Trapezoidal motion profile controller
- · Pure Pursuit
- · Generic auto program builder
- · Auto program UI selector
- Mathematical classes (Vector2D, Moving Average)

2 Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

VDP::AbstractDevice 10

Async	12
BasicSolenoidSet	14
BasicSpinCommand	15
BasicStopCommand	16
Branch	17
screen::ButtonWidget	18
CommandController	19
Condition	22
FunctionCondition	47
IfTimePassed	51
CRC32	23
CustomEncoder	25
DelayCommand	27
DriveForwardCommand	28
DriveStopCommand	30
DriveToPointCommand	31
AutoChooser::entry_t	33
Feedback	35
MotionController	67
PID	110
TakeBackHalf	167
FeedForward	37
FeedForward::ff_config_t	39
Filter	40
ExponentialMovingAverage	33
MovingAverage	72
Flywheel	40
FlywheelStopCommand	44
FlywheelStopMotorsCommand	45
FlywheelStopNonTasksCommand	46
FunctionCommand	46
GenericAuto	49

PurePursuit::hermite_point	50
InOrder	51
InterpolatingMap< KEY, VALUE >	52
Lift< T >	53
Lift< T >::lift_cfg_t	57
Logger	58
MotionController::m_profile_cfg_t	61
StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage	62
MecanumDrive	63
MecanumDrive::mecanumdrive_config_t	66
Odometry3Wheel::odometry3wheel_cfg_t	80
OdometryBase	81
Odometry3Wheel	78
OdometrySerial	91
OdometryTank	96
OdomSetPosition	99
VDP::PacketHeader	100
VDP::PacketWriter	100
screen::Page	104
AutoChooser	12
screen::FunctionPage	47
screen::OdometryPage	90
screen::PIDPage	120
screen::StatsPage	162
Parallel	105
VDP::Part	106
$\label{eq:VDP::Number} \textbf{VDP::Number} < \textbf{float, Type::Float} >$	74
${\tt VDP::Number}{<}\ {\tt double}, {\tt Type::Double}>$	74
VDP::Number < uint8_t, Type::Uint8 >	74
VDP::Number < uint16_t, Type::Uint16 >	74
VDP::Number < uint32_t, Type::Uint32 >	74
VDP::Number< uint64 t, Type::Uint64 >	74

2.1 Class Hierarchy 5

VDP::Number< int8_t, Type::Int8 >	74
VDP::Number < int16_t, Type::Int16 >	74
VDP::Number < int32_t, Type::Int32 >	74
VDP::Number < int64_t, Type::Int64 >	74
${\tt VDP::Number} < {\tt NumT, schemaType} >$	74
VDP::Record	129
VDP::MotorDataRecord	70
VDP::OdometryControlRecord	86
VDP::OdometryDataRecord	88
VDP::PIDControlRecord	116
VDP::PIDDataRecord	118
VDP::TimestampedRecord	179
VDP::String	163
PurePursuit::Path	109
PID::pid_config_t	115
Pose2d	121
PurePursuitCommand	128
Rect	132
VDP::RegistryListener< MutexType >	132
robot_specs_t	134
Rotation2d	135
ScaledSphericalSimplexSigmaPoints < STATES >	142
screen::ScreenData	145
Serializer	145
screen::SliderWidget	149
SpinRPMCommand	151
PurePursuit::spline	152
${\bf Square Root Unscented Kalman Filter < STATES, INPUTS, OUTPUTS >}$	152
StateMachine< System, IDType, Message, delay_ms, do_log >::State	160
StateMachine $<$ System, IDType, Message, delay_ms, do_log $>$	160
TankDrive	169
tracking_wheel_cfg_t	181

CRC32

CustomEncoder

DelayCommand

DriveForwardCommand

Transform2d	182
Translation2d	187
TrapezoidProfile	195
TurnDegreesCommand	197
TurnToHeadingCommand	198
Twist2d	200
WaitUntilCondition	202
WaitUntilUpToSpeedCommand	203
3 Class Index	
3.1 Class List	
Here are the classes, structs, unions and interfaces with brief descriptions:	
VDP::AbstractDevice	10
Async Async runs a command asynchronously will simply let it go and never look back THIS HAS VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT	A 12
AutoChooser	12
BasicSolenoidSet	14
BasicSpinCommand	15
BasicStopCommand	16
Branch Branch chooses from multiple options at runtime. the function decider returns an index in the choices vector If you wish to make no choice and skip this section, return NO_CHOICE; at choice that is out of bounds set to NO_CHOICE	
screen::ButtonWidget Widget that does something when you tap it. The function is only called once when you fir tap it	rst 18
CommandController	19
Condition	22

A class for calculating the CRC32 checksum from arbitrary data

23

25

27

28

3.1 Class List 7

DriveStopCommand	30
DriveToPointCommand	31
AutoChooser::entry_t	33
Exponential Moving Average	33
Feedback	35
FeedForward	37
FeedForward::ff_config_t	39
Filter	40
Flywheel	40
FlywheelStopCommand	44
FlywheelStopMotorsCommand	45
FlywheelStopNonTasksCommand	46
FunctionCommand	46
FunctionCondition FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime	47
screen::FunctionPage Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything	47
GenericAuto	49
PurePursuit::hermite_point	50
IfTimePassed IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time_s	51
InOrder InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?	51
InterpolatingMap < KEY, VALUE >	52
Lift <t></t>	53
Lift< T >::lift_cfg_t	57
Logger Class to simplify writing to files	58
MotionController::m_profile_cfg_t	61
StateMachine < System, IDType, Message, delay_ms, do_log >::MaybeMessage MaybeMessage a message of Message type or nothing MaybeMessage m = {}; // empty MaybeMessage m = Message::EnumField1	62
MecanumDrive	63

MecanumDrive::mecanumdrive_config_t	66
MotionController	67
VDP::MotorDataRecord	70
MovingAverage	72
VDP::Number < NumT, schemaType >	74
Odometry3Wheel	78
Odometry3Wheel::odometry3wheel_cfg_t	80
OdometryBase	81
VDP::OdometryControlRecord	86
VDP::OdometryDataRecord	88
screen::OdometryPage Page that shows odometry position and rotation and a map (if an sd card with the file is on)	90
OdometrySerial	91
OdometryTank	96
OdomSetPosition	99
VDP::PacketHeader	100
VDP::PacketWriter	100
screen::Page Page describes one part of the screen slideshow	104
Parallel Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on_timeout on all children continue	105
VDP::Part	106
PurePursuit::Path	109
PID	110
PID::pid_config_t	115
VDP::PIDControlRecord	116
VDP::PIDDataRecord	118
screen::PIDPage PIDPage provides a way to tune a pid controller on the screen	120
Pose2d	121
PurePursuitCommand	128
VDP::Record	129
Rect	132

3.1 Class List 9

VDP::RegistryListener< MutexType >	132
robot_specs_t	134
Rotation2d	135
ScaledSphericalSimplexSigmaPoints < STATES >	142
screen::ScreenData Holds the data that will be passed to the screen thread you probably shouldnt have to use it	145
Serializer Serializes Arbitrary data to a file on the SD Card	145
screen::SliderWidget Widget that updates a double value. Updates by reference so watch out for race conditions cuz the screen stuff lives on another thread	149
SpinRPMCommand	151
PurePursuit::spline	152
SquareRootUnscentedKalmanFilter < STATES, INPUTS, OUTPUTS >	152
StateMachine < System, IDType, Message, delay_ms, do_log >::State	160
StateMachine < System, IDType, Message, delay_ms, do_log > State Machine :)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024 Over Under game for our overly complex intake-cata subsystem (see there for an example) The statemachine runs in a background thread and a user thread can interact with it through current_state and send_message	160
screen::StatsPage Draws motor stats and battery stats to the screen	162
VDP::String	163
TakeBackHalf A velocity controller	167
TankDrive	169
VDP::TimestampedRecord	179
tracking_wheel_cfg_t	181
Transform2d	182
Translation2d	187
TrapezoidProfile	195
TurnDegreesCommand	197
TurnToHeadingCommand	198
Twist2d	200
WaitUntilCondition Waits until the condition is true	202

4 Namespace Documentation

4.1 VDB Namespace Reference

Functions

```
uint32_t time_ms ()void delay_ms (uint32_t ms)
```

4.1.1 Detailed Description

Defines a COBS Serial Device to transmit VDB data through

4.1.2 Function Documentation

delay_ms()

delay for ms time

Parameters

ms the ms to delay for	
------------------------	--

time_ms()

```
uint32_t VDB::time_ms ()
```

Returns

the time in ms of the bot since startup

5 Class Documentation

5.1 VDP::AbstractDevice Class Reference

```
#include otocol.hpp>
```

Public Member Functions

- virtual bool send_packet (const VDP::Packet &packet)=0
- virtual void register_receive_callback (std::function< void(const VDP::Packet &packet)> callback)=0
- virtual ∼AbstractDevice ()

5.1.1 Detailed Description

defines a generic device to trasmit packets through

5.1.2 Constructor & Destructor Documentation

\sim AbstractDevice()

```
VDP::AbstractDevice::~AbstractDevice () [virtual]
```

deleter for the device, used to delete it when it is no longer needed

5.1.3 Member Function Documentation

register_receive_callback()

a callback to function that runs when a new packet is available

Parameters

the function for the callback to call me when my ex-wife

send_packet()

Sends a packet over some transmission medium It is not specified how the packet reaches the partner The transmission medium and wire format are left to the user

Parameters

packet	the packet to send through the device

Returns

whether the packet was sent sucessfully or not

- · protocol.hpp
- · protocol.cpp

5.2 Async Class Reference

Async runs a command asynchronously will simply let it go and never look back THIS HAS A VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT.

```
#include <auto_command.h>
```

5.2.1 Detailed Description

Async runs a command asynchronously will simply let it go and never look back THIS HAS A VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT.


The documentation for this class was generated from the following files:

- · auto command.h
- · auto_command.cpp

5.3 AutoChooser Class Reference

```
#include <auto_chooser.h>
```

Inheritance diagram for AutoChooser:



Classes

struct entry_t

Public Member Functions

- AutoChooser (std::vector< std::string > paths, size_t def=0)
- size_t get_choice ()

Protected Attributes

- · size t choice
- std::vector< entry_t > list

5.3.1 Detailed Description

Autochooser is a utility to make selecting robot autonomous programs easier source: RIT VexU Wiki During a season, we usually code between 4 and 6 autonomous programs. Most teams will change their entire robot program as a way of choosing autonomi but this may cause issues if you have an emergency patch to upload during a competition. This class was built as a way of using the robot screen to list autonomous programs, and the touchscreen to select them.

5.3.2 Constructor & Destructor Documentation

AutoChooser()

Initialize the auto-chooser. This class places a choice menu on the brain screen, so the driver can choose which autonomous to run.

Parameters

brain the brain on which to draw the selection boxes

5.3.3 Member Function Documentation

get_choice()

```
size_t AutoChooser::get_choice ()
```

Get the currently selected auto choice

Returns

the identifier to the auto path

Return the selected autonomous

5.3.4 Member Data Documentation

choice

```
size_t AutoChooser::choice [protected]
```

the current choice of auto

list

```
std::vector<entry_t> AutoChooser::list [protected]
```

< a list of all possible auto choices

- · auto_chooser.h
- auto_chooser.cpp

5.4 BasicSolenoidSet Class Reference

```
#include <basic_command.h>
```

Public Member Functions

• BasicSolenoidSet (vex::pneumatics &solenoid, bool setting)

Construct a new BasicSolenoidSet Command.

• bool run () override

Runs the BasicSolenoidSet Overrides run command from AutoCommand.

5.4.1 Detailed Description

AutoCommand wrapper class for BasicSolenoidSet Using the Vex hardware functions

5.4.2 Constructor & Destructor Documentation

BasicSolenoidSet()

Construct a new BasicSolenoidSet Command.

Parameters

solenoid	Solenoid being set
setting	Setting of the solenoid in boolean (true,false)

5.4.3 Member Function Documentation

run()

```
bool BasicSolenoidSet::run () [override]
```

Runs the BasicSolenoidSet Overrides run command from AutoCommand.

Returns

True Command runs once

- basic_command.h
- basic_command.cpp

5.5 BasicSpinCommand Class Reference

```
#include <basic_command.h>
```

Public Member Functions

• BasicSpinCommand (vex::motor &motor, vex::directionType dir, BasicSpinCommand::type setting, double power)

Construct a new BasicSpinCommand.

• bool run () override

Runs the BasicSpinCommand Overrides run from Auto Command.

5.5.1 Detailed Description

AutoCommand wrapper class for BasicSpinCommand using the vex hardware functions

5.5.2 Constructor & Destructor Documentation

BasicSpinCommand()

```
BasicSpinCommand::BasicSpinCommand (
    vex::motor & motor,
    vex::directionType dir,
    BasicSpinCommand::type setting,
    double power)
```

Construct a new BasicSpinCommand.

a BasicMotorSpin Command

Parameters

motor	otor Motor to spin	
direc	Direction of motor spin	
setting	setting Power setting in volts,percentage,velocity	
power	Value of desired power	
motor	motor Motor port to spin	
dir	dir Direction for spining	
setting	setting Power setting in volts,percentage,velocity	
power	Value of desired power	

5.5.3 Member Function Documentation

run()

```
bool BasicSpinCommand::run () [override]
```

Runs the BasicSpinCommand Overrides run from Auto Command.

Run the BasicSpinCommand Overrides run from Auto Command.

Returns

True Async running command

True Command runs once

The documentation for this class was generated from the following files:

- · basic_command.h
- basic_command.cpp

5.6 BasicStopCommand Class Reference

```
#include <basic_command.h>
```

Public Member Functions

- BasicStopCommand (vex::motor &motor, vex::brakeType setting)
 Construct a new BasicMotorStop Command.
- bool run () override

Runs the BasicMotorStop Command Overrides run command from AutoCommand.

5.6.1 Detailed Description

AutoCommand wrapper class for BasicStopCommand Using the Vex hardware functions

5.6.2 Constructor & Destructor Documentation

BasicStopCommand()

Construct a new BasicMotorStop Command.

Construct a BasicMotorStop Command.

motor	The motor to stop	
setting	The brake setting for the motor	
motor	notor Motor to stop	
setting	Braketype setting brake,coast,hold	

5.6.3 Member Function Documentation

run()

```
bool BasicStopCommand::run () [override]
```

Runs the BasicMotorStop Command Overrides run command from AutoCommand.

Runs the BasicMotorStop command Ovverides run command from AutoCommand.

Returns

True Command runs once

The documentation for this class was generated from the following files:

- · basic_command.h
- · basic_command.cpp

5.7 Branch Class Reference

Branch chooses from multiple options at runtime. the function decider returns an index into the choices vector If you wish to make no choice and skip this section, return NO_CHOICE; any choice that is out of bounds set to NO_CHOICE.

```
#include <auto_command.h>
```

5.7.1 Detailed Description

Branch chooses from multiple options at runtime. the function decider returns an index into the choices vector If you wish to make no choice and skip this section, return NO_CHOICE; any choice that is out of bounds set to NO_CHOICE.

- · auto_command.h
- · auto_command.cpp

5.8 screen::ButtonWidget Class Reference

Widget that does something when you tap it. The function is only called once when you first tap it.

```
#include <screen.h>
```

Public Member Functions

• ButtonWidget (std::function < void(void) > onpress, Rect rect, std::string name)

Create a Button widget.

• ButtonWidget (void(*onpress)(), Rect rect, std::string name)

Create a Button widget.

bool update (bool was_pressed, int x, int y)

responds to user input

• void **draw** (vex::brain::lcd &, bool first_draw, unsigned int frame_number)

draws the button to the screen

5.8.1 Detailed Description

Widget that does something when you tap it. The function is only called once when you first tap it.

5.8.2 Constructor & Destructor Documentation

ButtonWidget() [1/2]

Create a Button widget.

Parameters

onpress the function to be called when the button is tappe	
rect	the area the button should take up on the screen
name the label put on the button	

ButtonWidget() [2/2]

Create a Button widget.

onpress the function to be called when the button is tappe	
rect	the area the button should take up on the screen
name	the label put on the button

5.8.3 Member Function Documentation

update()

```
bool screen::ButtonWidget::update ( bool \ was\_pressed, int \ x, int \ y)
```

responds to user input

Parameters

was_pressed	if the screen is pressed
X	x position if the screen was pressed
У	y position if the screen was pressed

Returns

true if the button was pressed

The documentation for this class was generated from the following files:

- · screen.h
- · screen.cpp

5.9 CommandController Class Reference

```
#include <command_controller.h>
```

Public Member Functions

• CommandController ()

Create an empty CommandController. Add Command with CommandController::add()

CommandController (std::initializer_list< AutoCommand * > cmds)

Create a CommandController with commands pre added. More can be added with CommandController::add()

- void add (std::vector< AutoCommand * > cmds)
- void add (AutoCommand *cmd, double timeout_seconds=10.0)
- void add (std::vector< AutoCommand * > cmds, double timeout_sec)
- void add_delay (int ms)
- void add_cancel_func (std::function< bool(void)> true_if_cancel)

add_cancel_func specifies that when this func evaluates to true, to cancel the command controller

- void run ()
- bool last_command_timed_out ()

5.9.1 Detailed Description

File: command_controller.h Desc: A CommandController manages the AutoCommands that make up an autonomous route. The AutoCommands are kept in a queue and get executed and removed from the queue in FIFO order.

5.9.2 Constructor & Destructor Documentation

CommandController()

```
\label{lem:commandController} CommandController \mbox{ (} \\ std::initializer\_list<\mbox{ AutoCommand } * > cmds) \mbox{ [inline]}
```

Create a CommandController with commands pre added. More can be added with CommandController::add()

Parameters

cmds

5.9.3 Member Function Documentation

add() [1/3]

File: command_controller.cpp Desc: A CommandController manages the AutoCommands that make up an autonomous route. The AutoCommands are kept in a queue and get executed and removed from the queue in FIFO order. Adds a command to the queue

Parameters

cmd	the AutoCommand we want to add to our list	
timeout_seconds	the number of seconds we will let the command run for. If it exceeds this, we cancel it and	
	run on_timeout	

add() [2/3]

Adds a command to the queue

Parameters

cmd	the AutoCommand we want to add to our list
timeout_seconds	the number of seconds we will let the command run for. If it exceeds this, we cancel it and
	run on_timeout. if it is \leq = 0 no time out will be applied

Add multiple commands to the queue. No timeout here.

	cmds	the AutoCommands we want to add to our list	
--	------	---	--

add() [3/3]

```
void CommandController::add (
          std::vector< AutoCommand * > cmds,
          double timeout_sec)
```

Add multiple commands to the queue. No timeout here.

Parameters

cmds	the AutoCommands we want to add to our list Add multiple commands to the queue. No timeout here.	
cmds	the AutoCommands we want to add to our list	
timeout_sec	timeout in seconds to apply to all commands if they are still the default	

Add multiple commands to the queue. No timeout here.

Parameters

cmds	the AutoCommands we want to add to our list
timeout	timeout in seconds to apply to all commands if they are still the default

add_cancel_func()

```
\label{lem:commandController::add_cancel_func (} $$ std::function< bool(void)> true\_if\_cancel)$
```

add_cancel_func specifies that when this func evaluates to true, to cancel the command controller

Parameters

add_delay()

Adds a command that will delay progression of the queue

Parameters

ms - number of milliseconds to wait before continuing execution of autonomous

last_command_timed_out()

```
bool CommandController::last_command_timed_out ()
```

last_command_timed_out tells how the last command ended Use this if you want to make decisions based on the end of the last command

Returns

true if the last command timed out. false if it finished regularly

run()

```
void CommandController::run ()
```

Begin execution of the queue Execute and remove commands in FIFO order


The documentation for this class was generated from the following files:

- · command controller.h
- command_controller.cpp

5.10 Condition Class Reference

```
#include <auto_command.h>
```

Inheritance diagram for Condition:



5.10.1 Detailed Description

File: auto_command.h Desc: Interface for module-specifc commands A Condition is a function that returns true or false is_even is a predicate that would return true if a number is even For our purposes, a Condition is a choice to be made at runtime drive_sys.reached_point(10, 30) is a predicate time.has_elapsed(10, vex::seconds) is a predicate extend this class for different choices you wish to make

- · auto command.h
- · auto_command.cpp

5.11 CRC32 Class Reference

A class for calculating the CRC32 checksum from arbitrary data.

```
#include <crc32.hpp>
```

Public Member Functions

· CRC32 ()

Initialize an empty CRC32 checksum.

• void reset ()

Reset the checksum claculation.

void update (const uint8_t &data)

Update the current checksum caclulation with the given data.

template<typename Type>
 void update (const Type &data)

Update the current checksum caclulation with the given data.

template<typename Type>
 void update (const Type *data, std::size_t size)

Update the current checksum caclulation with the given data.

• uint32_t finalize () const

Static Public Member Functions

```
    template < typename Type >
        static uint32_t calculate (const Type *data, std::size_t size)
        Calculate the checksum of an arbitrary data array.
```

5.11.1 Detailed Description

A class for calculating the CRC32 checksum from arbitrary data.

See also

```
http://forum.arduino.cc/index.php?topic=91179.0
```

5.11.2 Member Function Documentation

calculate()

Calculate the checksum of an arbitrary data array.

Template Parameters

Parameters

data	A pointer to the data to add to the checksum.
size	The size of the data to add to the checksum.

Returns

the calculated checksum.

finalize()

```
uint32_t CRC32::finalize () const
```

Returns

the caclulated checksum.

update() [1/3]

Update the current checksum caclulation with the given data.

Template Parameters

Type The data type to read	Туре
----------------------------	------

Parameters

data	The data to add to the checksum.
------	----------------------------------

update() [2/3]

Update the current checksum caclulation with the given data.

Template Parameters

Туре	The data type to read.
------	------------------------

Parameters

data	The array to add to the checksum.
size	Size of the array to add.

update() [3/3]

Update the current checksum caclulation with the given data.

Parameters

data The data to add to the checksum	
--------------------------------------	--

The documentation for this class was generated from the following files:

- · crc32.hpp
- crc32.cpp

5.12 CustomEncoder Class Reference

```
#include <custom_encoder.h>
```

Public Member Functions

- CustomEncoder (vex::triport::port &port, double ticks_per_rev)
- void setRotation (double val, vex::rotationUnits units)
- void setPosition (double val, vex::rotationUnits units)
- double rotation (vex::rotationUnits units)
- double position (vex::rotationUnits units)
- double velocity (vex::velocityUnits units)

5.12.1 Detailed Description

A wrapper class for the vex encoder that allows the use of 3rd party encoders with different tick-per-revolution values.

5.12.2 Constructor & Destructor Documentation

CustomEncoder()

Construct an encoder with a custom number of ticks

port	the triport port on the brain the encoder is plugged into
ticks_per_rev	the number of ticks the encoder will report for one revolution

5.12.3 Member Function Documentation

position()

get the position that the encoder is at

Parameters

units	the unit we want the return value to be in
-------	--

Returns

the position of the encoder in the units specified

rotation()

get the rotation that the encoder is at

Parameters

want the return	it we want the return value to be in
-----------------	--------------------------------------

Returns

the rotation of the encoder in the units specified

setPosition()

sets the stored position of the encoder. Any further movements will be from this value

val	the numerical value of the position we are setting to
units	the unit of val

setRotation()

sets the stored rotation of the encoder. Any further movements will be from this value

Parameters

val	the numerical value of the angle we are setting to
units	the unit of val

velocity()

get the velocity that the encoder is moving at

Parameters

Returns

the velocity of the encoder in the units specified

The documentation for this class was generated from the following files:

- · custom_encoder.h
- · custom_encoder.cpp

5.13 DelayCommand Class Reference

```
#include <delay_command.h>
```

Public Member Functions

- DelayCommand (int ms)
- bool run () override

5.13.1 Detailed Description

File: delay_command.h Desc: A DelayCommand will make the robot wait the set amount of milliseconds before continuing execution of the autonomous route

5.13.2 Constructor & Destructor Documentation

DelayCommand()

Construct a delay command

Parameters

ms the number of milliseconds to delay for

5.13.3 Member Function Documentation

run()

```
bool DelayCommand::run () [inline], [override]
```

Delays for the amount of milliseconds stored in the command Overrides run from AutoCommand

Returns

true when complete

The documentation for this class was generated from the following file:

· delay_command.h

5.14 DriveForwardCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- DriveForwardCommand (TankDrive &drive_sys, Feedback &feedback, double inches, directionType dir, double max_speed=1, double end_speed=0)
- bool run () override
- void on_timeout () override

5.14.1 Detailed Description

AutoCommand wrapper class for the drive_forward function in the TankDrive class

5.14.2 Constructor & Destructor Documentation

DriveForwardCommand()

File: drive_commands.h Desc: Holds all the AutoCommand subclasses that wrap (currently) TankDrive functions

Currently includes:

- · drive_forward
- · turn_degrees
- · drive_to_point
- turn_to_heading
- stop

Also holds AutoCommand subclasses that wrap OdometryBase functions

Currently includes:

• set_position Construct a DriveForward Command

Parameters

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the drive
inches	how far forward to drive
dir	the direction to drive
max_speed	0 -> 1 percentage of the drive systems speed to drive at

5.14.3 Member Function Documentation

on_timeout()

```
void DriveForwardCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we timeout

run()

```
bool DriveForwardCommand::run () [override]
```

Run drive_forward Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive_commands.h
- drive_commands.cpp

5.15 DriveStopCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- DriveStopCommand (TankDrive &drive_sys)
- bool run () override

5.15.1 Detailed Description

AutoCommand wrapper class for the stop() function in the TankDrive class

5.15.2 Constructor & Destructor Documentation

DriveStopCommand()

Construct a DriveStop Command

Parameters

drive_sys	the drive system we are commanding
-----------	------------------------------------

5.15.3 Member Function Documentation

run()

```
bool DriveStopCommand::run () [override]
```

Stop the drive system Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

Stop the drive train Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive_commands.h
- drive_commands.cpp

5.16 DriveToPointCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- DriveToPointCommand (TankDrive &drive_sys, Feedback &feedback, double x, double y, directionType dir, double max_speed=1, double end_speed=0)
- DriveToPointCommand (TankDrive &drive_sys, Feedback &feedback, Translation2d translation, directionType dir, double max_speed=1, double end_speed=0)
- bool run () override

5.16.1 Detailed Description

AutoCommand wrapper class for the drive to point function in the TankDrive class

5.16.2 Constructor & Destructor Documentation

DriveToPointCommand() [1/2]

Construct a DriveForward Command

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the drive
X	where to drive in the x dimension
У	where to drive in the y dimension
dir	the direction to drive
max_speed	0 -> 1 percentage of the drive systems speed to drive at

DriveToPointCommand() [2/2]

Construct a DriveForward Command

Parameters

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the drive
translation	the point to drive to
dir	the direction to drive
max_speed	0 -> 1 percentage of the drive systems speed to drive at

5.16.3 Member Function Documentation

run()

```
bool DriveToPointCommand::run () [override]
```

Run drive_to_point Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- drive_commands.h
- drive_commands.cpp

5.17 AutoChooser::entry_t Struct Reference

#include <auto_chooser.h>

Public Attributes

• std::string name

5.17.1 Detailed Description

entry_t is a datatype used to store information that the chooser knows about an auto selection button

5.17.2 Member Data Documentation

name

```
std::string AutoChooser::entry_t::name
```

name of the auto repretsented by the block

The documentation for this struct was generated from the following file:

· auto_chooser.h

5.18 Exponential Moving Average Class Reference

```
#include <moving_average.h>
```

Inheritance diagram for ExponentialMovingAverage:



Public Member Functions

- ExponentialMovingAverage (int buffer_size)
- ExponentialMovingAverage (int buffer_size, double starting_value)
- · void add_entry (double n) override
- double get_value () const override
- int get_size ()

5.18.1 Detailed Description

ExponentialMovingAverage

An exponential moving average is a way of smoothing out noisy data. For many sensor readings, the noise is roughly symmetric around the actual value. This means that if you collect enough samples those that are too high are cancelled out by the samples that are too low leaving the real value.

A simple mobing average lags significantly with time as it has to counteract old samples. An exponential moving average keeps more up to date by weighting newer readings higher than older readings so it is more up to date while also still smoothed.

The ExponentialMovingAverage class provides an simple interface to do this smoothing from our noisy sensor values.

5.18.2 Constructor & Destructor Documentation

ExponentialMovingAverage() [1/2]

Create a moving average calculator with 0 as the default value

Parameters

buffer_size	The size of the buffer. The number of samples that constitute a valid reading
-------------	---

ExponentialMovingAverage() [2/2]

Create a moving average calculator with a specified default value

Parameters

buffer_size	The size of the buffer. The number of samples that constitute a valid reading
starting_value	The value that the average will be before any data is added

5.18.3 Member Function Documentation

add_entry()

Add a reading to the buffer Before: [1 1 2 2 3 3] => 2 $^{\land}$ After: [2 1 2 2 3 3] => 2.16 $^{\land}$

n the sample that will be added to the moving average.

Implements Filter.

get_size()

```
int ExponentialMovingAverage::get_size ()
```

How many samples the average is made from

Returns

the number of samples used to calculate this average

get_value()

```
double ExponentialMovingAverage::get_value () const [override], [virtual]
```

Returns the average based off of all the samples collected so far

Returns

the calculated average. sum(samples)/numsamples

How many samples the average is made from

Returns

the number of samples used to calculate this average

Implements Filter.


The documentation for this class was generated from the following files:

- · moving_average.h
- · moving_average.cpp

5.19 Feedback Class Reference

```
#include <feedback_base.h>
```

Inheritance diagram for Feedback:



Public Member Functions

- virtual void init (double start_pt, double set_pt)=0
- virtual double update (double val)=0
- virtual double get ()=0
- virtual void set_limits (double lower, double upper)=0
- virtual bool is_on_target ()=0

5.19.1 Detailed Description

Interface so that subsystems can easily switch between feedback loops

Author

Ryan McGee

Date

9/25/2022

5.19.2 Member Function Documentation

get()

```
virtual double Feedback::get () [pure virtual]
```

Returns

the last saved result from the feedback controller

Implemented in MotionController, PID, and TakeBackHalf.

init()

Initialize the feedback controller for a movement

Parameters

start_pt	the current sensor value
set_pt	where the sensor value should be
start_vel	Movement starting velocity
end_vel	Movement ending velocity

Implemented in MotionController, PID, and TakeBackHalf.

is_on_target()

```
virtual bool Feedback::is_on_target () [pure virtual]
```

Returns

true if the feedback controller has reached it's setpoint

Implemented in MotionController, PID, and TakeBackHalf.

set_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

Parameters

lower	Upper limit
upper	Lower limit

Implemented in MotionController, PID, and TakeBackHalf.

update()

Iterate the feedback loop once with an updated sensor value

Parameters

val	value from the sensor
-----	-----------------------

Returns

feedback loop result

Implemented in MotionController, PID, and TakeBackHalf.

The documentation for this class was generated from the following file:

· feedback_base.h

5.20 FeedForward Class Reference

#include <feedforward.h>

Classes

· struct ff_config_t

Public Member Functions

- FeedForward (ff_config_t &cfg)
- double calculate (double v, double a, double pid ref=0.0)

Perform the feedforward calculation.

5.20.1 Detailed Description

FeedForward

Stores the feedfoward constants, and allows for quick computation. Feedfoward should be used in systems that require smooth precise movements and have high inertia, such as drivetrains and lifts.

This is best used alongside a PID loop, with the form: output = pid.get() + feedforward.calculate(v, a);

In this case, the feedforward does the majority of the heavy lifting, and the pid loop only corrects for inconsistencies

For information about tuning feedforward, I reccommend looking at this post: $https://www. \leftarrow chiefdelphi.com/t/paper-frc-drivetrain-characterization/160915$ (yes I know it's for FRC but trust me, it's useful)

Author

Ryan McGee

Date

6/13/2022

5.20.2 Constructor & Destructor Documentation

FeedForward()

Creates a FeedForward object.

Parameters

```
cfg | Configuration Struct for tuning
```

5.20.3 Member Function Documentation

calculate()

Perform the feedforward calculation.

This calculation is the equation: F = kG + kS*sgn(v) + kV*v + kA*a

V	Requested velocity of system
а	Requested acceleration of system

Returns

A feedforward that should closely represent the system if tuned correctly

The documentation for this class was generated from the following file:

· feedforward.h

5.21 FeedForward::ff_config_t Struct Reference

#include <feedforward.h>

Public Attributes

- double kS
- double kV
- double kA
- double kG

5.21.1 Detailed Description

ff_config_t holds the parameters to make the theoretical model of a real world system equation is of the form kS if the system is not stopped, 0 otherwise

- kV * desired velocity
- kA * desired acceleration
- kG

5.21.2 Member Data Documentation

kΑ

```
double FeedForward::ff_config_t::kA
```

kA - Acceleration coefficient: the power required to change the mechanism's speed. Multiplied by the requested acceleration.

kG

```
double FeedForward::ff_config_t::kG
```

kG - Gravity coefficient: only needed for lifts. The power required to overcome gravity and stay at steady state.

kS

```
double FeedForward::ff_config_t::kS
```

Coefficient to overcome static friction: the point at which the motor *starts* to move.

k۷

```
double FeedForward::ff_config_t::kV
```

Veclocity coefficient: the power required to keep the mechanism in motion. Multiplied by the requested velocity.


The documentation for this struct was generated from the following file:

· feedforward.h

5.22 Filter Class Reference

```
#include <moving_average.h>
```

Inheritance diagram for Filter:



5.22.1 Detailed Description

Interface for filters Use add_entry to supply data and get_value to retrieve the filtered value

The documentation for this class was generated from the following file:

· moving_average.h

5.23 Flywheel Class Reference

#include <flywheel.h>

Public Member Functions

- Flywheel (vex::motor_group &motors, Feedback &feedback, FeedForward &helper, const double ratio, Filter &filt)
- double get_target () const
- double getRPM () const
- vex::motor_group & get_motors () const
- void spin_manual (double speed, directionType dir=fwd)
- void spin_rpm (double rpm)
- void stop ()
- bool is_on_target ()

check if the feedback controller thinks the flywheel is on target

• screen::Page * Page () const

Creates a page displaying info about the flywheel.

AutoCommand * SpinRpmCmd (int rpm)

Creates a new auto command to spin the flywheel at the desired velocity.

AutoCommand * WaitUntilUpToSpeedCmd ()

Creates a new auto command that will hold until the flywheel has its target as defined by its feedback controller.

Friends

int spinRPMTask (void *wheelPointer)

5.23.1 Detailed Description

a Flywheel class that handles all control of a high inertia spinning disk It gives multiple options for what control system to use in order to control wheel velocity and functions alerting the user when the flywheel is up to speed. Flywheel is a set and forget class. Once you create it you can call spin_rpm or stop on it at any time and it will take all necessary steps to accomplish this

5.23.2 Constructor & Destructor Documentation

Flywheel()

Create the Flywheel object using PID + feedforward for control.

Parameters

motors	pointer to the motors on the fly wheel
feedback	a feedback controleller
helper	a feedforward config (only kV is used) to help the feedback controller along
ratio	ratio of the gears from the motor to the flywheel just multiplies the velocity
filter	the filter to use to smooth noisy motor readings

5.23.3 Member Function Documentation

```
get_motors()
```

```
motor_group & Flywheel::get_motors () const
```

Returns the motors

Returns

the motors used to run the flywheel

get_target()

```
double Flywheel::get_target () const
```

Return the target_rpm that the flywheel is currently trying to achieve

Returns

target_rpm the target rpm

Return the current value that the target_rpm should be set to

getRPM()

```
double Flywheel::getRPM () const
```

return the velocity of the flywheel

is_on_target()

```
bool Flywheel::is_on_target () [inline]
```

check if the feedback controller thinks the flywheel is on target

Returns

true if on target

Page()

```
screen::Page * Flywheel::Page () const
```

Creates a page displaying info about the flywheel.

Returns

the page should be used for `screen::start_screen(screen, {fw.Page()});

spin_manual()

Spin motors using voltage; defaults forward at 12 volts FOR USE BY OPCONTROL AND AUTONOMOUS - this only applies if the target_rpm thread is not running

	speed	- speed (between -1 and 1) to set the motor
ĺ	dir	- direction that the motor moves in; defaults to forward

Spin motors using voltage; defaults forward at 12 volts FOR USE BY OPCONTROL AND AUTONOMOUS - this only applies if the RPM thread is not running

Parameters

speed	- speed (between -1 and 1) to set the motor
dir	- direction that the motor moves in; defaults to forward

spin_rpm()

starts or sets the target_rpm thread at new value what control scheme is dependent on control_style

Parameters

	rpm	- the target_rpm we want to spin at
--	-----	-------------------------------------

starts or sets the RPM thread at new value what control scheme is dependent on control_style

Parameters

```
input_rpm - set the current RPM
```

SpinRpmCmd()

Creates a new auto command to spin the flywheel at the desired velocity.

Parameters

rpm	the rpm to spin at

Returns

an auto command to add to a command controller

stop()

```
void Flywheel::stop ()
```

Stops the motors. If manually spinning, this will do nothing just call spin_mainual(0.0) to send 0 volts stop the RPM thread and the wheel

WaitUntilUpToSpeedCmd()

```
AutoCommand * Flywheel::WaitUntilUpToSpeedCmd () [inline]
```

Creates a new auto command that will hold until the flywheel has its target as defined by its feedback controller.

Returns

an auto command to add to a command controller

5.23.4 Friends And Related Symbol Documentation

spinRPMTask

Runs a thread that keeps track of updating flywheel RPM and controlling it accordingly

The documentation for this class was generated from the following files:

- flywheel.h
- · flywheel.cpp

5.24 FlywheelStopCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- FlywheelStopCommand (Flywheel &flywheel)
- bool run () override

5.24.1 Detailed Description

AutoCommand wrapper class for the stop function in the Flywheel class

5.24.2 Constructor & Destructor Documentation

FlywheelStopCommand()

```
\label{limits} FlywheelStopCommand:: FlywheelStopCommand ( \\ Flywheel \& flywheel)
```

Construct a FlywheelStopCommand

flywheel the flywheel system we are commanding

5.24.3 Member Function Documentation

run()

```
bool FlywheelStopCommand::run () [override]
```

Run stop Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- flywheel_commands.h
- flywheel_commands.cpp

5.25 FlywheelStopMotorsCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- FlywheelStopMotorsCommand (Flywheel &flywheel)
- bool run () override

5.25.1 Detailed Description

AutoCommand wrapper class for the stopMotors function in the Flywheel class

5.25.2 Constructor & Destructor Documentation

FlywheelStopMotorsCommand()

```
\label{lem:flywheelStopMotorsCommand::FlywheelStopMotorsCommand (} Flywheel & flywheel)
```

Construct a FlywheeStopMotors Command

flywheel	the flywheel system we are commanding
----------	---------------------------------------

5.25.3 Member Function Documentation

run()

bool FlywheelStopMotorsCommand::run () [override]

Run stop Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · flywheel commands.h
- flywheel_commands.cpp

5.26 FlywheelStopNonTasksCommand Class Reference

```
#include <flywheel_commands.h>
```

5.26.1 Detailed Description

AutoCommand wrapper class for the stopNonTasks function in the Flywheel class

The documentation for this class was generated from the following files:

- flywheel_commands.h
- flywheel_commands.cpp

5.27 FunctionCommand Class Reference

```
#include <auto_command.h>
```

5.27.1 Detailed Description

FunctionCommand is fun and good way to do simple things Printing, launching nukes, and other quick and dirty one time things

The documentation for this class was generated from the following file:


auto_command.h

5.28 FunctionCondition Class Reference

FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime.

```
#include <auto_command.h>
```

Inheritance diagram for FunctionCondition:



5.28.1 Detailed Description

FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime.

The documentation for this class was generated from the following files:

- · auto command.h
- · auto_command.cpp

5.29 screen::FunctionPage Class Reference

Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything.

```
#include <screen.h>
```

Inheritance diagram for screen::FunctionPage:



Public Member Functions

- FunctionPage (update_func_t update_f, draw_func_t draw_t)
 Creates a function page.
- void update (bool was_pressed, int x, int y) override
 update uses the supplied update function to update this page
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

draw uses the supplied draw function to draw to the screen

5.29.1 Detailed Description

Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything.

5.29.2 Constructor & Destructor Documentation

FunctionPage()

Creates a function page.

FunctionPage.

Parameters

update⇔ _f	the function called every tick to respond to user input or do data collection	
draw_t	the function called to draw to the screen	
update⇔		
_f		
draw_f	drawing function	

5.29.3 Member Function Documentation

draw()

draw uses the supplied draw function to draw to the screen

See also

Page::draw

Reimplemented from screen::Page.

update()

update uses the supplied update function to update this page

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:

- · screen.h
- · screen.cpp

5.30 GenericAuto Class Reference

```
#include <generic_auto.h>
```

Public Member Functions

- bool run (bool blocking)
- void add (state ptr new state)
- void add_async (state_ptr async_state)
- void add_delay (int ms)

5.30.1 Detailed Description

GenericAuto provides a pleasant interface for organizing an auto path steps of the path can be added with add() and when ready, calling run() will begin executing the path

5.30.2 Member Function Documentation

add()

Add a new state to the autonomous via function point of type "bool (ptr*)()"

Parameters

```
new_state the function to run
```

add async()

Add a new state to the autonomous via function point of type "bool (ptr*)()" that will run asynchronously

async_state the f	unction to run
-------------------	----------------

add_delay()

```
void GenericAuto::add_delay (
          int ms)
```

add_delay adds a period where the auto system will simply wait for the specified time

Parameters

ms	how long to wait in milliseconds
----	----------------------------------

run()

```
bool GenericAuto::run (
          bool blocking)
```

The method that runs the autonomous. If 'blocking' is true, then this method will run through every state until it finished.

If blocking is false, then assuming every state is also non-blocking, the method will run through the current state in the list and return immediately.

Parameters

blocking	Whether or not to block the thread until all states have run
----------	--

Returns

true after all states have finished.

The documentation for this class was generated from the following files:

- · generic_auto.h
- generic_auto.cpp

5.31 PurePursuit::hermite_point Struct Reference

```
#include <pure_pursuit.h>
```

5.31.1 Detailed Description

a position along the hermite path contains a position and orientation information that the robot would be at at this point

The documentation for this struct was generated from the following file:

· pure pursuit.h

5.32 IfTimePassed Class Reference

IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time_s.

```
#include <auto_command.h>
```

Inheritance diagram for IfTimePassed:



5.32.1 Detailed Description

IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time s.

The documentation for this class was generated from the following files:

- · auto command.h
- · auto_command.cpp

5.33 InOrder Class Reference

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

```
#include <auto_command.h>
```

5.33.1 Detailed Description

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

The documentation for this class was generated from the following files:

- auto_command.h
- auto_command.cpp

5.34 InterpolatingMap < KEY, VALUE > Class Template Reference

#include <interpolating_map.h>

Public Member Functions

- void insert (const KEY &key, const VALUE &value)
- VALUE operator[] (const KEY &key)
- void clear ()

5.34.1 Detailed Description

template<typename KEY, typename VALUE> class InterpolatingMap< KEY, VALUE>

This class implements a map of key-value pairs.

If there is not a pair with the given key in the map, the value will be a linear interpolation of the preceding and following values.

Template Parameters

KEY	The type of the key.
VALUE	The type of the value.

5.34.2 Member Function Documentation

clear()

```
template<typename KEY, typename VALUE>
void InterpolatingMap< KEY, VALUE >::clear () [inline]
```

Clears the contents of the map.

insert()

Inserts a key value pair.

Parameters

key	The key.
vlue	The value.

operator[]()

Obtains the value at the given key.

If the key does not exactly match a pair in the map, it will interpolate between the preceding and following pairs.

key	The key.
-----	----------

Returns

The value.

The documentation for this class was generated from the following file:

· interpolating_map.h

5.35 Lift< T > Class Template Reference

```
#include <lift.h>
```

Classes

• struct lift_cfg_t

Public Member Functions

- Lift (motor_group &lift_motors, lift_cfg_t &lift_cfg, map< T, double > &setpoint_map, limit *homing_← switch=NULL)
- void control_continuous (bool up_ctrl, bool down_ctrl)
- void control_manual (bool up_btn, bool down_btn, int volt_up, int volt_down)
- void control_setpoints (bool up_step, bool down_step, vector< T > pos_list)
- bool set position (T pos)
- bool set_setpoint (double val)
- double get_setpoint ()
- void hold ()
- void home ()
- · bool get_async ()
- void set_async (bool val)
- void set_sensor_function (double(*fn_ptr)(void))
- void set_sensor_reset (void(*fn_ptr)(void))

5.35.1 Detailed Description

template<typename T> class Lift< T >

LIFT A general class for lifts (e.g. 4bar, dr4bar, linear, etc) Uses a PID to hold the lift at a certain height under load, and to move the lift to different heights

Author

Ryan McGee

5.35.2 Constructor & Destructor Documentation

Lift()

Construct the Lift object and begin the background task that controls the lift.

Usage example: /code{.cpp} enum Positions {UP, MID, DOWN}; map<Positions, double> setpt_map { {DOWN, 0.0}, {MID, 0.5}, {UP, 1.0} }; Lift<Positions> my_lift(motors, lift_cfg, setpt_map); /endcode

Parameters

lift_motors	A set of motors, all set that positive rotation correlates with the lift going up	
lift_cfg	Lift characterization information; PID tunings and movement speeds	
setpoint_map	A map of enum type T, in which each enum entry corresponds to a different lift height	

5.35.3 Member Function Documentation

control_continuous()

Control the lift with an "up" button and a "down" button. Use PID to hold the lift when letting go.

Parameters

up_ctrl	Button controlling the "UP" motion
down_ctrl	Button controlling the "DOWN" motion

control_manual()

Control the lift with manual controls (no holding voltage)

up_btn	Raise the lift when true				
down_btn	Lower the lift when true				
volt_up	Motor voltage when raising the lift				
volt_down	Motor voltage when lowering the lift				

control_setpoints()

Control the lift in "steps". When the "up" button is pressed, the lift will go to the next position as defined by pos_list. Order matters!

Parameters

up_step	A button that increments the position of the lift.			
down_step	A button that decrements the position of the lift.			
pos_list	A list of positions for the lift to go through. The higher the index, the higher the lift should be (generally).			

get_async()

```
template<typename T>
bool Lift< T >::get_async () [inline]
```

Returns

whether or not the background thread is running the lift

get_setpoint()

```
template<typename T>
double Lift< T >::get_setpoint () [inline]
```

Returns

The current setpoint for the lift

hold()

```
template<typename T>
void Lift< T >::hold () [inline]
```

Target the class's setpoint. Calculate the PID output and set the lift motors accordingly.

home()

```
template<typename T>
void Lift< T >::home () [inline]
```

A blocking function that automatically homes the lift based on a sensor or hard stop, and sets the position to 0. A watchdog times out after 3 seconds, to avoid damage.

set_async()

Enables or disables the background task. Note that running the control functions, or set_position functions will immediately re-enable the task for autonomous use.

Parameters

val Whether or not the background thread should run the lift

set_position()

Enable the background task, and send the lift to a position, specified by the setpoint map from the constructor.

Parameters

```
pos A lift position enum type
```

Returns

True if the pid has reached the setpoint

set_sensor_function()

Creates a custom hook for any other type of sensor to be used on the lift. Example: /code{.cpp} my_lift.set_ consor_function([](){return my_sensor.position();}); /endcode

Parameters

set_sensor_reset()

Creates a custom hook to reset the sensor used in set_sensor_function(). Example: /code{.cpp} my_lift.set_← sensor_reset(my_sensor.resetPosition); /endcode

set_setpoint()

Manually set a setpoint value for the lift PID to go to.

Parameters

val Lift setpoint, in motor revolutions or sensor units defined by get_sensor. Cannot be outside the softstops.

Returns

True if the pid has reached the setpoint

The documentation for this class was generated from the following file:

• lift.h

5.36 Lift< T >::lift_cfg_t Struct Reference

```
#include <lift.h>
```

5.36.1 Detailed Description

```
template<typename T> struct Lift< T >::lift_cfg_t
```

lift_cfg_t holds the physical parameter specifications of a lify system. includes:

- · maximum speeds for the system
- · softstops to stop the lift from hitting the hard stops too hard

The documentation for this struct was generated from the following file:

• lift.h

5.37 Logger Class Reference

Class to simplify writing to files.

```
#include <logger.h>
```

Public Member Functions

Logger (const std::string &filename)

Create a logger that will save to a file.

• Logger (const Logger &I)=delete

copying not allowed

• Logger & operator= (const Logger &I)=delete

copying not allowed

• void Log (const std::string &s)

Write a string to the log.

void Log (LogLevel level, const std::string &s)

Write a string to the log with a loglevel.

void LogIn (const std::string &s)

Write a string and newline to the log.

• void LogIn (LogLevel level, const std::string &s)

Write a string and a newline to the log with a loglevel.

void Logf (const char *fmt,...)

Write a formatted string to the log.

• void Logf (LogLevel level, const char *fmt,...)

Write a formatted string to the log with a loglevel.

Static Public Attributes

• static constexpr int **MAX_FORMAT_LEN** = 512

maximum size for a string to be before it's written

5.37.1 Detailed Description

Class to simplify writing to files.

5.37.2 Constructor & Destructor Documentation

Logger()

Create a logger that will save to a file.

Parameters

filename	the file to save to

5.37.3 Member Function Documentation

Log() [1/2]

```
void Logger::Log ( {\tt const\ std::string\ \&\ s)}
```

Write a string to the log.

```
s the string to write
```

Log() [2/2]

```
void Logger::Log (
          LogLevel level,
          const std::string & s)
```

Write a string to the log with a loglevel.

Parameters

level	the level to write. DEBUG, NOTICE, WARNING, ERROR, CRITICAL, TIME
s	the string to write

Logf() [1/2]

Write a formatted string to the log.

Parameters

fmt	the format string (like printf)
	the args

Logf() [2/2]

```
void Logger::Logf (
            LogLevel level,
            const char * fmt,
            ...)
```

Write a formatted string to the log with a loglevel.

Parameters

level	the level to write. DEBUG, NOTICE, WARNING, ERROR, CRITICAL, TI				
fmt	the format string (like printf)				
	the args				

LogIn() [1/2]

Write a string and newline to the log.

```
s the string to write
```

LogIn() [2/2]

Write a string and a newline to the log with a loglevel.

Parameters

lev	el the	level to write	DEBUG,	NOTICE,	WARNING,	ERROR,	CRITICAL,	TIME
s	the	string to write	Э					

The documentation for this class was generated from the following files:

- · logger.h
- · logger.cpp

5.38 MotionController::m_profile_cfg_t Struct Reference

```
#include <motion_controller.h>
```

Public Attributes

double max_v

the maximum velocity the robot can drive

· double accel

the most acceleration the robot can do

PID::pid_config_t pid_cfg

configuration parameters for the internal PID controller

FeedForward::ff_config_t ff_cfg

configuration parameters for the internal

5.38.1 Detailed Description

m_profile_config holds all data the motion controller uses to plan paths When motion pofile is given a target to drive to, max_v and accel are used to make the trapezoid profile instructing the controller how to drive pid_cfg, ff_cfg are used to find the motor outputs necessary to execute this path

The documentation for this struct was generated from the following file:

· motion_controller.h

5.39 StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage Class Reference

MaybeMessage a message of Message type or nothing MaybeMessage $m = \{\}$; // empty MaybeMessag

```
#include <state machine.h>
```

Public Member Functions

MaybeMessage ()

Empty message - when theres no message.

MaybeMessage (Message msg)

Create a maybemessage with a message.

• bool has_message ()

check if the message is here

Message message ()

Get the message stored. The return value is invalid unless has_message returned true.

5.39.1 Detailed Description

template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log = false> class StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage

5.39.2 Constructor & Destructor Documentation

MaybeMessage()

Create a maybemessage with a message.

Parameters

msg the message to hold on to

5.39.3 Member Function Documentation

has message()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
bool StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage::has_message ()
[inline]
```

check if the message is here

Returns

true if there is a message

message()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
Message StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage::message ()
[inline]
```

Get the message stored. The return value is invalid unless has message returned true.

Returns

The message if it exists. Undefined otherwise

The documentation for this class was generated from the following file:

· state machine.h

5.40 MecanumDrive Class Reference

```
#include <mecanum_drive.h>
```

Classes

· struct mecanumdrive_config_t

Public Member Functions

- MecanumDrive (vex::motor &left_front, vex::motor &right_front, vex::motor &left_rear, vex::motor &right_rear, vex::rotation *lateral_wheel=NULL, vex::inertial *imu=NULL, mecanumdrive_config_t *config=NULL)
- void drive raw (double direction deg, double magnitude, double rotation)
- void drive (double left_y, double left_x, double right_x, int power=2)
- bool auto_drive (double inches, double direction, double speed, bool gyro_correction=true)
- bool auto_turn (double degrees, double speed, bool ignore_imu=false)

5.40.1 Detailed Description

A class representing the Mecanum drivetrain. Contains 4 motors, a possible IMU (intertial), and a possible undriven perpendicular wheel.

5.40.2 Constructor & Destructor Documentation

MecanumDrive()

```
MecanumDrive::MecanumDrive (
    vex::motor & left_front,
    vex::motor & right_front,
    vex::motor & left_rear,
    vex::motor & right_rear,
    vex::rotation * lateral_wheel = NULL,
    vex::inertial * imu = NULL,
    mecanumdrive_config_t * config = NULL)
```

Create the Mecanum drivetrain object

5.40.3 Member Function Documentation

auto drive()

Drive the robot in a straight line automatically. If the inertial was declared in the constructor, use it to correct while driving. If the lateral wheel was declared in the constructor, use it for more accurate positioning while strafing.

Parameters

inches	How far the robot should drive, in inches	
direction	What direction the robot should travel in, in degrees. 0 is forward, +/-180 is reverse, clockwise is positive.	
speed	The maximum speed the robot should travel, in percent: -1.0->+1.0	
gyro_correction	=true Whether or not to use the gyro to help correct while driving. Will always be false if no gyro was declared in the constructor.	

Drive the robot in a straight line automatically. If the inertial was declared in the constructor, use it to correct while driving. If the lateral wheel was declared in the constructor, use it for more accurate positioning while strafing.

Parameters

inches	How far the robot should drive, in inches	
direction	What direction the robot should travel in, in degrees. 0 is forward, +/-180 is reverse, clockwise is positive.	
speed	The maximum speed the robot should travel, in percent: -1.0->+1.0	
gyro_correction	= true Whether or not to use the gyro to help correct while driving. Will always be false if no gyro was declared in the constructor.	

Returns

Whether or not the maneuver is complete.

auto_turn()

Autonomously turn the robot X degrees over it's center point. Uses a closed loop for control.

Parameters

degrees	How many degrees to rotate the robot. Clockwise postive.	
speed	What percentage to run the motors at: 0.0 -> 1.0	
ignore_imu	=false Whether or not to use the Inertial for determining angle. Will instead use circumference	
	formula + robot's wheelbase + encoders to determine.	

Returns

whether or not the robot has finished the maneuver

Autonomously turn the robot X degrees over it's center point. Uses a closed loop for control.

Parameters

degrees	How many degrees to rotate the robot. Clockwise postive.	
speed	What percentage to run the motors at: 0.0 -> 1.0	
ignore_imu	= false Whether or not to use the Inertial for determining angle. Will instead use circumference	
	formula + robot's wheelbase + encoders to determine.	

Returns

whether or not the robot has finished the maneuver

drive()

Drive the robot with a mecanum-style / arcade drive. Inputs are in percent (-100.0 -> 100.0) straight from the controller. Controls are mixed, so the robot can drive forward / strafe / rotate all at the same time.

Parameters

left_y	left joystick, Y axis (forward / backwards)
left_x	left joystick, X axis (strafe left / right)
right←	right joystick, X axis (rotation left / right)
_X	
power	=2 how much of a "curve" there should be on drive controls; better for low speed maneuvers. Leave
	blank for a default curve of 2 (higher means more fidelity)

Drive the robot with a mecanum-style / arcade drive. Inputs are in percent (-100.0 \rightarrow 100.0) straight from the controller. Controls are mixed, so the robot can drive forward / strafe / rotate all at the same time.

left_y	left joystick, Y axis (forward / backwards)
left_x	left joystick, X axis (strafe left / right)
right←	right joystick, X axis (rotation left / right)
_X	
power	= 2 how much of a "curve" there should be on drive controls; better for low speed maneuvers. Leave
	blank for a default curve of 2 (higher means more fidelity)

drive_raw()

Drive the robot using vectors. This handles all the math required for mecanum control.

Parameters

direction_deg	the direction to drive the robot, in degrees. 0 is forward, 180 is back, clockwise is positive, counterclockwise is negative.	
magnitude	How fast the robot should drive, in percent: 0.0->1.0	
rotation	How fast the robot should rotate, in percent: -1.0->+1.0	

The documentation for this class was generated from the following files:

- · mecanum_drive.h
- · mecanum_drive.cpp

5.41 MecanumDrive::mecanumdrive_config_t Struct Reference

```
#include <mecanum_drive.h>
```

5.41.1 Detailed Description

Configure the Mecanum drive PID tunings and robot configurations


The documentation for this struct was generated from the following file:

· mecanum_drive.h

5.42 MotionController Class Reference

#include <motion_controller.h>

Inheritance diagram for MotionController:



Classes

struct m_profile_cfg_t

Public Member Functions

MotionController (m_profile_cfg_t &config)

Construct a new Motion Controller object.

• void init (double start_pt, double end_pt) override

Initialize the motion profile for a new movement This will also reset the PID and profile timers.

• double update (double sensor_val) override

Update the motion profile with a new sensor value.

- · double get () override
- void set_limits (double lower, double upper) override
- bool is_on_target () override
- motion_t get_motion () const

Static Public Member Functions

• static FeedForward::ff_config_t tune_feedforward (TankDrive &drive, OdometryTank &odometry, double pct=0.6, double duration=2)

5.42.1 Detailed Description

Motion Controller class

This class defines a top-level motion profile, which can act as an intermediate between a subsystem class and the motors themselves

This takes the constants kS, kV, kA, kP, kI, kD, max_v and acceleration and wraps around a feedforward, PID and trapezoid profile. It does so with the following formula:

out = feedfoward.calculate(motion_profile.get(time_s)) + pid.get(motion_profile.get(time_s))

For PID and Feedforward specific formulae, see pid.h, feedforward.h, and trapezoid_profile.h

Author

Ryan McGee

Date

7/13/2022

5.42.2 Constructor & Destructor Documentation

MotionController()

Construct a new Motion Controller object.

Parameters

config	The definition of how the robot is able to move max_v Maximum velocity the movement is capable of
	accel Acceleration / deceleration of the movement pid_cfg Definitions of kP, kl, and kD ff_cfg
	Definitions of kS, kV, and kA

5.42.3 Member Function Documentation

get()

```
double MotionController::get () [override], [virtual]
```

Returns

the last saved result from the feedback controller

Implements Feedback.

get_motion()

```
motion_t MotionController::get_motion () const
```

Returns

The current postion, velocity and acceleration setpoints

init()

Initialize the motion profile for a new movement This will also reset the PID and profile timers.

Parameters

start⇔ _pt	Movement starting position
end_pt	Movement ending posiiton

Implements Feedback.

is_on_target()

```
bool MotionController::is_on_target () [override], [virtual]
```

Returns

Whether or not the movement has finished, and the PID confirms it is on target

Implements Feedback.

set_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied. if limits are applied, the controller will not target any value below lower or above upper

Parameters

lower	upper limit
upper	lower limiet

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

Parameters

lower	Upper limit
upper	Lower limit

Implements Feedback.

tune feedforward()

This method attempts to characterize the robot's drivetrain and automatically tune the feedforward. It does this by first calculating the kS (voltage to overcome static friction) by slowly increasing the voltage until it moves.

Next is kV (voltage to sustain a certain velocity), where the robot will record it's steady-state velocity at 'pct' speed.

Finally, kA (voltage needed to accelerate by a certain rate), where the robot will record the entire movement's velocity and acceleration, record a plot of [X=(pct-kV*V-kS), Y=(Acceleration)] along the movement, and since kA*Accel = pct-kV*V-kS, the reciprocal of the linear regression is the kA value.

drive	The tankdrive to operate on	
odometry	The robot's odometry subsystem	
pct	Maximum velocity in percent (0->1.0)	
duration	Amount of time the robot should be moving for the test	

Returns

A tuned feedforward object

update()

Update the motion profile with a new sensor value.

Parameters

sensor_val	Value from the sensor	
------------	-----------------------	--

Returns

the motor input generated from the motion profile

Implements Feedback.


The documentation for this class was generated from the following files:

- · motion_controller.h
- motion_controller.cpp

5.43 VDP::MotorDataRecord Class Reference

```
#include <builtins.hpp>
```

Inheritance diagram for VDP::MotorDataRecord:



Public Member Functions

- MotorDataRecord (std::string name, vex::motor &mot)
- · void fetch () override

Public Member Functions inherited from VDP::Record

- Record (std::string name)
- Record (std::string name, const std::vector< Part * > &parts)
- Record (std::string name, std::vector< PartPtr > parts)
- Record (std::string name, PacketReader &reader)
- void setFields (std::vector< PartPtr > fields)
- · void fetch () override
- void read_data_from_message (PacketReader &reader) override

Public Member Functions inherited from VDP::Part

- · Part (std::string name)
- std::string pretty_print () const
- std::string pretty_print_data () const

Additional Inherited Members

Protected Member Functions inherited from VDP::Record

- void write_schema (PacketWriter &sofar) const override
- void write_message (PacketWriter &sofar) const override

5.43.1 Detailed Description

Defines a record that holds motor values

5.43.2 Constructor & Destructor Documentation

MotorDataRecord()

Creates a record that contains a Float of the motor position Float of the motor velocity Float of the motor tempurature Float of the motor voltage Float of the motor current

Parameters

name	the name of the record to create
mot	the motor to get data from

5.43.3 Member Function Documentation

fetch()

```
void VDP::MotorDataRecord::fetch () [override], [virtual]
sets the data that the Motor Parts hold
```

Implements VDP::Part.

The documentation for this class was generated from the following files:

- · builtins.hpp
- · builtins.cpp

5.44 MovingAverage Class Reference

```
#include <moving_average.h>
```

Inheritance diagram for MovingAverage:



Public Member Functions

- MovingAverage (int buffer_size)
- MovingAverage (int buffer_size, double starting_value)
- void add_entry (double n) override
- double get_value () const override
- int get size () const

5.44.1 Detailed Description

MovingAverage

A moving average is a way of smoothing out noisy data. For many sensor readings, the noise is roughly symmetric around the actual value. This means that if you collect enough samples those that are too high are cancelled out by the samples that are too low leaving the real value.

The MovingAverage class provides a simple interface to do this smoothing from our noisy sensor values.

WARNING: because we need a lot of samples to get the actual value, the value given by the MovingAverage will 'lag' behind the actual value that the sensor is reading. Using a MovingAverage is thus a tradeoff between accuracy and lag time (more samples) vs. less accuracy and faster updating (less samples).

5.44.2 Constructor & Destructor Documentation

MovingAverage() [1/2]

Create a moving average calculator with 0 as the default value

buffer size	The size of the buffer. The number of samples that constitute a valid reading

MovingAverage() [2/2]

```
MovingAverage::MovingAverage (
          int buffer_size,
          double starting_value)
```

Create a moving average calculator with a specified default value

Parameters

buffer_size	The size of the buffer. The number of samples that constitute a valid reading
starting_value	The value that the average will be before any data is added

5.44.3 Member Function Documentation

add_entry()

Add a reading to the buffer Before: [1 1 2 2 3 3] => 2 $^{\wedge}$ After: [2 1 2 2 3 3] => 2.16 $^{\wedge}$

Parameters

n the sample that will be added to the moving average.

Implements Filter.

get_size()

```
int MovingAverage::get_size () const
```

How many samples the average is made from

Returns

the number of samples used to calculate this average

get_value()

```
double MovingAverage::get_value () const [override], [virtual]
```

Returns the average based off of all the samples collected so far

Returns

the calculated average. sum(samples)/numsamples

How many samples the average is made from

Returns

the number of samples used to calculate this average

Implements Filter.


The documentation for this class was generated from the following files:

- · moving_average.h
- · moving_average.cpp

5.45 VDP::Number < NumT, schemaType > Class Template Reference

```
#include <types.hpp>
```

Inheritance diagram for VDP::Number < NumT, schemaType >:



Public Types

• using FetchFunc = std::function<NumberType()>

Public Member Functions

- Number (std::string field_name, FetchFunc fetcher=[]() { return(NumberType) 0;})
- · void fetch () override
- void setValue (NumberType val)
- NumberType getValue ()
- void pprint (std::stringstream &ss, size_t indent) const override
- void pprint_data (std::stringstream &ss, size_t indent) const override
- · void read_data_from_message (PacketReader &reader) override

Public Member Functions inherited from VDP::Part

- Part (std::string name)
- std::string pretty_print () const
- std::string pretty print data () const

Protected Member Functions

- · void write schema (PacketWriter &sofar) const override
- void write_message (PacketWriter &sofar) const override

5.45.1 Detailed Description

```
template<typename NumT, Type schemaType> class VDP::Number< NumT, schemaType >
```

A number conveyed as a part

5.45.2 Member Typedef Documentation

FetchFunc

```
template<typename NumT, Type schemaType>
using VDP::Number< NumT, schemaType >::FetchFunc = std::function<NumberType()>
```

Function to run when fetching this number

5.45.3 Constructor & Destructor Documentation

Number()

creates a number with a name and fetcher

Parameters

field	name for the number part
fetcher	the function to run when fetching this number

5.45.4 Member Function Documentation

fetch()

```
template<typename NumT, Type schemaType>
void VDP::Number< NumT, schemaType >::fetch () [inline], [override], [virtual]
```

sets the value of the number stored to the value returned by its fetcher

Implements VDP::Part.

getValue()

```
template<typename NumT, Type schemaType>
NumberType VDP::Number< NumT, schemaType >::getValue () [inline]
```

Returns

the currently stored number value

pprint()

prints the Number with the format "[indent]name: schema_string"

Parameters

ss	the stream of strings to print to
indent	the amount of indents to use

Implements VDP::Part.

pprint_data()

prints the data the number holds with the format "[indent]name: value"

Parameters

ss	the stream of strings to print to
indent	the amount of indents to use

Implements VDP::Part.

read_data_from_message()

sets the value of the number stored to the value read by a PacketReader

reader the packet reader to get the number from

Implements VDP::Part.

setValue()

sets the value of the number stored

Parameters

val the value to store

write_message()

writes the number's data to a packet

Parameters

sofar the packet writer to write with

Implements VDP::Part.

write schema()

writes the number's schematic to a packet

Parameters

sofar the packet writer to write with

Implements VDP::Part.


The documentation for this class was generated from the following file:

· types.hpp

5.46 Odometry3Wheel Class Reference

#include <odometry_3wheel.h>

Inheritance diagram for Odometry3Wheel:



Classes

struct odometry3wheel_cfg_t

Public Member Functions

- Odometry3Wheel (CustomEncoder &lside_fwd, CustomEncoder &rside_fwd, CustomEncoder &off_axis, odometry3wheel_cfg_t &cfg, bool is_async=true)
- Pose2d update () override
- void tune (vex::controller &con, TankDrive &drive)

Public Member Functions inherited from OdometryBase

- OdometryBase (bool is_async)
- virtual Pose2d get_position (void)
- virtual void set_position (const Pose2d &newpos=zero_pos)
- void end async ()
- virtual double get_speed ()
- virtual double get_accel ()
- double get_angular_speed_deg ()
- double get_angular_accel_deg ()

Additional Inherited Members

Static Public Member Functions inherited from OdometryBase

- static int background_task (void *ptr)
- static double smallest_angle (double start_deg, double end_deg)

Public Attributes inherited from OdometryBase

• bool end_task = false

end_task is true if we instruct the odometry thread to shut down

- vex::task * handle
- vex::mutex mut
- · Pose2d current pos
- · double speed
- double accel
- double ang_speed_deg
- double ang_accel_deg

5.46.1 Detailed Description

Odometry3Wheel

This class handles the code for a standard 3-pod odometry setup, where there are 3 "pods" made up of undriven (dead) wheels connected to encoders in the following configuration:

```
+Y ------ ^{\wedge} | | | | | | | | | 0 | | | | | | | === | | ------ | +--------- > + X
```

Where O is the center of rotation. The robot will monitor the changes in rotation of these wheels and calculate the robot's X, Y and rotation on the field.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

Author

Ryan McGee

Date

Oct 31 2022

5.46.2 Constructor & Destructor Documentation

Odometry3Wheel()

Construct a new Odometry 3 Wheel object

Parameters

lside_fwd	left-side encoder reference
rside_fwd	right-side encoder reference
off_axis	off-axis (perpendicular) encoder reference
cfg	robot odometry configuration
is_async	true to constantly run in the background

5.46.3 Member Function Documentation

tune()

A guided tuning process to automatically find tuning parameters. This method is blocking, and returns when tuning has finished. Follow the instructions on the controller to complete the tuning process

con	Controller reference, for screen and button control
drive	Drivetrain reference for robot control

A guided tuning process to automatically find tuning parameters. This method is blocking, and returns when tuning has finished. Follow the instructions on the controller to complete the tuning process

It is assumed the gear ratio and encoder PPR have been set correctly

update()

```
Pose2d Odometry3Wheel::update () [override], [virtual]
```

Update the current position of the robot once, using the current state of the encoders and the previous known location

Returns

the robot's updated position

Implements OdometryBase.

The documentation for this class was generated from the following files:

- · odometry_3wheel.h
- odometry_3wheel.cpp

5.47 Odometry3Wheel::odometry3wheel cfg t Struct Reference

```
#include <odometry_3wheel.h>
```

Public Attributes

- double wheelbase_dist
- · double off axis center dist
- double wheel_diam

5.47.1 Detailed Description

odometry3wheel_cfg_t holds all the specifications for how to calculate position with 3 encoders See the core wiki for what exactly each of these parameters measures

5.47.2 Member Data Documentation

off_axis_center_dist

```
double Odometry3Wheel::odometry3wheel_cfg_t::off_axis_center_dist
```

distance from the center of the robot to the center off axis wheel

wheel_diam

```
double Odometry3Wheel::odometry3wheel_cfg_t::wheel_diam
```

the diameter of the tracking wheel

wheelbase_dist

```
double Odometry3Wheel::odometry3wheel_cfg_t::wheelbase_dist
```

distance from the center of the left wheel to the center of the right wheel


The documentation for this struct was generated from the following file:

· odometry_3wheel.h

5.48 OdometryBase Class Reference

```
#include <odometry_base.h>
```

Inheritance diagram for OdometryBase:



Public Member Functions

- OdometryBase (bool is_async)
- virtual Pose2d get_position (void)
- virtual void set_position (const Pose2d &newpos=zero_pos)
- virtual Pose2d update ()=0
- void end async ()
- virtual double get_speed ()
- virtual double get_accel ()
- double get_angular_speed_deg ()
- double get_angular_accel_deg ()

Static Public Member Functions

- static int background_task (void *ptr)
- static double smallest_angle (double start_deg, double end_deg)

Public Attributes

• bool end_task = false

end_task is true if we instruct the odometry thread to shut down

- vex::task * handle
- vex::mutex mut
- Pose2d current pos
- · double speed
- double accel
- double ang_speed_deg
- double ang_accel_deg

5.48.1 Detailed Description

OdometryBase

This base class contains all the shared code between different implementations of odometry. It handles the asynchronous management, position input/output and basic math functions, and holds positional types specific to field orientation.

All future odometry implementations should extend this file and redefine update() function.

Author

Ryan McGee

Date

Aug 11 2021

5.48.2 Constructor & Destructor Documentation

OdometryBase()

Construct a new Odometry Base object

Parameters

is_async True to run constantly in the background, false to call update() manually

5.48.3 Member Function Documentation

background_task()

Function that runs in the background task. This function pointer is passed to the vex::task constructor.

ptr | Pointer to OdometryBase object

Returns

Required integer return code. Unused.

end_async()

```
void OdometryBase::end_async ()
```

End the background task. Cannot be restarted. If the user wants to end the thread but keep the data up to date, they must run the update() function manually from then on.

get_accel()

```
double OdometryBase::get_accel () [virtual]
```

Get the current acceleration

Returns

the acceleration rate of the robot (inch/s^2)

get_angular_accel_deg()

```
double OdometryBase::get_angular_accel_deg ()
```

Get the current angular acceleration in degrees

Returns

the angular acceleration at which we are turning (deg/s^2)

get_angular_speed_deg()

```
double OdometryBase::get_angular_speed_deg ()
```

Get the current angular speed in degrees

Returns

the angular velocity at which we are turning (deg/s)

get_position()

Gets the current position and rotation

Returns

the position that the odometry believes the robot is at

Gets the current position and rotation

Reimplemented in OdometrySerial.

get_speed()

```
double OdometryBase::get_speed () [virtual]
```

Get the current speed

Returns

the speed at which the robot is moving and grooving (inch/s)

set_position()

Sets the current position of the robot

Parameters

newpos	the new position that the odometry will believe it is at
--------	--

Sets the current position of the robot

Reimplemented in OdometrySerial, and OdometryTank.

smallest_angle()

Get the smallest difference in angle between a start heading and end heading. Returns the difference between -180 degrees and +180 degrees, representing the robot turning left or right, respectively.

start_deg	intitial angle (degrees)
end_deg	final angle (degrees)

Returns

the smallest angle from the initial to the final angle. This takes into account the wrapping of rotations around 360 degrees

Get the smallest difference in angle between a start heading and end heading. Returns the difference between -180 degrees and +180 degrees, representing the robot turning left or right, respectively.

update()

```
virtual Pose2d OdometryBase::update () [pure virtual]
```

Update the current position on the field based on the sensors

Returns

the location that the robot is at after the odometry does its calculations

Implemented in Odometry3Wheel, OdometrySerial, and OdometryTank.

5.48.4 Member Data Documentation

accel

```
double OdometryBase::accel
```

the rate at which we are accelerating (inch/s^2)

ang_accel_deg

```
double OdometryBase::ang_accel_deg
```

the rate at which we are accelerating our turn (deg/s^2)

ang_speed_deg

```
double OdometryBase::ang_speed_deg
```

the speed at which we are turning (deg/s)

current_pos

Pose2d OdometryBase::current_pos

Current position of the robot in terms of x,y,rotation

handle

```
vex::task* OdometryBase::handle
```

handle to the vex task that is running the odometry code

mut

vex::mutex OdometryBase::mut

Mutex to control multithreading

speed

double OdometryBase::speed

the speed at which we are travelling (inch/s)


The documentation for this class was generated from the following files:

- · odometry_base.h
- odometry_base.cpp

5.49 VDP::OdometryControlRecord Class Reference

```
#include <builtins.hpp>
```

Inheritance diagram for VDP::OdometryControlRecord:



Public Member Functions

- OdometryControlRecord (std::string name, OdometryBase &odom)
- void response () override

Public Member Functions inherited from VDP::Record

- Record (std::string name)
- Record (std::string name, const std::vector < Part * > &parts)
- Record (std::string name, std::vector< PartPtr > parts)
- Record (std::string name, PacketReader &reader)
- void setFields (std::vector< PartPtr > fields)
- · void fetch () override
- void read_data_from_message (PacketReader &reader) override

Public Member Functions inherited from VDP::Part

- Part (std::string name)
- std::string pretty print () const
- std::string pretty_print_data () const

Additional Inherited Members

Protected Member Functions inherited from VDP::Record

- void write schema (PacketWriter &sofar) const override
- void write_message (PacketWriter &sofar) const override

5.49.1 Detailed Description

Defines a record sets odometry values from the board

5.49.2 Constructor & Destructor Documentation

OdometryControlRecord()

Creates a record for taking odometry data from the debug board

Parameters

name	the name of the record to create
odom	the odometry to get data from

5.49.3 Member Function Documentation

response()

```
void VDP::OdometryControlRecord::response () [override], [virtual]
```

sets the odom position to the values from the board

sets the odometry position to the values from the debug board

Reimplemented from VDP::Part.


The documentation for this class was generated from the following files:

- · builtins.hpp
- · builtins.cpp

5.50 VDP::OdometryDataRecord Class Reference

```
#include <builtins.hpp>
```

Inheritance diagram for VDP::OdometryDataRecord:



Public Member Functions

- OdometryDataRecord (std::string name, OdometryBase &odom)
- · void fetch () override

Public Member Functions inherited from VDP::Record

- Record (std::string name)
- Record (std::string name, const std::vector < Part * > &parts)
- Record (std::string name, std::vector< PartPtr > parts)
- Record (std::string name, PacketReader &reader)
- void setFields (std::vector< PartPtr > fields)
- void fetch () override
- void read_data_from_message (PacketReader &reader) override

Public Member Functions inherited from VDP::Part

- Part (std::string name)
- std::string pretty_print () const
- std::string pretty_print_data () const

Additional Inherited Members

Protected Member Functions inherited from VDP::Record

- void write_schema (PacketWriter &sofar) const override
- void write_message (PacketWriter &sofar) const override

5.50.1 Detailed Description

Defines a record that holds odometry values to be sent to the board

5.50.2 Constructor & Destructor Documentation

OdometryDataRecord()

Creates a record that contains a Float of the odometry X postion Float of the odometry Y postion Float of the odometry Rotation

Parameters

name	the name of the record to create
odom	the odometry to get data from

5.50.3 Member Function Documentation

fetch()

```
void VDP::OdometryDataRecord::fetch () [override], [virtual]
```

sets the data that the Odometry Parts hold

Implements VDP::Part.

The documentation for this class was generated from the following files:


- builtins.hpp
- builtins.cpp

5.51 screen::OdometryPage Class Reference

a page that shows odometry position and rotation and a map (if an sd card with the file is on)

```
#include <screen.h>
```

Inheritance diagram for screen::OdometryPage:



Public Member Functions

- OdometryPage (OdometryBase &odom, double robot_width, double robot_height, bool do_trail)
 Create an odometry trail. Make sure odometry is initilized before now.
- void update (bool was_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

5.51.1 Detailed Description

a page that shows odometry position and rotation and a map (if an sd card with the file is on)

5.51.2 Constructor & Destructor Documentation

OdometryPage()

```
screen::OdometryPage::OdometryPage (
    OdometryBase & odom,
    double robot_width,
    double robot_height,
    bool do_trail)
```

Create an odometry trail. Make sure odometry is initilized before now.

Parameters

odom	the odometry system to monitor
robot_width	the width (side to side) of the robot in inches. Used for visualization
robot_height	the robot_height (front to back) of the robot in inches. Used for visualization
do_trail	whether or not to calculate and draw the trail. Drawing and storing takes a very <i>slight</i> extra amount of processing power

5.51.3 Member Function Documentation

draw()

See also

Page::draw

Reimplemented from screen::Page.

update()

```
void screen::OdometryPage::update (
          bool was_pressed,
          int x,
          int y) [override], [virtual]
```

See also

Page::update

Reimplemented from screen::Page.


The documentation for this class was generated from the following files:

- screen.h
- screen.cpp

5.52 OdometrySerial Class Reference

```
#include <odometry_serial.h>
```

Inheritance diagram for OdometrySerial:



Public Member Functions

- OdometrySerial (bool is_async, bool calc_vel_acc_on_brain, Pose2d initial_pose, Pose2d sensor_offset, int32 t port, int32 t baudrate)
- void send_config (const Pose2d &initial_pose, const Pose2d &sensor_offset, const bool &calc_vel_acc_on
 — brain)
- Pose2d update () override
- void set_position (const Pose2d &new_pose) override
- int receive_cobs_packet (uint32_t port, uint8_t *buffer, size_t buffer_size)
- Pose2d get_position (void) override
- Pose2d get pose2d (void)
- size t cobs decode (const uint8 t *buffer, size t length, void *data)
- size t cobs encode (const void *data, size t length, uint8 t *buffer)

Public Member Functions inherited from OdometryBase

- OdometryBase (bool is_async)
- void end_async ()
- double get_angular_speed_deg ()
- double get angular accel deg ()

Additional Inherited Members

Static Public Member Functions inherited from OdometryBase

- static int background_task (void *ptr)
- static double smallest angle (double start deg, double end deg)

Public Attributes inherited from OdometryBase

bool end_task = false

end_task is true if we instruct the odometry thread to shut down

- vex::task * handle
- vex::mutex mut
- · Pose2d current pos
- · double speed
- double accel
- double ang_speed_deg
- double ang_accel_deg

5.52.1 Detailed Description

OdometrySerial

This class handles the code for an odometry setup where calculations are done on an external coprocessor. Data is sent to the brain via smart port, using a generic serial (UART) connection.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

https://rit.enterprise.slack.com/files/U04112Y5RB6/F080M01KPA5/predictperpindiculars2.4pdf 2024-2025 Notebook: Entries/Software Entries/Localization/N-Pod Odometry

Author

Jack Cammarata

Date

Jan 16 2025

5.52.2 Constructor & Destructor Documentation

OdometrySerial()

```
OdometrySerial::OdometrySerial (
    bool is_async,
    bool calc_vel_acc_on_brain,
    Pose2d initial_pose,
    Pose2d sensor_offset,
    int32_t port,
    int32_t baudrate)
```

Construct a new Odometry Serial Object

OdometrySerial

This class handles the code for an odometry setup where calculations are done on an external coprocessor. Data is sent to the brain via smart port, using a generic serial (UART) connection.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

https://rit.enterprise.slack.com/files/U04112Y5RB6/F080M01KPA5/predictperpindiculars2.epdf 2024-2025 Notebook: Entries/Software Entries/Localization/N-Pod Odometry

Author

Jack Cammarata

Date

Jan 16 2025 Construct a new Odometry Serial Object

5.52.3 Member Function Documentation

cobs_decode()

COBS decode data from buffer

Parameters

buffer	Pointer to encoded input bytes
length	Number of bytes to decode
data	Pointer to decoded output data

Returns

Number of bytes successfully decoded

Note

Stops decoding if delimiter byte is found

cobs_encode()

COBS encode data to buffer

Parameters

data	Pointer to input data to encode	
length	Number of bytes to encode	
buffer Pointer to encoded output bu		

Returns

Encoded buffer length in bytes

Note

Does not output delimiter byte

get_pose2d()

Gets the current position and rotation

Returns

the position that the odometry believes the robot is at

get_position()

Gets the current position and rotation

Returns

the position that the odometry believes the robot is at

Reimplemented from OdometryBase.

receive_cobs_packet()

Attempts to recieve an entire packet encoded with COBS, stops at delimiter or there's a buffer overflow

port	the port number the serial is plugged into, counts from 0 instead of 1	
buffer	pointer to a uint8_t[] where we put the data	
buffer_size	length in bytes of the buffer	

Returns

0 success

send_config()

Send

set_position()

Resets the position and rotational data to the input.

Resets the position and rotational data to the input.

Parameters

new_pose	the pose to set the odometry to

Reimplemented from OdometryBase.

update()

```
Pose2d OdometrySerial::update () [override], [virtual]
```

Update the current position of the robot once by reading a single packet from the serial port

Returns

the robot's updated position

Update the current position of the robot once by reading a single packet from the serial port, then updating all over values, velocity, accel

Returns

the robot's updated position

Implements OdometryBase.


The documentation for this class was generated from the following files:

- odometry_serial.h
- odometry_serial.cpp

5.53 OdometryTank Class Reference

#include <odometry_tank.h>

Inheritance diagram for OdometryTank:



Public Member Functions

- OdometryTank (CustomEncoder &left_custom_enc, CustomEncoder &right_custom_enc, robot_specs_t &config, vex::inertial *imu=NULL, bool is_async=true)
- Pose2d update () override
- void set_position (const Pose2d &newpos=zero_pos) override

Public Member Functions inherited from OdometryBase

- OdometryBase (bool is async)
- virtual Pose2d get_position (void)
- void end_async ()
- virtual double get_speed ()
- virtual double get_accel ()
- double get_angular_speed_deg ()
- double get_angular_accel_deg ()

Additional Inherited Members

Static Public Member Functions inherited from OdometryBase

- static int background_task (void *ptr)
- static double smallest_angle (double start_deg, double end_deg)

Public Attributes inherited from OdometryBase

• bool end_task = false

end_task is true if we instruct the odometry thread to shut down

- vex::task * handle
- vex::mutex mut
- · Pose2d current pos
- · double speed
- double accel
- · double ang speed deg
- double ang_accel_deg

5.53.1 Detailed Description

OdometryTank defines an odometry system for a tank drivetrain This requires encoders in the same orientation as the drive wheels Odometry is a "start and forget" subsystem, which means once it's created and configured, it will constantly run in the background and track the robot's X, Y and rotation coordinates.

5.53.2 Constructor & Destructor Documentation

OdometryTank() [1/3]

```
OdometryTank::OdometryTank (
    vex::motor_group & left_side,
    vex::motor_group & right_side,
    robot_specs_t & config,
    vex::inertial * imu = NULL,
    bool is_async = true)
```

Initialize the Odometry module, calculating position from the drive motors.

Parameters

left_side	The left motors
right_side	The right motors
config	the specifications that supply the odometry with descriptions of the robot. See robot_specs_t for what is contained
imu	The robot's inertial sensor. If not included, rotation is calculated from the encoders.
is_async	If true, position will be updated in the background continuously. If false, the programmer will have to manually call update().

OdometryTank() [2/3]

Initialize the Odometry module, calculating position from the drive motors.

Parameters

left_custom_enc	The left custom encoder
right_custom_enc	The right custom encoder
config	the specifications that supply the odometry with descriptions of the robot. See robot_specs_t for what is contained
imu	The robot's inertial sensor. If not included, rotation is calculated from the encoders.
is_async	If true, position will be updated in the background continuously. If false, the programmer will have to manually call update().

OdometryTank() [3/3]

```
OdometryTank::OdometryTank (
    vex::encoder & left_vex_enc,
    vex::encoder & right_vex_enc,
    robot_specs_t & config,
    vex::inertial * imu = NULL,
    bool is_async = true)
```

Initialize the Odometry module, calculating position from the drive motors.

Parameters

left_vex_enc	The left vex encoder
right_vex_enc	The right vex encoder
config	the specifications that supply the odometry with descriptions of the robot. See robot_specs_t for what is contained
imu	The robot's inertial sensor. If not included, rotation is calculated from the encoders.
is_async	If true, position will be updated in the background continuously. If false, the programmer will have to manually call update().

5.53.3 Member Function Documentation

set_position()

set_position tells the odometry to place itself at a position

Parameters

newpos	the position the odometry will take
newpos	the position the odometry will take

Resets the position and rotational data to the input.

Reimplemented from OdometryBase.

update()

```
Pose2d OdometryTank::update () [override], [virtual]
```

Update the current position on the field based on the sensors

Returns

the position that odometry has calculated itself to be at

Update, store and return the current position of the robot. Only use if not initializing with a separate thread.

Implements OdometryBase.

The documentation for this class was generated from the following files:

- odometry_tank.h
- odometry_tank.cpp

5.54 OdomSetPosition Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- OdomSetPosition (OdometryBase &odom, const Pose2d &newpos=OdometryBase::zero pos)
- · bool run () override

5.54.1 Detailed Description

AutoCommand wrapper class for the set_position function in the Odometry class

5.54.2 Constructor & Destructor Documentation

OdomSetPosition()

```
OdomSetPosition::OdomSetPosition (
          OdometryBase & odom,
          const Pose2d & newpos = OdometryBase::zero_pos)
```

constructs a new OdomSetPosition command

Parameters

odom	the odometry system we are setting
newpos	the position we are telling the odometry to take. defaults to $(0, 0)$, angle = 90

Construct an Odometry set pos

Parameters

odom	the odometry system we are setting	
newpos	the now position to set the odometry to	

5.54.3 Member Function Documentation

run()

```
bool OdomSetPosition::run () [override]
```

Run set_position Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- drive_commands.h
- drive_commands.cpp

5.55 VDP::PacketHeader Struct Reference

```
#include  protocol.hpp>
```

5.55.1 Detailed Description

struct to define the header of a packet, defines wheether a packet is Broadcoast or data and whether a packet is send or recieve

The documentation for this struct was generated from the following file:

· protocol.hpp

5.56 VDP::PacketWriter Class Reference

```
#include otocol.hpp>
```

Public Member Functions

- PacketWriter (Packet &scratch_space)
- void clear ()
- size_t size ()
- void write_byte (uint8_t b)
- void write_type (Type t)
- void write_string (const std::string &str)
- void write_channel_acknowledge (const Channel &chan)
- void write_channel_broadcast (const Channel &chan)
- void write_request ()
- void write_response (std::deque< Channel > &channels)
- void write_data_message (const Channel &part)
- const Packet & get_packet () const
- template<typename Number>
 void write_number (const Number &num)

5.56.1 Detailed Description

Defines a PacketWriter, it writes packets

5.56.2 Constructor & Destructor Documentation

PacketWriter()

creates a packet writer

scratch_space	the packet for the writer to write to	
---------------	---------------------------------------	--

5.56.3 Member Function Documentation

clear()

```
void VDP::PacketWriter::clear ()
```

clears the packet the writer is writing to

get_packet()

```
const Packet & VDP::PacketWriter::get_packet () const
```

Returns

the packet the writer is writing to

size()

```
size_t VDP::PacketWriter::size ()
```

Returns

the size of the packet

write_byte()

writes a byte to the end of the packet

Parameters

```
b the byte to write
```

write_channel_acknowledge()

writes a broadcast acknowledgement of a channel to the packet

chan the channel to write the acknowledgement for

write_channel_broadcast()

writes a broadcast of a channel schematic to the packet

Parameters

chan the channel to write the schematic from

write_data_message()

writes a broadcast of a channel schematic to the packet

Parameters

chan the channel to request

writes the data from a channel to the packet

Parameters

chan the Channel to write the data from

write_number()

writes a number to the end of the packet

write_request()

```
void VDP::PacketWriter::write_request ()
```

writes a request for a channel schematic to the packets

chan	the Channel to write the data from
------	------------------------------------

writes a request for a channel schematic to the packet

Parameters

chan the channel to reque	st
---------------------------	----

write_response()

writes a response packet to the packets

Parameters

writes a receive packet to the packets

Parameters

```
chan the channel to request
```

write_string()

writes a string to the packet

Parameters

```
str the string to write to the packet
```

write_type()

```
void VDP::PacketWriter::write_type ( {\tt Type}\ t)
```

writes a VDP type to the packet in the form of a byte

t the VDP type to write to the packet

The documentation for this class was generated from the following files:


- · protocol.hpp
- · protocol.cpp

5.57 screen::Page Class Reference

Page describes one part of the screen slideshow.

```
#include <screen.h>
```

Inheritance diagram for screen::Page:



Public Member Functions

- virtual void update (bool was_pressed, int x, int y)

 collect data, respond to screen input, do fast things (runs at 50hz even if you're not focused on this Page (only drawn page gets touch updates))
- virtual void draw (vex::brain::lcd &screen, bool first_draw, unsigned int frame_number)

 draw stored data to the screen (runs at 10 hz and only runs if this page is in front)

5.57.1 Detailed Description

Page describes one part of the screen slideshow.

5.57.2 Member Function Documentation

draw()

draw stored data to the screen (runs at 10 hz and only runs if this page is in front)

first_draw	true if we just switched to this page
frame_number	frame of drawing we are on (basically an animation tick)

Reimplemented in screen::FunctionPage, screen::OdometryPage, screen::PIDPage, and screen::StatsPage.

update()

collect data, respond to screen input, do fast things (runs at 50hz even if you're not focused on this Page (only drawn page gets touch updates))

Parameters

was_pressed	true if the screen has been pressed
X	x position of screen press (if the screen was pressed)
У	y position of screen press (if the screen was pressed)

Reimplemented in screen::FunctionPage, screen::OdometryPage, screen::PIDPage, and screen::StatsPage.

The documentation for this class was generated from the following file:

· screen.h

5.58 Parallel Class Reference

Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on_timeout on all children continue.

```
#include <auto_command.h>
```

5.58.1 Detailed Description

Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on_timeout on all children continue.


The documentation for this class was generated from the following files:

- · auto_command.h
- · auto_command.cpp

5.59 VDP::Part Class Reference

#include otocol.hpp>

Inheritance diagram for VDP::Part:



Public Member Functions

- Part (std::string name)
- std::string pretty_print () const
- std::string pretty_print_data () const
- virtual void read_data_from_message (PacketReader &reader)=0

Protected Member Functions

- virtual void write_schema (PacketWriter &sofar) const =0
- virtual void write_message (PacketWriter &sofar) const =0
- virtual void pprint (std::stringstream &ss, size_t indent) const =0
- virtual void pprint_data (std::stringstream &ss, size_t indent) const =0

5.59.1 Detailed Description

defines a Part, which has a name and contains data essentially defines data formatted so that it can be sent to the debug board

5.59.2 Constructor & Destructor Documentation

Part()

Creates a Part with a name a part is essentially data formatted so that it can be sent to the debug board

Parameters

ame name for the	e Part
------------------	--------

5.59.3 Member Function Documentation

pprint()

changes a stringstream to a specified format, meant to be overrided

Parameters

ss	the stream of strings to change
indent	the amount of double spaced indents to add to the string

```
Implemented in VDP::Number < NumT, schemaType >, VDP::Number < double, Type::Double >, VDP::Number < double, Type::Double VDP::Number < float, Type::Float >, VDP::Number < int16_t, Type::Int16 >, VDP::Number < int32_t, Type::Int32 >, VDP::Number < int32_t, Type::Int32 >, VDP::Number < int32_t, Type::Int32 >, VDP::Number < int64_t, Type::Int64 >, VDP::Number < int64_t, Type::Int64 >, VDP::Number < int8_t, Type::Int8 >, VDP::Number < int8_t, Type::Uint16 >, VDP::Number < uint16_t, Type::Uint16 >, VDP::Number < uint16_t, Type::Uint16 >, VDP::Number < uint16_t, Type::Uint32 >, VDP::Number < uint64_t, Type::Uint64 >, VDP::Number < uint64_t, Type::Uint64 >, VDP::Number < uint64_t, Type::Uint64 >, VDP::Number < uint64_t, Type::Uint8 >, and VDP::String.
```

pprint_data()

changes a stringstream to the contain the Part's data in a specified format, meant to be overrided

Parameters

ss	the stream of strings to change
indent	the amount of double spaced indents to add to the string

```
Implemented in VDP::Number< NumT, schemaType >, VDP::Number< double, Type::Double >, VDP::Number< double, Type::Int16 >, VDP::Number< int16_t, Type::Int16 >, VDP::Number< int32_t, Type::Int32 >, VDP::Number< int32_t, Type::Int32 >, VDP::Number< int64_t, Type::Int64 >, VDP::Number< int64_t, Type::Int64 >, VDP::Number< int8_t, Type::Int8 >, VDP::Number< int8_t, Type::Uint16 >, VDP::Number< uint16_t, Type::Uint16 >, VDP::Number< uint16_t, Type::Uint16 >, VDP::Number< uint64_t, Type::Uint64 >, VDP::Number< uint64_t, Type::Uint64 >, VDP::Number< uint64_t, Type::Uint64 >, VDP::Number< uint8_t, Type::Uint8 >, and VDP::String.
```

pretty_print()

```
std::string VDP::Part::pretty_print () const
```

Returns

a string of the Part with the format "name: string" a stringstream of the Part with the format "name: string"

pretty print data()

```
std::string VDP::Part::pretty_print_data () const
```

Returns

a string of the Part's data with the format "name: value" a stringstream of the Part's data with the format "name: value"

read_data_from_message()

sets the data the part contains to the data from a packet, meant to be overrided

Parameters

```
reader the PacketReader to read data from
```

```
Implemented in VDP::Number < NumT, schemaType >, VDP::Number < double, Type::Double >, VDP::Number < double, Type::Double >, VDP::Number < double, Type::Double >, VDP::Number < double, Type::Int16 >, VDP::Number < int16_t, Type::Int16 >, VDP::Number < int16_t, Type::Int16 >, VDP::Number < int32_t, Type::Int32 >, VDP::Number < int32_t, Type::Int32 >, VDP::Number < int64_t, Type::Int64 >, VDP::Number < int64_t, Type::Int8 >, VDP::Number < int8_t, Type::Int8 >, VDP::Number < int16_t, Type::Uint16 >, VDP::Number < uint16_t, Type::Uint16 >, VDP::Number < uint64_t, Type::Uint64 >, VDP::Number < uint64_t, Type::Uint64 >, VDP::Number < uint8_t, Type::Uint8 >, VDP::Record, and VDP::String.
```

write_message()

writes the value of the Part to a packet so that it can be sent to the debug board

Parameters

```
sofar the packet writer to write with
```

```
Implemented in VDP::Number< NumT, schemaType >, VDP::Number< double, Type::Double >, VDP::Number< double, Type::Int16 >, VDP::Number< int16_t, Type::Int16 >, VDP::Number< int32_t, Type::Int32 >, VDP::Number< int32_t, Type::Int32 >, VDP::Number< int64_t, Type::Int64 >, VDP::Number< int64_t, Type::Int8 >, VDP::Number< int8_t, Type::Int8 >, VDP::Number< int16_t, Type::Uint16 >, VDP::Number< uint16_t, Type::Uint16 >, VDP::Number< uint16_t, Type::Uint16 >, VDP::Number< uint64_t, Type::Uint64 >, VDP::Number< uint64_t, Type::Uint64 >, VDP::Number< uint64_t, Type::Uint64 >, VDP::Number< uint8_t, Type::Uint8 >, VDP::Number< uint8_t, Type::Uint8 >, VDP::Record, and VDP::String.
```

write_schema()

writes the Part schematic to a packet so that it can be sent to the debug board, meant to be overrided

Parameters

```
sofar the packet writer to write with
```

Implemented in VDP::Number < NumT, schemaType >, VDP::Number < double, Type::Double >, VDP::Number < double, Type::Int16 >, VDP::Number < int16_t, Type::Int16 >, VDP::Number < int16_t, Type::Int16 >, VDP::Number < int32_t, Type::Int32 >, VDP::Number < int64_t, Type::Int64 >, VDP::Number < int64_t, Type::Int8 >, VDP::Number < int8_t, Type::Int8 >, VDP::Number < int8_t, Type::Uint16 >, VDP::Number < uint16_t, Type::Uint16 >, VDP::Number < uint16_t, Type::Uint16 >, VDP::Number < uint16_t, Type::Uint16 >, VDP::Number < uint64_t, Type::Uint64 >, VDP::Number < uint64_t, Type::Uint64 >, VDP::Number < uint64_t, Type::Uint8 >, VDP::Number < uint8_t, Type::Uint8 >, VDP::Number < uint8_t, Type::Uint8 >, VDP::Record, and VDP::String.

The documentation for this class was generated from the following files:

- · protocol.hpp
- · protocol.cpp

5.60 PurePursuit::Path Class Reference

```
#include <pure_pursuit.h>
```

Public Member Functions

- Path (std::vector < Translation2d > points, double radius)
- const std::vector< Translation2d > get_points ()
- double get_radius ()
- bool is_valid ()

5.60.1 Detailed Description

Wrapper for a vector of points, checking if any of the points are too close for pure pursuit

5.60.2 Constructor & Destructor Documentation

Path()

Create a Path

points	the points that make up the path
radius	the lookahead radius for pure pursuit

5.60.3 Member Function Documentation

get_points()

```
const std::vector< Translation2d > PurePursuit::Path::get_points ()
```

Get the points associated with this Path

get_radius()

```
double PurePursuit::Path::get_radius ()
```

Get the radius associated with this Path

is_valid()

```
bool PurePursuit::Path::is_valid ()
```

Get whether this path will behave as expected

The documentation for this class was generated from the following files:

- pure_pursuit.h
- pure_pursuit.cpp

5.61 PID Class Reference

```
#include <pid.h>
```

Inheritance diagram for PID:



Classes

• struct pid_config_t

5.61 PID Class Reference 111

Public Types

• enum ERROR TYPE

Public Member Functions

- PID (pid_config_t &config)
- void init (double start_pt, double set_pt) override
- double update (double sensor_val) override
- double update (double sensor_val, double v_setpt)
- double get_sensor_val () const

gets the sensor value that we were last updated with

- double get () override
- void set_limits (double lower, double upper) override
- bool is_on_target () override
- void reset ()
- double get_error ()
- double get_output ()
- double get_target () const
- void set_target (double target)

Public Attributes

• pid_config_t & config

5.61.1 Detailed Description

PID Class

Defines a standard feedback loop using the constants kP, kI, kD, deadband, and on_target_time. The formula is:

```
out = kP*error + kI*integral(d Error) + kD*(dError/dt)
```

The PID object will determine it is "on target" when the error is within the deadband, for a duration of on_target_time

Author

Ryan McGee

Date

4/3/2020

5.61.2 Member Enumeration Documentation

ERROR_TYPE

```
enum PID::ERROR_TYPE
```

An enum to distinguish between a linear and angular caluclation of PID error.

5.61.3 Constructor & Destructor Documentation

PID()

Create the PID object

config the configuration data for this controller

Create the PID object

5.61.4 Member Function Documentation

get()

```
double PID::get () [override], [virtual]
```

Gets the current PID out value, from when update() was last run

Returns

the Out value of the controller (voltage, RPM, whatever the PID controller is controlling)

Gets the current PID out value, from when update() was last run

Implements Feedback.

get_error()

```
double PID::get_error ()
```

Get the delta between the current sensor data and the target

Returns

the error calculated. how it is calculated depends on error_method specified in pid_config_t

Get the delta between the current sensor data and the target

get_output()

```
double PID::get_output ()
```

Get the output calculated from the P, I, D and Error values

Returns

the output calculated from the pid controller specified in pid_config_t

Get the delta between the current sensor data and the target

5.61 PID Class Reference 113

get_sensor_val()

```
double PID::get_sensor_val () const
```

gets the sensor value that we were last updated with

Returns

sensor_val

get_target()

```
double PID::get_target () const
```

Get the PID's target

Returns

the target the PID controller is trying to achieve

init()

Inherited from Feedback for interoperability. Update the setpoint and reset integral accumulation

start_pt can be safely ignored in this feedback controller

Parameters

start_pt	commpletely ignored for PID. necessary to satisfy Feedback base
set_pt	sets the target of the PID controller
start_vel	completely ignored for PID. necessary to satisfy Feedback base
end_vel	sets the target end velocity of the PID controller

Implements Feedback.

is_on_target()

```
bool PID::is_on_target () [override], [virtual]
```

Checks if the PID controller is on target.

Returns

true if the loop is within [deadband] for [on_target_time] seconds

Returns true if the loop is within [deadband] for [on_target_time] seconds

Implements Feedback.

reset()

```
void PID::reset ()
```

Reset the PID loop by resetting time since 0 and accumulated error.

set limits()

Set the limits on the PID out. The PID out will "clip" itself to be between the limits.

Parameters

lower	the lower limit. the PID controller will never command the output go below lower
upper	the upper limit. the PID controller will never command the output go higher than upper

Set the limits on the PID out. The PID out will "clip" itself to be between the limits.

Implements Feedback.

set_target()

Set the target for the PID loop, where the robot is trying to end up

Parameters

	target	the sensor reading we would like to achieve
١	laryel	the sensor reading we would like to achieve

Set the target for the PID loop, where the robot is trying to end up

update() [1/2]

Update the PID loop by taking the time difference from last update, and running the PID formula with the new sensor data

Parameters

sensor_val the distance, angle, encoder position or whatever it is we are measuring

Returns

the new output. What would be returned by PID::get()

Implements Feedback.

update() [2/2]

Update the PID loop by taking the time difference from last update, and running the PID formula with the new sensor data

Parameters

sensor_val	the distance, angle, encoder position or whatever it is we are measuring
v_setpt	Expected velocity setpoint, to subtract from the D term (for velocity control)

Returns

the new output. What would be returned by PID::get()

5.61.5 Member Data Documentation

config

```
pid_config_t& PID::config
```

configuration struct for this controller. see pid_config_t for information about what this contains

The documentation for this class was generated from the following files:

- pid.h
- · pid.cpp

5.62 PID::pid_config_t Struct Reference

```
#include <pid.h>
```

Public Attributes

• double **p**

proportional coeffecient p * error()

• double i

integral coeffecient i * integral(error)

• double **d**

derivitave coeffecient d * derivative(error)

· double deadband

at what threshold are we close enough to be finished

- double on_target_time
- ERROR_TYPE error_method

5.62.1 Detailed Description

pid_config_t holds the configuration parameters for a pid controller In addition to the constant of proportional, integral and derivative, these parameters include:

- · deadband -
- on_target_time for how long do we have to be at the target to stop As well, pid_config_t holds an error type
 which determines whether errors should be calculated as if the sensor position is a measure of distance or
 an angle

5.62.2 Member Data Documentation

error method

```
ERROR_TYPE PID::pid_config_t::error_method
```

Linear or angular. wheter to do error as a simple subtraction or to wrap

on target time

```
double PID::pid_config_t::on_target_time
```

the time in seconds that we have to be on target for to say we are officially at the target


The documentation for this struct was generated from the following file:

• pid.h

5.63 VDP::PIDControlRecord Class Reference

```
#include <builtins.hpp>
```

Inheritance diagram for VDP::PIDControlRecord:



Public Member Functions

- PIDControlRecord (std::string name, PID &pid)
- void response () override

Public Member Functions inherited from VDP::Record

- Record (std::string name)
- Record (std::string name, const std::vector< Part * > &parts)
- Record (std::string name, std::vector< PartPtr > parts)
- Record (std::string name, PacketReader &reader)
- void setFields (std::vector< PartPtr > fields)
- · void fetch () override
- void read_data_from_message (PacketReader &reader) override

Public Member Functions inherited from VDP::Part

- Part (std::string name)
- std::string pretty print () const
- std::string pretty_print_data () const

Additional Inherited Members

Protected Member Functions inherited from VDP::Record

- void write schema (PacketWriter &sofar) const override
- void write_message (PacketWriter &sofar) const override

5.63.1 Detailed Description

Defines a record for setting pid values from the board

5.63.2 Constructor & Destructor Documentation

PIDControlRecord()

Creates a record for setting pid values from the board

Parameters

name	the name of the record to create
pid	the pid to get data from

5.63.3 Member Function Documentation

response()

```
void VDP::PIDControlRecord::response () [override], [virtual]
```

sets the PID values to the values from the board

Reimplemented from VDP::Part.


The documentation for this class was generated from the following files:

- · builtins.hpp
- · builtins.cpp

5.64 VDP::PIDDataRecord Class Reference

```
#include <builtins.hpp>
```

Inheritance diagram for VDP::PIDDataRecord:



Public Member Functions

- PIDDataRecord (std::string name, PID &pid)
- · void fetch () override

Public Member Functions inherited from VDP::Record

- Record (std::string name)
- Record (std::string name, const std::vector< Part * > &parts)
- Record (std::string name, std::vector< PartPtr > parts)
- Record (std::string name, PacketReader &reader)
- void setFields (std::vector< PartPtr > fields)
- void fetch () override
- void read_data_from_message (PacketReader &reader) override

Public Member Functions inherited from VDP::Part

- Part (std::string name)
- std::string pretty_print () const
- std::string pretty_print_data () const

Additional Inherited Members

Protected Member Functions inherited from VDP::Record

- void write schema (PacketWriter &sofar) const override
- void write_message (PacketWriter &sofar) const override

5.64.1 Detailed Description

Defines a record that holds pid values to be sent to the board

5.64.2 Constructor & Destructor Documentation

PIDDataRecord()

Creates a record that contains a Float of the pid P value Float of the pid I value Float of the pid D value Float of the pid output String of the pid type (linear or angular)

Parameters

name	the name of the record to create
pid	the pid to get data from

5.64.3 Member Function Documentation

fetch()

```
void VDP::PIDDataRecord::fetch () [override], [virtual]
```

sets the data that the PID Parts hold

sets the data that the PID Parts hold to be sent to the board

Implements VDP::Part.

The documentation for this class was generated from the following files:


- · builtins.hpp
- · builtins.cpp

5.65 screen::PIDPage Class Reference

PIDPage provides a way to tune a pid controller on the screen.

```
#include <screen.h>
```

Inheritance diagram for screen::PIDPage:



Public Member Functions

- PIDPage (PID &pid, std::string name, std::function < void(void) > onchange=[]() {})
 Create a PIDPage.
- void update (bool was_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

5.65.1 Detailed Description

PIDPage provides a way to tune a pid controller on the screen.

5.65.2 Constructor & Destructor Documentation

PIDPage()

```
screen::PIDPage::PIDPage (
          PID & pid,
          std::string name,
          std::function< void(void) > onchange = []() {})
```

Create a PIDPage.

Parameters

pid	the pid controller we're changing
name	a name to recognize this pid controller if we've got multiple pid screens
onchange	a function that is called when a tuning parameter is changed. If you need to update stuff on that change register a handler here

5.65.3 Member Function Documentation

draw()

See also

Page::draw

Reimplemented from screen::Page.

update()

```
void screen::PIDPage::update (
          bool was_pressed,
          int x,
          int y) [override], [virtual]
```

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:

- · screen.h
- · screen.cpp

5.66 Pose2d Class Reference

```
#include <pose2d.h>
```

Public Member Functions

- constexpr Pose2d ()
- Pose2d (const Translation2d &translation, const Rotation2d &rotation)
- Pose2d (const double &x, const double &y, const Rotation2d &rotation)
- Pose2d (const double &x, const double &y, const double &radians)
- Pose2d (const Translation2d &translation, const double &radians)
- Pose2d (const Eigen::Vector3d &pose vector)
- · Translation2d translation () const
- · double x () const
- double y () const
- · Rotation2d rotation () const
- void setRotationRad (double rotRad)
- void setRotationDeg (double rotDeg)
- bool operator== (const Pose2d other) const
- Pose2d operator* (const double &scalar) const
- Pose2d operator/ (const double &scalar) const
- Pose2d operator+ (const Transform2d &transform) const
- Transform2d operator- (const Pose2d &other) const
- Pose2d relative_to (const Pose2d &other) const
- Pose2d transform by (const Transform2d &transform) const
- Pose2d exp (const Twist2d &twist) const
- Twist2d log (const Pose2d &end_pose) const

Friends

std::ostream & operator<< (std::ostream &os, const Pose2d &pose)

5.66.1 Detailed Description

Class representing a pose in 2d space with x, y, and rotational components

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

5.66.2 Constructor & Destructor Documentation

Pose2d() [1/6]

```
Pose2d::Pose2d () [inline], [constexpr]
Default Constructor for Pose2d
```

Pose2d() [2/6]

Constructs a pose with given translation and rotation components.

Parameters

translation	translational component.
rotation	rotational component.

Pose2d() [3/6]

Constructs a pose with given translation and rotation components.

Parameters

X	x component.
У	y component.
rotation	rotational component.

Pose2d() [4/6]

```
Pose2d::Pose2d (

const double & x,

const double & y,

const double & radians)
```

Constructs a pose with given translation and rotation components.

X	x component.
У	y component.
radians	rotational component in radians.

Pose2d() [5/6]

Constructs a pose with given translation and rotation components.

Parameters

translation	translational component.
radians	rotational component in radians.

Pose2d() [6/6]

Constructs a pose with given translation and rotation components.

Parameters

pose vector	vector of the form [x, y, theta].
7	

5.66.3 Member Function Documentation

exp()

Applies a twist (pose delta) to a pose by including first order dynamics of heading.

When applying a twist, imagine a constant angular velocity, the translational components must be rotated into the global frame at every point along the twist, simply adding the deltas does not do this, and using euler integration results in some error. This is the analytic solution that that problem.

Can also be thought of more simply as applying a twist as following an arc rather than a straight line.

See this document for more information on the pose exponential and its derivation. https://file. \leftarrow tavsys.net/control/controls-engineering-in-frc.pdf#section.10.2

old_pose	The pose to which the twist will be applied.
twist	The twist, represents a pose delta.

Returns

new pose that has been moved forward according to the twist.

log()

The inverse of the pose exponential.

Determines the twist required to go from this pose to the given end pose. suppose you have Pose2d a, Twist2d twist if a.exp(twist) = b then a.log(b) = twist

Parameters

	end_pose	the end pose to find the mapping to.
--	----------	--------------------------------------

Returns

the twist required to go from this pose to the given end

operator*()

Multiplies this pose by a scalar. Simply multiplies each component.

Parameters

scalar	the scalar value to multiply by.
--------	----------------------------------

operator+()

Adds a transform to this pose. Transforms the pose in the pose's frame.

transform	the change in pose.
-----------	---------------------

operator-()

Subtracts one pose from another to find the transform between them.

Parameters

other the pose to subtract.

operator/()

Divides this pose by a scalar. Simply divides each component.

Parameters

the scalar value to divide by.

operator==()

Compares this to another pose.

Parameters

other	the other pose to compare to.

Returns

true if each of the components are within 1e-9 of each other.

relative_to()

Finds the pose equivalent to this pose relative to another arbitrary pose rather than the origin.

other	the pose representing the new origin.
-------	---------------------------------------

Returns

this pose relative to another pose.

rotation()

```
Rotation2d Pose2d::rotation () const
```

Returns the rotational component.

Returns

the rotational component.

setRotationDeg()

sets the ration value of the rotational component in Degrees

setRotationRad()

sets the ration value of the rotational component in Radians

transform_by()

Adds a transform to this pose. Simply adds each component.

Parameters

transform	the change in pose.

Returns

the pose after being transformed.

translation()

```
Translation2d Pose2d::translation () const
```

Returns the translational component.

Returns

the translational component.

x()

```
double Pose2d::x () const
```

Returns the x value of the translational component.

Returns

the x value of the translational component.

y()

```
double Pose2d::y () const
```

Returns the y value of the translational component.

Returns

the y value of the translational component.

5.66.4 Friends And Related Symbol Documentation

operator<<

Sends a pose to an output stream. Ex. std::cout << pose;

```
prints "Pose2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- · pose2d.h
- · pose2d.cpp

5.67 PurePursuitCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- PurePursuitCommand (TankDrive &drive_sys, Feedback &feedback, PurePursuit::Path path, directionType dir, double max_speed=1, double end_speed=0)
- · bool run () override
- void on_timeout () override

5.67.1 Detailed Description

Autocommand wrapper class for pure pursuit function in the TankDrive class

5.67.2 Constructor & Destructor Documentation

PurePursuitCommand()

Construct a Pure Pursuit AutoCommand

Parameters

path	The list of coordinates to follow, in order
dir	Run the bot forwards or backwards
feedback	The feedback controller determining speed
max_speed	Limit the speed of the robot (for pid / pidff feedbacks)

5.67.3 Member Function Documentation

on_timeout()

```
void PurePursuitCommand::on_timeout () [override]
```

Reset the drive system when it times out

run()

```
bool PurePursuitCommand::run () [override]
```

Direct call to TankDrive::pure_pursuit

The documentation for this class was generated from the following files:

- · drive_commands.h
- · drive commands.cpp

5.68 VDP::Record Class Reference

```
#include <types.hpp>
```

Inheritance diagram for VDP::Record:



Public Member Functions

- Record (std::string name)
- Record (std::string name, const std::vector< Part * > &parts)
- Record (std::string name, std::vector< PartPtr > parts)
- Record (std::string name, PacketReader &reader)
- void setFields (std::vector< PartPtr > fields)
- · void fetch () override
- void read_data_from_message (PacketReader &reader) override

Public Member Functions inherited from VDP::Part

- Part (std::string name)
- std::string pretty_print () const
- std::string pretty_print_data () const

Protected Member Functions

- void write_schema (PacketWriter &sofar) const override
- · void write_message (PacketWriter &sofar) const override

5.68.1 Detailed Description

Defines a Part that contains another Part essentially an array of parts that is formatted so that it can be sent to the debug board

5.68.2 Constructor & Destructor Documentation

Record() [1/4]

Creates a Record with just a name a Record is essentially an array of parts that is formatted so that it can be sent to the debug board

name	the name for the part
------	-----------------------

Record() [2/4]

Creates a Record with a name that contains the Parts inside a vector of Parts a Record is essentially an array of parts that is formatted so that it can be sent to the debug board

Parameters

name	the name for the part
parts	the vector of Parts for the record to hold

Record() [3/4]

Creates a Record with a name that contains the Parts inside a vector of Part Pointers a Record is essentially an array of parts that is formatted so that it can be sent to the debug board

Parameters

name	the name for the part
parts	the vector of Part Pointers for the record to hold

Creates a Record with a name that contains the Parts inside a vector of Part Pointers a Record is essentially an array of parts that is formatted so that it can be sent to the debug board

Parameters

name	the name for the Record
parts	the vector of Part Pointers for the record to hold

Record() [4/4]

Creates a record with a name based off of a packet read by a PacketReader a Record is essentially an array of parts that is formatted so that it can be sent to the debug board

name	
reader	

5.68.3 Member Function Documentation

fetch()

```
void VDP::Record::fetch () [override], [virtual]
```

sets the values of each Part the Record contains

Implements VDP::Part.

Reimplemented in VDP::TimestampedRecord.

read_data_from_message()

writes a message to the packet containing part record

Parameters

sofar	the PacketWriter to write with
-------	--------------------------------

Implements VDP::Part.

setFields()

```
void VDP::Record::setFields (
          std::vector< PartPtr > fs)
```

sets the Record to contain Parts from a part Pointer

Parameters

fs the vector of Part Pointers for the record to hold

write_message()

writes a message to the packet containing part record

sofar the PacketWriter to write with

Implements VDP::Part.

write_schema()

writes the Record as the

Implements VDP::Part.

The documentation for this class was generated from the following files:

- · types.hpp
- · types.cpp

5.69 Rect Struct Reference

```
#include <geometry.h>
```

5.69.1 Detailed Description

Describes a Rectangle with a minimum and maximum point

The documentation for this struct was generated from the following file:

· geometry.h

5.70 VDP::RegistryListener< MutexType > Class Template Reference

```
#include <registry-listener.hpp>
```

Public Member Functions

- RegistryListener (AbstractDevice *device)
- void take_packet (const Packet &pac)

Call this if you are a device who has a packet for the protocol to decode.

• bool submit_response (ChannelID id)

Submits a channel to respond to the board with.

- void install_broadcast_callback (CallbackFn on_broadcastf)
- void install_data_callback (CallbackFn on_dataf)
- bool send_data (ChannelID id, PartPtr data)

5.70.1 Detailed Description

```
template<typename MutexType> class VDP::RegistryListener< MutexType >
```

defines a device registry for sending data or listening to data over a device

5.70.2 Constructor & Destructor Documentation

RegistryListener()

creates a device registry for sending data or listening to data over the device

Parameters

device	the device to send data to
reg_type	the type of registry it is (Listener or Controller)

5.70.3 Member Function Documentation

install_broadcast_callback()

installs a callback to a function that is called when the registry broadcasts the data schematic

Parameters

on_broadcastf the callback to run when the re	egistry broadcasts the schematic
---	----------------------------------

install_data_callback()

installs a callback to a function that is called when the registry broadbasts data

Parameters

```
on_dataf the callback to run when the registry broadcasts data
```

send_data()

sets the data at the channel id to a Part Pointer and sends it to the device

id	The id of the channel to hold the data
data	the Part Pointer for the channel to hold and send to the device

submit response()

Submits a channel to respond to the board with.

Parameters

```
id the channel id to respond with
```

Returns

if the channel was submitted successfully or not

take_packet()

Call this if you are a device who has a packet for the protocol to decode.

Parameters

```
pac the packet to take.
```

The documentation for this class was generated from the following file:

· registry-listener.hpp

5.71 robot_specs_t Struct Reference

```
#include <robot_specs.h>
```

Public Attributes

· double robot_radius

if you were to draw a circle with this radius, the robot would be entirely contained within it

• double odom_wheel_diam

the diameter of the wheels used for

double odom_gear_ratio

the ratio of the odometry wheel to the encoder reading odometry data

double dist_between_wheels

the distance between centers of the central drive wheels

- · double drive_correction_cutoff
- Feedback * drive feedback

the default feedback for autonomous driving

Feedback * turn_feedback

the defualt feedback for autonomous turning

PID::pid_config_t correction_pid

the pid controller to keep the robot driving in as straight a line as possible

5.71.1 Detailed Description

Main robot characterization struct. This will be passed to all the major subsystems that require info about the robot. All distance measurements are in inches.

5.71.2 Member Data Documentation

drive_correction_cutoff

```
double robot_specs_t::drive_correction_cutoff
```

the distance at which to stop trying to turn towards the target. If we are less than this value, we can continue driving forward to minimize our distance but will not try to spin around to point directly at the target

The documentation for this struct was generated from the following file:

· robot_specs.h

5.72 Rotation2d Class Reference

#include <rotation2d.h>

Public Member Functions

- constexpr Rotation2d ()
- Rotation2d (const double &radians)
- Rotation2d (const double &x, const double &y)
- Rotation2d (const Translation2d &translation)
- double radians () const
- · double degrees () const
- double revolutions () const
- double f cos () const
- double f_sin () const
- double f_tan () const
- Eigen::Matrix2d rotation_matrix () const
- double wrapped_radians_180 () const
- double wrapped_degrees_180 () const
- double wrapped_revolutions_180 () const
- double wrapped_radians_360 () const
- double wrapped_degrees_360 () const
- double wrapped_revolutions_360 () const
- Rotation2d operator+ (const Rotation2d &other) const
- Rotation2d operator- (const Rotation2d &other) const
- Rotation2d operator- () const
- Rotation2d operator* (const double &scalar) const
- Rotation2d operator/ (const double &scalar) const
- bool operator== (const Rotation2d &other) const

Friends

std::ostream & operator<< (std::ostream &os, const Rotation2d &rotation)

5.72.1 Detailed Description

Class representing a rotation in 2d space. Stores theta in radians, as well as cos and sin.

Internally this angle is stored continuously, however there are functions that return wrapped angles: "180" is from [-pi, pi), [-180, 180), [-0.5, 0.5) "360" is from [0, 2pi), [0, 360), [0, 1)

5.72.2 Constructor & Destructor Documentation

Rotation2d() [1/4]

```
Rotation2d::Rotation2d () [inline], [constexpr]
```

Default Constructor for Rotation2d

Rotation2d() [2/4]

Constructs a rotation with the given value in radians.

radians the value of the rotation in radians.

Rotation2d() [3/4]

Constructs a rotation given x and y values. Does not have to be normalized. The angle from the x axis to the point.

```
[theta] = [atan2(y, x)]
```

Parameters

X	the x value of the point
у	the y value of the point

Rotation2d() [4/4]

Constructs a rotation given x and y values in the form of a Translation2d. Does not have to be normalized. The angle from the x axis to the point.

```
[theta] = [atan2(y, x)]
```

Parameters

translation

5.72.3 Member Function Documentation

degrees()

```
double Rotation2d::degrees () const
```

Returns the degree angle value.

Returns

the degree angle value.

f_cos()

```
double Rotation2d::f_cos () const
```

Returns the cosine of the angle value.

Returns

the cosine of the angle value

f_sin()

```
double Rotation2d::f_sin () const
```

Returns the sine of the angle value.

Returns

the sine of the angle value.

f_tan()

```
double Rotation2d::f_tan () const
```

Returns the tangent of the angle value.

Returns

the tangent of the angle value.

operator*()

Multiplies this rotation by a scalar.

Parameters

Returns

the rotation multiplied by the scalar.

operator+()

Adds the values of two rotations using a rotation matrix

 $[new_cos] = [other.cos, -other.sin][cos] \\ [new_sin] = [other.sin, other.cos][sin] \\ new_value = atan2(new_sin, new_cos) \\ [new_cos] \\ [new_sin] = [other.sin, other.cos][sin] \\ [new_value] = atan2(new_sin, new_cos) \\ [new_sin] \\ [new_sin] = [other.sin, other.sin][sin] \\ [new_sin] = [other.sin, other.sin, other.sin][sin] \\ [new_sin, other.sin, other.sin,$

other	the other rotation to add to this rotation.
-------	---

Returns

the sum of the two rotations.

Adds the values of two rotations using a rotation matrix.

[new_cos] = [other.cos, -other.sin][cos] [new_sin] = [other.sin, other.cos][sin] new_value = atan2(new_sin, new_cos)

Parameters

other	the other rotation to add to this rotation.

Returns

the sum of the two rotations.

operator-() [1/2]

```
Rotation2d Rotation2d::operator- () const
```

Takes the inverse of this rotation by flipping it. Equivalent to adding 180 degrees.

Returns

this inverse of the rotation.

Takes the inverse of this rotation by flipping it.

Returns

this inverse of the rotation.

operator-() [2/2]

Subtracts the values of two rotations.

Parameters

other	the other rotation to subtract from this rotation.
-------	--

Returns

the difference between the two rotations.

operator/()

Divides this rotation by a scalar.

scalar	the scalar value to divide the rotation by.
--------	---

Returns

the rotation divided by the scalar.

operator==()

Compares two rotations. Returns true if their values are within 1e-9 radians of each other, to account for floating point error.

Parameters

e other rotation to compare to	other
--------------------------------	-------

Returns

whether the values of the rotations are within 1e-9 radians of each other

radians()

```
double Rotation2d::radians () const
```

Returns the radian angle value.

Returns

the radian angle value.

revolutions()

```
double Rotation2d::revolutions () const
```

Returns the revolution angle value.

Returns

the revolution angle value.

rotation_matrix()

```
Eigen::Matrix2d Rotation2d::rotation_matrix () const
```

Returns the rotation matrix equivalent to this rotation [cos, -sin] R = [sin, cos]

Returns

the rotation matrix equivalent to this rotation

wrapped_degrees_180()

```
double Rotation2d::wrapped_degrees_180 () const
```

Returns the degree angle value, wrapped from [-180, 180).

Returns

the degree angle value, wrapped from [-180, 180)

wrapped_degrees_360()

```
double Rotation2d::wrapped_degrees_360 () const
```

Returns the degree angle value, wrapped from [0, 360).

Returns

the degree angle value, wrapped from [0, 360)

wrapped_radians_180()

```
double Rotation2d::wrapped_radians_180 () const
```

Returns the radian angle value, wrapped from [-pi, pi).

Returns

the radian angle value, wrapped from [-pi, pi)

wrapped_radians_360()

```
double Rotation2d::wrapped_radians_360 () const
```

Returns the radian angle value, wrapped from [0, 2pi).

Returns

the radian angle value, wrapped from [0, 2pi)

wrapped_revolutions_180()

```
double Rotation2d::wrapped_revolutions_180 () const
```

Returns the revolution angle value, wrapped from [-0.5, 0.5).

Returns

the revolution angle value, wrapped from [-0.5, 0.5)

wrapped_revolutions_360()

```
double Rotation2d::wrapped_revolutions_360 () const
```

Returns the revolution angle value, wrapped from [0, 1).

Returns

the revolution angle value, wrapped from [0, 1)

5.72.4 Friends And Related Symbol Documentation

operator <<

Sends a rotation to an output stream. Ex. std::cout << rotation;

```
prints "Rotation2d[rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- rotation2d.h
- rotation2d.cpp

5.73 ScaledSphericalSimplexSigmaPoints < STATES > Class Template Reference

```
#include <srukf.h>
```

Public Member Functions

- ScaledSphericalSimplexSigmaPoints (double alpha=0.001, double beta=2)
- int num_sigmas ()
- EMat< STATES, NUM_SIGMAS > square_root_sigma_points (const EVec< STATES > &x, const EMat< STATES, STATES > &S)
- const EVec< NUM_SIGMAS > & Wm () const
- const EVec< NUM_SIGMAS > & Wc () const
- double Wm (int i) const
- double Wc (int i) const

5.73.1 Detailed Description

template<int STATES> class ScaledSphericalSimplexSigmaPoints< STATES >

Generates sigma points and weights according to the paper [1] This is very different from Wan and Merwe's formulation.

This only requires N + 2 sigma points instead of 2N + 1 sigma points. Rather than generating sigma points symmetrically around the mean, it generates them as vertices of an N-simplex.

The performance of the filter using this reduced set of sigma points is identical to the standard method, so there is no downside to using it here.

[1] A Scaled Spherical Simplex Filter (S3F) with a decreased n + 2 sigma points set size and equivalent 2n + 1 Unscented Kalman Filter (UKF) accuracy

Template Parameters

STATES	the dimension of the state. NUM_SIGMAS sigma points and weights will be generated.
--------	--

5.73.2 Constructor & Destructor Documentation

ScaledSphericalSimplexSigmaPoints()

Constructs a sigma point generator for Spherical Simplex sigma points

Parameters

alpha	Determines the spread of the sigma points around the mean. Smaller values are closer to the mean, this is usually a small value.
beta	Incorporates prior knowledge of the distribution of the state. For Gaussian distributions, beta = 2 is optimal.

5.73.3 Member Function Documentation

num_sigmas()

```
template<int STATES>
int ScaledSphericalSimplexSigmaPoints< STATES >::num_sigmas () [inline]
```

Returns the number of sigma points, for simplex sigma points this is N+2.

square_root_sigma_points()

Computes the sigma points given a mean (x) and square-root covariance (S).

X	Vector of the means.
S	Square-root covariance.

Returns

Matrix containing the sigma points. Each column contains one sigma point in the same space as x. The first column is the same as the mean, with the others arranged around the mean.

Wc() [1/2]

Returns a vector containing the weights of each sigma point for the covariance.

Wc() [2/2]

Returns the weight for the i-th sigma point for the covariance.

Parameters

i Element of the weights vector to return.

Wm() [1/2]

```
template<int STATES>
const EVec< NUM_SIGMAS > & ScaledSphericalSimplexSigmaPoints< STATES >::Wm () const [inline]
```

Returns a vector containing the weights of each sigma point for the mean.

Wm() [2/2]

```
template<int STATES>
double ScaledSphericalSimplexSigmaPoints< STATES >::Wm (
          int i) const [inline]
```

Returns the weight for the i-th sigma point for the mean.

Parameters

i Element of the weights vector to return.

The documentation for this class was generated from the following file:

srukf.h

5.74 screen::ScreenData Struct Reference

The ScreenData class holds the data that will be passed to the screen thread you probably shouldnt have to use it.

5.74.1 Detailed Description

The ScreenData class holds the data that will be passed to the screen thread you probably shouldnt have to use it.

The documentation for this struct was generated from the following file:

· screen.cpp

5.75 Serializer Class Reference

Serializes Arbitrary data to a file on the SD Card.

```
#include <serializer.h>
```

Public Member Functions

∼Serializer ()

Save and close upon destruction (bc of vex, this doesnt always get called when the program ends. To be sure, call save_to_disk)

Serializer (const std::string &filename, bool flush_always=true)

create a Serializer

• void save_to_disk () const

saves current Serializer state to disk

• void set_int (const std::string &name, int i)

Setters - not saved until save_to_disk is called.

void set_bool (const std::string &name, bool b)

sets a bool by the name of name to b. If flush_always == true, this will save to the sd card

void set_double (const std::string &name, double d)

sets a double by the name of name to d. If flush_always == true, this will save to the sd card

void set_string (const std::string &name, std::string str)

sets a string by the name of name to s. If flush_always == true, this will save to the sd card

int int_or (const std::string &name, int otherwise)

gets a value stored in the serializer. If not found, sets the value to otherwise

• bool bool_or (const std::string &name, bool otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

double double_or (const std::string &name, double otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

std::string string_or (const std::string &name, std::string otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

5.75.1 Detailed Description

Serializes Arbitrary data to a file on the SD Card.

5.75.2 Constructor & Destructor Documentation

Serializer()

create a Serializer

filename	the file to read from. If filename does not exist we will create that file	
flush_always	If true, after every write flush to a file. If false, you are responsible for calling save_to_disk	

5.75.3 Member Function Documentation

bool_or()

gets a value stored in the serializer. If not, sets the value to otherwise

Parameters

name	name of value
otherwise	value if the name is not specified

Returns

the value if found or otherwise

double_or()

gets a value stored in the serializer. If not, sets the value to otherwise

Parameters

name	name of value
otherwise	value if the name is not specified

Returns

the value if found or otherwise

int_or()

gets a value stored in the serializer. If not found, sets the value to otherwise

Getters Return value if it exists in the serializer

name	name of value
otherwise	value if the name is not specified

Returns

the value if found or otherwise

save_to_disk()

```
void Serializer::save_to_disk () const
```

saves current Serializer state to disk

forms data bytes then saves to filename this was openned with

set_bool()

sets a bool by the name of name to b. If flush_always == true, this will save to the sd card

Parameters

name	name of bool
b	value of bool

set_double()

sets a double by the name of name to d. If flush_always == true, this will save to the sd card

Parameters

name	name of double
d	value of double

set_int()

Setters - not saved until save_to_disk is called.

sets an integer by the name of name to i. If flush_always == true, this will save to the sd card

name	name of integer
i	value of integer

set_string()

sets a string by the name of name to s. If flush_always == true, this will save to the sd card

Parameters

name	name of string
i	value of string

string_or()

gets a value stored in the serializer. If not, sets the value to otherwise

Parameters

name	name of value
otherwise	value if the name is not specified

Returns

the value if found or otherwise

The documentation for this class was generated from the following files:

- serializer.h
- · serializer.cpp

5.76 screen::SliderWidget Class Reference

Widget that updates a double value. Updates by reference so watch out for race conditions cuz the screen stuff lives on another thread.

```
#include <screen.h>
```

Public Member Functions

• SliderWidget (double &val, double low, double high, Rect rect, std::string name)

Creates a slider widget.

bool update (bool was_pressed, int x, int y)

responds to user input

• void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number)

Page::draws the slide to the screen

5.76.1 Detailed Description

Widget that updates a double value. Updates by reference so watch out for race conditions cuz the screen stuff lives on another thread.

5.76.2 Constructor & Destructor Documentation

SliderWidget()

Creates a slider widget.

Parameters

val	reference to the value to modify
low	minimum value to go to
high	maximum value to go to
rect	rect to draw it
name	name of the value

5.76.3 Member Function Documentation

update()

```
bool screen::SliderWidget::update (
          bool was_pressed,
          int x,
          int y)
```

responds to user input

Parameters

was_pressed	if the screen is pressed
X	x position if the screen was pressed
У	y position if the screen was pressed

Returns

true if the value updated

The documentation for this class was generated from the following files:

- · screen.h
- · screen.cpp

5.77 SpinRPMCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- SpinRPMCommand (Flywheel &flywheel, int rpm)
- bool run () override

5.77.1 Detailed Description

File: flywheel_commands.h Desc: [insert meaningful desc] AutoCommand wrapper class for the spin_rpm function in the Flywheel class

5.77.2 Constructor & Destructor Documentation

SpinRPMCommand()

Construct a SpinRPM Command

Parameters

flywheel	the flywheel sys to command
rpm	the rpm that we should spin at

File: flywheel_commands.cpp Desc: [insert meaningful desc]

5.77.3 Member Function Documentation

run()

```
bool SpinRPMCommand::run () [override]
```

Run spin_manual Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- flywheel_commands.h
- flywheel_commands.cpp

5.78 PurePursuit::spline Struct Reference

```
#include <pure_pursuit.h>
```

5.78.1 Detailed Description

Represents a piece of a cubic spline with $s(x) = a(x-xi)^3 + b(x-xi)^2 + c(x-xi) + d$ The x_start and x_end shows where the equation is valid.

The documentation for this struct was generated from the following file:

• pure_pursuit.h

${\bf 5.79 \quad Square Root Unscented Kalman Filter} < {\bf STATES, INPUTS, OUTPUTS} > {\bf Class} \\ {\bf Template \ Reference}$

#include <srukf.h>

Public Member Functions

- SquareRootUnscentedKalmanFilter (const std::function < StateVector(const StateVector &, const InputVector &)> &f, const std::function< OutputVector(const StateVector &, const InputVector &)> &h, const WithInput ← Integrator &integrator, const StateVector &state_stddevs, const OutputVector &measurement_stddevs)
- SquareRootUnscentedKalmanFilter (const std::function < StateVector(const StateVector &, const InputVector &)> &f, const std::function< OutputVector(const StateVector &, const InputVector &)> &h, const With← InputIntegrator &integrator, const StateVector &state stddevs, const OutputVector &measurement stddevs, const std::function < StateVector(const EMat < STATES, NUM_SIGMAS > &, const EVec < NUM_SIGMAS > &)> &mean_func_X, const std::function < OutputVector(const EMat < OUTPUTS, NUM_SIGMAS > &, const EVec < NUM SIGMAS > &)> &mean func Y, const std::function < StateVector(const StateVector &, const StateVector &) > &residual_func_X, const std::function < OutputVector(const OutputVector &, const Output ← Vector &)> &residual_func_Y, const std::function< StateVector(const StateVector &, const StateVector &)> &add func X)
- StateMatrix S () const
- double S (int i, int j) const
- void set S (const StateMatrix &S)
- StateMatrix P () const
- void set_P (const StateMatrix &P)
- StateVector xhat () const
- double xhat (int i) const
- void set_xhat (const StateVector &xhat)
- void set_xhat (int i, double value)
- · void reset ()
- void predict (const InputVector &u, double dt)
- void correct (const InputVector &u, const OutputVector &y)
- void correct (const InputVector &u, const OutputVector &y, const EVec< OUTPUTS > &measurement ← stddevs)
- · template<int ROWS>
 - void correct (const InputVector &u, const EVec < ROWS > &y, const std::function < EVec < ROWS > (const StateVector &, const InputVector &)> &h, const EVec< ROWS > &measurement_stddevs)
- - void correct (const InputVector &u, const EVec < ROWS > &y, const std::function < EVec < ROWS > (const $StateVector \ \&, \ const \ InputVector \ \&) > \ \&h, \ const \ EVec < \ ROWS \ > \ measurement_stddevs, \ const \ std \hookleftarrow$::function< EVec< ROWS >(const EMat< ROWS, NUM SIGMAS > &, const EVec< NUM SIGMAS > &)> &mean func Y, const std::function< EVec< ROWS >(const EVec< ROWS > &, const EVec< ROWS > &)> &residual func Y, const std::function< StateVector(const StateVector &, const StateVector &)> &residual_func_X, const std::function< StateVector(const StateVector &, const StateVector &)> &add_← func X)

5.79.1 Detailed Description

template<int STATES, int INPUTS, int OUTPUTS> class SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >

Kalman filters combine predictions from a model and measurements to estimate a system's true state.

The Unscented Kalman Filter is a nonlinear estimator, meaning that the model used to predict how the state changes over time can be nonlinear. The model that determines the expected measurement given the current state can also be nonlinear.

At each timestep, sigma points are generated close to the mean, they are all propagated forward in time according to the nonlinear model. The Unscented Transform uses the propagated sigma points to compute the prior state and covariance.

When correcting the state and covariance with a measurement, sigma points are again generated, but are transformed into the measurement space using the measurement function. A Kalman gain matrix K is then computed, and used to update the state and covariance.

To read more about Kalman filters and the standard UKF read: https://github.com/rlabbe/← Kalman-and-Bayesian-Filters-in-Python

This implementation is somewhat non-standard. The square-root form of the UKF (SR-UKF) is used, and the way the sigma points are generated is different than most implementations. The square-root form is used to ensure that the covariance matrix remains positive definite.

To learn more about the SR-UKF, and see the exact formulation that most of this implementation follows, read: https://www.researchgate.net/publication/3908304

The sigma points are not generated symmetrically around the mean, instead they are generated as vertices of a simplex. Using N = # of states, this method uses N + 2 sigma points instead of the standard 2N + 1 sigma points. This reduces computation up to 50%. To learn more about this method, read: $https://www. \leftarrow sciencedirect.com/science/article/pii/S0888327020308190$

This filter uses a method of "recalibrating" by essentially applying a measurement twice instead of once, and only using it if it is more accurate than before the measurement was applied. To learn more about this framework for nonlinear filters, read: https://arxiv.org/pdf/2407.05717

Template Parameters

STATES	Dimension of the state vector.
INPUTS	Dimension of the control input vector.
OUTPUTS	Dimension of the measurement vector.

5.79.2 Constructor & Destructor Documentation

SquareRootUnscentedKalmanFilter() [1/2]

Constructs an Unscented Kalman Filter.

Parameters

f	A vector valued function of x and u that returns the derivative of the state vector with respect to time.
h	A vector valued function of x and u that returns the expected measurement at the given state.
integrator	A function from "numerical_integration.h" that integrates a differential equation of the form $f(x, u)$.
state_stddevs	Standard deviations of the states in the model.
measurement_stddevs	Standard deviations of the measurements.

SquareRootUnscentedKalmanFilter() [2/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
SquareRootUnscentedKalmanFilter < STATES, INPUTS, OUTPUTS >::SquareRootUnscentedKalmanFilter (
             const std::function< StateVector(const StateVector &, const InputVector &)> & f,
             const std::function< OutputVector(const StateVector &, const InputVector &)> & h,
             const WithInputIntegrator & integrator,
             const StateVector & state_stddevs,
             const OutputVector & measurement_stddevs,
             const std::function< StateVector(const EMat< STATES, NUM_SIGMAS > &, const EVec<</pre>
NUM_SIGMAS > \&) > \& mean\_func_X,
             const std::function< OutputVector(const EMat< OUTPUTS, NUM_SIGMAS > &, const
EVec< NUM_SIGMAS > \&)> \& mean\_func\_Y,
             const std::function< StateVector(const StateVector &, const StateVector &)> &
residual_func_X,
             const std::function< OutputVector(const OutputVector &, const OutputVector &)> &
residual_func_Y,
            const std::function< StateVector(const StateVector &, const StateVector &)> &
add_func_X) [inline]
```

Constructs an Unscented Kalman Filter with custom mean, residual, and addition functions. The most common use for these functions is when you are estimating angles whose arithmetic operations need to be wrapped.

Parameters

f	A vector valued function of x and u that returns the derivative of the state vector with respect to time.
h	A vector valued function of x and u that returns the expected measurement at the given state.
integrator	A function from "numerical_integration.h" that integrates a differential equation of the form $f(x, u)$.
state_stddevs	Standard deviations of the states in the model.
measurement_stddevs	Standard deviations of the measurements.
mean_func_X	A function that computes the mean of a matrix containing NUM_SIGMAS state sigma points with a set of weights for each.
mean_func_Y	A function that computes the mean of a matrix containing NUM_SIGMAS measurement sigma points with a set of weights for each.
residual_func_X	A function that computes the residual of two state vectors, usually by simple subtraction.
residual_func_Y	A function that computes the residual of two measurement vectors, usually by simple subtraction.
add_funx_X	A function that adds two state vectors.

5.79.3 Member Function Documentation

correct() [1/4]

```
template<int STATES, int INPUTS, int OUTPUTS>
template<int ROWS>
void SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::correct (
            const InputVector & u,
            const EVec< ROWS > & y,
            const std::function< EVec< ROWS > (const StateVector &, const InputVector &) > &
```

Correct the state estimate using the measurements in y, a custom measurement function, and custom standard deviations. This is useful for when a different set of measurements are being applied.

Parameters

и	The control input used in the last predict step.
у	The vector of measurements.
h	A vector valued function of x and u that returns the expected measurement at the given state.
measurement_stddevs	The vector of standard deviations for each measurement to be used for this correct step.

correct() [2/4]

```
template<int STATES, int INPUTS, int OUTPUTS>
template<int ROWS>
void SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::correct (
             const InputVector & u,
             const EVec< ROWS > & y_{i}
             const std::function< EVec< ROWS > (const StateVector &, const InputVector &) > &
h,
             const EVec< ROWS > measurement_stddevs,
             const std::function< EVec< ROWS > (const EMat< ROWS, NUM_SIGMAS > &, const EVec<
\label{eq:num_sigmas} \mbox{NUM\_SIGMAS} \ > \ \&) > \ \& \ mean\_func\_Y \mbox{,}
             const std::function< EVec< ROWS > (const EVec< ROWS > &, const EVec< ROWS > &)>
& residual_func_Y,
             const std::function< StateVector(const StateVector &, const StateVector &)> &
residual_func_X,
             const std::function< StateVector(const StateVector &, const StateVector &)> &
add_func_X) [inline]
```

Correct the state estimate using the measurements in y, a custom measurement function, custom standard deviations, and custom mean, residual, and addition functions. This is useful for when a different set of measurements are being applied, and they require custom arithmetic functions.

Parameters

и	The control input used in the last predict step.
У	The vector of measurements.
h	A vector valued function of x and u that returns the expected measurement at the given state.
measurement_stddevs	The vector of standard deviations for each measurement to be used for this correct step.
mean_func_Y	A function that computes the mean of a matrix containing NUM_SIGMAS measurement sigma points with a set of weights for each.
residual_func_X	A function that computes the residual of two state vectors, usually by simple subtraction.
residual_func_Y	A function that computes the residual of two measurement vectors, usually by simple subtraction.
add_funx_X	A function that adds two state vectors.

correct() [3/4]

```
template<int STATES, int INPUTS, int OUTPUTS>
\verb|void SquareRootUnscentedKalmanFilter<| STATES, INPUTS, OUTPUTS| >:: correct | (
             const InputVector & u,
             const OutputVector & y) [inline]
```

Correct the state estimate using the measurements in y.

Parameters

и	The control input used in the last predict step.
У	The vector of measurements.

correct() [4/4]

```
template<int STATES, int INPUTS, int OUTPUTS>
void SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::correct (
            const InputVector & u,
            const OutputVector & y,
            const EVec< OUTPUTS > & measurement_stddevs) [inline]
```

Correct the state estimate using the measurements in y, and custom standard deviations. This is useful for when the noise in the measurements vary.

Parameters

и	The control input used in the last predict step.
У	The vector of measurements.
measurement_stddevs	The vector of standard deviations for each measurement to be used for this correct step.

P()

```
template<int STATES, int INPUTS, int OUTPUTS>
StateMatrix SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::P () const [inline]
```

Returns the reconstructed covariance matrix P.

predict()

```
template<int STATES, int INPUTS, int OUTPUTS>
void SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::predict (
            const InputVector & u,
            double dt) [inline]
```

Projects the state into the future by dt seconds with control input u.

и	The control input.
dt	The timestep in seconds.

reset()

```
template<int STATES, int INPUTS, int OUTPUTS>
void SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::reset () [inline]
```

Resets the filter. Make sure to explicitly set S after calling this.

S() [1/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
StateMatrix SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::S () const [inline]
```

Returns the square-root covariance matrix S.

S() [2/2]

```
template<int STATES, int INPUTS, int OUTPUTS> double SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::S ( int i, int j) const [inline]
```

Returns one element of the square-root covariance matrix S.

Parameters

i	Row of S.
j	Column of S.

set_P()

Set the current square-root covariance matrix S to the square-root of P.

Parameters

```
P The covariance matrix P.
```

set_S()

Set the current square-root covariance matrix S.

The new square-root covariance matrix S.

set_xhat() [1/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
void SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::set_xhat (
            const StateVector & xhat) [inline]
```

Set the current state estimate x-hat.

set_xhat() [2/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
void SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::set_xhat (
            int i,
            double value) [inline]
```

Set one element of the current state estimate x-hat.

Parameters

Row of x-hat.

xhat() [1/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
StateVector SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::xhat () const [inline]
```

Returns the current state estimate x-hat.

xhat() [2/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
double SquareRootUnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::xhat (
            int i) const [inline]
```

Returns one element of the current state estimate x-hat.

Parameters

```
Row of x-hat.
```

The documentation for this class was generated from the following file:

srukf.h

5.80 StateMachine< System, IDType, Message, delay_ms, do_log >::State Struct Reference

#include <state_machine.h>

5.80.1 Detailed Description

template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log = false> struct StateMachine< System, IDType, Message, delay_ms, do_log >::State

Abstract class that all states for this machine must inherit from States MUST override respond() and id() in order to function correctly (the compiler won't have it any other way)

The documentation for this struct was generated from the following file:

· state_machine.h

5.81 StateMachine< System, IDType, Message, delay_ms, do_log > Class Template Reference

State Machine :)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024 Over Under game for our overly complex intake-cata subsystem (see there for an example) The statemachine runs in a background thread and a user thread can interact with it through current state and send message.

#include <state_machine.h>

Classes

· class MaybeMessage

MaybeMessage a message of Message type or nothing MaybeMessage $m = \{ \}; \ // \ empty \ MaybeMessage \ m = Message::EnumField1.$

· struct State

Public Member Functions

• StateMachine (State *initial)

Construct a state machine and immediatly start running it.

• IDType current_state () const

retrieve the current state of the state machine. This is safe to call from external threads

void send_message (Message msg)

send a message to the state machine from outside

5.81.1 Detailed Description

template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log = false> class StateMachine< System, IDType, Message, delay_ms, do_log >

State Machine :)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024 Over Under game for our overly complex intake-cata subsystem (see there for an example) The statemachine runs in a background thread and a user thread can interact with it through current_state and send_message.

Designwise: the System class should hold onto any motors, feedback controllers, etc that are persistent in the system States themselves should hold any data that *only* that state needs. For example if a state should be exitted after a certain amount of time, it should hold a timer rather than the System holding that timer. (see Junder from 2024 for an example of this design)

Template Parameters

System The system that this is the base class of class Thing: public		
	StateMachine <thing> @tparam IDType The ID enum that recognizes</thing>	
	states. Hint hint, use an enum class `	
Message	ge the message enum that a state or an outside can send and that states respond to	
delay_ms	the delay to wait between each state processing to allow other threads to work	
do_log	true if you want print statements describing incoming messages and current states. If true, it is expected that IDType and Message have a function called to_string that takes them as its only parameter and returns a std::string	

5.81.2 Constructor & Destructor Documentation

StateMachine()

Construct a state machine and immediatly start running it.

Parameters

initial the state that the machine will begin in	1
--	---

5.81.3 Member Function Documentation

current_state()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
IDType StateMachine< System, IDType, Message, delay_ms, do_log >::current_state () const
[inline]
```

retrieve the current state of the state machine. This is safe to call from external threads

Returns

the current state

send_message()

send a message to the state machine from outside

msg the message to send This is safe to call from external threads

The documentation for this class was generated from the following file:


state_machine.h

5.82 screen::StatsPage Class Reference

Draws motor stats and battery stats to the screen.

```
#include <screen.h>
```

Inheritance diagram for screen::StatsPage:



Public Member Functions

- StatsPage (std::map< std::string, vex::motor & > motors)
 Creates a stats page.
- void update (bool was_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first_draw, unsigned int frame_number) override

5.82.1 Detailed Description

Draws motor stats and battery stats to the screen.

5.82.2 Constructor & Destructor Documentation

StatsPage()

Creates a stats page.

Parameters

motors a map of string to motor that we want to draw on this page

5.82.3 Member Function Documentation

draw()

See also

Page::draw

Reimplemented from screen::Page.

update()

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:

- screen.h
- screen.cpp

5.83 VDP::String Class Reference

```
#include <types.hpp>
```

Inheritance diagram for VDP::String:



Public Member Functions

- String (std::string name, FetchFunc fetcher=[]() { return "no value";})
- · void fetch () override
- void response () override
- void setValue (std::string new_value)
- void read_data_from_message (PacketReader &reader) override
- void pprint (std::stringstream &ss, size_t indent) const override
- void pprint_data (std::stringstream &ss, size_t indent) const override

Public Member Functions inherited from VDP::Part

- Part (std::string name)
- std::string pretty print () const
- std::string pretty_print_data () const

Protected Member Functions

- void write_schema (PacketWriter &sofar) const override
- void write_message (PacketWriter &sofar) const override

5.83.1 Detailed Description

A string type conveyed as a part

5.83.2 Constructor & Destructor Documentation

String()

creates a string type conveyed as a part with a name and a fetcher

Parameters

name	name of the string to have
fetcher	the fetch function to use when running fetch()

creates a string type conveyed as a part with a name and a fetcher

Parameters

name	name of the string to have
fetcher	the fetcher function to use when assigning it new data

5.83.3 Member Function Documentation

fetch()

```
void VDP::String::fetch () [override], [virtual]
```

function to run when fetching this part, runs the fetch function

used to assign the string new data, runs the fetch function

Implements VDP::Part.

pprint()

changes a stringstream to be formatted as name: string

Parameters

ss	the stringstream to change
indent	the amount of indents to use

Implements VDP::Part.

pprint_data()

changes a stringstream to be formatted as name: value

Parameters

SS	the stringstream to change
indent	the amount of indents to use

Implements VDP::Part.

read_data_from_message()

sets the string part's value to the string read by a packet reader

reader the packet reader to get t	ne string from
-----------------------------------	----------------

sets the string part's value to the string read by a packet reader

Parameters

eader to get	<i>reader</i> t
--------------	-----------------

Implements VDP::Part.

response()

```
void VDP::String::response () [override], [virtual]
```

function to run when receiving to this part

Reimplemented from VDP::Part.

setValue()

sets the string part's value to the string given

Parameters

new_value	the string to set the value to
-----------	--------------------------------

write_message()

writes the strings data to a packet

Parameters

sofar the packet writer to write with

Implements VDP::Part.

write_schema()

writes the schematic for the string to a packet

sofar the packet writer to write with

Implements VDP::Part.

The documentation for this class was generated from the following files:


- types.hpp
- types.cpp

5.84 TakeBackHalf Class Reference

A velocity controller.

```
#include <take_back_half.h>
```

Inheritance diagram for TakeBackHalf:



Public Member Functions

- void init (double start_pt, double set_pt)
- double update (double val) override
- double get () override
- void set_limits (double lower, double upper) override
- bool is_on_target () override

Public Attributes

• double TBH_gain

tuned parameter

5.84.1 Detailed Description

A velocity controller.

Warning

If you try to use this as a position controller, it will fail.

5.84.2 Member Function Documentation

get()

```
double TakeBackHalf::get () [override], [virtual]
```

Returns

the last saved result from the feedback controller

Implements Feedback.

init()

Initialize the feedback controller for a movement

Parameters

start_pt	the current sensor value
set_pt	where the sensor value should be
start_vel	Movement starting velocity (IGNORED)

Implements Feedback.

is_on_target()

```
bool TakeBackHalf::is_on_target () [override], [virtual]
```

Returns

true if the feedback controller has reached it's setpoint

Implements Feedback.

set_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

lower	Upper limit
upper	Lower limit

Implements Feedback.

update()

Iterate the feedback loop once with an updated sensor value

Parameters

val value from the sensor

Returns

feedback loop result

Implements Feedback.

The documentation for this class was generated from the following files:

- take_back_half.h
- take_back_half.cpp

5.85 TankDrive Class Reference

```
#include <tank_drive.h>
```

Public Types

• enum class BrakeType { None , ZeroVelocity , Smart , TurnOnly }

Public Member Functions

- TankDrive (motor_group &left_motors, motor_group &right_motors, robot_specs_t &config, OdometryBase *odom=NULL)
- void stop ()
- Pose2d get position ()
- void drive tank (double left, double right, int power=1, BrakeType bt=BrakeType::None)
- void drive tank raw (double left, double right)
- void drive_arcade (double forward_back, double left_right, int power=1, BrakeType bt=BrakeType::None)
- bool drive_forward (double inches, directionType dir, Feedback &feedback, double max_speed=1, double end speed=0)
- bool drive_forward (double inches, directionType dir, double max_speed=1, double end_speed=0)
- bool turn degrees (double degrees, Feedback &feedback, double max speed=1, double end speed=0)
- bool turn_degrees (double degrees, double max_speed=1, double end_speed=0)
- bool drive_to_point (double x, double y, vex::directionType dir, Feedback &feedback, double max_speed=1, double end_speed=0)
- bool drive_to_point (double x, double y, vex::directionType dir, double max_speed=1, double end_speed=0)
- bool turn_to_heading (double heading_deg, double max_speed=1, double end_speed=0)
- void reset auto ()
- bool pure_pursuit (PurePursuit::Path path, directionType dir, Feedback &feedback, double max_speed=1, double end speed=0)

Static Public Member Functions

• static double modify_inputs (double input, int power=2)

5.85.1 Detailed Description

TankDrive is a class to run a tank drive system. A tank drive system, sometimes called differential drive, has a motor (or group of synchronized motors) on the left and right side

5.85.2 Member Enumeration Documentation

BrakeType

```
enum class TankDrive::BrakeType [strong]
```

Enumerator

None	just send 0 volts to the motors
ZeroVelocity	try to bring the robot to rest. But don't try to hold position
Smart	bring the robot to rest and once it's stopped, try to hold that position

5.85.3 Constructor & Destructor Documentation

TankDrive()

Create the TankDrive Object

left_motors	left side drive motors
right_motors	right side drive motors
config	the configuration specification defining physical dimensions about the robot. See robot_specs_t for more info
odom	an odometry system to track position and rotation. this is necessary to execute autonomous paths

5.85.4 Member Function Documentation

drive_arcade()

Drive the robot using arcade style controls. forward_back controls the linear motion, left_right controls the turning.

forward_back and left_right are in "percent": -1.0 -> 1.0

Parameters

forward_back	the percent to move forward or backward
left_right	the percent to turn left or right
power	modifies the input velocities left^power, right^power
bt	breaktype. What to do if the driver lets go of the sticks

Drive the robot using arcade style controls. forward_back controls the linear motion, left_right controls the turning. left_motors and right_motors are in "percent": -1.0 -> 1.0

drive_forward() [1/2]

Autonomously drive the robot forward a certain distance

Parameters

inches	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
dir	the direction we want to travel forward and backward
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Autonomously drive the robot forward a certain distance

inches	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw	
dir	the direction we want to travel forward and backward	
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power	
end_speed	the movement profile will attempt to reach this velocity by its completion	

Returns

true if we have finished driving to our point

drive_forward() [2/2]

Use odometry to drive forward a certain distance using a custom feedback controller

Returns whether or not the robot has reached it's destination.

Parameters

inches	the distance to drive forward	
dir	the direction we want to travel forward and backward	
feedback	the custom feedback controller we will use to travel. controls the rate at which we accelerate and drive.	
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power	
end_speed	the movement profile will attempt to reach this velocity by its completion	

Returns

true when we have reached our target distance

Use odometry to drive forward a certain distance using a custom feedback controller

Returns whether or not the robot has reached it's destination.

Parameters

inches	the distance to drive forward
dir	the direction we want to travel forward and backward
feedback	the custom feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

drive_tank()

Drive the robot using differential style controls. left_motors controls the left motors, right_motors controls the right motors.

left_motors and right_motors are in "percent": -1.0 -> 1.0

Parameters

left	the percent to run the left motors
right	the percent to run the right motors
power	modifies the input velocities left^power, right^power
bt	breaktype. What to do if the driver lets go of the sticks

drive_tank_raw()

Drive the robot raw-ly

Parameters

left	the percent to run the left motors (-1, 1)
right	the percent to run the right motors (-1, 1)

drive_to_point() [1/2]

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot. Here we use the default feedback controller from the drive_sys

Returns whether or not the robot has reached it's destination.

Parameters

Χ	the x position of the target
у	the y position of the target

dir	the direction we want to travel forward and backward
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot. Here we use the default feedback controller from the drive_sys

Returns whether or not the robot has reached it's destination.

Parameters

X	the x position of the target
У	the y position of the target
dir	the direction we want to travel forward and backward
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true if we have reached our target point

drive_to_point() [2/2]

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot.

Returns whether or not the robot has reached it's destination.

Parameters

x	the x position of the target	
У	the y position of the target	
dir	the direction we want to travel forward and backward	
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.	
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power	
end_speed	the movement profile will attempt to reach this velocity by its completion	

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot.

Returns whether or not the robot has reached it's destination.

X	the x position of the target	
У	the y position of the target	
dir	the direction we want to travel forward and backward	
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and dr	
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power	
end_speed	the movement profile will attempt to reach this velocity by its completion	

Returns

true if we have reached our target point

get_position()

```
Pose2d TankDrive::get_position ()
```

Returns the Robot position as a Pose2d

modify_inputs()

Create a curve for the inputs, so that drivers have more control at lower speeds. Curves are exponential, with the default being squaring the inputs.

Parameters

input	the input before modification
power	the power to raise input to

Returns

input ^ power (accounts for negative inputs and odd numbered powers)

Modify the inputs from the controller by squaring / cubing, etc Allows for better control of the robot at slower speeds

Parameters

input	the input signal -1 -> 1
power	the power to raise the signal to

Returns

input^power accounting for any sign issues that would arise with this naive solution

pure_pursuit()

Drive the robot autonomously using a pure-pursuit algorithm - Input path with a set of waypoints - the robot will attempt to follow the points while cutting corners (radius) to save time (compared to stop / turn / start)

Parameters

path	The list of coordinates to follow, in order
dir	Run the bot forwards or backwards
feedback	The feedback controller determining speed
max_speed	Limit the speed of the robot (for pid / pidff feedbacks)
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

True when the path is complete

Drive the robot autonomously using a pure-pursuit algorithm - Input path with a set of waypoints - the robot will attempt to follow the points while cutting corners (radius) to save time (compared to stop / turn / start)

Parameters

path	The list of coordinates to follow, in order
dir	Run the bot forwards or backwards
feedback	The feedback controller determining speed
max_speed	Limit the speed of the robot (for pid / pidff feedbacks)

Returns

True when the path is complete

reset_auto()

```
void TankDrive::reset_auto ()
```

Reset the initialization for autonomous drive functions

stop()

```
void TankDrive::stop ()
```

Stops rotation of all the motors using their "brake mode"

turn_degrees() [1/2]

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses the defualt turning feedback of the drive system.

Parameters

		degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
		the maximum percentage of robot speed at which the robot will travel. 1 = full power
	end_speed	the movement profile will attempt to reach this velocity by its completion

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses the defualt turning feedback of the drive system.

Parameters

degrees	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true if we turned te target number of degrees

turn_degrees() [2/2]

Autonomously turn the robot X degrees counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses PID + Feedforward for it's control.

Parameters

degrees	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw	
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.	
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power	

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent_speed (-1.0 -> 1.0)

Uses the specified feedback for it's control.

degrees	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true if we have turned our target number of degrees

turn_to_heading() [1/2]

Turn the robot in place to an exact heading relative to the field. 0 is forward. Uses the defualt turn feedback of the drive system

Parameters

heading_	_deg	the heading to which we will turn
max_sp	eed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_spe	eed	the movement profile will attempt to reach this velocity by its completion

Turn the robot in place to an exact heading relative to the field. 0 is forward. Uses the defualt turn feedback of the drive system

Parameters

heading_deg	the heading to which we will turn
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Returns

true if we have reached our target heading

turn_to_heading() [2/2]

Turn the robot in place to an exact heading relative to the field. 0 is forward.

heading_deg the heading to which we will turn	
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Turn the robot in place to an exact heading relative to the field. 0 is forward.

Parameters

heading_deg	ding_deg the heading to which we will turn	
feedback the feedback controller we will use to travel. controls the rate at which we accele		
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power	
end_speed the movement profile will attempt to reach this velocity by its completion		

Returns

true if we have reached our target heading


The documentation for this class was generated from the following files:

- tank_drive.h
- · tank_drive.cpp

5.86 VDP::TimestampedRecord Class Reference

#include <builtins.hpp>

Inheritance diagram for VDP::TimestampedRecord:



Public Member Functions

- TimestampedRecord (std::string name, Part *data)
- void fetch ()

Public Member Functions inherited from VDP::Record

- Record (std::string name)
- Record (std::string name, const std::vector < Part * > &parts)
- Record (std::string name, std::vector< PartPtr > parts)
- Record (std::string name, PacketReader &reader)
- $\bullet \ \ \mathsf{void} \ \ \mathsf{setFields} \ (\mathsf{std} :: \mathsf{vector} < \mathsf{PartPtr} > \mathsf{fields}) \\$
- void read_data_from_message (PacketReader &reader) override

Public Member Functions inherited from VDP::Part

- Part (std::string name)
- std::string pretty_print () const
- std::string pretty print data () const

Additional Inherited Members

Protected Member Functions inherited from VDP::Record

- void write_schema (PacketWriter &sofar) const override
- · void write_message (PacketWriter &sofar) const override

5.86.1 Detailed Description

Defines a record that holds a timestamp and data

5.86.2 Constructor & Destructor Documentation

TimestampedRecord()

Creates a record that contains a Float of a timestamp Part of data

Parameters

	the name of the record to create
data	the data to put into the record

5.86.3 Member Function Documentation

fetch()

```
void VDP::TimestampedRecord::fetch () [virtual]
```

sets the data that the Timestamp Parts hold

Reimplemented from VDP::Record.

The documentation for this class was generated from the following files:

- · builtins.hpp
- · builtins.cpp

5.87 tracking_wheel_cfg_t Struct Reference

#include <odometry_nwheel.h>

Public Attributes

- double x
- double y
- double theta_rad
- · double radius

5.87.1 Detailed Description

OdometryNWheel

This class handles the code for an N-pod odometry setup, where there are N < WHEELS > free spinning omni wheels (dead wheels) placed in any known configuration on the robot.

Example of a possible wheel configuration:

Where O is the center of rotation. The robot will monitor the changes in rotation of these wheels, use this to calculate a pose delta, then integrate the deltas over time to determine the robot's position.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

https://rit.enterprise.slack.com/files/U04112Y5RB6/F080M01KPA5/predictperpindiculars2.epdf 2024-2025 Notebook: Entries/Software Entries/Localization/N-Pod Odometry

Author

Jack Cammarata, Richie Sommers

Date

Nov 14 2024 tracking_wheel_cfg_t holds all the specifications for a single tracking wheel The units for x, y, and radius will determine the units of the position estimate

5.87.2 Member Data Documentation

radius

double tracking_wheel_cfg_t::radius

radius of the wheel

theta_rad

```
double tracking_wheel_cfg_t::theta_rad
```

angle between wheel direction and x axis in the robot frame

X

```
double tracking_wheel_cfg_t::x
```

x position of the center of the wheel

у

```
double tracking_wheel_cfg_t::y
```

y position of the center of the wheel

The documentation for this struct was generated from the following file:

· odometry_nwheel.h

5.88 Transform2d Class Reference

```
#include <transform2d.h>
```

Public Member Functions

- constexpr Transform2d ()
- Transform2d (const Translation2d &translation, const Rotation2d &rotation)
- Transform2d (const double &x, const double &y, const Rotation2d &rotation)
- Transform2d (const double &x, const double &y, const double &radians)
- Transform2d (const Translation2d &translation, const double &radians)
- Transform2d (const Eigen::Vector3d &transform_vector)
- Transform2d (const Pose2d &start, const Pose2d &end)
- Translation2d translation () const
- double x () const
- double y () const
- · Rotation2d rotation () const
- Transform2d inverse () const
- Transform2d operator* (const double &scalar) const
- Transform2d operator/ (const double &scalar) const
- Transform2d operator- () const
- bool operator== (const Transform2d &other) const

Friends

std::ostream & operator<< (std::ostream &os, const Transform2d &transform)

5.88.1 Detailed Description

Class representing a transformation of a pose2d, or a linear difference between the components of poses.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

5.88.2 Constructor & Destructor Documentation

Transform2d() [1/7]

```
Transform2d::Transform2d () [constexpr]
```

Default Constructor for Transform2d

Transform2d() [2/7]

Constructs a transform given translation and rotation components.

Parameters

translation	the translational component of the transform.
rotation	the rotational component of the transform.

Transform2d() [3/7]

Constructs a transform given translation and rotation components.

Parameters

X	the x component of the transform.
У	the y component of the transform.
rotation	the rotational component of the transform.

Transform2d() [4/7]

Constructs a transform given translation and rotation components.

X	the x component of the transform.	
У	the y component of the transform.	
radians the rotational component of the transform in rac		

Transform2d() [5/7]

Constructs a transform given translation and rotation components.

Parameters

translation the translational component of the transform.	
radians	the rotational component of the transform in radians.

Transform2d() [6/7]

Constructs a transform given translation and rotation components given as a vector.

Parameters

transform_vector	vector of the form [x, y, theta]
------------------	----------------------------------

Transform2d() [7/7]

Constructs a transform given translation and rotation components.

Parameters

translation	the translational component of the transform.
rotation	the rotational component of the transform.

5.88.3 Member Function Documentation

inverse()

```
Transform2d Transform2d::inverse () const
```

Inverts the transform.

Returns

the inverted transform.

operator*()

Multiplies this transform by a scalar.

Parameters

scalar to multiply this transform by.

operator-()

```
Transform2d Transform2d::operator- () const
```

Inverts the transform.

Returns

the inverted transform.

operator/()

Divides this transform by a scalar.

Parameters

```
scalar | the scalar to divide this transform by.
```

operator==()

Compares this to another transform.

other	the other transform to compare to.
-------	------------------------------------

Returns

true if the components are within 1e-9 of each other.

rotation()

```
Rotation2d Transform2d::rotation () const
```

Returns the rotational component of the transform.

Returns

the rotational component of the transform.

translation()

```
Translation2d Transform2d::translation () const
```

Returns the translational component of the transform.

Returns

the translational component of the transform.

x()

```
double Transform2d::x () const
```

Returns the x component of the transform.

Returns

the x component of the transform.

y()

```
double Transform2d::y () const
```

Returns the y component of the transform.

Returns

the y component of the transform.

5.88.4 Friends And Related Symbol Documentation

operator<<

The documentation for this class was generated from the following files:

- · transform2d.h
- · transform2d.cpp

5.89 Translation2d Class Reference

```
#include <translation2d.h>
```

Public Member Functions

- constexpr Translation2d ()
- Translation2d (const double &x, const double &y)
- Translation2d (const Eigen::Vector2d &vector)
- Translation2d (const double &r, const Rotation2d &theta)
- · double x () const
- void setX (double x)
- double y () const
- void setY (double y)
- · Rotation2d theta () const
- Eigen::Vector2d as_vector () const
- double norm () const
- Translation2d normalize () const
- double distance (const Translation2d &other) const
- Translation2d rotate by (const Rotation2d &rotation) const
- Translation2d rotate_around (const Translation2d &other, const Rotation2d &rotation) const
- Translation2d operator+ (const Translation2d &other) const
- Translation2d operator- (const Translation2d &other) const
- Translation2d operator- () const
- Translation2d operator* (const double &scalar) const
- Translation2d operator/ (const double &scalar) const
- double operator* (const Translation2d &other) const
- bool operator== (const Translation2d &other) const

Friends

• std::ostream & operator<< (std::ostream &os, const Translation2d &translation)

5.89.1 Detailed Description

Class representing a point in 2d space with x and y coordinates.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

5.89.2 Constructor & Destructor Documentation

Translation2d() [1/4]

```
Translation2d::Translation2d () [inline], [constexpr]
```

Default Constructor for Translation2d

Translation2d() [2/4]

Constructs a Translation2d with the given x and y values.

Parameters

x The x component of the transla	
у	The y component of the translation.

Translation2d() [3/4]

Constructs a Translation2d with the values from the given vector.

Parameters

vector	The vector whose values will be used.
VCCLCI	THE VECTOR WINDSE VARIAGE WILL BE USED.

Translation2d() [4/4]

Constructs a Translation2d given polar coordinates of the form (r, theta).

r	The radius (magnitude) of the vector	
theta	The angle (direction) of the vector.	

5.89.3 Member Function Documentation

as_vector()

```
Eigen::Vector2d Translation2d::as_vector () const
```

Returns the vector as an Eigen::Vector2d.

Returns

Eigen::Vector2d with the same values as the translation.

distance()

Returns the distance between two translations.

Returns

the distance between two translations.

norm()

```
double Translation2d::norm () const
```

Returns the norm/radius/magnitude/distance from origin.

Returns

the norm of the translation.

normalize()

```
Translation2d Translation2d::normalize () const
```

returns a translation as if it were a vector with a magnitude of 1

Returns

the norm of the translation.

Returns a translation so that it has a vector magnitude of 1

Returns

the norm of the translation.

operator*() [1/2]

Returns this translation multiplied by a scalar.

$$[x] = [x] * [scalar] [y] = [y] * [scalar]$$

scalar the scalar to multiply by	
----------------------------------	--

Returns

this translation multiplied by a scalar.

operator*() [2/2]

Returns the dot product of two translations.

```
[scalar] = [x][otherx] + [y][othery]
```

Parameters

other the other translation to find the dot product with.

Returns

the scalar valued dot product.

operator+()

Returns the sum of two translations.

```
[x] = [x] + [otherx]; [y] = [y] + [othery];
```

Parameters

other the other translation to add to this translation.

Returns

the sum of the two translations.

operator-() [1/2]

```
Translation2d Translation2d::operator- () const
```

Returns the inverse of this translation. Equivalent to flipping the vector across the origin.

$$[x] = [-x][y] = [-y]$$

Returns

the inverse of this translation.

operator-() [2/2]

Returns the difference of two translations.

$$[x] = [x] - [otherx] [y] = [y] - [othery]$$

other	the translation to subtract from this translation.
-------	--

Returns

the difference of the two translations.

operator/()

Returns this translation divided by a scalar.

```
[x] = [x] / [scalar] [y] = [y] / [scalar]
```

Parameters

```
scalar the scalar to divide by.
```

Returns

this translation divided by a scalar.

operator==()

Compares two translations. Returns true if their components are each within 1e-9, to account for floating point error.

Parameters

Returns

whether the two translations are equal.

rotate_around()

Applies a rotation to this translation around another given point.

```
[x] = [\cos, -\sin][x - otherx] + [otherx][y] = [\sin, \cos][y - othery] + [othery]
```

other	the center of rotation.
rotation	the angle amount the translation will be rotated.

Returns

the translation that has been rotated.

rotate_by()

Applies a rotation to this translation around the origin.

Equivalent to multiplying a vector by a rotation matrix: $x = [\cos, -\sin][x] y = [\sin, \cos][y]$

Parameters

Г	rotation	the angle amount the translation will be rotated.
---	----------	---

Returns

the new translation that has been rotated around the origin.

setX()

Sets the x value of the translation.

setY()

Sets the y value of the translation.

theta()

```
Rotation2d Translation2d::theta () const
```

Returns the angle of the translation.

Returns

the angle of the translation.

x()

```
double Translation2d::x () const
```

Returns the x value of the translation.

Returns

the x value of the translation.

y()

```
double Translation2d::y () const
```

Returns the y value of the translation.

Returns

the y value of the translation.

5.89.4 Friends And Related Symbol Documentation

operator<<

Sends a translation to an output stream. Ex. std::cout << translation;

```
prints "Translation2d[x: (value), y: (value)]"
```

Sends a translation to an output stream. Ex. std::cout << translation;

```
prints "Translation2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- · translation2d.h
- translation2d.cpp

5.90 TrapezoidProfile Class Reference

```
#include <trapezoid_profile.h>
```

Public Member Functions

- TrapezoidProfile (const double &x_initial, const double &x_target, const double &v_max, const double &accel, const double &decel)
- motion_t calculate (double t)
- double total_time ()

5.90.1 Detailed Description

Class representing a trapezoidal motion profile. This consists of either two or three stages. First, an acceleration stage where the velocity increases to a maximum. Then a cruise stage where the velocity is constant, then a deceleration stage where the velocity decreases to zero.

This implementation allows for different acceleration and deceleration rates.

This is best used with LQR, as it tracks both velocity and position at the same time, however it can also be used with PID and feedforward.

Author

Jack Cammarata

Date

3/28/2025

5.90.2 Constructor & Destructor Documentation

TrapezoidProfile()

Constructs a TrapezoidProfile.

Parameters

x_initial	The initial position.
x_target	The target position.
v_max	The maximum velocity.
accel	The acceleration.
decel	The deceleration.

5.90.3 Member Function Documentation

calculate()

Calculate the state along the motion profile at some given time.

t The time in seconds.

Returns

the state.

Calculate the state along the motion profile after some given time.

Parameters

t The time in seconds.

Returns

the state.

total_time()

```
double TrapezoidProfile::total_time ()
```

Returns the total time that the motion profile takes to complete.

Returns

the total time that the motion profile takes to complete.

The documentation for this class was generated from the following files:

- · trapezoid_profile.h
- · trapezoid_profile.cpp

5.91 TurnDegreesCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- TurnDegreesCommand (TankDrive &drive_sys, Feedback &feedback, double degrees, double max_speed=1, double end speed=0)
- bool run () override
- void on_timeout () override

5.91.1 Detailed Description

AutoCommand wrapper class for the turn_degrees function in the TankDrive class

5.91.2 Constructor & Destructor Documentation

TurnDegreesCommand()

Construct a TurnDegreesCommand Command

Parameters

drive_sys	the drive system we are commanding			
feedback	the feedback controller we are using to execute the turn			
degrees	egrees how many degrees to rotate			
max_speed	0 -> 1 percentage of the drive systems speed to drive at			

5.91.3 Member Function Documentation

on_timeout()

```
void TurnDegreesCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we timeout

run()

```
bool TurnDegreesCommand::run () [override]
```

Run turn_degrees Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- drive_commands.h
- drive_commands.cpp

5.92 TurnToHeadingCommand Class Reference

```
#include <drive_commands.h>
```

Public Member Functions

- TurnToHeadingCommand (TankDrive &drive_sys, Feedback &feedback, double heading_deg, double speed=1, double end speed=0)
- bool run () override
- void on_timeout () override

5.92.1 Detailed Description

AutoCommand wrapper class for the turn_to_heading() function in the TankDrive class

5.92.2 Constructor & Destructor Documentation

TurnToHeadingCommand()

Construct a TurnToHeadingCommand Command

Parameters

drive_sys	the drive system we are commanding			
feedback	the feedback controller we are using to execute the drive			
heading_deg	the heading to turn to in degrees			
max_speed	0 -> 1 percentage of the drive systems speed to drive at			

5.92.3 Member Function Documentation

on_timeout()

```
void TurnToHeadingCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we don't hit our target

run()

```
bool TurnToHeadingCommand::run () [override]
```

Run turn_to_heading Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- drive_commands.h
- drive_commands.cpp

5.93 Twist2d Class Reference

```
#include <twist2d.h>
```

Public Member Functions

- constexpr Twist2d ()
- Twist2d (const double &dx, const double &dy, const double &dtheta)
- Twist2d (const Eigen::Vector3d &twist_vector)
- double dx () const
- double dy () const
- double dtheta () const
- bool operator== (const Twist2d &other) const
- Twist2d operator* (const double &scalar) const
- Twist2d operator/ (const double &scalar) const

Friends

std::ostream & operator<< (std::ostream &os, const Twist2d &twist)

5.93.1 Detailed Description

Class representing a difference between two poses, more specifically a distance along an arc from a pose.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

5.93.2 Constructor & Destructor Documentation

Twist2d() [1/3]

```
Twist2d::Twist2d () [constexpr]
```

Default Constructor for Twist2d

Twist2d() [2/3]

Constructs a twist with given translation and angle deltas.

Parameters

dx	the linear dx component.			
dy the linear dy component.				
dtheta	the angular dtheta component.			

Twist2d() [3/3]

Constructs a twist with given translation and angle deltas.

5.93.3 Member Function Documentation

dtheta()

```
double Twist2d::dtheta () const
```

Returns the angular dtheta component.

Returns

the angular dtheta component.

dx()

```
double Twist2d::dx () const
```

Returns the linear dx component.

Returns

the linear dx component.

dy()

```
double Twist2d::dy () const
```

Returns the linear dy component.

Returns

the linear dy component.

operator*()

Multiplies this twist by a scalar.

Parameters

scalar the scalar value to multiply by.

operator/()

Divides this twist by a scalar.

scalar	the scalar value to divide by.
--------	--------------------------------

operator==()

Compares this to another twist.

Parameters

other	the other twist to compare to.
-------	--------------------------------

Returns

true if each of the components are within 1e-9 of each other.

5.93.4 Friends And Related Symbol Documentation

operator<<

Sends a twist to an output stream. Ex. std::cout << twist;

```
prints "Twist2d[dx: (value), dy: (value), drad: (radians)]"
```

Sends a twist to an output stream. Ex. std::cout << twist;

```
prints "Twist2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- twist2d.h
- twist2d.cpp

5.94 WaitUntilCondition Class Reference

Waits until the condition is true.

```
#include <auto_command.h>
```

5.94.1 Detailed Description

Waits until the condition is true.

The documentation for this class was generated from the following file:

· auto_command.h

5.95 WaitUntilUpToSpeedCommand Class Reference

```
#include <flywheel_commands.h>
```

Public Member Functions

- WaitUntilUpToSpeedCommand (Flywheel &flywheel, int threshold_rpm)
- bool run () override

5.95.1 Detailed Description

AutoCommand that listens to the Flywheel and waits until it is at its target speed +/- the specified threshold

5.95.2 Constructor & Destructor Documentation

WaitUntilUpToSpeedCommand()

Creat a WaitUntilUpToSpeedCommand

Parameters

flywheel	the flywheel system we are commanding
threshold_rpm	the threshold over and under the flywheel target RPM that we define to be acceptable

5.95.3 Member Function Documentation

run()

```
bool WaitUntilUpToSpeedCommand::run () [override]
```

Run spin_manual Overrides run from AutoCommand

Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · flywheel commands.h
- flywheel_commands.cpp

Index

\sim AbstractDevice	calculate
VDP::AbstractDevice, 11	CRC32, 23
	FeedForward, 38
accel	TrapezoidProfile, 196
OdometryBase, 85	choice
add	AutoChooser, 13
CommandController, 20, 21	clear
GenericAuto, 49	InterpolatingMap< KEY, VALUE >, 52
add_async	VDP::PacketWriter, 101
GenericAuto, 49	cobs_decode
add cancel func	OdometrySerial, 93
CommandController, 21	cobs_encode
add_delay	OdometrySerial, 93
CommandController, 21	CommandController, 19
GenericAuto, 50	
add_entry	add, 20, 21
ExponentialMovingAverage, 34	add_cancel_func, 21
MovingAverage, 73	add_delay, 21
	CommandController, 20
ang_accel_deg	last_command_timed_out, 21
OdometryBase, 85	run, 22
ang_speed_deg	Condition, 22
OdometryBase, 85	config
as_vector	PID, 115
Translation2d, 189	control_continuous
Async, 12	Lift < T >, 54
auto_drive	control_manual
MecanumDrive, 64	Lift < T >, 54
auto_turn	control_setpoints
MecanumDrive, 64	Lift < T >, 55
AutoChooser, 12	Core, 1
AutoChooser, 13	correct
choice, 13	SquareRootUnscentedKalmanFilter< STATES, IN-
get_choice, 13	PUTS, OUTPUTS >, 155–157
list, 13	CRC32, 23
AutoChooser::entry_t, 33	calculate, 23
name, 33	finalize, 24
,	update, 24, 25
background_task	current_pos
OdometryBase, 82	OdometryBase, 85
BasicSolenoidSet, 14	
BasicSolenoidSet, 14	current_state
run, 14	StateMachine System, IDType, Message, de-
BasicSpinCommand, 15	lay_ms, do_log >, 161
BasicSpinCommand, 15	CustomEncoder, 25
run, 16	CustomEncoder, 25
BasicStopCommand, 16	position, 26
BasicStopCommand, 16	rotation, 26
•	setPosition, 26
run, 17	setRotation, 27
bool_or	velocity, 27
Serializer, 147	
BrakeType	degrees
TankDrive, 170	Rotation2d, 137
Branch, 17	delay_ms
ButtonWidget	VDB, 10
screen::ButtonWidget, 18	DelayCommand, 27

DelayCommand, 28	f_cos
run, 28	Rotation2d, 137
distance	f_sin_
Translation2d, 189	Rotation2d, 138
double_or	f_tan_
Serializer, 147	Rotation2d, 138
draw	Feedback, 35
screen::FunctionPage, 48	get, 36
screen::OdometryPage, 91	init, 36
screen::Page, 104	is_on_target, 36
screen::PIDPage, 121	set_limits, 37
screen::StatsPage, 163	update, 37
drive	FeedForward, 37
MecanumDrive, 65	calculate, 38
drive_arcade	FeedForward, 38
TankDrive, 171	FeedForward::ff_config_t, 39
drive_correction_cutoff	kA, 39
robot_specs_t, 135	kG, 39
drive_forward	kS, 39
TankDrive, 171, 172	kV, 40
drive_raw	fetch
MecanumDrive, 66	VDP::MotorDataRecord, 72
drive_tank	VDP::Number< NumT, schemaType >, 76
TankDrive, 172	VDP::OdometryDataRecord, 89
drive_tank_raw	VDP::PIDDataRecord, 119
TankDrive, 173	VDP::Record, 131
drive_to_point	VDP::String, 165
TankDrive, 173, 174	VDP::TimestampedRecord, 180
DriveForwardCommand, 28	FetchFunc
DriveForwardCommand, 29	VDP::Number< NumT, schemaType >, 75
on_timeout, 29	Filter, 40
run, 29	finalize
DriveStopCommand, 30	CRC32, 24
DriveStopCommand, 30	Flywheel, 40
run, 31	Flywheel, 41
DriveToPointCommand, 31	get_motors, 42
DriveToPointCommand, 31, 32	get_target, 42
run, 32	getRPM, 42
dtheta	is_on_target, 42
Twist2d, 201	Page, 42
dx	spin_manual, 42
Twist2d, 201	spin_rpm, 43
dy	SpinRpmCmd, 43
Twist2d, 201	spinRPMTask, 44
end async	stop, 43
OdometryBase, 83	WaitUntilUpToSpeedCmd, 44
error_method	FlywheelStopCommand, 44
PID::pid_config_t, 116	FlywheelStopCommand, 44
ERROR_TYPE	run, 45
PID, 111	FlywheelStopMotorsCommand, 45
exp	FlywheelStopMotorsCommand, 45
Pose2d, 123	run, 46
ExponentialMovingAverage, 33	FlywheelStopNonTasksCommand, 46
add_entry, 34	FunctionCommand, 46 FunctionCondition, 47
ExponentialMovingAverage, 34	FunctionCondition, 47 FunctionPage
get_size, 35	screen::FunctionPage, 48
get_value, 35	Screen unclionrage, 40
J ,	GenericAuto, 49

	add, 49	handle
	add_async, 49	OdometryBase, 86
	add_delay, 50	has message
	run, 50	StateMachine< System, IDType, Message, de
get		lay_ms, do_log >::MaybeMessage, 63
3	Feedback, 36	hold
	MotionController, 68	Lift< T >, 55
	PID, 112	home
	TakeBackHalf, 168	Lift< T >, 55
aet :	accel	
-	OdometryBase, 83	IfTimePassed, 51
	angular_accel_deg	init
	OdometryBase, 83	Feedback, 36
	angular_speed_deg	MotionController, 68
	OdometryBase, 83	PID, 113
	async	TakeBackHalf, 168
	Lift $<$ T $>$, 55	InOrder, 51
	choice	insert
_		InterpolatingMap< KEY, VALUE >, 52
	AutoChooser, 13	install_broadcast_callback
get_		VDP::RegistryListener< MutexType >, 133
	PID, 112	install_data_callback
_	motion	VDP::RegistryListener< MutexType >, 133
	MotionController, 68	int or
get_l	motors	Serializer, 147
	Flywheel, 42	
	output	InterpolatingMap< KEY, VALUE >, 52
	PID, 112	clear, 52
	packet	insert, 52
	VDP::PacketWriter, 101	operator[], 52
get_	points	inverse
	PurePursuit::Path, 110	Transform2d, 185
get_	pose2d	is_on_target
	OdometrySerial, 94	Feedback, 36
get_	position	Flywheel, 42
	OdometryBase, 83	MotionController, 68
	OdometrySerial, 94	PID, 113
	TankDrive, 175	TakeBackHalf, 168
get_i	radius	is_valid
	PurePursuit::Path, 110	PurePursuit::Path, 110
get_s	sensor_val	
	PID, 112	kA
get_s	setpoint	FeedForward::ff_config_t, 39
	Lift < T >, 55	kG
get_s	size	FeedForward::ff_config_t, 39
	ExponentialMovingAverage, 35	kS
	MovingAverage, 73	FeedForward::ff_config_t, 39
get :	speed	kV
_	OdometryBase, 84	FeedForward::ff_config_t, 40
	target	
	Flywheel, 42	last_command_timed_out
	PID, 113	CommandController, 21
net v	value	Lift
aor_	ExponentialMovingAverage, 35	Lift < T >, 54
	MovingAverage, 73	Lift < T >, 53
getR	-	control_continuous, 54
-	Flywheel, 42	control_manual, 54
	•	control_setpoints, 55
getV		get_async, 55
	VDP::Number< NumT, schemaType >, 76	get_setpoint, 55

hold, 55	name
home, 55	AutoChooser::entry_t, 33
Lift, 54	None
set_async, 56	TankDrive, 170
set_position, 56	norm
set_sensor_function, 56	Translation2d, 189
set_sensor_reset, 56	normalize
set_setpoint, 57	Translation2d, 189
Lift< T >::lift_cfg_t, 57	num_sigmas
list	ScaledSphericalSimplexSigmaPoints < STATES >,
AutoChooser, 13	143
Log	Number
Logger, 59, 60	VDP::Number< NumT, schemaType >, 75
log	7.
Pose2d, 124	Odometry3Wheel, 78
Logf	Odometry3Wheel, 79
Logger, 60	tune, 79
Logger, 58	update, 80
Log, 59, 60	Odometry3Wheel::odometry3wheel_cfg_t, 80
Logf, 60	off_axis_center_dist, 80
Logger, 58	wheel_diam, 80
Logln, 60, 61	wheelbase_dist, 81
Login	OdometryBase, 81
Logger, 60, 61	accel, 85
Logger, ou, or	ang_accel_deg, 85
MaybeMessage	ang_speed_deg, 85
StateMachine< System, IDType, Message, de-	background_task, 82
lay_ms, do_log >::MaybeMessage, 62	current_pos, 85
MecanumDrive, 63	end_async, 83
auto_drive, 64	get_accel, 83
auto_turn, 64	get_angular_accel_deg, 83
drive, 65	get_angular_speed_deg, 83
drive_raw, 66	get_position, 83
MecanumDrive, 64	get_speed, 84
MecanumDrive::mecanumdrive_config_t, 66	handle, 86
message	mut, 86
StateMachine < System, IDType, Message, de-	OdometryBase, 82
lay ms, do log >::MaybeMessage, 63	set_position, 84
modify_inputs	smallest_angle, 84
TankDrive, 175	speed, 86
MotionController, 67	update, 85
get, 68	OdometryControlRecord
_	VDP::OdometryControlRecord, 87
get_motion, 68	· · · · · · · · · · · · · · · · · · ·
init, 68	OdometryDataRecord
is_on_target, 68	VDP::OdometryDataRecord, 89
MotionController, 68	OdometryPage
set_limits, 69	screen::OdometryPage, 90
tune_feedforward, 69	OdometrySerial, 91
update, 70	cobs_decode, 93
MotionController::m_profile_cfg_t, 61	cobs_encode, 93
MotorDataRecord	get_pose2d, 94
VDP::MotorDataRecord, 71	get_position, 94
MovingAverage, 72	OdometrySerial, 93
add_entry, 73	receive_cobs_packet, 94
get_size, 73	send_config, 95
get_value, 73	set_position, 95
MovingAverage, 72, 73	update, 95
mut	OdometryTank, 96
OdometryBase, 86	OdometryTank, 97

set_position, 98	VDP::Part, 107
update, 98	Path
OdomSetPosition, 99	PurePursuit::Path, 109
OdomSetPosition, 99	PID, 110
run, 99	config, 115
off_axis_center_dist	ERROR_TYPE, 111
Odometry3Wheel::odometry3wheel_cfg_t, 80	get, 112
on_target_time	get_error, 112
PID::pid_config_t, 116	get_output, 112
on_timeout	get_sensor_val, 112
DriveForwardCommand, 29 PurePursuitCommand, 128	get_target, 113 init, 113
TurnDegreesCommand, 198	is_on_target, 113
TurnToHeadingCommand, 199	PID, 111
operator<	reset, 113
Pose2d, 127	set_limits, 114
Rotation2d, 142	set_target, 114
Transform2d, 187	update, 114
Translation2d, 195	PID::pid_config_t, 115
Twist2d, 202	error_method, 116
operator+	on_target_time, 116
Pose2d, 124	PIDControlRecord
Rotation2d, 138	VDP::PIDControlRecord, 117
Translation2d, 191	PIDDataRecord
operator-	VDP::PIDDataRecord, 119
Pose2d, 125	PIDPage
Rotation2d, 139	screen::PIDPage, 120
Transform2d, 185	Pose2d, 121
Translation2d, 191	exp, 123
operator/	log, 124
Pose2d, 125	operator<<, 127
Rotation2d, 139	operator+, 124
Transform2d, 185	operator-, 125
Translation2d, 193	operator/, 125
Twist2d, 201	operator==, 125
operator==	operator*, 124
Pose2d, 125	Pose2d, 122, 123
Rotation2d, 140	relative_to, 125
Transform2d, 185	rotation, 126
Translation2d, 193	setRotationDeg, 126
Twist2d, 202	setRotationRad, 126
operator[]	transform_by, 126
InterpolatingMap $<$ KEY, VALUE $>$, 52	translation, 126
operator*	x, 127
Pose2d, 124	y, 127
Rotation2d, 138	position
Transform2d, 185	CustomEncoder, 26
Translation2d, 189, 191	pprint
Twist2d, 201	VDP::Number< NumT, schemaType >, 76
Р	VDP::Part, 107
SquareRootUnscentedKalmanFilter< STATES, IN-	VDP::String, 165
PUTS, OUTPUTS >, 157	pprint_data
PacketWriter	VDP::Number< NumT, schemaType >, 76
VDP::PacketWriter, 100	VDP::Part, 107
Page	VDP::String, 165
Flywheel, 42	predict
Parallel, 105	SquareRootUnscentedKalmanFilter< STATES, IN-
Part	PUTS, OUTPUTS >, 157

pretty_print	Transform2d, 186
VDP::Part, 107	Rotation2d, 135
pretty_print_data	degrees, 137
VDP::Part, 108	f_cos, 137
pure_pursuit	f_sin, 138
TankDrive, 175	f_tan, 138
PurePursuit::hermite_point, 50	operator<<, 142
PurePursuit::Path, 109	operator+, 138
get_points, 110	operator-, 139
get_radius, 110	operator/, 139
is_valid, 110	operator==, 140
Path, 109	operator*, 138
PurePursuit::spline, 152	radians, 140
PurePursuitCommand, 128	revolutions, 140
on_timeout, 128	Rotation2d, 136, 137
PurePursuitCommand, 128	rotation_matrix, 140
run, 128	wrapped_degrees_180, 141
radians	wrapped_degrees_360, 141
Rotation2d, 140	wrapped_radians_180, 141
radius	wrapped_radians_360, 141
tracking_wheel_cfg_t, 181	wrapped_revolutions_180, 141 wrapped_revolutions_360, 142
read_data_from_message	rotation matrix
VDP::Number< NumT, schemaType >, 76	Rotation2d, 140
VDP::Part, 108	run
VDP::Record, 131	BasicSolenoidSet, 14
VDP::String, 165	BasicSpinCommand, 16
receive_cobs_packet	BasicStopCommand, 17
OdometrySerial, 94	CommandController, 22
Record	DelayCommand, 28
VDP::Record, 129, 130	DriveForwardCommand, 29
Rect, 132	DriveStopCommand, 31
register_receive_callback	DriveToPointCommand, 32
VDP::AbstractDevice, 11	FlywheelStopCommand, 45
RegistryListener	FlywheelStopMotorsCommand, 46
VDP::RegistryListener< MutexType >, 133	GenericAuto, 50
relative_to	OdomSetPosition, 99
Pose2d, 125	PurePursuitCommand, 128
reset	SpinRPMCommand, 152
PID, 113	TurnDegreesCommand, 198
SquareRootUnscentedKalmanFilter< STATES, IN-	TurnToHeadingCommand, 199
PUTS, OUTPUTS >, 158	WaitUntilUpToSpeedCommand, 203
reset_auto	
TankDrive, 176	S
response	SquareRootUnscentedKalmanFilter< STATES, IN-
VDP::OdometryControlRecord, 88	PUTS, OUTPUTS >, 158
VDP::PIDControlRecord, 118	save_to_disk
VDP::String, 166	Serializer, 148
revolutions	ScaledSphericalSimplexSigmaPoints
Rotation2d, 140	ScaledSphericalSimplexSigmaPoints < STATES >,
robot_specs_t, 134	143
drive_correction_cutoff, 135	ScaledSphericalSimplexSigmaPoints < STATES >, 142
rotate_around	num_sigmas, 143
Translation2d, 193	ScaledSphericalSimplexSigmaPoints, 143
rotate_by Translation2d_194	square_root_sigma_points, 143
Translation2d, 194 rotation	Wc, 144 Wm 144
CustomEncoder, 26	Wm, 144 screen::ButtonWidget, 18
Pose2d, 126	ButtonWidget, 18
. 55524, 125	

update, 19 screen::FunctionPage, 47	SquareRootUnscentedKalmanFilter< STATES, IN- PUTS, OUTPUTS >, 158
draw, 48	set_position
FunctionPage, 48	Lift< T >, 56
update, 48	OdometryBase, 84
screen::OdometryPage, 90	OdometrySerial, 95
draw, 91	OdometryTank, 98
OdometryPage, 90	set S
update, 91	SquareRootUnscentedKalmanFilter< STATES, IN-
screen::Page, 104	PUTS, OUTPUTS >, 158
_	
draw, 104	set_sensor_function
update, 105	Lift $<$ T $>$, 56
screen::PIDPage, 120	set_sensor_reset
draw, 121	Lift $<$ T $>$, 56
PIDPage, 120	set_setpoint
update, 121	Lift $< T >$, 57
screen::ScreenData, 145	set_string
screen::SliderWidget, 149	Serializer, 149
SliderWidget, 150	set_target
update, 150	PID, 114
screen::StatsPage, 162	set_xhat
draw, 163	SquareRootUnscentedKalmanFilter< STATES, IN-
StatsPage, 162	PUTS, OUTPUTS $>$, 159
update, 163	setFields
send_config	VDP::Record, 131
OdometrySerial, 95	setPosition
send_data	CustomEncoder, 26
VDP::RegistryListener< MutexType >, 133	setRotation
send_message	CustomEncoder, 27
StateMachine< System, IDType, Message, de-	setRotationDeg
lay_ms, do_log >, 161	Pose2d, 126
send_packet	setRotationRad
VDP::AbstractDevice, 11	Pose2d, 126
Serializer, 145	setValue
bool_or, 147	VDP::Number < NumT, schemaType >, 77
double_or, 147	VDP::String, 166
int_or, 147	setX
save_to_disk, 148	Translation2d, 194
Serializer, 146	setY
set_bool, 148	Translation2d, 194
set_double, 148	size
set_int, 148	VDP::PacketWriter, 101
set_string, 149	SliderWidget
string_or, 149	screen::SliderWidget, 150
set_async	smallest_angle
_ , Lift< T >, 56	OdometryBase, 84
set bool	Smart
Serializer, 148	TankDrive, 170
set double	speed
Serializer, 148	OdometryBase, 86
set int	spin_manual
Serializer, 148	Flywheel, 42
set_limits Feedback, 37	spin_rpm Flywheel, 43
	-
MotionController, 69	SpinRpmCmd
PID, 114 TakePeakHalf 169	Flywheel, 43
TakeBackHalf, 168	SpinRPMCommand, 151
set_P	run, 152

0 : 00110	1.1 (1.71 1.70
SpinRPMCommand, 151	drive_forward, 171, 172
spinRPMTask	drive_tank, 172
Flywheel, 44	drive_tank_raw, 173
square_root_sigma_points	drive_to_point, 173, 174
ScaledSphericalSimplexSigmaPoints < STATES >,	get_position, 175
143	modify_inputs, 175
SquareRootUnscentedKalmanFilter	None, 170
SquareRootUnscentedKalmanFilter< STATES, IN-	pure_pursuit, 175
PUTS, OUTPUTS >, 154	reset_auto, 176
SquareRootUnscentedKalmanFilter< STATES, IN-	Smart, 170
·	
PUTS, OUTPUTS >, 152	stop, 176
correct, 155–157	TankDrive, 170
P, 157	turn_degrees, 176, 177
predict, 157	turn_to_heading, 178
reset, 158	ZeroVelocity, 170
S, 158	theta
set_P, 158	Translation2d, 194
set_S, 158	theta_rad
set_xhat, 159	tracking_wheel_cfg_t, 181
SquareRootUnscentedKalmanFilter, 154	time_ms
xhat, 159	VDB, 10
StateMachine	TimestampedRecord
	VDP::TimestampedRecord, 180
StateMachine < System, IDType, Message, de-	•
lay_ms, do_log >, 161	total_time
StateMachine < System, IDType, Message, delay_ms,	TrapezoidProfile, 197
do_log >, 160	tracking_wheel_cfg_t, 181
current_state, 161	radius, 181
send_message, 161	theta_rad, 181
StateMachine, 161	x, 182
StateMachine System, IDType, Message, delay_ms,	y, 182
do_log >::MaybeMessage, 62	Transform2d, 182
has_message, 63	inverse, 185
MaybeMessage, 62	operator<<, 187
message, 63	operator-, 185
StateMachine < System, IDType, Message, delay_ms,	operator/, 185
do_log >::State, 160	operator==, 185
StatsPage	operator*, 185
-	•
screen::StatsPage, 162	rotation, 186
stop	Transform2d, 183, 184
Flywheel, 43	translation, 186
TankDrive, 176	x, 186
String	y, 186
VDP::String, 164	transform_by
string_or	Pose2d, 126
Serializer, 149	translation
submit_response	Pose2d, 126
VDP::RegistryListener< MutexType >, 134	Transform2d, 186
	Translation2d, 187
take_packet	as_vector, 189
VDP::RegistryListener< MutexType >, 134	distance, 189
TakeBackHalf, 167	norm, 189
get, 168	
init, 168	normalize, 189
•	operator<<, 195
is_on_target, 168	operator+, 191
set_limits, 168	operator-, 191
update, 169	operator/, 193
TankDrive, 169	•
D I T 170	operator==, 193
BrakeType, 170	operator==, 193 operator*, 189, 191

rotate_around, 193	VDP::AbstractDevice, 10
rotate_by, 194	\sim AbstractDevice, 11
setX, 194	register_receive_callback, 11
setY, 194	send_packet, 11
theta, 194	VDP::MotorDataRecord, 70
Translation2d, 188	fetch, 72
x, 194	MotorDataRecord, 71
y, 195	VDP::Number < NumT, schemaType >, 74
TrapezoidProfile, 195	fetch, 76
calculate, 196	FetchFunc, 75
total_time, 197	getValue, 76
TrapezoidProfile, 196	Number, 75
tune	pprint, 76
Odometry3Wheel, 79	pprint_data, 76
tune_feedforward	read_data_from_message, 76
MotionController, 69	setValue, 77
turn degrees	write message, 77
TankDrive, 176, 177	write_schema, 77
turn_to_heading	VDP::OdometryControlRecord, 86
TankDrive, 178	OdometryControlRecord, 87
TurnDegreesCommand, 197	response, 88
on_timeout, 198	VDP::OdometryDataRecord, 88
run, 198	fetch, 89
TurnDegreesCommand, 198	
	OdometryDataRecord, 89
TurnToHeadingCommand, 198	VDP::PacketHeader, 100
on_timeout, 199	VDP::PacketWriter, 100
run, 199	clear, 101
TurnToHeadingCommand, 199	get_packet, 101
Twist2d, 200	PacketWriter, 100
dtheta, 201	size, 101
dx, 201	write_byte, 101
dy, 201	write_channel_acknowledge, 101
operator<<, 202	write_channel_broadcast, 102
operator/, 201	write_data_message, 102
operator==, 202	write_number, 102
operator*, 201	write_request, 102
Twist2d, 200	write_response, 103
	write_string, 103
update	write_type, 103
CRC32, 24, 25	VDP::Part, 106
Feedback, 37	Part, 107
MotionController, 70	pprint, 107
Odometry3Wheel, 80	pprint_data, 107
OdometryBase, 85	pretty_print, 107
OdometrySerial, 95	pretty_print_data, 108
OdometryTank, 98	read data from message, 108
PID, 114	write message, 108
screen::ButtonWidget, 19	write schema, 108
screen::FunctionPage, 48	VDP::PIDControlRecord, 116
screen::OdometryPage, 91	PIDControlRecord, 117
screen::Page, 105	response, 118
screen::PIDPage, 121	VDP::PIDDataRecord, 118
screen::SliderWidget, 150	fetch, 119
screen::StatsPage, 163	PIDDataRecord, 119
TakeBackHalf, 169	VDP::Record, 129
•	fetch, 131
VDB, 10	read_data_from_message, 131
delay_ms, 10	Record, 129, 130
time_ms, 10	1160014, 120, 100

setFields, 131	VDP::PacketWriter, 102
write_message, 131	write_data_message
write schema, 132	VDP::PacketWriter, 102
VDP::RegistryListener< MutexType >, 132	write_message
install_broadcast_callback, 133	VDP::Number< NumT, schemaType >, 77
install data callback, 133	VDP::Part, 108
RegistryListener, 133	VDP::Record, 131
send_data, 133	VDP::String, 166
	_
submit_response, 134	write_number
take_packet, 134	VDP::PacketWriter, 102
VDP::String, 163	write_request
fetch, 165	VDP::PacketWriter, 102
pprint, 165	write_response
pprint_data, 165	VDP::PacketWriter, 103
read_data_from_message, 165	write_schema
response, 166	VDP::Number< NumT, schemaType >, 77
setValue, 166	VDP::Part, 108
String, 164	VDP::Record, 132
write_message, 166	VDP::String, 166
write_schema, 166	write_string
VDP::TimestampedRecord, 179	VDP::PacketWriter, 103
fetch, 180	write_type
TimestampedRecord, 180	VDP::PacketWriter, 103
velocity	Tan wondthing, 100
CustomEncoder, 27	X
Customencouci, 27	Pose2d, 127
WaitUntilCondition, 202	tracking_wheel_cfg_t, 182
WaitUntilUpToSpeedCmd	Transform2d, 186
Flywheel, 44	Translation2d, 194
WaitUntilUpToSpeedCommand, 203	xhat
run, 203	SquareRootUnscentedKalmanFilter< STATES, IN-
WaitUntilUpToSpeedCommand, 203	•
Wc	PUTS, OUTPUTS >, 159
ScaledSphericalSimplexSigmaPoints < STATES >,	V
144	Pose2d, 127
wheel_diam	tracking_wheel_cfg_t, 182
Odometry3Wheel::odometry3wheel_cfg_t, 80	Transform2d, 186
wheelbase_dist	Translation2d, 195
Odometry3Wheel::odometry3wheel_cfg_t, 81	ZoroVolo eity
Wm	Zero Velocity
ScaledSphericalSimplexSigmaPoints < STATES >,	TankDrive, 170
144	
wrapped_degrees_180	
Rotation2d, 141	
wrapped_degrees_360	
Rotation2d, 141	
wrapped_radians_180	
Rotation2d, 141	
wrapped_radians_360	
Rotation2d, 141	
wrapped_revolutions_180	
Rotation2d, 141	
wrapped_revolutions_360	
Rotation2d, 142	
write_byte	
VDP::PacketWriter, 101	
write_channel_acknowledge	
VDP::PacketWriter, 101	
write_channel_broadcast	