# RIT VEXU Core API

Generated by Doxygen 1.13.2

1	Core	1
	1.1 Getting Started	1
	1.2 Features	1
2	Hierarchical Index	2
	2.1 Class Hierarchy	2
3	Class Index	5
	3.1 Class List	5
4	Class Documentation	8
	4.1 Async Class Reference	8
	4.1.1 Detailed Description	8
	4.2 AutoChooser Class Reference	8
	4.2.1 Detailed Description	9
	4.2.2 Constructor & Destructor Documentation	9
	4.2.3 Member Function Documentation	9
	4.2.4 Member Data Documentation	10
	4.3 BasicSolenoidSet Class Reference	10
	4.3.1 Detailed Description	10
	4.3.2 Constructor & Destructor Documentation	10
	4.3.3 Member Function Documentation	11
	4.4 BasicSpinCommand Class Reference	11
	4.4.1 Detailed Description	11
	4.4.2 Constructor & Destructor Documentation	11
	4.4.3 Member Function Documentation	12
	4.5 BasicStopCommand Class Reference	12
	4.5.1 Detailed Description	12
	4.5.2 Constructor & Destructor Documentation	13
	4.5.3 Member Function Documentation	14
	4.6 Branch Class Reference	14
	4.6.1 Detailed Description	14
	4.7 screen::ButtonWidget Class Reference	15
	4.7.1 Detailed Description	15
	4.7.2 Constructor & Destructor Documentation	15
	4.7.3 Member Function Documentation	16
	4.8 CommandController Class Reference	16
	4.8.1 Detailed Description	17
	4.8.2 Constructor & Destructor Documentation	17
	4.8.3 Member Function Documentation	17
	4.9 Condition Class Reference	19
	4.9.1 Detailed Description	19
	4.10 CustomEncoder Class Reference	19

4.10.1 Detailed Description	 20
4.10.2 Constructor & Destructor Documentation	 20
4.10.3 Member Function Documentation	 20
4.11 DelayCommand Class Reference	 22
4.11.1 Detailed Description	 22
4.11.2 Constructor & Destructor Documentation	 22
4.11.3 Member Function Documentation	 22
4.12 DriveForwardCommand Class Reference	 22
4.12.1 Detailed Description	 23
4.12.2 Constructor & Destructor Documentation	 23
4.12.3 Member Function Documentation	 24
4.13 DriveStopCommand Class Reference	 24
4.13.1 Detailed Description	 24
4.13.2 Constructor & Destructor Documentation	 24
4.13.3 Member Function Documentation	 25
4.14 DriveToPointCommand Class Reference	 25
4.14.1 Detailed Description	 25
4.14.2 Constructor & Destructor Documentation	 25
4.14.3 Member Function Documentation	 26
4.15 AutoChooser::entry_t Struct Reference	 27
4.15.1 Detailed Description	 27
4.15.2 Member Data Documentation	 27
4.16 ExponentialMovingAverage Class Reference	 27
4.16.1 Detailed Description	 28
4.16.2 Constructor & Destructor Documentation	 28
4.16.3 Member Function Documentation	 28
4.17 Feedback Class Reference	 29
4.17.1 Detailed Description	 30
4.17.2 Member Function Documentation	 30
4.18 FeedForward Class Reference	 31
4.18.1 Detailed Description	 32
4.18.2 Constructor & Destructor Documentation	 32
4.18.3 Member Function Documentation	 32
4.19 FeedForward::ff_config_t Struct Reference	 33
4.19.1 Detailed Description	 33
4.19.2 Member Data Documentation	 33
4.20 Filter Class Reference	 34
4.20.1 Detailed Description	 34
4.21 Flywheel Class Reference	 34
4.21.1 Detailed Description	 35
4.21.2 Constructor & Destructor Documentation	 35
4.21.3 Member Function Documentation	 36

4.21.4 Friends And Related Symbol Documentation	38
4.22 FlywheelStopCommand Class Reference	38
4.22.1 Detailed Description	38
4.22.2 Constructor & Destructor Documentation	38
4.22.3 Member Function Documentation	39
4.23 FlywheelStopMotorsCommand Class Reference	39
4.23.1 Detailed Description	39
4.23.2 Constructor & Destructor Documentation	39
4.23.3 Member Function Documentation	40
4.24 FlywheelStopNonTasksCommand Class Reference	40
4.24.1 Detailed Description	40
4.25 FunctionCommand Class Reference	40
4.25.1 Detailed Description	40
4.26 FunctionCondition Class Reference	41
4.26.1 Detailed Description	41
4.27 screen::FunctionPage Class Reference	41
4.27.1 Detailed Description	42
4.27.2 Constructor & Destructor Documentation	42
4.27.3 Member Function Documentation	42
4.28 GenericAuto Class Reference	43
4.28.1 Detailed Description	43
4.28.2 Member Function Documentation	43
4.29 PurePursuit::hermite_point Struct Reference	44
4.29.1 Detailed Description	45
4.30 IfTimePassed Class Reference	45
4.30.1 Detailed Description	45
4.31 InOrder Class Reference	45
4.31.1 Detailed Description	45
4.32 KalmanFilter< STATES, INPUTS, OUTPUTS > Class Template Reference	46
4.32.1 Detailed Description	46
4.32.2 Constructor & Destructor Documentation	47
4.32.3 Member Function Documentation	47
4.33 Lift $<$ T $>$ Class Template Reference	51
4.33.1 Detailed Description	51
4.33.2 Constructor & Destructor Documentation	51
4.33.3 Member Function Documentation	52
4.34 Lift< T >::lift_cfg_t Struct Reference	55
4.34.1 Detailed Description	55
4.35 LinearSystem $<$ STATES, INPUTS, OUTPUTS $>$ Class Template Reference	55
4.35.1 Detailed Description	56
4.35.2 Constructor & Destructor Documentation	56
4.35.3 Member Function Documentation	56

4.36 Logger Class Reference	58
4.36.1 Detailed Description	58
4.36.2 Constructor & Destructor Documentation	58
4.36.3 Member Function Documentation	59
4.37 MotionController::m_profile_cfg_t Struct Reference	60
4.37.1 Detailed Description	61
4.38 StateMachine < System, IDType, Message, delay_ms, do_log >::MaybeMessage Class Reference .	61
4.38.1 Detailed Description	61
4.38.2 Constructor & Destructor Documentation	61
4.38.3 Member Function Documentation	62
4.39 MecanumDrive Class Reference	62
4.39.1 Detailed Description	63
4.39.2 Constructor & Destructor Documentation	63
4.39.3 Member Function Documentation	63
4.40 MecanumDrive::mecanumdrive_config_t Struct Reference	65
4.40.1 Detailed Description	66
4.41 motion_t Struct Reference	66
4.41.1 Detailed Description	66
4.42 MotionController Class Reference	66
4.42.1 Detailed Description	67
4.42.2 Constructor & Destructor Documentation	67
4.42.3 Member Function Documentation	68
4.43 MovingAverage Class Reference	70
4.43.1 Detailed Description	70
4.43.2 Constructor & Destructor Documentation	70
4.43.3 Member Function Documentation	71
4.44 Odometry3Wheel Class Reference	72
4.44.1 Detailed Description	73
4.44.2 Constructor & Destructor Documentation	74
4.44.3 Member Function Documentation	74
4.45 Odometry3Wheel::odometry3wheel_cfg_t Struct Reference	75
4.45.1 Detailed Description	75
4.45.2 Member Data Documentation	75
4.46 OdometryBase Class Reference	75
4.46.1 Detailed Description	76
4.46.2 Constructor & Destructor Documentation	76
4.46.3 Member Function Documentation	77
4.46.4 Member Data Documentation	79
4.47 screen::OdometryPage Class Reference	80
4.47.1 Detailed Description	81
4.47.2 Constructor & Destructor Documentation	81
4.47.3 Member Function Documentation	81

4.48 OdometryTank Class Reference	. 82
4.48.1 Detailed Description	. 83
4.48.2 Constructor & Destructor Documentation	. 83
4.48.3 Member Function Documentation	. 84
4.49 OdomSetPosition Class Reference	. 85
4.49.1 Detailed Description	. 85
4.49.2 Constructor & Destructor Documentation	. 85
4.49.3 Member Function Documentation	. 85
4.50 screen::Page Class Reference	. 86
4.50.1 Detailed Description	. 86
4.50.2 Member Function Documentation	. 86
4.51 Parallel Class Reference	. 87
4.51.1 Detailed Description	. 87
4.52 PurePursuit::Path Class Reference	. 87
4.52.1 Detailed Description	. 87
4.52.2 Constructor & Destructor Documentation	. 87
4.52.3 Member Function Documentation	. 88
4.53 PID Class Reference	. 88
4.53.1 Detailed Description	. 89
4.53.2 Member Enumeration Documentation	. 89
4.53.3 Constructor & Destructor Documentation	. 89
4.53.4 Member Function Documentation	. 90
4.53.5 Member Data Documentation	. 93
4.54 PID::pid_config_t Struct Reference	. 94
4.54.1 Detailed Description	. 94
4.54.2 Member Data Documentation	. 94
4.55 screen::PIDPage Class Reference	. 95
4.55.1 Detailed Description	. 95
4.55.2 Constructor & Destructor Documentation	. 95
4.55.3 Member Function Documentation	. 96
4.56 Pose2d Class Reference	. 96
4.56.1 Detailed Description	. 97
4.56.2 Constructor & Destructor Documentation	. 97
4.56.3 Member Function Documentation	. 99
4.56.4 Friends And Related Symbol Documentation	. 103
4.57 PurePursuitCommand Class Reference	. 103
4.57.1 Detailed Description	. 103
4.57.2 Constructor & Destructor Documentation	. 103
4.57.3 Member Function Documentation	. 104
4.58 Rect Struct Reference	
4.58.1 Detailed Description	. 104
4.59 robot_specs_t Struct Reference	. 104

4.59.1 Detailed Description	105
4.59.2 Member Data Documentation	105
4.60 Rotation2d Class Reference	105
4.60.1 Detailed Description	106
4.60.2 Constructor & Destructor Documentation	106
4.60.3 Member Function Documentation	107
4.60.4 Friends And Related Symbol Documentation	112
4.61 ScaledSphericalSimplexSigmaPoints < STATES > Class Template Reference	113
4.61.1 Detailed Description	113
4.61.2 Constructor & Destructor Documentation	113
4.61.3 Member Function Documentation	114
4.62 screen::ScreenData Struct Reference	115
4.62.1 Detailed Description	115
4.63 Serializer Class Reference	115
4.63.1 Detailed Description	116
4.63.2 Constructor & Destructor Documentation	116
4.63.3 Member Function Documentation	116
4.64 screen::SliderWidget Class Reference	119
4.64.1 Detailed Description	119
4.64.2 Constructor & Destructor Documentation	120
4.64.3 Member Function Documentation	120
4.65 SpinRPMCommand Class Reference	120
4.65.1 Detailed Description	
4.65.2 Constructor & Destructor Documentation	121
4.65.3 Member Function Documentation	121
4.66 PurePursuit::spline Struct Reference	121
4.66.1 Detailed Description	122
4.67 StateMachine < System, IDType, Message, delay_ms, do_log >::State Struct Reference	122
4.67.1 Detailed Description	122
4.68 StateMachine < System, IDType, Message, delay_ms, do_log > Class Template Reference	122
4.68.1 Detailed Description	123
4.68.2 Constructor & Destructor Documentation	123
4.68.3 Member Function Documentation	123
4.69 screen::StatsPage Class Reference	124
4.69.1 Detailed Description	124
4.69.2 Constructor & Destructor Documentation	124
4.69.3 Member Function Documentation	125
4.70 TakeBackHalf Class Reference	125
4.70.1 Detailed Description	
4.70.2 Member Function Documentation	
4.71 TankDrive Class Reference	128
	128

4.71.2 Member Enumeration Documentation	128
4.71.3 Constructor & Destructor Documentation	129
4.71.4 Member Function Documentation	129
4.72 tracking_wheel_cfg_t Struct Reference	137
4.72.1 Detailed Description	137
4.72.2 Member Data Documentation	138
4.73 Transform2d Class Reference	138
4.73.1 Detailed Description	139
4.73.2 Constructor & Destructor Documentation	139
4.73.3 Member Function Documentation	142
4.73.4 Friends And Related Symbol Documentation	144
4.74 Translation2d Class Reference	144
4.74.1 Detailed Description	145
4.74.2 Constructor & Destructor Documentation	145
4.74.3 Member Function Documentation	146
4.74.4 Friends And Related Symbol Documentation	151
4.75 TrapezoidProfile Class Reference	151
4.75.1 Detailed Description	152
4.75.2 Constructor & Destructor Documentation	152
4.75.3 Member Function Documentation	152
4.76 TurnDegreesCommand Class Reference	154
4.76.1 Detailed Description	154
4.76.2 Constructor & Destructor Documentation	154
4.76.3 Member Function Documentation	155
4.77 TurnToHeadingCommand Class Reference	155
4.77.1 Detailed Description	155
4.77.2 Constructor & Destructor Documentation	155
4.77.3 Member Function Documentation	156
4.78 Twist2d Class Reference	156
4.78.1 Detailed Description	157
4.78.2 Constructor & Destructor Documentation	157
4.78.3 Member Function Documentation	158
4.78.4 Friends And Related Symbol Documentation	159
4.79 UnscentedKalmanFilter < STATES, INPUTS, OUTPUTS > Class Template Reference  .  .  .  .	159
4.79.1 Detailed Description	160
4.79.2 Constructor & Destructor Documentation	161
4.79.3 Member Function Documentation	162
4.80 WaitUntilCondition Class Reference	167
4.80.1 Detailed Description	167
4.81 WaitUntilUpToSpeedCommand Class Reference	167
4.81.1 Detailed Description	167
4.81.2 Constructor & Destructor Documentation	167

1 Core 1

	4.81.3 Member Function Documentation	 	•	 •	•	•	•		 •	•	•	 •	 •	•	.07
Index															169

### Core

This is the host repository for the custom VEX libraries used by the RIT VEXU team

Automatically updated documentation is available at here. There is also a downloadable reference manual.

# 1.1 Getting Started

If you just want to start a project with Core, make a fork of the Fork Template and follow it's instructions.

To setup core for an existing project:

- 1. Create a new vex project (using the VSCode extension or other methods)
- 2. Initialize a git repository for the project
- 3. Execute git subtree add --prefix=core https://github.com/RIT-VEX-U/ $\leftarrow$ Core.git main
- 4. Update the vex Makefile (or any other build system) to know about the core files (core/src for source files, core/include for headers) (See here for an example)
- 5. Enable Eigen (Latest supported version is 3.4.0):
  - mkdir vendor
  - git submodule add <a href="https://gitlab.com/libeigen/eigen.git">https://gitlab.com/libeigen/eigen.git</a> vendor/eigen
  - cd vendor/eigen
  - git checkout 3.4.0
  - Add the following to the makefile to give Core access to the library: INC += -Ivendor/eigen (See here for an example)

If you only wish to use a single version of Core, you can simply clone core/ into your project and add the core source and header files to your makefile.

#### 1.2 Features

Here is the current feature list this repo provides:

Subsystems (See Wiki/Subsystems):

- · Tank drivetrain (user control / autonomous)
- Mecanum drivetrain (user control / autonomous)
- Odometry

- Tank (Differential)
- N-Pod
- Flywheel
- Lift
- · Custom encoders

Utilities (See Wiki/Utilites):

- PID controller
- FeedForward controller
- · Trapezoidal motion profile controller
- · Pure Pursuit
- · Generic auto program builder
- Auto program UI selector
- Mathematical classes (Vector2D, Moving Average)

# 2 Hierarchical Index

# 2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Async	8
BasicSolenoidSet	10
BasicSpinCommand	11
BasicStopCommand	12
Branch	14
screen::ButtonWidget	15
CommandController	16
Condition	19
FunctionCondition	41
IfTimePassed	45
CustomEncoder	19
DelayCommand	22
DriveForwardCommand	22

2.1 Class Hierarchy 3

DriveStopCommand	24
DriveToPointCommand	25
AutoChooser::entry_t	27
Feedback	29
MotionController	66
PID	88
TakeBackHalf	125
FeedForward	31
FeedForward::ff_config_t	33
Filter	34
Exponential Moving Average	27
MovingAverage	70
Flywheel	34
FlywheelStopCommand	38
FlywheelStopMotorsCommand	39
FlywheelStopNonTasksCommand	40
FunctionCommand	40
GenericAuto	43
PurePursuit::hermite_point	44
InOrder	45
KalmanFilter < STATES, INPUTS, OUTPUTS >	46
Lift< T >	51
Lift< T >::lift_cfg_t	55
${\bf Linear System} < {\bf STATES, INPUTS, OUTPUTS} >$	55
Logger	58
MotionController::m_profile_cfg_t	60
StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage	61
MecanumDrive	62
MecanumDrive::mecanumdrive_config_t	65
motion_t	66
Odometry3Wheel::odometry3wheel_cfg_t	75
OdometryBase	75

Odometry3Wheel	72
OdometryTank	82
OdomSetPosition	85
screen::Page	86
AutoChooser	8
screen::FunctionPage	41
screen::OdometryPage	80
screen::PIDPage	95
screen::StatsPage	124
Parallel	87
PurePursuit::Path	87
PID::pid_config_t	94
Pose2d	96
PurePursuitCommand	103
Rect	104
robot_specs_t	104
Rotation2d	105
${\bf ScaledSphericalSimplexSigmaPoints} < {\bf STATES} >$	113
screen::ScreenData	115
Serializer	115
screen::SliderWidget	119
SpinRPMCommand	120
PurePursuit::spline	121
${\bf State Machine < System,  IDType,  Message,  delay\_ms,  do\_log > :: State}$	122
${\bf State Machine < System,  IDType,  Message,  delay\_ms,  do\_log >}$	122
TankDrive	128
tracking_wheel_cfg_t	137
Transform2d	138
Translation2d	144
TrapezoidProfile	151
TurnDegreesCommand	154
TurnToHeadingCommand	155

3 Class Index 5

Twist2d	156
${\bf Unscented Kalman Filter} < {\bf STATES, INPUTS, OUTPUTS} >$	159
WaitUntilCondition	167
WaitUntilUpToSpeedCommand	167

# 3 Class Index

# 3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Async Async runs a command asynchronously will simply let it go and never look back THIS HAS A VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT	8
AutoChooser	8
BasicSolenoidSet	10
BasicSpinCommand	11
BasicStopCommand	12
Branch Branch chooses from multiple options at runtime. the function decider returns an index into the choices vector If you wish to make no choice and skip this section, return NO_CHOICE; any choice that is out of bounds set to NO_CHOICE	14
screen::ButtonWidget Widget that does something when you tap it. The function is only called once when you first tap it	15
CommandController	16
Condition	19
CustomEncoder	19
DelayCommand	22
DriveForwardCommand	22
DriveStopCommand	24
DriveToPointCommand	25
AutoChooser::entry_t	27
<b>ExponentialMovingAverage</b>	27
Feedback	29
FeedForward	31
FeedForward::ff config t	33

Filter	34
Flywheel	34
FlywheelStopCommand	38
FlywheelStopMotorsCommand	39
FlywheelStopNonTasksCommand	40
FunctionCommand	40
FunctionCondition FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime	41
screen::FunctionPage Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything	41
GenericAuto	43
PurePursuit::hermite_point	44
IfTimePassed  IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time_s	45
InOrder InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?	45
KalmanFilter < STATES, INPUTS, OUTPUTS >	46
Lift <t></t>	51
Lift< T >::lift_cfg_t	55
LinearSystem < STATES, INPUTS, OUTPUTS >	55
Logger Class to simplify writing to files	58
MotionController::m_profile_cfg_t	60
StateMachine < System, IDType, Message, delay_ms, do_log >::MaybeMessage  MaybeMessage a message of Message type or nothing MaybeMessage m = {}; // empty  MaybeMessage m = Message::EnumField1	61
MecanumDrive	62
MecanumDrive::mecanumdrive_config_t	65
motion_t	66
MotionController	66
MovingAverage	70
Odometry3Wheel	72
Odometry3Wheel::odometry3wheel_cfg_t	75

3.1 Class List 7

OdometryBase	75
screen::OdometryPage Page that shows odometry position and rotation and a map (if an sd card with the file is on)	80
OdometryTank	82
OdomSetPosition	85
screen::Page Page describes one part of the screen slideshow	86
Parallel Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on_timeout on all children continue	87
PurePursuit::Path	87
PID	88
PID::pid_config_t	94
screen::PIDPage PIDPage provides a way to tune a pid controller on the screen	95
Pose2d	96
PurePursuitCommand	103
Rect	104
robot_specs_t	104
Rotation2d	105
ScaledSphericalSimplexSigmaPoints < STATES >	113
screen::ScreenData  Holds the data that will be passed to the screen thread you probably shouldnt have to use it	115
Serializer Serializes Arbitrary data to a file on the SD Card	115
screen::SliderWidget Widget that updates a double value. Updates by reference so watch out for race conditions cuz the screen stuff lives on another thread	119
SpinRPMCommand	120
PurePursuit::spline	121
StateMachine < System, IDType, Message, delay_ms, do_log >::State	122
StateMachine < System, IDType, Message, delay_ms, do_log > State Machine :)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024 Over Under game for our overly complex intake-cata subsystem (see there for an example) The statemachine runs in a background thread and a user thread can interact with it through current_state and send_message	122
screen::StatsPage Draws motor stats and battery stats to the screen	124

TakeBackHalf	
A velocity controller	125
TankDrive	128
tracking_wheel_cfg_t	137
Transform2d	138
Translation2d	144
TrapezoidProfile	151
TurnDegreesCommand	154
TurnToHeadingCommand	155
Twist2d	156
UnscentedKalmanFilter < STATES, INPUTS, OUTPUTS >	159
WaitUntilCondition Waits until the condition is true	167
WaitUntilUpToSpeedCommand	167

# 4 Class Documentation

# 4.1 Async Class Reference

Async runs a command asynchronously will simply let it go and never look back THIS HAS A VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT.

#include <auto\_command.h>

# 4.1.1 Detailed Description

Async runs a command asynchronously will simply let it go and never look back THIS HAS A VERY NICHE USE CASE. THINK ABOUT IF YOU REALLY NEED IT.


The documentation for this class was generated from the following files:

- auto\_command.h
- auto\_command.cpp

# 4.2 AutoChooser Class Reference

#include <auto\_chooser.h>

Inheritance diagram for AutoChooser:



#### Classes

· struct entry\_t

#### **Public Member Functions**

- AutoChooser (std::vector< std::string > paths, size\_t def=0)
- size\_t get\_choice ()

#### **Protected Attributes**

- size\_t choice
- $std::vector < entry_t > list$

# 4.2.1 Detailed Description

Autochooser is a utility to make selecting robot autonomous programs easier source: RIT VexU Wiki During a season, we usually code between 4 and 6 autonomous programs. Most teams will change their entire robot program as a way of choosing autonomi but this may cause issues if you have an emergency patch to upload during a competition. This class was built as a way of using the robot screen to list autonomous programs, and the touchscreen to select them.

#### 4.2.2 Constructor & Destructor Documentation

### AutoChooser()

Initialize the auto-chooser. This class places a choice menu on the brain screen, so the driver can choose which autonomous to run.

#### **Parameters**

brain the brain on which to draw the selection boxes

#### 4.2.3 Member Function Documentation

### get\_choice()

```
size_t AutoChooser::get_choice ()
```

Get the currently selected auto choice

#### Returns

the identifier to the auto path

Return the selected autonomous

#### 4.2.4 Member Data Documentation

#### choice

```
size_t AutoChooser::choice [protected]
```

the current choice of auto

#### list

```
std::vector<entry_t> AutoChooser::list [protected]
```

< a list of all possible auto choices

The documentation for this class was generated from the following files:

- · auto\_chooser.h
- · auto\_chooser.cpp

# 4.3 BasicSolenoidSet Class Reference

```
#include <basic_command.h>
```

#### **Public Member Functions**

• BasicSolenoidSet (vex::pneumatics &solenoid, bool setting)

Construct a new BasicSolenoidSet Command.

• bool run () override

Runs the BasicSolenoidSet Overrides run command from AutoCommand.

### 4.3.1 Detailed Description

AutoCommand wrapper class for BasicSolenoidSet Using the Vex hardware functions

#### 4.3.2 Constructor & Destructor Documentation

# BasicSolenoidSet()

Construct a new BasicSolenoidSet Command.

solenoid	Solenoid being set
setting	Setting of the solenoid in boolean (true,false)

#### 4.3.3 Member Function Documentation

#### run()

```
bool BasicSolenoidSet::run () [override]
```

Runs the BasicSolenoidSet Overrides run command from AutoCommand.

#### Returns

True Command runs once

The documentation for this class was generated from the following files:

- · basic\_command.h
- · basic\_command.cpp

# 4.4 BasicSpinCommand Class Reference

```
#include <basic_command.h>
```

#### **Public Member Functions**

 BasicSpinCommand (vex::motor &motor, vex::directionType dir, BasicSpinCommand::type setting, double power)

Construct a new BasicSpinCommand.

• bool run () override

Runs the BasicSpinCommand Overrides run from Auto Command.

### 4.4.1 Detailed Description

AutoCommand wrapper class for BasicSpinCommand using the vex hardware functions

# 4.4.2 Constructor & Destructor Documentation

#### BasicSpinCommand()

```
BasicSpinCommand::BasicSpinCommand (
    vex::motor & motor,
    vex::directionType dir,
    BasicSpinCommand::type setting,
    double power)
```

Construct a new BasicSpinCommand.

a BasicMotorSpin Command

motor	Motor to spin
direc	Direction of motor spin
setting	Power setting in volts,percentage,velocity
power	Value of desired power
motor	Motor port to spin
dir	Direction for spining
setting	Power setting in volts,percentage,velocity
power	Value of desired power

#### 4.4.3 Member Function Documentation

#### run()

```
bool BasicSpinCommand::run () [override]
```

Runs the BasicSpinCommand Overrides run from Auto Command.

Run the BasicSpinCommand Overrides run from Auto Command.

#### Returns

True Async running command

True Command runs once

The documentation for this class was generated from the following files:

- · basic\_command.h
- · basic\_command.cpp

# 4.5 BasicStopCommand Class Reference

```
#include <basic_command.h>
```

#### **Public Member Functions**

BasicStopCommand (vex::motor &motor, vex::brakeType setting)

Construct a new BasicMotorStop Command.

• bool run () override

Runs the BasicMotorStop Command Overrides run command from AutoCommand.

# 4.5.1 Detailed Description

AutoCommand wrapper class for BasicStopCommand Using the Vex hardware functions

### 4.5.2 Constructor & Destructor Documentation

# BasicStopCommand()

Construct a new BasicMotorStop Command.

Construct a BasicMotorStop Command.

motor	The motor to stop
setting	The brake setting for the motor
motor	Motor to stop
setting	Braketype setting brake,coast,hold

#### 4.5.3 Member Function Documentation

### run()

```
bool BasicStopCommand::run () [override]
```

Runs the BasicMotorStop Command Overrides run command from AutoCommand.

Runs the BasicMotorStop command Ovverides run command from AutoCommand.

#### Returns

True Command runs once

The documentation for this class was generated from the following files:

- · basic\_command.h
- · basic\_command.cpp

# 4.6 Branch Class Reference

Branch chooses from multiple options at runtime. the function decider returns an index into the choices vector If you wish to make no choice and skip this section, return NO\_CHOICE; any choice that is out of bounds set to NO\_CHOICE.

```
#include <auto_command.h>
```

#### 4.6.1 Detailed Description

Branch chooses from multiple options at runtime. the function decider returns an index into the choices vector If you wish to make no choice and skip this section, return NO\_CHOICE; any choice that is out of bounds set to NO\_CHOICE.

The documentation for this class was generated from the following files:

- · auto\_command.h
- · auto\_command.cpp

# 4.7 screen::ButtonWidget Class Reference

Widget that does something when you tap it. The function is only called once when you first tap it.

```
#include <screen.h>
```

#### **Public Member Functions**

- ButtonWidget (std::function < void(void) > onpress, Rect rect, std::string name)

  Create a Button widget.
- ButtonWidget (void(\*onpress)(), Rect rect, std::string name)

Create a Button widget.

• bool update (bool was\_pressed, int x, int y)

responds to user input

• void **draw** (vex::brain::lcd &, bool first\_draw, unsigned int frame\_number)

draws the button to the screen

### 4.7.1 Detailed Description

Widget that does something when you tap it. The function is only called once when you first tap it.

#### 4.7.2 Constructor & Destructor Documentation

# ButtonWidget() [1/2]

```
screen::ButtonWidget::ButtonWidget (
          std::function< void(void)> onpress,
          Rect rect,
          std::string name) [inline]
```

Create a Button widget.

#### **Parameters**

onpress	the function to be called when the button is tapped
rect	the area the button should take up on the screen
name	the label put on the button

# ButtonWidget() [2/2]

Create a Button widget.

onpress	the function to be called when the button is tapped
rect	the area the button should take up on the screen
name	the label put on the button

#### 4.7.3 Member Function Documentation

#### update()

```
bool screen::ButtonWidget::update ( bool \ was\_pressed, int \ x, int \ y)
```

#### responds to user input

#### **Parameters**

was_pressed	if the screen is pressed
X	x position if the screen was pressed
У	y position if the screen was pressed

### Returns

true if the button was pressed

The documentation for this class was generated from the following files:

- screen.h
- · screen.cpp

#### 4.8 CommandController Class Reference

```
#include <command_controller.h>
```

#### **Public Member Functions**

• CommandController ()

Create an empty CommandController. Add Command with CommandController::add()

CommandController (std::initializer\_list< AutoCommand \* > cmds)

Create a CommandController with commands pre added. More can be added with CommandController::add()

- void add (std::vector< AutoCommand \* > cmds)
- void add (AutoCommand \*cmd, double timeout\_seconds=10.0)
- void add (std::vector< AutoCommand \* > cmds, double timeout\_sec)
- void add\_delay (int ms)
- void add\_cancel\_func (std::function< bool(void)> true\_if\_cancel)

add\_cancel\_func specifies that when this func evaluates to true, to cancel the command controller

- void run ()
- bool last\_command\_timed\_out ()

#### 4.8.1 Detailed Description

File: command\_controller.h Desc: A CommandController manages the AutoCommands that make up an autonomous route. The AutoCommands are kept in a queue and get executed and removed from the queue in FIFO order.

#### 4.8.2 Constructor & Destructor Documentation

#### CommandController()

```
\label{lem:commandController} CommandController \mbox{ (} \\ std::initializer\_list<\mbox{ AutoCommand } * > cmds) \mbox{ [inline]}
```

Create a CommandController with commands pre added. More can be added with CommandController::add()

#### **Parameters**

cmds

#### 4.8.3 Member Function Documentation

### add() [1/3]

File: command\_controller.cpp Desc: A CommandController manages the AutoCommands that make up an autonomous route. The AutoCommands are kept in a queue and get executed and removed from the queue in FIFO order. Adds a command to the queue

#### **Parameters**

cmd	the AutoCommand we want to add to our list
timeout_seconds	the number of seconds we will let the command run for. If it exceeds this, we cancel it and
	run on_timeout

# add() [2/3]

```
void CommandController::add ( {\tt std::vector} < {\tt AutoCommand} \ * \ > \ cmds)
```

### Adds a command to the queue

#### **Parameters**

cmd	the AutoCommand we want to add to our list
timeout_seconds	the number of seconds we will let the command run for. If it exceeds this, we cancel it and
	run on_timeout. if it is $\leq$ = 0 no time out will be applied

Add multiple commands to the queue. No timeout here.

the AutoCommands we want to add to our list
---

# add() [3/3]

```
void CommandController::add (
          std::vector< AutoCommand * > cmds,
          double timeout_sec)
```

Add multiple commands to the queue. No timeout here.

#### **Parameters**

cmds	the AutoCommands we want to add to our list Add multiple commands to the queue. No timeout here.
cmds	the AutoCommands we want to add to our list
timeout_sec	timeout in seconds to apply to all commands if they are still the default

Add multiple commands to the queue. No timeout here.

#### **Parameters**

cmds	the AutoCommands we want to add to our list
timeout	timeout in seconds to apply to all commands if they are still the default

# add\_cancel\_func()

add\_cancel\_func specifies that when this func evaluates to true, to cancel the command controller

#### **Parameters**

# add\_delay()

Adds a command that will delay progression of the queue

### **Parameters**

ms - number of milliseconds to wait before continuing execution of autonomous

### last\_command\_timed\_out()

```
bool CommandController::last_command_timed_out ()
```

last\_command\_timed\_out tells how the last command ended Use this if you want to make decisions based on the end of the last command

Returns

true if the last command timed out. false if it finished regularly

### run()

```
void CommandController::run ()
```

Begin execution of the queue Execute and remove commands in FIFO order


The documentation for this class was generated from the following files:

- command\_controller.h
- · command\_controller.cpp

#### 4.9 Condition Class Reference

```
#include <auto_command.h>
```

Inheritance diagram for Condition:



#### 4.9.1 Detailed Description

File: auto\_command.h Desc: Interface for module-specifc commands A Condition is a function that returns true or false is\_even is a predicate that would return true if a number is even For our purposes, a Condition is a choice to be made at runtime drive\_sys.reached\_point(10, 30) is a predicate time.has\_elapsed(10, vex::seconds) is a predicate extend this class for different choices you wish to make

The documentation for this class was generated from the following files:

- · auto command.h
- · auto\_command.cpp

### 4.10 CustomEncoder Class Reference

#include <custom\_encoder.h>

#### **Public Member Functions**

- CustomEncoder (vex::triport::port &port, double ticks per rev)
- void setRotation (double val, vex::rotationUnits units)
- void setPosition (double val, vex::rotationUnits units)
- double rotation (vex::rotationUnits units)
- double position (vex::rotationUnits units)
- double velocity (vex::velocityUnits units)

#### 4.10.1 Detailed Description

A wrapper class for the vex encoder that allows the use of 3rd party encoders with different tick-per-revolution values.

#### 4.10.2 Constructor & Destructor Documentation

#### CustomEncoder()

Construct an encoder with a custom number of ticks

#### **Parameters**

port	the triport port on the brain the encoder is plugged into
ticks_per_rev	the number of ticks the encoder will report for one revolution

#### 4.10.3 Member Function Documentation

### position()

get the position that the encoder is at

### Parameters

units	the unit we want the return value to be in

### Returns

the position of the encoder in the units specified

#### rotation()

get the rotation that the encoder is at

units the unit we want the return value to	be in
--	-------

### Returns

the rotation of the encoder in the units specified

# setPosition()

sets the stored position of the encoder. Any further movements will be from this value

#### **Parameters**

val	the numerical value of the position we are setting to
units	the unit of val

### setRotation()

sets the stored rotation of the encoder. Any further movements will be from this value

### **Parameters**

val	the numerical value of the angle we are setting to
units	the unit of val

### velocity()

get the velocity that the encoder is moving at

### **Parameters**

### Returns

the velocity of the encoder in the units specified

The documentation for this class was generated from the following files:

- custom\_encoder.h
- custom\_encoder.cpp

# 4.11 DelayCommand Class Reference

```
#include <delay_command.h>
```

#### **Public Member Functions**

- DelayCommand (int ms)
- bool run () override

#### 4.11.1 Detailed Description

File: delay\_command.h Desc: A DelayCommand will make the robot wait the set amount of milliseconds before continuing execution of the autonomous route

#### 4.11.2 Constructor & Destructor Documentation

# DelayCommand()

# Construct a delay command

#### **Parameters**

ms the number of milliseconds to delay for

### 4.11.3 Member Function Documentation

# run()

```
bool DelayCommand::run () [inline], [override]
```

Delays for the amount of milliseconds stored in the command Overrides run from AutoCommand

#### Returns

true when complete

The documentation for this class was generated from the following file:

· delay\_command.h

### 4.12 DriveForwardCommand Class Reference

```
#include <drive_commands.h>
```

#### **Public Member Functions**

- DriveForwardCommand (TankDrive &drive\_sys, Feedback &feedback, double inches, directionType dir, double max\_speed=1, double end\_speed=0)
- bool run () override
- · void on\_timeout () override

### 4.12.1 Detailed Description

AutoCommand wrapper class for the drive\_forward function in the TankDrive class

#### 4.12.2 Constructor & Destructor Documentation

### DriveForwardCommand()

File: drive\_commands.h Desc: Holds all the AutoCommand subclasses that wrap (currently) TankDrive functions

#### Currently includes:

- · drive\_forward
- · turn\_degrees
- · drive to point
- · turn\_to\_heading
- stop

Also holds AutoCommand subclasses that wrap OdometryBase functions

Currently includes:

· set\_position Construct a DriveForward Command

#### **Parameters**

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the drive
inches	how far forward to drive
dir	the direction to drive
max_speed	0 -> 1 percentage of the drive systems speed to drive at

#### 4.12.3 Member Function Documentation

### on\_timeout()

```
void DriveForwardCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we timeout

### run()

```
bool DriveForwardCommand::run () [override]
```

Run drive\_forward Overrides run from AutoCommand

#### Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive\_commands.h
- drive\_commands.cpp

### 4.13 DriveStopCommand Class Reference

```
#include <drive_commands.h>
```

#### **Public Member Functions**

- DriveStopCommand (TankDrive &drive\_sys)
- bool run () override

### 4.13.1 Detailed Description

AutoCommand wrapper class for the stop() function in the TankDrive class

### 4.13.2 Constructor & Destructor Documentation

# DriveStopCommand()

Construct a DriveStop Command

drive_sys the drive system we are comman	ıg
--	----

#### 4.13.3 Member Function Documentation

#### run()

```
bool DriveStopCommand::run () [override]
```

Stop the drive system Overrides run from AutoCommand

#### Returns

true when execution is complete, false otherwise

Stop the drive train Overrides run from AutoCommand

#### Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive\_commands.h
- · drive commands.cpp

#### 4.14 DriveToPointCommand Class Reference

```
#include <drive_commands.h>
```

### **Public Member Functions**

- DriveToPointCommand (TankDrive &drive\_sys, Feedback &feedback, double x, double y, directionType dir, double max\_speed=1, double end\_speed=0)
- DriveToPointCommand (TankDrive &drive\_sys, Feedback &feedback, Translation2d translation, directionType dir, double max\_speed=1, double end\_speed=0)
- bool run () override

### 4.14.1 Detailed Description

AutoCommand wrapper class for the drive\_to\_point function in the TankDrive class

#### 4.14.2 Constructor & Destructor Documentation

### DriveToPointCommand() [1/2]

### Construct a DriveForward Command

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the drive
X	where to drive in the x dimension
У	where to drive in the y dimension
dir	the direction to drive
max_speed	0 -> 1 percentage of the drive systems speed to drive at

# DriveToPointCommand() [2/2]

### Construct a DriveForward Command

### **Parameters**

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the drive
translation	the point to drive to
dir	the direction to drive
max_speed	0 -> 1 percentage of the drive systems speed to drive at

# 4.14.3 Member Function Documentation

### run()

```
bool DriveToPointCommand::run () [override]
```

Run drive\_to\_point Overrides run from AutoCommand

### Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- drive\_commands.h
- drive\_commands.cpp

# 4.15 AutoChooser::entry\_t Struct Reference

#include <auto\_chooser.h>

#### **Public Attributes**

• std::string name

### 4.15.1 Detailed Description

entry\_t is a datatype used to store information that the chooser knows about an auto selection button

#### 4.15.2 Member Data Documentation

#### name

```
std::string AutoChooser::entry_t::name
```

name of the auto repretsented by the block


The documentation for this struct was generated from the following file:

· auto\_chooser.h

### 4.16 Exponential Moving Average Class Reference

```
#include <moving_average.h>
```

Inheritance diagram for ExponentialMovingAverage:



#### **Public Member Functions**

- ExponentialMovingAverage (int buffer\_size)
- ExponentialMovingAverage (int buffer\_size, double starting\_value)
- · void add\_entry (double n) override
- double get\_value () const override
- int get\_size ()

#### 4.16.1 Detailed Description

### ExponentialMovingAverage

An exponential moving average is a way of smoothing out noisy data. For many sensor readings, the noise is roughly symmetric around the actual value. This means that if you collect enough samples those that are too high are cancelled out by the samples that are too low leaving the real value.

A simple mobing average lags significantly with time as it has to counteract old samples. An exponential moving average keeps more up to date by weighting newer readings higher than older readings so it is more up to date while also still smoothed.

The ExponentialMovingAverage class provides an simple interface to do this smoothing from our noisy sensor values.

#### 4.16.2 Constructor & Destructor Documentation

### ExponentialMovingAverage() [1/2]

Create a moving average calculator with 0 as the default value

#### **Parameters**

buffer_size	The size of the buffer. The number of samples that constitute a valid reading
-------------	---

# ExponentialMovingAverage() [2/2]

Create a moving average calculator with a specified default value

#### **Parameters**

buffer_size	The size of the buffer. The number of samples that constitute a valid reading
starting_value	The value that the average will be before any data is added

### 4.16.3 Member Function Documentation

#### add\_entry()

Add a reading to the buffer Before: [ 1 1 2 2 3 3] => 2  $^{\land}$  After: [ 2 1 2 2 3 3] => 2.16  $^{\land}$ 

n the sample that will be added to the moving average.

Implements Filter.

# get\_size()

```
int ExponentialMovingAverage::get_size ()
```

How many samples the average is made from

# Returns

the number of samples used to calculate this average

# get\_value()

```
double ExponentialMovingAverage::get_value () const [override], [virtual]
```

Returns the average based off of all the samples collected so far

# Returns

the calculated average. sum(samples)/numsamples

How many samples the average is made from

### Returns

the number of samples used to calculate this average

Implements Filter.


The documentation for this class was generated from the following files:

- · moving\_average.h
- · moving\_average.cpp

# 4.17 Feedback Class Reference

```
#include <feedback_base.h>
```

Inheritance diagram for Feedback:



# **Public Member Functions**

- virtual void init (double start\_pt, double set\_pt)=0
- virtual double update (double val)=0
- virtual double get ()=0
- virtual void set\_limits (double lower, double upper)=0
- virtual bool is\_on\_target ()=0

# 4.17.1 Detailed Description

Interface so that subsystems can easily switch between feedback loops

**Author** 

Ryan McGee

Date

9/25/2022

#### 4.17.2 Member Function Documentation

# get()

```
virtual double Feedback::get () [pure virtual]
```

# Returns

the last saved result from the feedback controller

Implemented in MotionController, PID, and TakeBackHalf.

# init()

Initialize the feedback controller for a movement

### **Parameters**

start_pt	the current sensor value	
set_pt	where the sensor value should be	
start_vel	vel Movement starting velocity	
end_vel	Movement ending velocity	

Implemented in MotionController, PID, and TakeBackHalf.

# is\_on\_target()

```
virtual bool Feedback::is_on_target () [pure virtual]
```

#### Returns

true if the feedback controller has reached it's setpoint

Implemented in MotionController, PID, and TakeBackHalf.

# set\_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

#### **Parameters**

lower	Upper limit
upper	Lower limit

Implemented in MotionController, PID, and TakeBackHalf.

### update()

Iterate the feedback loop once with an updated sensor value

### **Parameters**

val	value from the sensor
vai	value II UIII lile SeliSUI

# Returns

feedback loop result

Implemented in MotionController, PID, and TakeBackHalf.

The documentation for this class was generated from the following file:

· feedback\_base.h

# 4.18 FeedForward Class Reference

#include <feedforward.h>

#### **Classes**

· struct ff\_config\_t

#### **Public Member Functions**

- FeedForward (ff\_config\_t &cfg)
- double calculate (double v, double a, double pid ref=0.0)

Perform the feedforward calculation.

# 4.18.1 Detailed Description

#### FeedForward

Stores the feedfoward constants, and allows for quick computation. Feedfoward should be used in systems that require smooth precise movements and have high inertia, such as drivetrains and lifts.

This is best used alongside a PID loop, with the form: output = pid.get() + feedforward.calculate(v, a);

In this case, the feedforward does the majority of the heavy lifting, and the pid loop only corrects for inconsistencies

For information about tuning feedforward, I reccommend looking at this post: https://www. $\leftarrow$ chiefdelphi.com/t/paper-frc-drivetrain-characterization/160915 (yes I know it's for FRC but trust me, it's useful)

**Author** 

Ryan McGee

Date

6/13/2022

### 4.18.2 Constructor & Destructor Documentation

# FeedForward()

Creates a FeedForward object.

# **Parameters**

```
cfg | Configuration Struct for tuning
```

# 4.18.3 Member Function Documentation

### calculate()

Perform the feedforward calculation.

This calculation is the equation: F = kG + kS\*sgn(v) + kV\*v + kA\*a

V	Requested velocity of system
а	Requested acceleration of system

#### Returns

A feedforward that should closely represent the system if tuned correctly

The documentation for this class was generated from the following file:

· feedforward.h

# 4.19 FeedForward::ff\_config\_t Struct Reference

#include <feedforward.h>

#### **Public Attributes**

- double kS
- double kV
- double kA
- double kG

### 4.19.1 Detailed Description

ff\_config\_t holds the parameters to make the theoretical model of a real world system equation is of the form kS if the system is not stopped, 0 otherwise

- kV \* desired velocity
- · kA \* desired acceleration
- kG

#### 4.19.2 Member Data Documentation

#### kΑ

double FeedForward::ff\_config\_t::kA

kA - Acceleration coefficient: the power required to change the mechanism's speed. Multiplied by the requested acceleration.

# kG

double FeedForward::ff\_config\_t::kG

kG - Gravity coefficient: only needed for lifts. The power required to overcome gravity and stay at steady state.

# kS

```
double FeedForward::ff_config_t::kS
```

Coefficient to overcome static friction: the point at which the motor *starts* to move.

#### k۷

```
double FeedForward::ff_config_t::kV
```

Veclocity coefficient: the power required to keep the mechanism in motion. Multiplied by the requested velocity.


The documentation for this struct was generated from the following file:

· feedforward.h

# 4.20 Filter Class Reference

```
#include <moving_average.h>
```

Inheritance diagram for Filter:



# 4.20.1 Detailed Description

Interface for filters Use add\_entry to supply data and get\_value to retrieve the filtered value

The documentation for this class was generated from the following file:

· moving\_average.h

# 4.21 Flywheel Class Reference

#include <flywheel.h>

#### **Public Member Functions**

- Flywheel (vex::motor\_group &motors, Feedback &feedback, FeedForward &helper, const double ratio, Filter &filt)
- double get\_target () const
- double getRPM () const
- vex::motor\_group & get\_motors () const
- void spin\_manual (double speed, directionType dir=fwd)
- void spin\_rpm (double rpm)
- void stop ()
- bool is\_on\_target ()

check if the feedback controller thinks the flywheel is on target

• screen::Page \* Page () const

Creates a page displaying info about the flywheel.

AutoCommand \* SpinRpmCmd (int rpm)

Creates a new auto command to spin the flywheel at the desired velocity.

AutoCommand \* WaitUntilUpToSpeedCmd ()

Creates a new auto command that will hold until the flywheel has its target as defined by its feedback controller.

#### **Friends**

• int spinRPMTask (void \*wheelPointer)

# 4.21.1 Detailed Description

a Flywheel class that handles all control of a high inertia spinning disk It gives multiple options for what control system to use in order to control wheel velocity and functions alerting the user when the flywheel is up to speed. Flywheel is a set and forget class. Once you create it you can call spin\_rpm or stop on it at any time and it will take all necessary steps to accomplish this

#### 4.21.2 Constructor & Destructor Documentation

# Flywheel()

Create the Flywheel object using PID + feedforward for control.

# Parameters

motors	pointer to the motors on the fly wheel
feedback	a feedback controleller
helper	a feedforward config (only kV is used) to help the feedback controller along
ratio	ratio of the gears from the motor to the flywheel just multiplies the velocity
filter	the filter to use to smooth noisy motor readings

#### 4.21.3 Member Function Documentation

```
get_motors()
```

```
motor_group & Flywheel::get_motors () const
```

Returns the motors

Returns

the motors used to run the flywheel

# get\_target()

```
double Flywheel::get_target () const
```

Return the target\_rpm that the flywheel is currently trying to achieve

Returns

target\_rpm the target rpm

Return the current value that the target\_rpm should be set to

# getRPM()

```
double Flywheel::getRPM () const
```

return the velocity of the flywheel

# is\_on\_target()

```
bool Flywheel::is_on_target () [inline]
```

check if the feedback controller thinks the flywheel is on target

Returns

true if on target

# Page()

```
screen::Page * Flywheel::Page () const
```

Creates a page displaying info about the flywheel.

Returns

the page should be used for `screen::start\_screen(screen, {fw.Page()});

# spin\_manual()

Spin motors using voltage; defaults forward at 12 volts FOR USE BY OPCONTROL AND AUTONOMOUS - this only applies if the target\_rpm thread is not running

speed	- speed (between -1 and 1) to set the motor
dir	- direction that the motor moves in; defaults to forward

Spin motors using voltage; defaults forward at 12 volts FOR USE BY OPCONTROL AND AUTONOMOUS - this only applies if the RPM thread is not running

# **Parameters**

speed	- speed (between -1 and 1) to set the motor
dir	- direction that the motor moves in; defaults to forward

# spin\_rpm()

starts or sets the target\_rpm thread at new value what control scheme is dependent on control\_style

#### **Parameters**

	rpm	- the target_rpm we want to spin at	
--	-----	-------------------------------------	--

starts or sets the RPM thread at new value what control scheme is dependent on control\_style

#### **Parameters**

```
input_rpm - set the current RPM
```

# SpinRpmCmd()

Creates a new auto command to spin the flywheel at the desired velocity.

# Parameters

rpm	the rpm to spin at

### Returns

an auto command to add to a command controller

# stop()

```
void Flywheel::stop ()
```

Stops the motors. If manually spinning, this will do nothing just call spin\_mainual(0.0) to send 0 volts stop the RPM thread and the wheel

# WaitUntilUpToSpeedCmd()

```
AutoCommand * Flywheel::WaitUntilUpToSpeedCmd () [inline]
```

Creates a new auto command that will hold until the flywheel has its target as defined by its feedback controller.

#### Returns

an auto command to add to a command controller

# 4.21.4 Friends And Related Symbol Documentation

# spinRPMTask

Runs a thread that keeps track of updating flywheel RPM and controlling it accordingly

The documentation for this class was generated from the following files:

- flywheel.h
- · flywheel.cpp

# 4.22 FlywheelStopCommand Class Reference

```
#include <flywheel_commands.h>
```

# **Public Member Functions**

- FlywheelStopCommand (Flywheel &flywheel)
- bool run () override

### 4.22.1 Detailed Description

AutoCommand wrapper class for the stop function in the Flywheel class

#### 4.22.2 Constructor & Destructor Documentation

# FlywheelStopCommand()

```
\label{limits} FlywheelStopCommand:: FlywheelStopCommand ( \\ Flywheel \& flywheel)
```

Construct a FlywheelStopCommand

flywheel the flywheel system we are commanding

# 4.22.3 Member Function Documentation

# run()

```
bool FlywheelStopCommand::run () [override]
```

Run stop Overrides run from AutoCommand

# Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- flywheel\_commands.h
- flywheel\_commands.cpp

# 4.23 FlywheelStopMotorsCommand Class Reference

```
#include <flywheel_commands.h>
```

#### **Public Member Functions**

- FlywheelStopMotorsCommand (Flywheel &flywheel)
- bool run () override

# 4.23.1 Detailed Description

AutoCommand wrapper class for the stopMotors function in the Flywheel class

# 4.23.2 Constructor & Destructor Documentation

# FlywheelStopMotorsCommand()

Construct a FlywheeStopMotors Command

flywheel	the flywheel system we are commanding

#### 4.23.3 Member Function Documentation

#### run()

bool FlywheelStopMotorsCommand::run () [override]

Run stop Overrides run from AutoCommand

#### Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · flywheel commands.h
- flywheel\_commands.cpp

# 4.24 FlywheelStopNonTasksCommand Class Reference

#include <flywheel\_commands.h>

# 4.24.1 Detailed Description

AutoCommand wrapper class for the stopNonTasks function in the Flywheel class

The documentation for this class was generated from the following files:

- flywheel\_commands.h
- flywheel\_commands.cpp

# 4.25 FunctionCommand Class Reference

#include <auto\_command.h>

# 4.25.1 Detailed Description

FunctionCommand is fun and good way to do simple things Printing, launching nukes, and other quick and dirty one time things

The documentation for this class was generated from the following file:


auto\_command.h

# 4.26 FunctionCondition Class Reference

FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime.

```
#include <auto_command.h>
```

Inheritance diagram for FunctionCondition:



# 4.26.1 Detailed Description

FunctionCondition is a quick and dirty Condition to wrap some expression that should be evaluated at runtime.

The documentation for this class was generated from the following files:


- · auto command.h
- · auto\_command.cpp

# 4.27 screen::FunctionPage Class Reference

Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything.

```
#include <screen.h>
```

Inheritance diagram for screen::FunctionPage:



# **Public Member Functions**

- FunctionPage (update\_func\_t update\_f, draw\_func\_t draw\_t)
   Creates a function page.
- void update (bool was\_pressed, int x, int y) override
   update uses the supplied update function to update this page
- void draw (vex::brain::lcd &, bool first\_draw, unsigned int frame\_number) override

draw uses the supplied draw function to draw to the screen

# 4.27.1 Detailed Description

Simple page that stores no internal data. the draw and update functions use only global data rather than storing anything.

# 4.27.2 Constructor & Destructor Documentation

# FunctionPage()

Creates a function page.

# FunctionPage.

#### **Parameters**

update←	the function called every tick to respond to user input or do data collection
_f	
draw_t	the function called to draw to the screen
update⇔	drawing function
_f	
draw_f	drawing function

#### 4.27.3 Member Function Documentation

# draw()

draw uses the supplied draw function to draw to the screen

#### See also

Page::draw

Reimplemented from screen::Page.

# update()

update uses the supplied update function to update this page

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:

- · screen.h
- · screen.cpp

# 4.28 GenericAuto Class Reference

```
#include <generic_auto.h>
```

#### **Public Member Functions**

- bool run (bool blocking)
- void add (state ptr new state)
- void add\_async (state\_ptr async\_state)
- void add\_delay (int ms)

# 4.28.1 Detailed Description

GenericAuto provides a pleasant interface for organizing an auto path steps of the path can be added with add() and when ready, calling run() will begin executing the path

### 4.28.2 Member Function Documentation

# add()

Add a new state to the autonomous via function point of type "bool (ptr\*)()"

### **Parameters**

```
new_state the function to run
```

#### add async()

Add a new state to the autonomous via function point of type "bool (ptr\*)()" that will run asynchronously

# add\_delay()

```
void GenericAuto::add_delay (
          int ms)
```

add\_delay adds a period where the auto system will simply wait for the specified time

#### **Parameters**

ms	how long to wait in milliseconds
----	----------------------------------

#### run()

```
bool GenericAuto::run (
          bool blocking)
```

The method that runs the autonomous. If 'blocking' is true, then this method will run through every state until it finished.

If blocking is false, then assuming every state is also non-blocking, the method will run through the current state in the list and return immediately.

#### **Parameters**

blocking	Whether or not to block the thread until all states have run
----------	--

# Returns

true after all states have finished.

The documentation for this class was generated from the following files:

- generic\_auto.h
- generic\_auto.cpp

# 4.29 PurePursuit::hermite\_point Struct Reference

```
#include <pure_pursuit.h>
```

# 4.29.1 Detailed Description

a position along the hermite path contains a position and orientation information that the robot would be at at this point

The documentation for this struct was generated from the following file:

· pure pursuit.h

#### 4.30 IfTimePassed Class Reference

IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time\_s.

```
#include <auto_command.h>
```

Inheritance diagram for IfTimePassed:



#### 4.30.1 Detailed Description

IfTimePassed tests based on time since the command controller was constructed. Returns true if elapsed time > time s.

The documentation for this class was generated from the following files:

- · auto command.h
- · auto\_command.cpp

# 4.31 InOrder Class Reference

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

```
#include <auto_command.h>
```

#### 4.31.1 Detailed Description

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

InOrder runs its commands sequentially then continues. How to handle timeout in this case. Automatically set it to sum of commands timouts?

The documentation for this class was generated from the following files:

- auto\_command.h
- auto\_command.cpp

# 4.32 KalmanFilter < STATES, INPUTS, OUTPUTS > Class Template Reference

#include <kalman\_filter.h>

#### **Public Member Functions**

- KalmanFilter (const LinearSystem &plant, const StateVector &state\_stddevs, const OutputVector &measurement\_stddevs)
- KalmanFilter (const StateMatrix &A, const InputMatrix &B, const EMat< OUTPUTS, STATES > &C, const EMat< OUTPUTS, INPUTS > &D, const StateVector &state\_stddevs, const OutputVector &measurement← \_stddevs)
- const StateMatrix & S () const
- double S (int i, int j) const
- void set\_S (const StateMatrix &S)
- StateMatrix P () const
- void set P (const StateMatrix &P)
- const StateVector & xhat () const
- · double xhat (int i) const
- void set\_xhat (const StateVector &xhat)
- void set xhat (int i, double value)
- void reset ()
- void predict (const InputVector &u, const double &dt)
- void correct (const OutputVector &y, const InputVector &u)
- void correct (const OutputVector &y, const InputVector &u, const EMat< OUTPUTS, OUTPUTS > &sqrtR)
- template<int ROWS>
   void correct (const EVec< ROWS > &y, const InputVector &u, const EMat< ROWS, STATES > &C, const EMat< ROWS, INPUTS > &D, const EMat< ROWS, ROWS > &sqrtR)

### 4.32.1 Detailed Description

template<int STATES, int INPUTS, int OUTPUTS> class KalmanFilter< STATES, INPUTS, OUTPUTS >

Kalman filters combine predictions from a model and measurements to estimate a system's true state.

Each call of predict moves the state forward in time according to the matrix A, and the covariance has white noise Q added.

Each call of correct applies a measurement which moves the state more toward the true state, and it reduces the state covariance.

To read more about Kalman filters read: https://github.com/rlabbe/Kalman-and-Bayesian-← Filters-in-Python

This implementation uses the square-root form of the Kalman filter. The main reason for this is to ensure that the covariance matrix always remains positive definite. To see the formulation this implements, read: httpsecovariance matrix always remains positive definite. To see the formulation this implements, read: httpsecovariance matrix always remains positive definite.

### **Template Parameters**

STATES	Dimension of the state vector.
INPUTS	Dimension of the control input vector.
OUTPUTS	Dimension of the measurement vector.

#### 4.32.2 Constructor & Destructor Documentation

# KalmanFilter() [1/2]

#### Constructs a Kalman filter.

#### **Parameters**

plant	The linear system the filter tracks.
state_stddevs	The standard deviations of the states.
measurement_stddevs	The standard deviations of the measurements.

### KalmanFilter() [2/2]

### Constructs a Kalman filter.

### **Parameters**

Α	The state matrix.
В	The input matrix.
С	The measurement matrix.
D	The feedthrough matrix.
state_stddevs	The standard deviations of the states.
measurement_stddevs	The standard deviations of the measurements.

# 4.32.3 Member Function Documentation

#### correct() [1/3]

Correct the state estimate using the measurements in y, custom measurement and feedthrough matrices, and custom measurement standard deviations. This is useful for when a different set of measurements are being applied than what the plant defines.

У	The vector of measurements.
и	The control input used in the last predict step.
С	The measurement matrix to use for this step.
D	The feedthrough matrix to use for this step.
sqrtR	The square root measurement noise matrix to use for this step.

# correct() [2/3]

```
template<int STATES, int INPUTS, int OUTPUTS> void KalmanFilter< STATES, INPUTS, OUTPUTS >::correct ( const OutputVector & y, const InputVector & u) [inline]
```

Correct the state estimate using the measurements in y.

#### **Parameters**

У	The vector of measurements.
и	The control input used in the last predict step.

# correct() [3/3]

Correct the state estimate using the measurements in y, and custom standard deviations. This is useful for when the noise in the measurements vary.

#### **Parameters**

У	The vector of measurements.
и	The control input used in the last predict step.
sqrtR	The square root measurement noise matrix to use for this step.

# P()

```
template<int STATES, int INPUTS, int OUTPUTS>
StateMatrix KalmanFilter< STATES, INPUTS, OUTPUTS >::P () const [inline]
```

Returns the reconstructed covariance matrix P.

#### predict()

```
template<int STATES, int INPUTS, int OUTPUTS> void KalmanFilter< STATES, INPUTS, OUTPUTS >::predict ( const InputVector & u, const double & dt) [inline]
```

Projects the state into the future by dt seconds with control input u.

и	The control input.
dt	The timestep in seconds.

### reset()

```
template<int STATES, int INPUTS, int OUTPUTS>
void KalmanFilter< STATES, INPUTS, OUTPUTS >::reset () [inline]
```

Resets the filter.

#### S() [1/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
const StateMatrix & KalmanFilter< STATES, INPUTS, OUTPUTS >::S () const [inline]
```

Returns the square-root covariance matrix S.

# S() [2/2]

Returns one element of the square-root covariance matrix S.

# **Parameters**

i	Row of S.
j	Column of S.

# set\_P()

Set the current square-root covariance matrix S to the square-root of P.

### **Parameters**

```
P The covariance matrix P.
```

# set\_S()

```
template<int STATES, int INPUTS, int OUTPUTS> void KalmanFilter< STATES, INPUTS, OUTPUTS >::set_S ( const StateMatrix & S) [inline]
```

Set the current square-root covariance matrix S.

S The new square-root covariance matrix S.

### set\_xhat() [1/2]

Set the current state estimate x-hat.

# set\_xhat() [2/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
void KalmanFilter< STATES, INPUTS, OUTPUTS >::set_xhat (
          int i,
          double value) [inline]
```

Set one element of the current state estimate x-hat.

#### **Parameters**

```
i Row of x-hat.
```

# xhat() [1/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
const StateVector & KalmanFilter< STATES, INPUTS, OUTPUTS >::xhat () const [inline]
```

Returns the current state estimate x-hat.

# xhat() [2/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
double KalmanFilter< STATES, INPUTS, OUTPUTS >::xhat (
          int i) const [inline]
```

Returns one element of the current state estimate x-hat.

#### **Parameters**

```
i Row of x-hat.
```

The documentation for this class was generated from the following file:

kalman\_filter.h

# 4.33 Lift< T > Class Template Reference

```
#include <lift.h>
```

#### Classes

· struct lift\_cfg\_t

#### **Public Member Functions**

- Lift (motor\_group &lift\_motors, lift\_cfg\_t &lift\_cfg, map< T, double > &setpoint\_map, limit \*homing\_← switch=NULL)
- void control\_continuous (bool up\_ctrl, bool down\_ctrl)
- void control\_manual (bool up\_btn, bool down\_btn, int volt\_up, int volt\_down)
- void control setpoints (bool up step, bool down step, vector< T > pos list)
- bool set position (T pos)
- bool set\_setpoint (double val)
- double get\_setpoint ()
- void hold ()
- void home ()
- bool get\_async ()
- void set\_async (bool val)
- void set\_sensor\_function (double(\*fn\_ptr)(void))
- void set\_sensor\_reset (void(\*fn\_ptr)(void))

# 4.33.1 Detailed Description

```
template<typename T> class Lift< T >
```

LIFT A general class for lifts (e.g. 4bar, dr4bar, linear, etc) Uses a PID to hold the lift at a certain height under load, and to move the lift to different heights

**Author** 

Ryan McGee

### 4.33.2 Constructor & Destructor Documentation

#### Lift()

Construct the Lift object and begin the background task that controls the lift.

Usage example: /code{.cpp} enum Positions {UP, MID, DOWN}; map<Positions, double> setpt\_map { {DOWN, 0.0}, {MID, 0.5}, {UP, 1.0} }; Lift<Positions> my\_lift(motors, lift\_cfg, setpt\_map); /endcode

lift_motors	A set of motors, all set that positive rotation correlates with the lift going up	
lift_cfg	Lift characterization information; PID tunings and movement speeds	
setpoint_map	A map of enum type T, in which each enum entry corresponds to a different lift height	

# 4.33.3 Member Function Documentation

# control\_continuous()

Control the lift with an "up" button and a "down" button. Use PID to hold the lift when letting go.

#### **Parameters**

up_ctrl	Button controlling the "UP" motion
down_ctrl	Button controlling the "DOWN" motion

# control\_manual()

Control the lift with manual controls (no holding voltage)

### **Parameters**

up_btn	Raise the lift when true
down_btn	Lower the lift when true
volt_up	Motor voltage when raising the lift
volt_down	Motor voltage when lowering the lift

# control\_setpoints()

Control the lift in "steps". When the "up" button is pressed, the lift will go to the next position as defined by pos\_list. Order matters!

up_step	A button that increments the position of the lift.
down_step	A button that decrements the position of the lift.
pos_list	A list of positions for the lift to go through. The higher the index, the higher the lift should be (generally).

# get\_async()

```
template<typename T>
bool Lift< T >::get_async () [inline]
```

#### Returns

whether or not the background thread is running the lift

# get\_setpoint()

```
template<typename T>
double Lift< T >::get_setpoint () [inline]
```

#### Returns

The current setpoint for the lift

### hold()

```
template<typename T>
void Lift< T >::hold () [inline]
```

Target the class's setpoint. Calculate the PID output and set the lift motors accordingly.

# home()

```
template<typename T>
void Lift< T >::home () [inline]
```

A blocking function that automatically homes the lift based on a sensor or hard stop, and sets the position to 0. A watchdog times out after 3 seconds, to avoid damage.

# set\_async()

Enables or disables the background task. Note that running the control functions, or set\_position functions will immediately re-enable the task for autonomous use.

val Whether or not the background thread should run the lift

# set\_position()

Enable the background task, and send the lift to a position, specified by the setpoint map from the constructor.

#### **Parameters**

```
pos A lift position enum type
```

#### Returns

True if the pid has reached the setpoint

# set\_sensor\_function()

Creates a custom hook for any other type of sensor to be used on the lift. Example:  $/code\{.cpp\}$  my\_lift.set\_ $\leftarrow$  sensor\_function( [](){return my\_sensor.position();} );  $/code\{.cpp\}$  my\_lift.set\_ $\leftarrow$ 

# **Parameters**

```
fn_ptr | Pointer to custom sensor function
```

# set\_sensor\_reset()

Creates a custom hook to reset the sensor used in set\_sensor\_function(). Example:  $/code{.cpp}$  my\_lift.set\_ $\leftarrow$  sensor\_reset( my\_sensor.resetPosition );  $/code{.cpp}$ 

#### set\_setpoint()

Manually set a setpoint value for the lift PID to go to.

val Lift setpoint, in motor revolutions or sensor units defined by get sensor. Cannot be outside the softstops.

#### Returns

True if the pid has reached the setpoint

The documentation for this class was generated from the following file:

· lift.h

# 4.34 Lift< T >::lift\_cfg\_t Struct Reference

```
#include <lift.h>
```

#### 4.34.1 Detailed Description

```
template<typename T> struct Lift< T >::lift_cfg_t
```

lift\_cfg\_t holds the physical parameter specifications of a lify system. includes:

- · maximum speeds for the system
- · softstops to stop the lift from hitting the hard stops too hard

The documentation for this struct was generated from the following file:

• lift.h

# 4.35 LinearSystem < STATES, INPUTS, OUTPUTS > Class Template Reference

```
#include <linear_system.h>
```

# **Public Member Functions**

- LinearSystem (const MatrixA &A, const MatrixB &B, const MatrixC &C, const MatrixD &D)
- const MatrixA & A ()
- const MatrixB & B ()
- const MatrixC & C ()
- const MatrixD & D ()
- VectorX compute\_X (const VectorX &x, const VectorU &u, double dt)
- VectorY compute\_Y (const VectorX &x, const VectorU &u)

#### 4.35.1 Detailed Description

```
template<int STATES, int INPUTS, int OUTPUTS> class LinearSystem< STATES, INPUTS, OUTPUTS >
```

This class represents a state-space model of a linear system.

It contains the following continuous matrices: A, System matrix B, Input matrix C, Output matrix D, Feedthrough matrix

#### 4.35.2 Constructor & Destructor Documentation

# LinearSystem()

Constructs a discrete linear system with the given continuous matrices.

#### **Parameters**

Α	The continuous system matrix
В	The continuous input matrix
С	The output matrix
D	The feedthrough matrix

# 4.35.3 Member Function Documentation

# **A**()

```
template<int STATES, int INPUTS, int OUTPUTS>
const MatrixA & LinearSystem< STATES, INPUTS, OUTPUTS >::A () [inline]
```

Returns the continuous system matrix A.

# B()

```
template<int STATES, int INPUTS, int OUTPUTS>
const MatrixB & LinearSystem< STATES, INPUTS, OUTPUTS >::B () [inline]
```

Returns the continuous input matrix B.

# C()

```
template<int STATES, int INPUTS, int OUTPUTS>
const MatrixC & LinearSystem< STATES, INPUTS, OUTPUTS >::C () [inline]
```

Returns the output matrix C.

# compute\_X()

```
template<int STATES, int INPUTS, int OUTPUTS> 
 VectorX LinearSystem< STATES, INPUTS, OUTPUTS >::compute_X ( const VectorX & x, const VectorU & u, double dt) [inline]
```

Computes the new state vector given the previous state vector, an input vector, and the timestep in seconds.

#### **Parameters**

X	The current state vector.
и	The input vector.
dt	The timestep in seconds.

#### Returns

The new state vector.

# compute\_Y()

Computes the output vector given a state and an input.

# **Parameters**

Х	The state vector.
и	The input vector.

#### Returns

The output vector.

# D()

```
template<int STATES, int INPUTS, int OUTPUTS>
const MatrixD & LinearSystem< STATES, INPUTS, OUTPUTS >::D () [inline]
```

Returns the feedthrough matrix D.

The documentation for this class was generated from the following file:

· linear\_system.h

# 4.36 Logger Class Reference

Class to simplify writing to files.

```
#include <logger.h>
```

#### **Public Member Functions**

Logger (const std::string &filename)

Create a logger that will save to a file.

• Logger (const Logger &I)=delete

copying not allowed

• Logger & operator= (const Logger &I)=delete

copying not allowed

void Log (const std::string &s)

Write a string to the log.

void Log (LogLevel level, const std::string &s)

Write a string to the log with a loglevel.

void LogIn (const std::string &s)

Write a string and newline to the log.

void LogIn (LogLevel level, const std::string &s)

Write a string and a newline to the log with a loglevel.

void Logf (const char \*fmt,...)

Write a formatted string to the log.

void Logf (LogLevel level, const char \*fmt,...)

Write a formatted string to the log with a loglevel.

### **Static Public Attributes**

• static constexpr int MAX\_FORMAT\_LEN = 512

maximum size for a string to be before it's written

# 4.36.1 Detailed Description

Class to simplify writing to files.

### 4.36.2 Constructor & Destructor Documentation

### Logger()

Create a logger that will save to a file.

filename the file to save to

# 4.36.3 Member Function Documentation

# Log() [1/2]

Write a string to the log.

#### **Parameters**

s the string to write

# Log() [2/2]

```
void Logger::Log (
                LogLevel level,
               const std::string & s)
```

Write a string to the log with a loglevel.

#### **Parameters**

level	the level to write. DEBUG, NOTICE, WARNING, ERROR, CRITICAL, TIME
s	the string to write

# Logf() [1/2]

Write a formatted string to the log.

#### **Parameters**

fmt	the format string (like printf)
	the args

# **Logf()** [2/2]

```
void Logger::Logf (
          LogLevel level,
          const char * fmt,
```

Write a formatted string to the log with a loglevel.

level	the level to write. DEBUG, NOTICE, WARNING, ERROR, CRITICAL, TIME
fmt	the format string (like printf)
	the args

# LogIn() [1/2]

Write a string and newline to the log.

#### **Parameters**

```
s the string to write
```

# LogIn() [2/2]

```
void Logger::Logln (
          LogLevel level,
          const std::string & s)
```

Write a string and a newline to the log with a loglevel.

# **Parameters**

level	the level to write. DEBUG, NOTICE, WARNING, ERROR, CRITICAL, TIME
s	the string to write

The documentation for this class was generated from the following files:

- · logger.h
- logger.cpp

# 4.37 MotionController::m\_profile\_cfg\_t Struct Reference

```
#include <motion_controller.h>
```

# **Public Attributes**

double max\_v

the maximum velocity the robot can drive

double accel

the most acceleration the robot can do

PID::pid\_config\_t pid\_cfg

configuration parameters for the internal PID controller

FeedForward::ff\_config\_t ff\_cfg

configuration parameters for the internal

### 4.37.1 Detailed Description

m\_profile\_config holds all data the motion controller uses to plan paths When motion pofile is given a target to drive to, max\_v and accel are used to make the trapezoid profile instructing the controller how to drive pid\_cfg, ff\_cfg are used to find the motor outputs necessary to execute this path

The documentation for this struct was generated from the following file:

· motion controller.h

# 4.38 StateMachine< System, IDType, Message, delay\_ms, do\_log >::MaybeMessage Class Reference

MaybeMessage a message of Message type or nothing MaybeMessage  $m = \{\}$ ; // empty MaybeMessag

```
#include <state_machine.h>
```

#### **Public Member Functions**

MaybeMessage ()

Empty message - when theres no message.

MaybeMessage (Message msg)

Create a maybemessage with a message.

• bool has\_message ()

check if the message is here

• Message message ()

Get the message stored. The return value is invalid unless has\_message returned true.

# 4.38.1 Detailed Description

template<typename System, typename IDType, typename Message, int32\_t delay\_ms, bool do\_log = false> class StateMachine< System, IDType, Message, delay\_ms, do\_log >::MaybeMessage

MaybeMessage a message of Message type or nothing MaybeMessage  $m = \{\}$ ; // empty MaybeMessag

#### 4.38.2 Constructor & Destructor Documentation

### MaybeMessage()

Create a maybemessage with a message.

msg the message to hold on to

#### 4.38.3 Member Function Documentation

# has\_message()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
bool StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage::has_message ()
[inline]
```

check if the message is here

#### Returns

true if there is a message

# message()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
Message StateMachine< System, IDType, Message, delay_ms, do_log >::MaybeMessage::message ()
[inline]
```

Get the message stored. The return value is invalid unless has\_message returned true.

# Returns

The message if it exists. Undefined otherwise

The documentation for this class was generated from the following file:

· state\_machine.h

# 4.39 MecanumDrive Class Reference

#include <mecanum\_drive.h>

# Classes

· struct mecanumdrive config t

#### **Public Member Functions**

- MecanumDrive (vex::motor &left\_front, vex::motor &right\_front, vex::motor &left\_rear, vex::motor &right\_rear, vex::rotation \*lateral\_wheel=NULL, vex::inertial \*imu=NULL, mecanumdrive\_config\_t \*config=NULL)
- void drive\_raw (double direction\_deg, double magnitude, double rotation)
- void drive (double left\_y, double left\_x, double right\_x, int power=2)
- bool auto\_drive (double inches, double direction, double speed, bool gyro\_correction=true)
- bool auto turn (double degrees, double speed, bool ignore imu=false)

#### 4.39.1 Detailed Description

A class representing the Mecanum drivetrain. Contains 4 motors, a possible IMU (intertial), and a possible undriven perpendicular wheel.

#### 4.39.2 Constructor & Destructor Documentation

# MecanumDrive()

```
MecanumDrive::MecanumDrive (
    vex::motor & left_front,
    vex::motor & right_front,
    vex::motor & left_rear,
    vex::motor & right_rear,
    vex::rotation * lateral_wheel = NULL,
    vex::inertial * imu = NULL,
    mecanumdrive_config_t * config = NULL)
```

Create the Mecanum drivetrain object

# 4.39.3 Member Function Documentation

#### auto\_drive()

Drive the robot in a straight line automatically. If the inertial was declared in the constructor, use it to correct while driving. If the lateral wheel was declared in the constructor, use it for more accurate positioning while strafing.

# Parameters

inches	How far the robot should drive, in inches
direction	What direction the robot should travel in, in degrees. 0 is forward, +/-180 is reverse, clockwise is positive.
speed	The maximum speed the robot should travel, in percent: -1.0->+1.0
gyro_correction	=true Whether or not to use the gyro to help correct while driving. Will always be false if no gyro was declared in the constructor.

Drive the robot in a straight line automatically. If the inertial was declared in the constructor, use it to correct while driving. If the lateral wheel was declared in the constructor, use it for more accurate positioning while strafing.

inches	How far the robot should drive, in inches
direction	What direction the robot should travel in, in degrees. 0 is forward, +/-180 is reverse,
	clockwise is positive.
speed	The maximum speed the robot should travel, in percent: -1.0->+1.0
gyro_correction	= true Whether or not to use the gyro to help correct while driving. Will always be false if no gyro was declared in the constructor.

#### Returns

Whether or not the maneuver is complete.

# auto\_turn()

Autonomously turn the robot X degrees over it's center point. Uses a closed loop for control.

#### **Parameters**

degrees	How many degrees to rotate the robot. Clockwise postive.
speed	What percentage to run the motors at: 0.0 -> 1.0
ignore_imu	=false Whether or not to use the Inertial for determining angle. Will instead use circumference
	formula + robot's wheelbase + encoders to determine.

# Returns

whether or not the robot has finished the maneuver

Autonomously turn the robot X degrees over it's center point. Uses a closed loop for control.

#### **Parameters**

degrees	How many degrees to rotate the robot. Clockwise postive.
speed	What percentage to run the motors at: 0.0 -> 1.0
ignore_imu	= false Whether or not to use the Inertial for determining angle. Will instead use circumference formula + robot's wheelbase + encoders to determine.

### Returns

whether or not the robot has finished the maneuver

# drive()

Drive the robot with a mecanum-style / arcade drive. Inputs are in percent (-100.0 -> 100.0) straight from the controller. Controls are mixed, so the robot can drive forward / strafe / rotate all at the same time.

left_y	left joystick, Y axis (forward / backwards)	
left_x	left joystick, X axis (strafe left / right)	
right←	right joystick, X axis (rotation left / right)	
_X		
power	=2 how much of a "curve" there should be on drive controls; better for low speed maneuvers. Leave	
	blank for a default curve of 2 (higher means more fidelity)	

Drive the robot with a mecanum-style / arcade drive. Inputs are in percent (-100.0 -> 100.0) straight from the controller. Controls are mixed, so the robot can drive forward / strafe / rotate all at the same time.

#### **Parameters**

left_y	left joystick, Y axis (forward / backwards)	
left_x	left joystick, X axis (strafe left / right)	
right←	right joystick, X axis (rotation left / right)	
_X		
power	= 2 how much of a "curve" there should be on drive controls; better for low speed maneuvers. Leave	
	blank for a default curve of 2 (higher means more fidelity)	

# drive\_raw()

Drive the robot using vectors. This handles all the math required for mecanum control.

### **Parameters**

direction_deg	the direction to drive the robot, in degrees. 0 is forward, 180 is back, clockwise is positive, counterclockwise is negative.
magnitude	How fast the robot should drive, in percent: 0.0->1.0
rotation	How fast the robot should rotate, in percent: -1.0->+1.0

The documentation for this class was generated from the following files:

- · mecanum\_drive.h
- · mecanum\_drive.cpp

# 4.40 MecanumDrive::mecanumdrive\_config\_t Struct Reference

```
#include <mecanum_drive.h>
```

# 4.40.1 Detailed Description

Configure the Mecanum drive PID tunings and robot configurations

The documentation for this struct was generated from the following file:

· mecanum\_drive.h

# 4.41 motion\_t Struct Reference

```
#include <trapezoid_profile.h>
```

#### **Public Attributes**

· double pos

1d position at this point in time

· double vel

1d velocity at this point in time

double accel

1d acceleration at this point in time

# 4.41.1 Detailed Description

motion\_t is a description of 1 dimensional motion at a point in time.


The documentation for this struct was generated from the following file:

· trapezoid\_profile.h

# 4.42 MotionController Class Reference

```
#include <motion_controller.h>
```

Inheritance diagram for MotionController:



# Classes

• struct m\_profile\_cfg\_t

### **Public Member Functions**

• MotionController (m\_profile\_cfg\_t &config)

Construct a new Motion Controller object.

• void init (double start\_pt, double end\_pt) override

Initialize the motion profile for a new movement This will also reset the PID and profile timers.

double update (double sensor\_val) override

Update the motion profile with a new sensor value.

- · double get () override
- void set\_limits (double lower, double upper) override
- bool is\_on\_target () override
- motion\_t get\_motion () const

# **Static Public Member Functions**

• static FeedForward::ff\_config\_t tune\_feedforward (TankDrive &drive, OdometryTank &odometry, double pct=0.6, double duration=2)

#### 4.42.1 Detailed Description

Motion Controller class

This class defines a top-level motion profile, which can act as an intermediate between a subsystem class and the motors themselves

This takes the constants kS, kV, kA, kP, kI, kD, max\_v and acceleration and wraps around a feedforward, PID and trapezoid profile. It does so with the following formula:

```
out = feedfoward.calculate(motion_profile.get(time_s)) + pid.get(motion_profile.get(time_s))
```

For PID and Feedforward specific formulae, see pid.h, feedforward.h, and trapezoid\_profile.h

**Author** 

Ryan McGee

Date

7/13/2022

## 4.42.2 Constructor & Destructor Documentation

# MotionController()

Construct a new Motion Controller object.

config	The definition of how the robot is able to move max_v Maximum velocity the movement is capable of	
	accel Acceleration / deceleration of the movement pid_cfg Definitions of kP, kI, and kD ff_cfg	
	Definitions of kS, kV, and kA	

### 4.42.3 Member Function Documentation

# get()

```
double MotionController::get () [override], [virtual]
```

### **Returns**

the last saved result from the feedback controller

Implements Feedback.

# get\_motion()

```
motion_t MotionController::get_motion () const
```

### Returns

The current postion, velocity and acceleration setpoints

# init()

Initialize the motion profile for a new movement This will also reset the PID and profile timers.

#### **Parameters**

start← _pt	Movement starting position
end_pt	Movement ending posiiton

Implements Feedback.

# is\_on\_target()

```
bool MotionController::is_on_target () [override], [virtual]
```

#### Returns

Whether or not the movement has finished, and the PID confirms it is on target

Implements Feedback.

### set\_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied. if limits are applied, the controller will not target any value below lower or above upper

#### **Parameters**

lower	upper limit
upper	lower limiet

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

#### **Parameters**

lower	Upper limit
upper	Lower limit

Implements Feedback.

# tune\_feedforward()

This method attempts to characterize the robot's drivetrain and automatically tune the feedforward. It does this by first calculating the kS (voltage to overcome static friction) by slowly increasing the voltage until it moves.

Next is kV (voltage to sustain a certain velocity), where the robot will record it's steady-state velocity at 'pct' speed.

Finally, kA (voltage needed to accelerate by a certain rate), where the robot will record the entire movement's velocity and acceleration, record a plot of [X=(pct-kV\*V-kS), Y=(Acceleration)] along the movement, and since kA\*Accel = pct-kV\*V-kS, the reciprocal of the linear regression is the kA value.

### **Parameters**

drive The tankdrive to operate on	
odometry	The robot's odometry subsystem
pct	Maximum velocity in percent (0->1.0)
duration	Amount of time the robot should be moving for the test

### Returns

A tuned feedforward object

### update()

Update the motion profile with a new sensor value.

sensor_val Value from the sensor
----------------------------------

#### Returns

the motor input generated from the motion profile

Implements Feedback.

The documentation for this class was generated from the following files:

- · motion controller.h
- motion\_controller.cpp

# 4.43 MovingAverage Class Reference

```
#include <moving_average.h>
```

Inheritance diagram for MovingAverage:



#### **Public Member Functions**

- MovingAverage (int buffer\_size)
- MovingAverage (int buffer size, double starting value)
- · void add\_entry (double n) override
- double get\_value () const override
- int get\_size () const

# 4.43.1 Detailed Description

# MovingAverage

A moving average is a way of smoothing out noisy data. For many sensor readings, the noise is roughly symmetric around the actual value. This means that if you collect enough samples those that are too high are cancelled out by the samples that are too low leaving the real value.

The MovingAverage class provides a simple interface to do this smoothing from our noisy sensor values.

WARNING: because we need a lot of samples to get the actual value, the value given by the MovingAverage will 'lag' behind the actual value that the sensor is reading. Using a MovingAverage is thus a tradeoff between accuracy and lag time (more samples) vs. less accuracy and faster updating (less samples).

# 4.43.2 Constructor & Destructor Documentation

# MovingAverage() [1/2]

Create a moving average calculator with 0 as the default value

buffer size	The size of the buffer. The number of samples that constitute a valid reading

# MovingAverage() [2/2]

```
MovingAverage::MovingAverage (
          int buffer_size,
          double starting_value)
```

Create a moving average calculator with a specified default value

### **Parameters**

buffer_size	The size of the buffer. The number of samples that constitute a valid reading
starting_value	The value that the average will be before any data is added

# 4.43.3 Member Function Documentation

# add\_entry()

Add a reading to the buffer Before: [ 1 1 2 2 3 3] => 2  $^{\wedge}$  After: [ 2 1 2 2 3 3] => 2.16  $^{\wedge}$ 

# **Parameters**

*n* the sample that will be added to the moving average.

Implements Filter.

# get\_size()

```
int MovingAverage::get_size () const
```

How many samples the average is made from

# Returns

the number of samples used to calculate this average

# get\_value()

```
double MovingAverage::get_value () const [override], [virtual]
```

Returns the average based off of all the samples collected so far

#### Returns

the calculated average. sum(samples)/numsamples

How many samples the average is made from

### Returns

the number of samples used to calculate this average

Implements Filter.


The documentation for this class was generated from the following files:

- · moving\_average.h
- · moving\_average.cpp

# 4.44 Odometry3Wheel Class Reference

```
#include <odometry_3wheel.h>
```

Inheritance diagram for Odometry3Wheel:



# Classes

• struct odometry3wheel\_cfg\_t

# **Public Member Functions**

- Odometry3Wheel (CustomEncoder &lside\_fwd, CustomEncoder &rside\_fwd, CustomEncoder &off\_axis, odometry3wheel\_cfg\_t &cfg, bool is\_async=true)
- Pose2d update () override
- void tune (vex::controller &con, TankDrive &drive)

### Public Member Functions inherited from OdometryBase

- OdometryBase (bool is\_async)
- virtual Pose2d get\_position (void)
- virtual void set position (const Pose2d &newpos=zero pos)
- void end async ()
- virtual double get\_speed ()
- virtual double get accel ()
- double get\_angular\_speed\_deg ()
- double get\_angular\_accel\_deg ()

### **Additional Inherited Members**

### Static Public Member Functions inherited from OdometryBase

- static int background\_task (void \*ptr)
- static double smallest\_angle (double start\_deg, double end\_deg)

# Public Attributes inherited from OdometryBase

bool end\_task = false

end\_task is true if we instruct the odometry thread to shut down

- vex::task \* handle
- vex::mutex mut
- · Pose2d current pos
- · double speed
- · double accel
- double ang\_speed\_deg
- double ang\_accel\_deg

# 4.44.1 Detailed Description

## Odometry3Wheel

This class handles the code for a standard 3-pod odometry setup, where there are 3 "pods" made up of undriven (dead) wheels connected to encoders in the following configuration:

Where O is the center of rotation. The robot will monitor the changes in rotation of these wheels and calculate the robot's X, Y and rotation on the field.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

Author

Ryan McGee

Date

Oct 31 2022

#### 4.44.2 Constructor & Destructor Documentation

# Odometry3Wheel()

### Construct a new Odometry 3 Wheel object

### **Parameters**

Iside_fwd	left-side encoder reference
rside_fwd	right-side encoder reference
off_axis	off-axis (perpendicular) encoder reference
cfg	robot odometry configuration
is_async	true to constantly run in the background

#### 4.44.3 Member Function Documentation

### tune()

A guided tuning process to automatically find tuning parameters. This method is blocking, and returns when tuning has finished. Follow the instructions on the controller to complete the tuning process

## Parameters

con	Controller reference, for screen and button control
drive	Drivetrain reference for robot control

A guided tuning process to automatically find tuning parameters. This method is blocking, and returns when tuning has finished. Follow the instructions on the controller to complete the tuning process

It is assumed the gear ratio and encoder PPR have been set correctly

### update()

```
Pose2d Odometry3Wheel::update () [override], [virtual]
```

Update the current position of the robot once, using the current state of the encoders and the previous known location

#### Returns

the robot's updated position

Implements OdometryBase.

The documentation for this class was generated from the following files:

- · odometry\_3wheel.h
- odometry\_3wheel.cpp

# 4.45 Odometry3Wheel::odometry3wheel\_cfg\_t Struct Reference

#include <odometry\_3wheel.h>

### **Public Attributes**

- double wheelbase\_dist
- double off\_axis\_center\_dist
- · double wheel diam

# 4.45.1 Detailed Description

odometry3wheel\_cfg\_t holds all the specifications for how to calculate position with 3 encoders See the core wiki for what exactly each of these parameters measures

### 4.45.2 Member Data Documentation

### off\_axis\_center\_dist

double Odometry3Wheel::odometry3wheel\_cfg\_t::off\_axis\_center\_dist

distance from the center of the robot to the center off axis wheel

### wheel\_diam

double Odometry3Wheel::odometry3wheel\_cfg\_t::wheel\_diam

the diameter of the tracking wheel

# wheelbase\_dist

double Odometry3Wheel::odometry3wheel\_cfg\_t::wheelbase\_dist

distance from the center of the left wheel to the center of the right wheel


The documentation for this struct was generated from the following file:

· odometry\_3wheel.h

# 4.46 OdometryBase Class Reference

#include <odometry\_base.h>

Inheritance diagram for OdometryBase:



### **Public Member Functions**

- OdometryBase (bool is async)
- virtual Pose2d get\_position (void)
- virtual void set\_position (const Pose2d &newpos=zero\_pos)
- virtual Pose2d update ()=0
- void end\_async ()
- virtual double get speed ()
- virtual double get accel ()
- double get\_angular\_speed\_deg ()
- double get\_angular\_accel\_deg ()

#### **Static Public Member Functions**

- static int background\_task (void \*ptr)
- static double smallest\_angle (double start\_deg, double end\_deg)

#### **Public Attributes**

• bool end\_task = false

end\_task is true if we instruct the odometry thread to shut down

- vex::task \* handle
- vex::mutex mut
- Pose2d current\_pos
- · double speed
- double accel
- · double ang speed deg
- double ang\_accel\_deg

# 4.46.1 Detailed Description

# OdometryBase

This base class contains all the shared code between different implementations of odometry. It handles the asynchronous management, position input/output and basic math functions, and holds positional types specific to field orientation.

All future odometry implementations should extend this file and redefine update() function.

**Author** 

Ryan McGee

Date

Aug 11 2021

### 4.46.2 Constructor & Destructor Documentation

### OdometryBase()

```
OdometryBase::OdometryBase (
          bool is_async)
```

Construct a new Odometry Base object

is\_async True to run constantly in the background, false to call update() manually

### 4.46.3 Member Function Documentation

# background\_task()

Function that runs in the background task. This function pointer is passed to the vex::task constructor.

#### **Parameters**

ptr Pointer to OdometryBase object

### Returns

Required integer return code. Unused.

### end\_async()

```
void OdometryBase::end_async ()
```

End the background task. Cannot be restarted. If the user wants to end the thread but keep the data up to date, they must run the update() function manually from then on.

### get\_accel()

```
double OdometryBase::get_accel () [virtual]
```

Get the current acceleration

# Returns

the acceleration rate of the robot (inch/s^2)

# get\_angular\_accel\_deg()

```
double OdometryBase::get_angular_accel_deg ()
```

Get the current angular acceleration in degrees

# Returns

the angular acceleration at which we are turning (deg/s^2)

### get\_angular\_speed\_deg()

```
double OdometryBase::get_angular_speed_deg ()
```

Get the current angular speed in degrees

Returns

the angular velocity at which we are turning (deg/s)

# get\_position()

Gets the current position and rotation

Returns

the position that the odometry believes the robot is at

Gets the current position and rotation

### get\_speed()

```
double OdometryBase::get_speed () [virtual]
```

Get the current speed

Returns

the speed at which the robot is moving and grooving (inch/s)

# set\_position()

Sets the current position of the robot

**Parameters** 

newpos	the new position that the odometry will believe it is at
--------	--

Sets the current position of the robot

Reimplemented in OdometryTank.

# smallest\_angle()

Get the smallest difference in angle between a start heading and end heading. Returns the difference between -180 degrees and +180 degrees, representing the robot turning left or right, respectively.

start_deg	intitial angle (degrees)
end_deg	final angle (degrees)

#### Returns

the smallest angle from the initial to the final angle. This takes into account the wrapping of rotations around 360 degrees

Get the smallest difference in angle between a start heading and end heading. Returns the difference between -180 degrees and +180 degrees, representing the robot turning left or right, respectively.

### update()

```
virtual Pose2d OdometryBase::update () [pure virtual]
```

Update the current position on the field based on the sensors

### Returns

the location that the robot is at after the odometry does its calculations

Implemented in Odometry3Wheel, and OdometryTank.

### 4.46.4 Member Data Documentation

#### accel

```
double OdometryBase::accel
```

the rate at which we are accelerating (inch/s^2)

# ang\_accel\_deg

```
double OdometryBase::ang_accel_deg
```

the rate at which we are accelerating our turn (deg/s^2)

## ang\_speed\_deg

```
double OdometryBase::ang_speed_deg
```

the speed at which we are turning (deg/s)

### current\_pos

```
Pose2d OdometryBase::current_pos
```

Current position of the robot in terms of x,y,rotation

### handle

```
vex::task* OdometryBase::handle
```

handle to the vex task that is running the odometry code

#### mut

```
vex::mutex OdometryBase::mut
```

Mutex to control multithreading

#### speed

```
double OdometryBase::speed
```

the speed at which we are travelling (inch/s)

The documentation for this class was generated from the following files:


- · odometry\_base.h
- · odometry\_base.cpp

# 4.47 screen::OdometryPage Class Reference

a page that shows odometry position and rotation and a map (if an sd card with the file is on)

```
#include <screen.h>
```

Inheritance diagram for screen::OdometryPage:



### **Public Member Functions**

- OdometryPage (OdometryBase &odom, double robot\_width, double robot\_height, bool do\_trail)

  Create an odometry trail. Make sure odometry is initilized before now.
- void update (bool was\_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first\_draw, unsigned int frame\_number) override

# 4.47.1 Detailed Description

a page that shows odometry position and rotation and a map (if an sd card with the file is on)

# 4.47.2 Constructor & Destructor Documentation

### OdometryPage()

```
screen::OdometryPage::OdometryPage (
    OdometryBase & odom,
    double robot_width,
    double robot_height,
    bool do_trail)
```

Create an odometry trail. Make sure odometry is initilized before now.

#### **Parameters**

odom	the odometry system to monitor
robot_width	the width (side to side) of the robot in inches. Used for visualization
robot_height	the robot_height (front to back) of the robot in inches. Used for visualization
do_trail	whether or not to calculate and draw the trail. Drawing and storing takes a very <i>slight</i> extra amount of processing power

#### 4.47.3 Member Function Documentation

# draw()

#### See also

Page::draw

Reimplemented from screen::Page.

# update()

```
void screen::OdometryPage::update (
          bool was_pressed,
          int x,
          int y) [override], [virtual]
```

# See also

Page::update

Reimplemented from screen::Page.


The documentation for this class was generated from the following files:

- screen.h
- screen.cpp

# 4.48 OdometryTank Class Reference

#include <odometry\_tank.h>

Inheritance diagram for OdometryTank:



#### **Public Member Functions**

- OdometryTank (CustomEncoder &left\_custom\_enc, CustomEncoder &right\_custom\_enc, robot\_specs\_t &config, vex::inertial \*imu=NULL, bool is\_async=true)
- Pose2d update () override
- void set\_position (const Pose2d &newpos=zero\_pos) override

# Public Member Functions inherited from OdometryBase

- OdometryBase (bool is async)
- virtual Pose2d get\_position (void)
- void end\_async ()
- virtual double get\_speed ()
- virtual double get\_accel ()
- double get\_angular\_speed\_deg ()
- double get\_angular\_accel\_deg ()

### **Additional Inherited Members**

#### Static Public Member Functions inherited from OdometryBase

- static int background\_task (void \*ptr)
- static double smallest\_angle (double start\_deg, double end\_deg)

# Public Attributes inherited from OdometryBase

• bool end\_task = false

end\_task is true if we instruct the odometry thread to shut down

- vex::task \* handle
- vex::mutex mut
- · Pose2d current pos
- double speed
- double accel
- · double ang speed deg
- double ang\_accel\_deg

# 4.48.1 Detailed Description

OdometryTank defines an odometry system for a tank drivetrain This requires encoders in the same orientation as the drive wheels Odometry is a "start and forget" subsystem, which means once it's created and configured, it will constantly run in the background and track the robot's X, Y and rotation coordinates.

### 4.48.2 Constructor & Destructor Documentation

# OdometryTank() [1/3]

```
OdometryTank::OdometryTank (
    vex::motor_group & left_side,
    vex::motor_group & right_side,
    robot_specs_t & config,
    vex::inertial * imu = NULL,
    bool is_async = true)
```

Initialize the Odometry module, calculating position from the drive motors.

### **Parameters**

left_side	The left motors
right_side	The right motors
config	the specifications that supply the odometry with descriptions of the robot. See robot_specs_t for what is contained
imu	The robot's inertial sensor. If not included, rotation is calculated from the encoders.
is_async	If true, position will be updated in the background continuously. If false, the programmer will have to manually call update().

# OdometryTank() [2/3]

Initialize the Odometry module, calculating position from the drive motors.

### **Parameters**

left_custom_enc	The left custom encoder
right_custom_enc	The right custom encoder
config	the specifications that supply the odometry with descriptions of the robot. See robot_specs_t for what is contained
imu	The robot's inertial sensor. If not included, rotation is calculated from the encoders.
is_async	If true, position will be updated in the background continuously. If false, the programmer will have to manually call update().

# OdometryTank() [3/3]

```
OdometryTank::OdometryTank (
    vex::encoder & left_vex_enc,
    vex::encoder & right_vex_enc,
    robot_specs_t & config,
    vex::inertial * imu = NULL,
    bool is_async = true)
```

Initialize the Odometry module, calculating position from the drive motors.

#### **Parameters**

left_vex_enc	The left vex encoder
right_vex_enc	The right vex encoder
config	the specifications that supply the odometry with descriptions of the robot. See <a href="robot_specs_t">robot_specs_t</a> for what is contained
imu	The robot's inertial sensor. If not included, rotation is calculated from the encoders.
is_async	If true, position will be updated in the background continuously. If false, the programmer will have to manually call update().

### 4.48.3 Member Function Documentation

### set\_position()

set\_position tells the odometry to place itself at a position

# **Parameters**

newpos	the position the odometry will take

Resets the position and rotational data to the input.

Reimplemented from OdometryBase.

## update()

```
Pose2d OdometryTank::update () [override], [virtual]
```

Update the current position on the field based on the sensors

#### Returns

the position that odometry has calculated itself to be at

Update, store and return the current position of the robot. Only use if not initializing with a separate thread.

Implements OdometryBase.

The documentation for this class was generated from the following files:

- odometry\_tank.h
- odometry\_tank.cpp

# 4.49 OdomSetPosition Class Reference

```
#include <drive_commands.h>
```

#### **Public Member Functions**

- OdomSetPosition (OdometryBase &odom, const Pose2d &newpos=OdometryBase::zero pos)
- · bool run () override

### 4.49.1 Detailed Description

AutoCommand wrapper class for the set\_position function in the Odometry class

# 4.49.2 Constructor & Destructor Documentation

# OdomSetPosition()

```
OdomSetPosition::OdomSetPosition (
         OdometryBase & odom,
         const Pose2d & newpos = OdometryBase::zero_pos)
```

constructs a new OdomSetPosition command

#### **Parameters**

odom the odometry system we are setting		the odometry system we are setting
	newpos	the position we are telling the odometry to take. defaults to $(0, 0)$ , angle = 90

Construct an Odometry set pos

### **Parameters**

odom	the odometry system we are setting
newpos	the now position to set the odometry to

### 4.49.3 Member Function Documentation

# run()

```
bool OdomSetPosition::run () [override]
```

Run set\_position Overrides run from AutoCommand

### Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:


- drive\_commands.h
- drive\_commands.cpp

# 4.50 screen::Page Class Reference

Page describes one part of the screen slideshow.

```
#include <screen.h>
```

Inheritance diagram for screen::Page:



### **Public Member Functions**

- virtual void update (bool was\_pressed, int x, int y)

  collect data, respond to screen input, do fast things (runs at 50hz even if you're not focused on this Page (only drawn page gets touch updates))
- virtual void draw (vex::brain::lcd &screen, bool first\_draw, unsigned int frame\_number) draw stored data to the screen (runs at 10 hz and only runs if this page is in front)

# 4.50.1 Detailed Description

Page describes one part of the screen slideshow.

#### 4.50.2 Member Function Documentation

## draw()

draw stored data to the screen (runs at 10 hz and only runs if this page is in front)

#### **Parameters**

first_draw	true if we just switched to this page	
frame_number	frame of drawing we are on (basically an animation tick)	l

Reimplemented in screen::FunctionPage, screen::OdometryPage, screen::PIDPage, and screen::StatsPage.

## update()

collect data, respond to screen input, do fast things (runs at 50hz even if you're not focused on this Page (only drawn page gets touch updates))

was_pressed	true if the screen has been pressed
X	x position of screen press (if the screen was pressed)
У	y position of screen press (if the screen was pressed)

Reimplemented in screen::FunctionPage, screen::OdometryPage, screen::PIDPage, and screen::StatsPage.

The documentation for this class was generated from the following file:

· screen.h

# 4.51 Parallel Class Reference

Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on\_timeout on all children continue.

```
#include <auto_command.h>
```

### 4.51.1 Detailed Description

Parallel runs multiple commands in parallel and waits for all to finish before continuing. if none finish before this command's timeout, it will call on\_timeout on all children continue.

The documentation for this class was generated from the following files:

- · auto\_command.h
- auto\_command.cpp

## 4.52 PurePursuit::Path Class Reference

```
#include <pure_pursuit.h>
```

### **Public Member Functions**

- Path (std::vector < Translation2d > points, double radius)
- const std::vector< Translation2d > get\_points ()
- double get\_radius ()
- bool is\_valid ()

### 4.52.1 Detailed Description

Wrapper for a vector of points, checking if any of the points are too close for pure pursuit

### 4.52.2 Constructor & Destructor Documentation

### Path()

# Create a Path

points	the points that make up the path
radius	the lookahead radius for pure pursuit

# 4.52.3 Member Function Documentation

# get\_points()

```
const std::vector< Translation2d > PurePursuit::Path::get_points ()
```

Get the points associated with this Path

# get\_radius()

```
double PurePursuit::Path::get_radius ()
```

Get the radius associated with this Path

# is\_valid()

```
bool PurePursuit::Path::is_valid ()
```

Get whether this path will behave as expected

The documentation for this class was generated from the following files:

- pure\_pursuit.h
- pure\_pursuit.cpp

# 4.53 PID Class Reference

```
#include <pid.h>
```

Inheritance diagram for PID:



### **Classes**

• struct pid\_config\_t

4.53 PID Class Reference 89

# **Public Types**

• enum ERROR TYPE

### **Public Member Functions**

- PID (pid\_config\_t &config)
- · void init (double start\_pt, double set\_pt) override
- double update (double sensor\_val) override
- double update (double sensor\_val, double v\_setpt)
- double get\_sensor\_val () const

gets the sensor value that we were last updated with

- · double get () override
- void set\_limits (double lower, double upper) override
- bool is\_on\_target () override
- void reset ()
- double get\_error ()
- double get\_target () const
- · void set target (double target)

### **Public Attributes**

· pid\_config\_t & config

### 4.53.1 Detailed Description

### **PID** Class

Defines a standard feedback loop using the constants kP, kI, kD, deadband, and on\_target\_time. The formula is: out = kP\*error + kI\*integral(d Error) + kD\*(dError/dt)

The PID object will determine it is "on target" when the error is within the deadband, for a duration of on target time

Author

Ryan McGee

Date

4/3/2020

## 4.53.2 Member Enumeration Documentation

# ERROR\_TYPE

```
enum PID::ERROR_TYPE
```

An enum to distinguish between a linear and angular caluclation of PID error.

# 4.53.3 Constructor & Destructor Documentation

# PID()

Create the PID object

config the configuration data for this controller

Create the PID object

### 4.53.4 Member Function Documentation

### get()

```
double PID::get () [override], [virtual]
```

Gets the current PID out value, from when update() was last run

Returns

the Out value of the controller (voltage, RPM, whatever the PID controller is controlling)

Gets the current PID out value, from when update() was last run

Implements Feedback.

# get\_error()

```
double PID::get_error ()
```

Get the delta between the current sensor data and the target

Returns

the error calculated. how it is calculated depends on error\_method specified in pid\_config\_t

Get the delta between the current sensor data and the target

# get\_sensor\_val()

```
double PID::get_sensor_val () const
```

gets the sensor value that we were last updated with

**Returns** 

sensor\_val

4.53 PID Class Reference 91

# get\_target()

```
double PID::get_target () const
```

Get the PID's target

Returns

the target the PID controller is trying to achieve

# init()

Inherited from Feedback for interoperability. Update the setpoint and reset integral accumulation

start\_pt can be safely ignored in this feedback controller

start_pt	commpletely ignored for PID. necessary to satisfy Feedback base	
set_pt	ets the target of the PID controller	
start_vel	completely ignored for PID. necessary to satisfy Feedback base	
end_vel	end_vel sets the target end velocity of the PID controller	

Implements Feedback.

# is\_on\_target()

```
bool PID::is_on_target () [override], [virtual]
```

Checks if the PID controller is on target.

### Returns

true if the loop is within [deadband] for [on\_target\_time] seconds

Returns true if the loop is within [deadband] for [on\_target\_time] seconds

Implements Feedback.

# reset()

```
void PID::reset ()
```

Reset the PID loop by resetting time since 0 and accumulated error.

### set\_limits()

Set the limits on the PID out. The PID out will "clip" itself to be between the limits.

### **Parameters**

lower	ower the lower limit. the PID controller will never command the output go below lower	
upper the upper limit. the PID controller will never command the output go higher than u		

Set the limits on the PID out. The PID out will "clip" itself to be between the limits.

Implements Feedback.

# set\_target()

Set the target for the PID loop, where the robot is trying to end up

4.53 PID Class Reference 93

### **Parameters**

target	the sensor reading we would like to achieve
larget	The sensor reading we would like to deflicte

Set the target for the PID loop, where the robot is trying to end up

### update() [1/2]

Update the PID loop by taking the time difference from last update, and running the PID formula with the new sensor data

#### **Parameters**

### Returns

the new output. What would be returned by PID::get()

Implements Feedback.

### update() [2/2]

Update the PID loop by taking the time difference from last update, and running the PID formula with the new sensor data

## **Parameters**

	sensor_val	val the distance, angle, encoder position or whatever it is we are measuring	
v_setpt Expected velocity setpoint, to subtract from the D term (for vel		Expected velocity setpoint, to subtract from the D term (for velocity control)	

# Returns

the new output. What would be returned by PID::get()

## 4.53.5 Member Data Documentation

### config

```
pid_config_t& PID::config
```

configuration struct for this controller. see pid\_config\_t for information about what this contains

The documentation for this class was generated from the following files:

- pid.h
- pid.cpp

# 4.54 PID::pid\_config\_t Struct Reference

```
#include <pid.h>
```

### **Public Attributes**

• double p

proportional coeffecient p \* error()

• double i

integral coeffecient i \* integral(error)

· double d

derivitave coeffecient d \* derivative(error)

· double deadband

at what threshold are we close enough to be finished

- · double on target time
- ERROR\_TYPE error\_method

# 4.54.1 Detailed Description

pid\_config\_t holds the configuration parameters for a pid controller In addition to the constant of proportional, integral and derivative, these parameters include:

- · deadband -
- on\_target\_time for how long do we have to be at the target to stop As well, pid\_config\_t holds an error type which determines whether errors should be calculated as if the sensor position is a measure of distance or an angle

# 4.54.2 Member Data Documentation

# error\_method

```
ERROR_TYPE PID::pid_config_t::error_method
```

Linear or angular. wheter to do error as a simple subtraction or to wrap

### on\_target\_time

```
double PID::pid_config_t::on_target_time
```

the time in seconds that we have to be on target for to say we are officially at the target

The documentation for this struct was generated from the following file:


· pid.h

# 4.55 screen::PIDPage Class Reference

PIDPage provides a way to tune a pid controller on the screen.

```
#include <screen.h>
```

Inheritance diagram for screen::PIDPage:



#### **Public Member Functions**

- PIDPage (PID &pid, std::string name, std::function < void(void) > onchange=[]() {})
   Create a PIDPage.
- void update (bool was\_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first\_draw, unsigned int frame\_number) override

### 4.55.1 Detailed Description

PIDPage provides a way to tune a pid controller on the screen.

### 4.55.2 Constructor & Destructor Documentation

### PIDPage()

```
screen::PIDPage::PIDPage (
          PID & pid,
          std::string name,
          std::function< void(void) > onchange = []() {})
```

### Create a PIDPage.

### **Parameters**

pid the pid controller we're changing	
name	a name to recognize this pid controller if we've got multiple pid screens
onchange a function that is called when a tuning parameter is changed. If you need to update stuff change register a handler here	

# 4.55.3 Member Function Documentation

# draw()

See also

Page::draw

Reimplemented from screen::Page.

# update()

```
void screen::PIDPage::update (
          bool was_pressed,
          int x,
          int y) [override], [virtual]
```

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:

- screen.h
- screen.cpp

# 4.56 Pose2d Class Reference

```
#include <pose2d.h>
```

#### **Public Member Functions**

- constexpr Pose2d ()
- Pose2d (const Translation2d &translation, const Rotation2d &rotation)
- Pose2d (const double &x, const double &y, const Rotation2d &rotation)
- Pose2d (const double &x, const double &y, const double &radians)
- Pose2d (const Translation2d &translation, const double &radians)
- Pose2d (const Eigen::Vector3d &pose\_vector)
- Translation2d translation () const
- double x () const
- void setX (double x)
- double y () const
- void setY (double y)
- · Rotation2d rotation () const
- void setRotationRad (double rotRad)
- void setRotationDeg (double rotDeg)
- bool operator== (const Pose2d other) const
- Pose2d operator\* (const double &scalar) const
- Pose2d operator/ (const double &scalar) const
- Pose2d operator+ (const Transform2d &transform) const
- Transform2d operator- (const Pose2d &other) const
- Pose2d relative\_to (const Pose2d &other) const
- Pose2d transform by (const Transform2d &transform) const
- Pose2d exp (const Twist2d &twist) const
- Twist2d log (const Pose2d &end\_pose) const

## **Friends**

std::ostream & operator<< (std::ostream &os, const Pose2d &pose)</li>

# 4.56.1 Detailed Description

Class representing a pose in 2d space with x, y, and rotational components

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

#### 4.56.2 Constructor & Destructor Documentation

```
Pose2d() [1/6]
```

```
Pose2d::Pose2d () [inline], [constexpr]
```

Default Constructor for Pose2d

### Pose2d() [2/6]

Constructs a pose with given translation and rotation components.

translation	translational component.
rotation	rotational component.

# Pose2d() [3/6]

Constructs a pose with given translation and rotation components.

### **Parameters**

X	x component.
У	y component.
rotation	rotational component.

# Pose2d() [4/6]

Constructs a pose with given translation and rotation components.

### **Parameters**

X	x component.
У	y component.
radians	rotational component in radians.

# Pose2d() [5/6]

Constructs a pose with given translation and rotation components.

# **Parameters**

translation	translational component.
radians	rotational component in radians.

# Pose2d() [6/6]

Constructs a pose with given translation and rotation components.

pose_vector	vector of the form [x, y, theta].
-------------	-----------------------------------

### 4.56.3 Member Function Documentation

### exp()

Applies a twist (pose delta) to a pose by including first order dynamics of heading.

When applying a twist, imagine a constant angular velocity, the translational components must be rotated into the global frame at every point along the twist, simply adding the deltas does not do this, and using euler integration results in some error. This is the analytic solution that that problem.

Can also be thought of more simply as applying a twist as following an arc rather than a straight line.

See this document for more information on the pose exponential and its derivation. https://file.

tavsys.net/control/controls-engineering-in-frc.pdf#section.10.2

#### **Parameters**

old_pose	The pose to which the twist will be applied.
twist	The twist, represents a pose delta.

#### Returns

new pose that has been moved forward according to the twist.

# log()

The inverse of the pose exponential.

Determines the twist required to go from this pose to the given end pose. suppose you have Pose2d a, Twist2d twist if a.exp(twist) = b then a.log(b) = twist

# **Parameters**

```
end_pose the end pose to find the mapping to.
```

#### Returns

the twist required to go from this pose to the given end

#### operator\*()

Multiplies this pose by a scalar. Simply multiplies each component.

scalar	the scalar value to multiply by.
--------	----------------------------------

# operator+()

Adds a transform to this pose. Transforms the pose in the pose's frame.

### **Parameters**

transform	the change in pose.
-----------	---------------------

# operator-()

Subtracts one pose from another to find the transform between them.

# **Parameters**

other	the pose to subtract.
-------	-----------------------

# operator/()

Divides this pose by a scalar. Simply divides each component.

# **Parameters**

scalar	the scalar value to divide by.

# operator==()

Compares this to another pose.

er the other pose to compare to.	other
----------------------------------	-------

## Returns

true if each of the components are within 1e-9 of each other.

# relative\_to()

Finds the pose equivalent to this pose relative to another arbitrary pose rather than the origin.

#### **Parameters**

other	the pose representing the new origin.
-------	---------------------------------------

## Returns

this pose relative to another pose.

# rotation()

```
Rotation2d Pose2d::rotation () const
```

Returns the rotational component.

## Returns

the rotational component.

# setRotationDeg()

sets the ration value of the rotational component in Degrees

# setRotationRad()

sets the ration value of the rotational component in Radians

# setX()

sets the x value of the translational component.

# setY()

sets the y value of the translational component.

# transform\_by()

Adds a transform to this pose. Simply adds each component.

#### **Parameters**

transform the change in	n pose.
-------------------------	---------

## Returns

the pose after being transformed.

# translation()

```
Translation2d Pose2d::translation () const
```

Returns the translational component.

## Returns

the translational component.

# **x**()

```
double Pose2d::x () const
```

Returns the x value of the translational component.

# Returns

the x value of the translational component.

# **y**()

```
double Pose2d::y () const
```

Returns the y value of the translational component.

Returns

the y value of the translational component.

## 4.56.4 Friends And Related Symbol Documentation

## operator<<

Sends a pose to an output stream. Ex. std::cout << pose;

prints "Pose2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"

The documentation for this class was generated from the following files:

- · pose2d.h
- · pose2d.cpp

## 4.57 PurePursuitCommand Class Reference

```
#include <drive_commands.h>
```

## **Public Member Functions**

- PurePursuitCommand (TankDrive &drive\_sys, Feedback &feedback, PurePursuit::Path path, directionType dir, double max\_speed=1, double end\_speed=0)
- bool run () override
- void on\_timeout () override

# 4.57.1 Detailed Description

Autocommand wrapper class for pure pursuit function in the TankDrive class

## 4.57.2 Constructor & Destructor Documentation

## PurePursuitCommand()

Construct a Pure Pursuit AutoCommand

path	The list of coordinates to follow, in order
dir	Run the bot forwards or backwards
feedback	The feedback controller determining speed
max_speed	Limit the speed of the robot (for pid / pidff feedbacks)

# 4.57.3 Member Function Documentation

# on\_timeout()

```
void PurePursuitCommand::on_timeout () [override]
```

Reset the drive system when it times out

# run()

```
bool PurePursuitCommand::run () [override]
```

Direct call to TankDrive::pure\_pursuit

The documentation for this class was generated from the following files:

- · drive\_commands.h
- drive\_commands.cpp

# 4.58 Rect Struct Reference

```
#include <geometry.h>
```

# 4.58.1 Detailed Description

Describes a Rectangle with a minimum and maximum point

The documentation for this struct was generated from the following file:

· geometry.h

# 4.59 robot\_specs\_t Struct Reference

```
#include <robot_specs.h>
```

## **Public Attributes**

· double robot\_radius

if you were to draw a circle with this radius, the robot would be entirely contained within it

• double odom\_wheel\_diam

the diameter of the wheels used for

double odom\_gear\_ratio

the ratio of the odometry wheel to the encoder reading odometry data

double dist\_between\_wheels

the distance between centers of the central drive wheels

- · double drive\_correction\_cutoff
- Feedback \* drive feedback

the default feedback for autonomous driving

Feedback \* turn\_feedback

the defualt feedback for autonomous turning

PID::pid\_config\_t correction\_pid

the pid controller to keep the robot driving in as straight a line as possible

# 4.59.1 Detailed Description

Main robot characterization struct. This will be passed to all the major subsystems that require info about the robot. All distance measurements are in inches.

#### 4.59.2 Member Data Documentation

# drive\_correction\_cutoff

```
double robot_specs_t::drive_correction_cutoff
```

the distance at which to stop trying to turn towards the target. If we are less than this value, we can continue driving forward to minimize our distance but will not try to spin around to point directly at the target

The documentation for this struct was generated from the following file:

· robot\_specs.h

# 4.60 Rotation2d Class Reference

#include <rotation2d.h>

## **Public Member Functions**

- constexpr Rotation2d ()
- Rotation2d (const double &radians)
- Rotation2d (const double &x, const double &y)
- Rotation2d (const Translation2d &translation)
- double radians () const
- void setRad (double radRot)
- double degrees () const
- void setDeg (double degRot)
- double revolutions () const
- double f\_cos () const
- double f\_sin () const
- double f\_tan () const
- Eigen::Matrix2d rotation\_matrix () const
- double wrapped radians 180 () const
- double wrapped\_degrees\_180 () const
- double wrapped\_revolutions\_180 () const
- double wrapped\_radians\_360 () const
- double wrapped\_degrees\_360 () const
- double wrapped revolutions 360 () const
- Rotation2d operator+ (const Rotation2d &other) const
- Rotation2d operator- (const Rotation2d &other) const
- Rotation2d operator- () const
- Rotation2d operator\* (const double &scalar) const
- Rotation2d operator/ (const double &scalar) const
- bool operator== (const Rotation2d &other) const

## **Friends**

std::ostream & operator<< (std::ostream &os, const Rotation2d &rotation)</li>

## 4.60.1 Detailed Description

Class representing a rotation in 2d space. Stores theta in radians, as well as cos and sin.

Internally this angle is stored continuously, however there are functions that return wrapped angles: "180" is from [-pi, pi), [-180, 180), [-0.5, 0.5) "360" is from [0, 2pi), [0, 360), [0, 1)

## 4.60.2 Constructor & Destructor Documentation

## Rotation2d() [1/4]

```
Rotation2d::Rotation2d () [inline], [constexpr]
```

Default Constructor for Rotation2d

## Rotation2d() [2/4]

Constructs a rotation with the given value in radians.

radians the value of the rotation in radians.

# Rotation2d() [3/4]

Constructs a rotation given x and y values. Does not have to be normalized. The angle from the x axis to the point.

```
[theta] = [atan2(y, x)]
```

## **Parameters**

X	the x value of the point
У	the y value of the point

# Rotation2d() [4/4]

Constructs a rotation given x and y values in the form of a Translation2d. Does not have to be normalized. The angle from the x axis to the point.

```
[theta] = [atan2(y, x)]
```

# **Parameters**

translation

#### 4.60.3 Member Function Documentation

# degrees()

```
double Rotation2d::degrees () const
```

Returns the degree angle value.

## Returns

the degree angle value.

# f\_cos()

```
double Rotation2d::f_cos () const
```

Returns the cosine of the angle value.

Returns

the cosine of the angle value

# f\_sin()

```
double Rotation2d::f_sin () const
```

Returns the sine of the angle value.

Returns

the sine of the angle value.

# f\_tan()

```
double Rotation2d::f_tan () const
```

Returns the tangent of the angle value.

**Returns** 

the tangent of the angle value.

# operator\*()

Multiplies this rotation by a scalar.

# **Parameters**

١	scalar	the scalar value to multiply the rotation by.

## Returns

the rotation multiplied by the scalar.

# operator+()

Adds the values of two rotations using a rotation matrix

 $[new\_cos] = [other.cos, -other.sin][cos] \\ [new\_sin] = [other.sin, other.cos][sin] \\ new\_value = atan2(new\_sin, new\_cos) \\ [new\_cos] \\ [new\_sin] = [other.sin, other.cos][sin] \\ [new\_value] = atan2(new\_sin, new\_cos) \\ [new\_sin] \\ [new\_sin] = [other.sin, other.sin][sin] \\ [new\_sin] = [other.sin, other.sin, other.sin][sin] \\ [new\_sin, other.sin, other.sin,$ 

other	the other rotation to add to this rotation.
-------	---

## **Returns**

the sum of the two rotations.

Adds the values of two rotations using a rotation matrix.

[new\_cos] = [other.cos, -other.sin][cos] [new\_sin] = [other.sin, other.cos][sin] new\_value = atan2(new\_sin, new\_cos)

## **Parameters**

other	the other rotation to add to this rotation.
-------	---

#### Returns

the sum of the two rotations.

## operator-() [1/2]

```
Rotation2d Rotation2d::operator- () const
```

Takes the inverse of this rotation by flipping it. Equivalent to adding 180 degrees.

#### Returns

this inverse of the rotation.

Takes the inverse of this rotation by flipping it.

#### Returns

this inverse of the rotation.

# **operator-()** [2/2]

Subtracts the values of two rotations.

# **Parameters**

other	the other rotation to subtract from this rotation.
-------	--

## Returns

the difference between the two rotations.

# operator/()

Divides this rotation by a scalar.

scalar	the scalar value to divide the rotation by.
Scalai	ine scalar value to divide the rotation by.

# Returns

the rotation divided by the scalar.

# operator==()

Compares two rotations. Returns true if their values are within 1e-9 radians of each other, to account for floating point error.

#### **Parameters**

## Returns

whether the values of the rotations are within 1e-9 radians of each other

# radians()

```
double Rotation2d::radians () const
```

Returns the radian angle value.

## Returns

the radian angle value.

# revolutions()

```
double Rotation2d::revolutions () const
```

Returns the revolution angle value.

## Returns

the revolution angle value.

# rotation\_matrix()

```
Eigen::Matrix2d Rotation2d::rotation_matrix () const
```

Returns the rotation matrix equivalent to this rotation [cos, -sin] R = [sin, cos]

## Returns

the rotation matrix equivalent to this rotation

# setDeg()

sets the angle value in degrees

# setRad()

sets the angle value in radians

# wrapped\_degrees\_180()

```
double Rotation2d::wrapped_degrees_180 () const
```

Returns the degree angle value, wrapped from [-180, 180).

# Returns

the degree angle value, wrapped from [-180, 180)

## wrapped\_degrees\_360()

```
double Rotation2d::wrapped_degrees_360 () const
```

Returns the degree angle value, wrapped from [0, 360).

## Returns

the degree angle value, wrapped from [0, 360)

## wrapped\_radians\_180()

```
double Rotation2d::wrapped_radians_180 () const
```

Returns the radian angle value, wrapped from [-pi, pi).

## Returns

the radian angle value, wrapped from [-pi, pi)

# wrapped\_radians\_360()

```
double Rotation2d::wrapped_radians_360 () const
```

Returns the radian angle value, wrapped from [0, 2pi).

## Returns

the radian angle value, wrapped from [0, 2pi)

# wrapped\_revolutions\_180()

```
double Rotation2d::wrapped_revolutions_180 () const
```

Returns the revolution angle value, wrapped from [-0.5, 0.5).

## Returns

the revolution angle value, wrapped from [-0.5, 0.5)

# wrapped\_revolutions\_360()

```
double Rotation2d::wrapped_revolutions_360 () const
```

Returns the revolution angle value, wrapped from [0, 1).

## Returns

the revolution angle value, wrapped from [0, 1)

# 4.60.4 Friends And Related Symbol Documentation

## operator<<

Sends a rotation to an output stream. Ex. std::cout << rotation;

```
prints "Rotation2d[rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- rotation2d.h
- rotation2d.cpp

# 4.61 ScaledSphericalSimplexSigmaPoints < STATES > Class Template Reference

```
#include <unscented_kalman_filter.h>
```

#### **Public Member Functions**

- ScaledSphericalSimplexSigmaPoints (double alpha=0.001, double beta=2)
- int num\_sigmas ()
- EMat< STATES, NUM\_SIGMAS > square\_root\_sigma\_points (const EVec< STATES > &x, const EMat< STATES, STATES > &S)
- const EVec< NUM SIGMAS > & Wm () const
- const EVec< NUM SIGMAS > & Wc () const
- double Wm (int i) const
- double Wc (int i) const

## 4.61.1 Detailed Description

```
template<int STATES> class ScaledSphericalSimplexSigmaPoints< STATES >
```

Generates sigma points and weights according to the paper [1] This is very different from Wan and Merwe's formulation.

This only requires N + 2 sigma points instead of 2N + 1 sigma points. Rather than generating sigma points symmetrically around the mean, it generates them as vertices of an N-simplex.

The performance of the filter using this reduced set of sigma points is identical to the standard method, so there is no downside to using it here.

[1] A Scaled Spherical Simplex Filter (S3F) with a decreased n + 2 sigma points set size and equivalent 2n + 1 Unscented Kalman Filter (UKF) accuracy

# **Template Parameters**

STATES the dimension of the state. NUM SIGMAS sigma points and weights will be generated.

# 4.61.2 Constructor & Destructor Documentation

# ScaledSphericalSimplexSigmaPoints()

Constructs a sigma point generator for Spherical Simplex sigma points

alpha	Determines the spread of the sigma points around the mean. Smaller values are closer to the mean, this is usually a small value.
beta	Incorporates prior knowledge of the distribution of the state. For Gaussian distributions, beta = 2 is optimal.

# 4.61.3 Member Function Documentation

## num\_sigmas()

```
template<int STATES>
int ScaledSphericalSimplexSigmaPoints< STATES >::num_sigmas () [inline]
```

Returns the number of sigma points, for simplex sigma points this is N+2.

## square\_root\_sigma\_points()

```
template<int STATES> 
 EMat< STATES, NUM_SIGMAS > ScaledSphericalSimplexSigmaPoints< STATES >::square_root_sigma_\leftarrow points ( const EVec< STATES > & x, const EMat< STATES, STATES > & S) [inline]
```

Computes the sigma points given a mean (x) and square-root covariance (S).

## **Parameters**

X	Vector of the means.
S	Square-root covariance.

## Returns

Matrix containing the sigma points. Each column contains one sigma point in the same space as x. The first column is the same as the mean, with the others arranged around the mean.

# Wc() [1/2]

```
template<int STATES>
const EVec< NUM_SIGMAS > & ScaledSphericalSimplexSigmaPoints< STATES >::Wc () const [inline]
```

Returns a vector containing the weights of each sigma point for the covariance.

# Wc() [2/2]

Returns the weight for the i-th sigma point for the covariance.

*i* Element of the weights vector to return.

# Wm() [1/2]

```
template<int STATES>
const EVec< NUM_SIGMAS > & ScaledSphericalSimplexSigmaPoints< STATES >::Wm () const [inline]
```

Returns a vector containing the weights of each sigma point for the mean.

#### Wm() [2/2]

```
template<int STATES>
double ScaledSphericalSimplexSigmaPoints< STATES >::Wm (
          int i) const [inline]
```

Returns the weight for the i-th sigma point for the mean.

# **Parameters**

*i* Element of the weights vector to return.

The documentation for this class was generated from the following file:

· unscented\_kalman\_filter.h

# 4.62 screen::ScreenData Struct Reference

The ScreenData class holds the data that will be passed to the screen thread you probably shouldnt have to use it.

# 4.62.1 Detailed Description

The ScreenData class holds the data that will be passed to the screen thread you probably shouldnt have to use it.

The documentation for this struct was generated from the following file:

· screen.cpp

# 4.63 Serializer Class Reference

Serializes Arbitrary data to a file on the SD Card.

```
#include <serializer.h>
```

## **Public Member Functions**

∼Serializer ()

Save and close upon destruction (bc of vex, this doesnt always get called when the program ends. To be sure, call save to disk)

Serializer (const std::string &filename, bool flush\_always=true)

create a Serializer

· void save to disk () const

saves current Serializer state to disk

void set\_int (const std::string &name, int i)

Setters - not saved until save to disk is called.

• void set\_bool (const std::string &name, bool b)

sets a bool by the name of name to b. If flush\_always == true, this will save to the sd card

void set\_double (const std::string &name, double d)

sets a double by the name of name to d. If flush\_always == true, this will save to the sd card

void set\_string (const std::string &name, std::string str)

sets a string by the name of name to s. If flush\_always == true, this will save to the sd card

• int int or (const std::string &name, int otherwise)

gets a value stored in the serializer. If not found, sets the value to otherwise

bool bool or (const std::string &name, bool otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

double double\_or (const std::string &name, double otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

• std::string string\_or (const std::string &name, std::string otherwise)

gets a value stored in the serializer. If not, sets the value to otherwise

# 4.63.1 Detailed Description

Serializes Arbitrary data to a file on the SD Card.

## 4.63.2 Constructor & Destructor Documentation

# Serializer()

create a Serializer

#### **Parameters**

filename	the file to read from. If filename does not exist we will create that file
flush_always	If true, after every write flush to a file. If false, you are responsible for calling save_to_disk

## 4.63.3 Member Function Documentation

## bool\_or()

gets a value stored in the serializer. If not, sets the value to otherwise

name	name of value
otherwise	value if the name is not specified

# Returns

the value if found or otherwise

# double\_or()

gets a value stored in the serializer. If not, sets the value to otherwise

# **Parameters**

name	name of value
otherwise	value if the name is not specified

#### Returns

the value if found or otherwise

# int\_or()

gets a value stored in the serializer. If not found, sets the value to otherwise

Getters Return value if it exists in the serializer

## **Parameters**

name	name of value
otherwise	value if the name is not specified

## Returns

the value if found or otherwise

## save\_to\_disk()

```
void Serializer::save_to_disk () const
```

saves current Serializer state to disk

forms data bytes then saves to filename this was openned with

# set\_bool()

sets a bool by the name of name to b. If flush\_always == true, this will save to the sd card

#### **Parameters**

name	name of bool
b	value of bool

# set\_double()

sets a double by the name of name to d. If flush\_always == true, this will save to the sd card

## **Parameters**

name	name of double
d	value of double

# set\_int()

Setters - not saved until save\_to\_disk is called.

sets an integer by the name of name to i. If flush\_always == true, this will save to the sd card

## **Parameters**

name	name of integer
i	value of integer

# set\_string()

sets a string by the name of name to s. If flush\_always == true, this will save to the sd card

name	name of string
i	value of string

## string\_or()

gets a value stored in the serializer. If not, sets the value to otherwise

#### **Parameters**

name	name of value
otherwise	value if the name is not specified

#### Returns

the value if found or otherwise

The documentation for this class was generated from the following files:

- · serializer.h
- · serializer.cpp

# 4.64 screen::SliderWidget Class Reference

Widget that updates a double value. Updates by reference so watch out for race conditions cuz the screen stuff lives on another thread.

```
#include <screen.h>
```

#### **Public Member Functions**

• SliderWidget (double &val, double low, double high, Rect rect, std::string name)

Creates a slider widget.

bool update (bool was\_pressed, int x, int y)

responds to user input

• void draw (vex::brain::lcd &, bool first\_draw, unsigned int frame\_number)

Page::draws the slide to the screen

# 4.64.1 Detailed Description

Widget that updates a double value. Updates by reference so watch out for race conditions cuz the screen stuff lives on another thread.

# 4.64.2 Constructor & Destructor Documentation

# SliderWidget()

# Creates a slider widget.

## **Parameters**

val	reference to the value to modify
low	minimum value to go to
high	maximum value to go to
rect	rect to draw it
name	name of the value

## 4.64.3 Member Function Documentation

# update()

```
bool screen::SliderWidget::update (
          bool was_pressed,
          int x,
          int y)
```

# responds to user input

# **Parameters**

was_pressed	if the screen is pressed
X	x position if the screen was pressed
У	y position if the screen was pressed

## Returns

true if the value updated

The documentation for this class was generated from the following files:

- screen.h
- screen.cpp

# 4.65 SpinRPMCommand Class Reference

```
#include <flywheel_commands.h>
```

## **Public Member Functions**

- SpinRPMCommand (Flywheel &flywheel, int rpm)
- bool run () override

# 4.65.1 Detailed Description

File: flywheel\_commands.h Desc: [insert meaningful desc] AutoCommand wrapper class for the spin\_rpm function in the Flywheel class

# 4.65.2 Constructor & Destructor Documentation

# SpinRPMCommand()

# Construct a SpinRPM Command

#### **Parameters**

flywheel	I the flywheel sys to command	
rpm	the rpm that we should spin at	

File: flywheel\_commands.cpp Desc: [insert meaningful desc]

## 4.65.3 Member Function Documentation

#### run()

```
bool SpinRPMCommand::run () [override]
```

Run spin\_manual Overrides run from AutoCommand

## Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- flywheel\_commands.h
- flywheel commands.cpp

# 4.66 PurePursuit::spline Struct Reference

```
#include <pure_pursuit.h>
```

## 4.66.1 Detailed Description

Represents a piece of a cubic spline with  $s(x) = a(x-xi)^3 + b(x-xi)^2 + c(x-xi) + d$  The x\_start and x\_end shows where the equation is valid.

The documentation for this struct was generated from the following file:

· pure pursuit.h

# 4.67 StateMachine< System, IDType, Message, delay\_ms, do\_log >::State Struct Reference

```
#include <state machine.h>
```

#### 4.67.1 Detailed Description

template<typename System, typename IDType, typename Message, int32\_t delay\_ms, bool do\_log = false> struct StateMachine< System, IDType, Message, delay\_ms, do\_log >::State

Abstract class that all states for this machine must inherit from States MUST override respond() and id() in order to function correctly (the compiler won't have it any other way)

The documentation for this struct was generated from the following file:

state\_machine.h

# 4.68 StateMachine< System, IDType, Message, delay\_ms, do\_log > Class Template Reference

State Machine:)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024 Over Under game for our overly complex intake-cata subsystem (see there for an example) The statemachine runs in a background thread and a user thread can interact with it through current state and send message.

```
#include <state_machine.h>
```

## Classes

• class MaybeMessage

MaybeMessage a message of Message type or nothing MaybeMessage  $m = \{\}$ ; // empty MaybeMessage m = Message::EnumField1.

• struct State

## **Public Member Functions**

• StateMachine (State \*initial)

Construct a state machine and immediatly start running it.

• IDType current\_state () const

retrieve the current state of the state machine. This is safe to call from external threads

void send\_message (Message msg)

send a message to the state machine from outside

## 4.68.1 Detailed Description

template<typename System, typename IDType, typename Message, int32\_t delay\_ms, bool do\_log = false> class StateMachine< System, IDType, Message, delay\_ms, do\_log >

State Machine :)))))) A fun fun way of controlling stateful subsystems - used in the 2023-2024 Over Under game for our overly complex intake-cata subsystem (see there for an example) The statemachine runs in a background thread and a user thread can interact with it through current\_state and send\_message.

Designwise: the System class should hold onto any motors, feedback controllers, etc that are persistent in the system States themselves should hold any data that *only* that state needs. For example if a state should be exitted after a certain amount of time, it should hold a timer rather than the System holding that timer. (see Junder from 2024 for an example of this design)

#### **Template Parameters**

System	The system that this is the base class of class Thing: public StateMachine <thing> @tparam IDType The ID enum that recognizes states. Hint hint, use anenum class`</thing>
Message	the message enum that a state or an outside can send and that states respond to
delay_ms	the delay to wait between each state processing to allow other threads to work
do_log	true if you want print statements describing incoming messages and current states. If true, it is expected that IDType and Message have a function called to_string that takes them as its only parameter and returns a std::string

#### 4.68.2 Constructor & Destructor Documentation

#### StateMachine()

Construct a state machine and immediatly start running it.

# **Parameters**

initial	the state that the machine will begin in
miliai	the state that the machine will begin in

# 4.68.3 Member Function Documentation

## current\_state()

```
template<typename System, typename IDType, typename Message, int32_t delay_ms, bool do_log =
false>
IDType StateMachine< System, IDType, Message, delay_ms, do_log >::current_state () const
[inline]
```

retrieve the current state of the state machine. This is safe to call from external threads

# Returns

the current state

## send\_message()

send a message to the state machine from outside

#### **Parameters**

```
msg the message to send This is safe to call from external threads
```

The documentation for this class was generated from the following file:


· state machine.h

# 4.69 screen::StatsPage Class Reference

Draws motor stats and battery stats to the screen.

```
#include <screen.h>
```

Inheritance diagram for screen::StatsPage:



# **Public Member Functions**

- StatsPage (std::map< std::string, vex::motor & > motors)
   Creates a stats page.
- void update (bool was\_pressed, int x, int y) override
- void draw (vex::brain::lcd &, bool first\_draw, unsigned int frame\_number) override

# 4.69.1 Detailed Description

Draws motor stats and battery stats to the screen.

#### 4.69.2 Constructor & Destructor Documentation

# StatsPage()

Creates a stats page.

motors a map of string to motor that we want to draw on this page

#### 4.69.3 Member Function Documentation

## draw()

See also

Page::draw

Reimplemented from screen::Page.

# update()

```
void screen::StatsPage::update (
          bool was_pressed,
          int x,
          int y) [override], [virtual]
```

See also

Page::update

Reimplemented from screen::Page.

The documentation for this class was generated from the following files:


- screen.h
- · screen.cpp

# 4.70 TakeBackHalf Class Reference

A velocity controller.

```
#include <take_back_half.h>
```

Inheritance diagram for TakeBackHalf:



# **Public Member Functions**

- void init (double start\_pt, double set\_pt)
- double update (double val) override
- double get () override
- void set\_limits (double lower, double upper) override
- bool is\_on\_target () override

# **Public Attributes**

· double TBH\_gain

tuned parameter

# 4.70.1 Detailed Description

A velocity controller.

# Warning

If you try to use this as a position controller, it will fail.

#### 4.70.2 Member Function Documentation

## get()

```
double TakeBackHalf::get () [override], [virtual]
```

#### Returns

the last saved result from the feedback controller

Implements Feedback.

# init()

Initialize the feedback controller for a movement

## **Parameters**

start_pt	the current sensor value	
set_pt	set_pt where the sensor value should be	
start_vel Movement starting velocity (IGNORED		
end_vel	Movement ending velocity (IGNORED)	

Implements Feedback.

# is\_on\_target()

```
bool TakeBackHalf::is_on_target () [override], [virtual]
```

#### Returns

true if the feedback controller has reached it's setpoint

Implements Feedback.

# set\_limits()

Clamp the upper and lower limits of the output. If both are 0, no limits should be applied.

## **Parameters**

lower	Upper limit
upper	Lower limit

Implements Feedback.

# update()

Iterate the feedback loop once with an updated sensor value

## **Parameters**

```
val value from the sensor
```

## Returns

feedback loop result

Implements Feedback.

The documentation for this class was generated from the following files:

- · take\_back\_half.h
- · take\_back\_half.cpp

## 4.71 TankDrive Class Reference

```
#include <tank_drive.h>
```

## **Public Types**

enum class BrakeType { None , ZeroVelocity , Smart , TurnOnly }

## **Public Member Functions**

- TankDrive (motor\_group &left\_motors, motor\_group &right\_motors, robot\_specs\_t &config, OdometryBase \*odom=NULL)
- void stop ()
- Pose2d get\_position ()
- void drive\_tank (double left, double right, int power=1, BrakeType bt=BrakeType::None)
- void drive tank raw (double left, double right)
- void drive arcade (double forward back, double left right, int power=1, BrakeType bt=BrakeType::None)
- bool drive\_forward (double inches, directionType dir, Feedback &feedback, double max\_speed=1, double end\_speed=0)
- bool drive\_forward (double inches, directionType dir, double max\_speed=1, double end\_speed=0)
- bool turn degrees (double degrees, Feedback &feedback, double max speed=1, double end speed=0)
- bool turn\_degrees (double degrees, double max\_speed=1, double end\_speed=0)
- bool drive\_to\_point (double x, double y, vex::directionType dir, Feedback &feedback, double max\_speed=1, double end\_speed=0)
- bool drive to point (double x, double y, vex::directionType dir, double max speed=1, double end speed=0)
- bool turn\_to\_heading (double heading\_deg, double max\_speed=1, double end\_speed=0)
- void reset auto ()
- bool pure\_pursuit (PurePursuit::Path path, directionType dir, Feedback &feedback, double max\_speed=1, double end speed=0)

#### **Static Public Member Functions**

• static double modify\_inputs (double input, int power=2)

## 4.71.1 Detailed Description

TankDrive is a class to run a tank drive system. A tank drive system, sometimes called differential drive, has a motor (or group of synchronized motors) on the left and right side

## 4.71.2 Member Enumeration Documentation

## **BrakeType**

```
enum class TankDrive::BrakeType [strong]
```

#### Enumerator

None just send 0 volts to the motors	
ZeroVelocity try to bring the robot to rest. But don't try to hold position	
Smart bring the robot to rest and once it's stopped, try to hold that pos	

## 4.71.3 Constructor & Destructor Documentation

## TankDrive()

## Create the TankDrive object

#### **Parameters**

left_motors	left side drive motors
right_motors	right side drive motors
config	the configuration specification defining physical dimensions about the robot. See robot_specs_t for more info
odom	an odometry system to track position and rotation. this is necessary to execute autonomous paths

## 4.71.4 Member Function Documentation

## drive\_arcade()

Drive the robot using arcade style controls. forward\_back controls the linear motion, left\_right controls the turning.

forward\_back and left\_right are in "percent": -1.0 -> 1.0

# Parameters

forward_back	the percent to move forward or backward	
left_right	the percent to turn left or right	
power modifies the input velocities left^power, right^power		
bt	breaktype. What to do if the driver lets go of the sticks	

Drive the robot using arcade style controls. forward\_back controls the linear motion, left\_right controls the turning.

left\_motors and right\_motors are in "percent": -1.0 -> 1.0

# drive\_forward() [1/2]

Autonomously drive the robot forward a certain distance

# **Parameters**

inches	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
dir	the direction we want to travel forward and backward
max_speed the maximum percentage of robot speed at which the robot will travel. 1 = full power	
end_speed	the movement profile will attempt to reach this velocity by its completion

Autonomously drive the robot forward a certain distance

## **Parameters**

inches	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
dir	the direction we want to travel forward and backward
max_speed the maximum percentage of robot speed at which the robot will travel. 1 = full power	
end_speed	the movement profile will attempt to reach this velocity by its completion

## Returns

true if we have finished driving to our point

# drive\_forward() [2/2]

Use odometry to drive forward a certain distance using a custom feedback controller

Returns whether or not the robot has reached it's destination.

## **Parameters**

inches	the distance to drive forward
dir	the direction we want to travel forward and backward
feedback	the custom feedback controller we will use to travel. controls the rate at which we accelerate and
	drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

# Returns

true when we have reached our target distance

Use odometry to drive forward a certain distance using a custom feedback controller Returns whether or not the robot has reached it's destination.

inches	the distance to drive forward
dir	the direction we want to travel forward and backward
feedback	the custom feedback controller we will use to travel. controls the rate at which we accelerate and
	drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

# drive\_tank()

Drive the robot using differential style controls. left\_motors controls the left motors, right\_motors controls the right motors.

left\_motors and right\_motors are in "percent": -1.0 -> 1.0

#### **Parameters**

left	the percent to run the left motors
right	the percent to run the right motors
power	modifies the input velocities left^power, right^power
bt	breaktype. What to do if the driver lets go of the sticks

# drive\_tank\_raw()

Drive the robot raw-ly

#### **Parameters**

left		the percent to run the left motors (-1, 1)
righ	nt	the percent to run the right motors (-1, 1)

# drive\_to\_point() [1/2]

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot. Here we use the default feedback controller from the drive\_sys

Returns whether or not the robot has reached it's destination.

X	the x position of the target
У	the y position of the target
dir	the direction we want to travel forward and backward
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot. Here we use the default feedback controller from the drive\_sys

Returns whether or not the robot has reached it's destination.

#### **Parameters**

X	the x position of the target
У	the y position of the target
dir	the direction we want to travel forward and backward
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

#### Returns

true if we have reached our target point

## drive\_to\_point() [2/2]

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot.

Returns whether or not the robot has reached it's destination.

## **Parameters**

Х	the x position of the target
У	the y position of the target
dir	the direction we want to travel forward and backward
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Use odometry to automatically drive the robot to a point on the field. X and Y is the final point we want the robot.

Returns whether or not the robot has reached it's destination.

X	the x position of the target
У	the y position of the target
dir	the direction we want to travel forward and backward
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

## **Returns**

true if we have reached our target point

# get\_position()

```
Pose2d TankDrive::get_position ()
```

Returns the Robot position as a Pose2d

# modify\_inputs()

Create a curve for the inputs, so that drivers have more control at lower speeds. Curves are exponential, with the default being squaring the inputs.

#### **Parameters**

input	the input before modification
power	the power to raise input to

# Returns

input ^ power (accounts for negative inputs and odd numbered powers)

Modify the inputs from the controller by squaring / cubing, etc Allows for better control of the robot at slower speeds

# **Parameters**

input	the input signal -1 -> 1
power	the power to raise the signal to

## Returns

input^power accounting for any sign issues that would arise with this naive solution

## pure\_pursuit()

Drive the robot autonomously using a pure-pursuit algorithm - Input path with a set of waypoints - the robot will attempt to follow the points while cutting corners (radius) to save time (compared to stop / turn / start)

#### **Parameters**

path	The list of coordinates to follow, in order
dir	Run the bot forwards or backwards
feedback	The feedback controller determining speed
max_speed	Limit the speed of the robot (for pid / pidff feedbacks)
end_speed	the movement profile will attempt to reach this velocity by its completion

#### Returns

True when the path is complete

Drive the robot autonomously using a pure-pursuit algorithm - Input path with a set of waypoints - the robot will attempt to follow the points while cutting corners (radius) to save time (compared to stop / turn / start)

# **Parameters**

path	The list of coordinates to follow, in order
dir	Run the bot forwards or backwards
feedback	The feedback controller determining speed
max_speed	Limit the speed of the robot (for pid / pidff feedbacks)

# Returns

True when the path is complete

# reset\_auto()

```
void TankDrive::reset_auto ()
```

Reset the initialization for autonomous drive functions

# stop()

```
void TankDrive::stop ()
```

Stops rotation of all the motors using their "brake mode"

## turn\_degrees() [1/2]

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent\_speed (-1.0 -> 1.0)

Uses the defualt turning feedback of the drive system.

#### **Parameters**

degrees	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent\_speed (-1.0 -> 1.0)

Uses the defualt turning feedback of the drive system.

#### **Parameters**

degrees	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

#### Returns

true if we turned te target number of degrees

# turn\_degrees() [2/2]

Autonomously turn the robot X degrees counterclockwise (negative for clockwise), with a maximum motor speed of percent\_speed (-1.0 -> 1.0)

Uses PID + Feedforward for it's control.

# **Parameters**

degrees	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power

Autonomously turn the robot X degrees to counterclockwise (negative for clockwise), with a maximum motor speed of percent\_speed (-1.0 -> 1.0)

Uses the specified feedback for it's control.

degrees	degrees by which we will turn relative to the robot (+) turns ccw, (-) turns cw
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

#### Returns

true if we have turned our target number of degrees

# turn\_to\_heading() [1/2]

Turn the robot in place to an exact heading relative to the field. 0 is forward. Uses the defualt turn feedback of the drive system

#### **Parameters**

heading_deg	the heading to which we will turn
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

Turn the robot in place to an exact heading relative to the field. 0 is forward. Uses the defualt turn feedback of the drive system

## **Parameters**

heading_deg	the heading to which we will turn
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power
end_speed	the movement profile will attempt to reach this velocity by its completion

## Returns

true if we have reached our target heading

# turn\_to\_heading() [2/2]

Turn the robot in place to an exact heading relative to the field. 0 is forward.

heading_deg	the heading to which we will turn	
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.	
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power	
end_speed	the movement profile will attempt to reach this velocity by its completion	

Turn the robot in place to an exact heading relative to the field. 0 is forward.

#### **Parameters**

heading_deg	the heading to which we will turn	
feedback	the feedback controller we will use to travel. controls the rate at which we accelerate and drive.	
max_speed	the maximum percentage of robot speed at which the robot will travel. 1 = full power	
end_speed	the movement profile will attempt to reach this velocity by its completion	

#### Returns

true if we have reached our target heading

The documentation for this class was generated from the following files:

- · tank\_drive.h
- · tank\_drive.cpp

# 4.72 tracking\_wheel\_cfg\_t Struct Reference

#include <odometry\_nwheel.h>

## **Public Attributes**

- double x
- double y
- · double theta rad
- · double radius

# 4.72.1 Detailed Description

## OdometryNWheel

This class handles the code for an N-pod odometry setup, where there are N < WHEELS > free spinning omni wheels (dead wheels) placed in any known configuration on the robot.

Example of a possible wheel configuration:

Where O is the center of rotation. The robot will monitor the changes in rotation of these wheels, use this to calculate a pose delta, then integrate the deltas over time to determine the robot's position.

This is a "set and forget" class, meaning once the object is created, the robot will immediately begin tracking it's movement in the background.

https://rit.enterprise.slack.com/files/U04112Y5RB6/F080M01KPA5/predictperpindiculars2.pdf 2024-2025 Notebook: Entries/Software Entries/Localization/N-Pod Odometry

Author

Jack Cammarata, Richie Sommers

Date

Nov 14 2024 tracking\_wheel\_cfg\_t holds all the specifications for a single tracking wheel The units for x, y, and radius will determine the units of the position estimate

# 4.72.2 Member Data Documentation

## radius

```
double tracking_wheel_cfg_t::radius
```

radius of the wheel

# theta\_rad

```
double tracking_wheel_cfg_t::theta_rad
```

angle between wheel direction and x axis in the robot frame

X

```
\verb|double tracking_wheel_cfg_t:: x|\\
```

x position of the center of the wheel

у

```
double tracking_wheel_cfg_t::y
```

y position of the center of the wheel

The documentation for this struct was generated from the following file:

· odometry\_nwheel.h

# 4.73 Transform2d Class Reference

```
#include <transform2d.h>
```

#### **Public Member Functions**

- constexpr Transform2d ()
- Transform2d (const Translation2d &translation, const Rotation2d &rotation)
- Transform2d (const double &x, const double &y, const Rotation2d &rotation)
- Transform2d (const double &x, const double &y, const double &radians)
- Transform2d (const Translation2d &translation, const double &radians)
- Transform2d (const Eigen::Vector3d &transform\_vector)
- Transform2d (const Pose2d &start, const Pose2d &end)
- Translation2d translation () const
- double x () const
- · double y () const
- · Rotation2d rotation () const
- Transform2d inverse () const
- Transform2d operator\* (const double &scalar) const
- Transform2d operator/ (const double &scalar) const
- Transform2d operator- () const
- bool operator== (const Transform2d & other) const

#### **Friends**

• std::ostream & operator<< (std::ostream &os, const Transform2d &transform)

#### 4.73.1 Detailed Description

Class representing a transformation of a pose2d, or a linear difference between the components of poses.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

#### 4.73.2 Constructor & Destructor Documentation

# Transform2d() [1/7]

```
Transform2d::Transform2d () [constexpr]
```

Default Constructor for Transform2d

# Transform2d() [2/7]

Constructs a transform given translation and rotation components.

#### **Parameters**

translation	the translational component of the transform.
rotation	the rotational component of the transform.

# Transform2d() [3/7]

Constructs a transform given translation and rotation components.

X	the x component of the transform.
У	the y component of the transform.
rotation	the rotational component of the transform.

# Transform2d() [4/7]

Constructs a transform given translation and rotation components.

#### **Parameters**

X	the x component of the transform.
У	the y component of the transform.
radians	the rotational component of the transform in radians.

# Transform2d() [5/7]

Constructs a transform given translation and rotation components.

#### **Parameters**

translation	the translational component of the transform.
radians	the rotational component of the transform in radians.

# Transform2d() [6/7]

Constructs a transform given translation and rotation components given as a vector.

## **Parameters**

transform_vector	vector of the form [x, y, theta]
------------------	----------------------------------

# Transform2d() [7/7]

Constructs a transform given translation and rotation components.

translation	the translational component of the transform.
rotation	the rotational component of the transform.

# 4.73.3 Member Function Documentation

# inverse()

```
Transform2d Transform2d::inverse () const
```

Inverts the transform.

# Returns

the inverted transform.

# operator\*()

Multiplies this transform by a scalar.

# Parameters

scalar	the scalar to multiply this transform by.

# operator-()

```
Transform2d Transform2d::operator- () const
```

Inverts the transform.

# Returns

the inverted transform.

# operator/()

Divides this transform by a scalar.

scalar to divide this transform by.	
-------------------------------------	--

# operator==()

Compares this to another transform.

#### **Parameters**

other the other tra	ansform to compare to.
---------------------	------------------------

#### Returns

true if the components are within 1e-9 of each other.

# rotation()

```
Rotation2d Transform2d::rotation () const
```

Returns the rotational component of the transform.

#### Returns

the rotational component of the transform.

# translation()

```
Translation2d Transform2d::translation () const
```

Returns the translational component of the transform.

# Returns

the translational component of the transform.

# **x**()

```
double Transform2d::x () const
```

Returns the x component of the transform.

# Returns

the x component of the transform.

#### y()

```
double Transform2d::y () const
```

Returns the y component of the transform.

Returns

the y component of the transform.

#### 4.73.4 Friends And Related Symbol Documentation

#### operator<<

Sends a transform to an output stream. Ex. std::cout << transform;

prints "Transform2d[dx: (value), dy: (value), drad: (radians), ddeg: (degrees)]"

Sends a transform to an output stream. Ex. std::cout << transform;

prints "Transform2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"

The documentation for this class was generated from the following files:

- · transform2d.h
- · transform2d.cpp

# 4.74 Translation2d Class Reference

```
#include <translation2d.h>
```

# **Public Member Functions**

- constexpr Translation2d ()
- Translation2d (const double &x, const double &y)
- Translation2d (const Eigen::Vector2d &vector)
- Translation2d (const double &r, const Rotation2d &theta)
- double x () const
- void setX (double x)
- double y () const
- void setY (double y)
- Rotation2d theta () const
- Eigen::Vector2d as\_vector () const
- double norm () const
- double distance (const Translation2d & other) const
- Translation2d rotate\_by (const Rotation2d &rotation) const
- Translation2d rotate around (const Translation2d &other, const Rotation2d &rotation) const
- Translation2d operator+ (const Translation2d &other) const
- Translation2d operator- (const Translation2d &other) const
- Translation2d operator- () const
- Translation2d operator\* (const double &scalar) const
- Translation2d operator/ (const double &scalar) const
- double operator\* (const Translation2d &other) const
- bool operator== (const Translation2d &other) const

#### **Friends**

• std::ostream & operator<< (std::ostream &os, const Translation2d &translation)

# 4.74.1 Detailed Description

Class representing a point in 2d space with x and y coordinates.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

#### 4.74.2 Constructor & Destructor Documentation

# Translation2d() [1/4]

```
Translation2d::Translation2d () [inline], [constexpr]
```

Default Constructor for Translation2d

# Translation2d() [2/4]

Constructs a Translation2d with the given x and y values.

#### **Parameters**

Χ	The x component of the translation.	
У	The y component of the translation.	

# Translation2d() [3/4]

Constructs a Translation2d with the values from the given vector.

#### **Parameters**

	The vector whose values will be used.
vector I	I he vector whose values will be used

# Translation2d() [4/4]

Constructs a Translation2d given polar coordinates of the form (r, theta).

r	The radius (magnitude) of the vector.
theta	The angle (direction) of the vector.

#### 4.74.3 Member Function Documentation

# as\_vector()

```
Eigen::Vector2d Translation2d::as_vector () const
```

Returns the vector as an Eigen::Vector2d.

#### Returns

Eigen::Vector2d with the same values as the translation.

# distance()

Returns the distance between two translations.

# Returns

the distance between two translations.

# norm()

```
double Translation2d::norm () const
```

Returns the norm/radius/magnitude/distance from origin.

# Returns

the norm of the translation.

# operator\*() [1/2]

Returns this translation multiplied by a scalar.

```
[x] = [x] * [scalar] [y] = [y] * [scalar]
```

scalar	the scalar to multiply by.
--------	----------------------------

#### Returns

this translation multiplied by a scalar.

# operator\*() [2/2]

Returns the dot product of two translations.

```
[scalar] = [x][otherx] + [y][othery]
```

# **Parameters**

other the other translation to find the dot product with.

## Returns

the scalar valued dot product.

# operator+()

Returns the sum of two translations.

```
[x] = [x] + [otherx]; [y] = [y] + [othery];
```

#### **Parameters**

other the other translation to add to this translation.

#### Returns

the sum of the two translations.

# **operator-()** [1/2]

```
Translation2d Translation2d::operator- () const
```

Returns the inverse of this translation. Equivalent to flipping the vector across the origin.

$$[x] = [-x][y] = [-y]$$

# Returns

the inverse of this translation.

# operator-() [2/2]

Returns the difference of two translations.

$$[x] = [x] - [otherx] [y] = [y] - [othery]$$

other	the translation to subtract from this translation.
-------	--

#### Returns

the difference of the two translations.

# operator/()

Returns this translation divided by a scalar.

```
[x] = [x] / [scalar] [y] = [y] / [scalar]
```

# **Parameters**

```
scalar the scalar to divide by.
```

#### Returns

this translation divided by a scalar.

# operator==()

Compares two translations. Returns true if their components are each within 1e-9, to account for floating point error.

# **Parameters**

	other	the translation to compare to.
--	-------	--------------------------------

# Returns

whether the two translations are equal.

# rotate\_around()

Applies a rotation to this translation around another given point.

```
[x] = [\cos, -\sin][x - otherx] + [otherx][y] = [\sin, \cos][y - othery] + [othery]
```

other	the center of rotation.
rotation	the angle amount the translation will be rotated.

## Returns

the translation that has been rotated.

# rotate\_by()

Applies a rotation to this translation around the origin.

Equivalent to multiplying a vector by a rotation matrix:  $x = [\cos, -\sin][x] y = [\sin, \cos][y]$ 

#### **Parameters**

Г	rotation	the angle amount the translation will be rotated.
---	----------	---

# Returns

the new translation that has been rotated around the origin.

# setX()

Sets the x value of the translation.

# setY()

Sets the y value of the translation.

# theta()

```
Rotation2d Translation2d::theta () const
```

Returns the angle of the translation.

# Returns

the angle of the translation.

```
x()
```

```
double Translation2d::x () const
```

Returns the x value of the translation.

Returns

the x value of the translation.

#### y()

```
double Translation2d::y () const
```

Returns the y value of the translation.

Returns

the y value of the translation.

# 4.74.4 Friends And Related Symbol Documentation

#### operator <<

Sends a translation to an output stream. Ex. std::cout << translation;

```
prints "Translation2d[x: (value), y: (value)]"
```

Sends a translation to an output stream. Ex. std::cout << translation;

```
prints "Translation2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- · translation2d.h
- · translation2d.cpp

# 4.75 TrapezoidProfile Class Reference

```
#include <trapezoid_profile.h>
```

#### **Public Member Functions**

• TrapezoidProfile (double max v, double accel)

Construct a new Trapezoid Profile object.

• motion t calculate (double time s)

Run the trapezoidal profile based on the time that's ellapsed.

- void set\_endpts (double start, double end)
- void set\_accel (double accel)
- void set max v (double max v)
- double get\_movement\_time ()

# 4.75.1 Detailed Description

#### Trapezoid Profile

This is a motion profile defined by an acceleration, maximum velocity, start point and end point. Using this information, a parametric function is generated, with a period of acceleration, constant velocity, and deceleration. The velocity graph looks like a trapezoid, giving it it's name.

If the maximum velocity is set high enough, this will become a S-curve profile, with only acceleration and decelera-

This class is designed for use in properly modelling the motion of the robots to create a feedfoward and target for PID. Acceleration and Maximum velocity should be measured on the robot and tuned down slightly to account for battery drop.

Here are the equations graphed for ease of understanding: https://www.desmos.com/calculator/rkm3ivulyk

**Author** 

Ryan McGee

Date

7/12/2022

# 4.75.2 Constructor & Destructor Documentation

#### TrapezoidProfile()

Construct a new Trapezoid Profile object.

#### **Parameters**

max↔ _v	Maximum velocity the robot can run at
accel	Maximum acceleration of the robot

# 4.75.3 Member Function Documentation

#### calculate()

Run the trapezoidal profile based on the time that's ellapsed.

time⊷	Time since start of movement
_s	

#### Returns

motion\_t Position, velocity and acceleration

# get\_movement\_time()

```
double TrapezoidProfile::get_movement_time ()
```

uses the kinematic equations to and specified accel and max\_v to figure out how long moving along the profile would take

#### Returns

the time the path will take to travel

# set\_accel()

set\_accel sets the acceleration this profile will use (the left and right legs of the trapezoid)

## **Parameters**

accel the acceleration	n amount to use
------------------------	-----------------

# set\_endpts()

set\_endpts defines a start and end position

#### **Parameters**

start	the starting position of the path
end	the ending position of the path

# set\_max\_v()

sets the maximum velocity for the profile (the height of the top of the trapezoid)

max⊷	the maximum velocity the robot can travel at
_v	

The documentation for this class was generated from the following files:

- · trapezoid\_profile.h
- trapezoid\_profile.cpp

# 4.76 TurnDegreesCommand Class Reference

```
#include <drive_commands.h>
```

#### **Public Member Functions**

- TurnDegreesCommand (TankDrive &drive\_sys, Feedback &feedback, double degrees, double max\_speed=1, double end speed=0)
- bool run () override
- void on\_timeout () override

# 4.76.1 Detailed Description

AutoCommand wrapper class for the turn\_degrees function in the TankDrive class

#### 4.76.2 Constructor & Destructor Documentation

# TurnDegreesCommand()

# Construct a TurnDegreesCommand Command

## **Parameters**

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the turn
degrees	how many degrees to rotate
max_speed	0 -> 1 percentage of the drive systems speed to drive at

#### 4.76.3 Member Function Documentation

## on\_timeout()

```
void TurnDegreesCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we timeout

# run()

```
bool TurnDegreesCommand::run () [override]
```

Run turn\_degrees Overrides run from AutoCommand

#### Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive\_commands.h
- drive\_commands.cpp

# 4.77 TurnToHeadingCommand Class Reference

```
#include <drive_commands.h>
```

# **Public Member Functions**

- TurnToHeadingCommand (TankDrive &drive\_sys, Feedback &feedback, double heading\_deg, double speed=1, double end\_speed=0)
- bool run () override
- · void on\_timeout () override

## 4.77.1 Detailed Description

AutoCommand wrapper class for the turn to heading() function in the TankDrive class

# 4.77.2 Constructor & Destructor Documentation

#### TurnToHeadingCommand()

```
TurnToHeadingCommand::TurnToHeadingCommand (
    TankDrive & drive_sys,
    Feedback & feedback,
    double heading_deg,
    double max_speed = 1,
    double end_speed = 0)
```

Construct a TurnToHeadingCommand Command

drive_sys	the drive system we are commanding
feedback	the feedback controller we are using to execute the drive
heading_deg	the heading to turn to in degrees
max_speed	0 -> 1 percentage of the drive systems speed to drive at

#### 4.77.3 Member Function Documentation

# on\_timeout()

```
void TurnToHeadingCommand::on_timeout () [override]
```

Cleans up drive system if we time out before finishing

reset the drive system if we don't hit our target

# run()

```
bool TurnToHeadingCommand::run () [override]
```

Run turn\_to\_heading Overrides run from AutoCommand

#### Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · drive\_commands.h
- drive\_commands.cpp

#### 4.78 Twist2d Class Reference

#include <twist2d.h>

# **Public Member Functions**

- constexpr Twist2d ()
- Twist2d (const double &dx, const double &dy, const double &dtheta)
- Twist2d (const Eigen::Vector3d &twist\_vector)
- · double dx () const
- · double dy () const
- double dtheta () const
- bool operator== (const Twist2d &other) const
- Twist2d operator\* (const double &scalar) const
- Twist2d operator/ (const double &scalar) const

#### **Friends**

std::ostream & operator<< (std::ostream &os, const Twist2d &twist)</li>

# 4.78.1 Detailed Description

Class representing a difference between two poses, more specifically a distance along an arc from a pose.

Assumes conventional cartesian coordinate system: Looking down at the coordinate plane, +X is right +Y is up +Theta is counterclockwise

# 4.78.2 Constructor & Destructor Documentation

# Twist2d() [1/3]

```
Twist2d::Twist2d () [constexpr]
```

Default Constructor for Twist2d

# Twist2d() [2/3]

Constructs a twist with given translation and angle deltas.

# **Parameters**

dx	the linear dx component.
dy	the linear dy component.
dtheta	the angular dtheta component.

# Twist2d() [3/3]

Constructs a twist with given translation and angle deltas.

# **Parameters**

twist_vector	vector of the form [dx, dy, dtheta]

# 4.78.3 Member Function Documentation

# dtheta()

```
double Twist2d::dtheta () const
```

Returns the angular dtheta component.

#### Returns

the angular dtheta component.

# dx()

```
double Twist2d::dx () const
```

Returns the linear dx component.

#### Returns

the linear dx component.

# dy()

```
double Twist2d::dy () const
```

Returns the linear dy component.

#### Returns

the linear dy component.

# operator\*()

Multiplies this twist by a scalar.

#### **Parameters**

scalar	the scalar value to multiply by.
--------	----------------------------------

# operator/()

Divides this twist by a scalar.

scalar the scalar value to divide by.

# operator==()

Compares this to another twist.

#### **Parameters**

other the other twist to compare to.	
--------------------------------------	--

#### Returns

true if each of the components are within 1e-9 of each other.

#### 4.78.4 Friends And Related Symbol Documentation

# operator<<

```
std::ostream & operator<< (
          std::ostream & os,
          const Twist2d & twist) [friend]</pre>
```

Sends a twist to an output stream. Ex. std::cout << twist;

```
prints "Twist2d[dx: (value), dy: (value), drad: (radians)]"
```

Sends a twist to an output stream. Ex. std::cout << twist;

```
prints "Twist2d[x: (value), y: (value), rad: (radians), deg: (degrees)]"
```

The documentation for this class was generated from the following files:

- twist2d.h
- twist2d.cpp

# 4.79 UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS > Class Template Reference

```
#include <unscented_kalman_filter.h>
```

#### **Public Member Functions**

- UnscentedKalmanFilter (const std::function< StateVector(const StateVector &, const InputVector &)> &f, const std::function< OutputVector(const StateVector &, const InputVector &)> &h, const WithInputIntegrator &integrator, const StateVector &state\_stddevs, const OutputVector &measurement\_stddevs)
- UnscentedKalmanFilter (const std::function< StateVector(const StateVector &, const InputVector &)> &f, const std::function< OutputVector(const StateVector &, const InputVector &)> &h, const WithInputIntegrator &integrator, const StateVector &state\_stddevs, const OutputVector &measurement\_stddevs, const std \circ ::function< StateVector(const EMat< STATES, NUM\_SIGMAS > &, const EVec< NUM\_SIGMAS > &)> &mean\_func\_X, const std::function< OutputVector(const EMat< OUTPUTS, NUM\_SIGMAS > &, const EVec< NUM\_SIGMAS > &)> &mean\_func\_Y, const std::function< StateVector(const StateVector &, const StateVector &, const Output \circ Vector &)> &residual\_func\_X, const std::function< OutputVector(const StateVector &, const StateVector &)> &add func X)
- StateMatrix S () const
- double S (int i, int j) const
- void set S (const StateMatrix &S)
- StateMatrix P () const
- void set\_P (const StateMatrix &P)
- StateVector xhat () const
- double xhat (int i) const
- void set\_xhat (const StateVector &xhat)
- void set\_xhat (int i, double value)
- · void reset ()
- void predict (const InputVector &u, double dt)
- void correct (const InputVector &u, const OutputVector &y)
- void correct (const InputVector &u, const OutputVector &y, const EVec< OUTPUTS > &measurement\_← stddevs)
- template<int ROWS>
  - void correct (const InputVector &u, const EVec< ROWS > &y, const std::function< EVec< ROWS > (const StateVector &, const InputVector &)> &h, const EVec< ROWS > &measurement\_stddevs)
- template<int ROWS>
  - void correct (const InputVector &u, const EVec< ROWS > &y, const std::function< EVec< ROWS > (const StateVector &, const InputVector &)> &h, const EVec< ROWS > measurement\_stddevs, const std  $\leftarrow$  ::function< EVec< ROWS > (const EMat< ROWS, NUM\_SIGMAS > &, const EVec< NUM\_SIGMAS > &)> &mean\_func\_Y, const std::function< EVec< ROWS > (const EVec< ROWS > &, const EVec< ROWS > &)> &residual\_func\_Y, const std::function< StateVector(const StateVector &, const StateVector &)> &residual\_func\_X, const std::function< StateVector(const StateVector &, const StateVector &)> &add\_ $\leftarrow$  func\_X)

#### 4.79.1 Detailed Description

 $template < int \ STATES, \ int \ INPUTS, \ int \ OUTPUTS > \\ class \ Unscented Kalman Filter < \ STATES, \ INPUTS, \ OUTPUTS > \\$ 

Kalman filters combine predictions from a model and measurements to estimate a system's true state.

The Unscented Kalman Filter is a nonlinear estimator, meaning that the model used to predict how the state changes over time can be nonlinear. The model that determines the expected measurement given the current state can also be nonlinear.

At each timestep, sigma points are generated close to the mean, they are all propagated forward in time according to the nonlinear model. The Unscented Transform uses the propagated sigma points to compute the prior state and covariance.

When correcting the state and covariance with a measurement, sigma points are again generated, but are transformed into the measurement space using the measurement function. A Kalman gain matrix K is then computed, and used to update the state and covariance.

To read more about Kalman filters and the standard UKF read: https://github.com/rlabbe/← Kalman-and-Bayesian-Filters-in-Python

This implementation is somewhat non-standard. The square-root form of the UKF (SR-UKF) is used, and the way the sigma points are generated is different than most implementations. The square-root form is used to ensure that the covariance matrix remains positive definite.

To learn more about the SR-UKF, and see the exact formulation that most of this implementation follows, read: https://www.researchgate.net/publication/3908304

The sigma points are not generated symmetrically around the mean, instead they are generated as vertices of a simplex. Using N = # of states, this method uses N + 2 sigma points instead of the standard 2N + 1 sigma points. This reduces computation up to 50%. To learn more about this method, read:  $https://www. \leftarrow sciencedirect.com/science/article/pii/S0888327020308190$ 

This filter uses a method of "recalibrating" by essentially applying a measurement twice instead of once, and only using it if it is more accurate than before the measurement was applied. To learn more about this framework for nonlinear filters, read: https://arxiv.org/pdf/2407.05717

#### **Template Parameters**

STATES	Dimension of the state vector.
INPUTS	Dimension of the control input vector.
OUTPUTS	Dimension of the measurement vector.

#### 4.79.2 Constructor & Destructor Documentation

#### UnscentedKalmanFilter() [1/2]

Constructs an Unscented Kalman Filter.

#### **Parameters**

f	A vector valued function of x and u that returns the derivative of the state vector with respect to time.
h	A vector valued function of x and u that returns the expected measurement at the given state.
integrator	A function from "numerical_integration.h" that integrates a differential equation of the form $f(x, u)$ .
state_stddevs	Standard deviations of the states in the model.
measurement_stddevs	Standard deviations of the measurements.

#### UnscentedKalmanFilter() [2/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::UnscentedKalmanFilter (
             const std::function<br/>< StateVector(const StateVector &, const InputVector &)<br/>> & f,
             \verb|const| std::function| < Output Vector (const State Vector &, const Input Vector &) > & h, \\
             const WithInputIntegrator & integrator,
             const StateVector & state_stddevs,
             const OutputVector & measurement_stddevs,
             const std::function< StateVector(const EMat< STATES, NUM_SIGMAS > &, const EVec<</pre>
NUM_SIGMAS > \&) > \& mean\_func_X,
             const std::function< OutputVector(const EMat< OUTPUTS, NUM_SIGMAS > &, const
EVec< NUM_SIGMAS > \&) > \& mean\_func_Y,
             const std::function< StateVector(const StateVector &, const StateVector &)> &
residual_func_X,
             const std::function< OutputVector(const OutputVector &, const OutputVector &)> &
residual_func_Y,
             const std::function< StateVector(const StateVector &, const StateVector &)> &
add_func_X) [inline]
```

Constructs an Unscented Kalman Filter with custom mean, residual, and addition functions. The most common use for these functions is when you are estimating angles whose arithmetic operations need to be wrapped.

#### **Parameters**

f	A vector valued function of x and u that returns the derivative of the state vector with respect to time.
h	A vector valued function of x and u that returns the expected measurement at the given state.
integrator	A function from "numerical_integration.h" that integrates a differential equation of the form $f(x, u)$ .
state_stddevs	Standard deviations of the states in the model.
measurement_stddevs	Standard deviations of the measurements.
mean_func_X	A function that computes the mean of a matrix containing NUM_SIGMAS state sigma points with a set of weights for each.
mean_func_Y	A function that computes the mean of a matrix containing NUM_SIGMAS measurement sigma points with a set of weights for each.
residual_func_X	A function that computes the residual of two state vectors, usually by simple subtraction.
residual_func_Y	A function that computes the residual of two measurement vectors, usually by simple subtraction.
add_funx_X	A function that adds two state vectors.

# 4.79.3 Member Function Documentation

# correct() [1/4]

```
h, \label{eq:const_evec_rows} \mbox{const_EVec< ROWS} > \& \mbox{\it measurement\_stddevs}) \quad [\mbox{inline}]
```

Correct the state estimate using the measurements in y, a custom measurement function, and custom standard deviations. This is useful for when a different set of measurements are being applied.

#### **Parameters**

U	The control input used in the last predict step.
у	The vector of measurements.
h	A vector valued function of x and u that returns the expected measurement at the given state.
measurement_stddevs	The vector of standard deviations for each measurement to be used for this correct step.

## correct() [2/4]

```
template<int STATES, int INPUTS, int OUTPUTS>
template<int ROWS>
void UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::correct (
             const InputVector & u,
             const EVec< ROWS > & y_{i}
             const std::function< EVec< ROWS > (const StateVector &, const InputVector &) > &
h,
             const EVec< ROWS > measurement_stddevs,
             const std::function< EVec< ROWS > (const EMat< ROWS, NUM_SIGMAS > &, const EVec<
\label{eq:num_sigmas} \mbox{NUM\_SIGMAS} \ > \ \&) > \ \& \ mean\_func\_Y \mbox{,}
             const std::function< EVec< ROWS > (const EVec< ROWS > &, const EVec< ROWS > &)>
& residual_func_Y,
             const std::function< StateVector(const StateVector &, const StateVector &)> &
residual_func_X,
             const std::function< StateVector(const StateVector &, const StateVector &)> &
add_func_X) [inline]
```

Correct the state estimate using the measurements in y, a custom measurement function, custom standard deviations, and custom mean, residual, and addition functions. This is useful for when a different set of measurements are being applied, and they require custom arithmetic functions.

#### **Parameters**

U	The control input used in the last predict step.
у	The vector of measurements.
h	A vector valued function of x and u that returns the expected measurement at the given state.
measurement_stddevs	The vector of standard deviations for each measurement to be used for this correct step.
mean_func_Y	A function that computes the mean of a matrix containing NUM_SIGMAS measurement sigma points with a set of weights for each.
residual_func_X	A function that computes the residual of two state vectors, usually by simple subtraction.
residual_func_Y	A function that computes the residual of two measurement vectors, usually by simple subtraction.
add_funx_X	A function that adds two state vectors.

#### correct() [3/4]

Correct the state estimate using the measurements in y.

#### **Parameters**

и	The control input used in the last predict step.
У	The vector of measurements.

# correct() [4/4]

Correct the state estimate using the measurements in y, and custom standard deviations. This is useful for when the noise in the measurements vary.

#### **Parameters**

и	The control input used in the last predict step.
у	The vector of measurements.
measurement_stddevs	The vector of standard deviations for each measurement to be used for this correct step.

# P()

```
template<int STATES, int INPUTS, int OUTPUTS>
StateMatrix UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::P () const [inline]
```

Returns the reconstructed covariance matrix P.

# predict()

```
template<int STATES, int INPUTS, int OUTPUTS> void UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::predict ( const InputVector & u, double dt) [inline]
```

Projects the state into the future by dt seconds with control input u.

и	The control input.
dt	The timestep in seconds.

#### reset()

```
template<int STATES, int INPUTS, int OUTPUTS>
void UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::reset () [inline]
```

Resets the filter. Make sure to explicitly set S after calling this.

# S() [1/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
StateMatrix UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::S () const [inline]
```

Returns the square-root covariance matrix S.

# S() [2/2]

```
template<int STATES, int INPUTS, int OUTPUTS> double UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::S ( int i, int j) const [inline]
```

Returns one element of the square-root covariance matrix S.

# **Parameters**

i	Row of S.
j	Column of S.

### set\_P()

Set the current square-root covariance matrix S to the square-root of P.

## **Parameters**

```
P The covariance matrix P.
```

#### set\_S()

```
template<int STATES, int INPUTS, int OUTPUTS> void UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::set_S ( const StateMatrix & S) [inline]
```

Set the current square-root covariance matrix S.

S The new square-root covariance matrix S.

## set\_xhat() [1/2]

Set the current state estimate x-hat.

# set\_xhat() [2/2]

Set one element of the current state estimate x-hat.

#### **Parameters**

```
i Row of x-hat.
```

# xhat() [1/2]

```
template<int STATES, int INPUTS, int OUTPUTS>
StateVector UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >::xhat () const [inline]
```

Returns the current state estimate x-hat.

# xhat() [2/2]

Returns one element of the current state estimate x-hat.

#### **Parameters**

```
i Row of x-hat.
```

The documentation for this class was generated from the following file:

unscented\_kalman\_filter.h

#### 4.80 WaitUntilCondition Class Reference

Waits until the condition is true.

```
#include <auto_command.h>
```

# 4.80.1 Detailed Description

Waits until the condition is true.

The documentation for this class was generated from the following file:

· auto\_command.h

# 4.81 WaitUntilUpToSpeedCommand Class Reference

```
#include <flywheel_commands.h>
```

#### **Public Member Functions**

- WaitUntilUpToSpeedCommand (Flywheel &flywheel, int threshold rpm)
- bool run () override

# 4.81.1 Detailed Description

AutoCommand that listens to the Flywheel and waits until it is at its target speed +/- the specified threshold

#### 4.81.2 Constructor & Destructor Documentation

# WaitUntilUpToSpeedCommand()

# Creat a WaitUntilUpToSpeedCommand

## **Parameters**

flywheel	the flywheel system we are commanding
threshold_rpm	the threshold over and under the flywheel target RPM that we define to be acceptable

#### 4.81.3 Member Function Documentation

# run()

```
bool WaitUntilUpToSpeedCommand::run () [override]
```

Run spin\_manual Overrides run from AutoCommand

#### Returns

true when execution is complete, false otherwise

The documentation for this class was generated from the following files:

- · flywheel commands.h
- flywheel\_commands.cpp

# Index

```
Branch, 14
    LinearSystem< STATES, INPUTS, OUTPUTS >,
                                                    ButtonWidget
         56
                                                         screen::ButtonWidget, 15
accel
                                                    С
    OdometryBase, 79
                                                         LinearSystem< STATES, INPUTS, OUTPUTS >,
add
                                                              56
    CommandController, 17, 18
                                                    calculate
    GenericAuto, 43
                                                         FeedForward, 32
add_async
                                                         TrapezoidProfile, 152
    GenericAuto, 43
                                                    choice
add_cancel_func
                                                         AutoChooser, 10
    CommandController, 18
                                                     CommandController, 16
add_delay
                                                         add, 17, 18
    CommandController, 18
                                                         add_cancel_func, 18
    GenericAuto, 44
                                                         add delay, 18
add entry
                                                         CommandController, 17
    ExponentialMovingAverage, 28
                                                         last_command_timed_out, 18
    MovingAverage, 71
                                                         run, 19
ang_accel_deg
                                                    compute X
    OdometryBase, 79
                                                         LinearSystem< STATES, INPUTS, OUTPUTS >,
ang speed deg
                                                              57
    OdometryBase, 79
                                                     compute Y
as_vector
                                                         LinearSystem< STATES, INPUTS, OUTPUTS >,
    Translation2d, 146
Async, 8
                                                    Condition, 19
auto drive
                                                    config
    MecanumDrive, 63
                                                         PID, 93
auto turn
                                                    control continuous
    MecanumDrive, 64
                                                         Lift< T >, 52
AutoChooser, 8
                                                    control manual
    AutoChooser, 9
                                                         Lift< T >, 52
    choice, 10
                                                    control_setpoints
    get choice, 9
                                                         Lift< T >, 52
    list, 10
                                                    Core, 1
AutoChooser::entry t, 27
                                                    correct
    name, 27
                                                         KalmanFilter< STATES, INPUTS, OUTPUTS >,
В
                                                              47.48
    LinearSystem< STATES, INPUTS, OUTPUTS >,
                                                         UnscentedKalmanFilter< STATES, INPUTS, OUT-
                                                              PUTS >, 162-164
         56
background_task
                                                    current_pos
    OdometryBase, 77
                                                         OdometryBase, 79
BasicSolenoidSet, 10
                                                    current state
    BasicSolenoidSet, 10
                                                         StateMachine < System, IDType, Message, de-
    run, 11
                                                              lay_ms, do_log >, 123
BasicSpinCommand, 11
                                                    CustomEncoder, 19
    BasicSpinCommand, 11
                                                         CustomEncoder, 20
    run, 12
                                                         position, 20
BasicStopCommand, 12
                                                         rotation, 20
    BasicStopCommand, 13
                                                         setPosition, 21
    run, 14
                                                         setRotation, 21
bool or
                                                         velocity, 21
    Serializer, 116
                                                    D
BrakeType
                                                         LinearSystem< STATES, INPUTS, OUTPUTS >,
    TankDrive, 128
                                                              57
```

degrees	get_size, 29
Rotation2d, 107	get_value, 29
DelayCommand, 22	f and
DelayCommand, 22	f_cos
run, 22	Rotation2d, 107
distance	f_sin
Translation2d, 146	Rotation2d, 108
double_or	f_tan
Serializer, 117	Rotation2d, 108
draw	Feedback, 29
screen::FunctionPage, 42	get, 30
screen::OdometryPage, 81	init, 30
screen::Page, 86	is_on_target, 30
screen::PIDPage, 96	set_limits, 31
screen::StatsPage, 125	update, 31
drive	FeedForward, 31
MecanumDrive, 64	calculate, 32
drive_arcade	FeedForward, 32
TankDrive, 129	FeedForward::ff_config_t, 33
drive_correction_cutoff	kA, <mark>33</mark>
robot_specs_t, 105	kG, <mark>33</mark>
drive_forward	kS, 33
TankDrive, 129, 130	kV, 34
drive_raw	Filter, 34
MecanumDrive, 65	Flywheel, 34
drive_tank	Flywheel, 35
TankDrive, 131	get_motors, 36
drive_tank_raw	get_target, 36
TankDrive, 131	getRPM, 36
drive_to_point	is_on_target, 36
TankDrive, 131, 132	Page, 36
DriveForwardCommand, 22	spin_manual, 36
DriveForwardCommand, 23	spin_rpm, 37
on_timeout, 24	SpinRpmCmd, 37
run, 24	spinRPMTask, 38
DriveStopCommand, 24	stop, 37
DriveStopCommand, 24	WaitUntilUpToSpeedCmd, 38
run, 25	FlywheelStopCommand, 38
DriveToPointCommand, 25	FlywheelStopCommand, 38
DriveToPointCommand, 25, 26	run, 39
run, 26	FlywheelStopMotorsCommand, 39
dtheta	FlywheelStopMotorsCommand, 39
Twist2d, 158	run, 40
dx	FlywheelStopNonTasksCommand, 40
	FunctionCommand, 40
Twist2d, 158	FunctionCondition, 41
dy	FunctionPage
Twist2d, 158	screen::FunctionPage, 42
end_async	3010cm.ii unotiom ago, 42
OdometryBase, 77	GenericAuto, 43
error method	add, 43
PID::pid_config_t, 94	add_async, 43
ERROR TYPE	add_delay, 44
PID, 89	run, 44
	get
exp Pose2d, 99	Feedback, 30
ExponentialMovingAverage, 27	MotionController, 68
add_entry, 28	PID, 90
ExponentialMovingAverage, 28	TakeBackHalf, 126
ExponentialitiovingAverage, 20	ranobaomium, 120

get_accel	InOrder, 45
OdometryBase, 77	int_or
get_angular_accel_deg	Serializer, 117
OdometryBase, 77	inverse
get_angular_speed_deg	Transform2d, 142
OdometryBase, 77	is_on_target
•	Feedback, 30
get_async Lift $<$ T $>$ , 53	Flywheel, 36
get_choice	MotionController, 68
AutoChooser, 9	PID, 92
get error	TakeBackHalf, 126
PID, 90	is_valid
get_motion	PurePursuit::Path, 88
MotionController, 68	i diei disditi atii, oo
get motors	kA
· -	FeedForward::ff_config_t, 33
Flywheel, 36	KalmanFilter
get_movement_time	KalmanFilter < STATES, INPUTS, OUTPUTS >, 47
TrapezoidProfile, 153	KalmanFilter< STATES, INPUTS, OUTPUTS >, 46
get_points	correct, 47, 48
PurePursuit::Path, 88	KalmanFilter, 47
get_position	P, 48
OdometryBase, 78	predict, 48
TankDrive, 133	reset, 49
get_radius	
PurePursuit::Path, 88	S, 49
get_sensor_val	set_P, 49
PID, 90	set_S, 49
get_setpoint	set_xhat, 50
Lift< T >, 53	xhat, 50
get_size	kG
ExponentialMovingAverage, 29	FeedForward::ff_config_t, 33
MovingAverage, 71	kS
get_speed	FeedForward::ff_config_t, 33
OdometryBase, 78	kV
get_target	FeedForward::ff_config_t, 34
Flywheel, 36	last command timed out
PID, 90	last_command_timed_out
get_value	CommandController, 18
ExponentialMovingAverage, 29	Lift
MovingAverage, 71	Lift< T >, 51
getRPM	Lift< T >, 51
Flywheel, 36	control_continuous, 52
	control_manual, 52
handle	control_setpoints, 52
OdometryBase, 80	get_async, 53
has_message	get_setpoint, 53
StateMachine< System, IDType, Message, de-	hold, 53
lay_ms, do_log >::MaybeMessage, 62	home, 53
hold	Lift, 51
Lift < T >, 53	set_async, 53
home	set_position, 54
Lift< T >, 53	set_sensor_function, 54
	set_sensor_reset, 54
IfTimePassed, 45	set_setpoint, 54
init	Lift< T >::lift_cfg_t, 55
Feedback, 30	LinearSystem
MotionController, 68	${\tt LinearSystem} < {\tt STATES}, {\tt INPUTS}, {\tt OUTPUTS}>,$
PID, 91	56
TakeBackHalf, 126	LinearSystem< STATES, INPUTS, OUTPUTS >, 55

A, 56	None
B, 56	TankDrive, 129
C, 56	norm
compute_X, 57	Translation2d, 146
compute_Y, 57	num_sigmas
D, 57	ScaledSphericalSimplexSigmaPoints < STATES >
LinearSystem, 56	114
list	Odomotry/2\Mhool 72
AutoChooser, 10	Odometry3Wheel, 72
Log	Odometry3Wheel, 74
Logger, 59	tune, 74
log	update, 74
Pose2d, 99	Odometry3Wheel::odometry3wheel_cfg_t, 75
Logf	off_axis_center_dist, 75
Logger, 59	wheel_diam, 75
Logger, 58	wheelbase_dist, 75
Log, 59	OdometryBase, 75
Logf, 59	accel, 79
Logger, 58	ang_accel_deg, 79
LogIn, 60	ang_speed_deg, 79
LogIn	background_task, 77
Logger, 60	current_pos, 79
	end_async, 77
MaybeMessage	get_accel, 77
StateMachine < System, IDType, Message, de-	get_angular_accel_deg, 77
lay_ms, do_log >::MaybeMessage, 61	get_angular_speed_deg, 77
MecanumDrive, 62	get_position, 78
auto_drive, 63	get_speed, 78
auto_turn, 64	handle, 80
drive, 64	mut, 80
drive_raw, 65	OdometryBase, 76
MecanumDrive, 63	set_position, 78
MecanumDrive::mecanumdrive_config_t, 65	smallest_angle, 78
message	speed, 80
StateMachine< System, IDType, Message, de-	update, 79
lay_ms, do_log >::MaybeMessage, 62	OdometryPage
modify_inputs	screen::OdometryPage, 81
TankDrive, 133	OdometryTank, 82
motion_t, 66	OdometryTank, 83
MotionController, 66	set_position, 84
get, 68	update, 84
get_motion, 68	OdomSetPosition, 85
init, 68	OdomSetPosition, 85
is_on_target, 68	run, 85
MotionController, 67	off_axis_center_dist
set_limits, 68	Odometry3Wheel::odometry3wheel_cfg_t, 75
tune_feedforward, 69	on_target_time
update, 69	PID::pid_config_t, 94
MotionController::m_profile_cfg_t, 60	on timeout
MovingAverage, 70	DriveForwardCommand, 24
add_entry, 71	PurePursuitCommand, 104
get_size, 71	TurnDegreesCommand, 155
get_value, 71	TurnToHeadingCommand, 156
MovingAverage, 70, 71	operator<<
mut	Pose2d, 103
OdometryBase, 80	Rotation2d, 112
340mon y 2400, 00	Transform2d, 144
name	Translation2d, 151
AutoChooser::entry_t, 27	Twist2d, 159

operator+	operator<<, 103
Pose2d, 100	operator+, 100
Rotation2d, 108	operator-, 100
Translation2d, 147	operator/, 100
operator-	operator==, 100
Pose2d, 100	operator*, 99
Rotation2d, 109	Pose2d, 97, 98
Transform2d, 142	relative_to, 101
Translation2d, 147	rotation, 101
operator/	setRotationDeg, 101
Pose2d, 100	setRotationRad, 101
Rotation2d, 109	setX, 101
Transform2d, 142	setY, 102
Translation2d, 149	transform_by, 102
Twist2d, 158	translation, 102
operator==	x, 102
Pose2d, 100	y, 102
Rotation2d, 110	position
Transform2d, 143	CustomEncoder, 20
Translation2d, 149	predict
	•
Twist2d, 159	KalmanFilter < STATES, INPUTS, OUTPUTS >, 48 UnscentedKalmanFilter < STATES, INPUTS, OUT-
operator*	
Pose2d, 99	PUTS >, 164
Rotation2d, 108	pure_pursuit
Transform2d, 142	TankDrive, 133
Translation2d, 146, 147	PurePursuit::hermite_point, 44
Twist2d, 158	PurePursuit::Path, 87
P	get_points, 88
KalmanFilter < STATES, INPUTS, OUTPUTS >, 48	get_radius, 88
UnscentedKalmanFilter< STATES, INPUTS, OUT-	is_valid, 88
	Path, 87
PUTS >, 164	PurePursuit::spline, 121
Page	PurePursuitCommand, 103
Flywheel, 36	on_timeout, 104
Parallel, 87	PurePursuitCommand, 103
Path 07	run, 104
PurePursuit::Path, 87	P
PID, 88	radians
config, 93	Rotation2d, 110
ERROR_TYPE, 89	radius
get, 90	tracking_wheel_cfg_t, 138
get_error, 90	Rect, 104
get_sensor_val, 90	relative_to
get_target, 90	Pose2d, 101
init, 91	reset
is_on_target, 92	KalmanFilter < STATES, INPUTS, OUTPUTS >, 49
PID, 89	PID, 92
reset, 92	UnscentedKalmanFilter< STATES, INPUTS, OUT-
set_limits, 92	PUTS >, 165
set_target, 92	reset_auto
update, 93	TankDrive, 134
PID::pid_config_t, 94	revolutions
error_method, 94	Rotation2d, 110
on_target_time, 94	robot_specs_t, 104
PIDPage	drive_correction_cutoff, 105
screen::PIDPage, 95	rotate_around
Pose2d, 96	Translation2d, 149
exp, 99	rotate_by
log, 99	Translation2d, 150
<b>-</b>	•

rotation	ScaledSphericalSimplexSigmaPoints, 113
CustomEncoder, 20	square_root_sigma_points, 114
Pose2d, 101	Wc, 114
Transform2d, 143	Wm, 115
Rotation2d, 105	screen::ButtonWidget, 15
degrees, 107	ButtonWidget, 15
f_cos, 107	update, 16
f_sin, 108	screen::FunctionPage, 41
f_tan, 108	draw, 42
operator<<, 112	FunctionPage, 42
operator+, 108	update, 42
operator-, 109	screen::OdometryPage, 80
operator/, 109	draw, 81
operator==, 110	OdometryPage, 81
operator*, 108	update, 81
radians, 110	screen::Page, 86
revolutions, 110	draw, 86
Rotation2d, 106, 107	update, 86
rotation_matrix, 110	screen::PIDPage, 95
setDeg, 111	draw, 96
setRad, 111	PIDPage, 95
wrapped_degrees_180, 111	update, 96
wrapped_degrees_360, 111	screen::ScreenData, 115
wrapped_radians_180, 111	screen::SliderWidget, 119
wrapped_radians_360, 112	SliderWidget, 120
wrapped_revolutions_180, 112	update, 120
wrapped_revolutions_360, 112	screen::StatsPage, 124
rotation_matrix	draw, 125
Rotation2d, 110	StatsPage, 124
run	update, 125
BasicSolenoidSet, 11	send_message
BasicSpinCommand, 12	StateMachine< System, IDType, Message, de-
BasicStopCommand, 14	lay_ms, do_log >, 123
CommandController, 19	Serializer, 115
DelayCommand, 22	bool_or, 116
DriveForwardCommand, 24	double_or, 117
DriveStopCommand, 25	int_or, 117
DriveToPointCommand, 26	save_to_disk, 117
FlywheelStopCommand, 39	Serializer, 116
FlywheelStopMotorsCommand, 40	
GenericAuto, 44	set_bool, 118
OdomSetPosition, 85	set_bool, 118 set_double, 118
edomeetr content, co	
PurePursuitCommand, 104	set_double, 118
	set_double, 118 set_int, 118
PurePursuitCommand, 104	set_double, 118 set_int, 118 set_string, 118
PurePursuitCommand, 104 SpinRPMCommand, 121	set_double, 118 set_int, 118 set_string, 118 string_or, 119
PurePursuitCommand, 104 SpinRPMCommand, 121 TurnDegreesCommand, 155	set_double, 118 set_int, 118 set_string, 118 string_or, 119 set_accel
PurePursuitCommand, 104 SpinRPMCommand, 121 TurnDegreesCommand, 155 TurnToHeadingCommand, 156 WaitUntilUpToSpeedCommand, 167	set_double, 118 set_int, 118 set_string, 118 string_or, 119 set_accel TrapezoidProfile, 153
PurePursuitCommand, 104 SpinRPMCommand, 121 TurnDegreesCommand, 155 TurnToHeadingCommand, 156 WaitUntilUpToSpeedCommand, 167 S	set_double, 118 set_int, 118 set_string, 118 string_or, 119 set_accel TrapezoidProfile, 153 set_async
PurePursuitCommand, 104 SpinRPMCommand, 121 TurnDegreesCommand, 155 TurnToHeadingCommand, 156 WaitUntilUpToSpeedCommand, 167  S KalmanFilter < STATES, INPUTS, OUTPUTS >, 49	set_double, 118 set_int, 118 set_string, 118 string_or, 119 set_accel TrapezoidProfile, 153 set_async Lift< T >, 53
PurePursuitCommand, 104 SpinRPMCommand, 121 TurnDegreesCommand, 155 TurnToHeadingCommand, 156 WaitUntilUpToSpeedCommand, 167  S KalmanFilter < STATES, INPUTS, OUTPUTS >, 49 UnscentedKalmanFilter < STATES, INPUTS, OUT-	set_double, 118 set_int, 118 set_string, 118 string_or, 119 set_accel TrapezoidProfile, 153 set_async Lift< T >, 53 set_bool Serializer, 118 set_double
PurePursuitCommand, 104 SpinRPMCommand, 121 TurnDegreesCommand, 155 TurnToHeadingCommand, 156 WaitUntilUpToSpeedCommand, 167  S KalmanFilter< STATES, INPUTS, OUTPUTS >, 49 UnscentedKalmanFilter< STATES, INPUTS, OUT-PUTS >, 165	set_double, 118 set_int, 118 set_string, 118 string_or, 119 set_accel TrapezoidProfile, 153 set_async Lift< T >, 53 set_bool Serializer, 118
PurePursuitCommand, 104 SpinRPMCommand, 121 TurnDegreesCommand, 155 TurnToHeadingCommand, 156 WaitUntilUpToSpeedCommand, 167  S KalmanFilter < STATES, INPUTS, OUTPUTS >, 49 UnscentedKalmanFilter < STATES, INPUTS, OUT- PUTS >, 165 save_to_disk	set_double, 118 set_int, 118 set_string, 118 string_or, 119 set_accel TrapezoidProfile, 153 set_async Lift< T >, 53 set_bool Serializer, 118 set_double
PurePursuitCommand, 104 SpinRPMCommand, 121 TurnDegreesCommand, 155 TurnToHeadingCommand, 156 WaitUntilUpToSpeedCommand, 167  S KalmanFilter < STATES, INPUTS, OUTPUTS >, 49 UnscentedKalmanFilter < STATES, INPUTS, OUT- PUTS >, 165 save_to_disk Serializer, 117	set_double, 118 set_int, 118 set_string, 118 string_or, 119 set_accel TrapezoidProfile, 153 set_async Lift< T >, 53 set_bool Serializer, 118 set_double Serializer, 118
PurePursuitCommand, 104 SpinRPMCommand, 121 TurnDegreesCommand, 155 TurnToHeadingCommand, 156 WaitUntilUpToSpeedCommand, 167  S KalmanFilter < STATES, INPUTS, OUTPUTS >, 49 UnscentedKalmanFilter < STATES, INPUTS, OUT- PUTS >, 165 save_to_disk Serializer, 117 ScaledSphericalSimplexSigmaPoints	set_double, 118 set_int, 118 set_string, 118 string_or, 119 set_accel     TrapezoidProfile, 153 set_async     Lift< T >, 53 set_bool     Serializer, 118 set_double     Serializer, 118 set_endpts     TrapezoidProfile, 153 set_int
PurePursuitCommand, 104 SpinRPMCommand, 121 TurnDegreesCommand, 155 TurnToHeadingCommand, 156 WaitUntilUpToSpeedCommand, 167  S KalmanFilter< STATES, INPUTS, OUTPUTS >, 49 UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS >, 165 save_to_disk Serializer, 117 ScaledSphericalSimplexSigmaPoints ScaledSphericalSimplexSigmaPoints<	set_double, 118 set_int, 118 set_string, 118 string_or, 119 set_accel TrapezoidProfile, 153 set_async Lift< T >, 53 set_bool Serializer, 118 set_double Serializer, 118 set_endpts TrapezoidProfile, 153 set_int Serializer, 118
PurePursuitCommand, 104 SpinRPMCommand, 121 TurnDegreesCommand, 155 TurnToHeadingCommand, 156 WaitUntilUpToSpeedCommand, 167  S KalmanFilter < STATES, INPUTS, OUTPUTS >, 49 UnscentedKalmanFilter < STATES, INPUTS, OUT- PUTS >, 165 save_to_disk Serializer, 117 ScaledSphericalSimplexSigmaPoints	set_double, 118 set_int, 118 set_string, 118 string_or, 119 set_accel     TrapezoidProfile, 153 set_async     Lift< T >, 53 set_bool     Serializer, 118 set_double     Serializer, 118 set_endpts     TrapezoidProfile, 153 set_int

MotionController, 68	Flywheel, 36
PID, 92	spin_rpm
TakeBackHalf, 127	Flywheel, 37
set_max_v	SpinRpmCmd
TrapezoidProfile, 153	Flywheel, 37
set_P	SpinRPMCommand, 120
KalmanFilter < STATES, INPUTS, OUTPUTS >, 49	run, 121
UnscentedKalmanFilter< STATES, INPUTS, OUT-	SpinRPMCommand, 121
PUTS >, 165	spinRPMTask
set_position	Flywheel, 38
Lift< T >, 54	square_root_sigma_points
OdometryBase, 78	ScaledSphericalSimplexSigmaPoints < STATES >,
OdometryTank, 84	114
set S	StateMachine
KalmanFilter < STATES, INPUTS, OUTPUTS >, 49	StateMachine< System, IDType, Message, de-
UnscentedKalmanFilter< STATES, INPUTS, OUT-	lay_ms, do_log >, 123
PUTS >, 165	StateMachine System, IDType, Message, delay_ms,
set_sensor_function	do_log >, 122
Lift< T >, 54	current_state, 123
set_sensor_reset	send_message, 123
Lift< T >, 54	StateMachine, 123
set_setpoint Lift< T >, 54	StateMachine < System, IDType, Message, delay_ms,
	do_log >::MaybeMessage, 61
set_string	has_message, 62
Serializer, 118	MaybeMessage, 61
set_target	message, 62
PID, 92	StateMachine System, IDType, Message, delay_ms,
set_xhat	do_log >::State, 122
KalmanFilter < STATES, INPUTS, OUTPUTS >, 50	StatsPage
UnscentedKalmanFilter< STATES, INPUTS, OUT-	screen::StatsPage, 124
PUTS >, 166	stop
setDeg	Flywheel, 37
Rotation2d, 111	TankDrive, 134
setPosition	string_or
CustomEncoder, 21	Serializer, 119
setRad	TakeBackHalf, 125
Rotation2d, 111	get, 126
setRotation	init, 126
CustomEncoder, 21	is_on_target, 126
setRotationDeg	set_limits, 127
Pose2d, 101	
setRotationRad	update, 127
Pose2d, 101	TankDrive, 128
setX	BrakeType, 128
Pose2d, 101	drive_arcade, 129
Translation2d, 150	drive_forward, 129, 130
setY	drive_tank, 131
Pose2d, 102	drive_tank_raw, 131
Translation2d, 150	drive_to_point, 131, 132
SliderWidget	get_position, 133
screen::SliderWidget, 120	modify_inputs, 133
smallest_angle	None, 129
OdometryBase, 78	pure_pursuit, 133
Smart	reset_auto, 134
TankDrive, 129	Smart, 129
speed	stop, 134
OdometryBase, 80	TankDrive, 129
spin_manual	turn_degrees, 134, 135
	turn_to_heading, 136

7 1/1 1/2 100	
ZeroVelocity, 129	turn_to_heading
theta	TankDrive, 136
Translation2d, 150	TurnDegreesCommand, 154
theta_rad	on_timeout, 155
tracking_wheel_cfg_t, 138	run, 155
tracking_wheel_cfg_t, 137	TurnDegreesCommand, 154
radius, 138	TurnToHeadingCommand, 155
theta_rad, 138	on_timeout, 156
x, 138 y, 138	run, 156
Transform2d, 138	TurnToHeadingCommand, 155
inverse, 142	Twist2d, 156 dtheta, 158
operator<<, 144	dx, 158
operator-, 142	dy, 158 dy, 158
operator, 142	operator<<, 159
operator==, 143	operator/, 158
operator*, 142	operator, 159
rotation, 143	operator*, 158
Transform2d, 139, 141	Twist2d, 157
translation, 143	TWISTER, TOT
x, 143	UnscentedKalmanFilter
y, 143	UnscentedKalmanFilter< STATES, INPUTS, OUT-
transform_by	PUTS >, 161
Pose2d, 102	UnscentedKalmanFilter< STATES, INPUTS, OUTPUTS
translation	>, 159
Pose2d, 102	correct, 162-164
Transform2d, 143	P, 164
Translation2d, 144	predict, 164
as_vector, 146	reset, 165
distance, 146	S, 165
norm, 146	set_P, 165
operator<<, 151	set_S, 165
operator+, 147	set_xhat, 166
operator-, 147	UnscentedKalmanFilter, 161
operator/, 149	xhat, 166
operator==, 149	update
operator*, 146, 147	Feedback, 31
rotate around, 149	MotionController, 69
rotate_by, 150	Odometry3Wheel, 74
setX, 150	OdometryBase, 79
setY, 150	OdometryTank, 84
theta, 150	PID, 93
Translation2d, 145	screen::ButtonWidget, 16
x, 150	screen::FunctionPage, 42
y, 151	screen::OdometryPage, 81
TrapezoidProfile, 151	screen::Page, 86
calculate, 152	screen::PIDPage, 96
get_movement_time, 153	screen::SliderWidget, 120
set_accel, 153	screen::StatsPage, 125
set_endpts, 153	TakeBackHalf, 127
set_max_v, 153	1. %
TrapezoidProfile, 152	velocity
tune	CustomEncoder, 21
Odometry3Wheel, 74	WaitUntilCondition, 167
tune_feedforward	WaitUntilUpToSpeedCmd
MotionController, 69	Flywheel, 38
turn_degrees	WaitUntilUpToSpeedCommand, 167
TankDrive, 134, 135	run, 167
	run, 107

```
WaitUntilUpToSpeedCommand, 167
Wc
    {\tt ScaledSphericalSimplexSigmaPoints} < {\tt STATES}>,
         114
wheel_diam
    Odometry3Wheel::odometry3wheel cfg t, 75
wheelbase dist
    Odometry3Wheel::odometry3wheel_cfg_t, 75
Wm
    {\tt ScaledSphericalSimplexSigmaPoints} < {\tt STATES}>,
         115
wrapped_degrees_180
    Rotation2d, 111
wrapped_degrees_360
    Rotation2d, 111
wrapped_radians_180
    Rotation2d, 111
wrapped_radians_360
    Rotation2d, 112
wrapped_revolutions_180
    Rotation2d, 112
wrapped_revolutions_360
    Rotation2d, 112
Х
    Pose2d, 102
    tracking_wheel_cfg_t, 138
    Transform2d, 143
    Translation2d, 150
xhat
    KalmanFilter < STATES, INPUTS, OUTPUTS >, 50
    UnscentedKalmanFilter< STATES, INPUTS, OUT-
         PUTS >, 166
У
    Pose2d, 102
    tracking_wheel_cfg_t, 138
    Transform2d, 143
    Translation2d, 151
ZeroVelocity
    TankDrive, 129
```