

Introduction to recursive CTE

HIERARCHICAL AND RECURSIVE QUERIES IN SQL SERVER



Dominik Egarter

Data Engineering Enthusiast

The recursive CTE

Consists of 4 parts:

```
WITH cte_name AS (  
    -- Anchor member  
    initial_query  
    UNION ALL  
    -- Recursive member  
    recursive_query  
)  
SELECT *  
    FROM cte_name
```

Guide to use recursive CTE

- For more than 200 recursion steps, increase the number of recursion steps,
 - set `OPTION(MAXRECURSION 32767)`
- The following SQL statements are not allowed: `GROUP BY` , `HAVING` , `LEFT JOIN` , `RIGHT JOIN` , `OUTER JOIN` , `SELECT DISTINCT` , `Subqueries` , `TOP`
- The number of columns for anchor and recursive member are the same.
- The data types of anchor and recursive member are the same

Simple recursive example

Calculating the factorial:

The factorial of n is defined by the product of all positive integers less than or equal to n :

$$3! = 1 \times 2 \times 3 = 6$$

The factorial $n!$ is defined recursively as follows:

- $0! = 1$ for iteration = 1
- $(n+1)! = n! * (iteration+1)$ for iteration > 1

Simple recursive example

```
WITH recursion AS
  (SELECT 1 AS iterationCounter, 1 AS factorial
   UNION ALL
   SELECT iterationCounter+1, factorial * (iterationCounter+1)
    FROM recursion
    WHERE iterationCounter < 10 )
SELECT factorial
FROM recursion
```

3628800

Let's practice!

HIERARCHICAL AND RECURSIVE QUERIES IN SQL SERVER

Working with recursive queries

HIERARCHICAL AND RECURSIVE QUERIES IN SQL SERVER

SQL

Dominik Egarter
Data Engineering Enthusiast

The hierarchy of an IT-organization

The organization is described by:

- `ID` - Employee ID
- `Name` of Employee
- `JobTitle` in the company
- `Department` in the company
- `Supervisor` in the company

Fields describing hierarchy:

1. `ID`
2. `Supervisor`

The IT-organization

```
+-----+-----+-----+-----+
|ID | Name          | Position          | Department | Supervisor |
|-----|-----|-----|-----|
| 1 | Heinz Griesser  | IT Director       | IT         | 0          |
| 2 | Andreas Sitter  | Security Manager  | IT         | 1          |
| 3 | Thomas Bergman  | Innovation Manager| IT         | 1          |
| 4 | Hannes Berg     | Operation Manager | IT         | 1          |
| 5 | Anna Krugger    | Administrator     | IT         | 4          |
| 6 | Karin Pacher    | Developer         | IT         | 4          |
+-----+-----+-----+-----+
```

Common tasks for hierarchical data

Get the hierarchy of a record

Who is your supervisor?

Get the level of the hierarchy

Get the hierarchy level of an organization

Combine recursion results into one field

Which supervisors do I have?

Get the hierarchy

```
WITH hierarchy AS (  
    SELECT ID,Supervisor  
        FROM employee  
        WHERE supervisor = 0  
    UNION ALL  
    SELECT emp.ID,emp.Superior  
        FROM employee emp  
    JOIN employeeHierarchy  
        ON emp.Superior = hierarchy.ID)  
SELECT *  
FROM hierarchy
```

Get the hierarchy

```
+---+-----+
|ID |Supervisor |
|---|-----|
|1  | 0          |
|2  | 1          |
|3  | 2          |
+---+-----+
```

Get the level of the hierarchy

```
WITH hierarchy AS (  
    SELECT ID, Supervisor, 1 as LEVEL  
    FROM employee  
    WHERE Supervisor = 0  
  
    UNION ALL  
  
    SELECT emp.ID, emp.Supervisor, LEVEL + 1  
    FROM employee emp  
    JOIN hierarchy  
    ON emp.Supervisor = hierarchy.ID  
)  
  
SELECT *  
FROM hierarchy
```

Get the level of the hierarchy

```
+---+-----+-----+
|ID |Supervisor | Level |
|---|-----|-----|
|1  | 0          | 0     |
|2  | 1          | 1     |
+---+-----+-----+
```

Combine recursion results into one field

```
WITH hierarchy AS (  
    SELECT ID, Supervisor, CAST('0' AS VARCHAR(MAX)) as PATH  
    FROM employee  
    WHERE Supervisor = 0  
    UNION ALL  
    SELECT emp.ID, emp.Supervisor, Path + '->' + CAST(emp.Supervisor AS VARCHAR(MAX))  
    FROM employee emp  
    INNER JOIN hierarchy  
    ON emp.Supervisor = hierarchy.ID  
)  
SELECT *  
FROM hierarchy
```

Combine recursion results into one field

```
+-----+-----+
| PATH          |
|-----|
| 0 -> 1 -> 4  |
+-----+-----+
```


Let's query the IT- organization

HIERARCHICAL AND RECURSIVE QUERIES IN SQL SERVER

Analyze the family tree

HIERARCHICAL AND RECURSIVE QUERIES IN SQL SERVER



Dominik Egarter

Data Engineering Enthusiast


The family tree

The family tree is described by:

- `ID` of the person
- `Name` of the person
- `parentID` the ID of the parent

The elements describing the hierarchy:

- `ID`
- `parentID`



Putting it all together

Remember the following principles about recursive CTEs:

- Initialize the recursion in the anchor member
- Implement the recursion function in the recursion member
- Define a termination condition

Remember the following working principles:

- Get the level of recursion
- Combine the recursion function into one field

Questions about the family tree

Get the number of generations

- Define the `LEVEL`

```
-- Anchor member  
0 as LEVEL  
-- Recursive member  
LEVEL + 1
```

- Count the number of LEVELS to get generations `COUNT(LEVEL)`

```
Generations:  
100
```

Questions about the family tree

Get all possible parents in one field

- Combine recursion results into one field

```
-- Anchor member
CAST(ID AS VARCHAR(MAX)) as Parent
-- Recursive member
Parent + ' -> ' + CAST(parentID AS VARCHAR(MAX))
```

```
+-----+
| Name          | Parent                                |
+-----+-----+
|Dominik Egarter | 100 -> 101 -> 102 ->103            |
+-----+-----+
```

Let's check the family tree

HIERARCHICAL AND RECURSIVE QUERIES IN SQL SERVER