同济大学

TONGJI UNIVERSITY

School of Mechanical Engineering and Robotics
Sino-German Mechanical and Energy Engineering (CDHK)

Bachelor's Thesis

Thermal Debonding of Adhesive Joints in EV Battery Pack Disassembly

A parametric simulation study of localized heating windows for releasing bonded cells without thermal runaway

In partial fulfilment of the requirements for the degree of
Bachelor of Engineering

Author: Matteo Rizzolio

Student ID: 2456368

Supervisor: Prof. Christopher Ehrmann

Shanghai, China

October 2026

Abstract

Contents

1 Introduction **1**

1.1 Background and motivation 1
1.2 Problem statement 1
1.3 Aim and scope of the thesis 1
1.4 Research questions 1
1.5 Structure of the thesis 1

2 Fundamentals and State of the Art **2**

2.1 Adhesive bonding in battery packs 2
2.2 Thermal debonding methods 2
2.2.1 Localized heating methods: laser, induction and resistive heating . 2
2.2.2 Alternative debonding approaches: ultrasonic, cryogenic and reversible adhesives 2
2.3 Thermomechanical behaviour of structural adhesives 2
2.4 Lithium-ion cell thermal safety 2
2.5 Battery dismantling, automation and regulation 2
2.6 Research gap and positioning of this work 2

3 Reference Case and Material Data **3**

3.1 Reference case definition 3
3.2 Geometry and layer stacking 3
3.3 Material properties 3
3.3.1 Adhesive 3
3.3.2 Cell and aluminium adherends 3
3.3.3 Temperature-dependent properties 3
3.4 Operational temperature criteria 3
3.4.1 Adhesive debond threshold T_{debond} 3
3.4.2 Cell safety criterion T_{safe} 3
3.5 Summary of assumptions and data sources 3

4 Theoretical Modelling **4**
4.1 Governing equations of transient heat conduction 4
4.2 Boundary conditions 4
4.2.1 Gaussian surface heat flux 4
4.2.2 Convection and radiation losses 4
4.3 Interface and contact resistance treatment 4
4.4 Dimensional analysis 4
4.4.1 Thermal penetration depth 4
4.4.2 Fourier number 4
4.4.3 Biot number 4
4.5 Definition of the process window 4

5 Finite-Element Model and Verification **5**
5.1 Model geometry and domain extent 5
5.2 Symmetry assumptions and dimensionality 5
5.3 Mesh generation and interface refinement 5
5.4 Mesh-independence study 5
5.5 Energy-balance check 5
5.6 Verification against the semi-infinite-solid solution 5
5.7 Baseline case results 5

6 Parametric Study and Sensitivity Analysis **6**
6.1 Parameter selection and ranges 6
6.2 Uncertain material and interface inputs 6
6.3 Fractional-factorial screening 6
6.4 Local refinement near the feasible-window boundary 6
6.5 Process-window map: heat flux versus duration 6
6.6 Sensitivity analysis 6
6.7 Summary of the parameter study 6

7 Discussion **7**
7.1 Interpretation of the process window 7
7.2 Influence of assumptions and model limitations 7
7.3 Comparison with prior work 7
7.4 Implications for disassembly-oriented design 7
7.5 Threats to validity 7

8 Conclusions and Outlook **8**
8.1 Main findings 8
8.2 Answers to the research questions 8

8.3 Limitations 8
8.4 Future work 8

A Model Parameters **10**

B Supplementary Mesh-Study Data **11**

List of Figures

List of Tables

Chapter 1

Introduction

1.1 Background and motivation

1.2 Problem statement

1.3 Aim and scope of the thesis

1.4 Research questions

1.5 Structure of the thesis

Chapter 2

Fundamentals and State of the Art

2.1 Adhesive bonding in battery packs

2.2 Thermal debonding methods

2.2.1 Localized heating methods: laser, induction and resistive heating

2.2.2 Alternative debonding approaches: ultrasonic, cryogenic and reversible adhesives

2.3 Thermomechanical behaviour of structural adhesives

2.4 Lithium-ion cell thermal safety

2.5 Battery dismantling, automation and regulation

2.6 Research gap and positioning of this work

Chapter 3

Reference Case and Material Data

3.1 Reference case definition

3.2 Geometry and layer stacking

3.3 Material properties

3.3.1 Adhesive

3.3.2 Cell and aluminium adherends

3.3.3 Temperature-dependent properties

3.4 Operational temperature criteria

3.4.1 Adhesive debond threshold T_{debond}

3.4.2 Cell safety criterion T_{safe}

3.5 Summary of assumptions and data sources

Chapter 4

Theoretical Modelling

4.1 Governing equations of transient heat conduction

4.2 Boundary conditions

4.2.1 Gaussian surface heat flux

4.2.2 Convection and radiation losses

4.3 Interface and contact resistance treatment

4.4 Dimensional analysis

4.4.1 Thermal penetration depth

4.4.2 Fourier number

4.4.3 Biot number

4.5 Definition of the process window

Chapter 5

Finite-Element Model and Verification

5.1 Model geometry and domain extent

5.2 Symmetry assumptions and dimensionality

5.3 Mesh generation and interface refinement

5.4 Mesh-independence study

5.5 Energy-balance check

5.6 Verification against the semi-infinite-solid solution

5.7 Baseline case results

Chapter 6

Parametric Study and Sensitivity Analysis

6.1 Parameter selection and ranges

6.2 Uncertain material and interface inputs

6.3 Fractional-factorial screening

6.4 Local refinement near the feasible-window boundary

6.5 Process-window map: heat flux versus duration

6.6 Sensitivity analysis

6.7 Summary of the parameter study

Chapter 7

Discussion

7.1 Interpretation of the process window

7.2 Influence of assumptions and model limitations

7.3 Comparison with prior work

7.4 Implications for disassembly-oriented design

7.5 Threats to validity

Chapter 8

Conclusions and Outlook

8.1 Main findings

8.2 Answers to the research questions

8.3 Limitations

8.4 Future work

Bibliography

Appendix A

Model Parameters

Appendix B

Supplementary Mesh-Study Data