Lumen Freight Shipping API

Version 2026-10. Create rates, book shipments and follow parcels from pickup to delivery.

Authentication

Every request must carry your API key in the Authorization header as Bearer followed by the key. Keys starting with lmn_test_ run against the sandbox and never create a real pickup.

Conventions

Bodies and responses are JSON. Weights are in kilograms and dimensions in centimetres. Timestamps are RFC 3339 in UTC. Postal codes are strings, never numbers.
Errors return a JSON object with code, message and, where useful, the offending field.

1. Get rates

`POST /v1/rates`

Quotes every carrier service for a parcel between two addresses. Send origin and destination objects with country (ISO 3166-1 alpha-2), postal_code and city, plus a parcels array. Each parcel has weight_kg and dimensions_cm with length, width and height. The response lists rates with carrier, service, price (a decimal string with currency), transit_days and quote_id. A quote_id is valid for 30 minutes and is required to create a shipment.

2. Create a shipment

`POST /v1/shipments`

Books the parcel using a quote_id from the rates call. The body also takes the sender and recipient contact details, a label_format of pdf or zpl, and an optional pickup_window with start and end timestamps. A successful call returns 201 with the shipment, its id in the form shp_ followed by 12 characters, a tracking_number, status set to booked, and a label_url.

3. Retrieve a shipment

`GET /v1/shipments/{shipment_id}`

Returns one shipment with its status, parcels, carrier, service, cost and the timestamps of its booking and last update. A shipment that was never booked returns 404.

4. Track a parcel

`GET /v1/tracking/{tracking_number}`

Public tracking for a tracking number issued by any carrier. No API key is needed. The response carries the current status (one of pre_transit, in_transit, out_for_delivery, delivered or exception), an estimated_delivery date, and an events array. Each event has a timestamp, a city, a country code and a description written for the recipient.

Webhooks

Register an HTTPS endpoint in the dashboard to receive tracking.updated events. Each delivery is signed with an HMAC-SHA256 digest of the body in the X-Lumen-Signature header.

Rate limits

Each key may make 60 requests per minute. Above that the API answers 429 with Retry-After.