

Program for multiplying matrices (sequential and omp)

Student: Benno Waldhauer

Table of contents

| | |
|--|---|
| Requirements..... | 1 |
| Installation..... | 1 |
| Use of the programm..... | 1 |
| Run a lot of test cases in one step..... | 2 |
| Logfile..... | 2 |
| Comparison of sequential and omp method..... | 2 |

Requirements

- calculation of $A[n][n] * B[n][n] = C[n][n]$
- different sizes of matrices
- dynamical bufferallocation
- time measurement
- logging
- different methods for multiplication (sequential and parallel with openMP)

Installation

- unpack the benno_waldhauer_seq_omp.zip
- copy all files to your preferred folder
- go to these folder
- type in „make“ to compile the program

Use of the programm

To start the program go to the installationfolder.

There are 2 possibilities to start the program.

1. without passing arguments
 1. type `./prog`
 2. The program welcomes you and ask for the matrices dimensions. Type them in.
 3. Then you will be asked for the print options. Type in 0,1,2 or 3
 4. The program calculates and prints the results, every execution is logged (see log.txt)
2. with passing arguments
 1. type `./prog (int dimension n) (int dimension m) (int dimension p) (int print option)`
e.g. `./prog 500 400 300 1` ($A[p][n] * B[n][p] = C[m][p]$)
e.g. `./prog 100 100 100 0` (print option: 0 nothing, 1 screen, 2 file, 3 screen and file)
 2. The program calculate and print like in the first start possibilty

Run a lot of test cases in one step

To execute a line of test cases execute usecases.sh by typing ./usecases.sh. These script runs the program for a line of matrices dimensions. Every dimension size will be repeated 1 times with sequential and parallel (omp) method. Every execution is logged (look at log.txt) but nothing will be printed to screen or file. The script could be easily customized for different series of tests. For testcases there will be used two square matrices ($A[n][n] * B[n][n] = C[n][n]$)

Logfile

In log.txt every execution will be logged.

The Header of log.txt

```
LogID;Timestamp when Programm starts [s from 01.01.1970];  
m,n,p;Dimensions of the matrices ( $A[m][n] * B[n][p] = C[m][p]$ );  
print option;0=nothing 1=screen 2=file(LogID_xxxxxxxxx.txt) 3=screen and file;  
multipliTime;Time[s] for multiplication;  
multipliType;Type of multiplication;  
numOfProc;Number of Processors on the machine;
```

```
LogID;print option;m;n;p;multipliTime;multipliType;numOfProc;
```

You can easily import the file log.txt easily with e.g. open office calc and work with the logs. (Have a look at ods_import.pdf)

If print option 2 or 3 were chosen, then a file Result_LogID_xxxxxxxxx.txt will be printed. These file also can be easily imported in calculation programs.

All log-files are located in the „log“ folder.

Comparison of sequential and omp method

For very small square matrices the sequential method for multiplication is faster than the parallel method with omp. When the dimensions of the matrices to multiply become bigger than 100×100 , then the omp method becomes faster. So the strengths of omp matrix multiplication is the work with great matrix dimensions. Also have a look at „ods-import.pdf“. There you will find a visual idea of this.