

Glow and trails

Glow and trails

The ring already follows the pointer. This chapter is **look**: a steady halo on every dot, and a short fading trail. Do not change `boot()` or add new script tags.

1. `src/scene/canvas.js` — `clear()`

Keep `resize()` as it is. **Replace the body of `clear()`** (the function at the bottom of the file) so each frame paints a translucent veil instead of a solid wipe:

```
export function clear() {  
  ctx.shadowBlur = 0;  
  ctx.fillStyle = "rgba(7, 11, 20, 0.32)";  
  ctx.fillRect(0, 0, canvas.width, canvas.height);  
}
```

If the veil is too opaque, the tail vanishes at once. If it is too transparent, leftover light fills the screen.

2. `src/particle/particle.js` — `hue` and `draw()`

In the **constructor**, after `this.orbitSpeed = ...`, **add**:

```
this.hue = 195 + Math.random() * 40;
```

Replace the body of `draw()` so the halo size and brightness stay fixed (only hue differs per particle):

```
draw() {  
  ctx.beginPath();  
  ctx.arc(this.x, this.y, this.radius, 0, Math.PI * 2);  
  ctx.fillStyle = `hsla(${this.hue}, 85%, 70%, 0.85)`;  
  ctx.shadowColor = `hsla(${this.hue}, 90%, 68%, 0.9)`;  
  ctx.shadowBlur = 10;
```

```
    ctx.fill();  
  }
```

Do **not** scale radius or shadowBlur from speed. That makes the rush toward the cursor look like a flash.

3. src/particle/field.js — a denser field (optional)

In createParticles(), you may raise the count from 90 to 120:

```
for (let i = 0; i < 120; i += 1) {  
  particles.push(new Particle());  
}
```

4. css/styles.css — background (optional)

On html, body, you may replace the solid background: #070b14 with:

```
background:  
  radial-gradient(circle at 50% 40%, #1a2450 0%, #070b14 62%);
```

Check

Serve over http://. Move the pointer: a colored ring with an **even** glow and light trails, not a white bloom. Leave the window: dots scatter, still with the same halo.