



MONTANA
STATE UNIVERSITY

AJAX



Adding Interactivity To Web Applications

AJAX

- AJAX stands for Asynchronous Javascript and XML
- Technologies for issuing requests *asynchronously* outside of the normal HTML mechanisms
 - Links
 - Forms



AJAX

- Early 1990s - Websites were done with plain HTML pages
 - Each request caused a full page refresh
 - Clunky, but effective and *simple*
- 1998/1999 - Microsoft develops the XMLHttpRequest object (IE5)
- Allowed out of band HTTP requests in Javascript



AJAX

- API was Adopted by other browsers in early 2000s
- Originally XML was used as the data
- Early adopters (2004/2005)
 - GMail
 - Google Maps
 - Kayak
- 2005 - first use of the term AJAX



AJAX

- 2006 W3C standardizes the XMLHttpRequest object
- JSON, rather than XML, becomes the dominant way to transfer data
 - Easy to parse, easy to produce
 - <https://www.json.org/>



AJAX

- 2006 W3C standardizes the XMLHttpRequest object
- JSON, rather than XML, becomes the dominant way to transfer data
 - Easy to parse, easy to produce
 - <https://www.json.org/>



AJAX

- Example working with the raw XMLHttpRequest API
- Pretty ugly, isn't it?

```
var xhr = new XMLHttpRequest();
xhr.open( method: 'GET', url: '/wiki/Ajax_%28programming%29');
xhr.onreadystatechange = function () {
    if (xhr.readyState === 4) {
        if (xhr.status === 200) {
            console.log(xhr.responseText);
        } else {
            console.log('Error: ' + xhr.status);
        }
    }
};
xhr.send( body: null);
```


AJAX

- More modern API: *fetch()*
- I mean, I guess it's better...
- I'm not a big fan of promises and then chaining...

```
fetch( input: '/wiki/Ajax_%28programming%29' ) Promise<Response>  
  .then(response => response.text()) Promise<string>  
  .then(data => console.log(data)) Promise<void>  
  .catch (error => console.log('Error:' + error));
```

SPA

- AJAX technology has been widely adopted
- The rise of the SPA - Single Page Application
 - No full page refreshes
 - All navigation and actions are handled with AJAX
 - Typically client side templates are used to render new UI



React JS



Vue.js




ANGULAR JS

SPA

- SPA Frameworks

- Angular - From google, widely used in enterprise
- React - From facebook, widely used by young people
- Vue.js - Open source, gaining in popularity



React JS



Vue.js



ANGULAR JS

SPA

- Vue.js

- Component oriented
- Components encapsulate HTML and scripting behavior
- Components are reactive to changes in an underlying model
 - Change the greeting var and this component will re-render
- Includes a client-side routing mechanism




```
1 <template lang="jade">
2   div
3     p {{ greeting }} World!
4     other-component
5 </template>
6
7 <script>
8   import OtherComponent from './OtherComponent.vue'
9
10  export default {
11    data () {
12      return {
13        greeting: 'Hello'
14      }
15    },
16    components: {
17      OtherComponent
18    }
19  }
20 </script>
21
22 <style lang="stylus" scoped>
23   p
24     font-size 2em
25     text-align center
26 </style>
```

Line 27, Column 1 Spaces: 2 Vue Component


SPA

- > mfw
- If you want to get a job, you can go ahead and learn React or Vue
- But not in this class
 - Not on my watch




HTMX

- Let me tell you about a little library that I like to call htmx
 - allows you to add AJAX functionality to HTML directly in HTML
 - no javascript required
 - <https://htmx.org>



React JS



</> htmx

HTMX

- History

- Began life as intercooler.js
 - Based on jQuery
 - 4.6k stars on github
 - Part of the github arctic archive:
<https://archiveprogram.github.com/>
- Rewrote intercooler.js w/no jQuery dependency this summer
- Renamed it to htmx

```
<!-- Load from unpkg -->
<script src="https://unpkg.com/htmx.org@0.1.2"></script>
<!-- have a button POST a click via AJAX -->
<button hx-post="/clicked" hx-swap="outerHTML">
  Click Me
</button>
```

HTMX

- Consider this button
 - When a click occurs
 - Issue a POST to /clicked
 - Take the content that is returned and swap it into the outerHTML of this button
- Response is expected to be HTML
 - Not JSON, not XML

```
<!-- Load from unpkg -->
<script src="https://unpkg.com/htmx.org@0.1.2"></script>
<!-- have a button POST a click via AJAX -->
<button hx-post="/clicked" hx-swap="outerHTML">
  Click Me
</button>
```


HTMX

- Request is still issued asynchronously, using the standard XMLHttpRequest object
- Behavior is attribute driven
- There is a scripting layer as well, but not used extensively

```
<!-- Load from unpkg -->
<script src="https://unpkg.com/htmx.org@0.1.2"></script>
<!-- have a button POST a click via AJAX -->
<button hx-post="/clicked" hx-swap="outerHTML">
  Click Me
</button>
```

HTMX

- Core attributes:
 - hx-get, hx-post, hx-put, hx-delete (!!!)
 - hx-target - target another element in the DOM
 - hx-swap - specifies how to swap (default: innerHtml)
 - hx-trigger - specify the event that causes a request to be issued

```
<!-- Load from unpkg -->
<script src="https://unpkg.com/htmx.org@0.1.2"></script>
<!-- have a button POST a click via AJAX -->
<button hx-post="/clicked" hx-swap="outerHTML">
  Click Me
</button>
```

Next Level Search w/ HTMX

- Let's take our track search and next-level it by implementing *Active Search*
- As the user types, we filter the results
- Example code:

<https://htmx.org/examples/active-search/>

Tracks

Search [Advanced Search >>](#)

Track ID	Name	Milliseconds	Bytes	UnitPrice
1	For Those About To Rock (We Salute You)	343719	11170334	0.99
2	Balls to the Wall	342562	5510424	0.99
3	Fast As a Shark	230619	3990994	0.99
4	Restless and Wild	252051	4331779	0.99
5	Princess of the Dawn	375418	6290521	0.99
6	Put The Finger On You	205662	6713451	0.99
7	Let's Get It Up	233926	7636561	0.99
8	Inject The Venom	210834	6852860	0.99
9	Snowballed	203102	6599424	0.99
10	Evil Walks	263497	8611245	0.99

Next Level Search w/ HTMX

- Step 1: separate the table of results out to a new, independent template
 - Include it in the original index.vm file
 - Surround it with a div tag

```
<div id="results">  
  #parse('templates/tracks/table.vm')  
</div>
```

Next Level Search w/ HTMX

- Step 2: Add htmx attributes to our search input
 - hx-get - issue a request to /tracks
 - hx-push-url - you'll see
 - hx-trigger - trigger on a key up event, but only if it has been 500ms and the value of the input has changed
 - hx-target - put the response in the new div we created

```
<div id="search"></div>
<input type="text" placeholder="Search by track, album or artist name..."
      name="q"
      value="{{$web.param('q')}}"
      hx-get="/tracks"
      hx-push-url="true"
      hx-trigger="keyup changed delay:500ms"
      hx-target="#results">
```

Next Level Search w/ HTMX

- Step 3: fix up the controller code
 - If this is an htmx request (indicated by the HX-Request header) render only the table
 - Otherwise, render the whole page

```
/* READ */
get( path: "/tracks", (req, resp) -> {
    String search = req.queryParams("q");
    List<Track> tracks;
    if (search != null) {
        tracks = Track.search(Web.getPage(), Web.PAGE_SIZE, search);
    } else {
        tracks = Track.all(Web.getPage(), Web.PAGE_SIZE);
    }
    if (req.headers("HX-Request") != null) {
        return Web.renderTemplate( index: "templates/tracks/table.vm",
                                   ...args: "tracks", tracks);
    } else {
        return Web.renderTemplate( index: "templates/tracks/index.vm",
                                   ...args: "tracks", tracks);
    }
});
```

Next Level Search w/ HTMX

- That's it!
- We are rockin' and rollin' with active search for tracks
- I *assure* you, this is impressive

```
/* READ */
get( path: "/tracks", (req, resp) -> {
    String search = req.queryParams("q");
    List<Track> tracks;
    if (search != null) {
        tracks = Track.search(Web.getPage(), Web.PAGE_SIZE, search);
    } else {
        tracks = Track.all(Web.getPage(), Web.PAGE_SIZE);
    }
    if (req.headers("HX-Request") != null) {
        return Web.renderTemplate( index: "templates/tracks/table.vm",
                                   ...args: "tracks", tracks);
    } else {
        return Web.renderTemplate( index: "templates/tracks/index.vm",
                                   ...args: "tracks", tracks);
    }
});
```

HTMX

- There are lots of other examples and demos on the htmx website
- There is actually a pretty good theoretical basis for htmx based on REST

```
<!-- Load from unpkg -->  
<script src="https://unpkg.com/htmx.org@0.1.2"></script>  
<!-- have a button POST a click via AJAX -->  
<button hx-post="/clicked" hx-swap="outerHTML">  
  Click Me  
</button>
```

HTMX

- REST: REpresentational State Transfer
 - The original theoretical basis for the web
 - Codified the notion of *hypermedia*
 - The stateless exchange of hypermedia *representations* of server resources

```
<!-- Load from unpkg -->  
<script src="https://unpkg.com/htmx.org@0.1.2"></script>  
<!-- have a button POST a click via AJAX -->  
<button hx-post="/clicked" hx-swap="outerHTML">  
  Click Me  
</button>
```

HTMX

- A radical departure from older networking models
- One of the reasons why the web is so resilient is this new concept
- Htmx is firmly based on REST-ful principles
 - Most other front end libraries today are not

```
<!-- Load from unpkg -->
<script src="https://unpkg.com/htmx.org@0.1.2"></script>
<!-- have a button POST a click via AJAX -->
<button hx-post="/clicked" hx-swap="outerHTML">
  Click Me
</button>
```

Ajax Summary

- Htmx is really, really rad
 - Active search in a few attributes!?!?
- You should star it on Github
 - And tell all your friends about it
- Also: htmx is rad



htmx.org
@htmx_org

the htmx developer starter kit

- print out
- tape to wall





MONTANA
STATE UNIVERSITY