

# Nudge API Documentation

## Object Data Model for Nudge

A "nudge" represents a notification or alert associated with an event. Below is the structure of the nudge object:

- type: "nudge"
- id: MongoDB ObjectId (unique identifier)
- event\_id: MongoDB ObjectId (references the associated event)
- title: String (title of the nudge)
- cover\_image: File (uploaded image as the nudge cover)
- send\_time: Timestamp (date and time to send the nudge)
- description: String (detailed description of the nudge)
- icon: File (uploaded icon image for the nudge)
- invitation: String (one-line invitation text)
- status: String (e.g., "scheduled", "sent", "cancelled")

## Base URL

Base URL: /api/v3/app

## API Endpoints

Request Type	Endpoint	Payload	Description
GET	/nudges/:id	-	Retrieves a specific nudge by its unique ID.
GET	/nudges?event_id=:id	-	Retrieves all nudges associated with a specific event.
POST	/nudges	event_id, title, cover_image, send_time, description, icon, invitation, status	Creates a new nudge and returns the created nudge's ID.
PUT	/nudges/:id	event_id, title, cover_image, send_time, description, icon, invitation, status	Updates an existing nudge by its ID.

Name :- Raj Kashyap

Request Type	Endpoint	Payload	Description
DELETE	/nudges/:id	-	Deletes a specific nudge by its unique ID.

CRUD Functionalities

1. Get a Nudge

Description: Fetches a specific nudge by its unique ID.

- Request Type: GET
- Endpoint: /nudges/:id
- Payload: None
- Response:

json

```
{
  "id": "64a8f4d52f0034abc1234567",
  "event_id": "64a8f4d52f0034abc7654321",
  "title": "Event Reminder",
  "cover_image": "https://example.com/image.jpg",
  "send_time": "2024-11-22T18:00:00Z",
  "description": "Don't miss the upcoming event!",
  "icon": "https://example.com/icon.jpg",
  "invitation": "Join us for the big day!",
  "status": "scheduled"
}
```

2. Create a Nudge

Description: Creates a new nudge.

- Request Type: POST
- Endpoint: /nudges
- Payload:

json

```
{
  "event_id": "64a8f4d52f0034abc7654321",
  "title": "Event Reminder",
  "cover_image": "file (multipart upload)",
  "send_time": "2024-11-22T18:00:00Z",
  "description": "Don't miss the upcoming event!",
  "icon": "file (multipart upload)",
  "invitation": "Join us for the big day!",
}
```

Name :- Raj Kashyap

```
{  
  "status": "scheduled"  
}
```

- **Response:**

json

```
{  
  "id": "64a8f4d52f0034abc1234567",  
  "message": "Nudge created successfully"  
}
```

### 3. Update a Nudge

**Description:** Updates an existing nudge by its unique ID.

- **Request Type:** PUT
- **Endpoint:** /nudges/:id
- **Payload:**

json

```
{  
  "title": "Updated Event Reminder",  
  "send_time": "2024-11-23T10:00:00Z",  
  "description": "Updated description",  
  "invitation": "Updated invitation text",  
  "status": "cancelled"  
}
```

- **Response:**

json

```
{  
  "message": "Nudge updated successfully"  
}
```

### 4. Delete a Nudge

**Description:** Deletes a nudge by its unique ID.

- **Request Type:** DELETE
- **Endpoint:** /nudges/:id
- **Payload:** None
- **Response:**

json

```
{  
  "message": "Nudge deleted successfully"  
}
```

Name :- Raj Kashyap

## 5. Get Nudges for an Event

**Description:** Fetches all nudges associated with a specific event.

- **Request Type:** GET
- **Endpoint:** /nudges?event\_id=:id
- **Payload:** None
- **Response:**

json

```
[
  {
    "id": "64a8f4d52f0034abc1234567",
    "title": "Event Reminder 1",
    "send_time": "2024-11-22T18:00:00Z",
    "status": "scheduled"
  },
  {
    "id": "64a8f4d52f0034abc7654321",
    "title": "Event Reminder 2",
    "send_time": "2024-11-23T12:00:00Z",
    "status": "sent"
  }
]
```

---

## Error Handling

- **400 Bad Request:** Missing or invalid payload.
- **404 Not Found:** Nudge or event not found.
- **500 Internal Server Error:** Unexpected server error.