## Definition: Binary Operation

### **Definition: Binary Operation**

Let S be a Set. A binary operation on S is a function  $\star : S \times S \to S$ .

### Explanation

A binary operation takes two elements from a set and produces another element from the same set. We often write  $a \star b$  instead of  $\star (a, b)$ .

### **Properties of Binary Operations**

A binary operation  $\star$  on a set S may satisfy various properties:

- 1. Closure: By definition,  $a \star b \in S$  for all  $a, b \in S$
- 2. Associativity:  $(a \star b) \star c = a \star (b \star c)$  for all  $a, b, c \in S$
- 3. Commutativity:  $a \star b = b \star a$  for all  $a, b \in S$
- 4. **Identity element**: There exists  $e \in S$  such that  $a \star e = e \star a = a$  for all  $a \in S$
- 5. **Inverse elements**: For each  $a \in S$ , there exists  $b \in S$  such that  $a \star b = b \star a = e$  (where e is the identity)

#### Examples


Common binary operations include:

- Addition (+) on the integers  $\mathbb{Z}$
- Multiplication ( $\cdot$ ) on the real numbers  $\mathbb R$
- Matrix multiplication on  $n \times n$  matrices
- Composition of functions

#### See Also

- Definition: Group (uses this concept)
- Example: Integers under Addition (illustrates this concept)

# Dependency Graph



Local dependency graph