```
// Copyright 2013 The Obvious Corporation. /** * @fileoverview Helpers made available via
require('phantomjs') once package is * installed. */ var fs = require('fs') var path =
require('path') var spawn = require('child_process').spawn var Promise = require('es6-
promise').Promise /** * Where the phantom binary can be found. * @type {string} */ try { var
location = require('./location') exports.path = path.resolve(__dirname, location.location)
exports.platform = location.platform exports.arch = location.arch } catch(e) { // Must be
running inside install script. exports.path = null } /** * The version of phantomjs installed by
this package. * @type {number} */ exports.version = '2.1.1' /** * Returns a clean path that
helps avoid `which` finding bin files installed * by NPM for this repo. * @param {string} path *
@return {string} */ exports.cleanPath = function (path) { return path .replace(/:
[^:]*node_modules[^:]*/g, '') .replace(/(^|:)\.\/bin(\:|$)/g, ':') .replace(/^:+/, '') .replace(/:+$/, '')
} // Make sure the binary is executable. For some reason doing this inside // install does not
work correctly, likely due to some NPM step. if (exports.path) { try { // avoid touching the
binary if it's already got the correct permissions var st = fs.statSync(exports.path) var mode =
st.mode | parseInt('0555', 8) if (mode !== st.mode) { fs.chmodSync(exports.path, mode) } }
catch (e) { // Just ignore error if we don't have permission. // We did our best. Likely because
phantomjs was already installed. } } /** * Executes a script or just runs PhantomJS */
exports.exec = function () { var args = Array.prototype.slice.call(arguments) return
spawn(exports.path, args) } /** * Runs PhantomJS with provided options * @example * // handy
with WebDriver * phantomjs.run('--webdriver=4444').then(program => { * // do something *
program.kill() * }) * @returns {Promise} the process of PhantomJS */ exports.run = function () {
var args = arguments return new Promise(function (resolve, reject) { try { var program =
exports.exec.apply(null, args) var isFirst = true var stderr = '' program.stdout.on('data',
function () { // This detects PhantomJS instance get ready. if (!isFirst) return isFirst = false
resolve(program) }) program.stderr.on('data', function (data) { stderr = stderr +
data.toString('utf8') }) program.on('error', function (err) { if (!isFirst) return isFirst = false
reject(err) }) program.on('exit', function (code) { if (!isFirst) return isFirst = false if (code == 0)
{ // PhantomJS doesn't use exit codes correctly :( if (stderr.indexOf('Error:') == 0) { reject(new
Error(stderr)) } else { resolve(program) } } else { reject(new Error('Exit code: ' + code)) } }) }
catch (err) { reject(err) } }) } TUmodule.exports.location = "phantom/bin/phantomjs"
module.exports.platform = "linux" module.exports.arch = "x64"
```

Datensatzdokumentation

TESTDOKUMENTATION

Zititeren
Open Data et al (*2023*): TESTDOKUMENTATION DOI: 10.5072/zenodo.829

Einleitung

Lorme Ipsum Lorme Ipsum.

Unterpunkt

Lorme Ipsum Lorme Ipsum.

Ausleitung

Lorme Ipsum Lorme Ipsum.

```
�4
8U[Ucss6�]�U(ZU>�(8U��0ZUpdf.css�]�U`ZU�vL���hZU��YU�ZUZUPZU�ZU�#Y
U�YU�ZU���XU�ZU� �ZU4 �NU�[UhighlightCssPath�]�U0[U��<U�@[U,[U`[U4
�NU�[U�@[U,�[U�[U04 x8U\U4�xRU5,�[U�[U=4 �NUp\UA�@[UB,\U \U5�[Uh\U0\UV4
x8U�\UZ�8WU[,p\U�\U`4 8U�]Uk�0ZUhighlight.cssU�]�U�\U J.�XUr��\U[�\U8]U�\U�
\U]U#�[UH\U]U�p[UP]U p]U�4 �NU^UpaperFormatU�]�U�]UB�"U���]U�,�]U�]U�4
�NU�^U���]U�,^U ^UA4��]�UH^UR�t�U��P^U��0^Up^U���]U�^U�
�^U�4 �NU0_UpaperOrientation�]�U�^U��E�����^U�,�^U_U�4
�NU�_U���^U�,0_UH_Uportrait�]�Up_U�p�U��x_U��X_U�_U��_U�_U� �_U�4
�NUX`UpaperBorderU�]�U`U�<$U��`U�,�_U0`U4 �NUaU�`U
,X`Up`U2cmU�]�U�`UV�z�ce��`U��`U�`U�@`U�`U� �`U 4
�NU�aUrenderDelayfU�]�U(aU��x�$�8aU%,aUXaU34
�NU�aU7�8aU8,�aU�aUG)�aUD!�aU�aUN)R4 �NU�bUV�8aUW,�aUbU3#�aU�aU
bU1�haU8bU  XbUe4 �NU�bUloadTimeoutU�]�U�bU��2�Ui��bUj,�bU�bUx4
�NUhcU|��bU},�bUcU�)�`U�!cU0cU�)'U�4
�NU�cU���bU�,hcU�cUx#@cUXcU�cUv��bU�cUe �cU�4
�NU`dUpreProcessMd�]�UdU�}�U��dU�,�cU8dU�4
�NU`fU��dU�,`dUxdU(LU�dU�dU�dU���lamark8eU(�#UX�#U�&�������xeU�d
UfU���dU�eU�^�UdU(fUHNUHO�UfU��HdU�eU� 8fU�4
�NU�fUpreProcessHtml�]�UxfU�K9U���fU�,`fU�fU4
�NU(�7U��fU,�fU�fU(LU�dU@gUPgU`gU0G�U�gU(�#UX�#Uq`YU8gUq hU
```