Initial models for optimisation

R. Kuipers

April 20, 2020

Initial model for installation

$$\text{maximize} \sum_{p \in P} [DIS^p (O_p \cdot v_p - \sum_{r \in R} N_{rp} \cdot C_{rp})] \qquad (1)$$

subject to:

$$1 = \sum_{t \in T} s_{it} = \sum_{t \in T} f_{it} \qquad \forall i \in I \qquad (2)$$

$$1 \leq \sum_{t=t_0}^{t_N} [\sum_{t'=t_0}^{t} f_{it'} \cdot \sum_{t'=t}^{t_N} s_{jt'}] \qquad \forall (i,j) \in IP \qquad (3)$$

$$d_i \geq (f_{it''} + s_{it'} - 1) \cdot \sum_{t=t'}^{t''} \omega_{it} \qquad \forall i \in I, \forall t'' \geq t' + d_i, t', t'' \in T \qquad (4)$$

$$N_{rp} \geq \sum_{i \in I} \sum_{t'=t_0}^{t} \sum_{t''=t}^{t_N} s_{it'} \cdot f_{it''} \cdot \rho_{ir} \qquad \forall r \in R, \forall p \in P, \forall t \in T_p \qquad (5)$$

$$O_p = \sum_{t=t_0}^{\tau_p} \sum_{i \in F} f_{it} \qquad \forall p \in P \qquad (6)$$

Installation Model Explanation

(1) Objective function, sums up profits from energy made, subtracts money used on resources (vessels), and multiplies it all with a discount factor
(2) Forces every task to be starded and finished at some point
(3) For every precedence relation (i, j) it ensures there is a t such that i has a finish time before t, and i a starting time after t
(4) Ensures that between the starting and finish times of each task are enough timesteps with acceptable weather
(5) Counts up the resources needed in a time period summing up over all active tasks (an s before and f after t)
(6) Counts the number of turbines which finished installing by the end of a period

Notation overview

Sets:

- P: All time periods (large scale)
- T: All time intervals $[t_0, \ldots, t_N]$
- $T_p \in T$: All time intervals (small scale) in period p
- R: All resources
- I: All tasks
- $F \subset I$: All final tasks that complete a turbine
- IP: All precedency pairs (i, j)

Decision variables:

- O_p: Number of online turbines after period p
- N_{rp}: Number of resources r used in period p
- s_{it}: Binary variable, 1 if task i starts at time t
- f_{it}: Binary variable, 1 if task i ends at time t

Parameters:

- DIS: The discount factor per period
- v_p: The value of energy a single turbine produces in period p
- C_{rp}: The cost of chartering resource r in period p
- d_i: The duration of task i
- ω_{it}: Binary parameter representing weather, 1 if task i can be completed at time t, 0 otherwise
- ρ_{ir}: The amount of resource r used by task i
- τ_p: The final time interval (from T) in period p

Initial model for maintenance

$$\text{maximize} \sum_{p \in P} [DIS^p (\sum_{t \in T_p} (O_t \cdot v_t) - \sum_{r \in R} (N_{rp} \cdot C_{rp}))] \qquad (7)$$

subject to (1):

$$1 = \sum_{t \in T} s_{act} = \sum_{t \in T} f_{act} \qquad \forall a \in A, \forall c \in C^M \qquad (8)$$

$$1 \geq \sum_{t \in T} s_{act} \qquad \forall a \in A, \forall c \in C^O \qquad (9)$$

$$\sum_{t \in T} s_{act} = \sum_{t \in T} f_{act} \qquad \forall a \in A, \forall c \in C^O \qquad (10)$$

Initial model for maintenance

$$\text{maximize} \sum_{p \in P} [DIS^p (\sum_{t \in T_p} (O_t \cdot v_t) - \sum_{r \in R} (N_{rp} \cdot C_{rp}))] \tag{7}$$

subject to (2):

$$d_c \geq (f_{act''} + s_{act'} - 1) \cdot \sum_{t=t'}^{t''} \omega_{ct} \qquad \forall a \in A, \forall c \in C, \forall t'' \geq t' + d_a, t', t'' \in T \tag{11}$$

$$N_{rp} \geq \sum_{a \in A} \sum_{c \in C} \sum_{t'=t_0}^{t} \sum_{t''=t}^{t_N} s_{act'} \cdot f_{act''} \cdot \rho_{cr} \qquad \forall r \in R, \forall p \in P, \forall t \in T_p \tag{12}$$

$$b_{at} > \sum_{c \in C} \sum_{t'=t-\lambda_a}^{t} -f_{act'} \qquad \forall a \in A, \forall t \in T \tag{13}$$

$$O_t = |A| - \sum_{a \in A} b_{at} \qquad \forall t \in T \tag{14}$$

Maintenance Model Explanation

(7) Objective function, sums up profits from energy made, subtracts money used on resources (vessels), and multiplies it all with a discount factor
(8) Forces every mandatory maintenance cycle to be done at some point
(9) Ensures each optional maintenance cycle to be started at most once
(10) Ensures that every maintenance cycle for a particular asset that is started is also finished
(11) Ensures that between the starting and finish times of each cycle are enough timesteps with acceptable weather
(12) Counts up the resources needed in a time period summing up over all active tasks (an s before and f after t)
(13) If no maintenance tasks have finished in the past λ_a timesteps this asset is broken
(14) The number of active (online) turbines is equal to everything that isn't broken

Notation overview

Sets:

- P: All time periods (large scale)
- T: All time intervals (small scale) $[t_0, \ldots, t_N]$
- $T_p \in T$: All time intervals (small scale) in period p
- R: All resources
- A: All assets
- $C = C^M \cup C^O$: All (mandatory and optional) maintenance cycles

Decision variables:

- O_t: Number of active turbines at timestep t
- N_{rp}: Number of resources r used in period p
- s_{act}: Binary variable, 1 if maintenance cycle c for asset a starts at time t
- f_{act}: Binary variable, 1 if maintenance cycle c for asset a finishes at time t
- b_{at}: Binary variable, 1 if asset a is broken at timestep t

Parameters:

- DIS: The discount factor per time period
- v_t: The value of energy a single turbine produces at timestep t
- C_{rp}: The cost of chartering resource r in period p
- d_c: The duration per task during maintenance cycle c
- λ_a: The number of timesteps after the last maintenance before asset a fails
- ω_{ct}: Binary parameter representing weather, 1 if maintenance cycle c can be completed at time t, 0 otherwise
- ρ_{cr}: The amount of resource r used per task for maintenance cycle c

Initial mixed model

$$\text{maximize} \sum_{p \in P} [DIS^p(\sum_{t \in T_p} (O_t \cdot v_t) - \sum_{r \in R} (N_{rp} \cdot C_{rp}))] \tag{15}$$

subject to:

$$1 = \sum_{t \in T} s^I_{ait} = \sum_{t \in T} f^I_{ait} \qquad \forall i \in I, \forall a \in A \tag{16}$$

$$1 \leq \sum_{t=t_0}^{t_N} [\sum_{t'=t_0}^{t} f^I_{ait'} \cdot \sum_{t'=t}^{t_N} s^I_{ajt'}] \qquad \forall (i,j) \in IP, \forall a \in A \tag{17}$$

$$1 = \sum_{t \in T} s^M_{act} = \sum_{t \in T} f^M_{act} \qquad \forall a \in A, \forall c \in \{1, \ldots, c_M\} \tag{18}$$

$$1 \geq \sum_{t \in T} s^M_{act} \qquad \forall a \in A, \forall c \in \{c_M + 1, \ldots, c_N\} \tag{19}$$

$$\sum_{t \in T} s^M_{act} = \sum_{t \in T} f^M_{act} \qquad \forall a \in A, \forall c \in \{c_M + 1, \ldots, c_N\} \tag{20}$$

$$0 = \sum_{t=t_0}^{t'} s^M_{act} \cdot \sum_{t=t'}^{t_N} f^I_{ait} \qquad \begin{array}{r} \forall a \in A, \forall t' \in T, \\ \forall i \in I, \forall c \in C \end{array} \tag{21}$$

Initial mixed model

$$\text{maximize} \sum_{p \in P} [DIS^p (\sum_{t \in T_p} (O_t \cdot v_t) - \sum_{r \in R} (N_{rp} \cdot C_{rp}))] \tag{15}$$

subject to (2):

$$d_i^I \geq (f_{ait''}^I + s_{ait'}^I - 1) \cdot \sum_{t=t'}^{t''} \omega_{it}^I \qquad \forall i \in I, \forall a \in A, \forall t'' \geq t' + d_i, t', t'' \in T \tag{22}$$

$$d_c^M \geq (f_{act''}^M + s_{act'}^M - 1) \cdot \sum_{t=t'}^{t''} \omega_{ct}^M \qquad \forall a \in A, \forall c \in C, \forall t'' \geq t' + d_a, t', t'' \in T \tag{23}$$

$$N_{rp} \geq \sum_{a \in A} \sum_{t'=t_0}^{t} \sum_{t''=t}^{t_N} [\sum_{i \in I} (s_{ait'}^I \cdot f_{ait''}^I \cdot \rho_{ir}^I) + \sum_{c \in C} (s_{act'}^M \cdot f_{act''}^M \cdot \rho_{cr}^M)] \qquad \forall r \in R, \forall p \in P, \forall t \in T_p \tag{24}$$

$$o_{at} \leq \sum_{t'=t_0}^{t} f_{ai_N t'}^I \cdot \sum_{c \in C} \sum_{t'=t-\lambda_a}^{t} (f_{act'}^M + f_{ai_N t'}^I) \qquad \forall a \in A, \forall t \in T \tag{25}$$

$$O_t = \sum_{a \in A} o_{at} \qquad \forall t \in T \tag{26}$$

Mixed Model Explanation

(15) Objective function, sums up profits from energy made, subtracts money used on resources (vessels), and multiplies it all with a discount factor
(16) (Installation) Forces every task to be starded and finished at some point
(17) (Installation) For every precedence relation (i, j) it ensures there is a t such that i has a finish time before t, and i a starting time after t
(18) (Maintenance) Forces every mandatory maintenance cycle to be starded and finished at some point
(19) (Maintenance) Ensures each optional maintenance cycle to be started at most once
(20) (Maintenance) Ensures that every maintenance cycle for a particular asset that is started is also finished
(21) (Mixed) Ensures an asset is fully installed before maintenance starts
(22) (Installation) Ensures that between the starting and finish times of each task are enough timesteps with acceptable weather
(23) (Maintenance) Ensures that between the starting and finish times of each cycle are enough timesteps with acceptable weather
(24) (Mixed) Counts up the resources needed in a time period summing up over all active tasks (an s before and f after t)
(25) (Mixed) Sets an asset to be online if it installed and had work done on it recently
(26) (Mixed) Counts how many assets are online

Notation overview

Sets:

- P: All time periods (large scale)
- T: All time intervals (small scale) $[t_0, \ldots, t_N]$
- $T_p \in T$: All time intervals (small scale) in period p
- R: All resources
- I: All installation tasks per asset $[1, \ldots, i_N]$
- A: All assets
- C: All (c_M mandatory and $(c_N - c_M)$ optional) maintenance cycles $[1, \ldots, c_M, \ldots, c_N]$

Decision variables:

- O_t: Number of online turbines at timestep t
- o_{at}: Binary variable, 1 if asset a is online at timestep t
- N_{rp}: Number of resources r used in period p
- s^I_{ait}: Binary variable, 1 if installation task i for asset a starts at time t
- f^I_{ait}: Binary variable, 1 if installation task i for asset a finishes at time t
- s^M_{act}: Binary variable, 1 if maintenance cycle c for asset a starts at time t
- f^M_{act}: Binary variable, 1 if maintenance cycle c for asset a finishes at time t

Parameters:

- DIS: The discount factor per time period
- v_t: The value of energy a single turbine produces at timestep t
- C_{rp}: The cost of chartering resource r in period p
- d^I_i: The duration of installation task i
- d^M_c: The duration per task during maintenance cycle c
- λ_a: The number of timesteps after the last maintenance before asset a fails
- ω^I_{it}: Binary parameter representing weather, 1 if task i can be completed at time t, 0 otherwise
- ω^M_{ct}: Binary parameter representing weather, 1 if maintenance cycle c can be completed at time t, 0 otherwise
- ρ^I_{ir}: The amount of resource r used for intallation task i
- ρ^M_{cr}: The amount of resource r used per task for maintenance cycle c