

Mastering R Markdown

Michael Harper

2018-05-01

Contents

1	About the book	5
1.1	Recommended Reading	5
2	Introduction	7
2.1	Overview of Book	7
3	Basics	9
3.1	Quick Tips	9
4	Managing Big Projects	11
4.1	Sourcing Files	11
4.2	Caching	11
4.3	Notifications	11
5	LaTeX	13
5.1	Inserting Commands	13
5.2	LaTeX preamble	13
5.3	Multi-figure plots	13
5.4	Cross-output	13
5.5	LaTeX subfigures	13
5.6	Changing citation Engine	14
5.7	Altering Citation Style	14
6	HTML Output	17
6.1	Tabbed headings	17
7	Multi-format projects	19
7.1	Output-specific functions	19
7.2	Designing output	19
8	Knitr Hooks	21
9	Tables	23
10	References	25

Chapter 1

About the book

This book is in a very early stage of development. If you have any suggestions on what should be included within this book, please get in touch via GitHub: <https://github.com/mikey-harper/mastering-rmarkdown>

- This book aims to bring together lots of useful tips for R Markdown.
- One of the common criticisms of markdown as a language is that it naturally limits what you can write. Users often therefore feel limited in what they can achieve with advanced customisation. However, we can easily edit.

1.1 Recommended Reading

There are already several fantastic books out there which you may have already read:

- Dynamic documents and knitr
- R Markdown: The Definitive guide
- Authoring books with bookdown
- Blogdown

Chapter 2

Introduction

- Motivation for book
- What readers can learn
- Feedback and errata
- Suggested examples

2.1 Overview of Book

- Explain the structure of the book

Chapter 3

Basics

- What should be known before reading this book
- Recommended reading
- `bookdown` is used as the default engine as it provides improvements

3.1 Quick Tips

- Short index of some basic ideas on how to improve R Markdown documents
- Include current date in R Markdown <https://stackoverflow.com/questions/23449319/yaml-current-date-in-rmarkdown/23529410#23529410>

Chapter 4

Managing Big Projects

- Practical tips on how a big project should be managed
- `source` is particularly useful for loading external scripts so that the R Markdown project isn't too bloated with code.

Ideas: - Use `(ref:tag)` to store page formatting options which might need to be reused. For example a page break

4.1 Sourcing Files

A benefit of using R Markdown is that it is easy

```
source("yourScript.R")
```

4.2 Caching

- Caching
- Ways it can be tailored to suit analysis. This cache invalidation is a great example: <https://stackoverflow.com/questions/18376008/invalidate-a-chunks-cache-when-uncached-chunk-changes>

4.3 Notifications

- Can link R Markdown with notifications if have long analysis

Chapter 5

LaTeX

For many authors, the main of long reports or books, the primary output will be LaTeX. In this chapter, we discuss approaches which can be used to customise the output of PDF reports.

Users should approach with a note of caution. One of the major benefits of R Markdown is

5.1 Inserting Commands

5.2 LaTeX preamble

5.3 Multi-figure plots

If we need to print multiple output graphs or figures, there are several ways this can be achieved.

5.4 Cross-output

As explained in <https://bookdown.org/yihui/rmarkdown/r-code.html#figures-of-?>, we can place multiple figures side-by-side using the `fig.hold='hold'` along with the `out.width` option. As an example below, we have set the `out.width="50%"`:

```
plot(1:10)
plot(rnorm(10), pch=19)
```

The main benefits of this approach is that it is easily achieved, and also works for both PDF and HTML outputs.

5.5 LaTeX subfigures

When writing a document you may want to include some slightly more complicated figures with multiple images. Subfigures are a useful LaTeX feature which allows us to achieve this by plotting multiple figures within a single plot and providing each with their own subcaption.

Subfigures require the LaTeX package `subfig`. The line `\usepackage{subfig}` must therefore be included within the YAML, or if you are using an external tex template you can add this to that file. For example:




Figure 5.1: Side-by-side figures

As listed within the knitr chunk options, subfigures require a few additional settings to be set in the chunk header:

- `fig.subcap` is a list of the captions for subfigures
- `fig.ncol`: the number of columns of subfigures
- `out.width`: the output width of the figures. You will normally set this 100% divided by the number of sub columns.

An example is demonstrated below:

```
```yaml
output: pdf_document
header-includes:
 - \usepackage{subfig}
...

```{r fig-sub, fig.cap='two plots', fig.subcap=c('one plot', 'the other one'), out.width='.49\\linewidth}
plot(1:10)
plot(rnorm(10), pch=19)
```
```

The output is shown in Figure 5.2.

```
knitr::include_graphics("images/subfigure.png", dpi = NA)
```

### 5.5.1 Using with list

## 5.6 Changing citation Engine

## 5.7 Altering Citation Style

- Using short author citations: <https://stackoverflow.com/questions/48303890/using-short-author-citations-in-bookdown>  
utm\_medium=organic&utm\_source=google\_rich\_qa&utm\_campaign=google\_rich\_qa




Figure 1: two plots

Figure 5.2: An example subcaption





## Chapter 6

# HTML Output

- Take some of the details from here: [https://rmarkdown.rstudio.com/html\\_document\\_format.html](https://rmarkdown.rstudio.com/html_document_format.html)

### 6.1 Tabbed headings

[https://stackoverflow.com/questions/38062706/rmarkdown-tabbed-and-untabbed-headings?utm\\_medium=organic&utm\\_source=google\\_rich\\_qa&utm\\_campaign=google\\_rich\\_qa](https://stackoverflow.com/questions/38062706/rmarkdown-tabbed-and-untabbed-headings?utm_medium=organic&utm_source=google_rich_qa&utm_campaign=google_rich_qa)



## Chapter 7

# Multi-format projects

- One of the main benefits of R Markdown is that it is easy to create documents in a single source file and generate PDF, HTML, ebook and Word documents. This book example is available in all three formats. Project should therefore ideally be designed to be flexible for the multiple outputs. However, users will often find themselves wanting to fine-tune the output, and doing so will often require -Designing custom behavior which can respond to change in outputs using `is_latex_output` etc. For example, you may want to have interactive tables using `DT::datatable` in the HTML output but print static versions in the PDF.

### 7.1 Output-specific functions

- **bookdown** will take screenshots of HTML widgets in static reports

```
library(ggplot2)
library(plotly)
p <- ggplot(data = diamonds, aes(x = cut, fill = clarity)) +
 geom_bar(position = "dodge")
ggplotly(p)
```

### 7.2 Designing output

If we wish to design our own format-specific function we can use the functions `knitr::is_latex_output()` and `knitr::is_html_output()`. These function will return a TRUE/FALSE action

```
knitr::is_html_output()
```



## Chapter 8

# Knitr Hooks

- Knitr hooks: these are explained within previous R Markdown book
- Include practical examples could be very useful for readers to see the power of it.
- Use some of these: <https://gist.github.com/yihui/2629886>



## Chapter 9

# Tables

- Using `kableExtra` to style tables





## Chapter 10

## References



# Bibliography