

Technical Specification:

| FW-max pro | | 100 |
|------------------------------|---|---|
| Mechanical Specifications | Dimension(L*W*H) | 960*550*394mm |
| | Weight | 125kg |
| | Drive form | 4 wheels swerve steering and 4 motors drive |
| | Structure material | Aluminum alloy |
| | Ground clearance | 120mm |
| | Wheel base | 600mm |
| | Wheel track | 450mm |
| | Tire diameter | 10 inches/250mm |
| Basic Information | Motor power | 600W*4 Servo motor |
| | Battery | 48V/40AH lithium battery |
| | Charging time | 3-4h |
| | Charging mode | 48V/10A manual charging by charger |
| | Battery output power for external devices | 48V/10A-24V/15A-12V/15A |
| | Braking | Motor brake |
| | Parking | electromagnetic power-off parking |
| Security Setting | Emergency stop | √ |
| | Instruction verification | \checkmark |
| | Heartbeat protection | \checkmark |
| | Current protection | \checkmark |
| | Temperature protection | \checkmark |
| VCU Information | CPU basic frequency | 168MHz |
| | Interface | CAN interface |
| | Communication module | CAN2.0B |
| | Kinematic analysis | \checkmark |
| | Remote control distance | 100M |
| Performance | Payload | 250kg |
| | Max speed | 0-7.2km/h |
| | Mileage | 40km |
| | Turning radius | 0m |
| | Wading depth | 50mm |
| | Climbing capacity | 10°(full load) |
| | Span width | 120mm(full load) |
| | Obstacle surmounting height | 50mm(full load) |
| | IP Rating | IP44 |
| | Working temperature | -20℃~50℃ |