Vim实验

请完成以下操作，并在实验报告中附带各步骤的操作描述和对应截图

1. 在当前用户的家目录下建立一个名为 `vimlab` 的目录，并进入 `vimlab` 目录中
2. 在vimlab目录下创建一个文件 `test.txt`
3. 请严格地将下面所提供的的文本内容一行行地输入到文件 `test.txt` 中去。在输入完成后再将字母 a,b,c...,z 输入到文件中去,每个字母占一行。

```
Vim is a text editor for Unix that comes with Linux, BSD, and macOS. It is known
to be fast and powerful, partly because it is a small program that can run in a
terminal (although it has a graphical interface). It is mainly because it can be
managed entirely without menus or a mouse with a keyboard.
```

4. 保存文件并退出
5. 将 `vimlab` 目录下的 `test.txt` 文件拷贝到当前用户家目录下，并将新文件命名为 `copy_of_test.txt` 。
6. 用 vim 打开家目录下的 `copy_of_test.txt` 文件，并设定行号
7. 将光标放在第一行后，完成以下操作：
   - 将光标移动到文件的第四行
   - 将光标移动到行的末尾
   - 再移回行的开始
8. 将光标移动到文件的开始处，查找单词 `mainly` ，看看他在第几行。
9. 删除输入的单行字母 d,g, 但仍然保留空行。
10. 将刚才输入的单行字母 a 替换成 A
11. 一次一行地将第一段的前两行复制到文件末尾。如果一次复制两行，该如何操作?
12. 将刚才复制的两行删除，要求一次删除两行
13. 撤销上一步的删除操作
14. 将光标移动到带有“(although it has a graphical interface)”的那一行，在该行下面另起一行，输入“This is a new line.”
15. 不保存以上更改退出文件