

Contents

- [Step 1: Import CSV Data](#)
- [Step 2: R Bridge Implementation](#)
- [Step 3a: MDFT Formulation to Calculate Preference Dynamics in Parallel](#)
- [Step 3b: MDFT Formulation with State Continuity](#)
- [Helper Functions](#)

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Main Simulation Script for BoundingOverwatch Project with R Integration
% Randomly 10 trials is used to validate predictions
% DFT Parameters:
% phi1 - sensitivity to attribute differences (typically 0.5-2)
% phi2 - memory/feedback strength (0-1)
% tau - decision time steps (integer > 0)
% error_sd - noise standard deviation (sigma_epsilon)
% beta - attribute weights from R estimation
% w - attention weights (default [0.5;0.5])
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

clc;
clear all;
```

Step 1: Import CSV Data

(reference apolloMain_5 amd apolloMain_6 as example for data manipulation) biasData = readtable('user_choices.csv'); % Replace with the path to your data file disp('User bias data imported successfully.');

taskChoice_Data = readtable('user_choices.csv'); % Replace with the path to your data file disp('User task choice data imported successfully.');

```
robotChoice_Data = readtable('G:\My Drive\myResearch\Research Experimentation\Apollo\apollo\data\Bounding_Overwatch_Data\HumanData_Bounding_Overwatch - 20Split.csv')
% Convert all column headers to lowercase
robotChoice_Data.Properties.VariableNames = lower(robotChoice_Data.Properties.VariableNames);
disp('User robot choice data imported successfully.');
```

% Randomly select 10 rows (or all rows if fewer than 10)

```
numRows = height(robotChoice_Data);
randomIndices = randperm(numRows, min(10, numRows));
robotChoice_Data = robotChoice_Data(randomIndices, :);
```

% Extract robot state attributes dynamically

```
robot_states = struct();
attributeSuffixes = {'traversability', 'visibility'}; % No leading underscores
for i = 1:3
    attr = attributeSuffixes
        csvColName = sprintf('robot%d%s', i, attr{1}); % Matches CSV column names
        structFieldName = attr{1}; % Valid field name
        if ismember(csvColName, robotChoice_Data.Properties.VariableNames)
            robot_states.(['robot' num2str(i)]).(structFieldName) = robotChoice_Data(csvColName);
        else
            warning('Missing attribute column: %s', csvColName);
            robot_states.(['robot' num2str(i)]).(structFieldName) = NaN(height(robotChoice_Data), 1);
        end
    end
end
```

% Extract choice data and other metadata

```
choices = robotChoice_Data.choice;
participant_ids = robotChoice_Data.id;
stake_types = robotChoice_Data.stakes;
time_spent = robotChoice_Data.timeelapsed;
```

User robot choice data imported successfully.

Step 2: R Bridge Implementation

```
disp('Initializing R bridge...');
```

% Configure paths

```
rscript_path = 'C:\Program Files\R\R-4.4.2\bin\x64\Rscript.exe';
r_script = 'G:\My Drive\myResearch\Research Experimentation\Apollo\apollo\example\DFT_Bounding_Overwatch.R';
csvFile = 'G:\My Drive\myResearch\Research Experimentation\Apollo\apollo\data\Bounding_Overwatch_Data\HumanData_Bounding_Overwatch - 80Split.csv';
outputDir = 'G:\My Drive\myResearch\Research Experimentation\Apollo\apollo\Output_BoundingOverwatch';
```

% Verify installations

```
if ~isfile(rscript_path)
    error('Rscript.exe not found at: %s', rscript_path);
elseif ~isfile(r_script)
    error('R script not found at: %s', r_script);
elseif ~isfile(csvFile)
    error('Input CSV not found at: %s', csvFile);
elseif ~isfolder(outputDir)
    warning('Output folder does not exist, creating: %s', outputDir);
```

```

mkdir(outputDir);
end

% Execute R with JSON output
try
    % Use proper argument formatting
    cmd = sprintf(['"%s" "%s" ', ...
        '-i "%s" -o "%s"', ...
        rscript_path, r_script, csvFile, outputDir]);

    [status,result] = system(cmd);

    if status == 0
        % Handle output path (whether directory or file)
        if isfolder(outputDir)
            jsonFile = fullfile(outputDir, 'DFT_output.json');
        else
            jsonFile = outputDir;
        end

        % Parse JSON output
        if exist(jsonFile, 'file')
            jsonText = fileread(jsonFile);
            params = jsondecode(jsonText);

            % Extract parameters with validation
            %Boundedphi1, phi2 parameters
            phi1 = min(max(0, validateParam(params, 'phi1', 0.5)),5); % Ensure non-negative
            phi2 = min(max(0, validateParam(params, 'phi2', 0.8)), 0.99); % Constrain 0-1
            %tau = min(1 + exp(validateParam(params, 'timesteps', 0.5)),100); %Constrain to 100

            %Raw phi1, phi2 parameters
            % = validateParam(params, 'phi1', 0.5);
            %phi2 = validateParam(params, 'phi2', 0.8);
            tau = 1 + exp(validateParam(params, 'timesteps', 0.5));
            error_sd = min(max(0.1, validateParam(params, 'error_sd', 0.1)), 1); % still clip here

            % Extract attribute weights
            beta_weights = [
                params.b_attr1;
                params.b_attr2;
                params.b_attr3;
                params.b_attr4
            ];

            % Get initial preferences from ASCs
            initial_P = [
                validateParam(params, 'asc_1', 0);
                validateParam(params, 'asc_2', 0);
                validateParam(params, 'asc_3', 0);
            ];

            disp('Estimated Parameters:');
            disp(['phi1: ', num2str(phi1)]);
            disp(['phi2: ', num2str(phi2)]);
            disp(['tau: ', num2str(tau)]);
            disp(['error_sd: ', num2str(error_sd)]);
            disp('Initial Preferences (from ASCs):');
            disp(initial_P);
        else
            error('R output file not found');
        end
    else
        error('R execution failed: %s', result);
    end
catch ME
    disp('Error during R execution:');
    disp(getReport(ME, 'extended'));
    [phi1, phi2, tau, error_sd] = getFallbackParams();
    beta_weights = [0.3; 0.2; 0.4; 0.5]; % Default weights
    initial_P = zeros(3,1); % Neutral initial preferences
end

```

Initializing R bridge...

Step 3a: MDFT Formulation to Calculate Preference Dynamics in Parallel

```

%%{
% (MDFT calculations based on estimated parameters)
% Create M matrix from current trial's attributes
% C11-C14 are consequence attributes for Robot 1
% C21-C24 are consequence attributes for Robot 2
% C31-C34 are consequence attributes for Robot 3
for current_trial = 1:height(robotChoice_Data)

```

```

num_attributes = 4;

M = [
    robotChoice_Data.c11(current_trial), robotChoice_Data.c12(current_trial), robotChoice_Data.c13(current_trial), robotChoice_Data.c14(current_trial);
    robotChoice_Data.c21(current_trial), robotChoice_Data.c22(current_trial), robotChoice_Data.c23(current_trial), robotChoice_Data.c24(current_trial);
    robotChoice_Data.c31(current_trial), robotChoice_Data.c32(current_trial), robotChoice_Data.c33(current_trial), robotChoice_Data.c34(current_trial)
];

% Normalize M values by dividing by 2 and clamping to [0.01, 1]
%{
M = M / 2;
M = max(0.01, min(1, M));
%}

% --- Global Max Normalization ---
%{
global_max = max(robotChoice_Data(:, {'c11','c12','c13','c14','c21','c22','c23','c24','c31','c32','c33','c34'}), [], 'all', 'omitnan');
if ~isfinite(global_max) || global_max <= 0
    global_max = 1; % fallback in case of zero or NaN
end

M = M / global_max;          % Normalize by global max
M = max(0.01, min(1, M));    % Clamp to [0.01, 1]
%}

% --- Row-wise Min-Max Normalization ---
%{
for i = 1:size(M, 1)
    row = M(i, :);
    min_val = min(row);
    max_val = max(row);

    if max_val == min_val
        M(i, :) = pmax(0.01, pmin(1, row)); % constant row: clamp only
    else
        norm_row = (row - min_val) / (max_val - min_val);
        M(i, :) = max(0.01, min(1, norm_row)); % clamp to [0.01, 1]
    end
end
%}

attributes = {'C1 - Easy Nav, Low Exposure', 'C2 - Hard Nav, Low Exposure', 'C3 - Easy Nav, High Exposure', 'C4 - Hard Nav, High Exposure'};
beta = beta_weights ./ sum(abs(beta_weights));
beta = beta';

[E_P, V_P, choice_probs, P_tau] = calculateDFTdynamics(...
    phi1, phi2, tau, error_sd, beta, M, initial_P);

% Display results for the frame
disp('=== Trial Analysis ===');
disp(['Trial: ', num2str(current_trial)]);
disp(['Participant: ', num2str(participant_ids(current_trial))]);
disp(['Actual Choice: Robot ', num2str(choices(current_trial))]);

disp('M matrix (alternatives x attributes):');
disp(array2table(M, ...
    'RowNames', {'Robot1','Robot2','Robot3'}, ...
    'VariableNames', attributes));

disp('DFT Results:');
disp(['E_P: ', num2str(E_P', '%.2f ')]);
disp(['Choice probabilities: ', num2str(choice_probs', '%.3f ')]);
[~, predicted_choice] = max(choice_probs);
disp(['Predicted choice: Robot ', num2str(predicted_choice)]);
disp(['Actual choice: Robot ', num2str(choices(current_trial))]);
disp(' ');

if predicted_choice == choices(current_trial)
    disp('✓ Prediction matches actual choice');
else
    disp('X Prediction differs from actual choice');
end

% Plot evolution
figure;
%plot(0:tau, P_tau);
% Replace the plotting section with:
tau_rounded = round(tau); % Ensure integer steps
if size(P_tau,2) == tau_rounded+1 % Validate dimensions
    plot(0:tau_rounded, P_tau);
else
    warning('Dimension mismatch: P_tau has %d cols, expected %d',...
        size(P_tau,2), tau_rounded+1);
    plot(P_tau'); % Fallback plot
end

```

```

xlabel('Preference Step (\tau)');
ylabel('Preference Strength');
legend({'Robot1','Robot2','Robot3'});
title(sprintf('Preference Evolution (Trial %d)', current_trial));
grid on;
end
%%}

```

=== Trial Analysis ===

Trial: 1

Participant: 125802

Actual Choice: Robot 1

M matrix (alternatives × attributes):

	C1 - Easy Nav, Low Exposure	C2 - Hard Nav, Low Exposure	C3 - Easy Nav, High Exposure	C4 - Hard Nav, High Exposure
Robot1	0.65007	0.40784	0.30724	0.065007
Robot2	0.94956	0.55409	0.49043	0.094956
Robot3	0.84533	0.47243	0.45743	0.084533

DFT Results:

E_P: 0.04 -0.01 -0.03

Choice probabilities: 0.485 0.280 0.235

Predicted choice: Robot 1

Actual choice: Robot 1

✓ Prediction matches actual choice

=== Trial Analysis ===

Trial: 2

Participant: 125802

Actual Choice: Robot 3

M matrix (alternatives × attributes):

	C1 - Easy Nav, Low Exposure	C2 - Hard Nav, Low Exposure	C3 - Easy Nav, High Exposure	C4 - Hard Nav, High Exposure
Robot1	0.90176	0.509	0.48294	0.090176
Robot2	0.84846	0.48499	0.44832	0.084846
Robot3	0.94097	0.55305	0.48202	0.094097

DFT Results:

E_P: -0.00 0.01 -0.01

Choice probabilities: 0.325 0.363 0.312

Predicted choice: Robot 2

Actual choice: Robot 3

X Prediction differs from actual choice

=== Trial Analysis ===

Trial: 3

Participant: 141831

Actual Choice: Robot 3

M matrix (alternatives × attributes):

	C1 - Easy Nav, Low Exposure	C2 - Hard Nav, Low Exposure	C3 - Easy Nav, High Exposure	C4 - Hard Nav, High Exposure
Robot1	0.73819	0.4104	0.4016	0.073819
Robot2	0.73482	0.40703	0.40127	0.073482
Robot3	0.71114	0.41408	0.36817	0.071114

DFT Results:

E_P: 0.00 -0.00 0.00

Choice probabilities: 0.332 0.329 0.340

Predicted choice: Robot 3

Actual choice: Robot 3

✓ Prediction matches actual choice

=== Trial Analysis ===

Trial: 4

Participant: 125802

Actual Choice: Robot 2

M matrix (alternatives × attributes):

	C1 - Easy Nav, Low Exposure	C2 - Hard Nav, Low Exposure	C3 - Easy Nav, High Exposure	C4 - Hard Nav, High Exposure
Robot1	0.7801	0.50985	0.34826	0.07801
Robot2	0.77779	0.4865	0.36907	0.077779
Robot3	0.84381	0.51836	0.40983	0.084381

DFT Results:

E_P: 0.02 0.00 -0.02

Choice probabilities: 0.399 0.341 0.261

Predicted choice: Robot 1

Actual choice: Robot 2

X Prediction differs from actual choice

=== Trial Analysis ===

Trial: 5

Participant: 125802

Actual Choice: Robot 1

M matrix (alternatives × attributes):

	C1 - Easy Nav, Low Exposure	C2 - Hard Nav, Low Exposure	C3 - Easy Nav, High Exposure	C4 - Hard Nav, High Exposure
Robot1	0.75261	0.45291	0.37497	0.075261
Robot2	0.79099	0.48306	0.38703	0.079099
Robot3	0.80528	0.49482	0.39099	0.080528

DFT Results:

E_P: 0.01 0.01 -0.01

Choice probabilities: 0.346 0.349 0.305

Predicted choice: Robot 2

Actual choice: Robot 1

X Prediction differs from actual choice

=== Trial Analysis ===

Trial: 6

Participant: 125802

Actual Choice: Robot 2

M matrix (alternatives × attributes):

	C1 - Easy Nav, Low Exposure	C2 - Hard Nav, Low Exposure	C3 - Easy Nav, High Exposure	C4 - Hard Nav, High Exposure
Robot1	0.99703	0.55568	0.54105	0.099703
Robot2	0.83247	0.45565	0.46007	0.083247
Robot3	0.88905	0.48584	0.49212	0.088905

DFT Results:

E_P: -0.00 0.01 -0.01

Choice probabilities: 0.322 0.377 0.300

Predicted choice: Robot 2

Actual choice: Robot 2

✓ Prediction matches actual choice

=== Trial Analysis ===

Trial: 7

Participant: 141831

Actual Choice: Robot 3

M matrix (alternatives × attributes):

	C1 - Easy Nav, Low Exposure	C2 - Hard Nav, Low Exposure	C3 - Easy Nav, High Exposure	C4 - Hard Nav, High Exposure
Robot1	0.94136	0.56188	0.47362	0.094136
Robot2	0.90012	0.51862	0.47151	0.090012
Robot3	0.95531	0.57382	0.47703	0.095531

DFT Results:

E_P: 0.01 -0.00 -0.00

Choice probabilities: 0.359 0.327 0.314

Predicted choice: Robot 1

Actual choice: Robot 3

X Prediction differs from actual choice

=== Trial Analysis ===

Trial: 8

Participant: 125802

Actual Choice: Robot 1

M matrix (alternatives × attributes):

	C1 - Easy Nav, Low Exposure	C2 - Hard Nav, Low Exposure	C3 - Easy Nav, High Exposure	C4 - Hard Nav, High Exposure
Robot1	0.67711	0.38864	0.35617	0.067711
Robot2	0.68215	0.40175	0.34861	0.068215
Robot3	0.62086	0.34369	0.33926	0.062086

DFT Results:

E_P: 0.00 0.01 -0.01

Choice probabilities: 0.344 0.366 0.290

Predicted choice: Robot 2

Actual choice: Robot 1

X Prediction differs from actual choice

=== Trial Analysis ===

Trial: 9

Participant: 125802

Actual Choice: Robot 3

M matrix (alternatives × attributes):

	C1 - Easy Nav, Low Exposure	C2 - Hard Nav, Low Exposure	C3 - Easy Nav, High Exposure	C4 - Hard Nav, High Exposure
Robot1	0.80623	0.48071	0.40615	0.080623
Robot2	0.84985	0.45584	0.47899	0.084985
Robot3	0.91242	0.50248	0.50119	0.091242

DFT Results:

E_P: 0.03 -0.01 -0.02
Choice probabilities: 0.448 0.296 0.256
Predicted choice: Robot 1
Actual choice: Robot 3

X Prediction differs from actual choice

=== Trial Analysis ===

Trial: 10

Participant: 125802

Actual Choice: Robot 3



M matrix (alternatives x attributes):




	C1 - Easy Nav, Low Exposure	C2 - Hard Nav, Low Exposure	C3 - Easy Nav, High Exposure	C4 - Hard Nav, High Exposure
Robot1	1	0.58996	0.51004	0.1
Robot2	0.97203	0.58147	0.48777	0.097203
Robot3	0.9323	0.55028	0.47525	0.09323




DFT Results:



E_P: 0.00 0.01 -0.01
Choice probabilities: 0.331 0.361 0.309
Predicted choice: Robot 2
Actual choice: Robot 3

X Prediction differs from actual choice









Step 3b: MDFT Formulation with State Continuity

```
%{
% Initialize preference state tracking
if ~exist('P_final_prev', 'var')
    P_final_prev = initial_P; % Use estimated initial preferences for first trial
end

for current_trial = 1:height(robotChoice_Data)
    % Create M matrix for current trial
    M = [
        robotChoice_Data.c11(current_trial), robotChoice_Data.c12(current_trial), robotChoice_Data.c13(current_trial), robotChoice_Data.c14(current_trial);
        robotChoice_Data.c21(current_trial), robotChoice_Data.c22(current_trial), robotChoice_Data.c23(current_trial), robotChoice_Data.c24(current_trial);
        robotChoice_Data.c31(current_trial), robotChoice_Data.c32(current_trial), robotChoice_Data.c33(current_trial), robotChoice_Data.c34(current_trial)
    ];

    % Normalize beta weights
    beta = beta_weights ./ sum(abs(beta_weights));

    % Calculate DFT dynamics using previous trial's final state
    [E_P, V_P, choice_probs, P_tau] = calculateDFTdynamics(...
        phi1, phi2, tau, error_sd, beta, M, P_final_prev);

    % Store final preference state for next trial
    P_final_prev = P_tau(:, end);

    % Display results
    disp('=== Trial Analysis ===');
    disp(['Trial: ', num2str(current_trial)]);
    disp(['Participant: ', num2str(participant_ids(current_trial))]);
    disp(['Actual Choice: Robot ', num2str(choices(current_trial))]);

    disp('Initial Preferences (from previous trial):');
    disp(array2table(P_tau(:,1), 'VariableNames', {'Robot1','Robot2','Robot3'})); % Fixed this line
end
}
```

```

disp('Final Preferences:');
disp(array2table(P_tau(:,end)', 'VariableNames', {'Robot1','Robot2','Robot3'})); % Fixed this line

% Enhanced plotting with initial/final state markers
figure;
plot(0:tau, P_tau, 'LineWidth', 2);
hold on;
% Mark initial state
scatter(zeros(3,1), P_tau(:,1), 100, 'filled');
% Mark final state
scatter(tau*ones(3,1), P_tau(:,end), 100, 'x', 'LineWidth', 2);
hold off;

xlabel('Preference Step (\tau)');
ylabel('Preference Strength');
legend({'Robot1','Robot2','Robot3','Initial State','Final State'});
title(sprintf('Preference Evolution (Trial %d)', current_trial));
grid on;
end

%% Step 4: Output Results
disp('Saving results to CSV...');
output_table = table(E_P, V_P, P_tau(end,:), ...
    'VariableNames', {'ExpectedPreference', 'VariancePreference', 'FinalPreferences'});
writetable(output_table, 'results.csv');
disp('Results saved successfully!');
%}

```

Helper Functions

```

function param = validateParam(params, name, default)
    if isfield(params, name) && isnumeric(params.(name))
        param = params.(name);
    else
        warning('Using default for %s', name);
        param = default;
    end
end

function [phi1, phi2, tau, error_sd] = getFallbackParams()
    phi1 = 0.5 + 0.1*randn();
    phi2 = 0.8 + 0.1*randn();
    tau = 10 + randi(5);
    error_sd = 0.1 + 0.05*rand();
    warning('Using randomized default parameters');
end

```

```

Estimated Parameters:
phi1: 1.7857
phi2: 0.1
tau: 5.9998
error_sd: 0.1
Initial Preferences (from ASCs):
    0.0147    0.0144         0

```