

A L^AT_EX document class for the Revista Mexicana de Astronomía y Astrofísica*

William J. Henney[†]

2019/11/12

Abstract This document describes the `rmaa` L^AT_EX document class for the journal “Revista Mexicana de Astronomía y Astrofísica”. The macros can be used for

1. Preparing author manuscripts for the journal (including conference proceedings to be published in the “Serie de Conferencias”)
2. Typesetting an entire volume of the journal by inputting the individual article files from a container file. Facilities are included for automatic generation of TOC and Author Index.

Contents

1	The documentation driver file	2
2	The implementation	2
2.1	Option Handling	3
2.2	Other setup stuff	6
2.3	Compatibility with old L ^A T _E X versions	6
2.4	Page layout	7
2.5	Various text styles for different contexts	11
2.6	Page styles	12
2.7	Preamble commands	13
2.7.1	Commands for the title page	13
2.7.2	The full addresses	16
2.7.3	Commands for editors	18
2.8	Notes for Author Proofs and Communication between Editors . . .	21
2.9	Bibliographic Records for ADS	22
2.10	Automatic calculation of the page range	27

*This file has version 4.0 last revised 2019/11/12.

[†]w.henney@irya.unam.mx

2.11	Deal with explicit change in number of columns	29
2.12	The actual formatting of the title	29
2.13	The sectioning commands	32
2.14	Appendices	34
2.15	Floating thingies	35
2.15.1	Footnotes in tables	37
2.16	The bibliography and references	38
2.17	Uniquification of cross-references	38
2.18	HTML Table of Contents	41
2.19	Formatting the poster abstracts	41
2.20	Code for typesetting an entire volume of conference proceedings .	43
2.21	Front sections	46
3	User commands for astronomical articles	54
4	Other files	57
4.1	The driver and make files	57
4.2	Extended citation syntax	60
4.3	Auxilliary files for generating ADS data	61
5	Epilogue	66

1 The documentation driver file

This is the part that generates the documentation that you may or may not be reading, which is done with the help of the Makefile discussed in section 4.1.

```

1 ⟨*driver⟩
2 \documentclass{ltxdoc}
3 \usepackage{hyperref}
4 \usepackage{palatino}
5 \EnableCrossrefs \CodelineIndex \RecordChanges
6 \setlength{\parindent}{0pt}
7 \def\MacroFont{\footnotesize\tt}
8 \begin{document} \DocInput{rmaa.dtx} \PrintIndex \PrintChanges \end{document}
9 ⟨/driver⟩

```

2 The implementation

```

10 ⟨*package⟩
11 \newcommand{\rmaa@version}{3.26}
12 \newcommand{\rmaa@date}{2011/08/15}
13 \newcommand{\rmVersion}{\rmaa@version}
14 \newcommand{\rmDate}{\rmaa@date}
15 \NeedsTeXFormat{LaTeX2e}[1995/06/01]

16 \ProvidesClass{rmaa}[\rmaa@date\space v\rmaa@version\space RMxAA article
17 class]

```

2.1 Option Handling

Declarations that are needed in options

```
18 \newif\if@reviewarticle
19 \@reviewarticlefalse
20 \newif\if@proof
21 \@prooffalse
22 \newif\if@journal
23 \@journaltrue
24 \newif\if@printdates
25 \@printdatesfalse
26 \newif\if@proceedings
27 \@proceedingsfalse
28 \newif\if@manuscript
29 \@manuscripttrue
30 \newif\if@bigfont
31 \@bigfonttrue
32 \newif\if@guide
33 \@guidefalse
34 \newif\if@preprint
35 \@preprintfalse
36 \newif\if@rmtwocol
37 \@rmtwocoltrue
38 \newif\if@biblist
39 \@biblistfalse
40 \newif\if@book
41 \@bookfalse
42 \newif\if@natbib
43 \@natbibtrue
44 \newif\if@rmcite
45 \@rmcitefalse
46 \newif\if@titlevisible
47 \@titlevisibletrue
48 \newif\if@abstractpresent
49 \@abstractpresentfalse
50 \newif\if@printbanner
51 \@printbannerfalse
52 \newif\if@suppressfulladdresses
53 \@suppressfulladdressesfalse
54 \newif\if@newstyle
55 \@newstylefalse
56 \newif\if@debug
57 \@debugfalse
58 \newif\if@boldkeywords
59 \@boldkeywordsfalse
```

The option handling—mainly setting various booleans.

```
60 \DeclareOption{manuscript}{\typeout{Manuscript for referee}
61   \@manuscripttrue\@journalfalse\@rmtwocolfalse
62   \PassOptionsToClass{10pt}{article}}
63 \DeclareOption{bigfont}{\typeout{Big font manuscript requested by Gary
64   Ferland}
65   \@manuscripttrue\@journalfalse\@rmtwocolfalse\@bigfonttrue
66   \PassOptionsToClass{11pt}{article}}
67 \DeclareOption{journal}{\typeout{Main journal option}%
68   \@journaltrue\@rmtwocoltrue\@printdatefalse\@manuscriptfalse
69   \PassOptionsToClass{10pt}{article}}
```

```

70 \DeclareOption{guide}{\typeout{User guide option}%
71 \@guidetrue\@journalfalse\@rmtwocoltrue\@manuscriptfalse
72 \PassOptionsToClass{10pt}{article}}
73 \DeclareOption{preprint}{\typeout{Preprint option}%
74 \@preprinttrue\@manuscriptfalse\PassOptionsToClass{10pt}{article}}
75 \DeclareOption{proof}{\typeout{Author proof option}%
76 \@prooftrue\@manuscriptfalse}
77 \DeclareOption{proceedings}{\typeout{Proceedings option}%
78 \@proceedingstrue\@journalfalse\@rmtwocoltrue\@newstyletrue
79 \@suppressfulladdressestrue
80 \@printdatesfalse\@manuscriptfalse\PassOptionsToClass{10pt}{article}}
81 \DeclareOption{printdates}{\typeout{Force printing of received/accepted dates}%
82 \@printdatestrue}
83 \DeclareOption{book}{\typeout{Whole issue option}%
84 \@booktrue}
85 \DeclareOption{nonatbib}{\typeout{Turn off natbib support (required
86 for compatibility with old rmaacite package).}%
87 \@natbibfalse}
88 \DeclareOption{newstyle}{\typeout{Use new layout style}%
89 \@newstyletrue}
90 \DeclareOption{oldstyle}{\typeout{Use old layout style}%
91 \@newstylefalse}
92 \DeclareOption{debug}{\typeout{Loads of annoying messages}%
93 \@debugtrue}

```

These two need to be declared explicitly so that `\ExecuteOptions` actually does something.

```

94 \DeclareOption{twocolumn}{\@rmtwocoltrue}
95 \DeclareOption{onecolumn}{\@rmtwocolfalse}
96 \DeclareOption{twoside}{\PassOptionsToClass{\CurrentOption}{article}}
97 \DeclareOption{boldkeywords}{\@boldkeywordstrue}

```

Bold, upper-case keywords used to be the default. Now they must be turned on explicitly with the `boldkeywords` option.

```

98 \DeclareOption{boldkeywords}{\@boldkeywordstrue}

```

Pass any other option along to the article class.

```

99 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}

```

Default options are to be two-sided and based on the standard L^AT_EX `article` class, unless we are processing the entire book, in which case we base ourselves on the standard `book` class. Default is to use `manuscript` option unless otherwise specified.

```

100 \ExecuteOptions{twoside,manuscript} \ProcessOptions\relax
101 \if@book
102 \if@rmtwocol\LoadClass[twocolumn]{book}\else\LoadClass{book}\fi
103 \newcommand{\abstract}{\relax}
104 \newcommand{\@maketitle}{\relax}
105 \else
106 \if@rmtwocol\LoadClass[twocolumn]{article}\else\LoadClass{article}\fi
107 \fi

```

Attempt to use `natbib` for citations 02 Jan 2003.

```

108 \if@natbib
109 \RequirePackage{natbib}[1999/02/25]
110 \bibpunct{({})}{;}{a}{}{,}
111 \def\bibfont{\small}

```

```

112 \renewcommand\bibsection{\section*{REFERENCES}}
113 \setlength\bibsep{0pt}
114 \setlength\bibhang{1.5em}
115 \bibliographystyle{rmaa}
116 \fi

```

We want the `graphicx` package for the extended syntax of `\includegraphics`. We want the `ifthen` package for using in these macros (although we don't much yet). We explicitly load `babel` since some \LaTeX distributions messed up the hyphenation if we didn't.

```

117 \RequirePackage{graphicx}
118 \RequirePackage{ifthen}
119 \IfFileExists{babel.sty}{%
120 %   \let\@restoreindent=\@afterindentfalse
121   \RequirePackage[english]{babel}
122 %   \@restoreindent
123 %% reinstate the definition of \@roman so as not to break .idx files
124 \@ifundefined{org@@roman}{\relax}{\renewcommand{\@roman}[1]{\org@@roman{##1}}}
125 }{%
126 \typeout{Package babel.sty not found - don't worry about this}}

```

Try to load the `dcolumn` and `booktabs` packages if they can be found. These can produce nicer-looking tables.

```

127 \IfFileExists{dcolumn.sty}{%
128   \RequirePackage{dcolumn}
129 }{%
130   \typeout{Package dcolumn.sty not found - you will not be able to
131     align columns on decimal points in tables}}
132 \IfFileExists{booktabs.sty}{%
133   \RequirePackage{booktabs}
134 }{%
135   \typeout{Package booktabs.sty not found - your tables will not look
136     as pretty as they ought too.}
137 }
138 \IfFileExists{makeidx.sty}{%
139   \RequirePackage{makeidx}
140 }{%
141   \typeout{Package makeidx.sty not found - Author Index may not work.}
142 }
143 %% commented out for moment since requires more modern version of LaTeX
144 %% \RequirePackage{latin1}{inputenc}

```

We use `hyperref` to get internal and external links. But I don't like the colored boxes so I turn those off. We use `etoolbox` for patching and robustifying at the moment. In the future, I want to port a lot of other stuff over to it. For instance, replace the `ifthen` package and the \TeX ifs too.

We target the latest version (1.7) of PDF, rather than the default of 1.5. This reduces the chance of getting warnings from included `graphics`. This is not strictly related to `hyperref`, but we put it here anyway.

```

145 \RequirePackage{etoolbox}
146 \RequirePackage{hyperref}
147 \hypersetup{hidelinks}
148 \pdfminorversion=7

```

We patch the `\@combinedblfloats` following a suggestion by Heiko Oberdiek

at <https://tex.stackexchange.com/a/249743/3843>, which avoids problems when hyperlinks are split across pages.

```
149 \urlstyle{same}
150 \newcommand\email{\begingroup \urlstyle{rm}\Url}
151 \patchcmd\@combinedbfloats{\box\@outputbox}{\unvbox\@outputbox}{}{%
152 \errmessage{\noexpand\@combinedbfloats could not be patched}%
153 }%
```

2.2 Other setup stuff

Some declarations:

```
154 \newif\if@needaddresses
155 \@needaddressestrue
156 \newif\if@frontmatter
157 \@frontmatterfalse
158 \newif\if@inpreamble
159 \@inpreamblettrue
160 \newif\if@firstauthor
161 \@firstauthortrue
162 \newif\if@firstaffil
163 \@firstaffiltrue
164 \newif\if@firstaltaffil
165 \@firstaltaffiltrue
166 \newif\if@firstkwd
167 \@firstkwdtrue
168 \newif\if@noexpandADS
169 \@noexpandADSfalse
170 \newif\if@sessiontitlepages
171 \@sessiontitlepagesfalse
```

```
\@rmaaEmpty These are used in various commands to check if arg was left blank
\@rmaaArg 172 \newcommand{\@rmaaEmpty}{}
173 \newcommand{\@rmaaArg}{}%
```

2.3 Compatibility with old L^AT_EX versions

This package is based on the 1998/12/01 release of L^AT_EX. Older releases may not define all the commands that we need. Luckily, we can use `\providecommand` to define these if necessary. The following commands are not defined in the 1994/06/01 release.

```
\MakeUpperCase User commands:
\textsuperscript 174 \providecommand{\MakeUpperCase}[1]{\uppercase{#1}}
\textbackslash 175 \providecommand{\textsuperscript}[1]{\ensuremath{\textsuperscript{#1}}}
176 \providecommand{\textbackslash}{\ensuremath{\backslash}}
```

```
\protected@xdef LATEX internal commands:
\restore@protect 177 \providecommand{\protected@xdef}{}
178 \let\@protect\protect
\@unexpandable@protect 179 \let\protect\@unexpandable@protect
\hb@xt@ 180 \afterassignment\restore@protect
181 \xdef}
```

```

182 \providecommand{\restore@protect}{\let\protect\@@protect}
183 \providecommand{\@unexpandable@protect}{\noexpand\protect\noexpand}
184 \providecommand{\hb@xt@}{\hbox to}

```

2.4 Page layout

The dimensions of the text were defined by Elizabeth. Text width is 169 mm with equal margins on the two sides:

```

185 \setlength{\textwidth}{169mm}
186 \setlength{\@tempdima}{\paperwidth}
187 \addtolength{\@tempdima}{-\textwidth}
188 \setlength{\oddsidemargin}{0.5\@tempdima}
189 \addtolength{\oddsidemargin}{-1in}
190 \setlength{\evensidemargin}{\oddsidemargin}

```

Text height is 225 mm, top margin is 14 mm.

```

191 \setlength{\textheight}{225mm}
192 \setlength{\topmargin}{-1in}
193 \addtolength{\topmargin}{14mm}

```

Space between columns in two-column styles, header, footer, paragraph indentation:

```

194 \setlength{\columnsep}{9.5mm}
195 \setlength{\headsep}{0.7cm}
196 \setlength{\footskip}{0.75cm}
197 \setlength{\parindent}{1.5em}

```

\@set@scalable@length

Try out a new scheme for dealing with various spacing dimensions and allowing the user to easily modify them. The command

```
\set@scalable@length{<name>}{<defaultlength>}{<stretch>}{<shrink>}
```

does a `\setlength{<name>}{<defaultlength plus stretch minus shrink>}` and also defines the user command `\<name>Scale{<factor>}` that can be used to rescale length by `<factor>`. Additionally, now defines the package command `\<name>@set@scale{<FACTOR>}` that also rescales the length by `<FACTOR>`, so that the length becomes $\langle factor \rangle \times \langle FACTOR \rangle \times \langle defaultlength \rangle$.

```

198 \newcommand\@set@scalable@length[4]{%
199   %% arg #1: NAME of length without leading '\\'
200   %%
201   %% arg #2: default VALUE
202   \expandafter\newlength\csname @#1@default\endcsname
203   \expandafter\setlength\csname @#1@default\endcsname{#2}%
204   \expandafter\newlength\csname @@#1@@default\endcsname
205   \expandafter\setlength\csname @@#1@@default\endcsname{#2}%
206   %% arg #3: default STRETCH
207   \expandafter\newlength\csname @#1@stretch\endcsname
208   \expandafter\setlength\csname @#1@stretch\endcsname{#3}%
209   \expandafter\newlength\csname @@#1@@stretch\endcsname
210   \expandafter\setlength\csname @@#1@@stretch\endcsname{#3}%
211   %% arg #4: default SHRINK
212   \expandafter\newlength\csname @#1@shrink\endcsname
213   \expandafter\setlength\csname @#1@shrink\endcsname{#4}%
214   \expandafter\newlength\csname @@#1@@shrink\endcsname

```

```

215 \expandafter\setlength\csname @@#1@@shrink\endcsname{#4}%
216 %%
217 %% User-defined scale \@NAME@scale is unity by default
218 \expandafter\gdef\csname @#1@scale\endcsname{1}%
219 %% Package-defined scale \@NAME@SCALE is unity by default
220 \expandafter\gdef\csname @#1@SCALE\endcsname{1}%
221 %%
222 %% internal command \@reset@NAME should expand to
223 %% \setlength\@@NAME@@default{\@NAME@SCALE\@NAME@default}
224 %% \setlength\NAME{\@NAME@scale\@@NAME@@default}
225 %% in other words: scale x SCALE x default
226 \expandafter\gdef\csname @reset@#1\endcsname{%
227   \expandafter\setlength\csname @@#1@@default\endcsname{%
228     \csname @#1@SCALE\endcsname \csname @#1@default\endcsname
229   }
230   \expandafter\setlength\csname @@#1@@stretch\endcsname{%
231     \csname @#1@SCALE\endcsname \csname @#1@stretch\endcsname
232   }
233   \expandafter\setlength\csname @@#1@@shrink\endcsname{%
234     \csname @#1@SCALE\endcsname \csname @#1@shrink\endcsname
235   }
236   \expandafter\setlength\csname #1\endcsname{%
237     \csname @#1@scale\endcsname \csname @@#1@@default\endcsname
238     \@plus
239     \csname @#1@scale\endcsname \csname @@#1@@stretch\endcsname
240     \@minus
241     \csname @#1@scale\endcsname \csname @@#1@@shrink\endcsname
242   }}
243 %%
244 %% User command \NAMEscale should expand to
245 %% {\renewcommand\@NAME@scale{#1}\@reset@NAME}
246 \expandafter\gdef\csname #1Scale\endcsname##1{%
247   \expandafter\gdef\csname @#1@scale\endcsname{##1}%
248   \csname @reset@#1\endcsname}
249 %%
250 %% Package command \NAME@set@SCALE should expand to
251 %% {\renewcommand\@NAME@SCALE{#1}\@reset@NAME}
252 \expandafter\gdef\csname #1@set@SCALE\endcsname##1{%
253   \expandafter\gdef\csname @#1@SCALE\endcsname{##1}%
254   \csname @reset@#1\endcsname}
255 %%
256 %% initialize at default values with \@reset@NAME
257 \csname @reset@#1\endcsname
258 }

```

\parskip First use of this new infrastructure: set interparagraph space to be zero but with a small amount of stretchiness.

```

259 % \ifthenelse{\boolean{@manuscript}}{%
260 %   \@set@scalable@length{parskip}{0.5\baselineskip}{0.3\p@}{0.1\p@}
261 % }{
262 %   \@set@scalable@length{parskip}{0\p@}{0.3\p@}{0\p@}
263 % }

```

\abovesectionskip Define some utility rubber lengths for use in section 2.13.

```

\belowsectionskip 264 \newlength{\abovesectionskip}
\aboveparaskip 265 \newlength{\belowsectionskip}
\belowparaskip

```



```

266 \newlength{\aboveparaskip}
267 \newlength{\belowparaskip}

```

The default values for these lengths are those traditionally used for the onecolumn style.

```

268 \@set@scalable@length{abovesetionskip}{-3.5ex}{-4ex}{-2ex}
269 \@set@scalable@length{belowsetionskip}{2.3ex}{0ex}{2ex}
270 \@set@scalable@length{aboveparaskip}{3.25ex}{2ex}{0.5ex}
271 \@set@scalable@length{belowparaskip}{-1em}{\z@}{\z@}

```

We also make scalable some of the standard float parameters. These are the same defaults as in the standard article classes, but slightly more stretchy. For the twocolumn style, they are currently halved, see below. Note that I have also lumped `\abovecaptionskip` in with these, since it plays a similar role. There is also a `\belowcaptionskip` but it is set to zero in the standard classes.

```

272 \@set@scalable@length{floatsep}{12\p@}{4\p@}{4\p@}
273 \@set@scalable@length{textfloatsep}{20\p@}{4\p@}{8\p@}
274 \@set@scalable@length{intextsep}{12\p@}{4\p@}{4\p@}
275 \@set@scalable@length{dblfloatsep}{12\p@}{4\p@}{4\p@}
276 \@set@scalable@length{dbltextfloatsep}{20\p@}{4\p@}{8\p@}
277 \@set@scalable@length{abovecaptionskip}{10\p@}{\z@}{\z@}

```

<pre> \@before@title@skip \@before@author@skip \@between@author@skip \@before@abstract@skip \@after@abstracthead@skip \@between@abstract@skip \@before@kwd@skip \@before@dates@skip </pre>	<p>Spacing parameters used in <code>\@maketitle</code>. These are not changed by default except by the user, so they don't need to go into <code>\@package@default@lengths</code>.</p> <pre> 278 \newlength{\@before@title@skip} 279 \newlength{\@before@author@skip} 280 \newlength{\@between@author@skip} 281 \newlength{\@before@abstract@skip} 282 \newlength{\@after@abstracthead@skip} 283 \newlength{\@between@abstract@skip} 284 \newlength{\@before@kwd@skip} 285 \newlength{\@before@dates@skip} 286 \@set@scalable@length{@before@title@skip}{2em}{\z@}{\z@} 287 \@set@scalable@length{@before@author@skip}{1.5em}{\z@}{\z@} 288 \@set@scalable@length{@between@author@skip}{0.5em}{\z@}{\z@} 289 \@set@scalable@length{@before@abstract@skip}{3ex}{1ex}{0.5ex} 290 \@set@scalable@length{@after@abstracthead@skip}{1ex}{\z@}{\z@} 291 \@set@scalable@length{@between@abstract@skip}{2ex}{1ex}{0.5ex} 292 \@set@scalable@length{@before@kwd@skip}{1ex}{0.5ex}{0.2ex} 293 \@set@scalable@length{@before@dates@skip}{2ex}{0.5ex}{0.2ex} </pre>
--	---

Spacing above and below displayed equations also wants to be done like this, but it is more complicated since the standard article classes make these change with the fontsize. Something to do later, maybe.

<pre> \@package@default@lengths </pre>	<p>The value actually used for these lengths is controlled by the <code>\SCALE</code> parameter, which depends on the style option that is in effect. This is set using the <code>\@package@default@lengths</code> command, which must be called every time the style changes (e.g., changing from onecolumn to twocolumn).</p>
--	---

```

294 \newcommand{\@package@default@lengths}{%
295   \ifthenelse{\boolean{@rmtwocol}}{%
296     %% twocolumn mode
297     \abovesetionskip@set@SCALE{0.5}

```

```

298 \belowsections@set@SCALE{0.5}
299 \aboveparaskip@set@SCALE{0.5}
300 \belowparaskip@set@SCALE{1}
301 \floatsep@set@SCALE{0.5}
302 \textfloatsep@set@SCALE{0.5}
303 \intextsep@set@SCALE{0.5}
304 \dblfloatsep@set@SCALE{0.5}
305 \dbltextfloatsep@set@SCALE{0.5}
306 }{%
307 %% onecolumn mode
308 \abovesec@set@SCALE{1}
309 \belowsec@set@SCALE{1}
310 \abovepar@set@SCALE{1}
311 \belowpar@set@SCALE{1}
312 \floatsep@set@SCALE{1}
313 \textfloatsep@set@SCALE{1}
314 \intextsep@set@SCALE{1}
315 \dblfloatsep@set@SCALE{1}
316 \dbltextfloatsep@set@SCALE{1}
317 }%
318 }
319 \@package@default@lengths

```

`\RescaleLengths` User commands that will fiddle with all the scalable lengths.

```

\RescaleSecLengths 320 \newcommand{\RescaleLengths}[1]{%
\RescaleFloatLengths 321 \RescaleSecLengths{#1}\RescaleFloatLengths{#1}\RescaleTitleLengths{#1}}
\RescaleTitleLengths 322 \newcommand{\RescaleSecLengths}[1]{%
323 %% sections
324 \abovesec@set@SCALE{#1}
325 \belowsec@set@SCALE{#1}
326 \abovepar@set@SCALE{#1}
327 }
328 \newcommand{\RescaleFloatLengths}[1]{%
329 %% floats
330 \floatsep@set@SCALE{#1}
331 \textfloatsep@set@SCALE{#1}
332 \intextsep@set@SCALE{#1}
333 \dblfloatsep@set@SCALE{#1}
334 \dbltextfloatsep@set@SCALE{#1}
335 \abovecaption@set@SCALE{#1}
336 }
337 \newcommand{\RescaleTitleLengths}[1]{%
338 %% maketitle
339 \@before@title@skip@set@SCALE{#1}
340 \@before@author@skip@set@SCALE{#1}
341 \@between@author@skip@set@SCALE{#1}
342 \@before@abstract@skip@set@SCALE{#1}
343 \@after@abstracthead@skip@set@SCALE{#1}
344 \@between@abstract@skip@set@SCALE{#1}
345 \@before@kwd@skip@set@SCALE{#1}
346 \@before@dates@skip@set@SCALE{#1}
347 }

```

`\MSextramargin` For the manuscript option we have an extra 0.3 inch vertical margin and 1 inch horizontal margin for marginal notes (by hand or with `\marginpar`).

```

348 \newlength{\MSeextraHmargin}\newlength{\MSeextraVmargin}
349 \setlength{\MSeextraHmargin}{1in}
350 \setlength{\MSeextraVmargin}{0.3in}
351 \if@manuscript
352   \renewcommand{\baselinestretch}{1.1}
353   \addtolength{\textwidth}{-2\MSeextraHmargin}
354   \addtolength{\oddsidemargin}{\MSeextraHmargin}
355   \setlength{\evensidemargin}{\oddsidemargin}
356   \addtolength{\textheight}{-2\MSeextraVmargin}
357   \addtolength{\topmargin}{\MSeextraVmargin}
358 %     \raggedright
359 \fi

```

Float parameters: don't allow bottom floats by default.

```

360 \renewcommand{\fps@figure}{tp}
361 \renewcommand{\fps@table}{tp}

```

```

\rmaa@AuthorWidthFrac
\rmaa@AbstractWidthFrac

```

These parameters control what fraction of the total text width can be used by the list of authors and the abstract/resumen, respectively.

```

362 \newcommand{\rmaa@AuthorWidthFrac}{1.0}
363 \newcommand{\rmaa@AbstractWidthFrac}{0.75}

```

Use a wide abstract to save space in the new style.

```

364 \if@newstyle\renewcommand{\rmaa@AbstractWidthFrac}{1.0}\fi

```

Some things to consider in future versions. Trying to avoid too many widows, etc. Apparently, the following will work best with `\flushbottom`.

```

365 %%\widowpenalty=10000
366 %%\clubpenalty=10000

```

Also, should perhaps try getting rid of underfull/overfull box warnings.

```

367 \hbadness=10000
368 \vbadness=10000
369 \setlength\hfuzz{\maxdimen}
370 \setlength\vfuzz{\maxdimen}

```

2.5 Various text styles for different contexts

```

\rmaa@AffilStyle
\rmaa@PagesStyle
\rmaa@YearStyle
\rmaa@VolumeStyle
\rmaa@VolumenStyle
\rmaa@JournalNameStyle
\rmaa@ReceivedStyle
\rmaa@AbstractHeaderStyle
\rmaa@JournalNameStyle

```

Style commands for the different fields used by `\maketitle` in constructing the title page of the article. These have the form `\rmaa@XYZStyle{TEXT}`. I'm not sure these were really a good idea, but never mind ...

```

371 \newcommand{\rmaa@AffilStyle}[1]{\normalsize\rmfamily#1}
372 \newcommand{\rmaa@PagesStyle}[1]{\normalsize\rmfamily#1}
373 \newcommand{\rmaa@YearStyle}[1]{\normalsize\rmfamily#1}
374 \newcommand{\rmaa@VolumeStyle}[1]{\normalsize\rmfamily\bfseries#1}
375 \newcommand{\rmaa@VolumenStyle}[1]{\Large\sffamily\bfseries#1}
376 \newcommand{\rmaa@JournalNameStyle}[1]{\normalsize\itshape#1}
377 \newcommand{\rmaa@ReceivedStyle}[1]{\normalsize\rmfamily\itshape#1}
378 \newcommand{\rmaa@AbstractHeaderStyle}[1]{%
379   {\normalsize\rmfamily\MakeUpperCase{#1}}}
380 \newcommand{\rmaa@TitleStyle}[1]{%
381   {\large\bfseries\rmfamily\boldmath\MakeUpperCase{#1}\par}}

```

`\rmaa@FrontSecStyle` Headings of “front sections” (see section 2.21)

```

382 \newcommand{\rmaa@FrontSecStyle}[1]{%
383   {\normalsize\bfseries\rmfamily\MakeUpperCase{#1}}}
```

`\rmaa@TOCTitleStyle` Commands to set style of TOC and index entries. Rewritten to avoid unnecessary
`\rmaa@TOCPartStyle` font commands in the .toc and .ind files

```

\rmaa@IndexTitleStyle 384 \newcommand{\rmaa@TOCTitleStyle}[1]{\MakeUpperCase{#1}}
\rmaa@TOCAuthorStyle 385 \newcommand{\rmaa@TOCPartStyle}[1]{\rmaa@TOCTitleStyle{#1}}
\rmaa@IndexAuthorStyle 386 \newcommand{\rmaa@IndexTitleStyle}[1]{#1}
387 \newcommand{\rmaa@TOCAuthorStyle}[1]{%
388   {\itshape#1}}
389 \newcommand{\rmaa@IndexAuthorStyle}[1]{%
390   \protect\mbox{\bfseries#1}}
```

`\rmaa@KeywordStyle` The style of the keywords depends on whether we are using the newstyle op-
`\rmaa@KeywordHeaderStyle` tion or not. If we are, then they are small.

```

391 \ifthenelse{\boolean{@newstyle}}{
392   \newcommand{\rmaa@KeywordStyle}[1]{%
393     {\small%
394       \if@boldkeywords
395         \bfseries\MakeUpperCase{\raggedright #1}
396       \else
397         \raggedright #1
398       \fi
399     }}
400 \newcommand{\rmaa@KeywordHeaderStyle}[1]{%
401   {\small\itshape#1}}
402 {
403   \newcommand{\rmaa@KeywordStyle}[1]{%
404     {\normalsize%
405       \if@boldkeywords\bfseries\fi\raggedright #1}}
406 \newcommand{\rmaa@KeywordHeaderStyle}[1]{%
407   {\normalsize\itshape#1}}
```

2.6 Page styles

`\ps@rmaa` The running headers for normal pages:

```

408 \newcommand{\ps@rmaa}{%
nothing in either foot;
409 \renewcommand\@oddfoot{\relax}%
410 \renewcommand\@evenfoot{\relax}%
page number and short author list in the even heads;
411 \renewcommand\@evenhead{\rlap{\thepage}\hfil\@shortauthor\hfil}%
short title and page number in the odd heads.
412 \renewcommand\@oddhead{\hfil\@shorttitle\hfil\llap{\thepage}}
413 }
```

`\ps@rmaafirstpage` The header of the first page of each article:

```

414 \newcommand{\ps@rmaafirstpage}{%
415   \renewcommand\@oddfoot{\hfil\thepage}%
}
```

footer corrected (06 Jun 2000) to have page on outside edge;

```
416 \renewcommand\@evenfoot{\thepage\hfil}%
```

Header has journal name, volume, and page numbers for a regular article, or similar for special cases.

```
417 \if@preprint
418 \renewcommand\@oddhead{%
419   \if@proceedings
420     \textsc{To appear in ``\@conftitle{} (\rmaa@YearStyle{\@year})''}\hfil
421     \textit{RMxAC}
422   \else
423     \textsc{To appear in} \@journalname\hfil
424   \fi}\fi%
425 \if@guide
426 \renewcommand\@oddhead{\textsc{Documentation} (\rmaa@YearStyle{\@year})\hfil}
427 \fi%
428 \if@manuscript
429 \renewcommand\@oddhead{Manuscript for \@journalname{} (\rmaa@YearStyle{\@year})\hfil}
430 \fi%
431 \if@journal
432 \renewcommand\@oddhead{%
433   \parbox{\textwidth}{
434     \@journalname, \rmaa@VolumeStyle{\@volume},
435     \rmaa@PagesStyle{\@artpages}\
436     (\rmaa@YearStyle{\@year})\hfil\[\1pt]
437     {\small\textcopyright{} \@year:
438       Instituto de Astronom\i{}a,
439       Universidad Nacional Aut\onoma de M\exico}\hfil\[\1pt]
440     {\small\@DOI@url}\hfil
441   }%
442 }\fi%
443 \renewcommand\@evenhead{\@oddhead}}
```

By default, use the \ps@rmaa page style.

```
444 \pagestyle{rmaa}
```

2.7 Preamble commands

Everything you need for setting the title page, TOC and index entries, etc.

2.7.1 Commands for the title page

\resumen User commands for setting the resumen and abstract. These should be used in the document header. The internal commands \@resumen and \@abstract are used to hold the actual text pending output via the \maketitle command.

```
\@abstract 445 \newif\if@setresumen
446 \newcommand{\resumen}[1]{%
447 %% \renewcommand{\@resumen}{\selectlanguage{spanish}\#1}}%
448 \renewcommand{\@resumen}{\ignorespaces\#1}%
449 \@setresumentrue}
450 \renewcommand{\abstract}[1]{%
451 \renewcommand{\@abstract}{\ignorespaces\#1}}
452 \renewcommand\ADS@abstract{\#1}
453 %% Not a good idea, since then author macros are not expanded and
```

```

454 %% cause errors later. However, by not doing it we are vulnerable to
455 %% fragile commands.....
456 \if@noexpandADS\@onelevel@sanitize{\ADS@abstract}\fi
457 \abstractpresenttrue
458 }
459 \newcommand{\ADSnoexpand}{\@noexpandADStrue}

\boldabstract This is the version for doing 1-page conference proceedings. Still save the text for
ADS but then write it out immediately as a bold paragraph.

460 \newcommand{\boldabstract}[1]{%
461 \gdef\ADS@abstract{#1}%
462 \renewcommand{\@abstract}{#1}%
463 \if@noexpandADS\@onelevel@sanitize{\ADS@abstract}\fi%
464 \noindent\textbf{\boldmath #1}
465 }

Default value in each case is to print out a warning if not set

466 \newcommand{\@resumen}{%
467 \setresumenfalse \ClassWarningNoLine{rmaa}{No Spanish abstract
468 (resumen) specified - if you do not speak Spanish, this will be
469 translated by the editors}%
470 \textbf{Favor de proporcionar un resumen en espa\~nol. If you are
471 unable to translate your abstract into Spanish, the editors will
472 do it for you.} }
473 \newcommand{\@abstract}{\ClassWarningNoLine{rmaa}{No abstract
474 specified}}

\title Similarly, \title is the preamble command to set the title of the article. This
\@rawtitle is used in various places, typeset in different styles, hence the use of the inter-
\@TOCtitle nal \@rawtitle, \@title, \rmaaIndexTitle, and \@TOCtitle commands,
\rmaaIndexTitle each of which uses the relevant style from section 2.5

475 \newcommand{\@rawtitle}{Raw Title}
476 \newcommand{\@TOCtitle}{\rmaa@TOCTitleStyle{Title for TOC}}
477 \newcommand{\rmaaIndexTitle}{\rmaa@IndexTitleStyle{Title for index}.}
478 \newcommand{\@TOCaftertitle}{}
479 \renewcommand{\title}[1]{%
480 %% {\ADS@sanitize\xdef\@rawtitle{#1}}
481 \renewcommand{\@rawtitle}{\noexpand#1}
482 \let\ADS@title=\@rawtitle
483 \renewcommand{\@title}{\rmaa@TitleStyle{#1}}%
484 \renewcommand{\@TOCtitle}{\rmaa@TOCTitleStyle{#1}\@TOCaftertitle}%
485 \renewcommand{\rmaaIndexTitle}{\rmaa@IndexTitleStyle{#1}\@TOCaftertitle}.}%
486 }

All the weird and whacky ways of indicating the author affiliations.

\affil First, the way that sets it directly underneath the authors name. Note that
\affil trumps all other affiliations for the purposes of getting into the ADS
stuff (we use \gdef). ...

487 \newcommand{\affil}[1]{%
488 \[1.5ex]\rmaa@AffilStyle{#1}\[1.5ex]%
489 \if@firstaffil\gdef\ADS@affil{#1}\@firstaffilfalse\fi
490 }
491 \renewcommand{\and}{and\[1.5ex]}

```

`\altaffil` Alternative affiliations are footnoted.

```

492 \newcommand{\altaffil}[1]{%
493   \if@firstaltaffil\gdef\ADS@affil{#1}\@firstaltaffilfalse\fi%
494   \thanks{#1}}

```

`\altaffilmark` Alternative-alternative mechanism for affiliations—should not be mixed with
`\altaffiltext` `\altaffil` (unless you know what you are doing) or there will be problems with numbering.

```

495 \newcommand{\altaffilmark}[1]{\textsuperscript{#1}}
496 \newcommand{\altaffiltext}[2]{%
497   \if@firstaltaffil\gdef\ADS@affil{#2}\@firstaltaffilfalse\fi
498   \stepcounter{footnote}%
499   \protected@xdef\@thanks{\@thanks
500     \protect\footnotetext[#1]{#2}}

```

`\keywords` Sundry minor preamble commands. All self-explanatory, I hope. `\keywords` is
`\@keywords` the old user interface (deprecated). New articles should use `\addkeyword` once
`\@keywordheader` for each keyword. That way the ADS record comes out right too (comma rather than em-dash separator).

```

501 \newcommand{\@kwdsep}{ --- }
502 \newcommand{\ADS@kwdsep}{, }
503 \newcounter{kwdcounter}\setcounter{kwdcounter}{0}
504 \newcommand{\addkeyword}[1]{%
505   \addtocounter{kwdcounter}{1}
506   \ifthenelse{\thekwdcounter > 6}{
507     \ClassError{rmaa}{Too many keywords. A maximum of 6 keywords is allowed.}{}
508   }{}
509   \if@firstkwd%
510     \renewcommand{\@keywords}{\if@boldkeywords\uppercase{#1}\else #1\fi}
511     {\ADS@sanitize\def\ion{\plainion}\gdef\ADS@keywords{#1}}
512     \@firstkwdfalse
513   \else%
514     \edef\@keywords{\@keywords\@kwdsep \if@boldkeywords\uppercase{#1}\else #1\fi}%
515     {\ADS@sanitize\def\ion{\plainion}\xdef\ADS@keywords{\ADS@keywords\ADS@kwdsep #1}}%
516   \fi}
517 \newcommand{\ADS@sanitize}{%
518   \def\mathrm{}
519   \def\@{\ }
520   \def~{\ }
521   \def\langle{<}
522   \def\rangle{>}
523   \def\log{log }
524   \def\sin{sin }
525   \def\cos{cos }
526   \def\tan{tan }
527   \def\fd{^d.}
528   \def\fh{^h.}
529   \def\fm{^m.}
530   \def\fs{^s.}
531   \def\fdg{.}
532   \def\farcm{'.}
533   \def\farcs{''}
534   \def\arcdeg{}
535   \def\,{ }
536 }

```

```

537 \newcommand{\keywords}[1]{%
538   \renewcommand{\ADS@keywords}{#1}
539   \renewcommand{\@keywords}{\uppercase{#1}}
540 }
541 \newcommand{\@keywordheader}{\rmaa@KeywordHeaderStyle{Key Words:}}
542 \newcommand{\@keywords}{%
543   \ClassWarningNoLine{rmaa}{No keywords specified}%
544   Keywords go here
545 }

```

`\shorttitle` **Commands for setting the running headers.**

```

\shortauthor 546 \newcommand{\shorttitle}[1]{%
\shorttitle 547   \renewcommand{\@shorttitle}{\MakeUpperCase{#1}}
\@shortauthor 548 \newcommand{\shortauthor}[1]{%
549   \renewcommand{\@shortauthor}{\MakeUpperCase{#1}}
550 \newcommand{\@shorttitle}{SHORT TITLE GOES HERE}
551 \newcommand{\@shortauthor}{SHORT AUTHOR GOES HERE}

```

2.7.2 The full addresses

`\fulladdresses` **Aaghh, the full addresses! A perennial source of problems.**

```

\@fulladdresses 552 \newlength{\@fulladdheight}
\@fulladdheight 553 \newlength{\@fulladddepth}
\@fulladddepth 554 \newsavebox{\@fulladdbox}
\@fulladdbox 555 %% \fulladdresses command modified (11 May 2000) so that we can put
556 %% \fulladdresses{} in the article to suppress the output of the
557 %% addresses
558 \newcommand{\@FinalFigure}{\relax}
559 \newcommand{\FinalFigure}[1]{\renewcommand{\@FinalFigure}{#1}}
560 \newcommand{\fulladdresses}[1]{%
561   \renewcommand{\@rmaaArg}{#1}
562   \ifx\@rmaaArg\@rmaaEmpty
563     \renewcommand{\@fulladdresses}{}
564   \else
565     \renewcommand{\@fulladdresses}{
566       \normalsize%
567       \ifx\@FinalFigure\relax\else\vfill\@FinalFigure\vfill\fi
568     %%
569     %% do addresses as a list (copied from thebibliography environment)
570     \list{\null}{\leftmargin 1.5em\topsep\z@\labelwidth\z@\labelsep\z@itemindent -1.5em
571       \itemsep\z@\parsep\z@\usecounter{enumi}}
572     \sloppy\clubpenalty4000\widowpenalty4000
573     \sfcode'\.=1000\relax
574     #1
575     \endlist
576   }
577 \fi
578 }
579 \newcommand{\@fulladdresses}{Full addresses go here}

```

`\suppressfulladdresses` **New user-level command for suppressing full addresses should you so desire.
Currently used in the single-page-poster style.**

```

580 \newcommand{\suppressfulladdresses}{\@suppressfulladdressestrue\@needaddressesfalse}

```


`\printdates` Command to activate the printing out of the received/accepted dates. This can also be done using the `printdates` option, which is the default for `journal`, but not for `proceedings`.

```
581 \newcommand{\printdates}{\@printdatestrue}
582 \newcommand{\noprintdates}{\@printdatesfalse}
```

`\@outputaddressesifnecessary` Command to output the addresses if we haven't already done so This is called by:

1. The end of the `thebibliography` environment
2. The `\outputfulladdresses` command

```
583 \newcommand{\@outputaddressesifnecessary}{%
584   \ClassInfo{rmaa}{Calling \@outputaddressesifnecessary}
585   \ifthenelse{\boolean{@needaddresses}}{%
586     %% If in one column style, or in the first column of a two column
587     %% style then we can try to put it on this page
588     \ifthenelse{\boolean{@firstcolumn} \or \not\boolean{@rmtwocol}}{%
589       \@outputaddresses}{%
590       %% otherwise give warning it will be on a separate page
591       \ClassWarning{rmaa}{Full addresses will go on a separate
592         page (please see User Guide for how to remedy this)}}%
593     %% If we haven't managed yet, put it on its own page
594     \ifthenelse{\boolean{@needaddresses}}{%
595       \if@debug{\ClassWarning{rmaa}{In this silly bit!}}\fi
596       \clearpage\vfill\@outputaddresses}{}%
597   }{
598     %% If we don't need them, we still might need to do the eoa hook
599     \ifthenelse{\boolean{@suppressfulladdresses}}{%
600       \if@debug{\ClassWarning{rmaa}{XXX}}\fi
601     %%       \if@book\else\@endofarticlehook\null\fi
602     }{}
603   }%
604 }
```

`\outputfulladdresses` A user interface to the above command, in case there is no `biblio` (11 May 2000)

```
605 \newcommand{\outputfulladdresses}{\@outputaddressesifnecessary}
```

`\adjustfinalcols` This command starts a new column and should be used to ensure that the columns balance on the last page. It also outputs the full author addresses to ensure that this occurs in the left hand column. The `\par` command is so that the current line will be taken account of when working out `\pagetotal`

```
606 \newcommand{\adjustfinalcols}{\if@twocolumn\goodbreak\@outputaddresses\newpage\noindent\fi}
```

`\@outputaddresses` Command to do the work of outputting the addresses. This can be called by

1. an explicit `\adjustfinalcols`
2. via `\@outputaddressesifnecessary`, q.v.

```
607 \newcommand{\@outputaddresses}{%
608   % Allow option of suppressing the full addresses, in which case
609   % we just run the hook if we are not in a book style
610   \if@suppressfulladdresses
```

```

611 %%      \if@book\else\@endofarticlehook\null\fi
612 \else
613 %% save the full addresses in a box for output later
614 \sbox{\@fulladdbox}{\parbox{\textwidth}{\@fulladdresses}}
615 % calculate height of address box
616 \settoheight{\@fulladdheight}{\usebox{\@fulladdbox}}
617 \settodepth{\@fulladddepth}{\usebox{\@fulladdbox}}
618 \addtolength{\@fulladdheight}{\@fulladddepth}
619 \if@debug
620 { \typeout{Address total height: \the\@fulladdheight}
621   \typeout{Text height: \the\pagetotal}
622   \typeout{Goal height: \the\pagegoal}
623 }
624 \fi
625 % reuse \@fulladdheight to mean the total height of text+addresses
626 \addtolength{\@fulladdheight}{\pagetotal}
627 %% \addtolength{\@fulladdheight}{-\baselineskip}
628 \if@debug\typeout{Adjusted text + addresses height: \the\@fulladdheight}\fi
629 % check it will fit on current page
630 \ifdim\@fulladdheight<\pagegoal
631   %% must shift it to the left
632   %% to compensate for the hanging indentation in the reference list.
633   %% NOTE: this is not foolproof!
634   %% NB. This will give overfull hbox warnings, which is a bit ugly.
635   \vfill\noindent\if@Biblist\hspace*{-\leftmargin}\fi
636   \usebox{\@fulladdbox}
637   % Set this to show we've done it
638   \@needaddressesfalse
639   % and assume we are at the end of the article
640   % so that we do the EOA hook if not in the book style
641 %%      \if@book\else\@endofarticlehook\fi
642 \else
643   % if not, just do nothing. With luck, this function will get
644   % called again on the next page
645   \if@debug{\typeout{Holding over full addresses to next page}}\fi
646 \fi\fi
647 }

```

2.7.3 Commands for editors

Some user/editor commands for doing the TOC and index in the book option. They are defined here rather in the book-specific part since they need to be always available in order to avoid breaking documents.

<pre> \listofauthors \@rawauthors \rmaaTOCauthors </pre>	<p>The command <code>\listofauthors</code> formats an author list for use in the TOC. It should contain the same names as in the <code>\author</code> command, but without the affiliation garbage and using <code>\&</code> instead of and.</p> <pre> 648 \newcommand{\@rawauthors}{Raw Authors} 649 \newcommand{\rmaaTOCauthors}{\noexpand\rmaaTOCAuthorStyle{Author list for TOC}} 650 \newcommand{\listofauthors}[1]{% 651 \renewcommand{\@rawauthors}{#1} 652 \renewcommand\rmaaTOCauthors{\noexpand\rmaaTOCAuthorStyle{#1}}} </pre>
<pre> \indexauthor </pre>	<p>The command <code>\indexauthor</code> produces an index entry for each author. This command must come <i>after</i> the <code>\title</code> and the <code>\listofauthors</code> commands.</p>

Also, there should be one `\indexauthor` command for *each* author. We also add the author onto the end of the `\ADS@authors` macro and construct the `\ADS@authorinitial` by a most cunning method (see below), but only for the first author.

No, No, NO! This was all wrong. Backed out completely:

Completely rewritten (19 Dec 2002) since we now use the index class, so as to be able to alphabetize accented characters. A side effect of this is that `\index` no longer expands out the argument after the `@`, so we instead add all the `\index` commands to a list (`\indexauthor@deferlist`), which is executed in the `\@begofarticlehook`.

Note the stuff with `\toks0` is copied from Exercise 20.15 of the `TEXbook`—it is to make sure the latin1-accented name gets passed into the `idx` file.

We now go back to the old way of doing things, using an optional argument to the `\indexauthor` command that has the name without accents.

```

653 \newcommand\@isortkey{}
654 \newcommand\@emptykey{empty}
655 \newcommand\indexauthor[2][empty]{
656   \renewcommand\@isortkey{#1}
657   \ifx\@isortkey\@emptykey \renewcommand\@isortkey{#2}\fi
658   \index{\@isortkey @{\rmaaindexauthorstyle{#2}}\hskip1em plus1em minus0.4em
659     \rmaaindexTitle\hskip1em plus2em minus0.4em\penalty-100
660     \rmaaindexTOCauthors}}
661   \indexauthorADS{#2}
662 }
663 %%\def\indexauthor@deferlist{\relax}
664 %%\long\def\indexauthor#1{
665 %%  \def\@@name{#1} \toks0=\expandafter{\@@name}
666 %%  \toks1=\expandafter{\indexauthor@deferlist}
667 %%  \protected@xdef\indexauthor@deferlist{%
668 %%    \the\toks1
669 %%    \noexpand\index{\the\toks0@\noexpand\rmaaindexauthorstyle{\the\toks0}\noexpand\hskip1em
670 %%      \rmaaindexTitle\noexpand\hskip1em plus2em minus0.4em\noexpand\penalty-100
671 %%      \rmaaindexTOCauthors}}
672 %%  }
673 %%  \indexauthorADS{#1}
674 %%  }
675 %%\xdef\indexauthor@deferlist{}
676 \newcommand\indexauthorADS[1]{%
677   \if@firstauthor\protected@xdef\ADS@authorinitial{\firstletter{#1}}\fi
678   \protected@xdef\ADS@authors{\ADS@authors\if@firstauthor\else ; \fi
679     #1}
680   \@firstauthorfalse
681 }

```

Note that the first `#1` sets the key for the index, making sure it actually starts with first letter of the surname. Meanwhile, the `@{ . . . }` expression, which starts with some control sequences is what is written to the `.ind` file. See the `makeindex` man page for details.

`\KillAllAccents` These are utility functions used in the above. `lett` is a counter indicating the
`\firstletter`


```

713 \newcommand{\@journalname}{\rmaa@JournalNameStyle{%
714     \if@proceedings\RMAASCLong\else\RMAAlong\fi}}
715 \newcommand{\@received}{}
716 \newcommand{\@accepted}{}
717 \newcommand{\@MSnum}{0000}
718 \newcommand{\@DOI@prefix}{https://doi.org/10.22201/ia.01851101p}
719 \def\@DOI@url{\url{https://doi.org/10.22201/ia.01851101p.2099.00.00.00}}

```

The following commands are most useful in the book style. However, the `\SetConfTitle` command can now be used in individual articles to set the header for the preprint style.

```

720 \newcommand{\@reunionplace}{Lugar de la reuni\'on}
721 \newcommand{\@reuniondate}{Fecha de la reuni\'on}
722 \newcommand{\@conftitle}{Conference Title}
723 \newcommand{\SetReunion}[2]{\renewcommand{\@reunionplace}{#1}\renewcommand{\@reuniondate}{#2}}
724 \newcommand{\SetConfTitle}[1]{\renewcommand{\@conftitle}{#1}}
725 \newcommand{\@editors}{Juan Ram\'on de la Fuente and ``El Mosh''}
726 \newcommand{\SetEditors}[1]{\renewcommand{\@editors}{#1}}
727 \newcommand{\@editores}{Juan Ram\'on de la Fuente y ``El Mosh''}
728 \newcommand{\SetEditores}[1]{\renewcommand{\@editores}{#1}}
729 \newcommand{\@mes}{mes de la publicaci\'on}
730 \newcommand{\SetMes}[1]{\renewcommand{\@mes}{\rmaa@VolumenStyle{#1}}}

```

2.8 Notes for Author Proofs and Communication between Editors

We introduce a command `\Note` that should be used to describe any change made to the manuscript. These are a bit tricky to get right. In general we use `\marginpar` but this only works in outer paragraph mode, so we just bung the box where we are if we are in a figure caption or something. If we are in the preamble, then we just use a s part of the

a

November 18, 2019

command.

```
731 \newif\if@arenotes
732 \@arenotesfalse
733 \newcounter{notecounter}
734 \setcounter{notecounter}{0}
735 \newcommand\NotesList{}
736 \newcommand\Note[1]{%
737   \if@proof{%
738     \@arenotesttrue%
739     \stepcounter{notecounter}%
740     \if@inpreamble\else{%
741       \NoteMark{\arabic{notecounter}}}%
742     }\fi
743     \protected@xdef\NotesList{\NotesList
744       \protect\item #1}%
745   }\fi%
746 }
747 \newcommand\Changed[2]{Changed ``#1'' to ``#2'' .}
748 \newcommand\NoteMark[1]{%
749   \ifinner
750     \raisebox{1ex}[0pt][0pt]{\makebox[0pt][l]{\framebox{\footnotesize\bfseries
751       N#1}}}%
752   \else
753     \marginpar{\framebox{\footnotesize\bfseries N#1}}%
754   \fi
755 }
756 \newcommand\RefNote[1]{\if@proof\NoteMark{\ref{#1}}\relax\fi}
757 \newcommand\NoteLabel{\protect\label}
758 \newcommand\OutputNotes{%
759   \bgroup
760   \onecolumn
761   \section*{EDITORIAL NOTES}
762   \begin{enumerate}
763     \NotesList
764   \end{enumerate}
765   \egroup
766 }
767 \DeclareRobustCommand\cs[1]{\texttt{\char``\#1}}
768
```

2.9 Bibliographic Records for ADS

`\ADS@BibCode` We use the `\ADS@BibCode` command to hold the bibliographic code for ADS. It is used in the `%R` field of the bibliographic record for each article. The format is

`\ADS@year`
`\ADS@journal`
`\ADS@volume`

`\ADS@firstpage`

`\ADS@authorinitial`

YYYYJJJJJVVMPPPPA

where YYYY is the year, JJJJJ is the journal code, which is RMxAA or RMxAC, VVVV is the volume number (right-justified), M is not used by us, PPPP is the first page number (right-justified), and A is the initial of the first author's surname. The volume and page fields are padded with periods ('.'), which causes us some fun (this is done with the macro \PadToFourWithDots described below) .

All these individual bits are held in the commands \ADS@year, \ADS@journal, \ADS@volume, \ADS@firstpage, \ADS@authorinitial.

```
769 \newcommand{\SetADSBibCode}[1]{\renewcommand{\ADS@BibCode}{#1}}
770 \newcommand{\ADS@BibCode}
771 {\ADS@year\ADS@journal\ADS@volume.\PadToFourWithDots{\ADS@firstpage}\ADS@authorinitial}
772 \newcommand{\ADS@year}{2001}
773 \newcommand{\ADS@journal}{\if@proceedings RMxAC\else RMxAA\fi}
774 \newcommand{\ADS@volume}{....}
```

These two are just set to default values here, \ADS@firstpage is set in the document environment for included articles, in the frontsection environment, \tableofcontents command, index and abstracts environments. Also by \AtBeginDocument for stand-alone articles.

God knows how we are going to do \ADS@authorinitial!

```
775 \newcommand{\ADS@firstpage}{....}
776 \newcommand{\ADS@authorinitial}{A}
```

We also have a whole slew of other fields that can be set. These are all listed in Table 1. Most of them still have to be defined. A lot of these macros are set by other commands, as mentioned in the Table, but some need to be set explicitly here.

\ADS@doi	<p>The user/editor command \DOI is used to set this.</p> <pre>777 \newcommand{\ADS@doi}{https://doi.org/10.22201/ia.01851101p.0000.00.00.00}</pre>
\ADS@journalname	<p>This does not contain any accents at the moment so as not to cause problems—this maybe should be changed though.</p> <pre>778 \newcommand{\ADS@journalname}{% 779 \if@proceedings\@conftitle\space (Eds. \@editors) \fi% 780 Revista Mexicana de Astronom\'\i{}a y Astrof\'\i{}sica% 781 \if@proceedings\space (Serie de Conferencias)\fi% 782 \space Vol. \@volume, pp. \ADS@firstpage--\ADS@lastpage\space (\@year)% 783 \space (http://www.astroscu.unam.mx/\~{\rmaa/}) 784 }</pre>
\ADS@keywords	<p>\ADS@abstract is straightforward, since we already have the text saved as \@abstract. We could do the same with \ADS@keywords but to avoid unwanted formatting we explicitly set it in \keywords (p. 15). \ADS@title is just set to \@rawtitle, which we were already using for another purpose.</p> <pre>785 \let\ADS@title=\@rawtitle 786 \newcommand{\ADS@keywords}{No keywords specified} 787 \newcommand{\ADS@abstract}{No abstract specified}</pre>
\ADS@abstract	
\ADS@title	

Table 1: ADS Bibliographic Records

Code	Description	Macro Name	Comment
%R	Bibliographic Code	\ADS@BibCode	required
%A	Author list	\ADS@authors	required, generate from \indexauthor
%F	Author affiliation	\ADS@affil	format: AA(...) AB(...) ...
%J	Journal Name	\ADS@journalname	
%D	Publication Date	\ADS@fulldate	
%L	Last Page	\ADS@lastpage	generate from label
%T	Title	\ADS@title	required, generate from \title
%C	Abstract Copyright	\ADS@copyright	set to IA-UNAM
%U	URL for electronic document	\ADS@url	set to PDF file
%d	DOI for article	\ADS@doi	set by \DOI
%K	Keywords	\ADS@keywords	set equal to \@keywords
%A	Abstract Text	\ADS@abstract	set equal to \@abstract
%R	References	\ADS@references	generate from the bibliography

\ADS@authors \ADS@authors wants to be in “Other, A. N.” format, but with semi-colons between authors. The most natural way to do this seems to be with \indexauthor (p. 18). We append each author to this macro, which means we must explicitly clear it for each new article (done in \article). .

```
788 \newcommand{\ADS@authors}{}{}
```

\ADS@fulldate \ADS@lastpage \ADS@copyright \ADS@website \ADS@url \SetWebsite \SetMonthNumeric

Other sundry data, together with user commands for bits that can be set by the Editors. The \ADS@url is constructed from the website (currently <http://www.astrosmo.unam.mx/rmaa/>), the journal descriptor (e.g., RMxAC..10/), followed by the path to the PDF file (e.g., PDF/RMxAC..10_HEW1.pdf).

```
789 \newcommand{\ADS@website}{http://www.astrosmo.unam.mx/rmaa/}
790 \newcommand{\ADS@url}{}
791 {\ADS@website\ADS@journal\ADS@volume\ADS@number/PDF/\ADS@journal\ADS@volume\ADS@number\_article}
792 \newcommand{\ADS@number}{}{ }
793 \newcommand{\ADS@fulldate}{00/\ADS@year}
794 \newcommand{\ADS@lastpage}{00}
795 \newcommand{\ADS@copyright}{(C) \ADS@year; Instituto de Astronom\i{a},
796 Universidad Nacional Aut\onoma de M\exico}
797 \newcommand{\SetNumber}[1]{\renewcommand{\ADS@number}{-#1}}
```



```

798 \newcommand{\SetWebsite}[1]{\renewcommand{\ADS@website}{#1}}
799 \newcommand{\SetMonthNumeric}[1]{\renewcommand{\ADS@fulldate}{#1/\ADS@year}}

\ADS@affil These two are somewhat more problematical. Affiliation currently only works
\ADS@references for the first author (see ...) pending redesign of the user interface. References are
now done by wrapping the thebibliography environment to open another
input stream on the same file and search through for the \bibitems.

800 \newcommand{\ADS@references}{}
801 \newcommand{\ADS@affil}{}

```

Define two macros that expand to the strings `\begin{thebibliography}` and `\end{thebibliography}`. Note that the idea for this and much else is inspired by the code for the `docstrip` package. Also define `\StartBibX` in case authors use the more standard `\begin{thebibliography}{} syntax`.

```

802 \edef\EndBib{\expandafter@gobble\string\end\string{thebibliography}\string}}
803 \edef\StartBib{\expandafter@gobble\string\begin\string{thebibliography}\string}}
804 \edef\StartBibX{\expandafter@gobble\string\begin\string{thebibliography}\string\string{stri

```

Define two new logical variables. `\ifAnotherline` is true if we want to read another line from the input stream. It is set to false when we encounter the `\end{thebibliography}`. `\ifInBib` is set to true when we find the `\begin{thebibliography}` and tells us to start saving the following lines.

```

805 \newif\ifAnotherLine
806 \newif\ifInBib

```

`makeOther` We need a macro to change the catcodes of lots of things to other.

```

807 \def\makeOther#1{\catcode`#1=12\relax}

```

`\RereadBiblio` Define a macro to do all the fiddly stuff. This is used at the beginning of thebibliography environment (Sec 2.16).

```

808 \newread\tf@biblio
809 \newcommand{\RereadBiblio}{%

```

Open the current file again for reading

```

810 \begingroup
811 \immediate\openin\tf@biblio=\articlename

```

Everything in a group to be safe. Initialize logicals. Black magic to change catcodes and avoid blank lines being interpreted as `\par`.

```

812 \AnotherLinetrue\InBibfalse
813 \makeOther\ \makeOther\\ \makeOther\$\%
814 \makeOther\#\makeOther\^ \makeOther\^^K%
815 \makeOther\_ \makeOther\^A \makeOther\%%
816 \makeOther\~ \makeOther\{ \makeOther\} \makeOther\&%
817 \endlinechar-1\relax

```

Start looping through the file. Read each line to the macro `\Line`. If we have got to EOF or end of biblio then set `\AnotherLinefalse`.

```

818 \loop
819 \read\tf@biblio to \Line
820 \ifx\Line\EndBib\AnotherLinefalse\InBibfalse\fi
821 \ifeof\tf@biblio \AnotherLinefalse\fi

```

If we are in the biblio and the line is not blank then append it to the \ADS@references macro together with a newline.

```
822 \ifInBib
823 \ifx\Line\empty\else\xdef\ADS@references{\ADS@references\Line^^J}\fi
824 \fi
```

Check if the line we just saw was the start of biblio, then repeat the loop if necessary.

```
825 \ifx\Line\StartBib\InBibtrue\fi
826 \ifx\Line\StartBibX\InBibtrue\fi
827 \ifAnotherLine\repeat
828 \immediate\closein\tf@biblio
829 \endgroup
830 }
```

\PadToFourWithDots Utility function for left-padding a number to 4 characters with periods. Used in constructing \ADS@BibCode. This is a very simple algorithm and *requires* that the argument actually be a number—if it is not then dire consequences will result.

```
831 \newcommand{\PadToFourWithDots}[1]{%
832 \ifnum #1 > 999 #1%
833 \else\ifnum #1 > 99 .#1%
834 \else\ifnum #1 > 9 ..#1%
835 \else ...#1%
836 \fi\fi\fi}
837 %% \ifnum \count0 > 999 #1%
838 %% \else\ifnum \count0 > 99 .#1%
839 %% \else\ifnum \count0 > 9 ..#1%
840 %% \else ...#1%
841 %% \fi\fi\fi}
```

\AuthorADS New mechanism for setting the affiliations for ADS. The author labels (AA, AB, ...) are generated using two nested counters. We use the \robustify command from etoolbox so that accented characters in the affiliation addresses do not blow up. The list of accents may need to be expanded.

\ADS@affiliations

```
842 \newcounter{AUTHOR}
843 \newcounter{author}[AUTHOR]
844 \stepcounter{AUTHOR}
845 \newcommand\ADS@affiliations{}
846 \robustify{'}\robustify{\i}\robustify{\~}\robustify{\'}
847 \def\AuthorADS#1#2{%
848 \begingroup
849 \def\ORCIDiD##1{<ID system="ORCID">##1</ID>}
850 \def\Email##1{<EMAIL>##1</EMAIL>}
851 \def\Affil##1{##1}
852 \stepcounter{author}
853 \ifthenelse{\value{author} > 26}{\stepcounter{AUTHOR}\stepcounter{author}}{}
854 \ifthenelse{\equal{\ADS@affiliations}{\@rmaempty}}{%
855 \xdef\ADS@affiliations{\Alph{AUTHOR}\Alph{author} (#2) }
856 }{%
857 \xdef\ADS@affiliations{\ADS@affiliations, \Alph{AUTHOR}\Alph{author} (#2) }
858 }%
859 \endgroup
860 }
```

```

\ADS@dumppdata is the macro that actually does the job of writing out all the data
\ADS@write to an auxiliary file, using \ADS@write to write each field. The file is set up with
\ADS@openfile \ADS@openfile, which currently is done in the TOC of a book. The new multi-
author affiliations are used if \ADS@affiliations has been set, otherwise it
falls back to the single-author version \ADS@affil.

861 \newcommand{\ADSsfield}[2]{\relax}
862 \newcommand{\ADSvfield}[2]{\relax}
863 %%\renewcommand{\ADSsfield}[12]{\%#1 #2}
864 \newcommand{\ADS@dumppdata}
865 {
866   \ADS@write{\string\begin{ADSarticle}}
867   \ADS@WRITE{\string\ADSsfield{R}{\ADS@BibCode}}
868   \ADS@write{\string\ADSsfield{A}{\ADS@authors}}
869   \ifthenelse{\equal{\ADS@affiliations}{\@rmaaEmpty}}{\%
870     {\ADS@sanitize\ADS@write{\string\ADSsfield{F}{AA(\ADS@affil)}}}
871   }{\%
872     {\ADS@sanitize\ADS@write{\string\ADSsfield{F}{\ADS@affiliations}}}}
873 }
874 \ADS@write{\string\ADSsfield{J}{\ADS@journalname}}
875 \ADS@write{\string\ADSsfield{D}{\ADS@fulldate}}
876 \ADS@write{\string\ADSsfield{L}{\ADS@lastpage}}
877 {\ADS@sanitize\ADS@write{\string\ADSsfield{T}{\ADS@title}}}
878 \ADS@write{\string\ADSsfield{C}{\ADS@copyright}}
879 \ADS@write{\string\ADSsfield{d}{\ADS@doi}}
880 \ADS@write{\string\ADSsfield{U}{\ADS@url}}
881 \ADS@write{\string\ADSsfield{K}{\ADS@keywords}}
882 {\ADS@sanitize\ADS@write{\string\ADSsfield{B}{\ADS@abstract}}}
883 \ADS@write{\string\ADSsfield{Z}{\ADS@references}}
884 \ADS@write{\string\end{ADSarticle}}
885 }
886 %%\newcommand{\ADS@write}[1]{\if@book\addtocontents{ads}{#1}\fi}
887 %%\newcommand{\ADS@openfile}{\@starttoc{ads}}
888 \newcommand{\ADS@write}[1]{\set@display@protect\immediate\write\tf@ads{#1}}
889 \newcommand{\ADS@WRITE}[1]{\immediate\write\tf@ads{#1}}
890 \newcommand{\ADS@openfile}{\%
891   \newwrite\tf@ads%
892   \immediate\openout\tf@ads\jobname.ads\relax
893   \ADS@WRITE{\ADS@preamble}}
894 \newcommand{\ADS@closefile}{\ADS@WRITE{\ADS@postamble}}
895 \def\ADS@preamble{%
896   %% \string\documentclass{article}
897   %% \string\begin{document}
898 }
899 \def\ADS@postamble{%
900   %% \string\end{document}
901   \string%\string% Local Variables:~J
902   \string%\string% mode: LaTeX~J
903   \string%\string% mode: Font-lock~J
904   \string%\string% End:~J
905 }

```

Cunning trick to get the page numbers from \pageref. Put a label on the first and last page of the document using \AtBeginDocument and \AtEndDocument. This way won't work for the book option. In that case, we do it by defining \@endofarticlehook and \@begofarticlehook as parallels to \AtEndDocument and \AtBeginDocument. Note that we have to defer adding \@begofarticlehook to \AtBeginDocument to make sure it comes after the redefinitions of \ref and \label.

```
906 \if@book\AtEndDocument{\ADS@closefile}\else
907 %\AtBeginDocument{\@begofarticlehook}
908 \AtEndDocument{\@endofarticlehook}
909 \fi
```

\@begofarticlehook

Since we are getting more and more things that need to be done at the beginning of every article, frontsection, etc we define a sister hook to \@endofarticlehook. This hook does the following:

1. Labels the first page
2. Sets \ADS@firstpage
3. runs and then clears \indexauthor@deferlist
4. resets the keyword counter

It is executed in the following circumstances:

1. At \begin{document} for standalone files
2. At \begin{document} for each included file
3. At beginning of front sections
4. At beginning of TOC
5. At beginning of Author Index
6. At beginning of abstracts

For some reason, this is not always within the right group, so we use \xdef just to be sure.

```
910 \newcommand{\@begofarticlehook}{%
911   \if@frontmatter\frontlabel{RMAAFirstPage}\else\label{RMAAFirstPage}\fi%
912   \xdef\ADS@firstpage{\@arabic{\c@page}}%
913   \if@book\else\makeindex\fi % needed so default index is defined in stand-alone articles
914 %%   \indexauthor@deferlist
915 %%   \xdef\indexauthor@deferlist{}
916   \inpreamblefalse
917   \setcounter{kwdcounter}{0}
918 }
```

`\@endofarticlehook` This is a hook to be run at the end of each article currently, it just labels the last page and writes out all the ADS data to an auxiliary file. It should not produce any printed output. It is modelled on the `\AtEndDocument` command, to which it reduces in the case of a single article.

```
919 \newcommand{\@endofarticlehook}{%
920   \if@debug{\ClassWarning{rmaa}{***Doing Hook***}}\fi
921   \if@debug{\ClassWarning{rmaa}{ADSabstract is: \ADS@abstract}}\fi
922   \clearpage\rmaa@lastpagelabel\if@book\ADS@dumpdata\fi
923   \ifx\NotesList\@rmaaEmpty\else\OutputNotes\fi
924   \if@debug{\ClassWarning{rmaa}{Notes list is: \NotesList}}\fi
925 }
```

`\rmaa@lastpagelabel` New version of last page label command copied from Jeff Goldberg's `lastpage.sty` package - we can't just use `\label` here in case the output routine for the last page has already been called. Instead, we first explicitly clear the page, step back the page counter, explicitly write to the .aux file, then restep the page counter again.

But this will conflict with the `hyperref` package, which does labels differently. Compensate for that by using the five-argument form.

Also set the `\ADS@LastPage` macro to the appropriate number.

```
926 \newcommand{\rmaa@lastpagelabel}{%
927   \addtocounter{page}{-1}%
928   \immediate\write\@auxout{\string
929     \newlabel{\articlename:RMAALastPage}{{}{\thepage}}{{}}}%
930   \edef\ADS@lastpage{\thepage}%
931   \addtocounter{page}{1}}
```

2.11 Deal with explicit change in number of columns

Sometimes, when formatting a book, we need to switch between one-column articles and two-column articles. For this to work, we need to wrap the standard \LaTeX commands to set the `\@rmtwocol` flag appropriately and also reset the package default values of all scalable lengths. .

```
932 \let\latexonecolumn=\onecolumn
933 \let\latextwocolumn=\twocolumn
934 \renewcommand{\onecolumn}{\@rmtwocolfalse\@package@default@lengths\latexonecolumn}
935 \renewcommand{\twocolumn}{\@rmtwocoltrue\@package@default@lengths\latextwocolumn}
```

2.12 The actual formatting of the title

Note, we have to redefine the `\maketitle` command to use the numbered footnotes. This means we needn't use the `atbeginend` stuff.

```
936 \renewcommand{\maketitle}{\par
937   \beginingroup
```

Don't switch to marked footnotes. This is consistent with existing style but I'm not sure I like it

```
938   %% \renewcommand\thefootnote{\fnsymbol{footnote}}%
939   %% \def\@makefnmark{\hbox to\z@{${\m@th^{\@thefnmark}}$}\hss}}%
940   \def\@makefnmark{\textsuperscript{\@thefnmark}\hspace{-0.2em}}%
```

```

941 \long\def\@makefntext##1{\parindent 1em\noindent
942   \hbox to 1.8em{\hss$\m@th^{\@thefnmark}$}##1}%
943 \if@rmtwocol
944 { \if@debug{\ClassWarning{rmaa}{TWO COLUMN}}\fi
945   \twocolumn[\@maketitle]%
946 }
947 \else
948 { \if@debug{\ClassWarning{rmaa}{ONE COLUMN}}\fi
949   \newpage
950   \global\@topnum\z@    % Prevents figures from going at top of page.
951   \if@manuscript \@MSmaketitle \else \@maketitle \fi
952 }
953 \fi
954 \if@manuscript\else\thispagestyle{rmaafirstpage}\@thanks\fi
955 \ifx\NotesList\@rmaaEmpty\else{%
956   \NoteMark{1--\arabic{notecounter}}\vspace*{-2\baselineskip}%
957 }\fi%
958 \endgroup

```

Don't reset footnote counter (not sure whether this is good thing or not).

```

959 %% \setcounter{footnote}{0}%
960 \let\thanks\relax\let\affil\relax\let\altaffil\relax
961 \let\maketitle\relax\let\@maketitle\relax
962 \gdef\@thanks{}\gdef\@author{}\gdef\@title{}

```

\@kwhwidth Redefine \@maketitle to include the abstract, resumen and keywords. Note
\@kwtwidth that in the manuscripty style we use \@MSmaketitle instead.

```

963 \newlength{\@kwhwidth}\newlength{\@kwtwidth}
964 \newcommand\reviewname{Review}
965 \renewcommand{\@maketitle}{%
966   \newpage
967   \null
968   \if@reviewarticle
969     \smallskip
970     {\large\bfseries\itshape\reviewname}%
971     \bigskip
972   \else
973     \vskip\@before@title@skip%
974   \fi
975   \begin{center}%
976     {\@title \par}%
977     \vskip\@before@author@skip%
978     \parbox{\rmaa@AuthorWidthFrac\textwidth}{\centering
979       \lineskip\@between@author@skip%
980       \@author
981       \par}
982     %% this should be replaced with 'Submitted to...' for preprints
983     \if@printdates
984       \vskip\@before@dates@skip%
985       \if@preprint
986         \rmaa@ReceivedStyle{Submitted to RMxAA \@received}
987       \else
988         \rmaa@ReceivedStyle{Received \@received; accepted \@accepted}
989       \fi
990     \fi
991     \if@manuscript
992       \rmaa@ReceivedStyle{Submitted to RMxAA \@received}

```

```

993 \fi
994 \if@guide
995 \rmaa@ReceivedStyle{Version \rmaa@version, \rmaa@date}
996 \fi
997 \vskip\@before@abstract@skip%
998 \if@abstractpresent
999 \parbox{\rmaa@AbstractWidthFrac\textwidth}{%
1000 \setlength{\parindent}{0.9cm}%
1001 \centerline{\rmaa@AbstractHeaderStyle{Abstract}}\par%
1002 \vskip\@after@abstracthead@skip%
1003 \if@newstyle\noindent\fi\@abstract
1004 \vskip\@between@abstract@skip%
1005 \centerline{\rmaa@AbstractHeaderStyle{Resumen}}\par%
1006 \vskip\@after@abstracthead@skip%
1007 \if@newstyle\noindent\fi\@resumen
1008 \if@setresumen\else\@abstract\fi % append english abstract if
1009 % spanish one not set
1010 \if@guide\else %do not use keywords for guide
1011 \vskip\@before@kwd@skip%
1012 % Format the Key Words with hanging indentation:
1013 % They are put in a \parbox with width equal to the line width
1014 % minus the width of the header.
1015 { % Widths of keyword
1016 \settowidth{\@kwhwidth}{\@keywordheader~} % header and
1017 \setlength{\@kwtwidth}{\linewidth} % keyword text
1018 \addtolength{\@kwtwidth}{-\@kwhwidth} %
1019 \noindent\@keywordheader~\parbox[t]{\@kwtwidth}{%
1020 \rmaa@KeywordStyle{\boldmath\uppercase{\@keywords}}}%
1021 \fi
1022 }
1023 \fi
1024 \end{center}%
1025 \vspace*{\@afterkwdskip}
1026 \par
1027 }
1028 \newlength{\@afterkwdskip}\setlength{\@afterkwdskip}{\z@}

\reviewarticle User command to specify a review article. Must be used in preamble. Main effect
\reviewtoc is to place the text "Review" before the article title. Also add command for setting
\reviewlof a table of contents and a list of figures at the beginning of the article.
1029 \newcommand{\reviewarticle}{\@reviewarticletrue}
1030 \newcommand\reviewtoc{%
1031 \section*{CONTENTS}%
1032 \@starttoc{rtc}%
1033 }
1034 \newcommand\reviewlof{%
1035 \section*{LIST OF FIGURES}%
1036 \@starttoc{lof}%
1037 }

\l@section
1038 \renewcommand*\l@section[2]{%
1039 \ifnum \c@tocdepth >\z@
1040 \addpenalty\@secpenalty
1041 \addvspace{0.8em \@plus\p@}%
1042 \setlength{\tempdima}{1.5em}%

```

```

1043 \beginngroup
1044 \parindent \z@ \rightskip \@pnumwidth
1045 \parfillskip -\@pnumwidth
1046 \leavevmode %\bfseries
1047 \advance\leftskip\@tempdima
1048 \hskip -\leftskip
1049 #1\nobreak\hfil \nobreak\hb@xt@\@pnumwidth{\hss #2}\par
1050 \endgroup
1051 \fi}

```

`\@MSmaketitle` A special version of `\@maketitle` for the manuscript option. This can deal with a multi-page abstract/resumen. Not very well, mind.

```

1052 \newcommand{\@MSmaketitle}{%
1053 \if@debug\ClassInfo{rmaa}{Using special MS maketitle command}\fi
1054 \newpage
1055 {
1056 \thispagestyle{rmaafirstpage}
1057 % \setlength{\parindent}{0pt}
1058 \null\vskip 2ex
1059 \begin{center}
1060 \@title\par
1061 \@author\par
1062 \rmaa@ReceivedStyle{%
1063 \ifx\@received\@rmaaEmpty
1064 Draft version: \@date
1065 \else
1066 Received: \@received
1067 \ifx\@accepted\@rmaaEmpty
1068 \else
1069 ; Accepted: \@accepted
1070 \fi
1071 \fi}\par
1072 \end{center}
1073 \@thanks
1074 \centerline{\rmaa@AbstractHeaderStyle{Resumen}}
1075 \noindent\@resumen\par\vskip 2ex
1076 \centerline{\rmaa@AbstractHeaderStyle{Abstract}}
1077 \noindent\@abstract\par\vskip 2ex
1078 \noindent\@keywordheader~\rmaa@KeywordStyle{\@keywords}\par
1079 % \@keywordheader~\rmaa@KeywordStyle{\uppercase{\@keywords}}\par
1080 }%
1081 }

```

2.13 The sectioning commands

```

\section Redefine all the standard commands to use these lengths.
\subsection 1082 \renewcommand\section{\@startsection {section}{1}{\z@}%
\subsubsection 1083 {\abovesectionskip}%
\subsubsection 1084 {\belowsectionskip}%
\paragraph 1085 %% how do we get upper case here
\subparagraph 1086 {\centering\reset@font\normalsize}}
1087 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
1088 {\abovesectionskip}%
1089 {\belowsectionskip}%
1090 {\centering\reset@font\normalsize\itshape}}

```



```

1091 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
1092         {\abovesectionskip}%
1093         {\belowsectionsip}%
1094         {\centering\reset@font\normalsize\itshape}}
1095 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
1096         {\aboveparaskip}%
1097         {\belowparaskip}%
1098         {\reset@font\normalsize\bfseries}}
1099 \renewcommand\subparagraph{\@startsection{subparagraph}{5}{\parindent}%
1100         {\aboveparaskip}%
1101         {\belowparaskip}%
1102         {\reset@font\normalsize\bfseries}}

```

secnumdepth Make sure that we number the subsubsections—this is done by default in the article class but not the book class, which is why we must set it explicitly here.

```
1103 \setcounter{secnumdepth}{3}
```

\thesubsection For subsection and subsubsection, we want the numbers to be roman but the title to be italic. This seems the easiest way to go about it.

```

1104 \renewcommand{\thesubsection}{\upshape\thesection.\@arabic\c@section}}
1105 \renewcommand{\thesubsubsection}{\thesubsection\upshape.\@arabic\c@subsubsection}}

```

\@secntformat Add “.” to the number here so we can remove it from \thesection, etc. Reduce gap between number and title WJH 27 Jan 1995

```
1106 \def\@secntformat#1{\csname the#1\endcsname .\hskip 0.4em}
```

\@sect I didn’t really want to mess with the \@sect command, but it was the only way I could manage to force upper case. Other than the commented parts, it is identical to the standard version.

```

1107 \def\@sect#1#2#3#4#5#6[#7]#8{
1108   \ifnum #2>\c@secnumdepth
1109     \let\@svsec\@empty
1110   \else
1111     \refstepcounter{#1}%
1112     \let\@protect\protect
1113     \def\protect{\noexpand\protect\noexpand}%
1114     \edef\@svsec{\@secntformat{#1}}%
1115     \let\protect\@protect
1116   \fi

```

This is the bit I changed (27 Jan 1995). Use upper case for \section, use mixed case for the rest.

```

1117   \ifnum #2=1
1118     \def\sec@upcase##1{\uppercase{##1}}%
1119     \def\sec@shape{\upshape}%
1120   \else
1121     \def\sec@upcase##1{\relax{##1}}%
1122     \def\sec@shape{\itshape}%
1123   \fi
1124   \@tempskipa #5\relax
1125   \ifdim \@tempskipa>\z@
1126     \begingroup #6\relax

```

```

1127         \@hangfrom{\hskip #3\relax\@svsec}%
1128         {\interlinepenalty \@M \sec@upcase{#8}\par}%
1129     \endgroup
1130     \csname #1mark\endcsname{#7}%

```

Only write TOC entries if doing the Guide style.

```

1131     \if@guide
1132         \addcontentsline{toc}{#1}{%
1133             \ifnum #2>\c@secnumdepth \else
1134                 \protect\numberline{\csname the#1\endcsname}%
1135             \fi
1136             #7}%
1137     \fi

```

Also allow per-article TOC for review papers

```

1138     \if@reviewarticle
1139         \ifnum #2>2 \else
1140             \addcontentsline{rtc}{#1}{%
1141                 \protect\numberline{\csname the#1\endcsname}%
1142                 \sec@upcase{\sec@shape #7}}%
1143         \fi
1144     \fi
1145 \else
1146     \def\@svsechd{#6\hskip #3\relax %% \relax added 2 May 90
1147         \@svsec #8\csname #1mark\endcsname{#7}%
1148         \if@guide
1149             \addcontentsline{toc}{#1}{%
1150                 \ifnum #2>\c@secnumdepth \else
1151                     \protect\numberline{\csname the#1\endcsname}%
1152                 \fi
1153                 #7}%
1154             \fi
1155         }%
1156     \fi
1157     \@xsect{#5}

```

2.14 Appendices

Make sure that appendices in individual articles work properly. We copy the definition from the article class (the book one doesn't do what we want).

`appendices` This uses an environment `appendices` inside of which each `\section` will become a separate appendix. Note that the appendices must come before the references (otherwise the full addresses mechanism will not work properly). We make the equation numbering be subordinate to the appendix (equations A12, B6, etc). Finally, we have a `medskip` followed by `APPENDICES` to introduce them.

```

1158 \newenvironment{appendices}{\par
1159     \begingroup
1160     \setcounter{section}{0}%
1161     \setcounter{subsection}{0}%
1162     \renewcommand\thesection{\@Alph\c@section}
1163     \renewcommand\theequation{\thesection\arabic{equation}}
1164     \medskip
1165     \section*{APPENDICES}}
1166 {\endgroup}

```

appendix If there is only one appendix, then use appendix environment instead.

```

1167 \renewenvironment{appendix}{\par
1168   \begin{group}
1169   \setcounter{section}{0}%
1170   \setcounter{subsection}{0}%
1171   \renewcommand\thesection{\@Alph\c@section}
1172   \renewcommand\theequation{\thesection\arabic{equation}}
1173   \medskip
1174   \section*{APPENDIX}
1175 }{\endgroup}

```

2.15 Floating thingies

```

1176 \renewcommand{\thetable}{\@arabic\c@table}
1177 \renewcommand{\thefigure}{\@arabic\c@figure}
1178 \renewcommand{\figurename}{Fig.}
1179 \renewcommand{\tablename}{TABLE}
1180 %\renewcommand{\fnum@table}{\MakeUpperCase{\tablename}~\thetable}

```

For some reason, I have to write ‘TABLE’ explicitly here. If I use \tablename, it gets converted to mixed case—God knows why. \figurename is also being ignored.

```

1181 \renewcommand{\fnum@table}{TABLE~\thetable}
1182 \renewcommand{\fnum@figure}{Fig.~\thefigure}

```

Do captions in 9 pt face in the main journal style and in new-style anything.

```

1183 \long\def\@makefigcap#1#2{%
1184   \if@proceedings\else\small\fi
1185   \if@newstyle\small\fi
1186   \vskip\abovecaptionskip
1187   \sbox\@tempboxa{#1. #2}%
1188   \ifdim \wd\@tempboxa >\hsize
1189     #1. #2 \par
1190   \else
1191     \global \@minipagefalse
1192     \hb@xt@\hsize{\hfil\box\@tempboxa\hfil}%
1193   \fi
1194   \vskip\belowcaptionskip}

```

Make sure table caption is upper case.

```

1195 \long\def\@maketabcap#1#2{%
1196   \hbox to\hsize{\hfil #1 \hfil}
1197   \vskip 6pt
1198   \centering\MakeUpperCase{#2}\par
1199   \vskip 6pt}
1200 \newlength{\@roottabcapwidth}
1201 \long\def\@makerottabcap#1#2{%
1202   \setbox\@tempboxa\hbox{\MakeUpperCase{#2}}%
1203   \ifdim\wd\@tempboxa >.8\vsiz
1204     \setlength{\@roottabcapwidth}{.8\vsiz}
1205   \else
1206     \setlength{\@roottabcapwidth}{\wd\@tempboxa}
1207   \fi
1208   \rotatebox{90}{%
1209     \begin{minipage}{\vsiz}\centering
1210     \begin{minipage}{\@roottabcapwidth}\centering
1211       #1\ \vskip 6pt \MakeUpperCase{#2}

```

```

1212     \end{minipage}%
1213 \end{minipage}
1214 }%
1215 \hskip 6pt
1216 }
1217
1218 \newenvironment{Sideways}
1219   {\begin{sideways}\begin{minipage}{\vsize}\centering}
1220   {\end{minipage}\end{sideways}}
1221
1222 \newenvironment{Sidewaystable}
1223 {%
1224   \let\oldcaption=\caption%
1225   \def\caption{
1226     \def\@c@type{table}\renewcommand{\@makecaption}{\@maketabcap}
1227     \oldcaption
1228   \begin{sidewaystable}\centering}
1229   {\end{sidewaystable}\let\caption=\oldcaption}
1230 \newenvironment{Sidewaystable*}
1231 {%
1232   \let\oldcaption=\caption%
1233   \def\caption{
1234     \def\@c@type{table}\renewcommand{\@makecaption}{\@maketabcap}
1235     \oldcaption
1236   \begin{sidewaystable*}\centering}
1237   {\end{sidewaystable*}\let\caption=\oldcaption}

```

Not sure why we need to stick these lines in.

```

1238 \renewenvironment{figure}
1239   {\renewcommand{\@makecaption}{\@makefigcap}\@float{figure}}
1240   {\end@float}
1241 \renewenvironment{figure*}
1242   {\renewcommand{\@makecaption}{\@makefigcap}\@dblfloat{figure}}
1243   {\end@dblfloat}
1244 \renewenvironment{table}
1245   {\renewcommand{\@makecaption}{\@maketabcap}\@float{table}}
1246   {\end@float}
1247 \renewenvironment{table*}
1248   {\renewcommand{\@makecaption}{\@maketabcap}\@dblfloat{table}}
1249   {\end@dblfloat}

```

Redefine \@caption so that we don't bother with the list of figures. This saves us having to worry about fragile commands in the captions.

```

1250 \long\def\@caption#1[#2]#3{%
1251   \par
1252   %% \addcontentsline{\csname ext@#1\endcsname}{#1}%
1253   %% {\protect\numberline{\csname the#1\endcsname}{\ignorespaces #2}}%
1254   \begingroup
1255     \@parboxrestore
1256     \if@minipage
1257       \setminipage
1258     \fi
1259     \normalsize
1260     \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par
1261   \endgroup}

```

Make tables not quite so cramped. Allow \hline\hline to give a poor man's thick rule.

```

1262 \renewcommand{\arraystretch}{1.15}
1263 \setlength{\doublerulesep}{0.4pt}

\tablecols \tablecols is a user command for setting the number of columns. It is used by
\@tablecols commands that try and span the entire table (I think there must be a better way
\captioncontinued of achieving this). \captioncontinued is a user command for setting the
caption of a continued table on the next page.

1264 \newcommand{\tablecols}[1]{\renewcommand{\@tablecols}{#1}}
1265 \newcommand{\@tablecols}{1}
1266 \newcommand{\captioncontinued}{%
1267 \multicolumn{\@tablecols}{c}{\addtocounter{table}{-1}TABLE~\thetable\ (CONTINUED)} \\\ \\\
1268 }

```

2.15.1 Footnotes in tables

```

\tablenotemark Old user commands \tablenotemark{MARK}, \tablenote{MARK}{TEXT}—
\tablenote now deprecated.

\tablenoteskip 1269 \newcommand\tablenotemark[1]{\mathrm{#1}$}
1270 \newcommand\tablenote[2]{\if@proceedings\else\small\fi $\mathrm{#1}$ #2}
1271 \newcommand\tablenoteskip{\[0.5\baselineskip]}

\tabnotemark Alternative way of doing footnotes in tables.
\tabnotetext 1272 \newcommand{\tabnotemark}[1]{\textsuperscript{\lowercase{#1}}}
\tabnotetextTWO 1273 %\newcommand{\tabnotetextTWO}[4]{\tabnotetext{#1}{#2}\tabnotetext{#3}{#4}}
1274 \newcommand{\tabnotetextTWO}[4]{%
1275 \multicolumn{\@tablecols}{l}{%
1276 \parbox{0.5\tabnotewidth}{\small\textsuperscript{#1}#2}%
1277 \parbox{0.5\tabnotewidth}{\small\textsuperscript{#3}#4}%
1278 }%
1279 \\\}
1280 \newcommand{\tabnotetext}[2]{%
1281 \multicolumn{\@tablecols}{@{}p{\tabnotewidth}@{}{\small\textsuperscript{#1}#2}\\\}
1282 \newlength{\tabnotewidth}

changemargin
1283 % Command to allow margins to be changed on the fly. Useful to allow
1284 % tables and Figures to protrude into the margins.
1285 %
1286 % \changes{3.24}{2007/09/14}{Added \texttt{changemargin} environment
1287 % (copied from TeX FAQ).}
1288 \newenvironment{changemargin}[2]{%
1289 % From TeX FAQ http://www.tex.ac.uk/cgi-bin/texfaq2html?label=chngmargonfly
1290 \begin{list}{}{%
1291 \setlength{\topsep}{0pt}%
1292 \setlength{\leftmargin}{#1}%
1293 \setlength{\rightmargin}{#2}%
1294 \setlength{\listparindent}{\parindent}%
1295 \setlength{\itemindent}{\parindent}%
1296 \setlength{\parsep}{\parskip}%
1297 }%
1298 \item[]{\end{list}}

```

2.16 The bibliography and references

`\beforebibliostkip` I'm not entirely sure why I introduced these two commands, since directly putting `\vspace` before and after `\begin{thebibliography}` seems to work well enough.

```
1299 \newlength{\beforebibliostkip}
1300 \setlength{\beforebibliostkip}{0pt}
1301 \newlength{\afterbibliostkip}
1302 \setlength{\afterbibliostkip}{0pt}
```

`thebibliography` The environment itself is done as starred section with extra vertical space after heading. This space is currently zero. In the book style we do the cunning trick with rereading the file in order to get the references into the `\ADS@references` macro.

```
1303 \renewenvironment{thebibliography}{%
1304   \if@book\RereadBiblio\fi
1305   %% \vspace*{\beforebibliostkip}
1306   \section*{REFERENCES} \frenchspacing
1307   %% \vspace*{\afterbibliostkip}
1308   \small
```

The references themselves are set as a list in order to get the hanging indentation. They are done in a smaller font and with french spacing so we needn't worry about the distinction between sentence-ending periods and abbreviations.

```
1309 \list{\null}{\leftmargin 1.5em\labelwidth\z@\labelsep\z@\itemindent -1.5em
1310   \itemsep\z@\parsep\z@\usecounter{enumi}}
1311 \sloppy\clubpenalty4000\widowpenalty4000
1312 \sfcode'\.=1000\relax\@biblisttrue}
1313 {\endlist\@biblistfalse\normalsize\@outputaddressesifnecessary}
```

2.17 Uniquification of cross-references

`\articlename` In order that the `\label{}` command in individual articles be guaranteed to give a unique anchor, we append the article name (held in the `\articlename` command) to each key. This requires redefinition of the following commands: `\cite`, `\nocite`, `\ref`, `\pageref`, `\label`.

`\oldcite` The original versions of these commands are saved as `\oldcite`, `\oldnocite`, etc.

`\oldref` The uniquifying of cross-references is now always done, so we don't get multiply-defined labels in the single article case

```
\oldpageref
\oldlabel 1314 \newcommand{\articlename}{anon}
1315 \AtBeginDocument{
1316   \let\oldcite=\cite
1317   \let\oldnocite=\nocite
1318   \let\oldref=\ref
1319   \let\oldpageref=\pageref
1320   \let\oldlabel=\label
1321 }
```

Uniquify all cross-references by prepending the article name. This now has to go into `\AtBeginDocument` so it is working on the new versions that `hyperref.sty`

has set up. Then we need to put the `\@begofarticlehook` afterwards, so that the first page label is using the new definitions. If `amsmath` is loaded, then we also need to patch the special label command that they use.

```

1322 \AtBeginDocument{
1323   \renewcommand{\ref}[1]{\oldref{\articlename:#1}%
1324     \if@debug{\ClassInfo{rmaa}{Reference to \articlename:#1}}\fi}
1325   \renewcommand{\pageref}[1]{\oldpageref{\articlename:#1}%
1326     \if@debug{\ClassInfo{rmaa}{Page reference to \articlename:#1}}\fi}
1327   \renewcommand{\label}[1]{\oldlabel{\articlename:#1}%
1328     \if@debug{\ClassInfo{rmaa}{Label for \articlename:#1}}\fi}%
1329   \ifdef{\label@in@display}{%
1330     \let\oldlabel@in@display=\label@in@display
1331     \renewcommand{\label@in@display}[1]{\oldlabel@in@display{\articlename:#1}%
1332       \if@debug{\ClassInfo{rmaa}{AMSTeX Label for \articlename:#1}}\fi}%
1333   }{}
1334   \@begofarticlehook
1335 }%
```

Citations are more complicated since they can contain a list of keys. These are really only here for use with the `rmaacite` package, which is utterly deprecated (02 Jan 2003) now that I have the `natbib` code working. The command `\cite` should *not* be used with `natbib`: use `\citep`, `\citete`, etc. instead.

```

1336 \renewcommand{\nocite}[1]{\@bsphack
1337   \@for\@citeb:=#1\do{%
1338     \edef\@citeb{\expandafter\@firstofone\@citeb:\articlename}%
1339     \if@files\immediate\write\@auxout{\string\citation{\@citeb}}\fi
1340     \ifundefined{b@\@citeb:\articlename}{\G@refundefinedtrue
1341       \latex@warning{Citation '\@citeb' undefined}}{}%
1342     \@esphack}
1343 \renewcommand{\cite}[1]{\oldcite{#1:\articlename}}
1344 %   \end{macrocode}
1345
1346
1347 % Horrible fiddling with the bibliography citation mechanism.
1348 % This has to be globally available in case rmaacite puts it in the
1349 % \texttt{.aux} file.
1350 %   \begin{macrocode}
1351 \def\lbibcite#1#2#3{\global\@namedef{b@#1}{#2}
1352   \global\@namedef{by@#1}{#3}}
```

`\oldbibitem` Of course, `\bibitem` needs to get the uniquification treatment as well. While we are at it, we redefine it to use consecutive integers for the key if the user leaves it blank (using the counter `rmaabib`). This allows one to put `\bibitem{}` for all your references without getting annoying messages about multiply-defined labels.

We also take the opportunity to insert the optional argument to `\bibitem` if it is missing in the form Author(DATE) so that `natbib` doesn't try to do numerical citations. `Natbib` already provides a hook `\@extra@b@citeb` to help unify the citation key, so we just plug into that. However, it puts it *after* the original key, not before as I had had it. Easiest solution is to change the way that I do it. 02 Jan 2003. Note that the `\@extra@b@citeb` does not get written to the `.aux` file in the `\citation` command but it does work.

```

1353 \if@natbib\def\@extra@b@citeb{:\articlename}\fi
```

```

1354 %%\else
1355 \let\oldbibitem\bibitem
1356 \newcommand{\@rmaabibArg}{}
1357 \newcommand{\@rmaaSpace}{ }
1358 \newcounter{rmaabib}
1359 \if@natbib
1360 \renewcommand{\bibitem}[2][ABC(2003)]{%
1361   \renewcommand{\@rmaabibArg}{#2}
1362   \ifx\@rmaabibArg\@rmaaEmpty
1363     \addtocounter{rmaabib}{1}
1364     \oldbibitem[#1]{\thermaabib:\articlename}
1365   \else\ifx\@rmaabibArg\@rmaaSpace
1366     \addtocounter{rmaabib}{1}
1367     \oldbibitem[#1]{\thermaabib:\articlename}
1368   \else
1369     \oldbibitem[#1]{#2:\articlename}
1370   \fi\fi
1371   \renewcommand{\@rmaabibArg}{}
1372 }
1373 \else
1374 \renewcommand{\bibitem}[1]{%
1375   \renewcommand{\@rmaabibArg}{#1}
1376   \ifx\@rmaabibArg\@rmaaEmpty
1377     \addtocounter{rmaabib}{1}
1378     \oldbibitem{\articlename:\thermaabib}
1379   \else\ifx\@rmaabibArg\@rmaaSpace
1380     \addtocounter{rmaabib}{1}
1381     \oldbibitem{\articlename:\thermaabib}
1382   \else
1383     \oldbibitem{\articlename:#1}
1384   \fi\fi
1385   \renewcommand{\@rmaabibArg}{}
1386 }
1387 \fi
1388 %%\fi

```

oldpcite Then, we need to repeat the above scheme, but for the rmaacite definition.

```

oldscite 1389 \newcommand{\@redefinebibitem}{%
1390   \let\oldbibitem\bibitem
1391   \let\oldcite\cite
1392   \let\oldpcite\pcite
1393   \let\oldscite\scite
1394   \def\bibitem[##1<##2>]##3{%
1395     \renewcommand{\@rmaabibArg}{##3}
1396     \ifx\@rmaabibArg\@rmaaEmpty
1397       \addtocounter{rmaabib}{1}
1398       \oldbibitem[##1<##2>]{\thermaabib:\articlename}
1399     \else\ifx\@rmaabibArg\@rmaaSpace
1400       \addtocounter{rmaabib}{1}
1401       \oldbibitem[##1<##2>]{\thermaabib:\articlename}
1402     \else
1403       \oldbibitem[##1<##2>]{##3:\articlename}
1404     % trust the author here
1405     %% \oldbibitem[##1<##2>]{##3}
1406     \fi\fi
1407   }
1408 }

```


2.18 HTML Table of Contents

`\HyperTOCEntry` These commands are used to write information to the `.htoc` file, which is used
`\HyperTOCpart` in generating a Web Page of the Table of Contents. Since they only ever appear
`\HyperTOCmeeting` preceded by `\protect` in the argument to an `\addtocontents` command, they
`\HyperTOCeditors` should never need to be expanded by the macros. However, we define them here
`\HyperTOCpreamble` just in case ...

```
1409 \newcommand{\HyperTOCEntry}[3]{\relax}
1410 \newcommand{\HyperTOCpart}[1]{\relax}
1411 \newcommand{\HyperTOCmeeting}[3]{\relax}
1412 \newcommand{\HyperTOCeditors}[1]{\relax}
1413 \newcommand{\HyperTOCpreamble}{}{\relax}
```

2.19 Formatting the poster abstracts

These can now be used without using the book option.

```
1414
1415 \newcommand{\@makeminititle}{%
1416   \newpage
1417   \null
1418   \vskip 3em%
1419   \begin{center}%
1420     {\@title \par}%
1421   \end{center}
1422   \vskip 3em%
1423 }
1424
1425 \newif\if@abstractsads
1426 \@abstractsadsfalse
1427 \newcommand\abstractsADS{\@abstractsadstrue}
1428
1429 \if@book\RequirePackage{multicol}\fi
1430 \newenvironment{abstracts}[1][Abstracts of Contributed Papers]{%
1431   %% First, make sure we start on an odd page (06 Jun 2000)
1432   \if@book\clearpage\thispagestyle{empty}\cleardoublepage\fi
1433   %%
1434   \renewcommand{\articlename}{ABSTRACTS}
1435   \title{#1}\shortauthor{Abstracts}\shorttitle{Abstracts}
1436   \listofauthors{}
1437   \if@book
1438     \addcontentsline{toc}{chapter}{\protect\@fiddleauthors{\@TOCtitle}{\rmaaTOCauthors}}%
1439     \addtocontents{htc}{\protect\HyperTOCEntry{\@rawtitle}{\@rawauthors}{\articlename}}
1440   \fi
1441   \pagestyle{rmaa} % this now seems necessary (06 Jun 2000)
1442   \thispagestyle{rmaafirstpage}
1443   %% \twocolumn[\@makeminititle]
1444   \renewcommand{\abstract}[1]{%
1445     \renewcommand\ADS@abstract{##1}%
1446     \renewcommand{\@abstract}{##1}\@writeabstract%
1447   }
1448   \renewcommand{\title}[2][ ]{%
1449     \gdef\ADS@authors{ }%
1450     \gdef\ADS@affil{ }%
1451     \gdef\ADS@references{ }%
1452     \gdef\ADS@keywords{ }%
```

```

1453 \renewcommand{\@rmaaArg}{##1}
1454 \ifx\@rmaaArg\@rmaaEmpty
1455 \renewcommand{\@TOCaftertitle}{}
1456 \else
1457 \renewcommand{\@TOCaftertitle}{ (\@rmaaArg) }
1458 \fi
1459 \renewcommand{\@title}{\rmaa@TOCTitleStyle{##2}}%
1460 \renewcommand{\@TOCtitle}{\rmaa@TOCTitleStyle{##2}\@TOCaftertitle}%
1461 \renewcommand{\rmaaIndexTitle}{\rmaa@IndexTitleStyle{##2}\@TOCaftertitle.}%
1462 \renewcommand\ADS@title{##2}%
1463 \xdef\ADS@firstpage{\@arabic{\c@page}}%
1464 }
1465 \renewcommand{\author}[1]{\let\@thanks\@empty\renewcommand\@author{##1} }
1466 \renewcommand{\footnotetext}[2][XX]{\par\noindent\textsuperscript{##1}~##2}
1467 \renewcommand{\footnoterule}{\kern-3\p@ \hrule \@width 3em \kern 2.6\p@}
1468 \if@book\@begofarticlehook\fi
1469 \if@book\begin{multicols}{2}[\@makeminititle]\else\@makeminititle\fi
1470 \begin{group}
1471 \setcounter{footnote}{0}
1472 }% and at the end of the environment....
1473 {\endgroup\if@book\end{multicols}\listofabstracts\label{RMAALastPage}\clearpage\fi}
1474 %% auxiliary commands used:
1475 %% \@writeabstract does all the actual formatting
1476 \newcommand{\@writeabstract}{%
1477 \if@book%
1478 \addcontentsline{loa}{abstract}{\protect\@fiddleauthors{\@TOCtitle}{\rmaaTOCauthors}}%
1479 \fi%
1480 \begin{center}\@title\par\@author\end{center}
1481 \@abstract
1482 \par\noindent\footnoterule\nobreak\footnotesize\@thanks
1483 \par\noindent\hrulefill\goodbreak
1484 \vskip 1cm \@plus0.5cm
1485 %% write ADS entry
1486 \if@book\if@abstractsads\ADS@dumpdata\fi\fi%
1487 \endgroup % this pair is to make each abstract a self-contained group
1488 \begin{group}
1489 \setcounter{footnote}{0}
1490 }
1491 }
1492 \if@book
1493 %% List of abstracts (stuff written to .loa file)
1494 \newcommand{\listofabstracts}{%
1495 \begin{multicols}{2}[%
1496 \vskip 1.5cm \vfill % leave at least 1.5 cm and go to bottom of page if possible
1497 \centerline{\MakeUpperCase{List of Abstracts}}
1498 \vskip 1.5cm \@plus0.5cm
1499 ][6cm] % this makes it start a new page if there is not at least 6cm of space
1500 \renewcommand{\@fiddleauthors}[2]{##1\hskip1em plus2em minus0.4em\penalty-100 ##2}
1501 \parindent\z@
1502 %% \parskip.5\p@ \@plus .7\p@\relax
1503 \parskip3\p@ \@plus 1\p@ \@minus 1\p@\relax % allow quite a lot of
1504 % leeway here to avoid breaks inside
1505 % entries
1506 \renewcommand{\@}{\relax} % temporarily turn off explicit line breaks just in case
1507 \renewcommand{\altaffilmark}[1]{\relax} % ditto with this
1508 \@starttoc{loa}
1509 \end{multicols}

```

```

1510 }
1511 \newcommand*{\l@abstract}[2]{%
1512   \par\penalty-1000
1513   #1\hskip 1em\penalty0\null\nobreak\hfill#2}
1514 \fi
1515

```

2.20 Code for typesetting an entire volume of conference proceedings

```

1516
1517 \if@book
1518 %% environment for including the individual articles
1519 \newcommand{\@fiddleauthors}[2]{\relax}
1520 \renewcommand{\theequation}{\@arabic\c@equation}
1521 \newenvironment{articles}%
1522 { \begingroup % make it a group so that author definitions do not
1523   % spill over
1524   \gdef\ADS@authors{}
1525   \pagestyle{rmaa}
1526   \renewenvironment{document}{%
1527     \@begofarticlehook
1528     \addtocounter{chapter}{1}%
1529     \addcontentsline{toc}{chapter}{%
1530       \protect\@fiddleauthors{\@TOCtitle}{\rmaaTOCauthors}}%
1531     \addtocontents{htc}{\protect\HyperTOCEntry{\@rawtitle}{\@rawauthors}{\articlename}}
1532     }{\relax}
1533   \renewcommand{\documentclass}[2][foo]{\relax}
1534   \renewcommand{\usepackage}[2][foo]{%
1535     \def\@packagename{##2}\def\@rmaacitename{rmaacite}%
1536     \ifx\@packagename\@rmaacitename
1537       \@rmcitetrue\ClassInfo{rmaa}{This paper uses rmaacite}
1538       \makeatletter\input{rmaacite.sty}\makeatother % read it in here so that all changes
1539       \else % are local to paper
1540       \if@debug\ClassWarning{rmaa}{Package \@packagename\space was requested by \articlename\space}
1541       \fi
1542       %% Don't allow individual articles to mess with the pages, volume or year
1543       \renewcommand{\SetFirstPage}[1]{\relax}
1544       \renewcommand{\SetYear}[1]{\relax}
1545       \renewcommand{\SetVolume}[1]{\relax}
1546       \renewcommand{\SetConfTitle}[1]{\relax}
1547       %% Don't allow individual articles to change these
1548       \renewcommand{\nonstopmode}{\relax}
1549       \renewcommand{\scrollmode}{\relax}
1550       \renewcommand{\outputplates}{\relax}
1551       %% XXXX need to check if using rmaacite and act accordingly
1552       %% avoid multiple declarations of the same length
1553       \let\oldnewlength=\newlength
1554       \renewcommand{\newlength}[1]{%
1555         \edef\reserved@a{\expandafter\@gobble\string ##1}%
1556         \@ifundefined{\reserved@a}{%
1557           \oldnewlength{##1}}{%
1558           \if@debug\ClassInfo{rmaa}{\reserved@a\space already defined: doing nothing}}\fi%
1559         \relax}%
1560       \renewcommand\newcommand{\providecommand}
1561     }%

```

```

1562 {\endgroup\onecolumn}
1563
1564

```

Command to be used in 'articles' environment for including an article

```

1565 \newcommand{\article}[2][]{%
1566   % optional first argument is extra text to put in brackets after title in TOC
1567   % e.g. ``Invited Talk'' or ``Poster''
1568   \renewcommand{\articlename}{#2}
1569   % reset loads of counters
1570   \setcounter{footnote}{0}
1571   \setcounter{figure}{0}
1572   \setcounter{table}{0}
1573   \setcounter{section}{0}
1574   \setcounter{equation}{0}
1575   \setcounter{rmaabib}{0}
1576   \setcounter{author}{0}
1577   \setcounter{AUTHOR}{1}
1578   \gdef\ADS@authors{%
1579     \gdef\ADS@affil{%
1580       \gdef\ADS@affiliations{%
1581         \gdef\ADS@references{%
1582           \@firstauthortrue
1583           \@firststaffiltrue
1584           \@firstaltaffiltrue
1585           \@firstkwtrue
1586           \rmcitetfalse
1587           \if@suppressfulladdresses\else\@needaddressestrue\fi
1588           \renewcommand{\@rmaaArg}{#1}
1589           \ifx\@rmaaArg\@rmaaEmpty
1590             \renewcommand{\@TOCaftertitle}{}
1591           \else
1592             \renewcommand{\@TOCaftertitle}{ (#1)}
1593           \fi

```

In the main journal articles must start on an odd page.

```

1594 \if@journal\clearpage\thispagestyle{empty}\cleardoublepage\fi
1595 %% Now input the file, then run the end-of-article hook (reinstated 28
1596 %% Sep 2001)
1597 {\input{\@articledir/\articlename.tex}\@endofarticlehook}

```

Command to separate articles into sessions. Write an entry in the TOC, makes sure we start on an odd page (added 06 Jun 2000), then do a title page if \SessionTitlePages was called.

```

1598 \newcommand{\session}[1]{
1599   %% this does nothing except write an entry in the TOC
1600   \addcontentsline{toc}{part}{\rmaa@TOCPartStyle{#1}}
1601   \addtocontents{htc}{\protect\HyperTOCpart{#1}}
1602   %% and also makes sure we start on an odd page (added 06 Jun 2000)
1603   \clearpage\thispagestyle{empty}\cleardoublepage
1604   \stepcounter{part}
1605   \if@sessiontitlepages{%
1606     \onecolumn
1607     \thispagestyle{empty}
1608     \renewcommand{\articlename}{Section\thepart TitlePage}
1609     \label{RMAAFirstPage}
1610     \make@session@title{#1}
1611     \label{RMAALastPage}

```

```

1612 \clearpage\thispagestyle{empty}\cleardoublepage
1613 }\fi
1614 }
1615 \newcommand{\make@session@title}[1]{%
1616 {%
1617 \setlength\parindent{0pt}
1618 \vspace*{\stretch{1}}
1619 \rule{\linewidth}{1mm}
1620 \begin{flushright}\Huge\bfseries\boldmath
1621 #1
1622 \end{flushright}
1623 \rule{\linewidth}{1mm}
1624 \vspace*{\stretch{2}}
1625 }
1626 }

```

Command to turn on separate title pages for each session.

```

1627 \newcommand{\SessionTitlePages}{\@sessiontitlepagestrue}
1628 \newcommand{\BoldSessionTitles}{%
1629 \renewcommand{\rmaa@TOCPartStyle}[1]{\textbf{\rmaa@TOCTitleStyle{##1}}}
1630 }
1631 \newcommand{\ArticleDir}[1]{\renewcommand{\@articledir}{#1}\graphicspath{{1/}}}
1632 \newcommand{\@articledir}{.}
1633 %\newcommand{\ps@rmaafront}{\ps@rmaa}% page style for front matter (same as ever, actually)
1634 \newcommand{\ps@rmaafront}{% page style for front matter: page # in each foot
1635 \renewcommand{\@oddfoot}{\hfil\thepage}}%
1636 \renewcommand{\@evenfoot}{\thepage\hfil}%
1637 % shorttitle in both heads
1638 \renewcommand{\@evenhead}{\hfil\@shorttitle\hfil}%
1639 \renewcommand{\@oddhead}{\@evenhead}
1640 }
1641 \newcommand{\ps@rmaafrontfirstpage}{% page style for first page of front matter
1642 % page # in each foot, on outside edge
1643 \renewcommand{\@oddfoot}{\hfil\thepage}%
1644 \renewcommand{\@evenfoot}{\thepage\hfil}%
1645 % nothing in the even heads
1646 \renewcommand{\@evenhead}{\relax}%
1647 \renewcommand{\@oddhead}{\relax}%
1648 }
1649 %% slight modification to the standard \frontmatter and \mainmatter
1650 %% commands, just to set the \pagestyle
1651 \renewcommand\frontmatter{%
1652 \latexonecolumn
1653 \cleardoublepage
1654 \@frontmattertrue
1655 \@mainmatterfalse
1656 \pagenumbering{roman}
1657 \pagestyle{rmaafront}
1658 \addtocounter{page}{2} % leave space for the title page
1659 }
1660 \renewcommand\mainmatter{%
1661 \pagestyle{empty}
1662 \if@rmtwocol\twocolumn\fi
1663 \cleardoublepage
1664 \@frontmatterfalse
1665 \@mainmattertrue
1666 \pagenumbering{arabic}
1667 \pagestyle{rmaa}

```

```

1668 }
1669 \renewcommand\backmatter{%
1670 \clearpage\pagestyle{empty}\cleardoublepage
1671 \@mainmatterfalse
1672 %% put extra space in the TOC
1673 \addtocontents{toc}{\bigskip}
1674 }

```

2.21 Front sections

`\notitle` The environment `frontsection` is for doing a section in the front matter (preface, list of participants, or whatever). It has one optional argument:
`\shortname`
`frontsection` #1 Short title (no embedded spaces) for use in making PS files. E.g., “list_of_participants”.

and two mandatory arguments:

#2 Title of section (e.g., ‘Preface’)

#3 Commands to be evaluated before processing the contents of the environment. This is mainly useful for putting in the things that would go in the preamble of a normal article (e.g., `\listofauthors`, `\indexauthor`, `\notitle`)

```

1675 \newcommand{\notitle}{\@titlevisiblefalse} \newcommand{\shortname}{}
1676 \newenvironment{frontsection}[3][\%
1677 \begin{group}
1678 \renewcommand{\shortname}{#1}
1679 \ifx\shortname\@rmaasEmpty
1680 \renewcommand{\articlename}{#2}
1681 \else
1682 \renewcommand{\articlename}{\shortname}
1683 \fi
1684 \@begofarticlehook
1685 \@titlevisibletrue % default
1686 \thispagestyle{rmaafrontfirstpage}
1687 \listofauthors{} % blank out this in case it is not specified
1688 \title{#2}\shorttitle{#2}\shortauthor{#2}
1689 #3 % evaluate the command given as second mandatory arg
1690 \addcontentsline{toc}{chapter}{\protect\@fiddleauthors{\@TOCtitle}{\rmaaTOCauthors}}%
1691 \addtocontents{htc}{\protect\HyperTOCEntry{\@rawtitle}{\@rawauthors}{\articlename}}
1692 \if@titlevisible
1693 \vspace*{1cm}\centerline{\rmaa@FrontSecStyle{\@title}}\vspace*{1cm}
1694 \fi
1695 \setlength{\parskip}{3ex}
1696 }\frontlabel{RMAALastPage}\clearpage\endgroup}

1697 %% Definition of the command \frontlabel, which rights out something like 'F4' to
1698 %% the .aux file, instead of '\textlatin{i}'. This is so it is easy to post-process
1699 %% the file for making PS files of individual sections
1700 \newcommand{\frontlabel}[1][\%
1701 \@bsphack
1702 \protected@write\@auxout{}%
1703 {\string\newlabel{\articlename:#1}{F\@arabic{\c@page}}}%
1704 \@esphack
1705 }
1706 %% User command to say X, Y, Z, \ Editors of the Proceedings

```

```

1707 \newcommand{\EditorSignature}{\vspace*{\parskip}\rightline{\@editors}%
1708 \rightline{Editors of the proceedings}}
1709 %% Fiddle with \thesection, etc. so that they don't include the chapter number
1710 %% Basically go back to the 'article' definitions of these
1711 \renewcommand{\thesection}{\@arabic\c@section}
1712 \renewcommand{\thefigure}{\@arabic\c@figure}
1713 \renewcommand{\thetable}{\@arabic\c@table}
1714
1715 \newcommand{\@oldargs}{}
1716 \newcommand{\@newargs}{}
1717 %% add TOC entry for each paper
1718 \renewcommand{\title}[1]{%
1719 \renewcommand{\@title}{\rmma@TitleStyle{#1}}%
1720 \addtocounter{chapter}{1}\addcontentsline{toc}{chapter}{#1}%
1721 }%
1722
1723 %% Formatting of the table of contents
1724 %% dimensions of various parts
1725 \newlength{\TOCtextwidth}\setlength{\TOCtextwidth}{12.65cm}
1726 \newlength{\TOCpagemumwidth}\setlength{\TOCpagemumwidth}{1.3cm}
1727 \newlength{\TOCentrywidth}\setlength{\TOCentrywidth}{\TOCtextwidth}
1728 \addtolength{\TOCentrywidth}{-\TOCpagemumwidth}
1729 \newlength{\TOCextramargin}\setlength{\TOCextramargin}{1.25cm}
1730 \newcommand{\TOCbox}[1]{\hspace{\TOCextramargin}\parbox{\TOCtextwidth}{#1}\par}
1731 \newlength{\TOCextramarginx}\setlength{\TOCextramarginx}{\TOCextramargin}\addtolength{\TOCextramarginx}{\TOCtextwidth}
1732 \newlength{\TOCtextwidthx}\setlength{\TOCtextwidthx}{\TOCtextwidth}\addtolength{\TOCtextwidthx}{\TOCextramarginx}
1733 \newcommand{\TOCboxx}[1]{\hspace{\TOCextramarginx}\parbox{\TOCtextwidthx}{#1}\par}
1734
1735 \newcommand{\RMAAbannerimage}{rmsc}
1736 \renewcommand\tableofcontents{%
1737 \renewcommand{\articlename}{CONTENTS}
1738 \begingroup
1739 \begofarticlehook
1740 \if@twocolumn
1741 \restonecoltrue\onecolumn
1742 \else
1743 \restonecolfalse
1744 \fi
1745 %% 9pt for journal style
1746 \if@proceedings\else\small\fi
1747 \if@newstyle\small\fi %% same for new style
1748 \if@proceedings\thispagestyle{rmaafrontfirstpage}\else\thispagestyle{empty}\fi
1749 \shortauthor{Contents}\shorttitle{Contents}
1750 \vspace*{18mm}
1751 \if@printbanner
1752 %% put in the banner header (need to get better image of this)
1753 \TOCbox{\hspace*{-0.15cm}\includegraphics[width=0.9\TOCtextwidth]{\RMAAbannerimage}}
1754 \vspace*{8mm}
1755 %% volume and publication date (should really be in funny font)
1756 \TOCboxx{\@volumen\[\[2mm] \@mes\ \@anyo}
1757 \else
1758 %% put in the banner header (need to get better image of this)
1759 \TOCbox{\hspace*{-0.15cm}\includegraphics[width=0.9\TOCtextwidth]{\RMAAbannerimage}}
1760 \vspace*{12.5mm}
1761 %% volume and publication date (should really be in funny font)
1762 \TOCboxx{\[\[2mm] ~}
1763 \fi

```

```

1764 \vspace*{16mm}
1765 %% This is the command that fiddles with the TOC entry so that the
1766 %% title is flushleft but the authors are flushright
1767 \renewcommand{\@fiddleauthors}[2]{%
1768   % first put the paper title
1769   \renewcommand{\@}{\relax} % temporarily turn off explicit line breaks just in case
1770   \renewcommand{\altaffilmark}[1]{\relax} % ditto with this
1771   \renewcommand{\textsuperscript}[1]{\relax} % ditto with this
1772   ##1
1773   % now save the author list in a box
1774   \sbox\@tempboxa{##2}%
1775   % check that box is shorter than the total width available for the entry
1776   \ifdim \wd\@tempboxa <\TOCentrywidth
1777     % if so, then put it right here, flush against right margin
1778     \penalty10000\hskip1em plus10em\penalty0\hbox{\nobreak\hfill\box\@tempboxa
1779     % Note that we force a space of at least 1em between title and authorlist,
1780     % stretchable to 11em since we may have very short titles but still with an
1781     % authorlist too long to go on the same line. The only linebreak allowed is
1782     % directly before the authorlist.
1783   \else
1784     % if it is too long, we set the original authorlist text in its own parbox
1785     \par\vskip1ex\parbox[b]{\TOCentrywidth}{\raggedleft ##2}
1786   \fi
1787 }
1788 \@starttoc{toc}%
1789 \if@restonecol\twocolumn\fi
1790 \frontlabel{RMAALastPage}
1791 \clearpage
1792 \thispagestyle{empty}
1793 \cleardoublepage % make sure we start on an odd page
1794 \endgroup
1795
1796 %%% ALSO, do the HTML TOC
1797 %% The file that will be used to make the HTML TOC
1798 \@starttoc{htc}
1799 %% All the stuff in this file does nothing in the book style
1800 \addtocontents{htc}{\protect\HyperTOCmeeting{\@conftitle}{\@reunionplace}{\@reuniondate}}
1801 \addtocontents{htc}{\protect\HyperTOCeditors{\@editors}}
1802 \addtocontents{htc}{\protect\HyperTOCpreamble}
1803 \addtocontents{htc}{\protect\HyperTOCEntry{Table of Contents}{\@articlename}}
1804
1805 %% and the ADS file
1806 \ADS@openfile
1807 }
1808 %% This is now much simpler
1809 \renewcommand\l@chapter[2]{%TOC entry for articles
1810   \ifnum \c@tocdepth >\m@ne
1811     \vskip 1.0em \@plus\p@
1812     \TOCbox{%
1813       \parbox[b]{\TOCentrywidth}{#1}\parbox[b]{\TOCpagenumwidth}{\hfill#2}
1814     }
1815   \fi}
1816 \renewcommand\l@part[2]{%TOC entry for sessions: centered, no page number
1817   \ifnum \c@tocdepth >\m@ne
1818     \vskip 1.5em \@plus1.5em \goodbreak
1819     \TOCbox{%
1820       \parbox[b]{\TOCentrywidth}{\hfil#1\hfil}\hfill

```



```

1821     }
1822   \fi\nobreak}
1823
1824%% Formatting theindex
1825%% strongly encourage page breaks between index entries
1826\renewcommand{@idxtitem}{\par\penalty-1000\hangindent.45cm}
1827\renewcommand{\indexspace}{\par\penalty-1000\vskip 10\p@ \@plus15\p@ \@minus3\p@\relax}
1828\renewenvironment{theindex}{%
1829  %% first, make sure we start on an odd page (06 Jun 2000)
1830  \clearpage\thispagestyle{empty}\cleardoublepage
1831  %% this looks a bit like an article but is two columns and without abstract, etc
1832  \renewcommand{\articlename}{INDEX}
1833  \title{Author Index}\shortauthor{Author Index}\shorttitle{Author Index}
1834  \listofauthors{}
1835  \addcontentsline{toc}{chapter}{\protect\@fiddleauthors{\@TOCtitle}{\rmaaTOCauthors}}%
1836  \addtocontents{htc}{\protect\HyperTOCEntry{\@rawtitle}{\@rawauthors}{\articlename}}
1837  \pagestyle{rmaa}
1838  \thispagestyle{rmaafirstpage}
1839  \@begofarticlehook
1840  %% 9pt for journal style
1841  \if@proceedings\else\small\fi
1842  \if@newstyle\small\fi
1843  \twocolumn[\@makeminititle]
1844  %% vertical spacing (see also definition of \@idxtitem and \indexspace
1845  \parskip\z@ \@plus .6\p@\relax % allow quite a lot of leeway here to avoid breaks inside ent
1846  %% horizontal spacing, breaking and glue parameters (see also the stuff in the definition
1847  %% of \indexauthor
1848  \parindent\z@
1849  \exhyphenpenalty10000 % don't break on explicit hyphens, it always looks bad
1850  \rightskip=0pt plus.2em % allow a tiny bit of leeway at the ends of lines
1851  \spaceskip.3333em plus.5em minus.15em % a lot of leeway between words
1852  \xspaceskip.5em plus.5em minus.4em % this seems to have no effect
1853  \let\item\@idxtitem
1854  \renewcommand{\@}{\relax} % temporarily turn off explicit line breaks just in case
1855  \renewcommand{\altaffilmark}[1]{\relax} % ditto with this
1856  \renewcommand{\textsuperscript}[1]{\relax} % ditto with this
1857  }{\label{RMAALastPage}\clearpage} % clearpage necessary so that we know about \shortauthor
1858
1859
1860
1861%% end definitions for book styles
1862\fi
1863

```

In order to do away with plates, we sometimes want a figure to appear in color only in the online version. The following command can be used in a figure caption to typeset a note to this effect.

```

1864\newcommand\ColorOnlineOnly{%
1865  \textsc{Note: this figure is available in color in the electronic
1866    version of this article, obtainable from}
1867  \texttt{http://discretionary{}{}{}www.\discretionary{}{}{}astroscu.\discretionary{}{}{}unam
1868%% Plates
1869%% Define 2 counters: plate is the number in the whole document, plateloop is used
1870%% internally by \outputplates
1871\newcounter{plate}
1872\newcounter{plateloop}
1873%% Currently limited to 15 plates in document

```

```

1874%% when we do a label, we need to write to \newlabel entries to the .aux file, one
1875%% that says RMAAPlateX so that it can be referred to in \outputplates, and one that
1876%% says articlename:RMAAPlateX so that the dvips program can find it and associate it
1877%% with the right article
1878 \newcommand{\@platelabeli}{\oldlabel{RMAAPlate1}\label{RMAAPlate1}}
1879 \newcommand{\@platelabelii}{\oldlabel{RMAAPlate2}\label{RMAAPlate2}}
1880 \newcommand{\@platelabeliii}{\oldlabel{RMAAPlate3}\label{RMAAPlate3}}
1881 \newcommand{\@platelabeliv}{\oldlabel{RMAAPlate4}\label{RMAAPlate4}}
1882 \newcommand{\@platelabelv}{\oldlabel{RMAAPlate5}\label{RMAAPlate5}}
1883 \newcommand{\@platelabelvi}{\oldlabel{RMAAPlate6}\label{RMAAPlate6}}
1884 \newcommand{\@platelabelvii}{\oldlabel{RMAAPlate7}\label{RMAAPlate7}}
1885 \newcommand{\@platelabelviii}{\oldlabel{RMAAPlate8}\label{RMAAPlate8}}
1886 \newcommand{\@platelabelix}{\oldlabel{RMAAPlate9}\label{RMAAPlate9}}
1887 \newcommand{\@platelabelx}{\oldlabel{RMAAPlate10}\label{RMAAPlate10}}
1888 \newcommand{\@platelabelxi}{\oldlabel{RMAAPlate11}\label{RMAAPlate11}}
1889 \newcommand{\@platelabelxii}{\oldlabel{RMAAPlate12}\label{RMAAPlate12}}
1890 \newcommand{\@platelabelxiii}{\oldlabel{RMAAPlate13}\label{RMAAPlate13}}
1891 \newcommand{\@platelabelxiv}{\oldlabel{RMAAPlate14}\label{RMAAPlate14}}
1892 \newcommand{\@platelabelxv}{\oldlabel{RMAAPlate15}\label{RMAAPlate15}}
1893 \newcommand{\@outputplatelabeli}{\oldlabel{RMAAOutputPlate1}}
1894 \newcommand{\@outputplatelabelii}{\oldlabel{RMAAOutputPlate2}}
1895 \newcommand{\@outputplatelabeliii}{\oldlabel{RMAAOutputPlate3}}
1896 \newcommand{\@outputplatelabeliv}{\oldlabel{RMAAOutputPlate4}}
1897 \newcommand{\@outputplatelabelv}{\oldlabel{RMAAOutputPlate5}}
1898 \newcommand{\@outputplatelabelvi}{\oldlabel{RMAAOutputPlate6}}
1899 \newcommand{\@outputplatelabelvii}{\oldlabel{RMAAOutputPlate7}}
1900 \newcommand{\@outputplatelabelviii}{\oldlabel{RMAAOutputPlate8}}
1901 \newcommand{\@outputplatelabelix}{\oldlabel{RMAAOutputPlate9}}
1902 \newcommand{\@outputplatelabelx}{\oldlabel{RMAAOutputPlate10}}
1903 \newcommand{\@outputplatelabelxi}{\oldlabel{RMAAOutputPlate11}}
1904 \newcommand{\@outputplatelabelxii}{\oldlabel{RMAAOutputPlate12}}
1905 \newcommand{\@outputplatelabelxiii}{\oldlabel{RMAAOutputPlate13}}
1906 \newcommand{\@outputplatelabelxiv}{\oldlabel{RMAAOutputPlate14}}
1907 \newcommand{\@outputplatelabelxv}{\oldlabel{RMAAOutputPlate15}}
1908 \newcommand{\@platerefi}{\oldpageref{RMAAPlate1}}
1909 \newcommand{\@platerefii}{\oldpageref{RMAAPlate2}}
1910 \newcommand{\@platerefiii}{\oldpageref{RMAAPlate3}}
1911 \newcommand{\@platerefiv}{\oldpageref{RMAAPlate4}}
1912 \newcommand{\@platerefv}{\oldpageref{RMAAPlate5}}
1913 \newcommand{\@platerefvi}{\oldpageref{RMAAPlate6}}
1914 \newcommand{\@platerefvii}{\oldpageref{RMAAPlate7}}
1915 \newcommand{\@platerefviii}{\oldpageref{RMAAPlate8}}
1916 \newcommand{\@platerefix}{\oldpageref{RMAAPlate9}}
1917 \newcommand{\@platerefx}{\oldpageref{RMAAPlate10}}
1918 \newcommand{\@platerefxi}{\oldpageref{RMAAPlate11}}
1919 \newcommand{\@platerefxii}{\oldpageref{RMAAPlate12}}
1920 \newcommand{\@platerefxiii}{\oldpageref{RMAAPlate13}}
1921 \newcommand{\@platerefxiv}{\oldpageref{RMAAPlate14}}
1922 \newcommand{\@platerefxv}{\oldpageref{RMAAPlate15}}
1923 \newcounter{figplatei}
1924 \newcounter{figplateii}
1925 \newcounter{figplateiii}
1926 \newcounter{figplateiv}
1927 \newcounter{figplatev}
1928 \newcounter{figplatevi}
1929 \newcounter{figplatevii}
1930 \newcounter{figplateviii}

```

```

1931 \newcounter{figplateix}
1932 \newcounter{figplatex}
1933 \newcounter{figplatexi}
1934 \newcounter{figplatexii}
1935 \newcounter{figplatexiii}
1936 \newcounter{figplatexiv}
1937 \newcounter{figplatexv}
1938 %% Printed output should use the counter 'plate'
1939 \renewcommand{\theplate}{\@arabic\c@plate}
1940 \renewcommand{\theplateloop}{\@arabic\c@plateloop}
1941 %% Command to output all the saved plates in this paper
1942 \newcommand{\outputplates}{%
1943   \setcounter{plateloop}{0}
1944   \if@book\else\@endofarticlehook\fi % not entirely sure why, but this
1945                                     % seems to be needed
1946   \clearpage % first output the last page of text
1947   % now set pagestyle for blank even pages and make sure we start on an odd page
1948   \pagestyle{empty}
1949   \cleardoublepage
1950   \onecolumn
1951   \parindent\z@
1952   % first put in an extra sheet
1953   % the main purpose of this is so there is always a blank even page before
1954   % each plate for filling in the PS file if the article has an odd number
1955   % of pages (see splitbook.sh)
1956   \null\vfil\centerline{PLATES}\vfil\clearpage\pagestyle{rmaaplate}\cleardoublepage
1957   % output each plate in turn
1958   \@whilenum\value{plateloop}<\value{plate}\do{%
1959     \addtocounter{plateloop}{1}
1960     % restore the figure counter from \@figcounti, \@figcountii, etc
1961     \setcounter{figure}{\value{figplate}\roman{plateloop}}
1962     % spew out the plate (in its own group for safety)
1963     {\csname @plate\roman{plateloop}\endcsname\par}
1964   }
1965   \pagestyle{rmaa}
1966   % reset the page number as if nothing had happened
1967   \addtocounter{page}{-\value{plate}}
1968   \addtocounter{page}{-\value{plate}}
1969 }
1970 \newcommand\figcaption{%
1971   \def\@capttype{figure}
1972   \renewcommand{\@makecaption}{\@makefigcap}
1973   \caption}
1974 \newcommand\tabcaption{%
1975   \def\@capttype{table}
1976   \renewcommand{\@makecaption}{\@maketabcap}
1977   \caption}
1978
1979 \newcommand{\plate}[2][1]{%
1980   %% User command to make a plate page:
1981   %% Mandatory argument is what goes on the plate - this should not
1982   %% include any floating environments (e.g. figure). Instead, \figcaption
1983   %% should be used to do the captions.
1984   %% Optional argument is the number of figures (i.e. captions) on the plate
1985   %% page (default is 1). This is necessary for incrementing the figure counter.
1986   %%
1987   %% Note that we have to use a \gdef rather than an \xdef when we

```

```

1988 %% save the plate output in a command. This means that in the book styles when it
1989 %% comes to spewing out the plate, we will have forgotten about any user macros
1990 %% that may have been defined. This can be got round by repeating the macros inside the plat
1991 %% (Presumably, one would use a \newcommand rather than \renewcommand if they were new.)
1992 % increment global and local counters
1993 \addtocounter{plate}{1}
1994 % write appropriate label to .aux file
1995 \csname @platelabel\roman{plate}\endcsname
1996 % define a global macro called \@platei, \@plateii, \@plateiii, \@plateiv, ...
1997 \expandafter\gdef\csname @plate\roman{plate}\endcsname{%
1998   \csname @outputplatelabel\roman{plateloop}\endcsname
1999   \null\vfil #2 \vfil
2000   \cleardoublepage
2001 }
2002 % save the current shortauthor and shorttitle
2003 % need to be \xdef to take current values of \@shortauthor, etc
2004 \expandafter\xdef\csname @shorta\roman{plate}\endcsname{\@shortauthor}
2005 \expandafter\xdef\csname @shortt\roman{plate}\endcsname{\@shorttitle}
2006 % save the current value of the figure counter for later use in \outputplates
2007 \setcounter{figplate\roman{plate}}{\value{figure}}
2008 % increment the figure counter according to the optional argument
2009 \addtocounter{figure}{#1}
2010 }
2011 %% page style for plate pages
2012 \newcommand{\ps@rmaaplate}{%
2013   % Plate X (see page Y) in the foot
2014   \renewcommand\@oddfoot{\hfil\csname @shorta\roman{plateloop}\endcsname\
2015     (see page~\csname @plateref\roman{plateloop}\endcsname)\hfil}%
2016   \renewcommand\@evenfoot{\relax}%
2017   % nothing in even heads (blank pages)
2018   \renewcommand\@evenhead{\relax}
2019   % short title and page num in the odd heads
2020   \renewcommand\@oddhead{\hfil\csname @shortt\roman{plateloop}\endcsname%
2021     \hfil\llap{PLATE~\theplateloop}}
2022 }
2023
2024
2025
2026
2027
2028 %% Things for the User Guide
2029 \if@guide
2030 %% stolen from doc.sty
2031 \def\MakeShortVerb#1{%
2032   \expandafter\ifx\csname cc\string#1\endcsname\relax
2033     \@shortvrbinfo{Made }{#1}%
2034     \add@special{#1}%
2035     \expandafter
2036     \xdef\csname cc\string#1\endcsname{\the\catcode`#1}%
2037     \begingroup
2038     \catcode`\~\active \lccode`\~`#1%
2039     \lowercase{%
2040       \global\expandafter\let
2041       \csname ac\string#1\endcsname~%
2042       \gdef~{\verb~}}%
2043     \endgroup
2044     \global\catcode`#1\active

```

```

2045 \else
2046 \@shortvrbinf@empty{#1 already}%
2047 \fi}
2048 \def\DeleteShortVerb#1{%
2049 \expandafter\ifx\csname cc\string#1\endcsname\relax
2050 \else
2051 \@shortvrbinf@{Deleted }{#1 as}%
2052 \rem@special{#1}%
2053 \global\catcode'#1\csname cc\string#1\endcsname
2054 \global \expandafter\let \csname cc\string#1\endcsname \relax
2055 \ifnum\catcode'#1=\active
2056 \beginingroup
2057 \catcode'\~\active \lccode'\~'#1%
2058 \lowercase{%
2059 \global\expandafter\let\expandafter~%
2060 \csname ac\string#1\endcsname}%
2061 \endgroup \fi \fi}
2062 \def\@shortvrbinf@#1#2{%
2063 \PackageInfo{doc}{%
2064 #1\expandafter\@gobble\string#2 a short reference
2065 for \string\verb}}
2066 \def\add@special#1{%
2067 \rem@special{#1}%
2068 \expandafter\gdef\expandafter\dospecials\expandafter
2069 {\dospecials \do #1}%
2070 \expandafter\gdef\expandafter\@sanitize\expandafter
2071 {\@sanitize \@makeother #1}}
2072 \def\rem@special#1{%
2073 \def\do##1{%
2074 \ifnum'#1=##1 \else \noexpand\do\noexpand##1\fi}%
2075 \xdef\dospecials{\dospecials}%
2076 \beginingroup
2077 \def\@makeother##1{%
2078 \ifnum'#1=##1 \else \noexpand\@makeother\noexpand##1\fi}%
2079 \xdef\@sanitize{\@sanitize}%
2080 \endgroup}
2081 %% define | as shortcut for \verbatim
2082 \MakeShortVerb{|}
2083 %% comand to specify arguments to LaTeX commands
2084 \newcommand{\rmArg}[1]{%
2085 \ensuremath{\langle}\scriptsize \textsf{\MakeUpperCase{#1}}\ensuremath{\rangle}}
2086 %\newcommand{\rmArg}[1]{\ensuremath{\langle}\textsc{#1}\ensuremath{\rangle}}
2087 \providecommand{\BibTeX}{{\rmfamily B\kern-.05em%
2088 \textsc{i\kern-.025em b\kern-.08em %
2089 T\kern-.1667em lower.7ex\hbox{E}\kern-.125emX}}
2090 %% Environment for code examples
2091 \newenvironment{Code}{%
2092 \begin{list}{}{\setlength{\leftmargin}{0.05\columnwidth}}
2093 \item[]\end{list}}
2094 \fi
2095 \end{package}

```

3 User commands for astronomical articles

Some random definitions. These go both into the main class file and also into `adshtml.sty`.

Definitions of the journal name in different incarnations.

```
2096 \newcommand{\RMAA}{RMxAA}
2097 \newcommand{\RMAAlong}{Revista Mexicana de Astronom\'}{\i}a y Astrof\'}{\i}sica}
2098 \newcommand{\RMAASC}{RMxAC}
2099 \newcommand{\RMAASCLong}{\RMAA\ (Serie de Conferencias)}
```

`\ibidrule` This puts a horizontal rule with a period after it. It is used when the author list of a reference is identical to the preceding one.

```
2101 \newcommand{\ibidrule}{\rule[-0.03cm]{4.7em}{.01cm}.\ }
```

`\ThisVolume` References to other articles in the same volume can be coded as, e.g., `\bibitem{} Bloggs, J. \This`

```
2102 \newcommand{\ThisVolume}[1]{%
2103   \@year, \if@proceedings\RMAASC\else\RMAA\fi, \@volume,
2104   \if@book\oldpageref{#1:RMAAFirstPage}\else 000\fi\ (this volume)}
```

Other stuff that may be useful in ref lists.

```
2105 \newcommand{\etal}{et al.\@}
```

Various new commands from AAS macros

```
2106 \def\acknowledgments{\vskip 3ex plus .8ex minus .4ex}
2107 \let\acknowledgements=\acknowledgments % second spelling
2108 \let\jnl@style=\rm
2109 \def\ref@jnl#1{{\jnl@style#1}}
2110 \DeclareRobustCommand\aj{\ref@jnl{AJ}}
2111 \DeclareRobustCommand\araa{\ref@jnl{ARA\&A}}
2112 \DeclareRobustCommand\apj{\ref@jnl{ApJ}}
2113 \DeclareRobustCommand\apjl{\ref@jnl{ApJ}}
2114 \DeclareRobustCommand\apjs{\ref@jnl{ApJS}}
2115 \DeclareRobustCommand\ao{\ref@jnl{Appl.~Opt.}}
2116 \DeclareRobustCommand\apss{\ref@jnl{Ap\&SS}}
2117 \DeclareRobustCommand\ap{\ref@jnl{A\&A}}
2118 \DeclareRobustCommand\aprr{\ref@jnl{A\&A~Rev.}}
2119 \DeclareRobustCommand\aprs{\ref@jnl{A\&AS}}
2120 \DeclareRobustCommand\azh{\ref@jnl{AZh}}
2121 \DeclareRobustCommand\baas{\ref@jnl{BAAS}}
2122 \DeclareRobustCommand\jrasc{\ref@jnl{JRASC}}
2123 \DeclareRobustCommand\memras{\ref@jnl{MmRAS}}
2124 \DeclareRobustCommand\mnras{\ref@jnl{MNRAS}}
2125 \DeclareRobustCommand\pra{\ref@jnl{Phys.~Rev.~A}}
2126 \DeclareRobustCommand\prb{\ref@jnl{Phys.~Rev.~B}}
2127 \DeclareRobustCommand\prc{\ref@jnl{Phys.~Rev.~C}}
2128 \DeclareRobustCommand\prd{\ref@jnl{Phys.~Rev.~D}}
2129 \DeclareRobustCommand\pre{\ref@jnl{Phys.~Rev.~E}}
2130 \DeclareRobustCommand\prl{\ref@jnl{Phys.~Rev.~Lett.}}
2131 \DeclareRobustCommand\pasp{\ref@jnl{PASP}}
2132 \DeclareRobustCommand\pasj{\ref@jnl{PASJ}}
2133 \DeclareRobustCommand\qjras{\ref@jnl{QJRAS}}
2134 \DeclareRobustCommand\skytel{\ref@jnl{S\&T}}
2135 \DeclareRobustCommand\solphys{\ref@jnl{Sol.~Phys.}}
2136 \DeclareRobustCommand\sovast{\ref@jnl{Soviet~Ast.}}
```

```

2137 \DeclareRobustCommand\ssr{\ref@jnl{Space~Sci.~Rev.}}
2138 \DeclareRobustCommand\zap{\ref@jnl{ZAp}}
2139 \DeclareRobustCommand\nat{\ref@jnl{Nature}}
2140 \DeclareRobustCommand\iaucirc{\ref@jnl{IAU~Circ.}}
2141 \DeclareRobustCommand\aplett{\ref@jnl{Astrophys.~Lett.}}
2142 \DeclareRobustCommand\apspr{\ref@jnl{Astrophys.~Space~Phys.~Res.}}
2143 \DeclareRobustCommand\bain{\ref@jnl{Bull.~Astron.~Inst.~Netherlands}}
2144 \DeclareRobustCommand\fcpl{\ref@jnl{Fund.~Cosmic~Phys.}}
2145 \DeclareRobustCommand\gca{\ref@jnl{Geochim.~Cosmochim.~Acta}}
2146 \DeclareRobustCommand\grl{\ref@jnl{Geophys.~Res.~Lett.}}
2147 \DeclareRobustCommand\jcp{\ref@jnl{J.~Chem.~Phys.}}
2148 \DeclareRobustCommand\jgr{\ref@jnl{J.~Geophys.~Res.}}
2149 \DeclareRobustCommand\jqsrt{\ref@jnl{J.~Quant.~Spec.~Radiat.~Transf.}}
2150 \DeclareRobustCommand\memsai{\ref@jnl{Mem.~Soc.~Astron.~Italiana}}
2151 \DeclareRobustCommand\nphysa{\ref@jnl{Nucl.~Phys.~A}}
2152 \DeclareRobustCommand\physrep{\ref@jnl{Phys.~Rep.}}
2153 \DeclareRobustCommand\physscr{\ref@jnl{Phys.~Scr}}
2154 \DeclareRobustCommand\planss{\ref@jnl{Planet.~Space~Sci.}}
2155 \DeclareRobustCommand\procspie{\ref@jnl{Proc.~SPIE}}
2156 \let\astap=\aap
2157 \let\apjlett=\apjl
2158 \let\apjsupp=\apjs
2159 \let\applopt=\ao
2160 \def\phn{\phantom{0}}
2161 \def\phd{\phantom{.}}
2162 \def\phs{\phantom{\ensuremath{-}}}
2163 \def\phm#1{\phantom{#1}}

```

All these are redone as robust and using more modern commands where possible. The robustness is so they will not get expanded if used in abstracts and titles when these are passed to the ADS file.

```

2164 %%\def\sun{\hbox{$\odot$}}
2165 \DeclareRobustCommand\sun{\ensuremath{\odot}}
2166 %%\def\earth{\hbox{$\oplus$}}
2167 \DeclareRobustCommand\earth{\ensuremath{\oplus}}
2168 %%\def\lesssim{\mathrel{\hbox{\rlap{\hbox{\lower4pt\hbox{$\sim$}}}\hbox{$<$}}}}
2169 %%\def\gttrsim{\mathrel{\hbox{\rlap{\hbox{\lower4pt\hbox{$\sim$}}}\hbox{$>$}}}}
2170 \DeclareRobustCommand\lesssim{\mathrel{\hbox{\smaller\smaller\rlap{\hbox{\lower3pt\hbox{$\sim$}}}}}
2171 \DeclareRobustCommand\gttrsim{\mathrel{\hbox{\smaller\smaller\rlap{\hbox{\lower3pt\hbox{$\sim$}}}}}
2172 %%\def\lta{\mathrel{\spose{\lower 3pt\hbox{$\mathchar"218$}}}}
2173 %%\def\raise 2.0pt\hbox{$\mathchar"13C$}}
2174 %%\def\gta{\mathrel{\spose{\lower 3pt\hbox{$\mathchar"218$}}}}
2175 %%\def\raise 2.0pt\hbox{$\mathchar"13E$}}
2176 \DeclareRobustCommand\sq{\hbox{\rlap{$\sqcap$}$\sqcup$}}
2177 %%\def\arcdeg{\hbox{$^\circ$}}
2178 %%\def\arcmin{\hbox{$^\prime$}}
2179 %%\def\arcsec{\hbox{$^\prime\prime$}}
2180 \DeclareRobustCommand\arcdeg{\ensuremath{^\circ}}
2181 \DeclareRobustCommand\arcmin{\ensuremath{^\prime}}
2182 \DeclareRobustCommand\arcsec{\ensuremath{^\prime\prime}}
2183 %%\def\fd{\hbox{$.\!\!'\!\!^\circ$}}
2184 %%\def\fh{\hbox{$.\!\!'\!\!^\circ$}}
2185 %%\def\fm{\hbox{$.\!\!'\!\!^\circ$}}
2186 %%\def\fs{\hbox{$.\!\!'\!\!^\circ$}}
2187 %%\def\fdg{\hbox{$.\!\!'\!\!^\circ$}}
2188 %%\def\farcm{\hbox{$.\mkern-4mu^\prime$}}
2189 %%\def\farcs{\hbox{$.\!\!'\!\!^\circ$}}

```



```

2242 \newcounter{IonStage}
2243 \DeclareRobustCommand\plainion[2]{\setcounter{IonStage}{#2}\#1 \Roman{IonStage}}
2244 %%\def\ion#1#2{\ensuremath{\mathrm{#1}}\;}{\protect\small\rm\@Roman{#2}}

2245 \DeclareRobustCommand\nodata{$\cdots$}

```

These are needed by the `\ion` command. Isn't there an easier way of doing this?

```

2246 \let\@small=\small
2247 \let\@normalsize=\normalsize
2248 \let\@footnotesize=\footnotesize
2249 \let\@scriptsize=\scriptsize
2250 \let\@tiny=\tiny
2251 \let\@large=\large
2252 \let\@Large=\Large
2253 \let\@LARGE=\LARGE
2254 \let\@huge=\huge
2255 \let\@Huge=\Huge
2256 \newcommand{\smaller}{\small}
2257 \renewcommand{\normalsize}{\renewcommand{\smaller}{\small}\@normalsize}
2258 \renewcommand{\small}{\renewcommand{\smaller}{\footnotesize}\@small}
2259 \renewcommand{\footnotesize}{\renewcommand{\smaller}{\scriptsize}\@footnotesize}
2260 \renewcommand{\scriptsize}{\renewcommand{\smaller}{\tiny}\@scriptsize}
2261 \renewcommand{\tiny}{\renewcommand{\smaller}{\tiny}\@tiny}
2262 \renewcommand{\large}{\renewcommand{\smaller}{\normalsize}\@large}
2263 \renewcommand{\Large}{\renewcommand{\smaller}{\large}\@Large}
2264 \renewcommand{\LARGE}{\renewcommand{\smaller}{\Large}\@LARGE}
2265 \renewcommand{\huge}{\renewcommand{\smaller}{\LARGE}\@huge}
2266 \renewcommand{\Huge}{\renewcommand{\smaller}{\huge}\@Huge}
2267 \</package>| adshtml-style

```

4 Other files

4.1 The driver and make files

These are put here for completeness, although they still need to be distributed separately since otherwise the user won't be able to unpack this file into its constituent parts.

The Makefile has two principal rules: `docs`, and `macros`. The `docs` rule produces a PDF and gzipped PS file of the documentation. I still haven't perfected the combination of rules required to get it to run \LaTeX enough times in all circumstances. The `macros` rule runs \LaTeX on `rmaa.ins` in order to unpack `rmaa.cls` and all the other little files (including the Makefile and the `rmaa.ins` files themselves...

First set up lists of various types of file.

```

2268 <*makefile>
2269 DOCFILES=rmaa.pdf
2270 MACRO_LTX_FILES=rmaa.cls rmaacite.sty adshtml.sty
2271 SHELLSCRIPTS=makeads.sh
2272 MACRO_OTHER_FILES=adshtml.perl sample.latex2html-init
2273 MAKEFILE=Makefile
2274 MACROFILES=$(MACRO_LTX_FILES) $(SHELLSCRIPTS) $(MACRO_OTHER_FILES)
2275 SKELETONFILES=ADS.tex

```

Install the files read only into the package directory, specified via a path relative to the source directory.

```
2276 INSTALL=install
2277 INSTALL_DIR=../packages
```

The default rule is to make everything. Installation must be explicitly asked for.

```
2278 all: docs macros
2279
2280 install: install-docs install-macros
2281
```

Most files are installed read-only to prevent editing. Skeleton files must be writeable. Must be careful not to overwrite the Makefile in the parent directory.

```
2282 install-macros: macros
2283     $(INSTALL) -m 444 $(MACRO_LTX_FILES) $(MACRO_OTHER_FILES) $(INSTALL_DIR)
2284     $(INSTALL) -m 555 $(SHELLSCRIPTS) $(INSTALL_DIR)
2285     $(INSTALL) -m 644 $(SKELETONFILES) $(INSTALL_DIR)
2286
2287 install-docs: docs
2288     $(INSTALL) rmaa.pdf $(INSTALL_DIR)/rm-fulldocs.pdf
2289
```

Make the PDF and gzipped PS files.

```
2290 docs: $(DOCFILES)
2291
```

Make everything else if either the .dtx or .ins files have changed.

```
2292 macros: rmaa.dtx rmaa.ins
```

Ensure that all the macro files can be written to then recreate them. The touch is there in case any of the files don't exist yet.

```
2293     touch $(MACROFILES) $(MAKEFILE)
2294     chmod u+w $(MACROFILES) $(MAKEFILE) rmaa.ins
2295     latex "\input{rmaa.ins}"
```

TeX automatically adds the .tex extension to extensionless files. We fix this and take the opportunity to convert back to TABs all that it has lovingly converted to spaces.

```
2296     cp -f $(MAKEFILE) $(MAKEFILE).BCK && unexpand $(MAKEFILE).tex >| $(MAKEFILE) && rm $(MAKEFILE).BCK
```

Make the shell scripts executable and everything unwriteable (so they don't get hand-edited by mistake). However, undo this for the files that the user is *supposed* to modify.

```
2297     chmod a+x $(SHELLSCRIPTS)
2298     chmod a-w $(MACROFILES) $(MAKEFILE)
2299     chmod u+w $(SKELETONFILES)
2300
```

We now use PDF_LA_TE_X for this.

```
2301 rmaa.idx: rmaa.dtx
2302     @echo "REGENERATING .idx FILE"
2303     pdflatex "\nonstopmode\input{rmaa.dtx}"
2304
2305 rmaa.aux: rmaa.dtx rmaa.ind rmaa.gls
2306     @echo "REGENERATING .aux FILE"
2307     pdflatex "\nonstopmode\input{rmaa.dtx}"
```

```

2308
2309 rmaa.ind: rmaa.idx
2310         @echo "REGENERATING INDEX"
2311         makeindex -s gind.ist rmaa
2312
2313 rmaa.gls: rmaa.glo
2314         @echo "REGENERATING CHANGELOG"
2315         makeindex -s gglo.ist -o rmaa.gls rmaa.glo
2316
2317 rmaa.pdf: rmaa.aux rmaa.ind rmaa.gls
2318         @echo "REGENERATING .pdf FILE"
2319         pdflatex "\nonstopmode\input{rmaa.dtx}"
2320
2321 clean:
2322         rm -f rmaa.aux rmaa.dvi rmaa.ind rmaa.gls
2323 </makefile>

```

The `rmaa.ins` file uses the `docstrip` package to split out all the files and strip off this documentation.

```

2324 <{*ins}>
2325 %%
2326 %% Installation batch file for the RMAA LaTeX package
2327 %%
2328 \def\batchfile{rmaa.ins}
2329 \input docstrip.tex
2330 \preamble
2331
2332 PLEASE DO NOT EDIT THIS FILE! It is generated automatically from
2333 the file rmaa.dtx using the accompanying Makefile and rmaa.ins
2334 Any hand-edited changes will be lost
2335
2336 A LaTeX document class for the RMxAA
2337
2338 Author: William Henney (w.henney@crya.unam.mx)
2339
2340 Latest version available from: http://www.crya.unam.mx/rmaa
2341
2342 Copyright (C) 1999-2010 Instituto de Astronomia, UNAM, Mexico
2343
2344 This program is free software; you can redistribute it and/or
2345 modify it under the terms of the GNU General Public License
2346 as published by the Free Software Foundation; either version 2
2347 of the License, or (at your option) any later version.
2348
2349 This program is distributed in the hope that it will be useful,
2350 but WITHOUT ANY WARRANTY; without even the implied warranty of
2351 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
2352 GNU General Public License for more details.
2353
2354 You should have received a copy of the GNU General Public License
2355 along with this program; if not, write to the Free Software
2356 Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.
2357 \endpreamble

```

Clobber files without asking

```

2358 \askforoverwritefalse

```

Make the \LaTeX macro files (class and styles)

```

2359 \generate{%
2360   \file{rmaa.cls}{\from{rmaa.dtx}{package}}
2361   \file{rmaa.ins}{\from{rmaa.dtx}{ins}}
2362   \file{rmaacite.sty}{\from{rmaa.dtx}{rmaacite}}
2363   \file{adshtml.sty}{\from{rmaa.dtx}{adshtml-style}}
2364   \file{ADS.tex}{\from{rmaa.dtx}{ads-container}}
2365 }

```

Make the other non-L^AT_EX files. These are done separately since they can't use ‘%%’ as a comment character for the preamble/postamble (and Perl files can't have the postamble I don't think).

```

2366 \generate{\nopreamble\nopostamble%
2367   \file{Makefile}{\from{rmaa.dtx}{makefile}}
2368   \file{adshtml.perl}{\from{rmaa.dtx}{adshtml-perl}}
2369   \file{makeads.sh}{\from{rmaa.dtx}{ads-shell-script}}
2370   \file{sample.latex2html-init}{\from{rmaa.dtx}{latex2html-init}}
2371 }
2372
2373 %% Local Variables:
2374 %% mode: LaTeX
2375 %% mode: Font-lock
2376 %% End:
2377 </ins>

```

4.2 Extended citation syntax

Modified from a file called mnrascite.sty I no longer remember where I stole the original version of this from

Alterations to the cite commands to make them do more sensible things. N.B. the bibliography style should produce entries which have labels where the date is delimited by angle brackets ‘i>’ for these macros to work properly. They will not give very sensible error messages if you do not do this properly.

A new command \scite{key} is defined which produces a citation which is suitable for insertion in a sentence. i.e., it does not put brackets around the whole citation, only the date. Also \pcite{key} produce output with no parentheses whatsoever.

Should redefine \@bibitem really to have any hope of compatibility the command \lbibcite is defined to deal with the citations.

```

2378 <*rmaacite>
2379 \def\bibitem[#1<#2>]#3{\par\hangindent=1.5em\hangafter=1
2380   \if@filesw
2381     {\def\protect##1{\string ##1\space}
2382       \immediate\write\auxout{\string\lbibcite{#3}{#1}{#2}}}
2383   \fi}
2384 \@redefinebibitem % what it says

```

Note that the \lbibcite defines two types of citation one contains the names, the other the year

```

2385 \def\lbibcite#1#2#3{\global\@namedef{b@#1}{#2}
2386   \global\@namedef{by@#1}{#3}}
2387
2388 \def\@bcite#1#2{({#1\if@tempswa , #2\fi})}
2389 \def\@pcite#1#2{#1\if@tempswa , #2\fi}

```

This declaration contains what is put between the name and the date

```

2390 \def\@brcite{\ }
2391 \def\@ebrcite{}
2392 \def\@fmttop#1{\@fmtcite[\csname #1\endcsname]}
2393 \def\@citex[#1]#2{%
2394 %% \if@filesw\immediate\write\@auxout{\string\citation{#2}}\fi
2395 %% WJH added 16 Jan 2002
2396 \@for\@citeb:=#2\do{%
2397 \edef\@citeb{\expandafter\@firstofone\@citeb:\articlename}%
2398 \if@filesw\immediate\write\@auxout{\string\citation{\@citeb}}\fi}%
2399 %% to here
2400 \def\@citea{}%
2401 \@cite{\@for\@citeb:=#2\do
2402 {%
2403 \edef\@citeb{\expandafter\@firstofone\@citeb:\articlename}%
2404 \@citea\def\@citea{; \ } \@ifundefined
2405 {b@\@citeb}{\bf ?}\@warning {Citation '\@citeb' on page \thepage \space undefined}}%
2406 {\csname b@\@citeb\endcsname\@citebro\csname by@\@citeb\endcsname\@citebrc}}}%
2407 {#1}}
2408
2409 \def\cite{\@ifnextchar [{\let\@citebro=\space
2410 \let\@citebrc=\relax
2411 \let\@cite=\@bcite\@tempswattrue\@citex}
2412 {\let\@citebro=\space
2413 \let\@citebrc=\relax
2414 \let\@cite=\@bcite\@tempswafalse\@citex[]}]
2415 \def\pcite{\@ifnextchar [{\let\@citebro=\space
2416 \let\@citebrc=\relax
2417 \let\@cite=\@pcite\@tempswattrue\@citex}
2418 {\let\@citebro=\space
2419 \let\@citebrc=\relax
2420 \let\@cite=\@pcite\@tempswafalse\@citex[]}]
2421 \def\scite{\@ifnextchar [{\let\@citebro=\@brcite
2422 \let\@citebrc=\@ebrcite
2423 \let\@cite=\@pcite\@tempswattrue\@citex}
2424 {\let\@citebro=\@brcite
2425 \let\@citebrc=\@ebrcite
2426 \let\@cite=\@pcite\@tempswafalse\@citex[]}]
2427
2428 \renewenvironment{thebibliography}
2429 {\section*{REFERENCES}\vspace*{\afterbiblioskip}\small
2430 \if@book\RereadBiblio\fi
2431 \sloppy\clubpenalty4000\widowpenalty4000
2432 \sfcode\`=1000\relax
2433 \setlength\parindent{\z@}\setlength\parskip{\z@}}
2434 {\relax\normalsize\@outputaddressesifnecessary}
2435 \rmaacite)

```

4.3 Auxilliary files for generating ADS data

The ADS data are written by L^AT_EX to a .ads file. This file then has to be included in the following file (ADS.tex), which is run through L^AT_EX2HTML (see below).

```

2436 (*ads-container)
2437 %%
2438 %% Instructions:

```

```

2439%% Edit the \input{} line below to reflect the name of your file.
2440\documentclass{article}
2441\usepackage[latin1]{inputenc}
2442\usepackage{adshtml}
2443\newcommand{\ADSfield}[2]
2444{\%#1 #2\\}
2445%%\newcommand{\ADSvfield}[2]
2446%%{\%#1 \begin{verbatim}#2\end{verbatim}}
2447\newenvironment{ADSarticle}{}{\par\bigskip}
2448\renewcommand{\bibitem}[2][\par}
2449\setlength{\parindent}{0pt}
2450\renewcommand{\ThisVolume}[1]{%
2451 2001, \RMAASC, 12, \oldpageref{#1:RMAAFirstPage}}
2452
2453
2454\begin{document}
2455\makeatletter
2456\input{rmbooksamp.ads}
2457\end{document}
2458</ads-container>

```

This is the `adshtml.sty` style file used by `ADS.tex`. It just defines a few macros that might be used in abstracts, etc (really it should define them all). This now gets all its code from Sec 3.

```

2459<*adshtml-style>
2460%% Nothing else needs to go here now.
2461</adshtml-style>

```

The init file for `latex2html`.

```

2462<*latex2html-init>
2463$PDFTOCAIRO = "pdftocairo";
2464$PDFLATEX = "pdflatex";
2465$LATEX = "latex";
2466$MAX_SPLIT_DEPTH = 0;
2467$HTML_VERSION = "4.0,math";
2468$NO_SIMPLE_MATH = 1;
2469$ADDRESS = "<p><address><a href=\"mailto:rmaa@astro.unam.mx\">rmaa@astro.unam.mx</address></p>";
2470$INFO = "<p>This document was created using latex2html and the rmaa latex macros</p>";
2471$NO_NAVIGATION = 1;
24721;
2473</latex2html-init>

```

This is the `adshtml.perl` file that is used by `LATEX2HTML`. Some bizarre `TEX`y command sometimes show up so we tell it to ignore these. All the astronomy macros that come from AAS are processed in `TEX`. That way they get made to images but with an `ALT` tag that has the original code, which is what will be picked up by `lynx`, with the result that they get passed intact into the final `.txt` file.

```

2474<*adshtml-perl>
2475package main;
2476
2477$dum = &do_cmd_makeatletter();
2478
2479sub do_cmd_RMAA {
2480    local($_) = @_;
2481    "RMxAA" . $_;

```

```

2482 }
2483
2484 sub do_cmd_RMAASC {
2485     local($_) = @_;
2486     "RMxAASC" . $_;
2487 }
2488
2489 sub do_cmd_etal {
2490     local($_) = @_;
2491     "et al\." . $_;
2492 }
2493
2494 sub do_cmd_ibidrule {
2495     local($_) = @_;
2496     "<img src=\"foo\" alt=\"\ibidrule\">" . $_;
2497 }
2498
2499
2500 sub do_cmd_bibitem {
2501     local($_) = @_;
2502     local($key);
2503     local($opt, $dummy)=&get_next_optional_argument;
2504     $key = &missing_braces unless
2505         ((s/$next_pair_pr_rx/$key = $2; ''/eo)
2506         ||(s/$next_pair_rx/$key = $2; ''/eo));
2507     "<p>" . $_;
2508 }
2509
2510 &ignore_commands (<<_RAW_ARG_CMDS_);
2511 lowercase
2512 adjustfinalcols
2513 textsuperscript # {}
2514 newline # []
2515 thinmuskip
2516 mskip
2517 smallskip
2518 medskip
2519 bigskip
2520 hspace # {}
2521 hspacestar # {}
2522 vspace # {}
2523 vspacestar # {}
2524 mathrm
2525 _at_mathrm
2526 spacefactor
2527 discretionary
2528 unhbox
2529 voidb_at_x
2530 penalty
2531 _at_M
2532 _at_m
2533 null
2534 IeC
2535 _RAW_ARG_CMDS_
2536
2537 &process_commands_in_tex (<<_RAW_ARG_CMDS_);
2538 sun

```

2539 earth
2540 lesssim
2541 gtrsim
2542 sq
2543 argdeg
2544 arcmin
2545 arcsec
2546 fd
2547 fh
2548 fm
2549 fs
2550 fdg
2551 farcm
2552 farcs
2553 fp
2554 micron
2555 la
2556 ga
2557 case # {} # {}
2558 slantfrac # {} # {}
2559 onehalf
2560 onethird
2561 twothirds
2562 onequarter
2563 threequarters
2564 ubvr
2565 ub
2566 bv
2567 vr
2568 ur
2569 aj
2570 araa
2571 apj
2572 apjl
2573 apjs
2574 ao
2575 apss
2576 aap
2577 aapr
2578 aaps
2579 azh
2580 baas
2581 jrasc
2582 memras
2583 mnras
2584 pra
2585 prb
2586 prc
2587 prd
2588 pre
2589 prl
2590 pasp
2591 pasj
2592 qjras
2593 skytel
2594 solphys
2595 sovast


```

2596 ssr
2597 zap
2598 nat
2599 iaucirc
2600 aplett
2601 apspr
2602 bain
2603 fcp
2604 gca
2605 grl
2606 jcp
2607 jgr
2608 jqsrt
2609 memsai
2610 nphysa
2611 physrep
2612 physscr
2613 planss
2614 procsapie
2615 _RAW_ARG_CMDS_
2616
2617 l;                                     # This must be the last line
2618 </adshtml-perl>

This is a shell script makeads.sh that generates the _ads.txt file from
_ads.tex by using LATEX2HTML and lynx.

2619 <*ads-shell-script>
2620 #! /bin/sh
2621 if [ -z $1 ]; then
2622     echo "Usage: $0 basename"
2623     exit
2624 fi
2625 BASENAME=$1
2626 ADSBASENAME=${BASENAME}_ads
2627 AUXFILE=$BASENAME.aux
2628 TMPFILE=tmp.$$
2629
2630
2631 echo "Generating $ADSBASENAME.tex"
2632
2633 # For some reason, must double-up \\ to \\\ but not \ to \\ - odd!
2634 cat > $ADSBASENAME.tex <<EOF
2635 %% PLEASE DO NOT EDIT THIS FILE! It is generated automatically from
2636 %% the script makeads.sh. Any hand-edited changes will be lost
2637 %%
2638 \documentclass{article}
2639 \usepackage[latin1]{inputenc}
2640 \usepackage{html}
2641 \usepackage{adshtml}
2642 \newcommand{\ADSfield}[2]{\%#1 #2\\}
2643 \newenvironment{ADSarticle}{}{\par\bigskip}
2644 \setlength{\parindent}{0pt}
2645 \newcounter{istage}
2646 \renewcommand{\ion}[2]{\setcounter{istage}{#2}#1 \Roman{istage}}
2647 \begin{document}
2648 \makeatletter
2649 EOF

```

```

2650 echo >> $ADSBASENAME.tex "\input{$BASENAME.ads2}"
2651 echo >> $ADSBASENAME.tex "\end{document}"
2652
2653
2654
2655 echo "Generating $ADSBASENAME.sed"
2656
2657 # Find type of journal
2658 grep '\documentclass\[.*proceedings.*\]' $BASENAME.tex >/dev/null \
2659     && JOURNAL='RMxAC' \
2660     || JOURNAL='RMxAA'
2661
2662 # Find the year and volume number
2663 YEAR=`grep '\SetYear' $BASENAME.tex | sed 's/.*\SetYear{(.*)}.*$/1/'`
2664 VOLUME=`grep '\SetVolume' $BASENAME.tex | sed 's/.*\SetVolume{(.*)}.*$/1/'`
2665
2666 # Generate an auxilliary sed script
2667 cat > $TMPFILE <<EOF
2668 s|\\\\\\newlabel{(.*) :RMAAFirstPage}{(.*){(.*)}}|s|\\\\\\\\\\ThisVolume{\\1}/$YEAR, RMxAC, $VOL
2669 EOF
2670
2671 # Now go through the .aux file, looking for \newlabels and use the sed
2672 # script just generated in order to make another sed script, one that
2673 # will replace \ThisVolume{LABEL} with the correct reference
2674 grep '^\\newlabel{.*:RMAAFirstPage}' $AUXFILE \
2675     | sed -f $TMPFILE > $ADSBASENAME.sed && rm $TMPFILE
2676
2677 # Append a further sed command to get rid of \@, since redefining
2678 # it in _ads.tex didn't work
2679 echo >> $ADSBASENAME.sed 's/\\\\\\@//g'
2680
2681 echo "Generating $BASENAME.ads2 from $ADSBASENAME.sed and $BASENAME.ads"
2682
2683 # Apply this to the .ads file, generating the .ads2 file, which is included
2684 # by the _ads.tex file.
2685 sed -f $ADSBASENAME.sed $BASENAME.ads > $BASENAME.ads2
2686
2687 echo "Generating $ADSBASENAME.txt from $ADSBASENAME.tex and $BASENAME.ads2"
2688
2689 # Now run latex2html on the _ads.tex file
2690 latex2html -no_navigation -info 0 -address 0 -html_version 4.0,math $ADSBASENAME
2691
2692 # Then, convert to utf8 with lynx and tidy it up a bit
2693 lynx --justify=off --width=100 --dump --nolist --display_charset=utf-8 \
2694     $ADSBASENAME/$ADSBASENAME.html | cut -c4- \
2695     | sed 's/ibidrule/\\ibidrule/g' > $ADSBASENAME.txt
2696 </ads-shell-script>

```

5 Epilogue

Err, that's it ...

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\! .	2183–2187, 2189– 2193, 2195, 2198, 2199, 2205, 2212, 2218–2223, 2226	
\"	2469, 2496	
\#	814	
\\$	813	
\%	815, 863, 2444, 2446, 2642	
\&	816, 2111, 2116–2119, 2134	
\'	199, 438, 439, 682, 720, 721, 725, 727, 729, 780, 795, 796, 846, 2098	
\(2663, 2664, 2668	
\)	2663, 2664, 2668	
\,	535, 704, 706, 2205, 2212	
\.	573, 682, 1312, 2432, 2491	
\;	2244	
\@	519, 2105, 2677	
\@NAME@@default	223, 224	
\@name	665	
\@protect	178, 182, 1112, 1115	
\@Alpha	1162, 1171	
\@DOI@prefix	718	
\@DOI@url	440, 699, 719	
\@FinalFigure	558, 559, 567	
\@Huge	2255, 2266	
\@LARGE	2253, 2264	
\@Large	2252, 2263	
\@M	1128	
\@MSmaketitle	951, <u>1052</u>	
\@MSnum	689, <u>707</u>	
\@NAME@SCALE	219, 223, 251	
\@NAME@default	223	
\@NAME@scale	217, 224, 245	
\@Roman	2238, 2244	
\@TOCaftertitle	478, 484, 485, 1455, 1457, 1460, 1461, 1590, 1592	
\@TOCtitle	<u>475</u> , 1438, 1460, 1478, 1530, 1690, 1835	
\@abstract	445, 1003, 1008, 1077, 1446, 1481	
\@abstractpresentfalse	49	
\@abstractpresenttrue	457	
\@abstractsadsfalse	1426	
\@abstractsadstrue	1427	
\@accepted	697, <u>707</u> , 988, 1067, 1069	
\@after@abstracthead@skip	278, 1002, 1006	
\@after@abstracthead@skipScale	343	
\@afterindentfalse	120	
\@anyo	694, <u>707</u> , 1756	
\@arabic	912, 1104, 1105, 1176, 1177, 1463, 1520, 1703, 1711– 1713, 1939, 1940	
\@arenotesfalse	732	
\@arenotesttrue	738	
\@articledir	1597, 1631, 1632	
\@artpages	435, <u>707</u>	
\@astro	2469	
\@author	962, 980, 1061, 1465, 1480	
\@auxout	928, 1339, 1702, 2382, 2394, 2398	
\@bcite	2388, 2411, 2414	
\@before@abstract@skip	278, 997	
\@before@abstract@skipScale	342	
\@before@author@skip	278, 977	
\@before@author@skipScale	340	
\@before@dates@skip	278, 984	
\@before@dates@skipScale	346	
\@before@kwd@skip	278, 1011	
\@before@kwd@skipScale	345	
\@before@title@skip	278, 973	
\@before@title@skipScale	339	
\@begofarticlehook	907, <u>910</u> , 1334, 1468, 1527, 1684, 1739, 1839	
\@between@abstract@skip	278, 1004	
\@between@abstract@skipScale	344	
\@between@author@skip	278, 979	
\@between@author@skipScale	341	
\@biblistfalse	39, 1313	
\@biblisttrue	1312	
\@bigfonttrue	31, 65	
\@boldkeywordsfalse	59	
\@boldkeywordstrue	97, 98	

\@bookfalse	41	\@fiddleauthors .		\@ifnextchar	
\@booktrue	84 1438, 1478,		... 2409, 2415, 2421	
\@brcite 2390, 2421, 2424		1500, 1519, 1530,		\@ifundefined ...	
\@bsphack ..	1336, 1701	1690, 1767, 1835		124, 1340, 1556, 2404	
\@caption	1250	\@figcounti	1960	\@inpreamblesfalse 916	
\@capttype ... 1226,		\@figcountii ...	1960	\@inpreamblestrue 159	
1234, 1971, 1975		\@firstaffilfalse 489		\@isortkey 653, 656–658	
\@car	683, 2236	\@firstaffiltrue		\@journalfalse ..	
\@cite	2401, 163, 1583	 61, 65, 71, 78	
2411, 2414, 2417,		\@firstaltaffilfalse		\@journalname ...	
2420, 2423, 2426	 493, 497		.. 423, 429, 434, 713	
\@citea	2400, 2404	\@firstaltaffiltrue		\@journaltrue .. 23, 68	
\@citeb . 1337–1341,	 165, 1584		\@keywordheader .	
2396–2398, 2401,		\@firstauthorfalse	 501, 1016,	
2403, 2405, 2406	 680		1019, 1078, 1079	
\@citebrc ...	2406,	\@firstauthortrue		\@keywords	
2410, 2413, 2416,	 161, 1582		501, 1020, 1078, 1079	
2419, 2422, 2425		\@firstkwdfalse .	512	\@kwdsep	501, 514
\@citebro ...	2406,	\@firstkwdrue ..		\@kwhwidth	963
2409, 2412, 2415,	 167, 1585		\@kwtwidth	963
2418, 2421, 2424		\@firstofone		\@large	2251, 2262
\@citex	2393,	... 1338, 2397, 2403		\@latex@warning 1341	
2411, 2414, 2417,		\@float	1239, 1245	\@mainmatterfalse	
2420, 2423, 2426		\@fmtcite	2392 1655, 1671	
\@combinedblfloats		\@fmttop	2392	\@mainmattertrue 1665	
.....	151, 152	\@footnotesize ..		\@makecaption ...	
\@conftitle ..	420, 2248, 2259		1226, 1234, 1239,	
722, 724, 779, 1800		\@for ..	1337, 2396, 2401	1242, 1245, 1248,	
\@date	1064	\@frontmatterfalse		1260, 1972, 1976	
\@dblfloat .	1242, 1248 157, 1664		\@makefigcap 1183,	
\@debugfalse	57	\@frontmattertrue		1239, 1242, 1972	
\@debugtrue	93 1654		\@makefnmark . 939, 940	
\@ebrcite		\@fulladdbox . 552,		\@makefntext	941
... 2391, 2422, 2425		614, 616, 617, 636		\@makeminititle .	
\@editores ...	727, 728	\@fulladddepth 1415,	
\@editors	725, 552, 617, 618		1443, 1469, 1843	
726, 779, 1707, 1801		\@fulladdheight .		\@makeother	
\@empty 1109, 1465, 2046		.. 552, 616, 618,		... 2071, 2077, 2078	
\@emptykey ...	654, 657	620, 625–628, 630		\@makerottabcap 1201	
\@endofarticlehook		\@fulladdresses .		\@maketabcap	
.. 601, 611, 641,	 552, 614		1195, 1226, 1234,	
908, 919, 1597, 1944		\@gobble		1245, 1248, 1976	
\@esphack ..	1342, 1704	802–804, 1555, 2064		\@maketitle ..	104,
\@evenfoot ...	410,	\@guidefalse	33	945, 951, 961, 965	
416, 1636, 1644, 2016		\@guidetrue	71	\@manuscriptfalse	
\@evenhead		\@hangfrom	1127	... 68, 71, 74, 76, 80	
. 411, 443, 1638,		\@huge	2254, 2265	\@manuscripttrue	
1639, 1646, 2018		\@idxitem 29, 61, 65	
\@extra@b@citeb 1353		... 1826, 1844, 1853		\@mes	729, 730, 1756
				\@minipagefalse 1191	

\@minus . 240, 1503, 1827	\@outputplatelabelx	\@platerexfiii . 1920
\@namedef ... 1351, 1902	\@platerexxiv .. 1921
1352, 2385, 2386	\@outputplatelabelxi	\@platerexv ... 1922
\@natbibfalse 87 1903	\@plus 238,
\@natbibtrue 43	\@outputplatelabelxii	1041, 1484, 1498,
\@needaddressesfalse 1904	1502, 1503, 1811,
..... 580, 638	\@outputplatelabelxiii	1818, 1827, 1845
\@needaddressestrue 1905	\@pnumwidth
..... 155, 1587	\@outputplatelabelxiv	... 1044, 1045, 1049
\@newargs 1716 1906	\@preprintfalse .. 35
\@newstylefalse 55, 91	\@outputplatelabelxv	\@preprinttrue ... 74
\@newstyletrue . 78, 89 1907	\@printbannerfalse
\@nil 683, 2236	\@package@default@lengths 51
\@noexpandADSfalse 294, 934, 935	\@printdatesfalse
..... 169	\@packagename 25, 80, 582
\@noexpandADStrue 459	... 1535, 1536, 1540	\@printdatestrue
\@normalsize 2247, 2257	\@parboxrestore 1255 68, 82, 581
\@oddfoot 409,	\@pcite . 2389, 2417,	\@proceedingsfalse
415, 1635, 1643, 2014	2420, 2423, 2426 27
\@oddhead . 412, 418,	\@platei 1996	\@proceedingtrue 78
426, 429, 432,	\@plateii 1996	\@prooffalse 21
443, 1639, 1647, 2020	\@plateiii 1996	\@prooftrue 76
\@oldargs 1715	\@plateiv 1996	\@rawauthors
\@onelevel@sanitize	\@platelabeli .. 1878 648, 1439,
..... 456, 463	\@platelabelii . 1879	1531, 1691, 1836
\@orcid@icon 702	\@platelabeliii 1880	\@rawtitle
\@orcid@iconbig . 702	\@platelabeliv . 1881	. 475, 785, 1439,
\@outputaddresses	\@platelabelix . 1886	1531, 1691, 1836
.. 589, 596, 606, 607	\@platelabelv .. 1882	\@received
\@outputaddressesifneeded	\@platelabelvi . 1883	.. 696, 707, 986,
583, 605, 1313, 2434	\@platelabelvii 1884	988, 992, 1063, 1066
\@outputbox 151	\@platelabelviii 1885	\@redefinebibitem
\@outputplatelabeli	\@platelabelx .. 1887 1389, 2384
..... 1893	\@platelabelxi . 1888	\@reset@NAME
\@outputplatelabelii	\@platelabelxii 1889	.. 222, 245, 251, 256
..... 1894	\@platelabelxiii 1890	\@restonecolfalse
\@outputplatelabeliii	\@platelabelxiv 1891 1743
..... 1895	\@platelabelxv . 1892	\@restonecoltrue 1741
\@outputplatelabeliv	\@platerefi 1908	\@restoreindent .
..... 1896	\@platerefii ... 1909 120, 122
\@outputplatelabelix	\@platerefiii .. 1910	\@resumen 445, 1007, 1075
..... 1901	\@platerefiv ... 1911	\@reuniondate ...
\@outputplatelabelv	\@platerefix ... 1916 721, 723, 1800
..... 1897	\@platerefv 1912	\@reunionplace ..
\@outputplatelabelvi	\@platerefvi ... 1913 720, 723, 1800
..... 1898	\@platerefvii .. 1914	\@reviewarticlefalse
\@outputplatelabelvii	\@platerefviii . 1915 19
..... 1899	\@platerefx 1917	\@reviewarticletrue
\@outputplatelabelviii	\@platerefxi ... 1918 1029
..... 1900	\@platerefxii .. 1919	

\@rmaaArg . 172, 561, 562, 1453, 1454, 1457, 1588, 1589	\@startsection 1082, 1087, 1091, 1095, 1099	\@year 420, 426, 429, 436, 437, 692, 707, 782, 2103
\@rmaaBibArg 1353, 1395, 1396, 1399	\@starttoc 887, 1032, 1036, 1508, 1788, 1798	\[..... 2658 \\ 436, 439, 488, 491, 767,
\@rmaaEmpty 172, 562, 854, 869, 923, 955, 1063, 1067, 1362, 1376, 1396, 1454, 1589, 1679	\@suppressfulladdressesfalse 53 \@suppressfulladdressestrue 79, 580	802–804, 813, 1211, 1267, 1271, 1279, 1281, 1506, 1706, 1756, 1762, 1769, 1854, 2444, 2633, 2642, 2658, 2663, 2664, 2668, 2674, 2679, 2695
\@rmaaSpace 1353, 1399	\@svsec 1109, 1114, 1127, 1147	
\@rmaacitename 1535, 1536	\@svsechd 1146	
\@rmcitemapfalse 45, 1586	\@tablecols 1264, 1275, 1281	\{ 816 \} 816
\@rmcitemaptrue ... 1537	\@tempa 2236, 2237	
\@rmtwocolfalse 61, 65, 95, 934	\@tempboxa 1187, 1188, 1192, 1202, 1203, 1206, 1774, 1776, 1778	\] 2658 \^ 814, 815 _ 791, 815 \` 682, 846
\@rmtwocoltrue .. 37, 68, 71, 78, 94, 935	\@tempdima 186–188, 1042, 1047	\ 2082 \~ . 470, 682, 783, 816, 846, 1867, 2038, 2057
\@roman 123, 124	\@tempskipa 1124, 1125	
\@rottabcapwidth 1200, 1204, 1206, 1210	\@tempswafalse 2414, 2420, 2426	Numbers
\@sanitize 2070, 2071, 2079	\@tempswatrue 2411, 2417, 2423	\1 2663, 2664, 2668 \2 2668
\@scriptsize 2249, 2260	\@thanks .. 499, 954, 962, 1073, 1465, 1482	
\@seccntformat 1106, 1114	\@thefnmark 939, 940, 942	_ 435, 519, 520, 813, 1267, 1756, 2014, 2100, 2101, 2104, 2390, 2404, 2633, 2658, 2659, 2674, 2693, 2694
\@secpenalty ... 1040	\@tiny 2250, 2261	
\@sect 1107	\@title 483, 962, 976, 1060, 1420, 1459, 1480, 1693, 1719	
\@sessiontitlepagesfalse 171	\@titlevisiblefalse 1675	
\@sessiontitlepagetrue 1627	\@titlevisibletrue 47, 1685	A
\@set@scalable@length .. 198, 260, 262, 268–277, 286–293	\@topnum 950	\aap 2117, 2156 \aapr 2118 \aaps 2119
\@setminipage .. 1257	\@unexpandable@protect 177	\abovecaptionskip 1186
\@setresumenfalse 467	\@volume 434, 685, 707, 782, 2103	\abovecaptionskipScale 335
\@setresumentrue 449	\@volumen 687, 707, 1756	\aboveparaskip 264, 1096, 1100
\@shortauthor ... 411, 546, 2003, 2004	\@warning 2405	\aboveparaskip@set@SCALE 299, 310
\@shorttitle 412, 546, 1638, 2005	\@whilenum 1958	\aboveparaskipScale 326
\@shortvrbinfobin 2033, 2046, 2051, 2062	\@width 1467	
\@small 2246, 2258	\@writeabstract 1446, 1475, 1476	
	\@xsect 1157	

\abovesections	264, 1083, 1088, 1092	\ADS@authorinitial 677, 769	\Affil 851
\abovesections@set@Scale 297, 308	\ADS@authors 678, 788,	\affil 487, 960
\abovesections@Scale 324	\ADS@BibCode 769, 867	\afterassignment	180
\abstract	103, 445, 1444	\ADS@closefile	894, 906	\afterbibliostep	... 1299, 1307, 2429
\abstractsADS	.. 1427	\ADS@copyright	789, 878	\afterkwdskip	... 1025, 1028
\AcceptedDate	... 684	\ADS@doi	.. 700, 777, 879	\aj 2110
\acknowledgements 2107	\ADS@dumpdata	... 861, 922, 1486	\Alph 855, 857
\acknowledgments 2106, 2107	\ADS@firstpage	.. 769, 782, 912, 1463	\altaffil 492, 960
\active 2038,	\ADS@fulldate	789, 875	\altaffilmark	... 495, 1507, 1770, 1855
\add@special	2034, 2066	\ADS@journal	.. 769, 791	\altaffiltext	... 495
\addcontentsline 1132, 1140,	\ADS@journalname 778, 874	\and 491
	1149, 1252, 1438,	\ADS@keywords	... 511, 515,	\AnotherLinefalse	
	1478, 1529, 1600,		538, 785, 881, 1452	\AnotherLinetrue	812
	1690, 1720, 1835	\ADS@kwdskip	.. 502, 515	\ao 2115, 2159
\addkeyword 504	\ADS@lastpage	... 782, 789, 876, 930	\apj 2112
\addpenalty 1040	\ADS@number	791, 792, 797	\apjl 2113, 2157
\addtocontents	.. 886, 1439, 1531,	\ADS@openfile	861, 1806	\apjlett 2157
	1601, 1673, 1691,	\ADS@postamble	894, 899	\apjs 2114, 2158
	1800–1803, 1836	\ADS@preamble	893, 895	\apjsupp 2158
\addtocounter 505, 927, 931,	\ADS@references 800,	\aplett 2141
	1267, 1363, 1366,		823, 883, 1451, 1581	appendices (environ-	
	1377, 1380, 1397,	\ADS@sanitize	480,	ment) 1158
	1400, 1528, 1658,		511, 515, 517,	appendix (environ-	
	1720, 1959, 1967,		870, 872, 877, 882	ment) 1167
	1968, 1993, 2009	\ADS@title 482, 785, 877, 1462	\applopt 2159
\addtolength 187, 189,	\ADS@url 789, 880	\apspr 2142
	193, 353, 354,	\ADS@volume	686, 769, 791	\apss 2116
	356, 357, 618,	\ADS@website 789	\araa 2111
	626, 627, 1018,	\ADS@WRITE 867, 889, 893, 894	\arabic 741, 956, 1163, 1172
	1728, 1731, 1732	\ADS@write 861	\arcdeg	.. 534, 2177, 2180
\addvspace 1041	\ADS@year 693,	\arcmin 2178, 2181
\adjustfinalcols	606		769, 793, 795, 799	\arcsec 2179, 2182
\ADS@abstract	452,	\ADS@field 861,	\arraystretch	.. 1262
	456, 461, 463,		863, 867, 868,	\article 1565
	785, 882, 921, 1445		870, 872, 874–	\ArticleDir 1631
\ADS@affil 489, 493, 497,		883, 2443, 2642	\articlename	.. 710,
	800, 870, 1450, 1579	\ADSnoexpand 459		791, 811, 929,
\ADS@affiliations		\ADSvfield	.. 862, 2445		1314, 1323–
	.. 842, 869, 872, 1580	\advance 1047		1328, 1331, 1332,
					1338, 1340, 1343,
					1353, 1364, 1367,
					1369, 1378, 1381,
					1383, 1398, 1401,
					1403, 1434, 1439,
					1531, 1540, 1568,

1597, 1608, 1680,	\bf 2405	\catcode 807,
1682, 1691, 1703,	\bfseries . 374, 375,	2036, 2038, 2044,
1737, 1803, 1832,	381, 383, 390,	2053, 2055, 2057
1836, 2397, 2403	395, 405, 750,	\cdots 2245
\askforoverwritefalse	753, 970, 1046,	\centering ... 978,
..... 2358	1098, 1102, 1620	1086, 1090, 1094,
\astap 2156	\bgroup 759	1198, 1209, 1210,
\AtBeginDocument	\bibfont 111	1219, 1228, 1236
... 907, 1315, 1322	\bibhang 114	\centerline . 1001,
\AtEndDocument 906, 908	\bibitem 1355,	1005, 1074, 1076,
\author 1465	1360, 1374, 1390,	1497, 1693, 1956
\AuthorADS 842	1394, 2379, 2448	\Changed 747
\azh 2120	\bibliographystyle	\changemargin .. 1283
 115	\changes 1286
B	\bibpunct 110	\char 767
\baas 2121	\bibsection 112	\circ 2177,
\backmatter 1669	\bibsep 113	2180, 2187, 2195
\backslash 176	\BibTeX 2087	\citation
\bain 2143	\bigskip 1339, 2394, 2398
\baselineskip ...	971, 1673, 2447, 2643	\cite 1316,
. 260, 627, 956, 1271	\boldabstract ... 460	1343, 1391, 2409
\baselinestretch 352	\boldmath	\ClassError 507
\batchfile 2328	381, 464, 1020, 1620	\ClassInfo 584, 1053,
\beforebibliostyle	\BoldSessionTitles	1324, 1326, 1328,
..... 1299, 1305 1628	1332, 1537, 1558
\begin 8, 762, 866, 897,	\boolean	\ClassWarning ...
975, 1059, 1209,	.. 259, 295, 391, 591, 595,
1210, 1219, 1228,	585, 588, 594, 599	600, 920, 921,
1236, 1290, 1350,	\box 151, 1192, 1778	924, 944, 948, 1540
1419, 1469, 1480,	\bv 2220, 2229	\ClassWarningNoLine
1495, 1620, 2092,	 467, 473, 543
2446, 2454, 2647	C	\cleardoublepage
\beginingroup 150, 810,	\c@equation 1520	1432, 1594, 1603,
848, 937, 1043,	\c@figure .. 1177, 1712	1612, 1653, 1663,
1126, 1159, 1168,	\c@page . 912, 1463, 1703	1670, 1793, 1830,
1254, 1470, 1488,	\c@plate 1939	1949, 1956, 2000
1522, 1677, 1738,	\c@plateloop ... 1940	\clearpage 596, 922,
2037, 2056, 2076	\c@secnumdepth ..	1432, 1473, 1594,
\belowcaptionskip	... 1108, 1133, 1150	1603, 1612, 1670,
..... 1194	\c@section	1696, 1791, 1830,
\belowparaskip 1162, 1171, 1711	1857, 1946, 1956
... 264, 1097, 1101	\c@subsection .. 1104	\closein 828
\belowparaskip@set@SCALE	\c@subsubsection 1105	\clubpenalty
..... 300, 311	\c@table ... 1176, 1713	366, 572, 1311, 2431
\belowsectionskip	\c@tocdepth	\CodelineIndex 5
264, 1084, 1089, 1093	... 1039, 1810, 1817	\Color . 2224, 2228–2231
\belowsectionskip@set@SCALE	\c@caption 1224, 1225,	\ColorOnlineOnly 1864
..... 298, 309	1229, 1232, 1233,	\columnsep 194
\belowsectionskipScale	1237, 1973, 1977	\columnwidth ... 2092
..... 325	\case 2204, 2211	\cos 525

\count	837–839	1118, 1119, 1121,	947, 951, 954,
\cs	767	1122, 1146, 1183,	955, 972, 987,
\csname ...	202–205,	1195, 1201, 1225,	1008, 1010, 1065,
207–210,	212–	1226, 1233, 1234,	1068, 1110, 1120,
215, 218, 220,		1250, 1351, 1353,	1133, 1139, 1145,
226–228,	230,	1394, 1535, 1971,	1150, 1184, 1190,
231, 233, 234,		1975, 2031, 2048,	1205, 1270, 1354,
236, 237, 239,		2062, 2066, 2072,	1365, 1368, 1373,
241, 246–248,		2073, 2077, 2106,	1379, 1382, 1399,
252–254, 257,		2109, 2160–2164,	1402, 1456, 1469,
1106, 1130, 1134,		2166, 2168, 2169,	1539, 1587, 1591,
1141, 1147, 1151,		2172, 2174, 2177–	1681, 1742, 1746,
1252, 1253, 1260,		2179, 2183–2190,	1748, 1757, 1783,
1963, 1995, 1997,		2200, 2204–2210,	1841, 1944, 2045,
1998, 2004, 2005,		2218–2222, 2244,	2050, 2074, 2078,
2014, 2015, 2020,		2328, 2379, 2381,	2103, 2104, 2239
2032, 2036, 2041,		2385, 2388–	\Email 850
2049, 2053, 2054,		2393, 2400, 2404,	\email 150
2060, 2392, 2406		2409, 2415, 2421	\empty 823
\CurrentOption .	96, 99	\DeleteShortVerb 2048	\EnableCrossrefs .. 5
		\discretionary . 1867	\end . 8, 764, 884, 900,
D		\do 1337,	1024, 1072, 1212,
\dblfloatsep@set@SCALE		1958, 2069, 2073,	1213, 1220, 1229,
..... 304, 315		2074, 2396, 2401	1237, 1298, 1344,
\dblfloatsepScale 333		\DocInput 8	1421, 1473, 1480,
\dbltextfloatsep@set@SCALE		\documentclass . 2,	1509, 1622, 2093,
..... 305, 316		896, 1533, 2440, 2638	2446, 2457, 2651
\dbltextfloatsepScale		\DOI 698	\end@dblfloat ...
..... 334		\dospecials 1243, 1249
\DeclareOption 2068, 2069, 2075	\end@float . 1240, 1246
.. 60, 63, 67, 70,		\doublerulesep . 1263	\EndBib 802, 820
73, 75, 77, 81, 83,			\endcsname 202–205,
85, 88, 90, 92, 94–99		E	207–210, 212–
\DeclareRobustCommand		\earth 2166, 2167	215, 218, 220,
..... 767,		\edef 514, 686,	226–228, 230,
2110–2155, 2165,		802–804, 930,	231, 233, 234,
2167, 2170, 2171,		1114, 1338, 1555,	236, 237, 239,
2176, 2180–2182,		2236, 2397, 2403	241, 246–248,
2191–2199, 2201,		\EditorSignature 1707	252–254, 257,
2211–2217, 2223,		\egroup 765	1106, 1130, 1134,
2224, 2228–2231,		\else 102, 105,	1141, 1147, 1151,
2233, 2243, 2245		106, 396, 422,	1252, 1253, 1260,
\def 7, 111,		510, 513, 514,	1963, 1995, 1997,
511, 515, 518–		564, 567, 601,	1998, 2004, 2005,
535, 663–665,		611, 612, 641,	2014, 2015, 2020,
682, 699, 700,		642, 678, 714,	2032, 2036, 2041,
719, 807, 847,		740, 752, 773,	2049, 2053, 2054,
849–851, 895,		823, 833–835,	2060, 2392, 2406
899, 939–941,		838–840, 906,	\endgroup 829,
1106, 1107, 1113,		911, 913, 923,	859, 958, 1050,

1129, 1166, 1175,	493, 497, 510,	<code>\firstletter</code> . 677, <u>682</u>
1261, 1473, 1487,	514, 516, 567,	<code>\floatsep@set@SCALE</code>
1562, 1696, 1794,	577, 595, 600, 301, 312
2043, 2061, 2080	601, 606, 611,	<code>\floatsepScale</code> .. 330
<code>\endlinechar</code> 817	624, 628, 635,	<code>\fm</code> 529, 2185, 2193
<code>\endlist</code> 575, 1313	641, 645, 646,	<code>\fnsymbol</code> 938
<code>\endpreamble</code> ... 2357	657, 677, 678,	<code>\fnum@figure</code> ... 1182
<code>\ensuremath</code> 175, 176,	714, 742, 745,	<code>\fnum@table</code> 1180, 1181
2085, 2086, 2162,	754, 756, 773,	<code>\footnoterule</code> ...
2165, 2167, 2180–	779, 781, 820, 1467, 1482
2182, 2191–2199,	821, 823–826,	<code>\footnotesize</code> .. 7,
2201, 2211, 2212,	836, 841, 886,	750, 753, 1482,
2223, 2225, 2244	909, 911, 913,	2248, 2258, 2259
environments:	920–924, 944,	<code>\footnotetext</code> 500, 1466
appendices .. <u>1158</u>	948, 951, 953,	<code>\footskip</code> 196
appendix <u>1167</u>	954, 957, 974,	<code>\fp</code> 2190, 2199
<code>\equal</code> 854, 869	989, 990, 993,	<code>\fps@figure</code> 360
<code>\errmessage</code> 152	996, 1003, 1007,	<code>\fps@table</code> 361
<code>\etal</code> 2105	1008, 1021, 1023,	<code>\frac</code> 2204, 2211
<code>\evensidemargin</code> .	1051, 1053, 1070,	<code>\framebox</code> 750, 753
..... 190, 355	1071, 1116, 1123,	<code>\frenchspacing</code> . 1306
<code>\ExecuteOptions</code> . 100	1135, 1137, 1143,	<code>\from</code> 2360–
<code>\exhyphenpenalty</code> 1849	1144, 1152, 1154,	2364, 2367–2370
<code>\expandafter</code> . 202–	1156, 1184, 1185,	<code>\frontlabel</code>
205, 207–210,	1193, 1207, 1258, 911, 1696,
212–215, 218,	1270, 1304, 1324,	1697, 1700, 1790
220, 226, 227,	1326, 1328, 1332,	<code>\frontmatter</code> 1649, 1651
230, 233, 236,	1339, 1353, 1370,	<code>\frontsection</code> .. <u>1675</u>
246, 247, 252,	1384, 1387, 1388,	<code>\fs</code> 530, 2186, 2194
253, 665, 666,	1406, 1429, 1432,	<code>\fulladdresses</code> .. <u>552</u>
802–804, 1338,	1440, 1458, 1468,	
1555, 1997, 2004,	1469, 1473, 1479,	
2005, 2032, 2035,	1486, 1514, 1540,	G
2040, 2049, 2054,	1541, 1558, 1587,	<code>\G@refundefinedtrue</code>
2059, 2064, 2068,	1593, 1594, 1613, 1340
2070, 2397, 2403	1662, 1683, 1694,	<code>\ga</code> 2203
	1744, 1746–1748,	<code>\gca</code> 2145
	1763, 1786, 1789,	<code>\gdef</code> 218, 220,
F	1815, 1822, 1841,	226, 246, 247,
<code>\farc</code> .. 532, 2188, 2196	1842, 1862, 1944,	252, 253, 461,
<code>\farcs</code>	2047, 2061, 2074,	489, 493, 497,
533, 2189, 2197, 2198	2078, 2094, 2103,	511, 962, 1449–
<code>\fcp</code> 2144	2104, 2226, 2241,	1452, 1524, 1578–
<code>\fd</code> 527, 2183, 2191	2383, 2388, 2389,	1581, 1987, 1997,
<code>\fdg</code> 531, 2187, 2195	2394, 2398, 2430	2042, 2068, 2070
<code>\fh</code> 528, 2184, 2192	<code>\figcaption</code> 1970, 1982	<code>\generate</code> .. 2359, 2366
<code>\fi</code> ... 102, 106, 107,	<code>\figurename</code> 1178	<code>\global</code> .. 950, 1191,
116, 359, 364,	<code>\file</code> 2360–	1351, 1352, 2040,
398, 405, 424,	2364, 2367–2370	2044, 2053, 2054,
427, 430, 442,	<code>\FinalFigure</code> 559	2059, 2385, 2386
456, 463, 489,		

\goodbreak	\HyperTOCmeeting	\if@journal 22,431,1594
... 606, 1483, 1818 1409, 1800	\if@manuscript ..
\graphicspath .. 1631	\HyperTOCpart 28, 351,
\grl 2146 1409, 1601	428, 951, 954, 991
\gta 2174	\HyperTOCpreamble	\if@minipage ... 1256
\gtrsim 2169, 2171, 2203 1409, 1802	\if@natbib
		. 42, 108, 1353, 1359
H	I	\if@needaddresses 154
\hangafter 2379	\i 438, 682,	\if@newstyle .. 54,
\hangindent 1826, 2379	780, 795, 846, 2098	364, 1003, 1007,
\hb@xt@ . 177, 1049, 1192	\iaucirc 2140	1185, 1747, 1842
\hbadness 367	\ibidrule .. 2101, 2496	\if@noexpandADS .
\hbox 184,	\if@abstractpresent 168, 456, 463
939, 942, 1196, 48, 998	\if@preprint
1202, 1778, 2089,	\if@abstractsads 34, 417, 985
2164, 2166, 2168– 1425, 1486	\if@printbanner .
2179, 2183–	\if@arenotes 731 50, 1751
2190, 2200, 2204,	\if@biblist ... 38, 635	\if@printdates 24, 983
2205, 2218–2222	\if@bigfont 30	\if@proceedings .
\headsep 195	\if@boldkeywords	... 26, 419, 714,
\hfil . 411, 412, 415,	58, 394, 405, 510, 514	773, 779, 781,
416, 420, 423,	\if@book ... 40, 101,	1184, 1270, 1746,
426, 429, 436,	601, 611, 641,	1748, 1841, 2103
439, 440, 1049,	886, 906, 913,	\if@proof . 20, 737, 756
1192, 1196, 1635,	922, 1304, 1429,	\if@restonecol . 1789
1636, 1638, 1643,	1432, 1437, 1468,	\if@reviewarticle
1644, 1820, 2014,	1469, 1473, 1477, 18, 968, 1138
2015, 2020, 2021	1486, 1492, 1517,	\if@rmcite 44
\hfill 1513,	1944, 2104, 2430	\if@rmtwocol .. 36,
1778, 1813, 1820	\if@debug	102, 106, 943, 1662
\hfuzz 369	... 56, 595, 600,	\if@sessiontitlepages
\href 704, 706	619, 628, 645, 170, 1605
\hrule 1467	920, 921, 924,	\if@setresumen ..
\hrulefill 1483	944, 948, 1053, 445, 1008
\hsize . 1188, 1192, 1196	1324, 1326, 1328,	\if@suppressfulladdresses
\hskip 658, 659, 669,	1332, 1540, 1558 52, 610, 1587
670, 1048, 1106,	\if@fileswh .. 1339,	\if@tempswa 2388, 2389
1127, 1146, 1215,	2380, 2394, 2398	\if@titlevisible
1500, 1513, 1778	\if@firstaffil 162, 489 46, 1692
\hspace 635, 940, 1730,	\if@firstaltaffil	\if@twocolumn 606, 1740
1733, 1753, 1759 164, 493, 497	\if@AnotherLine 805, 827
\hss 939, 942, 1049	\if@firstauthor .	\ifcat 2237
\Huge .. 1620, 2255, 2266 160, 677, 678	\ifdef 1329
\huge .. 2254, 2265, 2266	\if@firstkwd . 166, 509	\ifdim ... 630, 1125,
\hypersetup 147	\if@frontmatter .	1188, 1203, 1776
\HyperTOCeditors 156, 911	\ifeof 821
..... 1409, 1801	\if@guide 32,	\IfFileExists ...
\HyperTOCEntry ..	425, 994, 1010,	.. 119, 127, 132, 138
1409, 1439, 1531,	1131, 1148, 2029	\ifInBib 806, 822
1691, 1803, 1836	\if@inpreamble 158, 740	\ifinner 749

<code>\ifnum</code> 832–834, 837–839, 1039, 1108, 1117, 1133, 1139, 1150, 1810, 1817, 2055, 2074, 2078	<code>\itshape</code> .. 376, 377, 388, 401, 407, 970, 1090, 1094, 1122	<code>\let</code> .. 120, 178, 179, 182, 482, 785, 932, 933, 960, 961, 1109, 1112, 1115, 1224, 1229, 1232, 1237, 1316–1320, 1330, 1355, 1390–1393, 1465, 1553, 1853, 2040, 2054, 2059, 2107, 2108, 2156–2159, 2202, 2203, 2246–2255, 2409–2426
<code>\ifthenelse</code> .. 259, 295, 391, 506, 585, 588, 594, 599, 853, 854, 869	J <code>\jcp</code> 2147 <code>\jgr</code> 2148 <code>\jnl@style</code> . 2108, 2109 <code>\jobname</code> 892 <code>\jqsrt</code> 2149 <code>\jrasc</code> 2122	<code>\Line</code> 819, 820, 823, 825, 826
<code>\ifx</code> .. 562, 567, 657, 820, 823, 825, 826, 923, 955, 1063, 1067, 1362, 1365, 1376, 1379, 1396, 1399, 1454, 1536, 1589, 1679, 2032, 2049, 2226	K <code>\kern</code> 1467, 2087–2089, 2234 <code>\keywords</code> 501 <code>\KillAllAccents</code> . 682	<code>\lineskip</code> 979 <code>\linewidth</code> 1017, 1619, 1623
<code>\ignorespaces</code> ... 448, 451, 1253, 1260	L <code>\l@abstract</code> 1511 <code>\l@chapter</code> 1809 <code>\l@part</code> 1816 <code>\l@section</code> 1038 <code>\la</code> 2202 <code>\label</code> 757, 911, 1320, 1327, 1473, 1609, 1611, 1857, 1878–1892 <code>\label@in@display</code> 1329–1331 <code>\labelsep</code> ... 570, 1309 <code>\labelwidth</code> . 570, 1309 <code>\langle</code> . 521, 2085, 2086 <code>\LARGE</code> . 2253, 2264, 2265 <code>\Large</code> 375, 2252, 2263, 2264 <code>\large</code> 381, 970, 2251, 2262, 2263 <code>\latexonecolumn</code> 932, 934, 1652 <code>\latextwocolumn</code> 933, 935 <code>\lbibcite</code> 1351, 2382, 2385 <code>\lccode</code> 2038, 2057 <code>\leavevmode</code> 1046 <code>\leftmargin</code> .. 570, 635, 1292, 1309, 2092 <code>\leftskip</code> .. 1047, 1048 <code>\lessim</code> 2168, 2170, 2202	<code>\list</code> 570, 1309 <code>\listofabstracts</code> 1473, 1494 <code>\listofauthors</code> .. 648, 1436, 1687, 1834 <code>\listparindent</code> . 1294 <code>\llap</code> 412, 2021 <code>\LoadClass</code> ... 102, 106 <code>\log</code> 523 <code>\long</code> . 664, 941, 1183, 1195, 1201, 1250 <code>\loop</code> 818 <code>\lower</code> 2089, 2168–2172, 2174 <code>\lowercase</code> 1272, 2039, 2058 <code>\lta</code> 2172
<code>\immediate</code> ... 811, 828, 888, 889, 892, 928, 1339, 2382, 2394, 2398		M <code>\m@ne</code> 1810, 1817 <code>\m@th</code> 939, 942 <code>\MacroFont</code> 7 <code>\mainmatter</code> 1649, 1660 <code>\make@session@title</code> 1610, 1615 <code>\makeatletter</code> ... 1538, 2455, 2648 <code>\makeatother</code> ... 1538 <code>\makebox</code> 750 <code>\makeindex</code> 913 <code>\makeOther</code> 807, 807, 813–816
<code>\InBibfalse</code> .. 812, 820		
<code>\InBibtrue</code> ... 825, 826		
<code>\includegraphics</code> 702, 703, 1753, 1759		
<code>\index</code> 658, 669		
<code>\indexauthor</code> 653, 1847		
<code>\indexauthor@deferlist</code> 663, 666, 667, 675, 914, 915		
<code>\indexauthorADS</code> 661, 673, 676		
<code>\indexspace</code> 1827, 1844		
<code>\input</code> 1538, 1597, 2295, 2303, 2307, 2319, 2329, 2439, 2456, 2650		
<code>\interlinepenalty</code> 1128		
<code>\intextsep@set@SCALE</code> 303, 314		
<code>\intextsepScale</code> . 332		
<code>\ion</code> 511, 515, 2232, 2233, 2646		
<code>\item</code> 744, 1298, 1853, 2093		
<code>\itemindent</code> 570, 1295, 1309		
<code>\itemsep</code> 571, 1310		

<code>\MakeShortVerb ..</code>	466, 473, 475–	1222, 1230, 1288,
..... 2031, 2082	478, 487, 492,	1430, 1521, 1676,
<code>\maketitle ...</code> 936, 961	495, 496, 501,	2091, 2447, 2643
<code>\MakeUpperCase ..</code>	502, 504, 517,	<code>\newif ...</code> 18, 20, 22,
..... 174, 379,	537, 541, 542,	24, 26, 28, 30, 32,
381, 383, 384,	546, 548, 550,	34, 36, 38, 40, 42,
395, 547, 549,	551, 558–560,	44, 46, 48, 50, 52,
1180, 1198, 1202,	579–583, 605–	54, 56, 58, 154,
1211, 1497, 2085	607, 648–650,	156, 158, 160,
<code>\marginpar</code> 753	653–655, 676,	162, 164, 166,
<code>\mathchar ..</code> 2172–2175	682–684, 689–	168, 170, 445,
<code>\mathrel</code> 2168–2172, 2174	691, 696–698,	731, 805, 806, 1425
<code>\mathrm</code> 518,	702–705, 707–	<code>\newlabel</code> 929, 1703, 1874
1269, 1270, 2191–	709, 711–713,	<code>\newlabels</code> 2671
2194, 2201, 2244	715–718, 720–	<code>\newlength</code> 202, 204,
<code>\maxdimen</code> 369, 370	730, 735, 736,	207, 209, 212,
<code>\mbox</code> 390, 2234	747, 748, 756–	214, 264–267,
<code>\medskip ...</code> 1164, 1173	758, 769, 770,	278–285, 348,
<code>\memras</code> 2123	772–778, 786–	552, 553, 963,
<code>\memsai</code> 2150	790, 792–795,	1028, 1200, 1282,
<code>\micron</code> 2200, 2201	797–801, 809,	1299, 1301, 1553,
<code>\mkern</code> 2188,	831, 845, 861,	1554, 1725–1727,
2194, 2196, 2197	862, 864, 886–	1729, 1731, 1732
<code>\mnras</code> 2124	890, 894, 910,	<code>\newpage</code> 606,
<code>\MSextraHmargin .</code>	919, 926, 964,	949, 966, 1054, 1416
.. 348, 349, 353, 354	1029, 1030, 1034,	<code>\newread</code> 808
<code>\MSextramargin ..</code> 348	1052, 1264–1266,	<code>\newsavebox</code> 554
<code>\MSextraVmargin .</code>	1269–1274, 1280,	<code>\newwrite</code> 891
.. 348, 350, 356, 357	1314, 1356, 1357,	<code>\nobreak</code> 1049, 1482,
<code>\mu</code> 2200, 2201	1389, 1409–1413,	1513, 1778, 1822
<code>\multicolumn</code>	1415, 1427, 1476,	<code>\nocite</code> 1317, 1336
... 1267, 1275, 1281	1494, 1511, 1519,	<code>\nodata</code> 2245
N	1560, 1565, 1598,	<code>\noexpand</code> 152,
<code>\NAME</code> 224	1615, 1627, 1628,	183, 481, 649,
<code>\NAME@set@SCALE .</code> 250	1631–1634, 1641,	652, 669, 670,
<code>\NAMEScale</code> 244	1675, 1700, 1707,	1113, 2074, 2078
<code>\nat</code> 2139	1715, 1716, 1730,	<code>\noindent</code> 464,
<code>\NeedsTeXFormat ..</code> 15	1733, 1735, 1864,	606, 635, 941,
<code>\newcommand ..</code> 11–	1878–1922, 1942,	1003, 1007, 1019,
14, 103, 104,	1970, 1974, 1979,	1075, 1077, 1078,
150, 172, 173,	1991, 2012, 2084,	1466, 1482, 1483
198, 294, 320,	2086, 2097–	<code>\nonstopmode</code> 1548,
322, 328, 337,	2102, 2105, 2256,	2303, 2307, 2319
362, 363, 371–	2443, 2445, 2642	<code>\nopostamble ...</code> 2366
378, 380, 382,	<code>\newcounter</code> 503, 733,	<code>\nopreamble</code> 2366
384–387, 389,	842, 843, 1358,	<code>\noprintdates ...</code> 581
392, 400, 403,	1871, 1872, 1923–	<code>\normalsize</code> 371–374,
406, 408, 414,	1937, 2242, 2645	376, 377, 379,
446, 459, 460,	<code>\newenvironment .</code>	383, 404, 407,
 1158, 1218,	566, 1086, 1090,

1094, 1098, 1102, 1259, 1313, 2247, 2257, 2262, 2434	\openout 892	\parfillskip ... 1045
\not 588	\oplus 2166, 2167	\parindent 6, 197, 941, 1000, 1044, 1057, 1099, 1294, 1295, 1501, 1617, 1848, 1951, 2433, 2449, 2644
\Note 736	\or 588	\parsep . 571, 1296, 1310
\NoteLabel 757	\ORCIDiD 702, 849	\parskip . 259, 1296, 1502, 1503, 1695, 1707, 1845, 2433
\NoteMark 741, 748, 756, 956	\ORCIDiDfull 702	\pasj 2132
\NotesList 735, 743, 763, 923, 924, 955	\org@@roman 124	\pasp 2131
\notitle 1675	\outputplates ... 1875	\PassOptionsToClass 62, 66, 69, 72, 74, 80, 96, 99
\nphysa 2151	\outputfulladdresses 605	\patchcmd 151
\null 570, 601, 611, 967, 1058, 1309, 1417, 1513, 1956, 1999	\OutputNotes . 758, 923	\pcite 1392, 2415
\numberline . 1134, 1141, 1151, 1253	\outputplates 1550, 1870, 1942, 2006	\pdfminorversion 148
O	P	\penalty .. 659, 670, 1500, 1512, 1513, 1778, 1826, 1827
\oddsidemargin 188–190, 354, 355	\p@ 260, 262, 272–277, 1041, 1467, 1502, 1503, 1811, 1827, 1845	\phantom ... 2160–2163
\odot 2164, 2165	\PackageInfo ... 2063	\phd 2161
\oldbitem 1353, 1390, 1398, 1401, 1403, 1405	\PadToFourWithDots 686, 771, 831	\phm 2163
\oldcaption 1224, 1227, 1229, 1232, 1235, 1237	\pagegoal 622, 630	\phn 2160
\oldcite 1314, 1343, 1391	\pagenumbering 1656, 1666	\phs 2162
\oldlabel ... 1314, 1327, 1878–1907	\pageref ... 1319, 1325	\physrep 2152
\oldlabel@in@display 1330, 1331	\pagestyle 444, 1441, 1525, 1650, 1657, 1661, 1667, 1670, 1837, 1948, 1956, 1965	\physscr 2153
\oldnewlength 1553, 1557	\pagetotal ... 621, 626	\plainion 511, 515, 2243
\oldnocite 1314	\paperwidth 186	\planss 2154
\oldpageref .. 710, 1314, 1325, 1908– 1922, 2104, 2451	\par 381, 936, 976, 981, 1001, 1005, 1026, 1049, 1060, 1061, 1071, 1075, 1077– 1079, 1128, 1158, 1167, 1189, 1198, 1251, 1260, 1420, 1466, 1480, 1482, 1483, 1512, 1730, 1733, 1785, 1826, 1827, 1963, 2379, 2447, 2448, 2643	\plate 1979
\oldpcite .. 1389, 1392	\paragraph 1082	\pra 2125
\oldref 1314, 1323	\parbox 433, 614, 978, 999, 1013, 1019, 1276, 1277, 1730, 1733, 1785, 1813, 1820	\prb 2126
\oldscite .. 1389, 1393		\prc 2127
\onecolumn ... 760, 932, 934, 1562, 1606, 1741, 1950		\prd 2128
\onehalf ... 2206, 2213		\pre 2129
\onequarter 2209, 2216		\preamble 2330
\onethird .. 2207, 2214		\prime .. 2178, 2179, 2181, 2182, 2188, 2189, 2196–2198
\openin 811		\PrintChanges 8
		\printdates 581
		\PrintIndex 8
		\prl 2130
		\ProcessOptions . 100
		\procs pie 2155
		\protect .. 178, 179, 182, 183, 390, 500, 744, 757,

1112, 1113, 1115,	1146, 1312, 1409–	1465–1467, 1500,
1134, 1141, 1151,	1413, 1502, 1503,	1506, 1507, 1520,
1253, 1438, 1439,	1506, 1507, 1519,	1533, 1534, 1543–
1478, 1530, 1531,	1532, 1533, 1543–	1546, 1548–1550,
1601, 1690, 1691,	1546, 1548–1550,	1554, 1560, 1568,
1800–1803, 1835,	1559, 1646, 1647,	1588, 1590, 1592,
1836, 2244, 2381	1769–1771, 1827,	1608, 1629, 1631,
\protected@write 1702	1845, 1854–	1635, 1636, 1638,
\protected@xdef .	1856, 2016, 2018,	1639, 1643, 1644,
..... 177, 499,	2032, 2049, 2054,	1646, 1647, 1651,
667, 677, 678, 743	2410, 2413, 2416,	1660, 1669, 1678,
\providecommand .	2419, 2432, 2434	1680, 1682, 1711–
..... 174–177,	\rem@special	1713, 1718, 1719,
182–184, 1560, 2087	... 2052, 2067, 2072	1736, 1737, 1767,
\ProvidesClass ... 16	\renewcommand ...	1769–1771, 1809,
\ps@rmaa 408, 1633 112, 124,	1816, 1826, 1827,
\ps@rmaafirstpage 414	245, 251, 352,	1832, 1854–
\ps@rmaafront ...	360, 361, 364,	1856, 1939, 1940,
..... 1633, 1634	409–412, 415,	1972, 1976, 1991,
\ps@rmaafrontfirstpage	416, 418, 426,	2014, 2016, 2018,
..... 1641	429, 432, 443,	2020, 2257–2266,
\ps@rmaaplate .. 2012	447, 448, 450–	2448, 2450, 2646
	452, 462, 479,	\renewenvironment
Q	481, 483–485,	1167, 1238, 1241,
\qjras 2133	491, 510, 538,	1244, 1247, 1303,
	539, 547, 549,	1526, 1828, 2428
R	559, 561, 563,	\repeat 827
\raggedleft 1785	565, 651, 652,	\RequirePackage .
\raggedright	656, 657, 685,	.. 109, 117, 118,
.. 358, 395, 397, 405	687, 689, 692–	121, 128, 133,
\raise 2170,	694, 696, 697,	139, 144–146, 1429
2171, 2173, 2175	723, 724, 726,	\RereadBiblio ...
\raisebox 750	728, 730, 769,	... 808, 1304, 2430
\rangle . 522, 2085, 2086	797–799, 863,	\RescaleFloatLengths
\read 819	934–936, 938, 320
\ReceivedDate ... 684	965, 1038, 1082,	\RescaleLengths . 320
\RecordChanges 5	1087, 1091, 1095,	\RescaleSecLengths
\ref 756, 1318, 1323	1099, 1104, 1105, 320
\ref@jnl ... 2109–2155	1162, 1163, 1171,	\RescaleTitleLengths
\RefNote 756	1172, 1176–1182, 320
\refstepcounter 1111	1226, 1234, 1239,	\reserved@a
\relax 100,	1242, 1245, 1248,	... 1555, 1556, 1558
103, 104, 124,	1262, 1264, 1323,	\reset@font
409, 410, 558,	1325, 1327, 1331, 1086, 1090,
567, 573, 663,	1336, 1343, 1360,	1094, 1098, 1102
756, 807, 817,	1361, 1371, 1374,	\restore@protect 177
861, 862, 892,	1375, 1385, 1395,	\resumen 445
960, 961, 1121,	1434, 1444–1446,	\reviewarticle . 1029
1124, 1126, 1127,	1448, 1453, 1455,	\reviewlof 1029
	1457, 1459–1462,	\reviewname .. 964, 970

\reviewtoc	1029	\rmaa@YearStyle .	\selectlanguage .	447
\rightline .	1707, 1708	\session	1598
\rightmargin . . .	1293	420, 426, 429, 436	\SessionTitlePages	
\rightskip .	1044, 1850	\RMAAbannerimage	1627
\rlap 411, 2168–2171, 2176		... 1735, 1753, 1759	\set@display@protect	
\rm . 2108, 2183–2186,		\rmaa@bib	888
2190, 2199, 2244		\rmaa@IndexAuthorStyle	\SetADSBibCode ..	769
\RMAA .. 2097, 2100, 2103		\setbox	1202
\rmaa@AbstractHeaderStyle		\rmaa@IndexTitle .	\SetConfTitle	724, 1546
....	371, 1001,	. 475, 659, 670, 1461	\setcounter ..	503,
1005, 1074, 1076		\RMAAlong . . .	690, 734, 917,	
\rmaa@AbstractWidthFrac		\RMAASC 2099, 2103, 2451	959, 1103, 1160,	
.....	362, 999	\RMAASClong .	1161, 1169, 1170,	
\rmaa@AffilStyle		\rmaa@TOCauthors .	1471, 1489, 1570–	
.....	371, 488	648, 1438, 1478,	1577, 1943, 1961,	
\rmaa@AuthorWidthFrac		1530, 1690, 1835	2007, 2243, 2646	
.....	362, 978	\rmaa@TOCAuthorStyle	\SetEditores	728
\rmaa@date 12, 14, 16, 995		\SetEditors	726
\rmaa@FrontSecStyle		\rmArg	\SetFirstPage	684, 1543
.....	382, 1693	\rmDate	\setlength .	6, 113,
\rmaa@IndexTitleStyle		\rmfamily . . .	114, 185, 186,	
. 384, 477, 485, 1461		374, 377, 379,	188, 190–192,	
\rmaa@JournalNameStyle		381, 383, 2087, 2235	194–197, 203,	
.....	371, 713	\rmVersion	205, 208, 210,	
\rmaa@KeywordHeaderStyle		\robustify	213, 215, 223,	
.....	391, 541	Roman	224, 227, 230,	
\rmaa@KeywordStyle		\roman .. 1961, 1963,	233, 236, 349,	
391, 1020, 1078, 1079		1995, 1997, 1998,	350, 355, 369,	
\rmaa@lastpagelabel		2004, 2005, 2007,	370, 1000, 1017,	
.....	922, 926	2014, 2015, 2020	1028, 1042, 1057,	
\rmaa@PagesStyle		\rotatebox	1204, 1206, 1263,	
.....	371, 435	\rule .. 1619, 1623, 2101	1291–1296, 1300,	
\rmaa@ReceivedStyle			1302, 1617, 1695,	
.....	371, 986,		1725–1727, 1729,	
988, 992, 995, 1062			1731, 1732, 2092,	
\rmaa@TitleStyle			2433, 2449, 2644	
....	380, 483, 1719		\SetMes	730
\rmaa@TOCPartStyle			\SetMonthNumeric	789
... 384, 1600, 1629			\SetMSnumber	684
\rmaa@TOCTitleStyle			\SetNumber	797
.....	384, 476,		\SetReunion	723
484, 1459, 1460, 1629			\settodepth	617
\rmaa@version . . .			\settoheight	616
....	11, 13, 16, 995		\settowidth	1016
\rmaa@VolumenStyle			\SetVolume ..	684, 1545
.....	371, 687,		\SetWebsite	789
694, 708, 712, 730			\SetYear	684, 1544
\rmaa@VolumeStyle			\sfcode .	573, 1312, 2432
.....	371, 434		\sffamily	375

<code>\shortauthor</code>	2064, 2065, 2381,	<code>\tf@biblio</code> ... 808,
546, 1435, 1688,	2382, 2394, 2398	811, 819, 821, 828
1749, 1833, 1857	<code>\subparagraph</code> .. 1082	<code>\thanks</code> 494, 960
<code>\shortname</code> 1675	<code>\subsection</code> 1082	<code>\the</code> .. 620–622, 628,
<code>\shorttitle</code>	<code>\subsubsection</code> . 1082	668, 669, 711, 2036
.... 546, 1435,	<code>\sun</code> 2164, 2165	<code>\thebibliography</code> 1303
1688, 1749, 1833	<code>\suppressfulladdresses</code>	<code>\theequation</code>
<code>\sim</code> 2168–2171 580	... 1163, 1172, 1520
<code>\sin</code> 524		<code>\thefigure</code>
<code>\skytel</code> 2134	T	... 1177, 1182, 1712
<code>\slantfrac</code> .. 2205–	<code>\tabcaption</code> 1974	<code>\thefootnote</code> 938
2210, 2212–2217	<code>\tabcaptioncontinued</code>	<code>\thekwdcounter</code> .. 506
<code>\sloppy</code> . 572, 1311, 2431 1264	<code>\thepage</code> .. 411, 412,
<code>\small</code> 111, 393, 401,	<code>\tablecols</code> 1264	415, 416, 929,
437, 440, 1184,	<code>\tablename</code> . 1179, 1180	930, 1635, 1636,
1185, 1270, 1276,	<code>\tablenote</code> 1269	1643, 1644, 2405
1277, 1281, 1308,	<code>\tablenotemark</code> . 1269	<code>\thepart</code> 1608
1746, 1747, 1841,	<code>\tablenoteskip</code> . 1269	<code>\theplate</code> 1939
1842, 2244, 2246,	<code>\tableofcontents</code> 1736	<code>\theplateloop</code> ...
2256–2258, 2429	<code>\tabnotemark</code> ... 1272 1940, 2021
<code>\smaller</code> 2170, 2171,	<code>\tabnotetext</code> ... 1272	<code>\thermaabib</code>
2235, 2256–2266	<code>\tabnotetextTWO</code> 1272	1364, 1367, 1378,
<code>\smallskip</code> 969	<code>\tabnotewidth</code> 1276,	1381, 1398, 1401
<code>\solphys</code> 2135	1277, 1281, 1282	<code>\thesection</code> . 1104,
<code>\sovast</code> 2136	<code>\tan</code> 526	1162, 1163, 1171,
<code>\space</code> . 16, 779, 781–	<code>\textbackslash</code> .. 174	1172, 1709, 1711
783, 1540, 1558,	<code>\textbf</code> .. 464, 470, 1629	<code>\thesubsection</code> . 1104
2381, 2405, 2409,	<code>\textcopyright</code> .. 437	<code>\thesubsubsection</code>
2412, 2415, 2418	<code>\textfloatsep@set@SCALE</code> 1104
<code>\spaceskip</code> 1851 302, 313	<code>\thetable</code> 1176, 1180,
<code>\spose</code> 2172, 2174	<code>\textfloatsepScale</code>	1181, 1267, 1713
<code>\sq</code> 2176 331	<code>\thispagestyle</code> 954,
<code>\sqcap</code> 2176	<code>\textheight</code> .. 191, 356	1056, 1432, 1442,
<code>\sqcup</code> 2176	<code>\textit</code> 421	1594, 1603, 1607,
<code>\ssr</code> 2137	<code>\textlatin</code> 1698	1612, 1686, 1748,
<code>\StartBib</code> 803, 825	<code>\textrm</code> 175	1792, 1830, 1838
<code>\StartBibX</code> ... 804, 826	<code>\textsc</code> ... 420, 423,	<code>\ThisVolume</code>
<code>\stepcounter</code>	426, 1865, 2086, 2088	... 2102, 2450, 2673
..... 498, 739,	<code>\textsf</code> 2085	<code>\threequarters</code> ..
844, 852, 853, 1604	<code>\textsuperscript</code> 2210, 2217
<code>\stretch</code> ... 1618, 1624 174,	<code>\tiny</code> .. 2250, 2260, 2261
<code>\string</code> ... 802–804,	495, 940, 1272,	<code>\title</code> 475, 1435, 1448,
866–868, 870,	1276, 1277, 1281,	1688, 1718, 1833
872, 874–884,	1466, 1771, 1856	<code>\TOCbox</code> . 1730, 1753,
896, 897, 900–	<code>\texttt</code>	1759, 1812, 1819
904, 928, 1339,	767, 1286, 1349, 1867	<code>\TOCboxx</code> 1733, 1756, 1762
1555, 1703, 2032,	<code>\textwidth</code>	<code>\TOCentrywidth</code> ..
2036, 2041, 2049,	.. 185, 187, 353,	1727, 1728, 1776,
2053, 2054, 2060,	433, 614, 978, 999	1785, 1813, 1820
	<code>\tf@ads</code> 888, 889, 891, 892	

<code>\TOCextramargin .</code> 1729–1731	<code>\upshape</code> 1104, 1105, 1119 <code>\ur</code> 2222, 2231	1618, 1624, 1693, 1707, 1750, 1754,
<code>\TOCextramarginx</code> 1731, 1733	<code>\Url</code> 150 <code>\url</code> 699, 706, 719	1760, 1764, 2429
<code>\TOCpagenumwidth</code> ... 1726, 1728, 1813	<code>\urlstyle</code> 149, 150 <code>\usebox</code> ... 616, 617, 636	W <code>\wd</code> 1188, 1203, 1206, 1776
<code>\TOCtextwidth ...</code> 1725, 1727, 1730, 1732, 1753, 1759	<code>\usecounter</code> . 571, 1310 <code>\usepackage</code> 3, 4, 1534, 2441,	<code>\widowpenalty</code> ... 365, 572, 1311, 2431
<code>\TOCtextwidthx ..</code> 1732, 1733	2442, 2639–2641	<code>\write</code> 888, 889, 928, 1339, 2382, 2394, 2398
<code>\toks</code> . 665, 666, 668, 669	V <code>\value</code> 853, 1958, 1961, 1967, 1968, 2007	X <code>\xdef</code> 181,
<code>\topmargin</code> 192, 193, 357	<code>\vbadness</code> 368	480, 515, 675,
<code>\topsep</code> 570, 1291	<code>\verb</code> 2042, 2065	823, 855, 857,
<code>\tt</code> 7	<code>\verbatim</code> 2081	912, 915, 1463,
<code>\twocolumn</code> ... 933, 935, 945, 1443, 1662, 1789, 1843	<code>\vfil</code> 1956, 1999	1987, 2003–2005,
<code>\twothirds</code> . 2208, 2215	<code>\vfill</code> 567, 596, 635, 1496	2036, 2075, 2079
<code>\typeout</code> 60, 63, 67, 70, 73, 75, 77, 81, 83, 85, 88, 90, 92, 126, 130, 135, 141, 620–622, 628, 645	<code>\vfuzz</code> 370 <code>\vr</code> 2221, 2230 <code>\vsize</code> 1203, 1204, 1209, 1219 <code>\vskip</code> 973, 977, 984, 997, 1002, 1004, 1006, 1011, 1058, 1075, 1077, 1186, 1194, 1197, 1199, 1211, 1418, 1422, 1484, 1496, 1498, 1785, 1811, 1818, 1827, 2106	<code>\xspaceskip</code> 1852
U	Y <code>\year</code> 711	
<code>\ub</code> 2219, 2228		Z
<code>\ubvr</code> 2218, 2223		<code>\z@</code> ... 271, 277, 286– 288, 290, 570, 571, 939, 950, 1028, 1039, 1044, 1082, 1087, 1091, 1095, 1125, 1309, 1310, 1501, 1845, 1848, 1951, 2433
<code>\unvbox</code> 151		<code>\zap</code> 2138
<code>\uppercase</code> 174, 510, 514, 539, 1020, 1079, 1118, 2240	<code>\vspace</code> ... 568, 956, 1025, 1305, 1307,	

Change History

0.0	General: So bored today, decided to rewrite RMAA LaTeX macros from scratch 2	0.3	General: Better mechanism for alternative affiliations Added 'guide' option for user guide . . . 2
0.1	General: Just about working - still missing Fig/Tab/Refs 2	0.4	General: Minor stylistic changes . . . 2
0.2	General: All basic functionality present, I think 2	0.5	General: Added \fulladdresses and \adjustfinalcols (just about working) 2

0.6	General: Tweaked <code>\adjustfinalcols</code> (still not perfect) Added proceedings option Added <code>onecolumn/twocolumn</code> options (orthogonal to journal/proceedings) 2	file of each page for sending to the printers. 2
0.7	General: Increased spacing between sections in single column styles. Suppressed floats at bottom of pages (didn't work though) 2	
1.0	General: Now does a whole book - lots of stuff tidied up 2	
1.1	General: Added manuscript option, corrected bugs 2	
1.2	General: Added <code>\plate</code> command 2	
1.3	General: Corrected <code>\figcaption</code> to do the caption formatting right Corrected font size of section headings in front matter 2	
1.4	General: Added copyright and license info (GPL) 2	
1.5	General: Eliminated superscripts from titles in TOC and index . . . 2	
1.6	General: More cleaning up: full stops after titles in index, running headers and footers in frontmatter, fontsize in title of index, etc 2	
1.7	General: Fixed more little things. Page labels now work, even if you have no bibliography. You can output the full addresses by hand with the <code>\outputfulladdresses</code> command. Editors' Guide updated but still not finished. Revamped <code>splitbook.sh</code> now produces PS file of each article for web page and also an EPS	1.8 General: Fixed bug in last page label with <code>\suppressfulladdresses</code> . . 2
		1.9 General: Corrected position of page number in footer of articles that open on even pages. Ensured that first article in each session opens on an odd page, as do list of abstracts and author index. Added extra space in TOC before the backmatter. Added command for editors, <code>\BoldSessionTitles</code> , that makes produces bold titles for session in the TOC. 2
		2.0 General: Added 'newstyle' option, which should be used in all new proceedings volumes (wider abstract, smaller typeface in fig captions, etc.) Added commands for formatting table captions. New demonstration document <code>rmpostsamp.tex</code> for 1-page posters. This will be the last release under a PRI government (for a while...) 2
		2.1 General: Fixed some inconsistencies in <code>\nocite</code> and <code>\bibitem</code> unification Fixed the definition of <code>\ion</code> so it will work in math mode and in contexts where the typesize is different from normal (e.g., title, fig captions). Modified the definition of <code>\@caption</code> , so we don't write any list-of-figures data (we never use it anyway, and it just causes problems with fragile commands in fig captions). 2
		2.2beta General: Fixed bug whereby <code>twocolumn</code> option was not passed through to book class.

Finally sorted out the “label on last page” issue.	2	3.09	General: Explicitly require a recent version of natbib, so that we get a decent error message if the package is too old.	4
2.2beta10				
General: Fixed \secnumdepth for \book style.	33	3.10	General: Set large values for \hbadness, \vbadness, \hfuzz, \vfuzz. To reduce amount of stuff that gets written to the terminal every time you compile something. . .	11
2.2beta11				
General: Just about finished all the ADS stuff now. Except for the references, which I have given up on for the time being.	22	3.11	General: Moved the \articlename to after the key for consistency with the new natbib stuff.	61
Made twocol and newstyle the default for proceedings.	3	3.12	General: Added option to have title page for each session. Turn it on with \SessionTitlePages. .	44
2.2beta12		3.14	General: Option to turn off natbib .	3
\@keywordheader: \addkeyword New user interface for keywords.	15	rmaabib: Reinstalled old definition of \bibitem for the case where the nonatbib option is requested, so that the rmaacite package will work. This means that you can’t use rmaacite and natbib in the same volume.	39	
2.2beta13		3.16	\@kwtwidth: Added extra vertical space between authors and accepted date.	30
\@keywordheader: \addkeyword Improved behaviour with .ads file. Use \ADS@sanitize to change definitions of ‘ and \ion. . . .	15	General: Added \Color command for doing photometric colors. . .	55	
3.05		3.17	appendices: Added appendices environment that does the right thing.	34
General: Added natbib option	3	3.18	General: trying out doctex mode . .	3
If the natbib option is used, then set things up so that natbib’s version of the bibliography is identical to the standard one. . . .	4	3.19	General: Changes for Silvia - remove addresses from end, new abstract style	2
thebibliography: Removed the \beforebibliosiskip and \afterbibliosiskip commands, since they cause unwanted vertical space in some instances.	38	3.21	General: Changes for Silvia - abstracts are now shipped out	
3.06				
General: Natbib option turned on permanently	3			
3.07				
General: Added proof option	3			
3.08				
\indexauthor: Remerged changes from 3.06 that got dropped from 3.07 after a synchronization disaster. Basically, the accentless optional argument to \indexauthor. Must add the macro directories to my unison set-up to stop this sort of thing from happening.	19			

to ADS.	2	review articles	30
3.22 General: Allow proceedings articles to have received/accepted dates	2	General: New option for review articles	3
3.23 \@keywordheader: \addkeyword now signals a compilation error if the author tries to add more than 6 keywords.	15	4.0 \ADS@doi: Save DOI for ADS . . .	23
\MSextramargin: Reduce baselinestretch in manuscript style to 1.2. No longer use raggedright for manuscript. . . .	10	\ADS@dumpdata: Write all author affiliations for ADS	26
General: Full addresses are now automatically suppressed for proceedings style.	3	\DOI: New user command \DOI to typeset DOI in the header of first page and add it to ADS info.	20
Manuscript is now 10 pt instead of 12pt	3	\ORCIDid: Add mechanism for giving ORCID iD links	20
Manuscript is now on by default. . .	3	\abovesectionskip: Use negative values for skip so that first paragraph after section headings is not indented. This is something that I have been trying to fix for years It turns out that the answer was in the documentation for the standard command \@startsection. . . .	8
Now allow Bibtex to work properly	4	\ps@rmaafirstpage: Change to three-line header with copyright info and DOI.	13
3.24 \@keywordheader: kwdcounter is now reset in \@begofarticlehook to prevent error in book style . . .	15	General: Change abstract to appear before resumen. Change RevMexAA to RMxAA for consistency with ADS.	2
\MSextramargin: Further reduction of baselinestretch in manuscript style to 1.1 since we now have wider margins. . . .	10	Fix for issue where breaking hyperlink across pages gave an error.	6
Split manuscript's extra margin into separate horizontal and vertical parts.	10	Fix labels for amsmath display equations, in case that package has been loaded.	39
General: Added user access to the macro version and date via \rmVersion and \rmDate . . .	2	Fix the at-sign substitution so that it only eliminates \@ and does not mess with email addresses.	65
New option boldkeywords that does the keywords in the old ugly way. Now off by default. . .	3	Make hyperref and etoolbox into hard requirements, since we now use them extensively. . .	5
3.25 General: Change \newcommand tp \def when setting \bibfont. This allows it to work with all versions of natbib.	4	Make sure that lynx writes utf-8 output instead of latin-1.	65
Updated copyright year.	4	Reorganize folder layout so that hardly anything is in the top level. That way, things are clearer on github.	58
Updated email and web addresses to crya.unam.mx. . .	4	appendix: Added appendix environment for case where there is only one section.	35
3.26 \@kwtwidth: Add extra label to			