

Hide menu

Introduction to Neural Networks and TensorFlow

Practice Assignment: Classification Using Deep Neural Networks

N-grams vs. Sequence Models

✓ **Video:** Lesson Introduction
49 sec

▶ **Video:** Traditional Language models
3 min

📖 **Reading:** Traditional Language models
5 min

▶ **Video:** Recurrent Neural Networks
4 min

📖 **Reading:** Recurrent Neural Networks
4 min

▶ **Video:** Applications of RNNs
3 min

📖 **Reading:** Application of RNNs
3 min

▶ **Video:** Math in Simple RNNs
3 min

📖 **Reading:** Math in Simple RNNs
6 min

📄 **Lab:** Hidden State Activation
20 min

▶ **Video:** Cost Function for RNNs
2 min

📖 **Reading:** Cost Function for RNNs
5 min



▶ **Video:** Implementation Note
1 min


🏠 > Week 1 > Traditional Language models

< Previous Next >

Traditional Language models

Traditional language models make use of probabilities to help identify which sentence is most likely to take place.

 J'ai vu le match de foot
 

Sequence	$P(\text{Sequence})$
I saw the game of soccer	4.5 e-5
I saw the soccer game	6.0 e-5
I saw the soccer match	4.6 e-5
Saw I the game of soccer	2.6 e-9

In the example above, the second sentence is the one that is most likely to take place as it has the highest probability of happening. To compute the probabilities, you can do the following:

$$P(w_2|w_1) = \frac{\text{count}(w_1, w_2)}{\text{count}(w_1)} \longrightarrow \text{Bigrams}$$

$$P(w_3|w_1, w_2) = \frac{\text{count}(w_1, w_2, w_3)}{\text{count}(w_1, w_2)} \longrightarrow \text{Trigrams}$$

$$P(w_1, w_2, w_3) = P(w_1) \times P(w_2|w_1) \times P(w_3|w_2)$$

Large N-grams capture dependencies between distant words and need a lot of space and RAM. Hence, we resort to using different types of alternatives.

