< Previous Next >


## **≡** Hide menu

## **Lecture: Part of Speech Tagging**

- ✔ Video: Week Introduction
- ✔ Video: Part of Speech Tagging
- Reading: Part of Speech Tagging
- Lab: Lecture Notebook Working with text files
- **Video:** Markov Chains
- Reading: Markov Chains
- Video: Markov Chains and POS Tags 4 min
- Reading: Markov Chains and POS Tags 6 min
- ✔ Video: Hidden Markov Models 3 min
- Reading: Hidden Markov Models
- ✔ Video: Calculating Probabilities
- Reading: Calculating Probabilities
- ✔ Video: Populating the Transition Matrix 4 min
- Reading: Populating the Transition Matrix
- **Video:** Populating the Emission Matrix 2 min
- Reading: Populating the Emission Matrix 5 min
- Lab: Lecture Notebook Working with tags and Numpy 20 min
- ✔ Video: The Viterbi Algorithm
- Reading: The Viterbi Algorithm
- **Video:** Viterbi: Initialization
- Reading: Viterbi Initialization
- Video: Viterbi: Forward Pass
- Reading: Viterbi: Forward Pass
- (>) Video: Viterbi: Backward Pass
- Reading: Viterbi: Backward Pass

## Viterbi Initialization


You will now populate a matrix **C** of dimension (num\_tags, num\_words). This matrix will have the probabilities that will tell you what part of speech each word belongs to.



C =		W <sub>1</sub>	W <sub>2</sub>	 w <sub>K</sub>
	t <sub>1</sub>	C <sub>1,1</sub>		
	t <sub>N</sub>	C <sub>N,1</sub>		

$$c_{i,1} = \pi_i * b_{i,cindex(w_1)}$$
$$= a_{1,i} * b_{i,cindex(w_1)}$$

Now to populate the first column, you just multiply the initial  $\pi$  distribution, for each tag, times bi, cindex(w1). Where the i, corresponds to the tag of the initial distribution and the cindex(w1), is the index of word 1 in the emission matrix. And that's it, you are done with populating the first column of your new C matrix. You will now need to keep track what part of speech you are coming from. Hence we introduce a matrix **D**, which allows you to store the labels that represent the different states you are going through when finding the most likely sequence of POS tags for the given sequence of words  $w1, \ldots, wK$ . At first you set the first column to 0, because you are not coming from any POS tag.



· =		W <sub>1</sub>	W <sub>2</sub>	 w <sub>K</sub>
	t <sub>1</sub>	d <sub>1,1</sub>		
	t <sub>N</sub>	d <sub>N,1</sub>		

$$d_{i,1} = 0$$

These two matrices will make more sense in the next videos.

Mark as completed

∆ Like 
¬ Dislike 
¬ Report an issue