



Hide menu

Lecture: Naive Bayes

- ✓ **Video:** Week Introduction
27 sec
- ✓ **Video:** Probability and Bayes' Rule
3 min
- ✓ **Reading:** Probability and Bayes' Rule
10 min
- ✓ **Video:** Bayes' Rule
4 min
- ✓ **Reading:** Bayes' Rule
10 min
- ✓ **Video:** Naïve Bayes Introduction
5 min
- ✓ **Reading:** Naive Bayes Introduction
10 min
- ✓ **Video:** Laplacian Smoothing
2 min
- ✓ **Reading:** Laplacian Smoothing
10 min
- ✓ **Video:** Log Likelihood, Part 1
6 min
- ✓ **Reading:** Log Likelihood, Part 1
10 min
- ✓ **Video:** Log Likelihood, Part 2
2 min
- ✓ **Reading:** Log Likelihood, Part 2

Week 2 > Testing naïve Bayes

Previous Next

Testing naïve Bayes

- log-likelihood dictionary $\lambda(w) = \log \frac{P(w|pos)}{P(w|neg)}$
- $logprior = \log \frac{D_{pos}}{D_{neg}} = 0$
- Tweet: [I, pass, the, NLP, interview] 🍀

$$score = -0.01 + 0.5 - 0.01 + 0 + logprior = 0.48$$

$$pred = score > 0$$

word	λ
I	-0.01
the	-0.01
happi	0.63
because	0.01
pass	0.5
NLP	0
sad	-0.75
not	-0.75

The example above shows how you can make a prediction given your λ dictionary. In this example the *logprior* is 0 because we have the same amount of positive and negative documents (i.e. $\log 1 = 0$).

Mark as completed

