

Previous



Next >

≔ Hide menu

Lecture: Naive Bayes

- Video: Week Introduction 27 sec
- **Video:** Probability and Bayes' Rule
- **Reading:** Probability and Bayes' Rule 10 min
- Video: Bayes' Rule
- Reading: Bayes' Rule 10 min
- Video: Naïve Bayes Introduction
- **Reading:** Naive Bayes Introduction 10 min
- **Video:** Laplacian Smoothing 2 min
- **Reading:** Laplacian Smoothing 10 min
- Video: Log Likelihood, Part 1 6 min
- Reading: Log Likelihood, Part 1 10 min
- Video: Log Likelihood, Part 2 2 min
- **Reading:** Log Likelihood Part 2

Laplacian Smoothing

We usually compute the probability of a word given a class as follows:

$$P\left(\mathrm{w_{i}\mid \ class}\;
ight) = rac{\mathrm{freq}\left(\mathrm{w_{i}, \, class}\;
ight)}{\mathrm{N_{class}}} \quad \ \mathrm{class} \ \in \{ \ \mathrm{Positive}, \, \mathrm{Negative} \ \}$$

However, if a word does not appear in the training, then it automatically gets a probability of 0, to fix this we add smoothing as follows

$$P\left(\mathrm{w_i}\mid \mathrm{class}
ight) = rac{\mathrm{freq}\left(\mathrm{w_i},\,\mathrm{class}\,
ight) + 1}{\left(\mathrm{N_{class}} + \mathrm{V}
ight)}$$

Note that we added a 1 in the numerator, and since there are V words to normalize, we add V in the denominator.

 N_{class} : frequency of all words in class

V: number of unique words in vocabulary

Mark as completed









☐ Report an issue

